

# Unsupervised Learning



It does not required lab's data.

It can be work on structure and unstructure data.

- ① k-mean clustering
- ② Hierarchical clustering
- ③ DBSCAN clustering
- ④ PCA
- ⑤ Apriori


$x_1$  Income  
 $x_2$  Spending score

After Applying clustering





# k-mean clustering


Geometric Intuition:-



K mean  $\Rightarrow$




K-mean  $\Rightarrow$





steps -


- ① Initialize some new centroid <sup>(K)</sup>
- ② point that are nearest to the centroid group them.
- ③ move centroid by calculating the mean of points



centroid point will shift toward....




Final  
output



# How to select $k$ -value?



WCSS - within cluster sum of square



$$WCSS = \sum_{i=0}^k \left( \text{Distance b/w point to nearest centroid} \right)^2$$

suppose  $k = 1 - 10$

\* Elbo method -



when wcss calculate with  $k=1$ , wcss value is high, when we increase  $k=2$ , it will reduce, when  $k=3$  it will reduce. when  $k=3$  it will reduce and after


Some point it will be straight in graph it is called elbo method.

When curve become straight at that point we got k value. like above graph, 5 will be our k value.

To calculate distance we need.

Euclidean distance or Manhattan distance


$P_2 (x_2, y_2)$





$$ED = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}$$

$$MD = |x_2 - x_1| + |y_2 - y_1|$$

## Random Initialization trap (k-means++)



$K=3$



When centroid form very nearest to each other it stuck in Random trap.

To handle this kind of trap we use k-means++ method.

With help of it centroid form far from each other. and prevent from random initialization trap.

