MCQ PRACTICE BOOK

OAVS Computer Teacher (TGT) Exam

Unit 1 — C Fundamentals
Chapter 1: C CHARACTER SET

150+	5	Detailed	Answer Key
MCQs	Sections	Explanations	Included

TOPICS COVERED

- ✔ C Character Set: Letters, Digits, Special Symbols
- ✔ White Space Characters
- ✔ Escape Sequences (\n, \t, \b, \\, \' etc.)
- ✔ Character Constants & ASCII Representation
- ✔ Previous-Year Exam Style Questions
- ✔ Chapter Test & Complete Answer Key

Prepared for OAVS TGT Computer Science Examination | Based on NCERT / ANSI C Syllabus

TABLE OF CONTENTS

Section 1	Letters, Digits & Special Symbols	**Q1–Q30**
Section 2	White Space Characters	**Q31–Q55**
Section 3	Escape Sequences	**Q56–Q90**
Section 4	Character Constants & ASCII	**Q91–Q120**
Section 5	Previous-Year Exam Style Questions	**Q121–Q150**
Chapter Test	50-Question Timed Test	**Test Paper**
Answer Key	All Answers at a Glance	**Answer Key**

SECTION 1: Letters, Digits & Special Symbols

Questions 1–30 | Conceptual + Application Questions

This section covers the three main groups of the C character set: alphabetic letters (A–Z, a–z), decimal digits (0–9), and the 29 special characters. Understanding these is fundamental to writing valid C programs.

Q1. How many alphabetic characters are present in the C character set?

(A) 26
(B) 52
(C) 54
(D) 56

✔ **Answer: (b) 52**

■ *C recognizes both uppercase (A–Z) and lowercase (a–z), giving 52 alphabetic characters.*

Q2. Which of the following is NOT a valid character in the C character set?

(A) @
(B) #
(C) €
(D) $

✔ **Answer: (c) €**

■ *€ (Euro sign) is not part of the standard ANSI C character set. C uses ASCII, which does not include '€'.*

Q3. How many decimal digits are included in the C character set?

(A) 8
(B) 9
(C) 10
(D) 11

✔ **Answer: (c) 10**

■ *C includes digits 0 through 9, making 10 decimal digits.*

Q4. The C character set is a subset of which standard?

(A) EBCDIC
(B) ASCII
(C) Unicode
(D) UTF-16

✔ **Answer: (b) ASCII**

■ *ANSI C uses the ASCII character set as its foundation.*

Q5. Which of the following special characters is used to terminate a C statement?

(A) ,
(B) .
(C) ;
(D) :

✔ **Answer: (c) ;**

■ *The semicolon (;) is the statement terminator in C.*

Q6. Which character is used to begin and end a string literal in C?

(A) Single quote (')
(B) Double quote (")
(C) Backtick (`)
(D) Hash (#)

✔ **Answer: (b) Double quote (")**

■ *String literals in C are enclosed in double quotes, e.g., "Hello".*

Q7. What is the total number of special characters defined in the ANSI C character set?

(A) 28
(B) 29
(C) 30
(D) 31

✔ **Answer: (b) 29**

■ *ANSI C defines 29 special characters including +, -, *, /, =, {}, [], etc.*

Q8. Which of the following is a valid C identifier character from the special-character group?

(A) @
(B) #
(C) _
(D) &

✔ **Answer: (c) _**

■ *The underscore (_) is the only special character allowed in C identifiers.*

Q9. In C, uppercase letters and lowercase letters are treated as:

(A) Same
(B) Different (case-sensitive)
(C) Interchangeable
(D) Depends on compiler

✔ **Answer: (b) Different (case-sensitive)**

■ *C is case-sensitive, so 'A' and 'a' are completely different characters.*

Q10. Which group of characters forms the C character set?

(A) Letters only
(B) Digits only
(C) Letters, digits, special characters, whitespace
(D) Letters and digits only

✔ **Answer: (c) Letters, digits, special characters, whitespace**

Q11. The character '*' in C is primarily used as:

(A) Bitwise AND
(B) Multiplication operator and pointer declarator
(C) String delimiter
(D) Logical NOT

✔ **Answer: (b) Multiplication operator and pointer declarator**

■ *'*' serves as multiplication operator (a*b) and also as pointer declarator (int *p).*

Q12. Which special character is used as the modulo operator in C?

(A) ^
(B) &
(C) %
(D) $

✔ **Answer: (c) %**

Q13. Which of the following characters is used for bitwise XOR in C?

(A) &
(B) |
(C) ^
(D) ~
✔ **Answer: (c) ^**

Q14. The character '~' in C is used for:

(A) Logical NOT
(B) Bitwise complement
(C) Tilde string
(D) Exponentiation
✔ **Answer: (b) Bitwise complement**

Q15. What is the maximum ASCII value of a printable character in standard ASCII?

(A) 126
(B) 127
(C) 128
(D) 255
✔ **Answer: (a) 126**
■ *The printable characters in ASCII range from 32 (space) to 126 (~). ASCII 127 is the DEL control character.*

Q16. Which character separates arguments in a C function call?

(A) Semicolon
(B) Colon
(C) Comma
(D) Period
✔ **Answer: (c) Comma**

Q17. The '#' character in C is associated with:

(A) Bitwise operations
(B) Preprocessor directives
(C) Pointer operations
(D) Comments
✔ **Answer: (b) Preprocessor directives**
■ *# is used with preprocessor directives like #include and #define.*

Q18. Which character is used to denote a single-line comment in C99 and later?

(A) /* */
(B) //
(C) --
(D) ##
✔ **Answer: (b) //**

Q19. The '{}' (curly braces) in C are used to:

(A) Define arrays
(B) Enclose blocks of code
(C) Both A and B
(D) Declare functions only
✔ **Answer: (c) Both A and B**

Q20. Which of the following characters is NOT a relational operator character in C?

(A) <
(B) >
(C) =
(D) @

✔ **Answer: (d) @**

Q21. How many bits does a standard ASCII character occupy?

(A) 4 bits
(B) 7 bits
(C) 8 bits
(D) 16 bits

✔ **Answer: (b) 7 bits**

■ *Standard ASCII uses 7 bits (128 characters). Extended ASCII uses 8 bits.*

Q22. The '\' (backslash) character in C is primarily used for:

(A) Division
(B) Starting escape sequences
(C) Comments
(D) String concatenation

✔ **Answer: (b) Starting escape sequences**

Q23. Which character separates the base from the fractional part of a floating-point constant?

(A) Comma (,)
(B) Colon (:)
(C) Dot (.)
(D) Semicolon (;)

✔ **Answer: (c) Dot (.)**

Q24. In C, identifiers can contain which of the following characters?

(A) Letters, digits, underscores
(B) Letters, digits, hyphens
(C) All ASCII characters
(D) Letters only

✔ **Answer: (a) Letters, digits, underscores**

Q25. Which special character is used to access structure members in C?

(A) ->
(B) ::
(C) .
(D) :

✔ **Answer: (c) .**

■ *The dot (.) operator accesses members of a structure. (->) is used with pointers to structures.*

Q26. The '!' character in C is used as:

(A) Bitwise NOT
(B) Logical NOT
(C) Arithmetic negation
(D) Factorial

✔ **Answer: (b) Logical NOT**

Q27. Which of the following is the correct character for bitwise AND in C?

(A) &&
(B) &
(C) AND
(D) @

✔ **Answer: (b) &**

■ *Single '&' is bitwise AND; '&&' is logical AND.*

Q28. How many characters are in the complete standard ANSI C character set (printable + control)?

(A) 128
(B) 256
(C) 64
(D) 96

✔ **Answer: (a) 128**

■ *Standard ASCII (which ANSI C is based on) has 128 characters (0–127).*

Q29. Which of these is a valid use of the colon ':' in C?

(A) Statement terminator
(B) Member access
(C) Ternary operator and bit-field declaration
(D) String delimiter

✔ **Answer: (c) Ternary operator and bit-field declaration**

Q30. The '|' character is used in C as:

(A) Logical OR only
(B) Bitwise OR only
(C) Bitwise OR; '||' is logical OR
(D) Pipe for streams

✔ **Answer: (c) Bitwise OR; '||' is logical OR**

SECTION 2: White Space Characters

Questions 31–55 | Conceptual + Output-Based Questions

White-space characters are invisible characters that act as separators in C source code. The six white-space characters are: space, horizontal tab (\t), newline (\n), vertical tab (\v), form feed (\f), and carriage return (\r).

Q31. Which of the following is NOT a white-space character in C?

(A) Space ( )
(B) Horizontal tab (\t)
(C) Newline (\n)
(D) Asterisk (*)
✔ **Answer: (d) Asterisk (*)**

■ *White-space characters are space, tab, newline, carriage return, form feed, and vertical tab. Asterisk is not one of them.*

Q32. How many white-space characters are defined in ANSI C?

(A) 3
(B) 4
(C) 5
(D) 6
✔ **Answer: (d) 6**

■ *The six white-space characters are: space, horizontal tab (\t), newline (\n), vertical tab (\v), form feed (\f), carriage return (\r).*

Q33. What is the ASCII value of the space character?

(A) 0
(B) 8
(C) 32
(D) 48
✔ **Answer: (c) 32**

■ *The space character has ASCII value 32.*

Q34. Which white-space character advances the cursor to the next tab stop?

(A) \n
(B) \t
(C) \r
(D) \f
✔ **Answer: (b) \t**

Q35. What does the newline character (\n) do in C output?

(A) Moves cursor to column 1 of the same line
(B) Moves cursor to beginning of next line
(C) Clears the screen
(D) Inserts a blank line
✔ **Answer: (b) Moves cursor to beginning of next line**

Q36. Which white-space character is used to advance paper to the next page on a printer?

(A) \t
(B) \v
(C) \n
(D) \f
✔ **Answer: (d) \f**

■ *\f is the form-feed character, historically used to advance printer paper to the next page.*

Q37. The carriage return character (\r) moves the cursor to:

(A) Next line
(B) Beginning of the current line
(C) Next tab stop
(D) End of the line

✔ **Answer: (b) Beginning of the current line**

■ *\r (CR) moves cursor to the beginning of the current line without advancing to the next line.*

Q38. In C, white-space characters between tokens are:

(A) Syntax errors
(B) Ignored by the compiler (used as separators)
(C) Part of string literals
(D) Treated as operators

✔ **Answer: (b) Ignored by the compiler (used as separators)**

■ *White-space separates tokens and is largely ignored by the C compiler except within string/character literals.*

Q39. What is the ASCII value of the horizontal tab character (\t)?

(A) 7
(B) 8
(C) 9
(D) 11

✔ **Answer: (c) 9**

■ *Horizontal tab has ASCII value 9.*

Q40. What is the ASCII value of the newline character (\n)?

(A) 8
(B) 10
(C) 12
(D) 13

✔ **Answer: (b) 10**

■ *Newline (\n) has ASCII value 10.*

Q41. The vertical tab character (\v) has ASCII value:

(A) 9
(B) 10
(C) 11
(D) 12

✔ **Answer: (c) 11**

Q42. Form feed (\f) has ASCII value:

(A) 10
(B) 11
(C) 12
(D) 13

✔ **Answer: (c) 12**

Q43. Carriage return (\r) has ASCII value:

(A) 11
(B) 12
(C) 13
(D) 14

✔ **Answer: (c) 13**

Q44. Which statement about white space inside a string literal is TRUE?

(A) It is ignored
(B) It is preserved as part of the string
(C) It causes a compiler error
(D) It is converted to underscores

✔ **Answer: (b) It is preserved as part of the string**

■ *White space within double-quoted strings is preserved. Only outside string/char literals is it treated as a separator.*

Q45. Which function in C can be used to skip white-space characters when reading input?

(A) getchar()
(B) scanf() with format specifiers
(C) fgets()
(D) Both A and B

✔ **Answer: (b) scanf() with format specifiers**

■ *scanf() automatically skips leading white space for most format specifiers (except %c).*

Q46. Which of the following correctly identifies all white-space characters in C?

(A) space, \t, \n
(B) space, \t, \n, \r, \f, \v
(C) space, \n, \r
(D) \t, \n, \r, \f

✔ **Answer: (b) space, \t, \n, \r, \f, \v**

Q47. In C, two or more consecutive spaces in source code are treated as:

(A) A syntax error
(B) A single white-space token
(C) A special comment
(D) Concatenated

✔ **Answer: (b) A single white-space token**

Q48. Which header file contains the isspace() function used to test white-space characters?

(A)
(B)
(C)
(D)

✔ **Answer: (c)**

■ *isspace() is declared in .*

Q49. What does isspace('\n') return in C?

(A) 0 (false)
(B) Non-zero (true)
(C) -1
(D) Undefined

✔ **Answer: (b) Non-zero (true)**

■ *isspace() returns non-zero for any white-space character including \n.*

Q50. In the printf statement, what does '\t' produce?

(A) A newline
(B) A tab space (typically 8 spaces)
(C) A backslash
(D) A null character

✔ **Answer: (b) A tab space (typically 8 spaces)**

Q51. White-space characters are part of which category in C character classification?

(A) Printable characters
(B) Control characters / separators
(C) Alphanumeric characters
(D) Punctuation
✔ **Answer: (b) Control characters / separators**

Q52. A blank line in C source code is made up of:

(A) A newline character only
(B) White-space characters followed by a newline
(C) Either A or B
(D) Neither A nor B
✔ **Answer: (c) Either A or B**

Q53. Which of the following produces a tab-separated output in C?

(A) printf("%s %s", a, b)
(B) printf("%s\t%s", a, b)
(C) printf("%s,\t%s", a, b)
(D) printf("%s\n%s", a, b)
✔ **Answer: (b) printf("%s\t%s", a, b)**

Q54. The C preprocessor treats white space as:

(A) Part of macro names
(B) Token separator and ignores extra white space
(C) Comments
(D) Error
✔ **Answer: (b) Token separator and ignores extra white space**

Q55. Which escape sequence represents a space in a C character constant?

(A) '\s'
(B) ' ' (a literal space)
(C) '\b'
(D) '\0'
✔ **Answer: (b) ' ' (a literal space)**
■ *There is no \s escape sequence in C. A space is represented literally as ' '.*

SECTION 3: Escape Sequences

Questions 56–90 | Tricky + Output-Based Questions

Escape sequences begin with a backslash (\) and represent non-printable or special characters. ANSI C defines 11 standard escape sequences. Mastering them is critical for writing correct printf/scanf statements.

Q56. What is an escape sequence in C?

(A) A jump in program execution
(B) A combination of \ and a character representing a special meaning
(C) An error-handling mechanism
(D) A preprocessor directive

✔ **Answer: (b) A combination of \ and a character representing a special meaning**

■ *An escape sequence starts with backslash (\) followed by a character and represents non-printable or special characters.*

Q57. How many standard escape sequences are defined in ANSI C?

(A) 8
(B) 10
(C) 11
(D) 12

✔ **Answer: (c) 11**

■ *ANSI C defines 11 escape sequences: \a, \b, \f, \n, \r, \t, \v, \\, \', \", \0.*

Q58. What is the purpose of '\a' escape sequence?

(A) Alert / Audible bell
(B) Ampersand
(C) Array start
(D) Assignment

✔ **Answer: (a) Alert / Audible bell**

■ *\a produces an audible bell (alert sound). Its ASCII value is 7.*

Q59. What does '\b' represent as an escape sequence?

(A) Blank space
(B) Backspace
(C) Backslash
(D) Break

✔ **Answer: (b) Backspace**

■ *\b is backspace, ASCII value 8, which moves cursor one position back.*

Q60. The escape sequence '\0' represents:

(A) The digit zero
(B) Null character (end of string)
(C) Octal escape
(D) Output newline

✔ **Answer: (b) Null character (end of string)**

■ *\0 is the null character with ASCII value 0, marking the end of a C string.*

Q61. What is the ASCII value of '\a' (alert/bell)?

(A) 5
(B) 6
(C) 7
(D) 8

✔ **Answer: (c) 7**

Q62. What is the ASCII value of '\b' (backspace)?

(A) 7
(B) 8
(C) 9
(D) 10
✔ **Answer: (b) 8**

Q63. What escape sequence represents a single backslash (\) in C?

(A) \b
(B) \s
(C) \\
(D) \/
✔ **Answer: (c) **
■ *To print a literal backslash, use \\ which is two backslash characters.*

Q64. To print a double quote (") inside a C string, which escape sequence is used?

(A) \"
(B) \q
(C) \dq
(D) ""
✔ **Answer: (a) \"**
■ *\" inserts a double-quote character inside a string literal.*

Q65. To print a single quote inside a character constant, which escape sequence is used?

(A) \"
(B) \q
(C) \'
(D) \s
✔ **Answer: (c) \'**

Q66. What is the output of: printf("Hello\bWorld");

(A) Hello World
(B) HellWorld
(C) Hello\bWorld
(D) HelloWorld
✔ **Answer: (b) HellWorld**
■ *\b moves cursor back one position, so 'o' is overwritten by 'W', producing 'HellWorld'.*

Q67. What is the output of: printf("A\tB");

(A) AB
(B) A B
(C) A B (tab-separated)
(D) A\tB
✔ **Answer: (c) A B (tab-separated)**

Q68. The escape sequence '\v' stands for:

(A) Variable
(B) Vertical tab
(C) Void
(D) Value
✔ **Answer: (b) Vertical tab**

Q69. What escape sequence is used for form feed?

(A) \f
(B) \ff
(C) \pg
(D) \p
✔ **Answer: (a) \f**

Q70. What is the output of: printf("Line1\nLine2");

(A) Line1 Line2
(B) Line1\nLine2
(C) Line1 followed by Line2 on next line
(D) Line1Line2
✔ **Answer: (c) Line1 followed by Line2 on next line**

Q71. Which escape sequence represents the carriage return?

(A) \n
(B) \r
(C) \t
(D) \c
✔ **Answer: (b) \r**

Q72. What does \xhh represent in C?

(A) A hexadecimal escape sequence for a character
(B) A hex number
(C) An HTML tag
(D) A preprocessor macro
✔ **Answer: (a) A hexadecimal escape sequence for a character**
■ *\x followed by hex digits represents the character with that hexadecimal ASCII value, e.g. \x41 = 'A'.*

Q73. What does \ooo represent in C (where o are octal digits)?

(A) An octal number constant
(B) An octal escape sequence for a character
(C) An operator
(D) A comment
✔ **Answer: (b) An octal escape sequence for a character**
■ *\followed by 1-3 octal digits represents the character with that octal ASCII code.*

Q74. printf("\101") produces which character? (101 octal = 65 decimal)

(A) A
(B) a
(C) 1
(D) 101
✔ **Answer: (a) A**
■ *\101 is an octal escape for ASCII 65, which is 'A'.*

Q75. printf("\x41") produces:

(A) x41
(B) A
(C) 65
(D) Error
✔ **Answer: (b) A**
■ *\x41 is hexadecimal 41 = decimal 65 = 'A'.*

Q76. Which of the following escape sequences is NOT valid in ANSI C?

(A) \n
(B) \t
(C) \s
(D) \v

✔ **Answer: (c) \s**

■ *\s is not a standard C escape sequence. \n, \t, and \v are all valid.*

Q77. What character does '\0' produce when used in printf?

(A) The character '0'
(B) Null character (nothing visible)
(C) A space
(D) A newline

✔ **Answer: (b) Null character (nothing visible)**

Q78. In C, char c = '\n'; — what is stored in c?

(A) Two characters: \ and n
(B) A single character with ASCII value 10
(C) ASCII 92 (backslash)
(D) Error

✔ **Answer: (b) A single character with ASCII value 10**

■ *\n is a single character escape sequence with ASCII value 10.*

Q79. What is the size of the character constant '\n' in bytes?

(A) 2 bytes
(B) 1 byte
(C) 4 bytes
(D) Depends on platform

✔ **Answer: (b) 1 byte**

■ *Even though written as two characters in source, \n is a single character and occupies 1 byte.*

Q80. The escape sequence '\a' is useful for:

(A) Producing an alarm/beep sound in terminal programs
(B) Advancing the cursor
(C) Clearing the screen
(D) Reading input

✔ **Answer: (a) Producing an alarm/beep sound in terminal programs**

Q81. What would printf("Rate: 10%%"); print?

(A) Rate: 10%
(B) Rate: 10%%
(C) Rate: 10
(D) Syntax error

✔ **Answer: (a) Rate: 10%**

■ *In printf, %% produces a literal percent sign %.*

Q82. Which escape sequence would you use to embed a null byte in the middle of a binary stream?

(A) \z
(B) \0
(C) \x00 or \0
(D) Both B and C

✔ **Answer: (d) Both B and C**

Q83. printf("C:\\Users"); prints:

(A) C:\\Users
(B) C:\Users
(C) C:Users
(D) C:\\\\Users
✔ **Answer: (b) C:\Users**
■ *Each \\ pair produces a single backslash, so C:\\Users prints as C:\Users.*

Q84. Which is the escape sequence for horizontal tab?

(A) \h
(B) \t
(C) \ht
(D) \tab
✔ **Answer: (b) \t**

Q85. Escape sequences in C are interpreted at which stage?

(A) Runtime
(B) Link time
(C) Compile time / during tokenisation
(D) Preprocessing
✔ **Answer: (c) Compile time / during tokenisation**
■ *Escape sequences are converted to their actual character values during the compilation (tokenisation) phase.*

Q86. The statement char ch = '\\'; assigns to ch:

(A) Two characters
(B) A single backslash character (ASCII 92)
(C) A null character
(D) Error
✔ **Answer: (b) A single backslash character (ASCII 92)**

Q87. What is the escape sequence for the alert (bell) character?

(A) \al
(B) \bell
(C) \a
(D) \bel
✔ **Answer: (c) \a**

Q88. What will printf("Hello\rWorld"); likely display on most terminals?

(A) HelloWorld
(B) Hello World
(C) WorldHello (World overwrites Hello)
(D) Hello\rWorld
✔ **Answer: (c) WorldHello (World overwrites Hello)**
■ *\r moves cursor to start of line; 'World' then overwrites 'Hello'.*

Q89. Which escape sequence is used in Windows to denote end of a line in text files?

(A) \n only
(B) \r only
(C) \r\n
(D) \n\r
✔ **Answer: (c) \r\n**
■ *Windows text files use \r\n (CRLF). Linux uses \n (LF) only.*

Q90. In C, '\'\'' represents:

(A) A syntax error
(B) A character constant containing a single quote
(C) An empty character constant
(D) Two characters
✔ **Answer: (b) A character constant containing a single quote**

SECTION 4: Character Constants & ASCII Representation

Questions 91–120 | Numerical + Conceptual Questions

A character constant is a single character enclosed in single quotes. In C (unlike C++), character constants are of type int. ASCII (American Standard Code for Information Interchange) assigns a unique 7-bit integer to each character in the C character set.

Quick ASCII Reference:

Character	ASCII	Character	ASCII	Character	ASCII
NUL (\0)	0	Space	32	'A'	65
Bell (\a)	7	'0'	48	'Z'	90
BS (\b)	8	'9'	57	'a'	97
HT (\t)	9	'@'	64	'z'	122
LF (\n)	10			DEL (\x7F)	127

Q91. How is a character constant written in C?

(A) Double quotes: "A"
(B) Single quotes: 'A'
(C) Parentheses: (A)
(D) Angle brackets: <A>

✔ **Answer: (b) Single quotes: 'A'**

■ *Character constants are enclosed in single quotes. "A" would be a string literal.*

Q92. What is the type of a character constant in C (e.g., 'A')?

(A) char
(B) int
(C) unsigned char
(D) short

✔ **Answer: (b) int**

■ *In C (unlike C++), a character constant like 'A' is of type int, with value equal to its ASCII code.*

Q93. What is the ASCII value of 'A' (uppercase)?

(A) 64
(B) 65
(C) 66
(D) 97

✔ **Answer: (b) 65**

■ *'A' has ASCII value 65.*

Q94. What is the ASCII value of 'a' (lowercase)?

(A) 96
(B) 97
(C) 98
(D) 65

✔ **Answer: (b) 97**

■ *'a' has ASCII value 97. The difference between lowercase and uppercase is 32.*

Q95. What is the ASCII value of '0' (digit zero)?

(A) 0
(B) 32
(C) 48
(D) 58

✔ **Answer: (c) 48**

■ *'0' has ASCII value 48. Digits '0'–'9' have ASCII values 48–57.*

Q96. What is 'A' - 'a' in C?

(A) 32
(B) -32
(C) 1
(D) 0

✔ **Answer: (b) -32**

■ *'A' is ASCII 65 and 'a' is ASCII 97. 65 - 97 = -32.*

Q97. What expression converts a lowercase letter c to uppercase in C?

(A) c - 32
(B) c + 32
(C) c - 'a' + 'A'
(D) Both A and C

✔ **Answer: (d) Both A and C**

■ *Both c-32 and c-'a'+'A' work. The standard way is toupper(c) from .*

Q98. Which of the following is a valid character constant in C?

(A) 'AB'
(B) '\n'
(C) "A"
(D) char(65)

✔ **Answer: (b) '\n'**

■ *'\n' is a valid single-character escape sequence. 'AB' is a multi-character constant (implementation-defined). "A" is a string.*

Q99. What is the value of ('9' - '0') in C?

(A) 0
(B) 9
(C) 57
(D) 48

✔ **Answer: (b) 9**

■ *'9' is ASCII 57 and '0' is ASCII 48. 57 - 48 = 9.*

Q100. ASCII stands for:

(A) American Standard Code for Information Interchange
(B) American Standard Coding for Internal Input
(C) Automated System for Character Interchange
(D) American System of Computer Information Input

✔ **Answer: (a) American Standard Code for Information Interchange**

Q101. The total number of characters in standard ASCII is:

(A) 64
(B) 128
(C) 256
(D) 512

✔ **Answer: (b) 128**

■ *Standard ASCII defines 128 characters (0–127).*

Q102. Which ASCII range represents control characters?

(A) 0–31 and 127
(B) 32–64
(C) 65–90
(D) 91–96

✔ **Answer: (a) 0–31 and 127**

■ *ASCII 0–31 are non-printable control characters, and 127 (DEL) is also a control character.*

Q103. Which ASCII range represents uppercase letters (A–Z)?

(A) 97–122
(B) 65–90
(C) 48–57
(D) 33–64

✔ **Answer: (b) 65–90**

Q104. Which ASCII range represents lowercase letters (a–z)?

(A) 65–90
(B) 48–57
(C) 97–122
(D) 91–96

✔ **Answer: (c) 97–122**

Q105. The ASCII value of the null character (\0) is:

(A) 0
(B) 32
(C) 127
(D) 255

✔ **Answer: (a) 0**

Q106. The ASCII value of the DEL character is:

(A) 0
(B) 26
(C) 127
(D) 128

✔ **Answer: (c) 127**

Q107. The ASCII value of the space character is:

(A) 0
(B) 32
(C) 64
(D) 127

✔ **Answer: (b) 32**

Q108. What is printf("%d", 'Z'); likely to print?

(A) Z
(B) 90
(C) 122
(D) 25

✔ **Answer: (b) 90**

■ *'Z' has ASCII value 90. %d prints the integer value of the character.*

Q109. In C, which header provides character classification functions like isalpha(), isdigit()?

(A)
(B)
(C)
(D)

✔ **Answer: (b)**

Q110. What does isdigit('7') return?

(A) 0
(B) 7
(C) Non-zero (true)
(D) ASCII value of '7'

✔ **Answer: (c) Non-zero (true)**

■ *isdigit() returns non-zero if the character is a decimal digit ('0'–'9').*

Q111. A C string is terminated by which character constant?

(A) '\n'
(B) '.'
(C) '\0'
(D) ' '

✔ **Answer: (c) '\0'**

Q112. What is the output of: printf("%c", 65);

(A) 65
(B) A
(C) a
(D) Error

✔ **Answer: (b) A**

■ *%c prints the character with the given ASCII code. 65 corresponds to 'A'.*

Q113. What is the output of: printf("%c", 'A' + 1);

(A) A1
(B) B
(C) 66
(D) Error

✔ **Answer: (b) B**

■ *'A' is 65; 65+1=66 which is 'B'.*

Q114. Which of the following stores the ASCII value of 'C' into variable x?

(A) int x = 'C';
(B) int x = "C";
(C) int x = C;
(D) char x = \C;

✔ **Answer: (a) int x = 'C';**

Q115. What is the ASCII value of '\n'?

(A) 92
(B) 10
(C) 13
(D) 110
✔ **Answer: (b) 10**

Q116. The expression ('a' <= c && c <= 'z') checks:

(A) If c is a digit
(B) If c is a lowercase letter
(C) If c is an uppercase letter
(D) If c is alphanumeric
✔ **Answer: (b) If c is a lowercase letter**

Q117. Extended ASCII uses how many bits?

(A) 7
(B) 8
(C) 16
(D) 32
✔ **Answer: (b) 8**
■ *Extended ASCII uses 8 bits allowing 256 characters (0–255).*

Q118. What is the ASCII value of 'Z' (uppercase)?

(A) 89
(B) 90
(C) 91
(D) 122
✔ **Answer: (b) 90**

Q119. What is the ASCII value of 'z' (lowercase)?

(A) 121
(B) 122
(C) 123
(D) 97
✔ **Answer: (b) 122**

Q120. Which is the correct way to print the ASCII value of character 'B'?

(A) printf("%c", 'B')
(B) printf("%d", 'B')
(C) printf("%s", 'B')
(D) printf("%f", 'B')
✔ **Answer: (b) printf("%d", 'B')**

SECTION 5: Previous-Year Exam Style Questions

Questions 121–150 | OAVS TGT Exam Pattern

These questions mirror the style, difficulty, and concepts tested in actual OAVS Computer Teacher (TGT) examinations and similar state-level teacher recruitment exams. Focus especially on tricky output questions and conceptual distinctions.

Q121. [Exam Style] In C, the statement char c = 300; would result in:

(A) c storing 300
(B) c storing 44 (300 mod 256)
(C) A compile-time error
(D) Undefined behaviour only on 64-bit

✔ **Answer: (b) c storing 44 (300 mod 256)**

■ *char is typically 8 bits (unsigned: 0-255, signed: -128 to 127). 300 % 256 = 44 when stored in unsigned char. This is an overflow/truncation.*

Q122. [Exam Style] Which of the following is TRUE about escape sequences?

(A) They occupy 2 bytes of memory
(B) They start with a forward slash
(C) They represent a single character despite being written as two characters
(D) They are only used in printf

✔ **Answer: (c) They represent a single character despite being written as two characters**

■ *Escape sequences like \n look like 2 characters in source code but compile to a single byte.*

Q123. [Exam Style] What will the following print? printf("%c%c%c", 72, 105, 33);

(A) 727133
(B) Hi!
(C) H i !
(D) Error

✔ **Answer: (b) Hi!**

■ *ASCII 72='H', 105='i', 33='!'. Together: 'Hi!'*

Q124. [Exam Style] In OAVS TGT papers, which is the correct definition of white space in C?

(A) Only the space character
(B) Space, tab, and newline only
(C) Space, horizontal tab, vertical tab, newline, form feed, carriage return
(D) Any invisible character including null

✔ **Answer: (c) Space, horizontal tab, vertical tab, newline, form feed, carriage return**

Q125. [Exam Style] The character set of C language as per ANSI standard includes:

(A) 52 letters + 10 digits + special characters
(B) 26 letters + 10 digits
(C) Only printable ASCII characters
(D) All Unicode characters

✔ **Answer: (a) 52 letters + 10 digits + special characters**

■ *C character set includes 52 letters (26 upper + 26 lower), 10 digits, and 29+ special characters.*

Q126. [Exam Style] Which of the following escape sequences clears the current line on most terminals?

(A) \n
(B) \r
(C) \f
(D) \b

✔ **Answer: (b) \r**

■ *\r (carriage return) returns the cursor to the beginning of the line. Combined with spaces it can 'clear' a line.*

Q127. [Exam Style] What is the value of 'A' + 32 in C?

(A) 'a'
(B) 97
(C) Both A and B
(D) Neither

✔ **Answer: (c) Both A and B**

■ *'A' = 65; 65+32 = 97 = 'a'. Both representations are correct.*

Q128. [Exam Style] In C89/ANSI C, sizeof('A') equals:

(A) 1
(B) 2
(C) 4
(D) Platform-dependent but sizeof(int)

✔ **Answer: (c) 4**

■ *In C89, character constants are of type int, so sizeof('A') = sizeof(int) = typically 4. (In C++ it is 1.)*

Q129. [Exam Style] Which header file must be included to use the tolower() function?

(A)
(B)
(C)
(D)

✔ **Answer: (c)**

Q130. [Exam Style] The expression isalnum('_') returns:

(A) Non-zero (true)
(B) Zero (false)
(C) ASCII value of '_'
(D) Error

✔ **Answer: (b) Zero (false)**

■ *isalnum() checks for letters or digits. Underscore '_' (ASCII 95) is neither, so it returns 0.*

Q131. [Exam Style] A character constant in C can hold at most:

(A) 1 character
(B) 2 characters
(C) Any number of characters
(D) 255 characters

✔ **Answer: (a) 1 character**

■ *A character constant is a single character enclosed in single quotes. Multi-character constants exist but are implementation-defined.*

Q132. [Exam Style] What does the C standard say about multi-character constants like 'AB'?

(A) Compile error
(B) Always stores ASCII of last character
(C) Implementation-defined behaviour
(D) Stores both characters packed into int

✔ **Answer: (c) Implementation-defined behaviour**

■ *The C standard says multi-character constants are implementation-defined. Most compilers pack the characters.*

Q133. [Exam Style] Which special character starts a preprocessor directive?

(A) @
(B) $
(C) #
(D) %

✔ **Answer: (c) #**

Q134. [Exam Style] In the C character set, which characters can be used as the FIRST character of an identifier?

(A) Letters and digits
(B) Letters and underscores only
(C) Any character
(D) Only letters

✔ **Answer: (b) Letters and underscores only**

■ *An identifier must start with a letter (A-Z, a-z) or underscore (_). It cannot start with a digit.*

Q135. [Exam Style] What is the output? char c='A'; printf("%d",c);

(A) A
(B) 65
(C) 1
(D) 0

✔ **Answer: (b) 65**

■ *%d prints the integer (ASCII) value. 'A' = 65.*

Q136. [Exam Style] Which of the following is the correct escape sequence to insert a tab in output?

(A) \b
(B) \r
(C) \t
(D) \s

✔ **Answer: (c) \t**

Q137. [Exam Style] The null character '\0' is used in C primarily for:

(A) Ending programs
(B) Marking the end of a string
(C) Clearing variables
(D) Starting loops

✔ **Answer: (b) Marking the end of a string**

Q138. [Exam Style] ASCII value of 'B' is one more than ASCII value of 'A'. This is because:

(A) Coincidence
(B) ASCII assigns consecutive values to consecutive letters
(C) B comes before A alphabetically
(D) Compiler specific

✔ **Answer: (b) ASCII assigns consecutive values to consecutive letters**

Q139. [Exam Style] Which of the following correctly represents the letter 'M' using an escape sequence / numeric constant?

(A) '\77' (octal 77 = 63, which is '?')
(B) '\x4D' (hex 4D = 77 = 'M')
(C) '\113' (octal 113 = 75 = 'K')
(D) '\x4E' (hex 4E = 78 = 'N')
✔ **Answer: (b) '\x4D' (hex 4D = 77 = 'M')**
■ *Hex 4D = 77 decimal = ASCII 'M'.*

Q140. [Exam Style] Which of the following is FALSE about the C character set?

(A) It includes lowercase and uppercase letters
(B) It includes all Unicode characters
(C) It includes special symbols like @, #, $
(D) It includes white-space characters
✔ **Answer: (b) It includes all Unicode characters**
■ *Standard C (ANSI C) is based on ASCII, not Unicode. Unicode support is a feature of newer standards (C11 with).*

Q141. [Exam Style] How does the compiler treat: int x = 'a';

(A) Error: type mismatch
(B) x gets the ASCII value of 'a' (97)
(C) x gets 0
(D) x gets 1
✔ **Answer: (b) x gets the ASCII value of 'a' (97)**
■ *Character constants are integers in C. 'a' evaluates to 97.*

Q142. [Exam Style] The character '\f' has which primary use today?

(A) Frequently used for line breaking in console apps
(B) Historically used for printer page advance; rarely used today
(C) Used to clear the screen
(D) Used to advance tab stops
✔ **Answer: (b) Historically used for printer page advance; rarely used today**

Q143. [Exam Style] Which statement about '\0' and '0' is TRUE?

(A) They are the same
(B) '\0' has value 0; '0' has value 48
(C) Both have value 48
(D) Both have value 0
✔ **Answer: (b) '\0' has value 0; '0' has value 48**
■ *'\0' is the null character (ASCII 0). '0' is the digit zero (ASCII 48).*

Q144. [Exam Style] To check if a character c is a printable character (not control), which function is used?

(A) isprint(c)
(B) isprintable(c)
(C) ischar(c)
(D) isvisible(c)
✔ **Answer: (a) isprint(c)**
■ *isprint() from returns non-zero if c is a printable character (ASCII 32–126).*

Q145. [Exam Style] What will the following code print? char a='A'; a=a+1; printf("%c",a);

(A) A1
(B) B
(C) 66
(D) A+1
✔ **Answer: (b) B**
■ *'A'=65; 65+1=66='B'. Character arithmetic works via ASCII values.*

Q146. [Exam Style] In C, the expression 'Z' - 'A' + 1 evaluates to:

(A) 25
(B) 26
(C) 90
(D) 1
✔ **Answer: (b) 26**
■ *'Z'=90, 'A'=65. 90-65+1 = 26 = number of uppercase letters.*

Q147. [Exam Style] Which of the following is a white-space character that does NOT move to a new line?

(A) \n
(B) \r
(C) \t
(D) Both B and C
✔ **Answer: (d) Both B and C**
■ *\r moves to start of same line; \t moves to next tab stop on same line. Only \n moves to next line.*

Q148. [Exam Style] char c = 'a' - 32; What is stored in c?

(A) 'A' (uppercase A)
(B) 65
(C) Both A and B
(D) Error
✔ **Answer: (c) Both A and B**
■ *'a'=97; 97-32=65='A'. c stores the uppercase version.*

Q149. [Exam Style] Which escape sequence would produce no visible output but terminates a string?

(A) \n
(B) \t
(C) \0
(D) \a
✔ **Answer: (c) \0**

Q150. [Exam Style] When the C compiler encounters '\n' in a string, it stores:

(A) Two separate bytes: ASCII 92 and ASCII 110
(B) One byte: ASCII 10
(C) One byte: ASCII 92
(D) Zero bytes
✔ **Answer: (b) One byte: ASCII 10**
■ *Escape sequences are single characters. \n stores ASCII 10 (newline), just 1 byte.*

Q151. [Exam Style] The OAVS TGT exam often tests: printf("a=%d, b=%c", 'b', 98); — the output is:

(A) a=b, b=98
(B) a=98, b=b
(C) a=b, b=b
(D) a=98, b=98

✔ Answer: (b) a=98, b=b

■ *'b' as %d prints 98 (ASCII of 'b'). 98 as %c prints 'b'. Output: a=98, b=b.*

CHAPTER TEST

50 Questions | Time Allowed: 60 Minutes | Marks: 50

Instructions: Each question carries 1 mark. There is no negative marking. Circle the best answer. Attempt all questions.

Q1. How many alphabetic characters are present in the C character set?

(A) 26
(B) 52
(C) 54
(D) 56

■ *C recognizes both uppercase (A–Z) and lowercase (a–z), giving 52 alphabetic characters.*

Q2. How many decimal digits are included in the C character set?

(A) 8
(B) 9
(C) 10
(D) 11

■ *C includes digits 0 through 9, making 10 decimal digits.*

Q3. Which of the following special characters is used to terminate a C statement?

(A) ,
(B) .
(C) ;
(D) :

■ *The semicolon (;) is the statement terminator in C.*

Q4. What is the total number of special characters defined in the ANSI C character set?

(A) 28
(B) 29
(C) 30
(D) 31

■ *ANSI C defines 29 special characters including +, -, *, /, =, {}, [], etc.*

Q5. In C, uppercase letters and lowercase letters are treated as:

(A) Same
(B) Different (case-sensitive)
(C) Interchangeable
(D) Depends on compiler

■ *C is case-sensitive, so 'A' and 'a' are completely different characters.*

Q6. The character '*' in C is primarily used as:

(A) Bitwise AND
(B) Multiplication operator and pointer declarator
(C) String delimiter
(D) Logical NOT

■ *'*' serves as multiplication operator (a*b) and also as pointer declarator (int *p).*

Q7. Which of the following characters is used for bitwise XOR in C?

(A) &
(B) |
(C) ^
(D) ~

Q8. What is the maximum ASCII value of a printable character in standard ASCII?

(A) 126
(B) 127
(C) 128
(D) 255

■ *The printable characters in ASCII range from 32 (space) to 126 (~). ASCII 127 is the DEL control character.*

Q9. The '#' character in C is associated with:

(A) Bitwise operations
(B) Preprocessor directives
(C) Pointer operations
(D) Comments

■ *# is used with preprocessor directives like #include and #define.*

Q10. The '{}' (curly braces) in C are used to:

(A) Define arrays
(B) Enclose blocks of code
(C) Both A and B
(D) Declare functions only

Q11. Which of the following is NOT a white-space character in C?

(A) Space ( )
(B) Horizontal tab (\t)
(C) Newline (\n)
(D) Asterisk (*)

■ *White-space characters are space, tab, newline, carriage return, form feed, and vertical tab. Asterisk is not one of them.*

Q12. What is the ASCII value of the space character?

(A) 0
(B) 8
(C) 32
(D) 48

■ *The space character has ASCII value 32.*

Q13. What does the newline character (\n) do in C output?

(A) Moves cursor to column 1 of the same line
(B) Moves cursor to beginning of next line
(C) Clears the screen
(D) Inserts a blank line

Q14. The carriage return character (\r) moves the cursor to:

(A) Next line
(B) Beginning of the current line
(C) Next tab stop
(D) End of the line

■ *\r (CR) moves cursor to the beginning of the current line without advancing to the next line.*

Q15. What is the ASCII value of the horizontal tab character (\t)?

(A) 7
(B) 8
(C) 9
(D) 11

■ *Horizontal tab has ASCII value 9.*

Q16. The vertical tab character (\v) has ASCII value:

(A) 9
(B) 10
(C) 11
(D) 12

Q17. Carriage return (\r) has ASCII value:

(A) 11
(B) 12
(C) 13
(D) 14

Q18. Which function in C can be used to skip white-space characters when reading input?

(A) getchar()
(B) scanf() with format specifiers
(C) fgets()
(D) Both A and B

■ *scanf() automatically skips leading white space for most format specifiers (except %c).*

Q19. What is an escape sequence in C?

(A) A jump in program execution
(B) A combination of \ and a character representing a special meaning
(C) An error-handling mechanism
(D) A preprocessor directive

■ *An escape sequence starts with backslash (\) followed by a character and represents non-printable or special characters.*

Q20. What is the purpose of '\a' escape sequence?

(A) Alert / Audible bell
(B) Ampersand
(C) Array start
(D) Assignment

■ *\a produces an audible bell (alert sound). Its ASCII value is 7.*

Q21. The escape sequence '\0' represents:

(A) The digit zero
(B) Null character (end of string)
(C) Octal escape
(D) Output newline

■ *\0 is the null character with ASCII value 0, marking the end of a C string.*

Q22. What is the ASCII value of '\b' (backspace)?

(A) 7
(B) 8
(C) 9
(D) 10

Q23. To print a double quote (") inside a C string, which escape sequence is used?

(A) \"
(B) \q
(C) \dq
(D) ""

■ *\" inserts a double-quote character inside a string literal.*

Q24. What is the output of: printf("Hello\bWorld");

(A) Hello World
(B) HellWorld
(C) Hello\bWorld
(D) HelloWorld

■ *\b moves cursor back one position, so 'o' is overwritten by 'W', producing 'HellWorld'.*

Q25. The escape sequence '\v' stands for:

(A) Variable
(B) Vertical tab
(C) Void
(D) Value

Q26. What is the output of: printf("Line1\nLine2");

(A) Line1 Line2
(B) Line1\nLine2
(C) Line1 followed by Line2 on next line
(D) Line1Line2

Q27. What does \xhh represent in C?

(A) A hexadecimal escape sequence for a character
(B) A hex number
(C) An HTML tag
(D) A preprocessor macro

■ *\x followed by hex digits represents the character with that hexadecimal ASCII value, e.g. \x41 = 'A'.*

Q28. printf("\101") produces which character? (101 octal = 65 decimal)

(A) A
(B) a
(C) 1
(D) 101

■ *\101 is an octal escape for ASCII 65, which is 'A'.*

Q29. Which of the following escape sequences is NOT valid in ANSI C?

(A) \n
(B) \t
(C) \s
(D) \v

■ *\s is not a standard C escape sequence. \n, \t, and \v are all valid.*

Q30. In C, char c = '\n'; — what is stored in c?

(A) Two characters: \ and n
(B) A single character with ASCII value 10
(C) ASCII 92 (backslash)
(D) Error

■ *\n is a single character escape sequence with ASCII value 10.*

Q31. How is a character constant written in C?

(A) Double quotes: "A"
(B) Single quotes: 'A'
(C) Parentheses: (A)
(D) Angle brackets: <A>

■ *Character constants are enclosed in single quotes. "A" would be a string literal.*

Q32. What is the ASCII value of 'A' (uppercase)?

(A) 64
(B) 65
(C) 66
(D) 97

■ *'A' has ASCII value 65.*

Q33. What is the ASCII value of '0' (digit zero)?

(A) 0
(B) 32
(C) 48
(D) 58

■ *'0' has ASCII value 48. Digits '0'–'9' have ASCII values 48–57.*

Q34. What expression converts a lowercase letter c to uppercase in C?

(A) c - 32
(B) c + 32
(C) c - 'a' + 'A'
(D) Both A and C

■ *Both c-32 and c-'a'+'A' work. The standard way is toupper(c) from .*

Q35. What is the value of ('9' - '0') in C?

(A) 0
(B) 9
(C) 57
(D) 48

■ *'9' is ASCII 57 and '0' is ASCII 48. 57 - 48 = 9.*

Q36. The total number of characters in standard ASCII is:

(A) 64
(B) 128
(C) 256
(D) 512

■ *Standard ASCII defines 128 characters (0–127).*

Q37. Which ASCII range represents uppercase letters (A–Z)?

(A) 97–122
(B) 65–90
(C) 48–57
(D) 33–64

Q38. The ASCII value of the null character (\0) is:

(A) 0
(B) 32
(C) 127
(D) 255

Q39. The ASCII value of the space character is:

(A) 0
(B) 32
(C) 64
(D) 127

Q40. In C, which header provides character classification functions like isalpha(), isdigit()?

(A)
(B)
(C)
(D)

Q41. [Exam Style] In C, the statement char c = 300; would result in:

(A) c storing 300
(B) c storing 44 (300 mod 256)
(C) A compile-time error
(D) Undefined behaviour only on 64-bit

■ *char is typically 8 bits (unsigned: 0-255, signed: -128 to 127). 300 % 256 = 44 when stored in unsigned char. This is an overflow/truncation.*

Q42. [Exam Style] What will the following print? printf("%c%c%c", 72, 105, 33);

(A) 727133
(B) Hi!
(C) H i !
(D) Error

■ *ASCII 72='H', 105='i', 33='!'. Together: 'Hi!'*

Q43. [Exam Style] The character set of C language as per ANSI standard includes:

(A) 52 letters + 10 digits + special characters
(B) 26 letters + 10 digits
(C) Only printable ASCII characters
(D) All Unicode characters

■ *C character set includes 52 letters (26 upper + 26 lower), 10 digits, and 29+ special characters.*

Q44. [Exam Style] What is the value of 'A' + 32 in C?

(A) 'a'
(B) 97
(C) Both A and B
(D) Neither

■ *'A' = 65; 65+32 = 97 = 'a'. Both representations are correct.*

Q45. [Exam Style] Which header file must be included to use the tolower() function?

(A)
(B)
(C)
(D)

Q46. [Exam Style] A character constant in C can hold at most:

(A) 1 character
(B) 2 characters
(C) Any number of characters
(D) 255 characters

■ *A character constant is a single character enclosed in single quotes. Multi-character constants exist but are implementation-defined.*

Q47. [Exam Style] Which special character starts a preprocessor directive?

(A) @
(B) $
(C) #
(D) %

Q48. [Exam Style] What is the output? char c='A'; printf("%d",c);

(A) A
(B) 65
(C) 1
(D) 0

■ *%d prints the integer (ASCII) value. 'A' = 65.*

Q49. [Exam Style] The null character '\0' is used in C primarily for:

(A) Ending programs
(B) Marking the end of a string
(C) Clearing variables
(D) Starting loops

Q50. [Exam Style] Which of the following correctly represents the letter 'M' using an escape sequence / numeric constant?

(A) '\77' (octal 77 = 63, which is '?')
(B) '\x4D' (hex 4D = 77 = 'M')
(C) '\113' (octal 113 = 75 = 'K')
(D) '\x4E' (hex 4E = 78 = 'N')

■ *Hex 4D = 77 decimal = ASCII 'M'.*

ANSWER KEY

All 150 MCQs + Chapter Test

Section 1 (Q1–Q30): Letters, Digits & Special Symbols				
Q1: **(B)**	Q2: **(C)**	Q3: **(C)**	Q4: **(B)**	Q5: **(C)**
Q6: **(B)**	Q7: **(B)**	Q8: **(C)**	Q9: **(B)**	Q10: **(C)**
Q11: **(B)**	Q12: **(C)**	Q13: **(C)**	Q14: **(B)**	Q15: **(A)**
Q16: **(C)**	Q17: **(B)**	Q18: **(B)**	Q19: **(C)**	Q20: **(D)**
Q21: **(B)**	Q22: **(B)**	Q23: **(C)**	Q24: **(A)**	Q25: **(C)**
Q26: **(B)**	Q27: **(B)**	Q28: **(A)**	Q29: **(C)**	Q30: **(C)**

Section 2 (Q31–Q55): White Space Characters				
Q31: **(D)**	Q32: **(D)**	Q33: **(C)**	Q34: **(B)**	Q35: **(B)**
Q36: **(D)**	Q37: **(B)**	Q38: **(B)**	Q39: **(C)**	Q40: **(B)**
Q41: **(C)**	Q42: **(C)**	Q43: **(C)**	Q44: **(B)**	Q45: **(B)**
Q46: **(B)**	Q47: **(B)**	Q48: **(C)**	Q49: **(B)**	Q50: **(B)**
Q51: **(B)**	Q52: **(C)**	Q53: **(B)**	Q54: **(B)**	Q55: **(B)**

Section 3 (Q56–Q90): Escape Sequences				
Q56: **(B)**	Q57: **(C)**	Q58: **(A)**	Q59: **(B)**	Q60: **(B)**
Q61: **(C)**	Q62: **(B)**	Q63: **(C)**	Q64: **(A)**	Q65: **(C)**
Q66: **(B)**	Q67: **(C)**	Q68: **(B)**	Q69: **(A)**	Q70: **(C)**
Q71: **(B)**	Q72: **(A)**	Q73: **(B)**	Q74: **(A)**	Q75: **(B)**
Q76: **(C)**	Q77: **(B)**	Q78: **(B)**	Q79: **(B)**	Q80: **(A)**
Q81: **(A)**	Q82: **(D)**	Q83: **(B)**	Q84: **(B)**	Q85: **(C)**
Q86: **(B)**	Q87: **(C)**	Q88: **(C)**	Q89: **(C)**	Q90: **(B)**

Section 4 (Q91–Q120): Character Constants & ASCII				
Q91: **(B)**	Q92: **(B)**	Q93: **(B)**	Q94: **(B)**	Q95: **(C)**
Q96: **(B)**	Q97: **(D)**	Q98: **(B)**	Q99: **(B)**	Q100: **(A)**
Q101: **(B)**	Q102: **(A)**	Q103: **(B)**	Q104: **(C)**	Q105: **(A)**
Q106: **(C)**	Q107: **(B)**	Q108: **(B)**	Q109: **(B)**	Q110: **(C)**

Q111: **(C)**	Q112: **(B)**	Q113: **(B)**	Q114: **(A)**	Q115: **(B)**
Q116: **(B)**	Q117: **(B)**	Q118: **(B)**	Q119: **(B)**	Q120: **(B)**

Section 5 (Q121–Q150): Previous-Year Exam Style				
Q121: **(B)**	Q122: **(C)**	Q123: **(B)**	Q124: **(C)**	Q125: **(A)**
Q126: **(B)**	Q127: **(C)**	Q128: **(C)**	Q129: **(C)**	Q130: **(B)**
Q131: **(A)**	Q132: **(C)**	Q133: **(C)**	Q134: **(B)**	Q135: **(B)**
Q136: **(C)**	Q137: **(B)**	Q138: **(B)**	Q139: **(B)**	Q140: **(B)**
Q141: **(B)**	Q142: **(B)**	Q143: **(B)**	Q144: **(A)**	Q145: **(B)**
Q146: **(B)**	Q147: **(D)**	Q148: **(C)**	Q149: **(C)**	Q150: **(B)**
Q151: **(B)**				

Chapter Test Answer Key (T1–T50)				
Q1: **(B)**	Q2: **(C)**	Q3: **(C)**	Q4: **(B)**	Q5: **(B)**
Q6: **(B)**	Q7: **(C)**	Q8: **(A)**	Q9: **(B)**	Q10: **(C)**
Q11: **(D)**	Q12: **(C)**	Q13: **(B)**	Q14: **(B)**	Q15: **(C)**
Q16: **(C)**	Q17: **(C)**	Q18: **(B)**	Q19: **(B)**	Q20: **(A)**
Q21: **(B)**	Q22: **(B)**	Q23: **(A)**	Q24: **(B)**	Q25: **(B)**
Q26: **(C)**	Q27: **(A)**	Q28: **(A)**	Q29: **(C)**	Q30: **(B)**
Q31: **(B)**	Q32: **(B)**	Q33: **(C)**	Q34: **(D)**	Q35: **(B)**
Q36: **(B)**	Q37: **(B)**	Q38: **(A)**	Q39: **(B)**	Q40: **(B)**
Q41: **(B)**	Q42: **(B)**	Q43: **(A)**	Q44: **(C)**	Q45: **(C)**
Q46: **(A)**	Q47: **(C)**	Q48: **(B)**	Q49: **(B)**	Q50: **(B)**

QUICK REVISION NOTES

Key Facts for Last-Minute Preparation

C Character Set	52 letters (A–Z, a–z) + 10 digits (0–9) + 29 special characters + 6 white-space chars.
White Space Characters	Space (32), \t (9), \n (10), \v (11), \f (12), \r (13) — 6 in total.
Escape Sequences	11 standard: \a(7), \b(8), \t(9), \n(10), \v(11), \f(12), \r(13), \\\ (92), \' (39), \" (34), \0 (0).
Important ASCII Values	'0'=48, '9'=57, 'A'=65, 'Z'=90, 'a'=97, 'z'=122, Space=32, NUL=0, DEL=127.
Character Constants	In C89: type is int. In C++: type is char. Always use single quotes: 'A'.
Case Conversion	lowercase = uppercase + 32 | uppercase = lowercase - 32. Or use toupper()/tolower() from .
Identifier Rules	Must start with letter or '_'. Can contain letters, digits, '_'. Case-sensitive. No keywords.
isspace() test	Returns non-zero for: ' ', \t, \n, \v, \f, \r. Declared in .

Best of luck for your OAVS TGT Computer Science Examination!