VALIDATING AND PROCESSING USER INPUTS

OAVS TGT Computer Teacher Examination | MCQ Question Bank

Syllabus covered

1. Overview of Input Validation
2. Importance of Input Validation
3. Types of Validation
4. Implementing Form-Level Validation
5. Implementing Field-Level Validation
6. Text Box Properties
7. Using Events for Validation
8. Validate Event

135 questions in 10 sections. Each card shows the question, four options, the answer strip and a short explanation. Question numbering is continuous across the book.

1. Overview and Importance of Input Validation

11 Questions

Q1 | Concept | Input Validation

What is the primary purpose of input validation in a form?

A. To automatically create database tables
B. To ensure that entered data meets specified requirements
C. To change the form's background colour
D. To increase the number of controls on the form

Ans: B

Explanation: Input validation checks whether user-entered data satisfies the required conditions before it is processed.

Q2 | Definition | Input Validation

Input validation is best described as the process of:

A. arranging controls neatly on the form at design time
B. increasing the execution speed of the program
C. compiling the source code into an executable file
D. checking user-supplied data for acceptability before using it

Ans: D

Explanation: It tests entered values against rules (type, range, length, format, presence) before they are processed.

Q3 | Importance | Data Quality

Which problem is directly reduced by validating user input?

A. Slow redrawing of the form on screen
B. Large size of the compiled executable file
C. Missing captions on command buttons
D. Invalid or inconsistent data entering the program

Ans: D

Explanation: Validation filters out wrong entries so that only acceptable data is processed.

Q4 | Concept | Timing

Input validation should ideally be carried out:

A. only after the results have been displayed
B. only once, when the project is first designed
C. before the entered data is accepted and processed
D. only after the application has been closed

Ans: C

Explanation: Checking early prevents wrong data from affecting calculations or results.

Q5 | Importance | Run-time Errors

A user types "abc" in a text box and the program executes `CInt(Text1.Text)`. Which benefit of validation does this situation highlight?

A. It shortens the time taken to compile the project
B. It reduces the number of controls needed on the form
C. It improves the visual appearance of the form
D. It prevents run-time errors caused by incompatible data

Ans: D

Explanation: `CInt("abc")` raises a Type mismatch error (Error 13); validating first avoids the crash.

Q6 | Concept | Scope of Validation

Which statement about input validation is correct?

A. It checks that data is reasonable and well-formed, not that it is factually true
B. It is needed only for numeric entries, never for text
C. It guarantees that every accepted value is factually correct
D. It is carried out by VB 6.0 automatically, without any code

Ans: A

Explanation: A valid-looking entry (e.g. age 25) may still be untrue; validation only tests rules such as type, range and format.

Q7 | Importance | User Guidance

Showing a message such as "Age must be between 1 and 100" after a failed check mainly helps to:

A. reduce the memory used by the program
B. hide the invalid value from the program
C. guide the user in correcting the mistake
D. speed up the loading of the form

Ans: C

Explanation: Clear messages tell the user what was wrong and how to correct it.

Q8 | Concept | GIGO

The principle "Garbage In, Garbage Out" in the context of validation means:

A. unused variables are automatically deleted
B. output quality is independent of the input given
C. invalid input is corrected by VB 6.0 on its own
D. poor-quality input produces unreliable output

Ans: D

Explanation: If wrong data is accepted, the results computed from it will also be wrong.

Q9 | Concept | Implementation in VB 6.0

In VB 6.0, input validation is usually implemented by:

A. writing code in event procedures and setting control properties
B. installing an extra operating-system service pack
C. changing the screen resolution of the system
D. editing the project (.vbp) file in a text editor

Ans: A

Explanation: Properties (e.g. `MaxLength`) and event code (e.g. `KeyPress`, `Validate`, `Click`) together enforce validation rules.

Q10 | Importance | NOT Type

Which of the following is NOT a benefit of input validation?

A. It prevents some run-time errors
B. It reduces the number of invalid entries
C. It helps maintain data integrity
D. It removes the need to test the application

Ans: D

Explanation: Validation improves reliability but never replaces proper testing of the application.

Q11 | Concept | Getting Input

Which VB 6.0 function displays a prompt in a dialog box and returns the text typed by the user, so that the value can then be validated?

A. MsgBox
B. Format
C. InputBox
D. Print

Ans: C

Explanation: `InputBox` collects a value from the user as a string, which should be validated before use.

2. Types of Validation

14 Questions

Q12 | Types | Presence Check

Making sure that a mandatory text box is not left blank is called a:

A. Format check
B. Presence (required-field) check
C. Range check
D. Lookup check

Ans: B

Explanation: A presence check confirms that a value has been entered in a required field.

Q13 | Types | Range Check

Ensuring that the value entered in an Age box lies between 18 and 60 is a:

A. Length check
B. Presence check
C. Range check
D. Lookup check

Ans: C

Explanation: A range check tests that a value falls between a lower and an upper limit.

Q14 | Types | Data Type Check

Ensuring that a Quantity box accepts only numeric data is a:

A. Presence check
B. Range check
C. Data type check
D. Lookup check

Ans: C

Explanation: A type check confirms that the entry is of the expected kind (number, date, text).

Q15 | Types | Length Check

Verifying that a postal PIN code contains exactly 6 characters is a:

A. Range check
B. Format check
C. Presence check
D. Length check

Ans: D

Explanation: A length check tests the number of characters in the entry.

Q16 | Types | Format Check

Checking that an e-mail address contains the "@" symbol is a:

A. Length check
B. Range check
C. Presence check
D. Format check

Ans: D

Explanation: A format check verifies that data follows an expected pattern or structure.

Q17 | Types | List (Lookup) Check

Accepting only "Male", "Female" or "Other" for a Gender field is a:

A. List (lookup) check
B. Data type check
C. Length check
D. Range check

Ans: A

Explanation: A list check allows only values that belong to a predefined set.

Q18 | Types | Keystroke Validation

Rejecting a non-digit character at the moment it is typed is called:

A. compile-time validation
B. batch validation after closing the form
C. form-level validation after submission
D. keystroke (character-level) validation

Ans: D

Explanation: Checking each key as it is typed (e.g. in `KeyPress`) stops invalid characters from entering the box.

Q19 | Types | Cross-field Validation

Checking that "To Date" is not earlier than "From Date" is an example of:

A. cross-field (consistency) validation
B. presence validation
C. keystroke validation
D. length validation

Ans: A

Explanation: It compares two fields with each other, so it can be done only when both values are available.

Q20 | Types | Function for Numbers

Which VB 6.0 function is most suitable for checking whether a text box entry is numeric?

A. IsArray
B. IsNumeric
C. IsNull
D. IsDate

Ans: B

Explanation: `IsNumeric(expression)` returns True if the expression can be evaluated as a number.

Q21 | Types | Function for Dates

Which function tests whether text can be interpreted as a valid date?

A. IsObject
B. IsDate
C. IsNumeric
D. IsEmpty

Ans: B

Explanation: `IsDate` returns True when the expression is a date or can be converted to a valid date.

Q22 | Types | Pattern Check

Which VB 6.0 operator compares a string against a pattern such as "[A-Z]##"?

A. Like
B. Mod
C. Is
D. Xor

Ans: A

Explanation: The `Like` operator tests a string against a pattern and returns True or False; it is useful for format checks.

Q23 | Types | Like Wildcards

In a `Like` pattern, the character # matches:

A. a literal hash symbol only
B. any number of characters
C. any single digit
D. any single letter

Ans: C

Explanation: # = one digit, ? = one character, * = zero or more characters, `[A-Z]` = one letter in the range.

Q24 | Types | Like Result

What is the result of the following expression?

```
"AB12" Like "[A-Z][A-Z]##"
```

A. Null
B. False
C. A syntax error
D. True

Ans: D

Explanation: The string has two letters followed by two digits, which exactly matches the pattern.

Q25 | Types | Consistency Check

Checking that the Date of Joining is not earlier than the Date of Birth is an example of a:

A. list check
B. consistency (cross-field) check
C. presence check
D. length check

Ans: B

Explanation: A consistency check tests that two related fields are logically compatible.

3. Form-Level Validation

10 Questions

Q26 | Definition | Form-Level

Form-level validation means:

A. validating the form's Caption property
B. validating only the first control placed on the form
C. checking all the fields together, usually when the user submits the form
D. checking each key as it is typed into a text box

Ans: C

Explanation: Form-level validation is performed on the whole set of entries, typically at an OK / Submit / Save action.

Q27 | Event | Form-Level

Form-level validation is most commonly coded in the Click event of:

A. the Form_Resize event
B. the Timer control's Interval property
C. an OK or Submit command button
D. a Label's Caption property

Ans: C

Explanation: The command button's `Click` procedure runs when the user confirms the data, so all fields can be checked there.

Q28 | Concept | Advantage

A key advantage of form-level validation over field-level validation is that it:

A. can check relationships among several fields at once
B. avoids writing any code at all
C. removes the need for any message to the user
D. stops each wrong keystroke immediately

Ans: A

Explanation: Because every field is available at submission, cross-field rules (e.g. From/To dates) can be tested.

Q29 | Concept | Limitation

A drawback of form-level validation is that:

A. it cannot be used with text boxes
B. the user learns about mistakes only after filling in the whole form
C. it cannot examine more than one control
D. it works only with option buttons

Ans: B

Explanation: Errors are reported at the end, unlike field-level checks which give immediate feedback.

Q30 | Code | Form-Level Flow

Study the code.

```
Private Sub cmdOK_Click()
    If Len(Trim(txtName.Text)) = 0 Then
        MsgBox "Enter name"
        txtName.SetFocus
        Exit Sub
    End If
    If Not IsNumeric(txtAge.Text) Then
        MsgBox "Age must be numeric"
        txtAge.SetFocus
        Exit Sub
    End If
    MsgBox "Data accepted"
End Sub
```

txtName is empty and txtAge contains "xx". What happens when cmdOK is clicked?

A. Only "Age must be numeric" is displayed
B. Only "Enter name" is shown and focus goes to txtName
C. Both messages are shown one after the other
D. "Data accepted" is displayed

Ans: B

Explanation: The first failed check displays its message and `Exit Sub` ends the procedure, so later checks never run.

Q31 | Concept | Logic Sequence

Which sequence correctly reflects typical form-level validation logic?

A. Accept the data first and check the fields afterwards
B. Check the fields only after the form has been unloaded
C. Clear all fields first and then check them
D. Check each field; on failure show a message, set focus and stop; otherwise accept the data

Ans: D

Explanation: Validation must come before processing; the procedure stops at the first invalid entry.

Q32 | Scenario | Confirm Password

Which check can be meaningfully done only after both entries exist, i.e. at form level?

A. Comparing a Password box with a Confirm Password box
B. Allowing only digits in a phone number box
C. Converting each typed letter to upper case
D. Limiting the length of one box using MaxLength

Ans: A

Explanation: Comparing two fields needs both values, so it is done when the form is submitted.

Q33 | Error-ID | Missing Exit Sub

Study the code.

```
Private Sub cmdSave_Click()
    If txtCode.Text = "" Then
        MsgBox "Code required"
    End If
    MsgBox "Saved"
End Sub
```

Why is "Saved" still displayed when txtCode is blank?

A. Nothing stops the procedure after the error message

B. MsgBox cannot be used inside an If block

C. A Click event cannot contain an If statement

D. A text box cannot be compared with an empty string

Ans: A

Explanation: After the error message, `Exit Sub` (or an Else part) is needed to prevent the save step from running.

Q34 | Scenario | Form-Level Choice

Total Marks must not exceed Maximum Marks, and both values are entered in separate text boxes. The most suitable place for this check is:

A. the Form_Load event

B. the Click event of the Submit button

C. the KeyPress event of the Total Marks box

D. the MaxLength property of the Total Marks box

Ans: B

Explanation: The rule depends on two fields, so it is checked when both values are available, i.e. on submission.

Q35 | Concept | Comparison

Which statement correctly distinguishes form-level from field-level validation?

A. Form-level checks each key typed; field-level checks the whole form on closing

B. Both are always performed automatically by VB 6.0 without code

C. Form-level checks the data collectively on submission; field-level checks a single control as it is entered or left

D. Form-level works only for command buttons; field-level only for labels

Ans: C

Explanation: Form-level is collective and at the end; field-level is per control and immediate.

4. Field-Level Validation

10 Questions

Q36 | Definition | Field-Level

Field-level validation checks:

A. the value of an individual control as it is entered or when it is left
B. all controls together after the form is closed
C. only the Caption of the form
D. only the command buttons on the form

Ans: A

Explanation: It is applied to one control at a time, giving immediate feedback near the point of error.

Q37 | Concept | Advantage

Which is an advantage of field-level validation?

A. It runs only when the form is closed
B. It removes the need for any form-level checks
C. Errors are caught immediately, close to where they occur
D. It validates relationships among all fields at once

Ans: C

Explanation: Immediate feedback lets the user correct a field while it is still in mind.

Q38 | Scenario | Digits Only

A phone number text box must accept only digits as the user types. The best approach is to:

A. filter the characters in the KeyPress event
B. check the value in the Form_Unload event
C. set the Locked property to True
D. set the Visible property to False

Ans: A

Explanation: `KeyPress` receives each character, so unwanted ones can be cancelled by setting `KeyAscii = 0`.

Q39 | Concept | KeyPress vs Validate

Which pairing correctly describes field-level validation techniques?

A. Both run only when the OK button is clicked
B. Validate checks each character; KeyPress checks the complete value of the field
C. KeyPress checks each character; Validate checks the complete value of the field
D. KeyPress runs only when the form loads; Validate only when it closes

Ans: C

Explanation: `KeyPress` works at character level, whereas `Validate` examines the finished entry as focus leaves the control.

Q40 | Concept | Identify Field-Level

Which of the following is an example of field-level validation?

A. Comparing From and To dates when Save is clicked
B. Ensuring all required boxes are filled when OK is clicked
C. Rejecting a letter typed into an Age box
D. Checking Password against Confirm Password on submission

Ans: C

Explanation: The other options involve several fields and are normally handled at form level.

Q41 | Event | Not Suitable

Which event is NOT suitable for field-level validation of a text box?

A. LostFocus
B. KeyPress
C. Validate
D. Form_Load

Ans: D

Explanation: `Form_Load` runs once when the form loads, before the user enters anything.

Q42 | Concept | Combined Use

Why are field-level and form-level validation often used together?

A. Field checks make the form-level code compile faster
B. VB 6.0 refuses to run a form unless both are present
C. Field checks give instant feedback; form checks catch skipped or cross-field errors
D. Form-level checks automatically correct the wrong entries

Ans: C

Explanation: The two approaches complement each other: immediate guidance plus a final safety net before processing.

Q43 | Statement | Field-Level

Consider the statements about field-level validation:
1. It can give immediate feedback to the user.
2. It is applied to one control at a time.
3. It can be carried out only after the form is closed.
Which statements are correct?

A. 2 and 3 only
B. 1 and 3 only
C. 1 and 2 only
D. 1, 2 and 3

Ans: C

Explanation: Field-level checks happen while the user works on the form, not after it is closed, so statement 3 is wrong.

Q44 | Scenario | Field-Level Choice

An Age box must be checked for the range 1 to 100 at the moment the user tries to leave it. The best event is:

A. Validate
B. Form_Resize
C. Form_Load
D. Click of the form

Ans: A

Explanation: `Validate` is raised as focus leaves the control and can keep focus there when the value is wrong.

Q45 | Scenario | Character Filtering

A Name box must reject digits as soon as they are typed. The most suitable approach is:

A. checking KeyAscii in the KeyPress event
B. setting the Locked property to True
C. setting the Visible property to False
D. checking the value in the Form_Unload event

Ans: A

Explanation: `KeyPress` receives each character before it appears, so unwanted ones can be cancelled by setting `KeyAscii = 0`.

5. Text Box Properties

19 Questions

Q46 | Property | MaxLength

Which text box property limits the number of characters a user can type?

A. MaxChars
B. TextSize
C. MaxLength
D. TextLimit

Ans: C

Explanation: `MaxLength` sets the maximum number of characters that can be entered.

Q47 | Property | MaxLength = 0

What does `MaxLength = 0` mean for a text box?

A. No limit is set other than the control's own maximum (about 32K)
B. The text box is hidden at run time
C. Only one character may be typed
D. The text box accepts no characters at all

Ans: A

Explanation: A value of 0 means the length is limited only by the text box's capacity.

Q48 | Property | PasswordChar

Which property displays a substitute character such as * while the user types?

A. SecretChar
B. PasswordChar
C. MaskChar
D. InputMask

Ans: B

Explanation: Setting `PasswordChar = "*"` shows an asterisk for every character typed.

Q49 | Property | PasswordChar Condition

The `PasswordChar` property has no effect when:

A. Alignment is Center
B. MaxLength is 0
C. MultiLine is True
D. Locked is True

Ans: C

Explanation: Masking works only for single-line text boxes; it is ignored when `MultiLine = True`.

Q50 | Property | Locked

Which setting lets the user see and select the text but not edit it?

A. Enabled = False
B. Visible = False
C. Locked = True
D. TabStop = False

Ans: C

Explanation: A locked text box still displays text and can receive focus; a disabled one is dimmed and cannot.

Q51 | Property | Text

Which property holds the string entered by the user and is the default property of a text box?

A. Value
B. Name
C. Caption
D. Text

Ans: D

Explanation: `Text1 = "abc"` is the same as `Text1.Text = "abc"` because `Text` is the default property.

Q52 | Property | SelStart and SelLength

What does this code do?

```
Text1.SelStart = 0
Text1.SelLength = Len(Text1.Text)
```

A. Deletes all text from the text box
B. Selects (highlights) the entire text in the text box
C. Sets MaxLength equal to the text length
D. Moves the text box to the left edge of the form

Ans: B

Explanation: It is commonly used after a failed validation so the user can overwrite the wrong entry.

Q53 | Property | CausesValidation

What is the default value of the `CausesValidation` property of a text box?

A. False
B. Empty
C. True
D. Null

Ans: C

Explanation: By default a control triggers validation of the control that is losing focus.

Q54 | Property | TabStop

If TabStop is False for a text box, then:

A. the Tab key skips it, but the user can still click into it
B. it becomes invisible at run time
C. its Validate event is removed
D. it can never receive focus

Ans: A

Explanation: `TabStop = False` removes it from the Tab sequence only; the mouse can still give it focus.

Q55 | Property | MultiLine

To let the Enter key create a new line inside a text box, which setting is required?

A. MultiLine = True
B. MaxLength = 1
C. PasswordChar = Chr(13)
D. Locked = True

Ans: A

Explanation: A multi-line text box accepts line breaks and can show several lines of text.

Q56 | Property | Empty Test

Which expression is True when a text box is empty?

A. Text1.Text = Nothing
B. Text1.Length = 0
C. Text1.Text Is Nothing
D. Len(Text1.Text) = 0

Ans: D

Explanation: The `Text` property is a string, so an empty box has length 0 (or equals `""`).

Q57 | Property | ToolTipText

Which property displays a short hint when the mouse pauses over a text box?

A. ToolTipText
B. Tag
C. DataField
D. Appearance

Ans: A

Explanation: `ToolTipText` can tell the user what input is expected, e.g. "Enter age (1-100)".

Q58 | Property | Enabled

What is the effect of setting `Enabled = False` for a text box?

A. The text box is deleted from the form
B. The text box accepts only digits
C. The text is dimmed and the user cannot give it focus or edit it
D. The text box becomes invisible

Ans: C

Explanation: A disabled control ignores user input; `Visible = False` is what hides a control.

Q59 | Property | Visible

Which property, when set to False, hides a text box at run time while leaving it on the form?

A. Visible
B. Locked
C. TabStop
D. Enabled

Ans: A

Explanation: `Visible = False` hides the control; `Enabled = False` only dims and disables it.

Q60 | Property | Tag

The Tag property of a text box is mainly used to:

A. store extra programmer-defined information about the control
B. mask the typed characters
C. display a tooltip to the user
D. limit the number of characters typed

Ans: A

Explanation: `Tag` is not used by VB itself; programmers keep custom data in it, e.g. a rule code for validation.

Q61 | Property | SelText

Assigning a string to the `SelText` property of a text box:

A. changes the font of the selected text
B. sets the maximum length of the text box
C. replaces the whole text of the text box
D. replaces the currently selected text with that string

Ans: D

Explanation: `SelText` returns or sets the selected portion; with no selection, the text is inserted at the insertion point.

Q62 | Property | ScrollBars

The ScrollBars property of a text box takes effect only when:

A. PasswordChar is set
B. Locked is True
C. MaxLength is 0
D. MultiLine is True

Ans: D

Explanation: A single-line text box cannot display scroll bars, so the property is ignored unless `MultiLine = True`.

Q63 | Method | SetFocus

Which method moves the cursor into a particular text box, for example after a failed validation?

A. Refresh
B. SetFocus
C. Move
D. Drag

Ans: B

Explanation: `txtAge.SetFocus` places the focus in the control; the control must be visible and enabled.

Q64 | Property | Alignment

Which property decides whether text in a text box is left-aligned, right-aligned or centred?

A. TextAlign
B. Alignment
C. Align
D. Justify

Ans: B

Explanation: `Alignment` accepts 0-Left Justify, 1-Right Justify and 2-Center; it affects display only when `MultiLine = True`.

6. Events Used for Validation

16 Questions

Q65 | Event | KeyPress

Which event supplies the ASCII code of the pressed key through the `KeyAscii` argument?

A. KeyUp
B. KeyDown
C. KeyPress
D. Change

Ans: C

Explanation: `KeyPress(KeyAscii As Integer)` gives the ASCII value; `KeyDown`/`KeyUp` give `KeyCode`.

Q66 | Event | Cancelling a Key

Setting `KeyAscii = 0` inside the KeyPress event will:

A. move the focus to the next control
B. cancel the keystroke so the character is not entered
C. raise a run-time error
D. clear the entire text box

Ans: B

Explanation: Assigning 0 tells VB to discard the key, so it never reaches the text box.

Q67 | Event | Change

Which event occurs whenever the contents of a text box change?

A. GotFocus
B. LostFocus
C. Change
D. Click

Ans: C

Explanation: `Change` fires after the `Text` property is modified, either by typing or by code.

Q68 | Event | Typing Sequence

When a character is typed in a text box, the events occur in which order?

A. KeyPress, KeyDown, Change, KeyUp
B. KeyDown, KeyPress, Change, KeyUp
C. KeyDown, Change, KeyPress, KeyUp
D. Change, KeyDown, KeyPress, KeyUp

Ans: B

Explanation: The sequence is KeyDown, then KeyPress, then Change (text updated), and finally KeyUp.

Q69 | Event | KeyDown

In the KeyDown event, the argument that identifies the physical key pressed is:

A. KeyCode
B. KeyValue
C. KeyAscii
D. KeyChar

Ans: A

Explanation: `KeyDown(KeyCode As Integer, Shift As Integer)` reports key codes such as `vbKeyF1` or `vbKeyDelete`.

Q70 | Event | GotFocus

Which event is commonly used to select the existing text automatically when the user enters a text box?

A. Change
B. Unload
C. GotFocus
D. LostFocus

Ans: C

Explanation: `GotFocus` occurs when the control receives the focus, so `SelStart`/`SelLength` can be set there.

Q71 | Event | KeyPress Limitation

Which key does NOT trigger the KeyPress event of a text box?

A. The Enter key
B. The Backspace key
C. The letter A
D. The F1 function key

Ans: D

Explanation: `KeyPress` responds only to keys that produce ASCII codes; function and arrow keys need `KeyDown`.

Q72 | Event | Form KeyPreview

To let a form see keystrokes before the control that has focus, which setting is used?

A. Text box's CausesValidation = True
B. Form's AutoRedraw = True
C. Text box's TabStop = True
D. Form's KeyPreview = True

Ans: D

Explanation: With `KeyPreview = True`, the form's `KeyDown`, `KeyPress` and `KeyUp` events occur first.

Q73 | Event | ASCII Enter

In the KeyPress event, the Enter key returns a KeyAscii value of:

A. 32
B. 13
C. 27
D. 10

Ans: B

Explanation: Enter = 13, Esc = 27, Space = 32 and Backspace = 8.

Q74 | Event | ASCII Digits

In KeyPress, the characters "0" to "9" have KeyAscii values from:

A. 65 to 90
B. 97 to 122
C. 32 to 47
D. 48 to 57

Ans: D

Explanation: Digits are 48-57, upper-case letters 65-90 and lower-case letters 97-122.

Q75 | Event | Chr Function

In `KeyPress`, the expression `Chr(KeyAscii)` is used to:

A. convert a character into its ASCII code
B. clear the typed key from the buffer
C. convert the ASCII code into the character typed
D. convert a string into a number

Ans: C

Explanation: `Chr` turns a code into a character; `Asc` does the reverse.

Q76 | Concept | Event-Driven

Validation code is placed in event procedures because VB 6.0 programs are:

A. menu-driven only
B. executed strictly from the first line to the last
C. event-driven
D. free of any objects

Ans: C

Explanation: Code runs in response to user actions (events) such as key presses, focus changes and clicks.

Q77 | Event | LostFocus

Which event occurs when a control loses the focus but, unlike Validate, has no Cancel argument?

A. LostFocus
B. Change
C. KeyPress
D. GotFocus

Ans: A

Explanation: `LostFocus` cannot stop the focus from leaving the control.

Q78 | Event | KeyUp

Which event occurs when a pressed key is released and supplies the KeyCode argument?

A. KeyUp
B. GotFocus
C. Change
D. KeyPress

Ans: A

Explanation: `KeyUp(KeyCode, Shift)` fires when the key is released; `KeyPress` provides `KeyAscii` instead.

Q79 | Event | QueryUnload

A form must refuse to close while some entries are still invalid. Which event allows the closing to be cancelled by setting its Cancel argument?

A. Form_Load
B. QueryUnload
C. Form_Activate
D. Form_Resize

Ans: B

Explanation: In `Form_QueryUnload(Cancel, UnloadMode)`, setting `Cancel` to True stops the form from unloading.

Q80 | Event | Click

Which event of a command button is normally used to run form-level validation when the user confirms the entries?

A. Change
B. KeyPress
C. Validate
D. Click

Ans: D

Explanation: The `Click` procedure of an OK or Submit button runs when the user submits, so all fields can be checked together.

7. Validate Event

14 Questions

Q81 | Validate | Syntax

Which is the correct declaration of the Validate event for a text box named txtAge?

A. Private Sub txtAge_Validate(KeyAscii As Integer)
B. Private Sub txtAge_Validate(Cancel As Boolean)
C. Private Sub txtAge_Validate(Cancel As Integer)
D. Private Sub txtAge_Validate(Shift As Integer)

Ans: B

Explanation: `Validate` has one Boolean argument, `Cancel`; (Cancel As Integer) belongs to events like `QueryUnload`.

Q82 | Validate | Cancel

Setting `Cancel = True` in a Validate event procedure:

A. moves the focus to the next control
B. clears the text of the control
C. unloads the form immediately
D. keeps the focus in the control being validated

Ans: D

Explanation: The focus change is cancelled, so the user must correct the entry before leaving.

Q83 | Validate | CausesValidation Role

A Cancel button is given `CausesValidation = False` so that:

A. the text boxes are cleared automatically
B. the button's Click event is disabled
C. the button is hidden from the user
D. the user can leave the form without being forced to correct invalid data

Ans: D

Explanation: Otherwise `Validate` would fire first and could trap the user in an invalid field.

Q84 | Validate | Event Order

Focus moves from Text1 to Text2 (CausesValidation of Text2 is True). The correct order of events is:

A. Text2_GotFocus, Text1_Validate, Text1_LostFocus
B. Text1_LostFocus, Text1_Validate, Text2_GotFocus
C. Text1_Validate, Text1_LostFocus, Text2_GotFocus
D. Text1_Validate, Text2_GotFocus, Text1_LostFocus

Ans: C

Explanation: `Validate` occurs before `LostFocus`, which in turn occurs before the next control's `GotFocus`.

Q85 | Validate | Behaviour

Study the code.

```
Private Sub txtAge_Validate(Cancel As Boolean)
    If Not IsNumeric(txtAge.Text) Then
        MsgBox "Enter a number"
        Cancel = True
    End If
End Sub
```

The user types "abc" in txtAge and presses Tab to move to another text box. What happens?

A. The message appears and the focus stays in txtAge
B. A run-time error occurs
C. No message appears
D. The message appears and the focus moves to the next box

Ans: A

Explanation: `Cancel = True` stops the focus from leaving the control.

Q86 | Validate | Availability

The Validate event is available for:

A. most controls that can receive focus, such as TextBox and ComboBox
B. the Form object only
C. controls placed on MDI forms only
D. Label and Timer controls only

Ans: A

Explanation: Controls that cannot get focus (e.g. Label, Timer) do not have a `Validate` event.

Q87 | Validate | ValidateControls

Which method of a form forces the Validate event of the control that currently has focus?

A. Refresh
B. ValidateControls
C. SetFocus
D. CheckControls

Ans: B

Explanation: `Form.ValidateControls` triggers the pending `Validate` event, e.g. before saving data on an OK click.

Q88 | Validate | FALSE Statement

Which statement about the Validate event is FALSE?

A. It fires every time a key is pressed in the text box
B. It fires before the LostFocus event
C. It has a Cancel argument
D. It can keep the focus in the control

Ans: A

Explanation: `Validate` fires when the user tries to move focus away, not on each keystroke.

Q89 | Validate | Control Array

For a text box control array, the Validate event procedure also includes the argument:

A. KeyAscii As Integer
B. Index As Integer
C. Shift As Integer
D. Button As Integer

Ans: B

Explanation: It is declared as `txtField_Validate(Index As Integer, Cancel As Boolean)`.

Q90 | Validate | Default Cancel

What is the value of `Cancel` when the Validate event procedure begins?

A. Empty
B. True
C. False
D. Null

Ans: C

Explanation: `Cancel` starts as False; focus leaves unless the code sets it to True.

Q91 | Validate | Event Selection

A programmer wants to check the complete Age value after the user finishes entering it and tries to leave the box. Which event is most appropriate?

A. DblClick
B. Validate
C. Change
D. KeyPress

Ans: B

Explanation: `Validate` receives the finished entry as focus is about to move, and can cancel the move.

Q92 | Validate | Why Introduced

Why is `Validate` generally preferred to `LostFocus` for checking a text box?

A. It fires for every keystroke typed
B. It runs before focus leaves and can cancel the move
C. It runs after the next control has received focus
D. It works only for Label controls

Ans: B

Explanation: `LostFocus` has no `Cancel` argument, so it cannot stop the focus from leaving.

Q93 | Validate | Not Fired

Focus moves from txtA to cmdHelp, and cmdHelp has CausesValidation = False. Which statement is correct?

A. txtA_LostFocus runs, but txtA_Validate does not
B. Neither event runs
C. txtA_Validate runs, but txtA_LostFocus does not
D. Both txtA_Validate and txtA_LostFocus run

Ans: A

Explanation: The Validate event fires only if the control receiving the focus has `CausesValidation = True`.

Q94 | Validate | Comparison

Which statement is correct about Validate and LostFocus?

A. LostFocus occurs first and has a Cancel argument; Validate occurs later and has none
B. Validate occurs first and has a Cancel argument; LostFocus occurs later and has none
C. Neither occurs when the user presses the Tab key
D. Both have a Cancel argument and occur together

Ans: B

Explanation: Validate can stop the focus change; LostFocus is only a notification that the focus has already gone.

8. Code-Based and Scenario-Based Questions 15 Questions

Q95 | Code | Letters Only

Study the code.

```
Private Sub txtName_KeyPress(KeyAscii As Integer)
    If Not ((KeyAscii >= 65 And KeyAscii <= 90) Or _
            (KeyAscii >= 97 And KeyAscii <= 122) Or _
            KeyAscii = 32 Or KeyAscii = 8) Then
        KeyAscii = 0
    End If
End Sub
```

Which character can the user still type into txtName?

A. The symbol @
B. The symbol #
C. The letter m
D. The digit 5

Ans: C

Explanation: Letters (65-90, 97-122), Space (32) and Backspace (8) are allowed; digits and symbols are cancelled.

Q96 | Code | Backspace Trap

Study the code.

```
Private Sub txtQty_KeyPress(KeyAscii As Integer)
    If KeyAscii < 48 Or KeyAscii > 57 Then KeyAscii = 0
End Sub
```

Which statement about this procedure is correct?

A. It blocks every non-digit key, including Backspace
B. It allows only alphabetic characters
C. It allows digits and the Backspace key only
D. It converts digits into letters

Ans: A

Explanation: Backspace has ASCII code 8, outside 48-57, so it is cancelled too; add `And KeyAscii <> 8` to permit it.

Q97 | Output | Trim and Len

Study the code.

```
Dim s As String
s = "   "
If Len(Trim(s)) = 0 Then
    MsgBox "Empty"
Else
    MsgBox "Filled"
End If
```

What is displayed?

A. Filled
B. A run-time error
C. Nothing is displayed
D. Empty

Ans: D

Explanation: `Trim` removes the spaces, leaving a string of length 0.

Q98 | Code | Boundary Value

Study the code.

```
Dim age As Integer
age = Val(txtAge.Text)
If age < 18 Or age > 60 Then
    MsgBox "Invalid age"
Else
    MsgBox "Valid age"
End If
```

If txtAge contains 60, which message is displayed?

A. An Overflow error
B. Invalid age
C. No message
D. Valid age

Ans: D

Explanation: 60 is not less than 18 and not greater than 60, so the Else part runs.

Q99 | Code | Upper Case

What is the effect of this statement in a text box's KeyPress event?

```
KeyAscii = Asc(UCase(Chr(KeyAscii)))
```

A. Every typed letter is converted to upper case
B. Lower-case letters are rejected
C. Letters are converted into digits
D. The text box is cleared

Ans: A

Explanation: `Chr` gives the character, `UCase` capitalises it, and `Asc` converts it back to a code.

Q100 | Error-ID | Wrong Cancel

Study the code.

```
Private Sub txtName_Validate(Cancel As Boolean)
    If txtName.Text = "" Then
        MsgBox "Name required"
        Cancel = False
    End If
End Sub
```

Why does the focus still leave txtName when it is blank?

A. MsgBox cannot be used inside Validate
B. Cancel is set to False instead of True
C. Validate has no Cancel argument
D. A text box cannot be compared with ""

Ans: B

Explanation: The focus change is stopped only when `Cancel = True`.

Q101 | Scenario | Mobile Number

A Mobile box must accept at most 10 characters and only digits. Which combination is best?

A. MaxLength = 10 and a digit filter in KeyPress
B. Locked = True and code in Validate
C. MultiLine = True and code in Form_Resize
D. PasswordChar = "#" and code in Change

Ans: A

Explanation: `MaxLength` limits the length and `KeyPress` rejects non-digit characters.

Q102 | Code | InStr Check

What does this statement test?

```
If InStr(txtEmail.Text, "@") = 0 Then MsgBox "Invalid e-mail"
```

A. Whether the box is empty
B. Whether the text begins with "@"
C. Whether the text ends with "@"
D. Whether the "@" symbol is absent from the text

Ans: D

Explanation: `InStr` returns 0 when the searched character is not found, so the message appears for a missing "@".

Q103 | Output | Val Function

What is printed by the following statement?

```
Print Val("25kg") + Val("abc")
```

A. 25
B. Type mismatch error
C. 25kg
D. 0

Ans: A

Explanation: `Val` reads leading numeric characters: "25kg" gives 25 and "abc" gives 0.

Q104 | Error-ID | Invalid Age Condition

Which condition correctly detects an INVALID age outside the range 18 to 60?

A. age > 18 And age < 60
B. age < 18 And age > 60
C. age < 18 Or age > 60
D. age <= 18 Or age >= 60

Ans: C

Explanation: A value outside the range is below the lower limit OR above the upper limit; `And` can never be true here.

Q105 | Code | InputBox Cancel

Study the code.

```
Dim n As String
n = InputBox("Enter name")
If Len(n) = 0 Then MsgBox "No input"
```

The user clicks the Cancel button of the input box. What happens?

A. Nothing is displayed
B. n receives the text "Cancel"
C. "No input" is displayed
D. The program stops with a run-time error

Ans: C

Explanation: `InputBox` returns a zero-length string when Cancel is clicked, so `Len(n)` is 0.

Q106 | Code | MsgBox Return

Study the code.

```
If MsgBox("Save changes?", vbYesNo) = vbNo Then Exit Sub
MsgBox "Saved"
```

The user clicks the No button. What happens?

A. The procedure ends without displaying "Saved"
B. A run-time error occurs
C. "Saved" is displayed
D. The message box is shown again

Ans: A

Explanation: `MsgBox` returns `vbNo` (7), so `Exit Sub` runs before the second statement.

Q107 | Code | Like Format Check

Study the code.

```
If Not (txtCode.Text Like "[A-Z]##") Then MsgBox "Invalid code"
```

txtCode contains B25. What is the result?

A. "Invalid code" is displayed
B. No message is displayed
C. A syntax error occurs
D. A Type mismatch error occurs

Ans: B

Explanation: "B25" is one letter followed by two digits, so the pattern matches and the Like test is True.

Q108 | Code | Selecting Wrong Text

Study the code.

```
Private Sub txtAge_Validate(Cancel As Boolean)
    If Val(txtAge.Text) < 1 Or Val(txtAge.Text) > 100 Then
        MsgBox "Age must be 1 to 100"
        txtAge.SelStart = 0
        txtAge.SelLength = Len(txtAge.Text)
        Cancel = True
    End If
End Sub
```

What is the purpose of the SelStart and SelLength statements?

A. They delete the wrong entry from memory

B. They highlight the wrong entry so that the user can overwrite it directly

C. They cancel the Validate event

D. They increase the MaxLength of the box

Ans: B

Explanation: Selecting the entire text lets the user simply type the corrected value over it.

Q109 | Scenario | Calculated Field

A Total box must show a calculated value that the user can select and copy but cannot edit. Which setting is most suitable?

A. MaxLength = 1

B. Enabled = False

C. Visible = False

D. Locked = True

Ans: D

Explanation: A locked text box keeps its normal appearance and can be selected, but its contents cannot be edited.

9. Important and Tricky Questions

12 Questions

Q110 | Tricky | LostFocus Problem

Why is validating with `SetFocus` inside `LostFocus` considered unreliable?

- **A.** Focus has already started moving, which can cause focus loops between invalid controls
- **B.** SetFocus is not permitted inside any event
- **C.** LostFocus cannot display a message box
- **D.** LostFocus exists only for Label controls

Ans: A

Explanation: The focus change cannot be cancelled in `LostFocus`; `Validate` was provided to solve this.

Q111 | Tricky | IsNumeric

Which call returns False?

- **A.** IsNumeric("45")
- **B.** IsNumeric("1E3")
- **C.** IsNumeric("")
- **D.** IsNumeric("3.14")

Ans: C

Explanation: An empty string is not numeric, whereas "1E3" is a valid number in scientific notation.

Q112 | Tricky | CausesValidation Target

Focus moves from Text1 to Command1. Whose CausesValidation setting decides whether Text1's Validate event fires?

- **A.** Text1 (the control losing focus)
- **B.** Command1 (the control receiving focus)
- **C.** Both controls must be False
- **D.** The form

Ans: B

Explanation: `Validate` fires only if the control that is about to receive focus has `CausesValidation = True`.

Q113 | Tricky | Val with Comma

What is displayed by `Print Val("1,234")`?

- **A.** 1234
- **B.** 1
- **C.** Type mismatch error
- **D.** 1.234

Ans: B

Explanation: `Val` stops reading at the first character it cannot recognise as part of a number, here the comma.

Q114 | Tricky | Code Assignment

The statement `Text1.Text = "A"` in code triggers which event of the text box?

A. KeyPress
B. Validate
C. KeyDown
D. Change

Ans: D

Explanation: Key events are raised only by the keyboard; assigning text from code raises `Change`.

Q115 | Tricky | Trim Before Len

Why is `Trim` used before `Len` when checking a required text box?

A. To convert the text into a number
B. To change the text to upper case
C. To increase the MaxLength of the box
D. So that a box containing only spaces is treated as empty

Ans: D

Explanation: `Len(" ")` is 3, but `Len(Trim(" "))` is 0.

Q116 | Tricky | String Comparison

Study the code.

```
If txtAge.Text < "18" Then MsgBox "Under age"
```

The user enters 9. Why is "Under age" NOT displayed?

A. The Text property cannot be used with the < operator
B. The two strings are compared character by character, so "9" is greater than "18"
C. IsNumeric returns False for the single digit 9
D. MsgBox fails for single-digit ages

Ans: B

Explanation: Text must be converted (e.g. `Val(txtAge.Text) < 18`) for a numeric comparison.

Q117 | Tricky | PasswordChar and Text

PasswordChar of txtPwd is "*" and the user types abc. What does `txtPwd.Text` return?

A. *
B. ***
C. An empty string
D. abc

Ans: D

Explanation: `PasswordChar` changes only what is displayed; the `Text` property keeps the real characters.

Q118 | Tricky | Type Mismatch

txtAge is blank. Which expression raises a Type mismatch run-time error?

A. Val(txtAge.Text)
B. CInt(txtAge.Text)
C. IsNumeric(txtAge.Text)
D. Len(txtAge.Text)

Ans: B

Explanation: `CInt("")` fails with Error 13, whereas `Val("")` safely returns 0.

Q119 | Tricky | IsNull

What does `IsNull("")` return?

A. A Type mismatch error
B. Null
C. False
D. True

Ans: C

Explanation: An empty string is a valid string value of length 0; it is not Null.

Q120 | Tricky | Locked vs Enabled

Which type of text box lets the user select and copy its text but not edit it?

A. One with Enabled = False
B. One with Visible = False
C. One with Locked = True
D. One with TabStop = False

Ans: C

Explanation: A disabled control cannot receive focus, whereas a locked one can; locking blocks only editing.

Q121 | Tricky | ScrollBars

A single-line text box (MultiLine = False) has ScrollBars set to 2-Vertical. What happens?

A. MultiLine changes to True automatically
B. A vertical scroll bar appears
C. A run-time error occurs
D. No scroll bar appears

Ans: D

Explanation: Scroll bars are displayed only when `MultiLine = True`.

10. Mixed OAVS TGT Practice Set

14 Questions

Q122 | Match | Properties

Match Column I with Column II.
Column I: 1. MaxLength 2. PasswordChar 3. Locked 4. CausesValidation
Column II: P. Prevents the user from editing the text
Q. Decides whether the previous control's Validate fires
R. Masks the typed characters with a symbol
S. Limits the number of characters typed

A. 1-P, 2-R, 3-S, 4-Q
B. 1-S, 2-Q, 3-P, 4-R
C. 1-R, 2-S, 3-Q, 4-P
D. 1-S, 2-R, 3-P, 4-Q

Ans: D

Explanation: MaxLength limits characters (S), PasswordChar masks them (R), Locked prevents editing (P), CausesValidation controls Validate (Q).

Q123 | Match | Events

Match Column I with Column II.
Column I: 1. KeyPress 2. KeyDown 3. Validate 4. Change
Column II: P. Has a Cancel argument
Q. Fires whenever the text content changes
R. Supplies KeyAscii
S. Supplies KeyCode and Shift

A. 1-R, 2-S, 3-P, 4-Q
B. 1-S, 2-R, 3-P, 4-Q
C. 1-R, 2-S, 3-Q, 4-P
D. 1-P, 2-S, 3-R, 4-Q

Ans: A

Explanation: KeyPress gives KeyAscii (R), KeyDown gives KeyCode and Shift (S), Validate has Cancel (P), Change fires on text change (Q).

Q124 | Assertion-Reason | Validate Event

Assertion (A): The Validate event can stop a user from leaving a text box that contains invalid data.
Reason (R): Setting Cancel = True inside the Validate event keeps the focus in that control.

A. Both A and R are true and R is the correct explanation of A
B. Both A and R are true but R is not the correct explanation of A
C. A is true but R is false
D. A is false but R is true

Ans: A

Explanation: Because `Cancel = True` cancels the focus change, the user cannot leave until the entry is corrected.

Q125 | Assertion-Reason | KeyPress

Assertion (A): The KeyPress event can be used to block unwanted characters.
Reason (R): The KeyPress event occurs after the character has already been added to the Text property.

A. Both A and R are true and R is the correct explanation of A
B. Both A and R are true but R is not the correct explanation of A
C. A is true but R is false
D. A is false but R is true

Ans: C

Explanation: `KeyPress` occurs before the character appears, which is why `KeyAscii = 0` can cancel it.

Q126 | Assertion-Reason | MaxLength

Assertion (A): Setting MaxLength = 0 stops the user from typing anything.
Reason (R): MaxLength = 0 means that no limit is set by the programmer.

A. Both A and R are true and R is the correct explanation of A
B. Both A and R are true but R is not the correct explanation of A
C. A is true but R is false
D. A is false but R is true

Ans: D

Explanation: `MaxLength = 0` removes the programmer-set limit, so typing is allowed up to the control's capacity.

Q127 | Assertion-Reason | Field and Form Level

Assertion (A): Field-level validation gives immediate feedback to the user.
Reason (R): Form-level validation is usually triggered by the OK or Submit button.

A. Both A and R are true and R is the correct explanation of A
B. Both A and R are true but R is not the correct explanation of A
C. A is true but R is false
D. A is false but R is true

Ans: B

Explanation: Both statements are correct, but the Reason describes form-level validation, which does not explain field-level feedback.

Q128 | Statement | Text Box Facts

Consider the statements:
1. SelLength gives the number of characters currently selected.
2. TabIndex decides the order in which controls receive focus on pressing Tab.
3. A Label control can receive focus through the Tab key.
Which statements are correct?

A. 1 only
B. 1 and 2 only
C. 2 and 3 only
D. 1, 2 and 3

Ans: B

Explanation: A Label cannot receive focus, so statement 3 is false.

Q129 | Statement | Functions

Consider the statements:
1. Trim removes leading and trailing spaces from a string.
2. Len(Text1.Text) is 0 for an empty text box.
3. Val("abc") returns 0.
Which statements are correct?

A. 1 and 2 only
B. 1 and 3 only
C. 2 and 3 only
D. 1, 2 and 3

Ans: D

Explanation: All three statements describe standard VB 6.0 behaviour.

Q130 | Scenario | Skipped Fields

A user may reach the OK button without visiting some mandatory text boxes. Which validation guarantees that none of them is empty before the data is processed?

A. Setting PasswordChar for every text box
B. A form-level check in the OK button's Click event
C. A Validate event written only for the first text box
D. Setting MaxLength for every text box

Ans: B

Explanation: Field-level events do not run for boxes the user never visits, so a final form-level check is required.

Q131 | Concept | SelLength

In a text box, `SelLength = 0` means:

A. MaxLength has been set to 0
B. no text is currently selected
C. all the text is selected
D. the text box is empty

Ans: B

Explanation: `SelLength` returns the number of selected characters; 0 means there is no selection.

Q132 | Concept | MsgBox Icon

Which constant displays the exclamation (warning) icon in a MsgBox used to report invalid input?

A. vbInformation
B. vbCritical
C. vbExclamation
D. vbQuestion

Ans: C

Explanation: `MsgBox "Invalid entry", vbExclamation` shows the yellow warning triangle.

Q133 | Match | Properties and Methods

Match Column I with Column II.
Column I: 1. SetFocus 2. SelText 3. Tag 4. ScrollBars
Column II: P. Moves the cursor into a control
Q. Holds or replaces the selected text
R. Stores extra programmer-defined information
S. Requires MultiLine = True to be effective

A. 1-Q, 2-P, 3-R, 4-S
B. 1-P, 2-R, 3-Q, 4-S
C. 1-P, 2-Q, 3-S, 4-R
D. 1-P, 2-Q, 3-R, 4-S

Ans: D

Explanation: SetFocus moves focus (P), SelText holds selected text (Q), Tag stores custom data (R), ScrollBars needs MultiLine (S).

Q134 | Assertion-Reason | CausesValidation

Assertion (A): Clicking a Cancel button may not trigger the Validate event of the text box that was being edited.
Reason (R): A control whose CausesValidation property is False does not trigger the Validate event of the control losing focus.

A. Both A and R are true and R is the correct explanation of A
B. Both A and R are true but R is not the correct explanation of A
C. A is true but R is false
D. A is false but R is true

Ans: A

Explanation: Giving the Cancel button `CausesValidation = False` lets the user leave an invalid field without being trapped.

Q135 | Statement | Enabled and Locked

Consider the statements:
1. A text box with Locked = True can still receive the focus.
2. A text box with Enabled = False cannot receive the focus.
3. The Tag property of a text box is shown to the user at run time.
Which statements are correct?

A. 1 only
B. 1 and 2 only
C. 2 and 3 only
D. 1, 2 and 3

Ans: B

Explanation: The Tag property is for programmer use and is not displayed, so statement 3 is wrong.

Quick Answer Key

135 Questions

1-B	2-D	3-D	4-C	5-D	6-A	7-C	8-D	9-A	10-D
11-C	12-B	13-C	14-C	15-D	16-D	17-A	18-D	19-A	20-B
21-B	22-A	23-C	24-D	25-B	26-C	27-C	28-A	29-B	30-B
31-D	32-A	33-A	34-B	35-C	36-A	37-C	38-A	39-C	40-C
41-D	42-C	43-C	44-A	45-A	46-C	47-A	48-B	49-C	50-C
51-D	52-B	53-C	54-A	55-A	56-D	57-A	58-C	59-A	60-A
61-D	62-D	63-B	64-B	65-C	66-B	67-C	68-B	69-A	70-C
71-D	72-D	73-B	74-D	75-C	76-C	77-A	78-A	79-B	80-D
81-B	82-D	83-D	84-C	85-A	86-A	87-B	88-A	89-B	90-C
91-B	92-B	93-A	94-B	95-C	96-A	97-D	98-D	99-A	100-B
101-A	102-D	103-A	104-C	105-C	106-A	107-B	108-B	109-D	110-A
111-C	112-B	113-B	114-D	115-D	116-B	117-D	118-B	119-C	120-C
121-D	122-D	123-A	124-A	125-C	126-D	127-B	128-B	129-D	130-B
131-B	132-C	133-D	134-A	135-B					