OAVS TGT COMPUTER TEACHER EXAMINATION

Database Connectivity

Visual Basic 6.0 | MCQ Question Bank

209 exam-focused questions with answers and short explanations

Syllabus covered

Topic	Covered in this bank
How VB accesses data	Data access interface; Relational database concepts
Introduction to OLE DB and ADO	What is OLE DB; How OLE DB relates to ADO; SQL statements
ADO Data Control	Using ADO; Connecting to a data source; Binding controls (DataCombo, DataList, DataGrid)
Coding ADO	Creating a recordset; Adding records; Modify, Delete, Search
Data Environment	Data Environment designer, Connection and Command objects
Introduction to Crystal Report (7.0 or above)	Report basics, sections and report control

Contents

No.	Section	Questions	Count
1	How VB Accesses Data	Q1 - Q10	10
2	Data Access Interface and Relational Database Concepts	Q11 - Q29	19
3	OLE DB and ADO	Q30 - Q40	11
4	SQL Statements	Q41 - Q62	22
5	ADO Data Control and Data-Source Connections	Q63 - Q84	22
6	DataCombo, DataList and DataGrid	Q85 - Q103	19
7	Coding ADO and Recordset Operations	Q104 - Q139	36
8	Data Environment	Q140 - Q157	18
9	Crystal Reports 7.0 or Above	Q158 - Q176	19
10	Important and Tricky Questions	Q177 - Q196	20
11	Mixed OAVS TGT Practice Set	Q197 - Q209	13
	Total		**209**

How to use: attempt each question first, then check the highlighted answer strip and the explanation. Answer positions (A to D) are randomly spread across the whole bank. A full answer key is given on the last page.

SECTION 1 HOW VB ACCESSES DATA

Q1 - Q10 | 10 questions

Q1 | Concept | Database Connectivity

Which data access technology of Visual Basic 6.0 is built on OLE DB and is recommended for new database applications?

A. DAO (Data Access Objects)
B. RDO (Remote Data Objects)
C. Jet Database Engine API
D. ADO (ActiveX Data Objects)

Ans: D

Explanation: ADO is the newest model in VB 6.0. It sits on OLE DB and reaches relational as well as non-relational data.

Q2 | Concept | Database Connectivity

Which sequence shows the order in which VB data access models were introduced?

A. DAO, ADO, RDO
B. DAO, RDO, ADO
C. ADO, RDO, DAO
D. RDO, DAO, ADO

Ans: B

Explanation: DAO (Jet) came first, RDO (ODBC) followed for client/server work, and ADO (OLE DB) is the latest.

Q3 | Concept | Database Connectivity

DAO is mainly designed for accessing which kind of data?

A. E-mail and file-system data only
B. Crystal Report (.rpt) files only
C. Local Jet (Microsoft Access .mdb) databases
D. Remote ODBC server databases only

Ans: C

Explanation: DAO works through the Jet engine and suits Access databases. RDO targets remote ODBC sources.

Q4 | Concept | Database Connectivity

RDO (Remote Data Objects) was introduced mainly to access:

A. Only Microsoft Access files through the Jet engine
B. Only XML documents transferred over HTTP
C. Only text and spreadsheet files on a local disk
D. Client/server databases such as SQL Server and Oracle through ODBC

Ans: D

Explanation: RDO is a thin object layer over the ODBC API for client/server databases.

Q5 | Concept | Database Connectivity

The intrinsic Data control that sits in the standard VB toolbox talks to databases through:

A. The Crystal Reports engine
B. The Jet database engine (DAO-based)
C. OLE DB service components (ADO-based)
D. The Data Environment run-time

Ans: B

Explanation: The old intrinsic Data control is DAO-based. The ADO Data control has to be added separately as a component.

Q6 | Concept | Database Connectivity

A control such as TextBox or DataGrid that shows or edits a database field through a data control is called a:

A. Data provider
B. Data-bound control
C. Data service
D. Data environment

Ans: B

Explanation: Bound controls connect to a data source using properties such as DataSource and DataField.

Q7 | Concept | Database Connectivity

In the OLE DB model, which component exposes data from a source in a uniform way?

A. Data consumer
B. Data provider (OLE DB provider)
C. Recordset
D. Bound control

Ans: B

Explanation: A provider exposes data through OLE DB interfaces. A consumer, such as ADO, uses those interfaces.

Q8 | Concept | Database Connectivity

Microsoft's Universal Data Access (UDA) strategy aims to:

A. Give uniform access to relational and non-relational data without converting it to one format
B. Restrict applications to Microsoft SQL Server only
C. Convert all data into Microsoft Access tables before use
D. Replace SQL with a purely visual query language

Ans: A

Explanation: UDA (ADO + OLE DB + ODBC) gives a common access layer to many kinds of data.

Q9 | Concept | Database Connectivity

What is the topmost object in the DAO object hierarchy?

A. DBEngine
B. Recordset
C. Workspace
D. Database

Ans: A

Explanation: The DAO hierarchy runs DBEngine, Workspace, Database, then Recordset and TableDef.

Q10 | Concept | Database Connectivity

What is the purpose of a data access interface between a VB application and a database?

A. To design the forms and menus of the application
B. To give the application a common way to connect to, read and update data without knowing how it is stored
C. To store the VB project files inside the database
D. To compile the VB code into native machine code

Ans: B

Explanation: A data access interface hides the storage details and exposes standard objects and methods to the program.

SECTION 2 DATA ACCESS INTERFACE AND RELATIONAL DATABASE CONCEPTS

Q11 - Q29 | 19 questions

Q11 | Concept | Database Connectivity

Which of the following is NOT a data access interface or model?

A. ODBC
B. OLE DB
C. DAO
D. Crystal Reports

Ans: D

Explanation: Crystal Reports is a reporting tool. ODBC, OLE DB and DAO are data access interfaces.

Q12 | Concept | Database Connectivity

ODBC stands for:

A. Object Database Connector
B. Open Database Connectivity
C. Open Data Broker Channel
D. Online Data Binding Component

Ans: B

Explanation: ODBC is a standard API for accessing relational DBMSs using SQL.

Q13 | Concept | Database Connectivity

Which interface can directly access non-relational sources such as e-mail stores and file systems?

A. ODBC
B. RDO
C. OLE DB
D. DAO

Ans: C

Explanation: ODBC is SQL/relational oriented, while OLE DB defines interfaces for any kind of data.

Q14 | Concept | Database Connectivity

In a relational database, data is organised into:

A. Hierarchical parent-child trees
B. Objects with inheritance
C. Tables made of rows and columns
D. Networks of linked records

Ans: C

Explanation: The relational model stores data as tables (relations).

Q15 | Concept | Database Connectivity

In relational terminology, a row of a table is called a:

A. Field (attribute)
B. Domain
C. Relation
D. Record (tuple)

Ans: D

Explanation: A row is a record/tuple, a column is a field/attribute, and the table is the relation.

Q16 | Concept | Database Connectivity

Which key uniquely identifies every record of a table and cannot contain NULL?

A. Secondary key
B. Primary key
C. Foreign key
D. Index key

Ans: B

Explanation: A primary key must be unique and not null for each record.

Q17 | Concept | Database Connectivity

A field in one table that refers to the primary key of another table is called a:

A. Foreign key
B. Candidate key
C. Primary key
D. Composite key

Ans: A

Explanation: Foreign keys create the link between related tables.

Q18 | Scenario | Database Connectivity

One class contains many students, but each student belongs to exactly one class. The relationship between Class and Student is:

A. One-to-one
B. Self-referencing
C. One-to-many
D. Many-to-many

Ans: C

Explanation: One Class record is related to many Student records.

Q19 | Concept | Database Connectivity

Referential integrity guarantees that:

A. Every column in a table contains only unique values
B. Every table has an index on each of its columns
C. All records are stored in sorted order of the primary key
D. Every foreign key value matches an existing primary key value in the related table

Ans: D

Explanation: It prevents orphan records, for example a student whose class does not exist.

Q20 | Concept | Database Connectivity

A many-to-many relationship between two tables is normally implemented using:

A. A calculated field stored in either table
B. A single shared primary key column in one table
C. Two separate primary keys in one table
D. A third (junction) table holding the keys of both tables

Ans: D

Explanation: A link table with two foreign keys breaks many-to-many into two one-to-many relationships.

Q21 | Concept | Database Connectivity

A NULL value in a field means:

A. The value is zero
B. The value is unknown or missing
C. The value is an empty string
D. The field has been deleted

Ans: B

Explanation: NULL is different from 0 or an empty string.

Q22 | Concept | Database Connectivity

A column or set of columns that could be chosen as the primary key of a table is called a:

A. Candidate key
B. Foreign key
C. Alternate index
D. Composite field

Ans: A

Explanation: All minimal attribute sets that identify rows uniquely are candidate keys. One of them becomes the primary key.

Q23 | Concept | Database Connectivity

In relational terminology, the number of columns in a table is its:

A. Cardinality
B. Degree
C. Schema
D. Domain

Ans: B

Explanation: Degree = number of columns (attributes). Cardinality = number of rows (tuples).

Q24 | Concept | Database Connectivity

What mainly distinguishes an RDBMS from a basic DBMS?

A. It stores data only in text files
B. Data can be accessed only through VB
C. It cannot be queried using SQL
D. Data is stored in related tables, and relationships are maintained through keys

Ans: D

Explanation: An RDBMS organises data as related tables linked by primary and foreign keys.

Q25 | Concept | Database Connectivity

In the ODBC architecture, which component loads the correct driver and passes the application's calls to it?

A. Data Source Name (DSN)
B. Recordset
C. Driver Manager
D. Jet Engine

Ans: C

Explanation: Application, ODBC Driver Manager, ODBC driver, then data source.

Q26 | SQL | Database Connectivity

CREATE TABLE and ALTER TABLE are examples of which type of SQL statement?

A. DDL (Data Definition Language)
B. DML (Data Manipulation Language)
C. DCL (Data Control Language)
D. TCL (Transaction Control Language)

Ans: A

Explanation: DDL defines or changes structure. DML works on the data inside the tables.

Q27 | SQL | Database Connectivity

Which join returns only the rows that have matching values in both tables?

A. CROSS JOIN
B. INNER JOIN
C. RIGHT JOIN
D. LEFT JOIN

Ans: B

Explanation: LEFT and RIGHT joins also keep unmatched rows of one table. CROSS JOIN pairs every row with every row.

Q28 | Concept | Database Connectivity

Which property of the intrinsic (DAO) Data control gives the name and path of the database file?

A. ConnectionString
B. RecordSource
C. Connect
D. DatabaseName

Ans: D

Explanation: ConnectionString is the ADO Data Control's equivalent. RecordSource names the table or query.

Q29 | Concept | Database Connectivity

Which property of the intrinsic Data control chooses between table, dynaset or snapshot Recordsets?

A. RecordSource
B. DefaultType
C. CursorType
D. RecordsetType

Ans: D

Explanation: RecordsetType values: 0 Table, 1 Dynaset (default), 2 Snapshot.

SECTION 3 OLE DB AND ADO

Q30 - Q40 | 11 questions

Quick view: ADO data access path



The application calls ADO objects (Connection, Command, Recordset). ADO passes the request to the OLE DB provider, which reads or writes the data source.

Q30 | Concept | Database Connectivity

Which technology provides a standard interface for accessing data from different data sources?

A. DataGrid
B. Form Designer
C. Crystal Reports
D. OLE DB

Ans: D

Explanation: OLE DB provides interfaces for accessing data from different types of data sources.

Q31 | Concept | Database Connectivity

OLE DB stands for:

A. Object Library for Enterprise Databases
B. Object Level Embedded DataBase
C. Open Linking and Exchange Database
D. Object Linking and Embedding Database

Ans: D

Explanation: OLE DB is Microsoft's COM-based data access technology.

Q32 | Concept | Database Connectivity

OLE DB is based on which Microsoft technology?

A. CORBA
B. COM (Component Object Model)
C. JDBC
D. DDE (Dynamic Data Exchange)

Ans: B

Explanation: OLE DB is a set of COM interfaces implemented by data providers and used by consumers.

Q33 | Concept | Database Connectivity

What is the relationship between ADO and OLE DB?

A. ADO replaces OLE DB providers with ODBC drivers
B. OLE DB is a high-level wrapper built on top of ADO
C. ADO is a high-level object interface that uses OLE DB providers underneath
D. ADO and OLE DB are the same thing with different names

Ans: C

Explanation: ADO gives VB programmers an easy object model, while OLE DB does the low-level work.

Q34 | Concept | Database Connectivity

Which of the following is NOT an ADO object?

A. Command
B. Recordset
C. Connection
D. Workspace

Ans: D

Explanation: Workspace belongs to the DAO hierarchy (DBEngine - Workspace - Database).

Q35 | Concept | Database Connectivity

Which ADO object is typically used to run a parameterised query or stored command?

A. Command
B. Property
C. Error
D. Field

Ans: A

Explanation: The Command object holds the command text and its Parameters collection.

Q36 | Concept | Database Connectivity

Which provider name is used by ADO for an Access .mdb database through Jet 4.0?

A. SQLOLEDB
B. MSDASQL
C. MSDAORA
D. Microsoft.Jet.OLEDB.4.0

Ans: D

Explanation: SQLOLEDB is for SQL Server, MSDAORA for Oracle and MSDASQL for ODBC drivers.

Q37 | Concept | Database Connectivity

Which OLE DB provider lets ADO use an existing ODBC driver?

A. MSDAORA
B. Microsoft.Jet.OLEDB.4.0
C. SQLOLEDB
D. MSDASQL

Ans: D

Explanation: MSDASQL is the OLE DB Provider for ODBC drivers.

Q38 | Concept | Database Connectivity

What is the main advantage of ADO over DAO and RDO?

A. Support only for Jet databases and ODBC drivers
B. A deeper hierarchy that must always be created from the top
C. A simple, flat object model that reaches many data sources through OLE DB
D. Mandatory use of the Data control for every operation

Ans: C

Explanation: ADO objects such as Recordset can be created independently, and ADO works with many sources.

Q39 | Concept | Database Connectivity

To write ADO code in VB 6.0, which reference is added through Project > References?

A. Microsoft ActiveX Data Objects 2.x Library
B. Microsoft Remote Data Object 2.0
C. Microsoft DAO 3.6 Object Library
D. Microsoft DataGrid Control 6.0 (OLEDB)

Ans: A

Explanation: This library provides the ADODB.Connection, ADODB.Recordset and ADODB.Command classes.

Q40 | Concept | Database Connectivity

Which flow correctly shows the ADO data access path?

A. ADO -> VB application -> data source -> OLE DB provider
B. VB application -> OLE DB provider -> ADO -> data source
C. VB application -> data source -> ADO -> OLE DB provider
D. VB application -> ADO -> OLE DB provider -> data source

Ans: D

Explanation: The application calls ADO, ADO calls the OLE DB provider, and the provider talks to the data source.

SECTION 4 SQL STATEMENTS

Q41 - Q62 | 22 questions

Q41 | Concept | Database Connectivity

Which of the following SQL commands is a DML (data manipulation) command?

A. ALTER
B. DROP
C. CREATE
D. INSERT

Ans: D

Explanation: INSERT, UPDATE, DELETE and SELECT work on data. CREATE, ALTER and DROP are DDL.

Q42 | SQL | Database Connectivity

Which statement correctly adds a new row to the Student table?

A. `INSERT INTO Student (RollNo, Name) VALUES (1, 'Asha')`
B. `ADD INTO Student (RollNo, Name) VALUES (1, 'Asha')`
C. `INSERT INTO Student SET RollNo = 1, Name = 'Asha'`
D. `INSERT Student (RollNo, Name) INTO VALUES (1, 'Asha')`

Ans: A

Explanation: The standard form is INSERT INTO table (columns) VALUES (values).

Q43 | SQL | Database Connectivity

What is the effect of the following statement?

```
UPDATE Student SET Marks = 0
```

A. Only the first record of the table is changed
B. Nothing changes, because UPDATE requires a WHERE clause
C. Only the current record of the Recordset is changed
D. Marks of ALL students become 0 because there is no WHERE clause

Ans: D

Explanation: Without WHERE, UPDATE modifies every row of the table.

Q44 | SQL | Database Connectivity

Which statement removes all rows of the Student table but keeps the table structure?

A. `DELETE FROM Student`
B. `DROP TABLE Student`
C. `DELETE TABLE Student`
D. `ALTER TABLE Student DROP ALL`

Ans: A

Explanation: DELETE removes rows. DROP TABLE removes the table itself.

Q45 | SQL | Database Connectivity

Which condition selects names that begin with the letter A?

A. `WHERE Name = 'A%'`
B. `WHERE Name STARTS 'A'`
C. `WHERE Name LIKE 'A%'`
D. `WHERE Name CONTAINS 'A'`

Ans: C

Explanation: LIKE with the % wildcard performs pattern matching.

Q46 | SQL | Database Connectivity

SELECT COUNT(*) FROM Student returns:

A. The sum of all numeric columns
B. All rows of the Student table
C. A single value: the number of rows in Student
D. The first row of the Student table

Ans: C

Explanation: COUNT is an aggregate function that returns the row count.

Q47 | SQL | Database Connectivity

Which clause combines rows from two tables using a related column?

A. ORDER BY
B. INNER JOIN ... ON
C. HAVING
D. GROUP BY

Ans: B

Explanation: A join links tables, typically on primary key = foreign key.

Q48 | SQL | Database Connectivity

What does this query return?

```
SELECT Dept, COUNT(*) FROM Emp GROUP BY Dept
```

A. The number of employees in each department
B. All employees sorted by department
C. The total number of employees only
D. Departments that have no employees

Ans: A

Explanation: GROUP BY forms one group per Dept and COUNT(*) counts rows in each group.

Q49 | SQL | Database Connectivity

Which clause filters groups after GROUP BY has been applied?

A. HAVING
B. WHERE
C. DISTINCT
D. ORDER BY

Ans: A

Explanation: WHERE filters rows before grouping. HAVING filters the groups.

Q50 | Code | Database Connectivity

A text box txtName holds a student name. Which VB string builds a correct SQL query for it?

A. `"SELECT * FROM Student WHERE Name = " & "'txtName.Text'"`
B. `"SELECT * FROM Student WHERE Name = " & txtName.Text`
C. `"SELECT * FROM Student WHERE Name = '" & txtName.Text & "'"`
D. `"SELECT * FROM Student WHERE Name = ' & txtName.Text & '"`

Ans: C

Explanation: Text values must be enclosed in single quotes, and the text box value must be concatenated outside the string.

Q51 | SQL | Database Connectivity

WHERE Marks BETWEEN 40 AND 60 selects:

A. Marks from 40 to 60, both values included
B. Marks less than 40 or more than 60
C. Marks from 41 to 60 only
D. Marks greater than 40 and less than 60

Ans: A

Explanation: BETWEEN is inclusive of both limits.

Q52 | SQL | Database Connectivity

Which keyword removes duplicate values from a query result?

A. REMOVE
B. SINGLE
C. DISTINCT
D. UNIQUE

Ans: C

Explanation: SELECT DISTINCT returns each different value only once.

Q53 | SQL | Database Connectivity

SELECT * FROM Student ORDER BY Name sorts the records:

A. Randomly
B. In the order they were entered
C. In descending order of Name
D. In ascending order of Name (the default)

Ans: D

Explanation: ORDER BY is ascending unless DESC is specified.

Q54 | SQL | Database Connectivity

SELECT AVG(Marks) FROM Student returns:

A. The total of the Marks column
B. The average value of the Marks column
C. The number of non-null Marks values
D. The highest Marks value

Ans: B

Explanation: AVG is an aggregate function. SUM totals, MAX gives the highest and COUNT gives the number of values.

Q55 | SQL | Database Connectivity

Which condition correctly selects students whose Phone value is missing?

A. `WHERE Phone IS EMPTY`
B. `WHERE Phone == NULL`
C. `WHERE Phone = NULL`
D. `WHERE Phone IS NULL`

Ans: D

Explanation: NULL cannot be compared with =. It must be tested using IS NULL or IS NOT NULL.

Q56 | SQL | Database Connectivity

In a LIKE pattern, the underscore (_) wildcard stands for:

A. Exactly one digit
B. A literal underscore only
C. Exactly one character
D. Any number of characters including none

Ans: C

Explanation: % matches any number of characters, while _ matches a single character. So LIKE '_a%' means the second letter is a.

Q57 | SQL | Database Connectivity

WHERE Dept IN ('CS', 'IT') is equivalent to:

A. `WHERE Dept = 'CS' OR Dept = 'IT'`
B. `WHERE Dept LIKE 'CS' AND 'IT'`
C. `WHERE Dept = 'CS' AND Dept = 'IT'`
D. `WHERE Dept BETWEEN 'CS' AND 'IT'`

Ans: A

Explanation: IN tests membership in a list and acts like a series of OR conditions.

Q58 | SQL | Database Connectivity

In SELECT Name AS StudentName FROM Student, the AS keyword:

A. Creates a new table called StudentName
B. Converts Name to a different data type
C. Gives the column an alias in the result
D. Renames the column permanently in the table

Ans: C

Explanation: An alias only changes the heading in the query result.

Q59 | SQL | Database Connectivity

Which statement creates a new table?

A. `ADD TABLE Student (RollNo INTEGER, Name VARCHAR(30))`
B. `MAKE TABLE Student (RollNo INTEGER, Name VARCHAR(30))`
C. `CREATE TABLE Student (RollNo INTEGER, Name VARCHAR(30))`
D. `NEW TABLE Student (RollNo INTEGER, Name VARCHAR(30))`

Ans: C

Explanation: CREATE TABLE is the standard DDL statement to define a table.

Q60 | SQL | Database Connectivity

Which statement adds a new column to an existing table?

A. `ALTER TABLE Student ADD Phone VARCHAR(10)`

B. `MODIFY TABLE Student ADD Phone VARCHAR(10)`

C. `UPDATE TABLE Student ADD Phone VARCHAR(10)`

D. `INSERT COLUMN Phone INTO Student`

Ans: A

Explanation: ALTER TABLE changes the structure of an existing table.

Q61 | SQL | Database Connectivity

The Student table has 10 rows, and Marks is NULL in 2 of them. What does SELECT COUNT(Marks) FROM Student return?

A. 8

B. 0

C. 10

D. 2

Ans: A

Explanation: COUNT(column) ignores NULL values. COUNT(*) would give 10.

Q62 | SQL | Database Connectivity

What does this query return?

```
SELECT * FROM Student
WHERE Marks > (SELECT AVG(Marks) FROM Student)
```

A. Students whose marks equal the class average

B. Students whose marks are above the class average

C. The student with the highest marks only

D. All students, with the average added as a column

Ans: B

Explanation: The inner query computes the average, and the outer query compares each row with it.

SECTION 5 ADO DATA CONTROL AND DATA-SOURCE CONNECTIONS

Q63 - Q84 | 22 questions

Q63 | Concept | Database Connectivity

The ADO Data Control is added to the toolbox using:

A. It is already present in the standard toolbox
B. Project > Components > Microsoft ADO Data Control 6.0 (OLEDB)
C. Tools > Add-Ins > ADO Data Control
D. Project > References > Microsoft ADO Data Control 6.0

Ans: B

Explanation: The ADO Data Control is an ActiveX control (MSADODC.OCX) added from the Components dialog.

Q64 | Concept | Database Connectivity

The default name given to the first ADO Data Control placed on a form is:

A. AdoData1
B. Data1
C. ADO1
D. Adodc1

Ans: D

Explanation: Data1 is the default name of the intrinsic (DAO) Data control.

Q65 | Concept | Database Connectivity

Which property of the ADO Data Control specifies how to connect to the data source?

A. RecordSource
B. DataMember
C. ConnectionString
D. DatabaseName

Ans: C

Explanation: DatabaseName belongs to the DAO Data control, not to ADO Data Control.

Q66 | Concept | Database Connectivity

Which property decides the table, query or command that supplies the records?

A. DataSource
B. ConnectionString
C. DataField
D. RecordSource

Ans: D

Explanation: RecordSource, together with CommandType, tells Adodc what to retrieve.

Q67 | Concept | Database Connectivity

To give a table name directly in RecordSource, the CommandType must be:

A. adCmdFile
B. adCmdStoredProc
C. adCmdTable
D. adCmdText

Ans: C

Explanation: adCmdTable (2) means the source is a table name. adCmdText (1) is used for SQL text.

Q68 | Concept | Database Connectivity

How can the underlying ADO Recordset of Adodc1 be reached in code?

A. `Adodc1.DataSource`
B. `Adodc1.Connection`
C. `Adodc1.Recordset`
D. `Adodc1.Records`

Ans: C

Explanation: For example, Adodc1.Recordset.MoveNext.

Q69 | Concept | Database Connectivity

Which property of the ADO Data Control sets the text shown between its navigation buttons?

A. RecordSource
B. Caption
C. Text
D. Name

Ans: B

Explanation: Caption displays text, for example "Student Records", between the arrow buttons.

Q70 | Concept | Database Connectivity

What is the default value of EOFAction in the ADO Data Control?

A. adStayEOF
B. adDoMoveFirst
C. adDoMoveLast
D. adDoAddNew

Ans: C

Explanation: Values: 0 adDoMoveLast (default), 1 adStayEOF, 2 adDoAddNew.

Q71 | Concept | Database Connectivity

Which EOFAction adds a blank new record automatically when the user clicks Next on the last record?

A. adDoMoveNext
B. adDoAddNew
C. adDoMoveLast
D. adStayEOF

Ans: B

Explanation: adDoAddNew (2) calls AddNew when the user moves past the last record.

Q72 | Concept | Database Connectivity

A Universal Data Link file has the extension:

A. MDB
B. DSN
C. ADO
D. UDL

Ans: D

Explanation: .udl stores an OLE DB connection string. .dsn is an ODBC File DSN.

Q73 | Code | Database Connectivity

Which connection string correctly connects to an Access database?

A. `Provider=Microsoft.Jet.OLEDB.4.0;Database Name=C:\School.mdb`
B. `Provider=SQLOLEDB;Data Source=C:\School.mdb`
C. `Driver=Microsoft.Jet.OLEDB.4.0;File=C:\School.mdb`
D. `Provider=Microsoft.Jet.OLEDB.4.0;Data Source=C:\School.mdb`

Ans: D

Explanation: An OLE DB connection string needs Provider and Data Source.

Q74 | Concept | Database Connectivity

To make Adodc1 re-run its RecordSource after changing it at run time, you call:

A. `Adodc1.Reload`
B. `Adodc1.Reset`
C. `Adodc1.Refresh`
D. `Adodc1.Update`

Ans: C

Explanation: Refresh re-creates the Recordset from the current ConnectionString and RecordSource.

Q75 | Concept | Database Connectivity

To bind a TextBox to the field Name supplied by Adodc1, you set:

A. DataMember = Adodc1 and ListField = Name
B. RecordSource = Adodc1 and DataField = Name
C. DataSource = Adodc1 and DataField = Name
D. ConnectionString = Adodc1 and RowSource = Name

Ans: C

Explanation: A bound control needs DataSource (the data control) and DataField (the column).

Q76 | Concept | Database Connectivity

Which type of ODBC DSN is stored in the registry and is available to all users of a computer?

A. User DSN
B. System DSN
C. Remote DSN
D. File DSN

Ans: B

Explanation: A User DSN is visible to one user only, and a File DSN is stored in a .dsn file.

Q77 | Concept | Database Connectivity

What is the default ConnectionTimeout of the ADO Data Control (in seconds)?

A. 15
B. 0
C. 30
D. 60

Ans: A

Explanation: ConnectionTimeout defaults to 15 seconds and CommandTimeout to 30 seconds.

Q78 | Concept | Database Connectivity

Which property of the ADO Data Control sets the read/write permissions of its connection?

A. EOFAction
B. Mode
C. LockType
D. CursorType

Ans: B

Explanation: Mode takes values such as adModeRead, adModeWrite and adModeReadWrite.

Q79 | Concept | Database Connectivity

What is the default BOFAction of the ADO Data Control?

A. adDoAddNew
B. adStayBOF
C. adDoMoveLast
D. adDoMoveFirst

Ans: D

Explanation: BOFAction 0 = adDoMoveFirst (default), 1 = adStayBOF.

Q80 | Concept | Database Connectivity

The MaxRecords property of the ADO Data Control:

A. Limits the number of records returned, where 0 means no limit
B. Sets the maximum number of fields in the Recordset
C. Sets the maximum number of Adodc controls per form
D. Sets the size of each record in bytes

Ans: A

Explanation: MaxRecords is useful to avoid fetching very large result sets.

Q81 | Concept | Database Connectivity

Which event of the ADO Data Control occurs AFTER the current record has changed?

A. RecordChanging
B. MoveComplete
C. WillChangeRecord
D. WillMove

Ans: B

Explanation: WillMove is fired before the move, and MoveComplete after it.

Q82 | Code | Database Connectivity

Which statement starts adding a new record through the recordset of the ADO Data Control Adodc1?

A. `Adodc1.Recordset.Insert`
B. `Adodc1.NewRecord`
C. `Adodc1.AddNew`
D. `Adodc1.Recordset.AddNew`

Ans: D

Explanation: The ADO Data Control itself has no AddNew method. It is a method of its Recordset.

Q83 | Code | Database Connectivity

Which connection string uses an ODBC data source (DSN) named SchoolDSN?

A. `Provider=MSDASQL;DSN=SchoolDSN`

B. `DSN=Provider=MSDASQL;SchoolDSN`

C. `Driver=SchoolDSN;Provider=MSDASQL`

D. `Provider=SQLOLEDB;DSN=SchoolDSN`

Ans: A

Explanation: MSDASQL is the OLE DB provider for ODBC, and DSN names the data source.

Q84 | Concept | Database Connectivity

In the Property Pages of the ADO Data Control, clicking the Build button opens:

A. The Data Link Properties dialog box

B. The Crystal Reports Expert

C. The Query Builder form

D. The Data Environment designer

Ans: A

Explanation: Data Link Properties lets you choose the provider and database and test the connection.

SECTION 6 DATACOMBO, DATALIST AND DATAGRID

Q85 - Q103 | 19 questions

Q85 | Concept | Database Connectivity

The DataCombo and DataList controls belong to which component?

A. Microsoft DataList Controls 6.0 (OLEDB)
B. Microsoft Windows Common Controls 6.0
C. Microsoft DataGrid Control 6.0 (OLEDB)
D. Microsoft ADO Data Control 6.0 (OLEDB)

Ans: A

Explanation: DataGrid has its own component (MSDATGRD.OCX). DataCombo and DataList share MSDATLST.OCX.

Q86 | Concept | Database Connectivity

What is the main difference between DataCombo and DataList?

A. DataCombo is unbound while DataList is bound
B. DataList works only with DAO while DataCombo works with ADO
C. DataList can edit records but DataCombo cannot
D. DataCombo is a drop-down combo with a text portion, while DataList is an always-visible list

Ans: D

Explanation: Both are data-bound. DataCombo behaves like a ComboBox, DataList like a ListBox.

Q87 | Concept | Database Connectivity

Which property gives the data control that fills the list of a DataCombo or DataList?

A. DataField
B. BoundText
C. RowSource
D. DataSource

Ans: C

Explanation: RowSource supplies the list items. DataSource is the recordset that will be updated.

Q88 | Concept | Database Connectivity

The ListField property of DataCombo specifies:

A. The ADO control to which the list is bound
B. The field used for sorting the list
C. The field of RowSource whose values are displayed in the list
D. The field of DataSource that is updated by the selection

Ans: C

Explanation: ListField selects what the user sees in the list.

Q89 | Concept | Database Connectivity

The DataField property of DataCombo specifies:

A. The field of the DataSource recordset that is updated with the selected value
B. The column width of the list
C. The name of the table that fills the list
D. The field of RowSource shown in the list

Ans: A

Explanation: DataField is the destination field in the table being edited.

Q90 | Concept | Database Connectivity

The BoundColumn property of a DataCombo is:

A. The column number of the grid
B. The RowSource field whose value is passed to the DataField
C. The number of columns of the ADO control
D. The field displayed in the text portion

Ans: B

Explanation: BoundColumn supplies the value that is saved, for example an ID, even if ListField shows a name.

Q91 | Concept | Database Connectivity

Which property returns the BoundColumn value of the current selection?

A. SelectedItem
B. Text
C. BoundText
D. MatchedWithList

Ans: C

Explanation: Text holds the displayed ListField text, and SelectedItem returns a bookmark.

Q92 | Concept | Database Connectivity

To stop users typing a value that is not in a DataCombo list, set Style to:

A. dbcFixedList
B. dbcDropdownList
C. dbcDropdownCombo
D. dbcSimpleCombo

Ans: B

Explanation: Style values: 0 dbcDropdownCombo, 1 dbcSimpleCombo, 2 dbcDropdownList.

Q93 | Concept | Database Connectivity

A DataGrid is bound to an ADO Data Control using the property:

A. DataSource
B. DataField
C. RowSource
D. ListField

Ans: A

Explanation: DataGrid shows a whole recordset, so it only needs DataSource.

Q94 | Concept | Database Connectivity

Which settings make a DataGrid read-only?

A. AllowAddNew, AllowDelete and AllowUpdate all set to False
B. Only AllowAddNew and AllowDelete set to False
C. Only AllowAddNew set to False
D. Only AllowUpdate set to False

Ans: A

Explanation: All three permissions must be turned off to block adding, deleting and editing.

Q95 | Concept | Database Connectivity

Which DataGrid property lets users add records through the blank row at the bottom?

A. AllowDelete
B. AllowRowSizing
C. AllowAddNew
D. AllowUpdate

Ans: C

Explanation: AllowAddNew = True shows an empty row for new records.

Q96 | Concept | Database Connectivity

To load the column layout of a DataGrid from its bound recordset at design time, you use:

A. Project > Add Columns

B. Right-click > Retrieve Fields

C. Format > Auto Fields

D. Insert > Fields

Ans: B

Explanation: Retrieve Fields fills the Columns collection from the recordset.

Q97 | Scenario | Database Connectivity

The Orders table has CustID. The Customers table has CustID and CustName. A DataCombo must show CustName but store CustID in Orders (AdodcOrders and AdodcCustomers are the data controls). Which settings are correct?

A. DataSource = AdodcCustomers, DataField = CustID, RowSource = AdodcOrders, ListField = CustName, BoundColumn = CustID

B. DataSource = AdodcCustomers, DataField = CustName, RowSource = AdodcOrders, ListField = CustID, BoundColumn = CustName

C. DataSource = AdodcOrders, DataField = CustID, RowSource = AdodcCustomers, ListField = CustName, BoundColumn = CustID

D. DataSource = AdodcOrders, DataField = CustName, RowSource = AdodcCustomers, ListField = CustID, BoundColumn = CustName

Ans: C

Explanation: DataSource/DataField point to the table being updated, and RowSource/ListField/BoundColumn point to the lookup table.

Q98 | Concept | Database Connectivity

Which property of a bound control becomes True when the user changes its contents?

A. DataChanged

B. Modified

C. DataField

D. Changed

Ans: A

Explanation: DataChanged lets code detect that the displayed value was edited.

Q99 | Concept | Database Connectivity

The MatchEntry property of a DataList or DataCombo decides:

A. Which field is used as the data source
B. Whether the list is sorted
C. How many columns are displayed
D. How the list matches the characters the user types (basic or extended matching)

Ans: D

Explanation: dblBasicMatching goes by the first character. dblExtendedMatching matches the whole typed text.

Q100 | Concept | Database Connectivity

Which property of a DataList returns a bookmark for the currently selected item?

A. SelectedItem
B. RowSource
C. ListField
D. BoundText

Ans: A

Explanation: The bookmark can be assigned to the Recordset's Bookmark to move to that record.

Q101 | Concept | Database Connectivity

Which DataGrid property shows or hides the column heading row?

A. AllowRowSizing
B. HeadFont
C. Caption
D. ColumnHeaders

Ans: D

Explanation: ColumnHeaders = False removes the heading row.

Q102 | Code | Database Connectivity

Which statement sets the heading text of the FIRST column of DataGrid1?

A. `DataGrid1.Columns(1).Caption = "Name"`
B. `DataGrid1.Column(0).Text = "Name"`
C. `DataGrid1.Fields(0).Caption = "Name"`
D. `DataGrid1.Columns(0).Caption = "Name"`

Ans: D

Explanation: The Columns collection is zero-based, so the first column is Columns(0).

Q103 | Code | Database Connectivity

How is a DataGrid bound in code to an existing ADO Recordset named rs?

A. `Set DataGrid1.DataSource = rs`

B. `DataGrid1.RowSource = rs`

C. `DataGrid1.Recordset = rs`

D. `DataGrid1.DataSource = rs`

Ans: A

Explanation: DataSource is an object property, so the Set keyword is required.

SECTION 7 CODING ADO AND RECORDSET OPERATIONS

Q104 - Q139 | 36 questions

Quick reference: Recordset constants

CursorType

Constant	Val.	Meaning
`adOpenForwardOnly`	0	Forward only (default)
`adOpenKeyset`	1	Sees edits and deletes
`adOpenDynamic`	2	Sees all changes
`adOpenStatic`	3	Fixed snapshot

LockType

Constant	Val.	Meaning
`adLockReadOnly`	1	Read only (default)
`adLockPessimistic`	2	Lock on edit
`adLockOptimistic`	3	Lock on Update
`adLockBatchOptimistic`	4	Batch updates

Q104 | Code | Database Connectivity

If cn is declared as Dim cn As ADODB.Connection, which statement must run before cn.Open?

A. `Set cn = New ADODB.Connection`

B. `Create cn As ADODB.Connection`

C. `Load cn`

D. `cn = New ADODB.Connection`

Ans: A

Explanation: Object variables need the Set keyword to be assigned an object.

Q105 | Concept | Database Connectivity

What is the correct order of arguments of Recordset.Open?

A. Options, Source, ActiveConnection, CursorType, LockType

B. ActiveConnection, Source, LockType, CursorType, Options

C. Source, CursorType, ActiveConnection, Options, LockType

D. Source, ActiveConnection, CursorType, LockType, Options

Ans: D

Explanation: Example: rs.Open "Student", cn, adOpenStatic, adLockOptimistic, adCmdTable.

Q106 | Concept | Database Connectivity

What is the default CursorType of an ADO Recordset opened without specifying it?

A. adOpenDynamic

B. adOpenForwardOnly

C. adOpenStatic

D. adOpenKeyset

Ans: B

Explanation: The default is a forward-only cursor (value 0) with read-only locking.

Q107 | Concept | Database Connectivity

Which LockType allows editing and locks the record only when Update is called?

A. adLockReadOnly
B. adLockOptimistic
C. adLockBatchOptimistic
D. adLockPessimistic

Ans: B

Explanation: Pessimistic locking locks the record as soon as editing starts.

Q108 | Scenario | Database Connectivity

A programmer opens a Recordset with default settings and then calls rs.AddNew, which causes an error. The most likely reason is:

A. The Connection was opened using Jet 4.0
B. AddNew cannot be used with Access databases
C. The default forward-only, read-only Recordset does not allow updates
D. Update must be called before AddNew

Ans: C

Explanation: Open the Recordset with a suitable cursor and adLockOptimistic before using AddNew.

Q109 | Concept | Database Connectivity

What is the correct sequence for adding a record to a Recordset?

A. AddNew, Update, assign field values
B. Update, AddNew, assign field values
C. AddNew, assign field values, Update
D. Assign field values, AddNew, Update

Ans: C

Explanation: AddNew creates a blank record, you fill it, and Update saves it.

Q110 | Concept | Database Connectivity

Which method of DAO has no equivalent in ADO, because ADO field values can be changed directly?

A. AddNew
B. Delete
C. Edit
D. Update

Ans: C

Explanation: In ADO you simply assign a new value to the field and call Update.

Q111 | Code | Database Connectivity

What does this code do?

```
rs.Find "RollNo = 5"
If Not rs.EOF Then
    rs!Marks = 90
    rs.Update
End If
```

A. Adds a new record having RollNo 5

B. Sets Marks of every student to 90

C. Deletes the record with RollNo 5

D. Sets Marks of the student with RollNo 5 to 90, if found

Ans: D

Explanation: Find locates the record, the field is assigned a new value, and Update saves the change.

Q112 | Concept | Database Connectivity

After rs.Delete is executed on the current record, what should the program do next?

A. Call rs.AddNew to refill the record

B. Call rs.Update to complete the deletion

C. Move to another record, because the deleted record cannot be used

D. Nothing, the same record remains usable

Ans: C

Explanation: Delete takes effect immediately in non-batch mode, so use MoveNext or MoveFirst afterwards.

Q113 | Concept | Database Connectivity

Which method abandons changes made to the current record (or a new record after AddNew) before Update is called?

A. Cancel

B. Close

C. CancelUpdate

D. Requery

Ans: C

Explanation: CancelUpdate discards pending changes.

Q114 | Code | Database Connectivity

Which statement correctly searches for the student named Ravi?

A. `rs.Find "Name = 'Ravi'"`

B. `rs.Find Name = 'Ravi'`

C. `rs.Find Name, "Ravi"`

D. `rs.Search "Name = 'Ravi'"`

Ans: A

Explanation: Find takes one criteria string, and text values go inside single quotes.

Q115 | Concept | Database Connectivity

Which statement about Recordset.Find is TRUE?

A. It supports several conditions combined with AND

B. It always searches from the first record

C. The criteria can use only one column, so AND/OR combinations are not allowed

D. It returns a new Recordset of the matching rows

Ans: C

Explanation: Find searches from the current record. For multiple conditions use Filter or an SQL query.

Q116 | Concept | Database Connectivity

If Find does not find a match while searching forward, then:

A. A run-time error "record not found" occurs

B. rs.BOF becomes True

C. The first record becomes current

D. rs.EOF becomes True

Ans: D

Explanation: After a failed forward Find, EOF is True (BOF for a backward search).

Q117 | Concept | Database Connectivity

Which Recordset property shows only the records that meet a condition, without running a new query?

A. `Sort`

B. `Source`

C. `Filter`

D. `Bookmark`

Ans: C

Explanation: Example: rs.Filter = "Marks > 60".

Q118 | Concept | Database Connectivity

rs.RecordCount returns -1 when:

A. The Recordset uses a forward-only cursor
B. The connection is closed
C. The Recordset is empty
D. The table has no primary key

Ans: A

Explanation: Forward-only cursors cannot report the count. An empty Recordset returns 0.

Q119 | Concept | Database Connectivity

If both rs.BOF and rs.EOF are True, then:

A. The Recordset is closed
B. The pointer is on the last record
C. The Recordset is read-only
D. The Recordset contains no records

Ans: D

Explanation: BOF and EOF are both True only for an empty Recordset.

Q120 | Concept | Database Connectivity

What happens if MoveNext is called when rs.EOF is already True?

A. The pointer silently stays at EOF
B. A run-time error occurs
C. A new blank record is added
D. The pointer wraps to the first record

Ans: B

Explanation: Moving beyond EOF raises the error "Either BOF or EOF is True...".

Q121 | Code | Database Connectivity

What happens when this code runs on a Recordset that has records?

```
Do While Not rs.EOF
    List1.AddItem rs!Name
Loop
```

A. The same name is added again and again, an infinite loop (no MoveNext)
B. Each name is added once and the loop ends
C. A compile error occurs at List1.AddItem
D. Only the first name is added and the loop ends

Ans: A

Explanation: Without rs.MoveNext, EOF never becomes True.

Q122 | Code | Database Connectivity

Which of the following is NOT a valid way to read the Name field of the current record?

A. `rs!Name`
B. `rs.Field("Name")`
C. `rs("Name")`
D. `rs.Fields("Name")`

Ans: B

Explanation: The collection is Fields. There is no Field member.

Q123 | Concept | Database Connectivity

Which of the following runs an action query (UPDATE, DELETE, INSERT) directly without returning a Recordset?

A. `rs.Execute`
B. `cn.Execute`
C. `cn.Run`
D. `cn.Query`

Ans: B

Explanation: Connection.Execute can run SQL statements. Example: cn.Execute "DELETE FROM Student WHERE RollNo = 5".

Q124 | Code | Database Connectivity

What is the correct way to release a Recordset when work is finished?

A. `Set rs = Nothing and then rs.Close`
B. `Unload rs`
C. `rs.Close and then Set rs = Nothing`
D. `rs.Dispose`

Ans: C

Explanation: Close the object first, then release the reference.

Q125 | Concept | Database Connectivity

Which cursor type shows additions, changes and deletions made by other users?

A. adOpenKeyset
B. adOpenForwardOnly
C. adOpenStatic
D. adOpenDynamic

Ans: D

Explanation: Keyset shows changes and deletions but not new records. Static shows none of them.

Q126 | Concept | Database Connectivity

Which Recordset method re-executes the underlying command to refresh the data?

A. Requery
B. Update
C. MoveFirst
D. Clone

Ans: A

Explanation: Requery re-runs the query and brings fresh data.

Q127 | Concept | Database Connectivity

Which property stores the current record position so you can return to it later?

A. Source
B. Index
C. Bookmark
D. RecordCount

Ans: C

Explanation: Save with bm = rs.Bookmark and return with rs.Bookmark = bm.

Q128 | Concept | Database Connectivity

What is the difference between Find and Filter?

A. Both return a new Recordset object
B. Find moves the pointer to a matching record, while Filter hides the records that do not match
C. Find hides non-matching records, while Filter moves the pointer
D. Find works only on indexed fields, Filter on any field

Ans: B

Explanation: Find changes the current record. Filter changes which records are visible.

Q129 | Concept | Database Connectivity

Which Options constant tells ADO that the Source argument of Recordset.Open is an SQL statement?

A. adCmdText
B. adCmdTable
C. adCmdUnknown
D. adCmdFile

Ans: A

Explanation: adCmdText is used for SQL text. adCmdTable is used when the Source is a table name.

Q130 | Code | Database Connectivity

After this statement executes, the variable n holds:

```
cn.Execute "DELETE FROM Student WHERE Marks < 33", n
```

A. The number of records in the whole table
B. Always 1
C. The ID of the last deleted record
D. The number of records deleted

Ans: D

Explanation: The second argument of Connection.Execute receives RecordsAffected.

Q131 | Concept | Database Connectivity

Which Recordset property gets or sets the ordinal position of the current record?

A. RecordCount
B. AbsolutePosition
C. CursorLocation
D. Bookmark

Ans: B

Explanation: AbsolutePosition gives the record number, starting from 1.

Q132 | Concept | Database Connectivity

Setting rs.Sort = "Name DESC" requires which CursorLocation?

A. `adUseDynamic`
B. `adUseServer`
C. `adUseClient`
D. `adUseNone`

Ans: C

Explanation: The Sort property works on a client-side cursor, so set rs.CursorLocation = adUseClient before opening the Recordset.

Q133 | Concept | Database Connectivity

Which Recordset method creates a duplicate Recordset that refers to the same data?

A. Copy
B. Requery
C. Clone
D. Duplicate

Ans: C

Explanation: A clone has its own current-record pointer, so you can move in it independently.

Q134 | Concept | Database Connectivity

Which LockType is required to use UpdateBatch on a Recordset?

A. adLockBatchOptimistic
B. adLockPessimistic
C. adLockReadOnly
D. adLockOptimistic

Ans: A

Explanation: In batch mode, changes are stored locally and sent to the database together by UpdateBatch.

Q135 | Code | Database Connectivity

In the CommandText of an ADO Command, what does the ? mark represent?

A. `An error in the SQL statement`
B. `A comment marker`
C. `A parameter placeholder whose value is supplied through the Parameters collection`
D. `A wildcard that matches any single character`

Ans: C

Explanation: Example: SELECT * FROM Student WHERE RollNo = ? with a parameter for RollNo.

Q136 | Concept | Database Connectivity

Which Recordset method copies records into a two-dimensional array?

A. ToArray
B. GetRows
C. CopyRows
D. GetArray

Ans: B

Explanation: GetRows returns a variant array, with the first index for fields and the second for records.

Q137 | Code | Database Connectivity

What does MsgBox display after this code runs on a Recordset that has records?

```
rs.MoveFirst
rs.MovePrevious
MsgBox rs.BOF
```

A. False
B. 0
C. True
D. A run-time error occurs

Ans: C

Explanation: Moving back from the first record places the pointer before it, so BOF becomes True.

Q138 | Code | Database Connectivity

Which code deletes all the records of an open, updatable Recordset?

A. `Do While Not rs.EOF: rs.Delete: rs.MoveNext: Loop`

B. `rs.MoveFirst: rs.Delete`

C. `rs.DeleteAll`

D. `Do Until rs.EOF: rs.Delete: Loop`

Ans: A

Explanation: Each record needs Delete followed by MoveNext. The last option deletes only one record.

Q139 | Scenario | Database Connectivity

A student must be found using two conditions, such as Class = 10 AND Section = 'A'. Since Find accepts one condition only, what is the best approach?

A. Use an SQL query with AND in the WHERE clause (or Filter)

B. Use rs.Seek on the Class field

C. Use rs.Find with two arguments separated by a comma

D. Call Find twice with the same field

Ans: A

Explanation: SQL (or Filter, which allows AND) handles multi-condition searches.

SECTION 8 DATA ENVIRONMENT

Q140 - Q157 | 18 questions

Q140 | Concept | Database Connectivity

A Data Environment is added to a VB 6.0 project using:

A. Project > Components > Data Environment
B. Tools > Add Data Environment
C. File > New > Data Environment Report
D. Project > Add Data Environment

Ans: D

Explanation: The Data Environment designer is added from the Project menu.

Q141 | Concept | Database Connectivity

What are the two basic types of objects in the Data Environment designer?

A. Provider and Parameter
B. Recordset and Field
C. Table and Query
D. Connection and Command

Ans: D

Explanation: A Connection defines the data source and Commands define the data retrieved through it.

Q142 | Concept | Database Connectivity

A Command object in the Data Environment can be based on:

A. A table, view, stored procedure or SQL statement
B. Only a Crystal Report file
C. Only an SQL statement typed at run time
D. Only a table

Ans: A

Explanation: The Command's Source of Data can be a database object or an SQL statement.

Q143 | Concept | Database Connectivity

What happens when a Command is dragged from the Data Environment designer onto a form?

A. A Crystal report is created from the Command
B. The Command is deleted from the Data Environment
C. A new Connection object is created on the form
D. Data-bound labels and text boxes are created for its fields

Ans: D

Explanation: Drag and drop quickly creates a bound data-entry form.

Q144 | Code | Database Connectivity

If a Command named Students is defined in DataEnvironment1, its Recordset is reached in code as:

A. `DataEnvironment1.Students.rs`
B. `DataEnvironment1.Recordset.Students`
C. `DataEnvironment1.rsStudents`
D. `Students.DataEnvironment1`

Ans: C

Explanation: The Recordset of a Command is exposed with the prefix rs, followed by the Command name.

Q145 | Concept | Database Connectivity

A child Command is related to its parent Command through which tab of Command Properties?

A. General
B. Relation
C. Advanced
D. Parameters

Ans: B

Explanation: The Relation tab (Relate to a Parent Command Object) gives a parent-child hierarchy.

Q146 | Concept | Database Connectivity

A Data Environment designer is saved in a file with the extension:

A. CLS
B. FRM
C. DSR
D. RPT

Ans: C

Explanation: Designers are saved as .dsr files. .frm is a form and .rpt is a Crystal report.

Q147 | Concept | Database Connectivity

What is an advantage of the Data Environment over placing separate ADO Data controls on every form?

A. It stores the data inside the project file
B. It removes the need for an OLE DB provider
C. Connection and commands are defined once in a designer and reused across forms
D. It works without any database connection

Ans: C

Explanation: The Data Environment centralises Connection and Command definitions.

Q148 | Code | Database Connectivity

Which settings bind a TextBox to the field Name of the Command Students in DataEnvironment1?

A. RecordSource = DataEnvironment1, DataMember = Name
B. DataSource = DataEnvironment1, DataMember = Students, DataField = Name
C. RowSource = DataEnvironment1, ListField = Students, BoundColumn = Name
D. DataSource = Students, DataMember = DataEnvironment1

Ans: B

Explanation: DataMember selects the Command inside the Data Environment.

Q149 | Concept | Database Connectivity

In the Data Environment Connection properties, the OLE DB provider is chosen on which tab of Data Link Properties?

A. All
B. Connection
C. Provider
D. Advanced

Ans: C

Explanation: Choose the provider on the Provider tab, then set the database on the Connection tab.

Q150 | Concept | Database Connectivity

Which object of the Data Environment stores the details of the provider and the database?

A. Connection
B. Command
C. Recordset
D. Parameter

Ans: A

Explanation: A Connection defines how to reach the data source. Commands retrieve data through it.

Q151 | Concept | Database Connectivity

In the SQL of a Data Environment Command, a parameter is shown by:

A. An ampersand (&)
B. A question mark (?)
C. An asterisk (*)
D. A hash sign (#)

Ans: B

Explanation: Example: SELECT * FROM Student WHERE Class = ?. The value is set in the Parameters tab or through code.

Q152 | Code | Database Connectivity

If the Command Students in DataEnvironment1 has one parameter, how can it be executed from code with the value 10?

A. `DataEnvironment1.Execute Students, 10`
B. `DataEnvironment1.rsStudents = 10`
C. `DataEnvironment1.Students(10).Open`
D. `DataEnvironment1.Students 10`

Ans: D

Explanation: Each Command is exposed as a method of the Data Environment, and the parameters are passed as arguments.

Q153 | Scenario | Database Connectivity

A Data Environment Command is executed again, and an error says the operation is not allowed when the object is open. What is the likely fix?

A. Delete and recreate the Connection
B. Add a primary key to the table
C. Close its Recordset (for example DataEnvironment1.rsStudents) before executing the Command again
D. Set the CommandType to adCmdText

Ans: C

Explanation: A Command whose Recordset is already open cannot be run again until that Recordset is closed.

Q154 | Concept | Database Connectivity

A Data Report designer in VB 6.0 gets its data from:

A. A Form's Print method only
B. A Crystal Report file
C. The Windows registry
D. A Data Environment Command

Ans: D

Explanation: A Data Report is bound to the Data Environment through its DataSource and DataMember properties.

Q155 | Concept | Database Connectivity

How is a Data Report added to a VB 6.0 project?

A. Project > Add Data Report
B. File > New Report
C. Tools > Report Designer
D. Project > Components > Data Report

Ans: A

Explanation: It is added from the Project menu, like the Data Environment.

Q156 | Concept | Database Connectivity

A hierarchical Command in the Data Environment is:

A. A Command that can only read one record
B. A Command that contains another Connection
C. A parent Command that has one or more child Commands related through key fields
D. A Command with more than five parameters

Ans: C

Explanation: The relation is defined on the Relation tab, and child Commands are shown under their parent.

Q157 | Concept | Database Connectivity

A Data Environment Connection is opened:

A. Only through a call to the Windows API
B. Every time a form is unloaded
C. Only when the project is compiled
D. Automatically the first time one of its Commands is executed or its Recordset is accessed

Ans: D

Explanation: You can also open it explicitly in code with DataEnvironment1.Connection1.Open.

SECTION 9 CRYSTAL REPORTS 7.0 OR ABOVE

Q158 - Q176 | 19 questions

Q158 | Concept | Database Connectivity

Crystal Reports is mainly used to:

A. Design and print formatted reports from database data
B. Write SQL stored procedures
C. Create database tables and relationships
D. Compile VB projects into EXE files

Ans: A

Explanation: Crystal Reports is a report designer and report-writing tool.

Q159 | Concept | Database Connectivity

A saved Crystal Reports report file has the extension:

A. DSR
B. REP
C. CRP
D. RPT

Ans: D

Explanation: Crystal reports are saved as .rpt files. .dsr is a Data Environment designer.

Q160 | Scenario | Database Connectivity

A company logo and the report title must appear only once, at the start of the report. Which section should hold them?

A. Page Header
B. Page Footer
C. Details
D. Report Header

Ans: D

Explanation: Report Header prints once at the beginning. Page Header prints at the top of every page.

Q161 | Concept | Database Connectivity

Which Crystal Reports section prints once for every record?

A. Report Header
B. Details
C. Report Footer
D. Page Footer

Ans: B

Explanation: The Details section repeats for each record of the report.

Q162 | Scenario | Database Connectivity

A grand total of all records must print only once at the very end. The summary field should be placed in:

A. Group Footer
B. Report Footer
C. Page Footer
D. Details

Ans: B

Explanation: Report Footer prints once after the last record.

Q163 | Concept | Database Connectivity

To show the current page number on every page, you use:

A. The Group Number special field in Report Footer
B. The Print Date special field in Details
C. The Page Number special field in the Page Header or Page Footer
D. The Record Number special field in Report Header

Ans: C

Explanation: Special fields like Page Number, Print Date and Record Number can be inserted in any section.

Q164 | Concept | Database Connectivity

A field whose value is calculated using a Crystal formula is called a:

A. Formula field
B. Special field
C. Text object
D. Database field

Ans: A

Explanation: Formula fields are created with the Formula Editor and can be placed in the report like other fields.

Q165 | Concept | Database Connectivity

With the Crystal Report control in VB, which property specifies the report file to run?

A. `SelectionFormula`
B. `ReportFileName`
C. `DataFiles`
D. `WindowTitle`

Ans: B

Explanation: Example: CrystalReport1.ReportFileName = App.Path & "\Student.rpt".

Q166 | Concept | Database Connectivity

Setting the Destination property to crptToWindow sends the report to:

A. The default printer
B. A preview window on the screen
C. A disk file
D. An e-mail message

Ans: B

Explanation: Destination values: crptToWindow = 0, crptToPrinter = 1, crptToFile = 2.

Q167 | Concept | Database Connectivity

Which property of the Crystal Report control limits the records printed at run time?

A. `SelectionFormula`
B. `WindowState`
C. `ReportFileName`
D. `Formulas`

Ans: A

Explanation: Example: CrystalReport1.SelectionFormula = "{Student.Marks} > 60".

Q168 | Concept | Database Connectivity

In a Crystal Reports formula, a database field is written as:

A. {Table.Field}
B. [Table.Field]
C. <Table.Field>
D. (Table.Field)

Ans: A

Explanation: Fields are enclosed in curly braces, for example {Student.Name}.

Q169 | Concept | Database Connectivity

In Crystal Reports 7.0 or above, which tool guides the user step by step in creating a common report type?

A. Formula Editor
B. Section Expert
C. Browser Pane
D. Report Expert

Ans: D

Explanation: Report Experts cover standard, cross-tab, mailing label and other report types.

Q170 | Scenario | Database Connectivity

A subtotal of marks must print after the last record of each class. Which section should hold the subtotal field?

A. Report Header
B. Page Header
C. Group Footer
D. Details

Ans: C

Explanation: The Group Footer prints at the end of each group.

Q171 | Concept | Database Connectivity

A field that asks the user for a value when the report is run is called a:

A. SQL expression field
B. Special field
C. Formula field
D. Parameter field

Ans: D

Explanation: A parameter field can be used to select records, for example a particular class.

Q172 | Concept | Database Connectivity

A Running Total field in Crystal Reports:

A. Converts numbers to text
B. Accumulates a value record by record as the report is processed
C. Prints only the grand total at the end
D. Counts the pages in the report

Ans: B

Explanation: Running totals can be reset after each group or after each page.

Q173 | Concept | Database Connectivity

Which Crystal Reports tool sets the order in which records appear in the report?

A. Record Sort Expert
B. Group Sort Expert only
C. Section Expert
D. Highlighting Expert

Ans: A

Explanation: Records can be sorted on one or more fields in ascending or descending order.

Q174 | Concept | Database Connectivity

A Cross-Tab report presents data as:

A. A single value per page
B. A mailing-label layout
C. A grid of rows and columns with summarised values at the intersections
D. A list of formulas

Ans: C

Explanation: Cross-Tab is a standard report type, available in Crystal Reports 7.0 or above.

Q175 | Code | Database Connectivity

Which method of the Crystal Report control sends the report to the selected Destination?

A. `RunReport`
B. `PrintReport`
C. `ShowReport`
D. `Execute`

Ans: B

Explanation: Example: CrystalReport1.PrintReport after setting ReportFileName and Destination.

Q176 | Concept | Database Connectivity

In the Crystal Reports designer, which tab shows the report with actual data?

A. Formula
B. Preview
C. Design
D. Layout

Ans: B

Explanation: The Design tab is used for layout and the Preview tab shows the report with the data.

SECTION 10 IMPORTANT AND TRICKY QUESTIONS

Q177 - Q196 | 20 questions

Q177 | Statement | Database Connectivity

Consider the statements:
1. ADO is a high-level interface built on top of OLE DB.
2. OLE DB providers can expose relational and non-relational data.
3. ADO can work only with Jet databases.
Which statements are correct?

A. 1 and 2 only
B. 2 and 3 only
C. 1, 2 and 3
D. 1 and 3 only

Ans: A

Explanation: ADO works with any OLE DB provider, so statement 3 is false.

Q178 | Statement | Database Connectivity

Consider the statements:
1. Find can combine two columns using AND.
2. Filter limits the records visible in a Recordset.
3. After a successful Find, the pointer is at the matching record.
Which statements are correct?

A. 2 and 3 only
B. 1, 2 and 3
C. 1 and 2 only
D. 1 and 3 only

Ans: A

Explanation: Find accepts a single-column criteria only.

Q179 | Statement | Database Connectivity

Consider the statements about the Data Environment:
1. It can hold more than one Connection.
2. A Command can be based on an SQL statement.
3. A parent-child relation can be defined between Commands.
Which statements are correct?

A. 1 and 2 only
B. 1, 2 and 3
C. 2 and 3 only
D. 1 and 3 only

Ans: B

Explanation: All three statements are true.

Q180 | Assertion-Reason | Database Connectivity

Assertion (A): rs.RecordCount may return -1 for an ADO Recordset.
Reason (R): The default ADO Recordset uses a forward-only cursor, which cannot report the number of records.

A. A is true, but R is false
B. Both A and R are true, and R is the correct explanation of A
C. A is false, but R is true
D. Both A and R are true, but R is not the correct explanation of A

Ans: B

Explanation: Opening with adOpenStatic or adOpenKeyset gives a valid RecordCount.

Q181 | Assertion-Reason | Database Connectivity

Assertion (A): In ADO, a new record that is being added is saved even if Update is not called, when the pointer moves to another record.
Reason (R): ADO automatically calls Update when you move off a record that has pending changes.

A. A is false, but R is true
B. A is true, but R is false
C. Both A and R are true, but R is not the correct explanation of A
D. Both A and R are true, and R is the correct explanation of A

Ans: D

Explanation: This differs from DAO, where such pending changes are discarded.

Q182 | Assertion-Reason | Database Connectivity

Assertion (A): A DataCombo can show customer names but store customer IDs in another table.
Reason (R): ListField and BoundColumn of a DataCombo can refer to different fields of the RowSource.

A. A is true, but R is false
B. Both A and R are true, but R is not the correct explanation of A
C. Both A and R are true, and R is the correct explanation of A
D. A is false, but R is true

Ans: C

Explanation: ListField is displayed, while BoundColumn is the value written to DataField.

Q183 | Assertion-Reason | Database Connectivity

Assertion (A): Adodc1.Recordset gives access to the ADO Recordset behind the ADO Data Control.
Reason (R): The ADO Data Control does not use ADO objects internally.

A. Both A and R are true, and R is the correct explanation of A
B. A is true, but R is false
C. A is false, but R is true
D. Both A and R are true, but R is not the correct explanation of A

Ans: B

Explanation: The ADO Data Control wraps an ADO Connection and Recordset.

Q184 | Assertion-Reason | Database Connectivity

Assertion (A): OLE DB can access only relational databases.
Reason (R): OLE DB is based on COM interfaces.

A. A is true, but R is false
B. Both A and R are true, but R is not the correct explanation of A
C. Both A and R are true, and R is the correct explanation of A
D. A is false, but R is true

Ans: D

Explanation: OLE DB can reach non-relational data too, such as e-mail and file systems.

Q185 | Match | Database Connectivity

Match the technology with its description:
1. DAO
2. RDO
3. ADO
4. ODBC
a. Object layer over ODBC for client/server databases
b. Standard API for relational databases using SQL
c. High-level interface over OLE DB
d. Jet-based object model

A. 1-d, 2-c, 3-a, 4-b
B. 1-a, 2-d, 3-b, 4-c
C. 1-b, 2-a, 3-c, 4-d
D. 1-d, 2-a, 3-c, 4-b

Ans: D

Explanation: DAO uses Jet, RDO sits over ODBC, ADO sits over OLE DB and ODBC is the SQL API.

Q186 | Match | Database Connectivity

Match each CursorType constant with its value:
1. adOpenKeyset
2. adOpenStatic
3. adOpenDynamic
4. adOpenForwardOnly
a. 0
b. 1
c. 2
d. 3

A. 1-b, 2-d, 3-c, 4-a
B. 1-a, 2-d, 3-c, 4-b
C. 1-c, 2-d, 3-b, 4-a
D. 1-b, 2-c, 3-d, 4-a

Ans: A

Explanation: adOpenForwardOnly = 0, adOpenKeyset = 1, adOpenDynamic = 2, adOpenStatic = 3.

Q187 | Match | Database Connectivity

Match the Crystal Reports section with when it prints:
1. Report Header
2. Page Header
3. Details
4. Report Footer
a. Once for each record
b. Once at the start of the report
c. Once at the end of the report
d. At the top of every page

A. 1-b, 2-d, 3-a, 4-c
B. 1-d, 2-b, 3-a, 4-c
C. 1-a, 2-d, 3-b, 4-c
D. 1-b, 2-d, 3-c, 4-a

Ans: A

Explanation: Report Header and Report Footer print once. Page Header repeats on each page.

Q188 | Tricky | Database Connectivity

Which property is available in a DataCombo but NOT in a DataList?

A. ListField
B. Style
C. RowSource
D. BoundColumn

Ans: B

Explanation: DataList is only a list, so it has no Style property to choose a drop-down or simple combo.

Q189 | Tricky | Database Connectivity

After rs.Find finds the first matching record, how can the NEXT match be found in ADO?

A. Move past the current record (MoveNext or SkipRows = 1) and call Find again

B. Call rs.Requery and then Find

C. Call Find again with the same arguments, it moves on automatically

D. Call rs.FindNext

Ans: A

Explanation: FindNext belongs to DAO. In ADO calling Find again from the same record finds the same record.

Q190 | Tricky | Database Connectivity

The DAO snapshot-type Recordset is closest to which ADO cursor type?

A. adOpenStatic

B. adOpenKeyset

C. adOpenDynamic

D. adOpenForwardOnly

Ans: A

Explanation: Snapshot is a static copy, and a dynaset is similar to a keyset cursor.

Q191 | Match | Database Connectivity

Match the ADO Data Control property with its function:
1. ConnectionString
2. RecordSource
3. EOFAction
4. CommandType
a. How to connect to the data source
b. The table or query supplying the records
c. Behaviour when moving past the last record
d. Whether the source is a table, SQL text or procedure

A. 1-a, 2-b, 3-d, 4-c

B. 1-a, 2-b, 3-c, 4-d

C. 1-c, 2-b, 3-a, 4-d

D. 1-b, 2-a, 3-c, 4-d

Ans: B

Explanation: ConnectionString connects, RecordSource selects the data, EOFAction handles movement past the last record and CommandType gives the source type.

Q192 | Assertion-Reason | Database Connectivity

Assertion (A): A DataGrid can display records of an ADO Recordset created entirely in code.
Reason (R): The DataSource property of a DataGrid accepts a Recordset object when it is assigned with Set.

A. Both A and R are true, but R is not the correct explanation of A
B. A is true, but R is false
C. A is false, but R is true
D. Both A and R are true, and R is the correct explanation of A

Ans: D

Explanation: No data control is needed. Set DataGrid1.DataSource = rs is enough.

Q193 | Statement | Database Connectivity

Consider the statements:
1. Connection.Execute can run action queries such as UPDATE.
2. Connection.Execute with a SELECT returns a forward-only, read-only Recordset.
3. Connection.Execute always returns an updatable Recordset.
Which statements are correct?

A. 1, 2 and 3
B. 2 and 3 only
C. 1 and 2 only
D. 1 and 3 only

Ans: C

Explanation: Execute returns a default-type (forward-only, read-only) Recordset. For an updatable one, use Recordset.Open.

Q194 | Statement | Database Connectivity

Consider the statements about the Data Environment:
1. Each Command exposes its Recordset with the prefix rs.
2. A Data Environment can hold more than one Connection.
3. A Data Environment cannot be used as a source for data-bound controls.
Which statements are correct?

A. 1 and 2 only
B. 1 and 3 only
C. 2 and 3 only
D. 1, 2 and 3

Ans: A

Explanation: Controls are bound to a Command using DataSource and DataMember, so statement 3 is false.

Q195 | Tricky | Database Connectivity

Which statement correctly searches a Date field named DOB for 1 January 2000 using Find?

A. `rs.Find "DOB = $1/1/2000$"`

B. `rs.Find "DOB LIKE #1/1/2000#"`

C. `rs.Find "DOB = #1/1/2000#"`

D. `rs.Find "DOB IS #1/1/2000#"`

Ans: C

Explanation: Date values in Find criteria are enclosed in # signs, and text values in single quotes.

Q196 | Tricky | Database Connectivity

A text box contains O'Neil, and the SQL string built from it fails. Which fix is correct?

A. `Use double quotes around the whole name in the SQL`

B. `Remove the Where clause from the SQL`

C. `Set the Recordset CursorType to adOpenStatic`

D. `Double the single quote using Replace(txt.Text, "'", "''") before building the SQL`

Ans: D

Explanation: A single quote ends the SQL text literal, so an embedded one must be written as two single quotes.

SECTION 11 MIXED OAVS TGT PRACTICE SET

Q197 - Q209 | 13 questions

Q197 | Scenario | Database Connectivity

Which statement adds 5 marks to every student of Class 10 in one step from VB?

A. `cn.Execute "SELECT Marks + 5 FROM Student WHERE Class = 10"`

B. `cn.Execute "UPDATE Student SET Marks = Marks + 5 WHERE Class = 10"`

C. `cn.Execute "INSERT Student SET Marks = Marks + 5 WHERE Class = 10"`

D. `rs.Update "Marks = Marks + 5 WHERE Class = 10"`

Ans: B

Explanation: An UPDATE query run through Connection.Execute changes all matching rows at once.

Q198 | Concept | Database Connectivity

Which property of the Connection object tells whether the connection is open?

A. State

B. Version

C. Mode

D. Attributes

Ans: A

Explanation: State is adStateOpen (1) when the connection is open and adStateClosed (0) otherwise.

Q199 | Code | Database Connectivity

If the Student table has 25 records, what does this code display?

```
rs.Open "SELECT * FROM Student", cn, adOpenStatic, adLockReadOnly
rs.MoveLast
MsgBox rs.RecordCount
```

A. 25

B. 1

C. -1

D. 0

Ans: A

Explanation: A static cursor reports an accurate RecordCount.

Q200 | SQL | Database Connectivity

What does this query return?

```
SELECT TOP 3 * FROM Student ORDER BY Marks DESC
```

A. The three students with the lowest marks

B. Three randomly chosen students

C. The three students with the highest marks

D. The first three students in order of entry

Ans: C

Explanation: ORDER BY Marks DESC puts the highest marks first and TOP 3 keeps three rows.

Q201 | Code | Database Connectivity

For a table with 8 records, how many items does this code add to List1?

```
Adodc1.Recordset.MoveFirst
Do While Not Adodc1.Recordset.EOF
    List1.AddItem Adodc1.Recordset!Name
    Adodc1.Recordset.MoveNext
Loop
```

A. 7

B. 8

C. 1

D. 9

Ans: B

Explanation: The loop visits every record from first to last, and MoveNext moves it forward.

Q202 | Code | Database Connectivity

After this code runs, the variable n contains:

```
rs.Filter = "Marks >= 40"
n = 0
Do While Not rs.EOF
    n = n + 1
    rs.MoveNext
Loop
```

A. The total number of records in the table

B. The number of records with Marks of 40 or more

C. Always 0

D. The number of records with Marks below 40

Ans: B

Explanation: Filter shows only the matching records, so the loop counts only those.

Q203 | Concept | Database Connectivity

Which expression gives the number of fields (columns) in a Recordset?

A. `rs.Columns.Count`
B. `rs.FieldCount`
C. `rs.RecordCount`
D. `rs.Fields.Count`

Ans: D

Explanation: The Fields collection holds the columns. RecordCount holds the rows.

Q204 | Concept | Database Connectivity

What is the correct order of steps to display records using ADO code?

A. Open Recordset, add ADO reference, create Connection, process records, close objects
B. Add ADO reference, create Connection, open it, open Recordset, process records, close objects
C. Add ADO reference, open Recordset, create Connection, open Connection, process records
D. Create Recordset, open Connection, add ADO reference, process records, close objects

Ans: B

Explanation: A Recordset needs an open Connection (or its own connection string) before records are processed.

Q205 | Code | Database Connectivity

Which constant makes Find search towards the beginning of the Recordset?

A. `adSearchReverse`
B. `adSearchBackward`
C. `adSeekBefore`
D. `adBackward`

Ans: B

Explanation: Example: rs.Find "Marks > 90", , adSearchBackward.

Q206 | Concept | Database Connectivity

Which collection of the Connection object holds errors returned by the data provider?

A. Errors
B. Properties
C. Parameters
D. Fields

Ans: A

Explanation: Each provider error appears as an Error object in Connection.Errors.

Q207 | Scenario | Database Connectivity

Adodc1.RecordSource is changed to an SQL SELECT statement at run time, but the grid stays empty or errors out, because CommandType is still adCmdTable. What is the best fix?

A. Set the DataField of the grid to the table name
B. Set CommandType to adCmdText and call Adodc1.Refresh
C. Call Adodc1.Update
D. Set Adodc1.EOFAction = adDoAddNew

Ans: B

Explanation: CommandType must match the kind of RecordSource, and Refresh re-runs it.

Q208 | Concept | Database Connectivity

Which cursor type should be chosen for a Recordset that needs forward and backward movement and an accurate RecordCount, but need not show other users' changes?

A. adOpenKeyset
B. adOpenForwardOnly
C. adOpenStatic
D. adOpenDynamic

Ans: C

Explanation: A static cursor is a fixed snapshot that supports scrolling and RecordCount.

Q209 | Concept | Database Connectivity

Which statement about the ADO Data Control is FALSE?

A. It has buttons to move between records
B. It needs a ConnectionString or Data Link to reach the data
C. It contains an ADO Recordset
D. It can be bound to only one control at a time

Ans: D

Explanation: Many controls can be bound to one data control through their DataSource property.

SECTION 12 ANSWER KEY

Q1 - Q209 | 209 questions

1 D	2 B	3 C	4 D	5 B	6 B	7 B	8 A	9 A	10 B
11 D	12 B	13 C	14 C	15 D	16 B	17 A	18 C	19 D	20 D
21 B	22 A	23 B	24 D	25 C	26 A	27 B	28 D	29 D	30 D
31 D	32 B	33 C	34 D	35 A	36 D	37 D	38 C	39 A	40 D
41 D	42 A	43 D	44 A	45 C	46 C	47 B	48 A	49 A	50 C
51 A	52 C	53 D	54 B	55 D	56 C	57 A	58 C	59 C	60 A
61 A	62 B	63 B	64 D	65 C	66 D	67 C	68 C	69 B	70 C
71 B	72 D	73 D	74 C	75 C	76 B	77 A	78 B	79 D	80 A
81 B	82 D	83 A	84 A	85 A	86 D	87 C	88 C	89 A	90 B
91 C	92 B	93 A	94 A	95 C	96 B	97 C	98 A	99 D	100 A
101 D	102 D	103 A	104 A	105 D	106 B	107 B	108 C	109 C	110 C
111 D	112 C	113 C	114 A	115 C	116 D	117 C	118 A	119 D	120 B
121 A	122 B	123 B	124 C	125 D	126 A	127 C	128 B	129 A	130 D
131 B	132 C	133 C	134 A	135 C	136 B	137 C	138 A	139 A	140 D
141 D	142 A	143 D	144 C	145 B	146 C	147 C	148 B	149 C	150 A
151 B	152 D	153 C	154 D	155 A	156 C	157 D	158 A	159 D	160 D
161 B	162 B	163 C	164 A	165 B	166 B	167 A	168 A	169 D	170 C
171 D	172 B	173 A	174 C	175 B	176 B	177 A	178 A	179 B	180 B
181 D	182 C	183 B	184 D	185 D	186 A	187 A	188 B	189 A	190 A
191 B	192 D	193 C	194 A	195 C	196 D	197 B	198 A	199 A	200 C
201 B	202 B	203 D	204 B	205 B	206 A	207 B	208 C	209 D	

Distribution of correct answers: A = 53, B = 52, C = 52, D = 52