

# Identity and Access Management in AWS (IAM)

# IAM

- **Close control-** who(U), which(A) and what(R)
- AWS Group-block network traffic based on IP or traffic type(protocol or port number)
- Give Users Unique account identities- IAM Service
- Manage users, authentication credentials, password rotation policies, Multi-factor authentication (MFA)
- Access via Console, CLI, SDK or as HTTPS API.

# Root Account vs IAM User

- Sign up to use AWS
- Using email and password
- Unrestricted access to all resources inc billing , account settings and pwd policy
- Additional layer by MFA- both pwd and authentication code 6 digit numeric code
- MFA device- hardware(Germalto) or Virtual(Google authenticator)



Services ▾

Resource Groups ▾



Dr Sandeep K Singh ▾

Global ▾

Support ▾

Search IAM

Dashboard

Groups

Users

Roles

Policies

Identity providers

Account settings

Credential report

Encryption keys

## Welcome to Identity and Access Management

IAM users sign-in link:

<https://951169881444.signin.aws.amazon.com/console>

[Customize](#)

### IAM Resources

Users: 1

Roles: 2

Groups: 0

Identity Providers: 0

[Customer Managed Policies: 0](#)

### Security Status

2 out of 5 complete.



Delete your root access keys



Activate MFA on your root account



Create individual IAM users



Use groups to assign permissions



Apply an IAM password policy



## Feature Spotlight



## Additional Information

[IAM best practices](#)

[IAM documentation](#)

[Web Identity Federation Playground](#)

[Policy Simulator](#)

[Videos, IAM release history and additional resources](#)

# Users

- . IAM user – a user or an application -no power
- . Dedicated sign-in link, pwd and access keys.
- . IAM Account within an root account
- . As top root owner you can create accounts, assign policies, generate passwords and security credentials.
- . IAM tags are **key-value pairs** you can add to your user.
- . Tags can include user information, such as an email address, or can be descriptive, such as a job title. You can use the tags to organize, track, or control access for this user.

←→↺🏠

🔒https://console.aws.amazon.com/iam/home?region=ap-south-1#/users

📖☆

☆📌📄⋮

aws

Services ▾Resource Groups ▾📌

🔔

Dr Sandeep K Singh ▾Global ▾Support ▾

Search IAM

Dashboard

Groups

Users

Roles

Policies

Identity providers

Account settings

Credential report

Encryption keys

Add userDelete user

🔄⚙️❓

🔍Find users by username or access key

Showing 1 result

<input type="checkbox"/>	User name ▾	Groups	Access key age	Password age	Last activity	MFA
<input type="checkbox"/>	sandeep	None	✔️74 days	74 days	None	Not enabled



Services ▾

Resource Groups ▾



Dr Sandeep K Singh ▾

Global ▾

Support ▾

## Select AWS access type

Select how these users will access AWS. Access keys and autogenerated passwords are provided in the last step. [Learn more](#)

Access type\* ☒

**Programmatic access**

Enables an **access key ID** and **secret access key** for the AWS API, CLI, SDK, and other development tools.



**AWS Management Console access**

Enables a **password** that allows users to sign-in to the AWS Management Console.

Console password\* ☒

Autogenerated password



Custom password

Require password reset ☒

User must create a new password at next sign-in

Users automatically get the [IAMUserChangePassword](#) policy to allow them to change their own password.

\* Required

[Cancel](#)

[Next: Permissions](#)

# Add user

- 1
- 2
- 3
- 4
- 5

## Add tags (optional)

IAM tags are key-value pairs you can add to your user. Tags can include user information, such as an email address, or can be descriptive, such as a job title. You can use the tags to organize, track, or control access for this user. [Learn more](#)

Key	Value (optional)	Remove
<input type="text" value="Add new key"/>	<input type="text"/>	

You can add 50 more tags.



### User details

<b>User name</b>	Steve
<b>AWS access type</b>	Programmatic access and AWS Management Console access
<b>Console password type</b>	Custom
<b>Require password reset</b>	Yes
<b>Permissions boundary</b>	Permissions boundary is not set

### Permissions summary

The user shown above will be added to the following groups.

Type	Name
Managed policy	<a href="#">IAMUserChangePassword</a>

### Tags

No tags were added.



Search IAM

- Dashboard
- Groups
- Users
- Roles
- Policies
- Identity providers
- Account settings
- Credential report
- Encryption keys

# Summary

Delete user

?

User ARN

am:aws:iam::951169881444:user/Steve

Path

/

Creation time

2019-03-23 04:16 UTC+0530

- Permissions
- Groups
- Tags
- Security credentials
- Access Advisor

▼ Permissions policies (1 policy applied)

Add permissions

+ Add inline policy


Policy name ▾	Policy type ▾	
Attached directly		
▶ IAMUserChangePassword	AWS managed policy	✕

▶ Permissions boundary (not set)


# Add user

- 1
- 2
- 3
- 4
- 5


## ▾ Set permissions



Add user to group



Copy permissions from existing user



Attach existing policies directly

Add user to an existing group or create a new one. Using groups is a best-practice way to manage user's permissions by job functions. [Learn more](#)

## Add user to group

Create group

🔄 Refresh

🔍 Search

Showing 1 result

Group ▾	Attached policies
<input checked="" type="checkbox"/> designteam	AmazonS3FullAccess

# Policies: who, which and what

- JSON Document- grant permission to user, group and role
- User based or resource based
- Principal defined by Amazon Resource Names (ARN)
- Policy Action
- Target Resource identified by its ARN

Search IAM

- Dashboard
  - Groups
  - Users
  - Roles
  - Policies**
  - Identity providers
  - Account settings
  - Credential report
- 
- Encryption keys

# Summary

**Policy ARN**    `arn:aws:iam::aws:policy/AdministratorAccess` 

**Description**    Provides full access to AWS services and resources.

- Permissions**
- Policy usage
- Policy versions
- Access Advisor

- Policy summary**
- `{ } JSON`



A summary for this policy cannot be generated. You can still view or edit the JSON policy document.

```
1 {
2   "Version": "2012-10-17",
3   "Statement": [
4     {
5       "Effect": "Allow",
6       "Action": "*",
7       "Resource": "*"
8     }
9   ]
10 }
```

# Group

- Logical entity to organize users.
- Members inherit from group
- Individual credentials to gain group access.
- Permit ease in binding the policies.