UN R10 (version 7.3.0)

Consolidated text of this version, rendered by Certivity for the hackathon. Cite pages of THIS file: the page number is printed at the bottom of every page.
Role in the hackathon: latest version.

0. Introduction

0.1. Supplement 3 to the 07 series of amendments is introduced to take into account vehicles of categories X and Y [1], as well as conventional vehicles which are equipped with an Automated Driving System (ADS) [1].

0.1.1. The Regulation was originally drafted for vehicles with driver's compartment and manual driving controls. It is the intention of this amendment to keep the spirit of the Regulation and to extend its application to vehicles without driver, driver's compartment and without manual driving controls in the vehicle.

0.1.2. Vehicles equipped with an ADS can be tested using an ADS test configuration. The aim of the ADS test configuration is to enable the functioning of an ADS feature in the test facility. Different test configurations may be created for the different test conditions (e.g. for emissions, immunity testing).

1. Scope

This Regulation applies to:

1.1. Vehicles of categories L, M, N O, T, R and S[1] with regard to electromagnetic compatibility;

[1] As defined in the Consolidated Resolution on the Construction of Vehicles (R.E.3.), document ECE/TRANS/WP.29/78/Rev.8.

1.2. Components and separate technical units intended to be fitted in these vehicles with the limitation given in paragraph 3.2.1. with regard to electromagnetic compatibility.

1.3. It covers:

(a) Requirements regarding the immunity to radiated and conducted disturbances for functions related to direct control of the vehicle**,** including control by an ADS, related to driver, passenger and other road users' protection, related to disturbances, which would cause confusion to the driver, ADS or other road users, related to vehicle data bus functionality, related to disturbances, which would affect vehicle statutory data;

(b) Requirements regarding the control of unwanted radiated and conducted emissions to protect the intended use of electrical or electronic equipment at own or adjacent vehicles or nearby, and the control of disturbances from accessories that may be retrofitted to the vehicle;

(c) Additional requirements for vehicles and ESAs providing coupling systems for charging the REESS regarding the control of emissions and immunity from this connection between vehicle and power grid.

Note: The immunity levels stated in this Regulation ensure robustness of vehicle systems in the electromagnetic environment and therefore address one of the external environments to be considered for functional safety (e.g. in ISO 26262).

2. Definitions

For the purposes of this Regulation:

2.1. "*Electromagnetic compatibility*" means the ability of a vehicle or component(s) or separate technical unit(s) to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment.

2.2. "*Electromagnetic disturbance*" means any electromagnetic phenomenon which may degrade the performance of a vehicle or component(s) or separate technical unit(s), or of any other device, unit of equipment or system

operated in vicinity of a vehicle. An electromagnetic disturbance may be electromagnetic noise, an unwanted signal or a change in the propagation medium itself.

2.3. "*Electromagnetic immunity*" means the ability of a vehicle or component(s) or separate technical unit(s) to operate without degradation of performance in the presence of (specified) electromagnetic disturbances which includes wanted radio frequency signals from radio transmitters or radiated in-band emissions of industrial-scientific-medical (ISM) apparatus, internal or external to the vehicle.

2.4. "*Electromagnetic environment*" means the totality of electromagnetic phenomena existing at a given location.

2.5. "*Broadband emission*" means an emission, which has a bandwidth greater than that of a particular measuring apparatus or receiver (International Special Committee on Radio Interference (CISPR) 25).

2.6. "*Narrowband emission*" means an emission which has a bandwidth less than that of a particular measuring apparatus or receiver (CISPR 25).

2.7. "*Electrical/electronic system*" means (an) electrical and/or electronic device(s) or set(s) of devices together with any associated electrical connections which form part of a vehicle but which are not intended to be type approved separately from the vehicle.

2.8. "*Electrical/electronic sub-assembly*" (ESA) means an electrical and/or electronic device or set(s) of devices intended to be part of a vehicle, together with any associated electrical connections and wiring, which performs one or more specialized functions. An ESA may be approved at the request of a manufacturer or his authorized representative as either a "component" or a "separate technical unit (STU)".

2.9. "*Vehicle type*" in relation to electromagnetic compatibility includes all vehicles, which do not differ essentially in such respects as:

2.9.1. The overall size and shape of the engine compartment;

2.9.2. The general arrangement of the electrical and/or electronic components and the general wiring arrangement;

2.9.3. The primary material of which the body or shell of the vehicle is constructed (for example, a steel, aluminium or fiberglass body shell). The presence of panels of different material does not change the vehicle type provided the primary material of the body is unchanged. However, such variations shall be notified.

2.9.4. Presence of an ADS

2.10. An "*ESA type*" in relation to electromagnetic compatibility means ESAs, which do not differ in such essential respects as:

2.10.1. The function performed by the ESA;

2.10.2. The general arrangement of the electrical and/or electronic components, if applicable.

2.11. "*Vehicle wiring harness*" means supply voltage, bus system (e.g. CAN), signal or active antenna cables, which are installed by the vehicle manufacturer.

2.12. "Immunity related functions" are the following functions; this list is not exhaustive and shall be adapted to the technical evolution of vehicle/technology:

(a) Functions related to the direct control of the vehicle:

(i) By degradation or change in: e.g. engine, gear, brake,

suspension, active steering, speed limitation devices;

(ii) By affecting drivers position, if applicable: e.g. seat or steering wheel positioning;

(iii) By affecting driver's visibility, if applicable: e.g. dipped beam, windscreen wiper, indirect vision systems, blind spot systems.

(b) Functions related to driver, passenger and other road user protection:

(i) E.g. airbag and safety restraint systems, emergency calling systems;

(c) Functions which, when disturbed, cause confusion to the driver or other road users:

(i) Optical disturbances: incorrect operation of e.g. direction indicators, stop lamps, end outline marker lamps, rear position lamp, light bars for emergency system, wrong information from warning indicators, lamps or displays related to functions in Subparagraphs (a) or (b) which might be observed in the direct view of the driver, if applicable.

(ii) Acoustical disturbances: incorrect operation of e.g. anti-theft alarm, horn.

(d) Functions related to vehicle data bus functionality:

(i) By blocking data transmission on vehicle data bus-systems, which are used to transmit data, required to ensure the correct functioning of other immunity related functions.

(e) Functions which when disturbed affect vehicle statutory data: e.g.

tachograph, odometer, event data recorder and data storage system for Automated Driving (DSSAD);

(f) Functions related to charging mode when coupled to the power grid:

(i) For vehicle test: by leading to unexpected vehicle motion;

(ii) For ESA test: by leading to an incorrect charging condition (e.g. over-current, over-voltage).

(g) Functions related to the ADS, which when disturbed, result in degradation or change of performance.

2.13. "*REESS*" means the rechargeable energy storage system that provides electric energy for electric propulsion of the vehicle.

2.14. "*Coupling system for charging the REESS*" means the electrical circuit installed in the vehicle used for charging the REESS.

2.15. "*REESS charging mode coupled to the power grid*" means the normal charging operation mode of the vehicle and/or charging system.

2.16. "*Mode 1 Charging Mode"* means charging mode as defined in IEC 61851-1 Subclause 6.2.1 where the vehicle is connected directly to AC mains without any communication between the vehicle and the charging station and without any supplementary pilot or auxiliary contacts. In some countries Mode 1 charging may be prohibited or requires special pre-cautions.

2.17. "*Mode 2 Charging Mode"* means charging mode as defined in IEC 61851-1 Subclause 6.2.2 where the vehicle is connected to AC mains using a charging harness including an Electric Vehicle Supply Equipment (EVSE) box providing control pilot signalling between the vehicle and the EVSE box and personal protection against electric shock. In some countries, special restrictions have to be applied for mode 2 charging. There is no communication between the vehicle and the AC supply network (mains).

2.18. "*Mode 3 Charging Mode"* means charging mode as defined in IEC 61851-1 Subclause 6.2.3 where the vehicle is connected to an EVSE (e.g charging station, wallbox) providing AC power to the vehicle with communication between the vehicle and the charging station (through signal/control lines and/or through wired network lines).

2.19. "*Mode 4 Charging Mode"*means charging mode as defined in IEC 61851-1 Subclause 6.2.4 where the vehicle is connected to an EVSE providing DC power to the vehicle (with an off-board charger) with communication between the vehicle and the charging station (through signal/control lines and/or through wired network lines)

2.20. "*Signal/control port*" means port intended for the interconnection of components of an ESA, or between an ESA and local AE (Auxiliary Equipment) and used in accordance with relevant functional specifications (for example for the maximum length of cable connected to it). Examples include RS-232, Universal Serial Bus

(USB), High-Definition Multimedia Interface (HDMI), IEEE Standard 1394 (“Fire Wire”). For vehicle in charging mode this includes Control Pilot signal, PLC technology used on Control Pilot signal line, CAN.

2.21. "*Wired network port”* means port for the connection of voice, data and signaling transfers intended to interconnect widely dispersed systems by direct connection to a single-user or multi-user communication network. Examples of these include CATV, PSTN, ISDN, xDSL, LAN and similar networks. These ports may support screened or unscreened cables and may also carry AC or DC power where this is an integral part of the telecommunication specification.

2.22. "*Asymmetric artificial network (AAN)”* means network used to measure (or inject) asymmetric (common mode) voltages on unshielded symmetric signal (e.g. telecommunication) lines while rejecting the symmetric (differential mode) signal. This network is inserted in the communication/signal lines of the vehicle in charging mode to provide a specific load impedance and/or a decoupling (e.g. between communication/signal lines and power mains). AAN is also used in this regulation for symmetric lines

2.23. "*Direct current charging artificial network (DC-charging-AN)* means network inserted in the high voltage DC lead of vehicle in charging mode which provides, in a given frequency range, a specified load impedance and which may isolate the vehicle from the HV DC charging station in that frequency range.

2.24. "*Artificial mains network (AMN)”* means provides a defined impedance to the ESA at radio frequencies, couples the disturbance voltage to the measuring receiver and decouples the test circuit from the supply mains. There are two basic types of AMN, the V-network (V-AMN) that couples the unsymmetrical voltages, and the delta-network that couples the symmetric and the asymmetric voltages separately. The terms line impedance stabilization network (LISN) and V-AMN are used interchangeably. Network inserted in the power mains of the vehicle in charging mode which provides, in a given frequency range, a specified load impedance and which isolates the vehicle from the power mains in that frequency range.

2.25. "Outdoor Test Site (OTS)” measurement site similar to an open area test site as specified in CISPR 16, however a ground plane is not required and there are dimensional changes.

2.26. “*Failure situations*” involve those in which the ADS or another vehicle system experiences a fault or failure that removes or reduces the ADS’s ability to perform the DDT, such as sensor or computer failure or a failed propulsion system.

2.27. “*Residential environment*” refers to Clause 3.1.14 of IEC 61000-6-3: 2020.
Area of land designated for domestic dwellings where the mains power within these locations is directly connected to the low-voltage (lower than 1000 V a.c. and 1500 V d.c.) public mains network.
Note 1 to entry: Examples of residential locations are: houses, apartments, farm buildings housing people.
Note 2 to entry: A dwelling can be a single building, separate building or a separate section of a larger building.
Note 3 to entry: Within these locations it is expected to operate a radio receiver within a distance of 10 m from the equipment.
Note 4 to entry: Domestic dwellings are places for one or more people to live.

2.28. “*Non-residential environment*” refers to Clause 3.1.12 of IEC 61000-6-4:2018.
Location characterized by a separate power network, supplied from a high- or medium-voltage transformer, dedicated for the supply of the installation.
Note 1 to entry: Industrial locations can generally be described by the existence of an installation with one or more of the following characteristics:
• items of equipment installed and connected together and working simultaneously;
• significant amount of electrical power generated, transmitted and/or consumed;
• frequent switching of heavy inductive or capacitive loads;
• high currents and associated magnetic fields;
• presence of industrial, high power scientific and medical (ISM) equipment (for example, welding machines).

The electromagnetic environment at an industrial location is predominantly produced by the equipment and installation present at the location. There are types of industrial locations where some of the electromagnetic phenomena appear in a more severe degree than in other installations.
Example locations include metalworking, pulp and paper, chemical plants, car production, farm building, high voltage areas of airports.

2.29. "*Acoustic Vehicle Alerting System (AVAS)*" as defined in the latest series of amendments to UN Regulation No. 138.

2.30. "*Accident Emergency Call Systems (AECS)*" as defined in the latest series of amendments to UN Regulation No. 144.

2.31. "*Auxiliary Equipment (AE)*" means equipment needed to exercise or monitor the operation of the test object.

2.32. *"ADS test configuration"* means a mode of operation of an ADS which enables the activation of an ADS feature in the test facility.

2.33. "*Lowest usable frequency (LUF)"* means lowest frequency for which the field uniformity requirements are met.

3. Application for approval

3.1. Approval of a vehicle type

3.1.1. The application for approval of a vehicle type, with regard to its electromagnetic compatibility, shall be submitted by the vehicle manufacturer.

3.1.2. A model of information document is shown in Annex 2A.

3.1.3. The vehicle manufacturer shall draw up a schedule describing all relevant vehicle electrical/electronic systems or ESAs, body styles, variations in body material, general wiring arrangements, engine variations, left-hand/right-hand drive versions and wheelbase versions. Relevant vehicle electrical/electronic systems or ESAs are those which may emit significant broadband or narrowband radiation and/or those which are involved in immunity related functions of the vehicle (see paragraph 2.12.) and those which provide coupling systems for charging the REESS.

3.1.4. A vehicle representative of the type to be approved shall be selected from this schedule by mutual agreement between the manufacturer and the Type Approval Authority. The choice of vehicle shall be based on the electrical/electronic systems offered by the manufacturer. One or more vehicles may be selected from this schedule if it is considered by mutual agreement between the manufacturer and the Type Approval Authority that different electrical/electronic systems are included which are likely to have a significant effect on the vehicle's electromagnetic compatibility compared with the first representative vehicle.

3.1.5. The choice of the vehicle(s) in conformity with paragraph 3.1.4. above shall be limited to vehicle/electrical/electronic system combinations intended for actual production.

3.1.6. The manufacturer may supplement the application with a report on tests which have been carried out. Any such data provided may be used by the Type Approval Authority for the purpose of drawing up the communication form for type approval.

3.1.7. If the Technical Service responsible for the type approval test carries out the test itself, then a vehicle representative of the type to be approved according to paragraph 3.1.4. above shall be provided.

3.1.8. For vehicles of categories L_6, L_7, M, N, O, T, R and S, the vehicle manufacturer shall provide a statement of frequency bands, power levels, antenna positions and installation provisions for the installation of radio frequency transmitters (RF-transmitters), even if the vehicle is not equipped with an RF transmitter at time of type approval, and this statement shall be noted in the information document (e.g. under item 63, Annex 2A). This


should cover all mobile radio services normally used in vehicles. This information shall be made publicly available following the type approval.

Vehicle manufacturers shall provide evidence that vehicle performance is not adversely affected by such transmitter installations.

3.1.9. If a driver's seat is fitted but it is not the front seat nearest to the opposing traffic, the applicant shall specify this seating position.

3.2. ESA type approval

3.2.1. Applicability of this Regulation to ESA:



3.2.2. The application for approval of a type of ESA with regard to its electromagnetic compatibility shall be submitted by the vehicle manufacturer or by the manufacturer of the ESA.

3.2.3. A model of information document is shown in Annex 2B.

3.2.4. The manufacturer may supplement the application with a report on tests which have been carried out. Any such data provided may be used by the Type Approval Authority for the purpose of drawing up the communication form for type approval.

3.2.5. If the Technical Service responsible for the type approval test carries out the test itself, then a sample of the ESA system representative of the type to be approved shall be provided, if necessary, after discussion with the manufacturer on, e.g. possible variations in the layout, number of components, number of sensors. If the Technical Service deems it necessary, it may select a further sample.

3.2.6. The sample(s) shall be clearly and indelibly marked with the manufacturer's trade name or mark and the type designation.

3.2.7. Where applicable, any restrictions on use should be identified. Any such restrictions should be included in Annexes 2B and/or 3B.

3.2.8. ESA which are brought to the market as replacement parts do not need a type approval if they are obviously marked as a replacement part by an identification number and if they are identical and from the same manufacturer as the corresponding original equipment.

3.2.9. Components sold as aftermarket equipment and intended for the installation in motor vehicles need no type approval if they are not related to immunity related functions (see paragraph 2.12.). In this case a declaration shall be issued by the manufacturer that the ESA fulfils the requirements of this Regulation and in particular the limits defined in paragraphs 6.5., 6.6., 6.7., 6.8. and 6.9. of this Regulation.

3.2.10. In case of an ESA is (part of) a light source, the applicant shall:

(a) Specify the approval number according to Regulation No. 37, Regulation No. 99 or Regulation No. 128, granted to this ESA;

or

(b) Provide a test report by a Technical Service designated by the Type Approval Authority, stating that this ESA is not mechanically interchangeable with any light source according to Regulation No. 37, Regulation No. 99 or Regulation No. 128.

4. Approval

4.1. Type approval procedures

4.1.1. Type approval of a vehicle

The following alternative procedures for vehicle type approval may be used at the discretion of the vehicle manufacturer.

4.1.1.1. Approval of a vehicle installation

A vehicle installation may be type approved directly by following the provisions laid down in paragraph 6. and, if applicable, in paragraph 7. of this Regulation. If this procedure is chosen by a vehicle manufacturer, no separate testing of electrical/electronic systems or ESAs is required.

4.1.1.2. Approval of vehicle type by testing of individual ESAs.

A vehicle manufacturer may obtain approval for the vehicle by demonstrating to the Type Approval Authority that all the relevant (see paragraph 3.1.3. of this Regulation) electrical/electronic systems or ESAs have been approved in accordance with this Regulation and have been installed in accordance with any conditions attached thereto.

4.1.1.3. A manufacturer may obtain approval according to this Regulation if the vehicle has no equipment of the type, which is subject to immunity or emission tests. Such approvals do not require testing.

4.1.2. Type approval of an ESA

Type approval may be granted to an ESA to be fitted either to any vehicle type (component approval) or to a specific vehicle type or types requested by the ESA manufacturer (separate technical unit approval).

4.1.3. ESAs, which are intentional RF transmitters, which have not received type approval in conjunction with a vehicle manufacturer, shall be supplied with suitable installation guidelines.

4.2. Granting of type approval

4.2.1. Vehicle

4.2.1.1. If the representative vehicle fulfils the requirements of paragraph 6. and, if applicable, paragraph 7. of this Regulation, type approval shall be granted.

4.2.1.2. A model of communication form for type approval is contained in Annex 3A.

4.2.2. ESA

4.2.2.1. If the representative ESA system(s) fulfil(s) the requirements of paragraph 6. and, if applicable, paragraph 7. of this Regulation, type approval shall be granted.

4.2.2.2. A model of communication form for type approval is contained in Annex 3B.

4.2.3. In order to draw up the communication forms referred to in paragraph 4.2.1.2. or 4.2.2.2. above, the Type Approval Authority of the Contracting Party granting the approval may use a report prepared or approved by a recognized laboratory or in accordance with the provisions of this Regulation.

4.2.4. In case of an ESA is (part of) a light source and if the documentation as specified in paragraph 3.2.10. above is missing, approval of this ESA according to Regulation No. 10 shall not be granted.

4.3. Approval, or refusal of approval, of a type of vehicle or ESA in accordance with this Regulation shall be notified to the Parties to the Agreement applying this Regulation on a form conforming to the model in Annex 3A or 3B to this Regulation, accompanied by photographs and/or diagrams or drawings on an appropriate scale supplied by the applicant in a format not larger than A4 (210 x 297 mm) or folded to those dimensions.

5. Markings

5.1. An approval number shall be assigned to each vehicle or ESA type approved in accordance with Schedule 4 of the 1958 Agreement (E/ECE/TRANS/505/Rev.3).

5.2. Presence of markings

5.2.1. Vehicle

An approval mark described in paragraph 5.3. below shall be affixed to every vehicle conforming to a type approved under this Regulation.

5.2.2. Electrical/electronic sub-assembly (ESA)

An approval mark described in paragraph 5.3. below shall be affixed to every ESA conforming to a type approved under this Regulation.

No marking is required for electrical/electronic systems built into vehicles which are approved as units.

5.3. An international approval mark shall be affixed, in a conspicuous and easily accessible place specified on the approval communication form, on each vehicle conforming to the type approved under this Regulation. This mark shall comprise:

5.3.1. A circle containing the letter "E", followed by the distinguishing number of the country granting the approval.[2]

[2]The distinguish numbers of the Contracting Parties to the 1958 Agreement are reproduced in Annex 3 to Consolidated Resolution on the Construction of Vehicles (R.E.3), document ECE/TRANS/WP.29/78/Rev.6, Annex 3.

5.3.2. The number of this Regulation, followed by the letter "R", a dash and the approval number to the right of the circle specified in paragraph 5.3.1. above.

5.4. An example of the type approval mark is shown in Annex 1 to this Regulation.

5.5. Markings on ESAs in conformity with paragraph 5.3. above need not be visible when the ESA is installed in the vehicle.

6. Specification in configurations other than REESS charging mode coupled to the power grid

6.1. General specifications

6.1.1. A vehicle and its electrical/electronic system(s) or ESA(s) shall be designed, constructed and fitted in such a way as to enable the vehicle, in normal conditions of use, to comply with the requirements of this Regulation.

6.1.1.1. A vehicle shall be tested for radiated emissions and for immunity to radiated disturbances. No tests for conducted emissions or immunity to conducted disturbances are required for vehicle type approval.

6.1.1.2. ESA(s) shall be tested for radiated and conducted emissions, for immunity to radiated and conducted disturbances.

6.1.2. Before testing, the Technical Service shall prepare a test plan in conjunction with the manufacturer, which contains at least mode of operation, stimulated function(s), monitored function(s), pass/fail criterion(criteria) and intended emissions.

Depending on the intended operating conditions of the propulsion system, the test plan shall define the minimum number of steady state operating conditions of the vehicle, selectable by the driver or by the control system. The test conditions shall consider multiple propulsion system operating strategies which can be activated permanently by the driver or the vehicle control system and shall be based on documentation provided in Annexes 2A and 2B (e.g. risk analysis).

6.2. Specifications concerning broadband electromagnetic radiation from vehicles

6.2.1. Method of measurement

The electromagnetic radiation generated by the vehicle representative of its type shall be measured using the method described in Annex 4. The method of measurement shall be defined by the vehicle manufacturer in accordance with the Technical Service.

6.2.2. Vehicle broadband type approval limits

6.2.2.1. If measurements are made using the method described in Annex 4 using a vehicle-to-antenna spacing of 10.0 ± 0.2 m, the limits shall be 32 dB microvolts/m in the 30 to 75 MHz frequency band and 32 to 43 dB microvolts/m in the 75 to 400 MHz frequency band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 2 to this Regulation. In the 400 to 1,000 MHz frequency band the limit remains constant at 43 dB microvolts/m.

6.2.2.2. If measurements are made using the method described in Annex 4 using a vehicle-to-antenna spacing of 3.0 ± 0.05 m, the limits shall be 42 dB microvolts/m in the 30 to 75 MHz frequency band and 42 to 53 dB microvolts/m in the 75 to 400 MHz frequency band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 3 to this Regulation. In the 400 to 1,000 MHz frequency band the limit remains constant at 53 dB microvolts/m.

6.2.2.3. On the vehicle representative of its type, the measured values, expressed in dB microvolts/m shall be below the type approval limits.

6.3. Specifications concerning narrowband electromagnetic radiation from vehicles

6.3.1. Method of measurement

The electromagnetic radiation generated by the vehicle representative of its type shall be measured using the method described in Annex 5. These shall be defined by the vehicle manufacturer in accordance with the

Technical Service.

6.3.2. Vehicle narrowband type approval limits

6.3.2.1. If measurements are made using the method described in Annex 5 using a vehicle-to-antenna spacing of 10.0 ± 0.2 m, the limits shall be 28 dB microvolts/m in the 30 to 230 MHz frequency band and 35 dB microvolts/m in the 230 to 1,000 MHz frequency band.

6.3.2.2. If measurements are made using the method described in Annex 5 using a vehicle-to-antenna spacing of 3.0 ± 0.05 m, the limits shall be 38 dB microvolts/m in the 30 to 230 MHz frequency band and 45 dB microvolts/m in the 230 to 1,000 MHz frequency band.

6.3.2.3. On the vehicle representative of its type, the measured values, expressed in dB microvolts/m, shall be below the type approval limit.

6.4. Specifications concerning immunity of vehicles to electromagnetic radiation

6.4.1. Method of testing

The immunity to electromagnetic radiation of the vehicle representative of its type shall be tested by the method described in Annex 6.

6.4.2. Vehicle immunity type approval limits

6.4.2.1. If tests are made using the method described in Annex 6, in accordance with ISO 11451-2, the field strength shall be 30 volts/m in over 90 per cent of the 20 to 2,000 MHz frequency band and a minimum of 25 volts/m over the whole 20 to 2,000 MHz frequency band. The field strength shall be 10 volts/m in over 90 per cent of the 2,000 to 6,000 MHz frequency band and a minimum of 8 volts/m over the whole 2,000 to 6,000 MHz frequency band.

If tests are made using the method described in Annex 6, in accordance with ISO 11451-4 BCI the current shall be 60 mA in over 90 per cent of the 20 to 2,000 MHz frequency band and a minimum of 50 mA over the whole 20 to 2,000 MHz frequency band.

6.4.2.2. The vehicle representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 6, there shall be no degradation of performance of "immunity related functions", according to paragraph 2.1. of Annex 6.

6.5. Specification concerning broadband electromagnetic interference generated by ESAs

6.5.1. Method of measurement

The electromagnetic radiation generated by the ESA representative of its type shall be measured by the method described in Annex 7.

6.5.2. ESA broadband type approval limits

6.5.2.1. If measurements are made using the method described in Annex 7, the limits shall be 62 to 52 dB microvolts/m in the 30 to 75 MHz frequency band, this limit decreasing logarithmically with frequencies above 30 MHz, and 52 to 63 dB microvolts/m in the 75 to 400 MHz band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 6 to this Regulation. In the 400 to 1,000 MHz frequency band the limit remains constant at 63 dB microvolts/m.

6.5.2.2. On the ESA representative of its type, the measured values, expressed in dB microvolts/m, shall be below the type approval limits.

6.6. Specifications concerning narrowband electromagnetic interference generated by ESAs

6.6.1. Method of measurement

The electromagnetic radiation generated by the ESA representative of its type shall be measured by the method described in Annex 8.

6.6.2. ESA narrowband type approval limits

6.6.2.1. If measurements are made using the method described in Annex 8, the limits shall be 52 to 42 dB microvolts/m in the 30 to 75 MHz frequency band, this limit decreasing logarithmically with frequencies above 30 MHz, and 42 to 53 dB microvolts/m in the 75 to 400 MHz band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 7. In the 400 to 1,000 MHz frequency band the limit remains constant at 53 dB microvolts/m.

6.6.2.2. On the ESA representative of its type, the measured value, expressed in dB microvolts/m shall be below the type approval limits.

6.7. Specifications concerning the emission of transient conducted disturbances generated by ESAs on 12/24 V supply lines

6.7.1. Method of testing

The emission of ESA representative of its type shall be tested by the method(s) according to ISO 7637-2 as described in Annex 10 for the levels given in Table 1.

Table 1 **Maximum allowed pulse amplitude**

	Maximum allowed pulse amplitude for	
Polarity of pulse amplitude	*Vehicles with 12 V systems*	*Vehicles with 24 V systems*
Positive	+75 V	+150 V
Negative	-100 V	-450 V

6.8. Specifications concerning immunity of ESAs to electromagnetic radiation

6.8.1. Method(s) of testing

The immunity to electromagnetic radiation of the ESA representative of its type shall be tested by the method(s) chosen from those described in Annex 9.

6.8.2. ESA immunity type approval limits

6.8.2.1. The immunity to electromagnetic radiation of ESA representative of its type shall be tested by the method(s) as described in Annex 9:

Test severity in over 90 per cent of the 20 to 6,000 MHz frequency band are given in Table 2a.

Test severity for the minimum test Level over the whole 20 to 6,000 MHz frequency band given in Table 2b.

Table 2a

	Test Level in over 90 per cent of the 20 to 6,000 MHz frequency band				
Frequency range	*Stripline*	*TEM cell*	*BCI*	*ALSE*	*Reverberation chamber*
Frequency range below 2 GHz	20 to 400 MHz	20 to 200 MHz	20 to 400 MHz	80 to 2,000 MHz	LUF to 2,000 MHz
Test level below 2 GHz	60 V/m	75 V/m	60 mA	30 V/m	21 V/m
Frequency range above 2 GHz	Not applicable	Not applicable	Not applicable	2,000 to 6,000 MHz	2,000 to 6,000 MHz
Test level above 2 GHz	Not applicable	Not applicable	Not applicable	10 V/m	7 V/m

Table 2b

	Minimum Test Level over the whole 20 to 6,000 MHz frequency band				
Frequency range	*Stripline*	*TEM cell*	*BCI*	*ALSE*	*Reverberation chamber*
Frequency range below 2 GHz	20 to 400 MHz	20 to 200 MHz	20 to 400 MHz	80 to 2,000 MHz	LUF to 2,000 MHz
Test level below 2 GHz	50 V/m	62,5 V/m	50 mA	25 V/m	18 V/m
Frequency range above 2 GHz	Not applicable	Not applicable	Not applicable	2,000 to 6,000 MHz	2,000 to 6,000 MHz
Test level above 2 GHz	Not applicable	Not applicable	Not applicable	8 V/m	6 V/m

6.8.2.2. The ESA representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 9, there shall be no degradation of performance of "immunity related functions".

6.9. Specifications concerning the immunity of ESAs to transient disturbances conducted along 12/24 V supply lines

6.9.1. Method of testing

The immunity of ESA representative of this type shall be tested by the method(s) according to ISO 16750-2 for starting profile and ISO 7637-2 for pulses 1, 2a, 2b, 3a and 3b, as described in Annex 10, with the test levels given in Tables 3a and 3b. Starting profile shall be tested according to the functional status classification as defined in ISO 16750-1. Functional Performance Status Classification (FPSC) as in ISO 7637-1 shall be applied for pulses 1, 2a, 2b, 3a and 3b.

Immunity of ESA

Table 3a

Test pulse	*Immunity test level*		*Number of pulses*	*Functional status classification for ESA:*	
	12 V system	*24 V system*		*Related to immunity related functions*	*Not related to immunity related functions*
				B	D
Starting profile	II	II	10 pulses	(for ESA which shall be operational during engine start phases) C (for other ESA)	

Table 3b

Test pulse number	*Immunity test level*		*Test duration / number of pulses*	*FPSC for ESA:*	
	12V system	*24V system*		*Related to immunity related functions*	*Not related to immunity related functions*
1	-75 V	-450 V	500 pulses	III	III

2a	+37 V	+37 V	500 pulses	I	III
2b	+10 V	+20 V	10 pulses	II	III
3a	-112 V	-150 V	1 h	I	III
3b	+75 V	+150 V	1 h	I	III

Starting profile is only applicable to ESAs that could be installed in vehicles with internal combustion engines which are started with a 12V/24V starter motor.

6.10. Exceptions

6.10.1. Where a vehicle or electrical/electronic system or ESA does not include an electronic oscillator with an operating frequency greater than 9 kHz, it shall be deemed to comply with paragraph 6.3.2. or 6.6.2. and with Annexes 5 and 8.

6.10.2. Vehicles which do not have electrical/electronic systems with "immunity related functions" need not be tested for immunity to radiated disturbances and shall be deemed to comply with paragraph 6.4. and with Annex 6 to this Regulation.

6.10.3. ESAs with no immunity related functions need not be tested for immunity to radiated disturbances and shall be deemed to comply with paragraph 6.8. and with Annex 9 to this Regulation.

6.10.4. Electrostatic discharge

For vehicles fitted with tyres, the vehicle body/chassis can be considered to be an electrically isolated structure. Significant electrostatic forces in relation to the vehicle's external environment only occur at the moment of occupant entry into or exit from the vehicle. As the vehicle is stationary at these moments, no type approval test for electrostatic discharge is deemed necessary.

6.10.5. Emission of transient conducted disturbances generated by ESAs on 12/24 V supply lines.

ESAs that are not switched, contain no switches or do not include inductive load need not be tested for transient conducted emission and shall be deemed to comply with paragraph 6.7.

6.10.6. The loss of function of receivers during the immunity test, when the test signal is within the receiver bandwidth (RF exclusion band) as specified for the specific radio service/product in the harmonized international EMC standard, does not necessarily lead to fail criteria.

6.10.7. RF transmitters shall be tested in the transmit mode. Wanted emissions (e.g. from RF transmitting systems) within the necessary bandwidth and out of band emissions are disregarded for the purpose of this Regulation. Spurious emissions are subject to this Regulation.

6.10.7.1. "*Necessary bandwidth*": For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions (Article 1, No. 1.152 of the International Telecommunication Union (ITU) Radio Regulations).

6.10.7.2. "*Out-of-band Emissions*": Emission on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process, but excluding spurious emissions (Article 1, No. 1.144 of the ITU Radio Regulations).

6.10.7.3. "*Spurious emission*": In every modulation process additional undesired signals exist. They are summarized under the expression "spurious emissions". Spurious emissions are emissions on a frequency or frequencies, which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions (Article 1 No. 1.145 of the ITU Radio Regulations).

6.10.8. Trolleybuses: AC/DC mains portion of the vehicle propulsion system shall be excluded from this Regulation.

6.11. Special requirements for vehicles equipped with an ADS

6.11.1. If not otherwise specified, all requirements to this Regulation related to the “driver” or “manual operation”, assume that no “ADS feature” is active.

6.11.2. The references to ADS features are only applicable while an ADS feature is active.

6.11.3. For vehicles equipped with an ADS, in the case where the ADS cannot be fully activated or function normally within the EMC (laboratory) test environment, the manufacturer, in agreement with the Type Approval Authority, shall propose alternative methods and/or test configurations, to ensure the ADS is evaluated in a manner which is representative of its intended on-road operation and to demonstrate compliance with the provisions of this Regulation. Alternative methods may include ESA immunity testing and/or the use of an ADS test configuration. The methods used shall be subject to agreement by the Type Approval Authority and shall be recorded and described in the test report.

Alternative method using ESA immunity to external sources according to Annex 9, which may include the evaluation of multiple modules to enable a system-level test, does not require E-marking of the concerned ESA. The test report shall be prepared by a laboratory accredited to ISO 17025 and recognized by the Type Approval Authority responsible for carrying out the tests and provided along with the information document shown in Annex 2B. The same test method (vehicle type approval in combination with ESA test report for Annex 9) shall be applied during Conformity of Production test or any applicable test method according to this Annex.

7. Additional specifications in the configuration "REESS charging mode coupled to the power grid"

7.1. General specifications

7.1.1. A vehicle and its electrical/electronic system(s) or ESA(s) shall be so designed, constructed and fitted as to enable the vehicle, in configuration "REESS charging mode coupled to the power grid", to comply with the requirements of this Regulation.

7.1.1.1. A vehicle in configuration "REESS charging mode coupled to the power grid" shall be tested for radiated emissions, immunity to radiated disturbances, conducted emissions and immunity to conducted disturbances.

7.1.1.2. ESAs in configuration "REESS charging mode coupled to the power grid" shall be tested for radiated and conducted emissions, for immunity to radiated and conducted disturbances.

7.1.2. Before testing the Technical Service shall prepare a test plan in conjunction with the manufacturer, for the configuration "REESS charging mode coupled to the power grid" configuration which contains at least mode of operation, stimulated function(s), monitored function(s), pass/fail criterion (criteria) and intended emissions.

Depending on the available charging modes of the REESS, the test plan shall define the minimum number of test conditions of the vehicle, selectable by the driver or by the control system and shall be based on documentation provided in Annexes 2A and 2B (e.g. risk analysis). Refer to flow charts in Annexes where REESS charge mode is applicable.

7.1.3. A vehicle in configuration "REESS charging mode coupled to the power grid" should be tested with the charging harness delivered by the manufacturer in line with flowcharts provided in Annexes 4, 6, 11, 12, 13, 15 and 16.

7.1.4. Artificial networks

AC Power mains shall be applied to the vehicle / ESA through 50 µH/50 Ω AMN(s) as defined in Appendix 8, paragraph 4.

DC Power mains shall be applied to the vehicle / ESA through 5 µH/50 Ω DC-charging-AN(s) as defined in Appendix 8, paragraph 3.

High voltage power line shall be applied to the ESA through a 5 µH/50 Ω HV-AN(s) as defined in Appendix 8, paragraph 2.

Signal port lines, control port lines or wired network port lines should be applied to the vehicle / ESA through an AAN as defined in Appendix 8, paragraph 5.

7.2. Specifications concerning broadband electromagnetic radiation from vehicles

7.2.1. Method of measurement

The electromagnetic radiation generated by the vehicle representative of its type shall be measured using the method described in Annex 4. The method of measurement shall be defined by the vehicle manufacturer in accordance with the Technical Service.

7.2.2. Vehicle broadband type approval limits

7.2.2.1. If measurements are made using the method described in Annex 4 using a vehicle-to-antenna spacing of 10.0 ± 0.2 m, the limits shall be 32 dB microvolts/m in the 30 to 75 MHz frequency band and 32 to 43 dB microvolts/m in the 75 to 400 MHz frequency band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 2. In the 400 to 1,000 MHz frequency band the limit remains constant at 43 dB microvolts/m.

7.2.2.2. If measurements are made using the method described in Annex 4 using a vehicle-to-antenna spacing of 3.0 ± 0.05 m, the limits shall be 42 dB microvolts/m in the 30 to 75 MHz frequency band and 42 to 53 dB microvolts/m in the 75 to 400 MHz frequency band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 3. In the 400 to 1,000 MHz frequency band the limit remains constant at 53 dB microvolts/m.

On the vehicle representative of its type, the measured values, expressed in dB microvolts/m shall be below the type approval limits.

7.3. Specifications concerning emission of harmonics on AC power lines from vehicles

7.3.1. Method of measurement

The harmonics emission on AC power lines generated by the vehicle representative of its type shall be measured using the method described in Annex 11. The method of measurement shall be defined by the vehicle manufacturer in accordance with the Technical Service.

7.3.2. Vehicle type approval limit

7.3.2.1. If measurements are made using the method described in Annex 11, the limits for input current ≤ 16 A per phase are those defined in IEC 61000-3-2-and given in Table 4.

Table 4 **Maximum allowed harmonics (input current ≤ 16 A per phase)**

Harmonic number *n*	*Maximum authorized harmonic current* *A*
Odd harmonics	
3	2.3
5	1.14
7	0.77
9	0.40

Harmonic number n	*Maximum authorized harmonic current A*
11	0.33
13	0.21
15 ≤ n ≤ 39	0.15x15/n
Even harmonics	
2	1.08
4	0.43
6	0.30
8 ≤ n ≤ 40	0.23x8/n

NOTE: For the application of limits given in Table 4, refer to IEC 61000-3-2, Clause 6.3.3.4.

7.3.2.2. If measurements are made using the method described in Annex 11, the limits for input current > 16 A and ≤ 75 A per phase are those defined in IEC 61000-3-12, and given in given in Table 5, Table 6 and Table 7.

Table 5 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for single phase or other than balanced three-phase equipment**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*						*Maximum current harmonic ratio %*	
	I_3	I_5	I_7	I_9	I_{11}	I_{13}	THD	PWHD
33	21.6	10.7	7.2	3.8	3.1	2	23	23
66	24	13	8	5	4	3	26	26
120	27	15	10	6	5	4	30	30
250	35	20	13	9	8	6	40	40
≥ 350	41	24	15	12	10	8	47	47
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the Total Harmonic Distortion (THD) and Partial Weighted Harmonic Distortion (PWHD) the same way than odd harmonics. Linear interpolation between successive values of Short Circuit Ratio of an Equipment (R_{sce}) is authorized.								

Table 6 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for balanced three-phase equipment**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
	I_5	I_7	I_{11}	I_{13}	THD	PWHD
33	10.7	7.2	3.1	2	13	22
66	14	9	5	3	16	25

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
120	19	12	7	4	22	28
250	31	20	12	7	37	38
≥ 350	40	25	15	10	48	46
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the THD and PWHD the same way than odd harmonics. Linear interpolation between successive values of R_{sce} is authorized.						

Table 7 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for balanced three-phase equipment under specific conditions**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
	I_5	I_7	I_{11}	I_{13}	THD	PWHD
33	10.7	7.2	3.1	2	13	22
≥ 120	40	25	15	10	48	46
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the THD and PWHD the same way than odd harmonics**.**						

7.4. Specifications concerning emission of voltage changes, voltage fluctuations and flicker on AC power lines from vehicles.

7.4.1. Method of measurement

The emission of voltage changes, voltage fluctuations and flicker on AC power lines generated by the vehicle representative of its type shall be measured using the method described in Annex 12. The method of measurement shall be defined by the vehicle manufacturer in accordance with the Technical Service.

7.4.2. Vehicle type approval limit

7.4.2.1. If measurements are made using the method described in Annex 12, the limits for rated current ≤ 16 A per phase and not subjected to conditional connection are those defined in IEC 61000-3-3, Clause 5:

- The value of P_{st} shall not be greater than 1.0;

- The value of P_{lt} shall not be greater than 0.65;

- The value of d(t) during a voltage change shall not exceed 3.3 per cent for more than 500 ms;

- The relative steady-state voltage change, d_c, shall not exceed 3.3 per cent;

- The maximum relative voltage change d_{max}, shall not exceed 6 per cent.

7.4.2.2. If measurements are made using the method described in Annex 12, the limits for rated current > 16 A and ≤ 75 A per phase and subjected to conditional connection are those defined in IEC 61000-3-11, Clause 5:

- The value of P_{st} shall not be greater than 1.0;

- The value of P_{lt} shall not be greater than 0.65;

- The value of d(t) during a voltage change shall not exceed 3.3 per cent for more than 500 ms;

- The relative steady-state voltage change, d_c, shall not exceed 3.3 per cent;

- The maximum relative voltage change d_{max}, shall not exceed 6 per cent.

7.5. Specifications concerning emission of radiofrequency conducted disturbances on AC or DC power lines from vehicles

7.5.1. Method of measurement

The emission of radiofrequency conducted disturbances on AC or DC power lines generated by the vehicle representative of its type shall be measured using the method described in Annex 13. The method of measurement shall be defined by the vehicle manufacturer in accordance with the Technical Service.

7.5.2. Vehicle type approval limit for vehicle charged in residential environment

7.5.2.1. If measurements are made using the method described in Annex 13, the limits on AC power lines are those defined in IEC 61000-6-3 and given in Table 8.

Table 8 **Maximum allowed radiofrequency conducted disturbances on AC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	66 to 56 dBµV	56 to 46 dBµV
	(linearly decreasing with logarithm of frequency)	
0.5 to 5	56 dBµV	46 dBµV
5 to 30	60 dBµV	50 dBµV

7.5.2.2. If measurements are made using the method described in Annex 13, the limits on DC power lines are those defined in IEC 61000-6-3 and given in Table 9.

Table 9 **Maximum allowed radiofrequency conducted disturbances on DC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	79 dBµV	66 dBµV
0.5 to 30	73 dBµV	60 dBµV

7.5.3 Vehicle type approval limit for vehicles charged in non-residential environment.

7.5.3.1. For specific vehicles which are charged only with charging stations located in area characterized by a separate power network, supplied from a high or medium voltage transformer, dedicated for the supply of the installation (buses, heavy duty trucks, etc..), limits from IEC 61000-6-4 shall be applied.

7.5.3.2. In this case, the manufacturer shall provide a statement that the vehicle can be used in "REESS charging mode coupled to the power grid" only in area characterized by a separate power network, supplied from a high or medium voltage transformer, dedicated for the supply of the installation. The manufacturer shall provide a statement that the vehicle shall be charged in non-residential environment only. This information shall be made publicly available following the type-approval.

7.5.3.3 If measurements are made using the method described in Annex 13, the limits on AC power lines are those defined in IEC 61000-6-4 and given in Table 10.

Table 10 **Maximum allowed radiofrequency conducted disturbances on AC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	79 dBµV	66 dBµV
0.5 to 30	73 dBµV	60 dBµV

7.5.3.4. If measurements are made using the method described in Annex 13, the limits on DC power lines are those defined in IEC 61000-6-4 and given in Table 11.

Table 11 **Maximum allowed radiofrequency conducted disturbances on DC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	89 dBµV	76 dBµV
0.5 to 30	83 dBµV	70 dBµV

7.6. Specifications concerning emission of radiofrequency conducted disturbances on wired network port from vehicles.

No longer applicable.

7.7. Specifications concerning immunity of vehicles to electromagnetic radiation

7.7.1. Method of testing

The immunity to electromagnetic radiation of the vehicle representative of its type shall be tested by the method described in Annex 6.

7.7.2. Vehicle immunity type approval limits

7.7.2.1. If tests are made using the method described in Annex 6, the field strength shall be 30 volts/m in over 90 per cent of the 20 to 2,000 MHz frequency band and a minimum of 25 volts/m over the whole 20 to 2,000 MHz frequency band. The field strength shall be 10 volts/m in over 90 per cent of the 2,000 to 6,000 MHz frequency band and a minimum of 8 volts/m over the whole 2,000 to 6,000 MHz frequency band.

If tests are made using the method described in Annex 6, with ISO 11451-4 BCI method the current shall be 60 mA in over 90 per cent of the 20 to 2,000 MHz frequency band and a minimum of 50 mA over the whole 20 to 2,000 MHz frequency band.

7.7.2.2. The vehicle representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 6, there shall be no degradation of performance of "immunity related functions", according to paragraph 2.2. of Annex 6.

7.8. Specifications concerning the immunity of vehicles to Electrical Fast Transient/Burst disturbances conducted along AC and DC power lines.

7.8.1. Method of testing

7.8.1.1. The immunity to Electrical Fast Transient/Burst disturbances conducted along AC and DC power lines of the vehicle representative of its type shall be tested by the method described in Annex 15.

7.8.2. Vehicle immunity type approval limits

7.8.2.1. If tests are made using the methods described in Annex 15, the immunity test levels, for AC or DC power lines, shall be: ±2 kV test voltage in open circuit, with a rise time (T_r) of 5 ns, and a hold time (T_h) of 50 ns and a repetition rate of 5 kHz for at least 1 minute.

7.8.2.2. The vehicle representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 15, there shall be no degradation of performance of "immunity related functions", according to paragraph 2.1.2. of Annex 15.

7.9. Specifications concerning the immunity of vehicles to surge conducted along AC or DC power lines.

7.9.1. Method of testing

7.9.1.1. The immunity to surge conducted along AC/DC power lines of the vehicle representative of its type shall be tested by the method described in Annex 16.

7.9.2. Vehicle immunity type approval limits

7.9.2.1. If tests are made using the methods described in Annex 16, the immunity test levels shall be:

(a) For AC power lines: ±2 kV test voltage in open circuit between line and earth and ±1 kV between lines with a rise time (T_r) of 1.2 µs, and a hold time (T_h) of 50 µs. Each surge shall be applied five times with a maximum delay of 1 minute between each pulse. This shall be applied for the following phases: 0, 90, 180 and 270°,

(b) For DC power lines: ±0.5 kV test voltage in open circuit between line and earth and ±0.5 kV between lines with a rise time (T_r) of 1.2 µs, and a hold time (T_h) of 50 µs. Each surge shall be applied five times with a maximum delay of 1 minute.

7.9.2.2. The vehicle representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 16, there shall be no degradation of performance of "immunity related functions", according to paragraph 2.1.2. of Annex 16.

7.10. Specifications concerning broadband electromagnetic interference caused by ESAs

7.10.1. Method of measurement

The electromagnetic radiation generated by the ESA representative of its type shall be measured by the method described in Annex 7.

7.10.2. ESA broadband type approval limits

7.10.2.1. If measurements are made using the method described in Annex 7, the limits shall be 62 to 52 dBµV/m in the 30 to 75 MHz frequency band, this limit decreasing logarithmically with frequencies above 30 MHz, and 52 to
63 dBµV/m in the 75 to 400 MHz band, this limit increasing logarithmically with frequencies above 75 MHz as shown in Appendix 6. In the 400 to 1,000 MHz frequency band the limit remains constant at 63 dBµV/m.

7.10.2.2. On the ESA representative of its type, the measured values, expressed in dBµV/m, shall be below the type approval limits.

7.11. Specifications concerning emission of harmonics on AC power lines from ESAs

7.11.1. Method of measurement

The harmonics emission on AC power lines generated by the ESA representative of its type shall be measured using the method described in Annex 17. The method of measurement shall be defined by the manufacturer in accordance with the Technical Service.

7.11.2. ESA type approval limit

7.11.2.1. If measurements are made using the method described in Annex 17, the limits for input current ≤ 16 A per phase are those defined in IEC 61000-3-2 and given in Table 12.

Table 12 **Maximum allowed harmonics (input current ≤ 16 A per phase)**

Harmonic number *n*	*Maximum authorized harmonic current* *A*
Odd harmonics	
3	2.3
5	1.14
7	0.77
9	0.40

Harmonic number *n*	*Maximum authorized harmonic current* *A*
11	0.33
13	0.21
15 ≤ n ≤ 39	0.15x15/n
Even harmonics	
2	1.08
4	0.43
6	0.30
8 ≤ n ≤ 40	0.23x8/n

NOTE: For the application of limits given in Table 12, refer to IEC 61000-3-2, paragraph 6.3.3.4.

7.11.2.2. If measurements are made using the method described in Annex 17, the limits for input current > 16 A and ≤ 75 A per phase are those defined in IEC 61000-3-12 and given in Table 13, Table 14 and Table 15.

Table 13 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for single phase or other than balanced three-phase equipment**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*						*Maximum current harmonic ratio %*	
	I_3	I_5	I_7	I_9	I_{11}	I_{13}	*THD*	*PWHD*
33	21.6	10.7	7.2	3.8	3.1	2	23	23
66	24	13	8	5	4	3	26	26
120	27	15	10	6	5	4	30	30
250	35	20	13	9	8	6	40	40
≥ 350	41	24	15	12	10	8	47	47
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the THD and PWHD in the same way than odd harmonics. Linear interpolation between successive values of R_{sce} is authorized.								

Table 14 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for balanced three-phase equipment**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
	I_5	I_7	I_{11}	I_{13}	*THD*	*PWHD*
33	10.7	7.2	3.1	2	13	22
66	14	9	5	3	16	25
120	19	12	7	4	22	28
250	31	20	12	7	37	38

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
≥ 350	40	25	15	10	48	46
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the THD and PWHD in the same way as odd harmonics. Linear interpolation between successive values of R_{sce} is authorized.						

Table 15 **Maximum allowed harmonics (input current > 16 A and ≤ 75 A per phase) for balanced three-phase equipment under specific conditions**

Minimum R_{sce}	*Acceptable individual harmonic current I_n/I_1 %*				*Maximum current harmonic ratio %*	
	I_5	*I_7*	*I_{11}*	*I_{13}*	*THD*	*PWHD*
33	10.7	7.2	3.1	2	13	22
≥ 120	40	25	15	10	48	46
Relative values of even harmonics lower or equal to 12 shall be lower than 16/n %. Even harmonics greater than 12 are taken into account in the THD and PWHD in the same way as odd harmonics.						

7.12. Specifications concerning emission of voltage changes, voltage fluctuations and flicker on AC power lines from ESAs

7.12.1. Method of measurement

The emission of voltage changes, voltage fluctuations and flicker on AC power lines generated by the ESA representative of its type shall be measured using the method described in Annex 18. The method of measurement shall be defined by the ESA manufacturer in accordance with the Technical Service.

7.12.2. ESA type approval limit

7.12.2.1. If measurements are made using the method described in Annex 18, the limits for rated current ≤ 16 A per phase and not subjected to conditional connection are those defined in IEC 61000-3-3, Clause 5:

- The value of P_{st} shall not be greater than 1.0;

- The value of P_{lt} shall not be greater than 0.65;

- The value of d(t) during a voltage change shall not exceed 3.3 per cent for more than 500 ms;

- The relative steady-state voltage change, d_c, shall not exceed 3.3 per cent;

- The maximum relative voltage change d_{max}, shall not exceed 6 per cent.

7.12.2.2. If measurements are made using the method described in Annex 18, the limits for rated current > 16 A and ≤ 75 A per phase and subjected to conditional connection are those defined in IEC 61000-3-11, Clause 5:

- The value of P_{st} shall not be greater than 1.0;

- The value of P_{lt} shall not be greater than 0.65;

- The value of d(t) during a voltage change shall not exceed 3.3 per cent for more than 500 ms;

- The relative steady-state voltage change, d_c, shall not exceed 3.3 per cent;

- The maximum relative voltage change d_{max}, shall not exceed 6 per cent.

7.13. Specifications concerning emission of radiofrequency conducted disturbances on AC or DC power lines from ESA

7.13.1. Method of measurement

The emission of radiofrequency conducted disturbances on AC or DC power lines generated by the ESA representative of its type shall be measured using the method described in Annex 19. The method of measurement shall be defined by the ESA manufacturer in accordance with the Technical Service.

7.13.2. ESA type approval limit

7.13.2.1. If measurements are made using the method described in Annex 19, the limits on AC power lines are those defined in IEC 61000-6-3 and given in Table 16.

Table 16 **Maximum allowed radiofrequency conducted disturbances on AC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	66 to 56 dBµV	56 to 46 dBµV
	(linearly decreasing with logarithm of frequency)	
0.5 to 5	56 dBµV	46 dBµV
5 to 30	60 dBµV	50 dBµV

7.13.2.2. If measurements are made using the method described in Annex 19, the limits on DC power lines are those defined in IEC 61000-6-3 and given in Table 17.

Table 17 **Maximum allowed radiofrequency conducted disturbances on DC power lines**

Frequency (MHz)	*Quasi-Peak limit*	*Average limit*
0.15 to 0.5	79 dBµV	66 dBµV
0.5 to 30	73 dBµV	60 dBµV

7.14. Specifications concerning emission of radiofrequency conducted disturbances wired network port from ESA

No longer applicable.

7.15. Specifications concerning the immunity of ESAs to electrical fast transient/burst disturbances conducted along AC and DC power lines.

7.15.1. Method of testing

7.15.1.1. The immunity to Electrical Fast Transient/Burst disturbances conducted along AC and DC power lines of the ESA representative of its type shall be tested by the method described in Annex 21.

7.15.2. ESA immunity type approval limits

7.15.2.1. If tests are made using the methods described in Annex 21, the immunity test levels, for AC or DC power lines, shall be: ± 2 kV test voltage in open circuit, with a rise time (T_r) of 5 ns, and a hold time (T_h) of 50 ns and a repetition rate of 5 kHz for at least 1 minute.

7.15.2.2. The ESA representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 21, there shall be no degradation of performance of the charging function as defined in paragraph 2.1. of Annex 21.

7.16. Specifications concerning the immunity of ESAs to surge conducted along AC or DC power lines

7.16.1. Method of testing

7.16.1.1. The immunity to surge conducted along AC / DC power lines of the ESA representative of its type shall be tested by the method described in Annex 22.

7.16.2. ESA immunity type approval limits

7.16.2.1. If tests are made using the methods described in Annex 22, the immunity test levels shall be:

(a) For AC power lines: ±2 kV test voltage in open circuit between line and earth and ±1 kV between lines with a rise time (T_r) of 1.2 µs, and a hold time (T_h) of 50 µs. Each surge shall be applied five times with a maximum delay of 1 minute between each pulse. This shall be applied for the following phases: 0, 90, 180 and 270°,

(b) For DC power lines: ±0.5 kV test voltage in open circuit between line and earth and ±0.5 kV between lines with a rise time (T_r) of 1.2 µs, and a hold time (T_h) of 50 µs. Each surge shall be applied five times with a maximum delay of 1 minute.

7.16.2.2. The ESA representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 22, there shall be no degradation of performance of the charging function as defined in paragraph 2.1. of Annex 22.

7.17. Specifications concerning the emission of transient conducted disturbances generated by ESAs on 12 / 24 V supply lines

7.17.1. Method of testing

The emission of ESA representative of its type shall be tested by the method(s) according to ISO 7637-2:2011, as described in Annex 10 for the levels given in Table 18.

Table 18 **Maximum allowed pulse amplitude**

	Maximum allowed pulse amplitude for	
Polarity of pulse amplitude	*Vehicles with 12 V systems*	*Vehicles with 24 V systems*
Positive	+75 V	+150 V
Negative	-100 V	-450 V

7.18. Specifications concerning immunity of ESAs to electromagnetic radiation

7.18.1. Method(s) of testing

The immunity to electromagnetic radiation of the ESA representative of its type shall be tested by the method(s) chosen from those described in Annex 9.

7.18.2. ESA immunity type approval limits

7.18.2.1. The immunity to electromagnetic radiation of ESA representative of its type shall be tested by the method(s) as described in Annex 9:

- for the levels in over 90 per cent of the 20 to 6,000 MHz frequency band given in Table 19a.

- for the minimum test Level over the whole 20 to 6,000 MHz frequency band given in Table 19b.

Table 19a

	Test Level in over 90 per cent of the 20 to 6,000 MHz frequency band	
Frequency range	*BCI*	*ALSE*
Frequency range below 2 GHz	20 to 400 MHz	80 to 2,000 MHz
Test level below 2 GHz	60 mA	30 V/m
Frequency range above 2 GHz	Not applicable	2,000 to 6,000 MHz
Test level above 2 GHz	Not applicable	10 V/m

Table 19b

	Minimum Test Level over the whole 20 to 6,000 MHz frequency band	
Frequency range	*BCI*	*ALSE*
Frequency range below 2 GHz	20 to 400 MHz	80 to 2,000 MHz
Test level below 2 GHz	50 mA	25 V/m
Frequency range above 2 GHz	Not applicable	2,000 to 6,000 MHz
Test level above 2 GHz	Not applicable	8 V/m

7.18.2.2. The ESA representative of its type shall be considered as complying with immunity requirements if, during the tests performed in accordance with Annex 9, there shall be no degradation of performance of the charging function as defined in paragraph 2.3. of Annex 9.

7.19. Specifications concerning the immunity of ESAs to transient disturbances conducted along 12 / 24 V supply lines.

7.19.1 Method of testing

The immunity of ESA representative of its type shall be tested by the method(s) according to ISO 7637-2, as described in Annex 10 with the test levels given in Table 20.

Table 20 **Immunity of ESA**

Test pulse number	*Immunity test level*		*Test duration / Number of pulses*	*FPSC for ESA*	
	12V system	*24V system*		*Related to immunity related functions*	*Not related to immunity related functions*
1	-75 V	-450V	500 pulses	III	III
2a	+37 V	+37 V	500 pulses	I	III
2b	+10 V	+ 20 V	10 pulses	II	III
3a	-112 V	-150 V	1 h	I	III
3b	+ 75 V	+150 V	1 h	I	III

7.20. Exceptions

7.20.1. Vehicles and / or ESA which are intended to be used in "REESS charging mode coupled to the power grid" in the configuration connected to a DC-charging station with a length of a DC network cable (cable between the DC charging station and the vehicle plug) shorter than 30 m do not have to fulfil the requirements of paragraphs 7.5., 7.8., 7.9., 7.13., 7.15., and 7.16.

In this case, the manufacturer shall provide a statement that the vehicle and/or ESA can be used in "REESS charging mode coupled to the power grid" only with cables shorter than 30 m. This information shall be made publicly available following the type approval.

7.20.2. Vehicles and / or ESA which are intended to be used in "REESS charging mode coupled to the power grid" in the configuration connected to a local / private DC-charging station without additional participants do not have to fulfil requirements of paragraphs 7.5., 7.8., 7.9., 7.13., 7.15., and 7.16.

In this case, the manufacturer shall provide a statement that the vehicle
and / or ESA can be used in "REESS charging mode coupled to the power grid" only with a local/private DC charging station without additional participants. This information shall be made publicly available following the type approval.

8. Amendment or extension of a vehicle type approval following electrical/electronic sub-assembly (ESA) addition or substitution

8.1. Where a vehicle manufacturer has obtained type approval for a vehicle installation and wishes to fit an additional or substitutional electrical/electronic system or ESA which has already received approval under this Regulation, and which will be installed in accordance with any conditions attached thereto, the vehicle approval may be extended without further testing. The additional or substitutional electrical/electronic system or ESA shall be considered as part of the vehicle for conformity of production purposes.

8.2. Where the additional or substitution part(s) has (have) not received approval pursuant to this Regulation, and if testing is considered necessary, the whole vehicle shall be deemed to conform if the new or revised part(s) can be shown to conform to the relevant requirements of paragraph 6. and, if applicable, of paragraph 7. or if, in a comparative test, the new part can be shown not to be likely to adversely affect the conformity of the vehicle type.

8.3. The addition by a vehicle manufacturer to an approved vehicle of standard domestic or business equipment, other than mobile communication equipment, which conforms to other Regulations, and the installation, substitution or removal of which is according to the recommendations of the equipment and vehicle manufacturers, shall not invalidate the vehicle approval. This shall not preclude vehicle manufacturers fitting communication equipment in accordance with suitable installation guidelines developed by the vehicle manufacturer and/or manufacturer(s) of such communication equipment. The vehicle manufacturer shall provide evidence (if requested by the test authority) that vehicle performance is not adversely affected by such transmitters. This can be a statement that the power levels and installation are such that the immunity levels of this Regulation offer sufficient protection when subject to transmission alone i.e. excluding transmission in conjunction with the tests specified in paragraph 6. This Regulation does not authorize the use of a communication transmitter when other requirements on such equipment or its use apply.

9. Conformity of production

The conformity of production procedures shall comply with those set out in Schedule 1 of the 1958 Agreement (E/ECE/TRANS/505/Rev.3), with the following requirements:

9.1. Vehicles or components or ESAs approved under this Regulation shall be so manufactured as to conform to the type approved by meeting the requirements set forth in paragraph 6. and, if applicable, in paragraph 7. above.

9.2. Conformity of production of the vehicle or component or separate technical unit shall be checked on the basis of the data contained in the communication form(s) for type approval set out in Annex 3A and/or 3B to this Regulation.

9.3. If the Type Approval Authority is not satisfied with the checking procedure of the manufacturer, then paragraphs 9.3.1., 9.3.2. and 9.3.3. below shall apply.

9.3.1. When the conformity of a vehicle, component or ESA taken from the series is being verified, production shall be deemed to conform to the requirements of this Regulation in relation to broadband electromagnetic disturbances and narrowband electromagnetic disturbances if the levels measured do not exceed by more than 4 dB (60 per cent) the reference limits prescribed in paragraphs 6.2.2.1., 6.2.2.2., 6.3.2.1., 6.3.2.2. and, if applicable, paragraphs 7.2.2.1. and 7.2.2.2. for vehicles and paragraphs 6.5.2.1., 6.6.2.1., and, if applicable, paragraph 7.10.2.1. above for ESAs (as appropriate).

9.3.2. When the conformity of a vehicle, component or ESA taken from the series is being verified, production shall be deemed to conform to the requirements of this Regulation in relation to immunity to electromagnetic radiation if the vehicle ESA does not exhibit any degradation relating to the direct control of the vehicle by the ADS or which could be observed by the driver or other road user when the vehicle is in the state defined in Annex 6, paragraph 4., and is subjected to a field strength, expressed in V/m, up to 80% of the reference limits prescribed

in paragraph 6.4.2.1., and, if applicable, paragraph 7.7.2.1. for vehicles and paragraph 6.8.2.1. and, if applicable, paragraph 7.18.2.1. for ESAs above.

9.3.3. If the conformity of a component, or Separate Technical Unit (STU) taken from the series is being verified, production shall be deemed to conform to the requirements of this Regulation in relation to immunity to conducted disturbances and emission if the component or STU shows no degradation of performance of "immunity related functions" up to levels given in paragraph 6.9.1. and, if applicable, paragraph 7.19.1., and does not exceed the levels given in paragraph 6.7.1. and, if applicable, paragraph 7.17.1. above.

10. Penalties for non-conformity of production

10.1. The approval granted in respect of a type of vehicle, component or separate technical unit pursuant to this Regulation may be withdrawn if the requirements laid down in paragraph 6. and, if applicable, paragraph 7. above are not complied with or if the selected vehicles fail to pass the tests provided for in paragraph 6. and, if applicable, paragraph 7. above.

10.2. If a Party to the Agreement which applies this Regulation withdraws an approval it has previously granted, it shall forthwith notify the other Contracting Parties applying this Regulation thereof by means of a communication form conforming to the model in Annexes 3A and 3B to this Regulation.

11. Production definitively discontinued

If the holder of an approval permanently ceases to manufacture a type of vehicle or ESA approved in accordance with this Regulation, he shall so inform the Type Approval Authority which granted the approval, which shall in turn notify the other Parties to the 1958 Agreement which apply this Regulation, by means of a communication form conforming to the model in Annexes 3A and 3B to this Regulation.

12. Modification and extension of type approval of a vehicle or ESA

12.1. Every modification of the vehicle or ESA type shall be notified to the Type Approval Authority which granted approval of the vehicle type. This Authority may then either:

12.1.1. Consider that the modifications made are unlikely to have an appreciable adverse effect and that in any case the vehicle or ESA still meets the requirements; or

12.1.2. Require a further test report from the Technical Service responsible for conducting the tests.

12.2. Notice of conformation of approval or of refusal of approval, accompanied by particulars of the modifications, shall be communicated by the procedure indicated in paragraph 4. of this Regulation above to the Parties to the Agreement applying this Regulation.

12.3. The Type Approval Authority granting the approval extension shall assign a serial number to the extension and so notify the other Parties to the 1958 Agreement applying this Regulation by means of a communication form conforming to the models in Annexes 3A and 3B to this Regulation.

13. Transitional provisions

13.1 **Transitional provisions applicable to the 05 series of amendments**

13.1.1. As from 9 October 2014, no Contracting Party applying this UN Regulation shall refuse to grant or refuse to accept UN type-approvals under this UN Regulation as amended by the 05 series of amendments.

13.1.2. As from 9 October 2017, Contracting Parties applying this UN Regulation shall not be obliged to accept UN type-approvals to the preceding series of amendments, first issued after 9 October 2017 or extensions thereof.

13.1.3. Notwithstanding paragraph 13.1.2., Contracting Parties applying the UN Regulation shall continue to accept UN type-approvals issued according to the preceding series of amendments to the UN Regulation, for the

vehicle type which are not equipped with a coupling system to charge the REESS, or for component or separate technical unit which doesn't include a coupling part to charge the REESS which are not affected by the changes introduced by the 05 series of amendments

13.1.4. Contracting Parties applying this UN Regulation shall not refuse to grant UN type-approvals according to any preceding series of amendments to this UN Regulation or extensions thereof.

13.2 **Transitional provisions applicable to the 06 series of amendments**

13.2.1. As from the official date of entry into force of the 06 series of amendments, no Contracting Party applying this UN Regulation shall refuse to grant or refuse to accept UN type-approvals under this UN Regulation as amended by the 06 series of amendments.

13.2.2. As from 1 September 2022, Contracting Parties applying this UN Regulation shall not be obliged to accept UN type-approvals to the preceding series of amendments, first issued after 1 September 2022 or extensions thereof.

13.2.3. Notwithstanding paragraph 13.2.2., Contracting Parties applying the UN Regulation shall continue to accept UN type-approvals issued according to the preceding series of amendments to the UN Regulation, for the vehicle type which are not equipped with a coupling system to charge the REESS, or for component or separate technical unit which doesn't include a coupling part to charge the REESS which are not affected by the changes introduced by the 05 or 06 series of amendments

13.2.4. Contracting Parties applying this UN Regulation shall not refuse to grant UN type-approvals according to any preceding series of amendments to this UN Regulation or extensions thereof.

13.3. Transitional provisions applicable to the 07 series of amendments

13.3.1. As from the official date of entry into force of the 07 series of amendments, no Contracting Party applying this Regulation shall refuse to grant or refuse to accept type approvals under this Regulation as amended by the 07 series of amendments.

13.3.2. As from 1 September 2029, Contracting Parties applying this Regulation shall not be obliged to accept type approvals to any of the preceding series of amendments, first issued after 1 September 2029.

13.3.3. Contracting Parties applying this Regulation shall continue to accept type approvals issued according to the 06 series of amendments to this Regulation first issued before 1 September 2029.

13.3.4. Notwithstanding paragraph 13.3.3., Contracting Parties applying this Regulation shall continue to accept type approvals issued according to the 06 series of amendments to this Regulation, for vehicles, vehicle systems, equipment and parts which are not affected by the changes introduced by the 07 series of amendments.

13.3.5. Notwithstanding the transitional provisions above, Contracting Parties who start to apply this Regulation after the date of entry into force of the most recent series of amendments are not obliged to accept type approvals which were granted in accordance with any of the preceding series of amendments to this Regulation.

13.3.6. Contracting Parties applying this Regulation may grant type approvals according to any of the preceding series of amendments to this Regulation.

13.3.7. Contracting Parties applying this Regulation shall continue to grant extensions of existing approvals to any of the preceding series of amendments to this Regulation.

14. Names and addresses of Technical Services conducting approval tests and of Type Approval Authorities

The Parties to the 1958 Agreement applying this Regulation shall communicate to the United Nations Secretariat the names and addresses of the Technical Services conducting approval tests and of the Type Approval Authorities

which grant approvals and to which forms certifying approval or extension, refusal or withdrawal of approval, issued in other countries, are to be sent.

Appendix 1 List of standards referred to in this Regulation

1. CISPR 12 "Vehicles,boats, and internal combustion engine driven devices - Radio disturbance characteristics - Limits and methods of measurement for the protection of receivers except those installed in the vehicle/boat/device itself or in adjacent vehicles/boats/devices", Edition 5.1 - 2001 and AMD1:2005.

2. CISPR 16-1-4 "Specifications for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus, antennas and test sites for radiated disturbances measurements", Edition 4.2 - 2019, AMD1:2020 and AMD2:2023.

3. CISPR 25 "Radio disturbance characteristics for the protection of receivers used on board vehicles, boats, and on devices - Limits and methods of measurement", Edition 2.0 - 2002 and corrigendum 2004.

4. ISO 7637 "Road vehicles - Electrical disturbance from conduction and coupling**":**

Part 1: Definitions and general considerations (ISO 7637-1, Third edition 2015);

Part 2: Electrical transient conduction along supply lines only, (ISO 7637-2, Third edition 2011).

5. ISO/IEC 17025 "General requirements for the competence of testing and calibration laboratories", Third edition 2017.

6. ISO 11451 "Road vehicles – Vehicle test methods for electrical disturbances from narrowband radiated electromagnetic energy":

Part 1: General principles and terminology (ISO 11451-1, Fifth edition 2025);

Part 2: Off-vehicle radiation sources (ISO 11451-2, Fifth edition 2025);

Part 4: Harness excitation methods (ISO 11451-4, Fourth edition 2022).

7. ISO 11452 "Road vehicles - Component test methods for electrical disturbances from narrowband radiated electromagnetic energy":

Part 1: General principles and terminology (ISO 11452-1, Fifth edition 2025);

Part 2: Absorber-lined shielded enclosure (ISO 11452-2, Third edition 2019);

Part 3: Transverse electromagnetic (TEM) cell (ISO 11452-3,

Fourth edition 2024);

Part 4: Harness excitation methods (ISO 11452-4, Fifth edition 2020);

Part 5: Stripline (ISO 11452-5, Second edition 2002);

Part 11: Reverberation chamber (ISO 11452-11, First edition 2010).

9. IEC 61000-3-2 "Electromagnetic Compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)", Edition 5.2 - 2018, AMD1:2020 and AMD2:2024.

10. IEC 61000-3-3 "Electromagnetic Compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection", Edition 3.2 - 2013, AMD1:2017, AMD2:2021 and COR1:2022.

11. IEC 61000-3-11 "Electromagnetic Compatibility (EMC) - Part 3-11: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems - Equipment with rated current ≤ 75 A and subject to conditional connection", Edition 2.0 - 2017.

12. IEC 61000-3-12 "Electromagnetic Compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current > 16 A and ≤ 75 A per phase",

Edition 1.0 - 2004.

13. IEC 61000-4-4 "Electromagnetic Compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transients/burst immunity test", Edition 3.0 - 2012.

14. IEC 61000-4-5 "Electromagnetic Compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test", Edition 3.1 - 2014 and AMD1:2017.

15. IEC 61000-6-3 "Electromagnetic Compatibility (EMC) - Part 6-3: Generic standards - Emission standard for equipment in residential environments", Edition 3.0 - 2020.

16. IEC 61000-6-4 “Electromagnetic compatibility (EMC) - Part 6-4: Generic standards - Emission standard for industrial environments”, Edition 3.0 - 2018.

17. CISPR 16-2-1 "Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-1: Methods of measurement of disturbances and immunity - Conducted disturbance measurements", Edition 3.1 - 2014, AMD1:2017 and COR1:2020.

18. CISPR 16-1-2 "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-2: Radio disturbance and immunity measuring apparatus, coupling devices for conducted disturbance measurements", Edition 2.1 - 2014 and AMD1:2017.

19. IEC 61851-1 "Electric vehicle conductive charging system - Part 1: General requirements", Edition 3.0 - 2017.

20. IEC 61851-21-2 "Electric vehicle conductive charging system - Part 21-2: Electric vehicle requirements for conductive connection to an AC/DC supply - EMC requirements for off board electric vehicle charging systems", Edition 1.0 - 2018.

21. CISPR 32 "Electromagnetic compatibility of multimedia equipment - Emission requirements”, Edition 2.1 - 2015 and AMD1:2019.

22. CISPR 16-1-1 “Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus", Edition 5.0: 2019.

23. ISO 16750 "Road vehicles - Environmental conditions and testing for electrical and electronic equipment":

Part 1: General (ISO 16750-1, Fourth edition 2023);


Part 2: Electrical loads (ISO 16750-2, Fifth edition 2023).

Appendix 2 Vehicle broadband reference limits - Antenna-vehicle separation: 10 m

Frequency - megahertz - logarithmic

(See paragraphs 6.2.2.1. and 7.2.2.1. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth		
30-75 MHz	75-400 MHz	400-1,000 MHz
E = 32	E = 32 + 15.13 log (F/75)	E = 43




Appendix 3 Vehicle broadband reference limits - Antenna-vehicle separation: 3 m

Frequency - megahertz - logarithmic

(See paragraphs 6.2.2.2. and 7.2.2.2. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth		
30-75 MHz	75-400 MHz	400-1,000 MHz
E = 42	E = 42 + 15.13 log (F/75)	E = 53




Appendix 4 Vehicle narrowband reference limits - Antenna-vehicle separation: 10 m

Frequency - megahertz - logarithmic

(See paragraph 6.3.2.1. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth	
30-230 MHz	230-1,000 MHz
E = 28	E = 35
The limits shall be measured with a 120 kHz bandwidth.	




Appendix 5 Vehicle narrowband reference limits - Antenna-vehicle separation: 3 m

Frequency - megahertz - logarithmic

(See paragraph 6.3.2.2. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth	
30-230 MHz	230-1,000 MHz
E = 38	E = 45




Appendix 6 Electrical/electronic sub-assembly (ESA) - Broadband reference limits

Frequency - megahertz - logarithmic

(See paragraphs 6.5.2.1. and 7.10.2.1. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth		
30-75 MHz	75-400 MHz	400-1,000 MHz
E = 62 - 25.13 log (F/30)	E = 52 + 15.13 log (F/75)	E = 63




Appendix 7 Electrical/electronic sub-assembly (ESA) - Narrowband reference limits

Frequency - megahertz - logarithmic

(See paragraph 6.6.2.1. of this Regulation)

Limit E (dBµV/m) at frequency F (MHz) for a 120 kHz bandwidth		
30-75 MHz	75-400 MHz	400-1,000 MHz
E = 52 - 25.13 log (F/30)	E = 42 + 15.13 log (F/75)	E = 53



Appendix 8 Artificial networks (AN), High Voltage Artificial Networks (HV-AN), Direct Current charging Artificial Networks (DC-charging-AN), Artificial Mains Networks (AMN) and Asymmetric Artificial Networks (AAN)

This appendix defines the artificial networks for vehicle in charging mode:

- Artificial networks (AN): used for low voltage power supplies;
- High Voltage Artificial networks (HV-AN) : used for DC power supplies;
- Direct Current charging Artificial Networks (DC-charging-AN): used for DC power supplies;
- Artificial Mains Networks (AMN) : used for AC power mains;
- Asymmetric artificial network (AAN): used for signal/control port lines and/or wired network port lines.

1. Artificial networks (AN)


For an ESA powered by LV, a 5 µH / 50 Ω AN as defined in Figure 1 shall be used.

The AN(s) shall be mounted directly on the ground plane. The grounding connection of the AN(s) shall be bonded to the ground plane.

Measurement ports of AN(s) shall be terminated with a 50 Ω load.

The AN impedance Z_{PB} (tolerance ± 20 %) in the measurement frequency range of 0,1 MHz to 100 MHz is shown in Figure 2. It is measured between the terminals P and B (of Figure 1) with a 50 Ω load on the measurement port with terminals A and B (of Figure 1) short circuited.


Figure 1 **Example of 5 µH AN schematic**



Key

L_1 5 µH	A port to power supply
C_1 0,1 µF	P port to ESA
C_2 1 µF (default value)	B ground
R_1 1 kΩ	MEP measuring port

Figure 2 **Characteristics of the AN impedance Z_{PB}**



2. High Voltage Artificial networks (HV-AN)


For an ESA powered by HV, a 5 µH / 50 Ω HV-AN as defined in Figure 3 shall be used.

The HV-AN(s) shall be mounted directly on the ground plane. The grounding connection of the HV-AN(s) shall be bonded to the ground plane.

Measurement ports of HV-AN(s) shall be terminated with a 50 Ω load.

The HV-AN impedance Z_{PB} (tolerance ± 20 %) in the measurement frequency range of 0,1 MHz to 100 MHz is shown in Figure 2. It is measured between the “ESA HV” and “GND” terminals (of Figure 3) with a 50 Ω load on the measurement port and with the “HV supply” and “GND” terminals short circuited.

Figure 3 Example of 5 µH HV-AN schematic




Key

L_1	5 µH		HV supply high voltage power supply
C_1	0,1 µF		ESA HV high voltage of ESA
C_2	0,1 µF (default value)		MEP measuring port
R_1	1 kΩ		GND ground
R_2	1 MΩ (discharging C_2 to < 50 V_{dc} within 20 s)		

If unshielded HV-ANs are used in a single shielded box, then there shall be an inner shield between the HV-ANs as described in Figure 4.

Figure 4 Example of 5 µH HV-AN combination in a single shielded box




Key		
L_1	5 µH	HV supply high voltage power supply (positive and negative)
C_1	0,1 µF	ESA HV high voltage of ESA (positive and negative)
C_2	0,1 µF (default value)	MEP measuring port
R_1	1 kΩ	GND ground

R_2 1 MΩ (discharging C_2 to < 50 V_{dc} within 20 s)

An optional impedance matching network may be used to simulate common mode / differential mode impedance seen by the ESA plugged on HV power supply (see Figure 5).

Figure 5 Impedance matching network attached between HV-ANs and ESA



Key	
L_1 5 µH	HV supply high voltage power supply (positive and negative)
C_1 0,1 µF	ESA HV high voltage of ESA (positive and negative)
C_2 0,1 µF (default value)	MEP measuring port
R_1 1 kΩ	GND ground
R2 1 MΩ (discharging C2 to < 50 V_{dc} within **2**0 s)	Z_{DI-CM} differential and common-mode impedance


3. Direct Current charging Artificial Networks (DC-charging-AN)

For a vehicle/ESA in charging mode connected to a DC power supply, a 5 µH / 50 Ω DC-charging-AN as defined in Figure 6 shall be used.

Measurement ports of DC-charging-AN(s) shall be terminated with 50 Ω loads.

The DC-charging-AN impedance Z_{PB} (tolerance ±20 %) in the measurement frequency range of 0,1 MHz to 100 MHz is shown in Figure 7. It is measured between the terminals “Vehicle/ESA HV” and “GND” (of Figure 6) with a 50 Ω load on the measurement port and with terminals “HV Supply” and “GND” (of Figure 6) short circuited.


Figure 6 Example of 5 µH DC-charging-AN schematic



Key

L_1	5 µH	HV supply high voltage power supply
C_1	0,1 µF	Vehicle / ESA HV high voltage of vehicle or ESA
C2	1 µF (default value, if another value is used, it shall be justified)	MEP measuring port
R_1	1 kΩ	GND ground
R_2	1 MΩ (discharging C_2 to < 50 V_{dc} within 20)	

Figure 7 **Characteristics of the DC-charging-AN impedance**



4. Artificial Mains networks (AMN)

For a vehicle/ESA in charging mode connected to an AC power mains, a 50 µH / 50 Ω-AMN as defined in CISPR 16-1-2 Clause 4.4 shall be used.

Measurement ports of AMN(s) shall be terminated with 50 Ω loads.

5. Asymmetric artificial network (AAN)

Currently, different technologies for signal/control port lines and/or wired network port lines are used for the communication between charging station and vehicle/ESA. Therefore, a distinction between some specific signal/control port lines and/or wired network port lines (for example, control pilot line, CAN lines) is necessary.

Measurement ports of AAN(s) shall be terminated with 50 Ω loads.

AANs that are defined in paragraphs 5.1., 5.2., 5.3. and 5.4. of this appendix are used for unshielded signal/control port lines and/or wired network port lines.

If shielded signal/control port lines are used, then shielded AANs defined in CISPR 32:2015 Annex G, Figures G.10 and G.11 should be used.

5.1. Signal/Control port with symmetric lines

An asymmetric artificial network (AAN) to be connected between the vehicle and the charging station or any auxiliary equipment (AE) used to simulate communication is defined in CISPR 16-1-2 Annex E Clause E.2 (T network circuit) (see example in Figure 8).


The AAN has a common mode impedance of 150 Ω. The impedance Z_{cat} adjusts the symmetry of the cabling and attached periphery typically expressed as longitudinal conversion loss (LCL). The value of LCL should be predetermined by measurements or be defined by the manufacturer of the charging station/charging harness. The selected value for LCL and its origin shall be stated in the test report.

CAN communication is an example of symmetric lines used for vehicle DC charging mode.

If an original charging station can be used for the test, an AAN is not required for CAN communication.

If the CAN communication is emulated and if the presence of the AAN prevents proper CAN communication, then no AAN should be used.

Figure 8 **Example of an AAN for Signal/Control port with symmetric lines (e.g. CAN)**



Key

1 AAN	
2 vehicle	Z_{cat} symmetric adjustment impedance
3 charging station	A symmetrical line 1 (in vehicle)
L_1 2 x 38 mH	B symmetrical line 2 (in vehicle)
L_2 2 x 38 mH	C symmetrical line 1 (charging station side)
R 200 Ω	D symmetrical line 2 (charging station side)
C 4,7 µF	E measuring port with 50 Ω load


5.2. Wired network port with PLC on power lines

If an original charging station can be used for the test, an AAN and/or AMN/DC-charging-AN might not be required for PLC communication.

If the presence of the AMN/DC-charging-AN prevents proper PLC communication with the original charging station or if the PLC communication needs to be simulated by means of a piece of auxiliary equipment (e.g. a PLC modem) instead of the original charging station, it is necessary to add an AAN between the AE (e.g. the PLC modem) and the AMN/DC-charging-AN output (vehicle side), as shown in Figure 9.

The circuit in Figure 9 provides a common mode termination by the AMN / DC-charging-AN / HV-AN. In order to minimize emission from the PLC modem of the vehicle, an attenuator is located between the powerline and the PLC modem at the AE side in the circuit for emission tests. This attenuator consists of two resistors in combination with the input/output impedance of the PLC modem. The value of the resistors depends on the design impedance of the PLC modems and the allowed attenuation for the PLC system.

Figure 9 **Example of AAN with Signal/Control port with PLC on AC or DC power lines**



Key

1 AAN	C_1 4,7 nF
2 vehicle	A PLC on AC or DC power line (vehicle side)
3 charging station / power supply	B PLC on AC or DC power line (vehicle side)
4 HV-AN or AMN or DC-charging-AN	C PLC line (charging station or AE side)
5 AE	D PLC line (charging station or AE side)
R_1 2,5 kΩ	

The value of the resistors depends on the allowed attenuation and the design impedance of the PLC modem (here: 40dB attenuation, 100Ω PLC design impedance).

5.3. Signal/Control port with PLC (technology) on control pilot

Some communication systems use the control pilot line (versus PE) with a superimposed (high frequency) communication. Typically the technology developed for powerline communication (PLC) is used for that purpose. On one hand the communication lines are operated unsymmetrically, on the other hand two different communication systems operate on the same line. Therefore, a special AAN shall be used as defined in Figure 10.


It provides a common mode impedance of 150 Ω ± 20 Ω (150 kHz to 30 MHz) on the control pilot line (assuming a design impedance of the modem of 100 Ω). Both types of communications (control pilot, PLC) are separated by the network.

Therefore, typically a communication simulation is used in combination with this network. The attenuator built by the resistors and the design impedance of the PLC modem makes sure that the signal on the charging harness is dominated by the vehicle's communication signals rather than the AE PLC modem.

The values of inductance and capacitance in the networks added for PLC on control pilot shown in Figure 10 shall not induce any malfunction of communication between vehicle and AE or charging station. It may therefore be necessary to adapt these values to ensure proper communication.

If PLC communication is emulated and if the presence of the AAN prevents proper PLC communication then no AAN should be used.

Figure 10 **Example of AAN circuit for Signal/Control port with PLC on control pilot**



Key

1 AAN	
2 vehicle	R_2 270 Ω
3 charging station	C_1 2,2 nF
4 control pilot (in vehicle)	$L_1$100 µH
5 PLC (in vehicle)	A control pilot line (vehicle side)
6 AE	B/D protective earth
R_1 39 Ω	C control pilot line (charging station side)

The values of the three resistors depend on the design impedance of the PLC modem connected at AE side. The values given in the schematic are valid for a design impedance of 100 Ω.

5.4. Signal/Control port with control pilot

Some communication systems use the control pilot line (versus PE). On one hand the communication lines are operated unsymmetrically, on the other hand two different communication systems operate on the same line. Therefore, a special AAN shall be used as defined in Figure 11.


It provides a common mode impedance of 150 Ω ± 20 Ω (150 kHz to 30 MHz) on the control pilot line (between A and B/D).

Therefore, typically a communication simulation is used in combination with this network.

The values of inductance and capacitance in the networks on control pilot shown in Figure 11 shall not induce any malfunction of communication between vehicle and charging station. It may therefore be necessary to adapt these values to ensure proper communication.

If Control pilot communication is emulated and if the presence of the AAN prevents proper Control pilot communication**,** then no AAN should be used.

Figure 11 **Example of AAN circuit for pilot line**




Key	
1 AAN	C_1 1,1 nF
2 vehicle	L_1 100 µH
3 charging station	A control pilot line (vehicle side)
4 control pilot (in vehicle)	B/D protective earth
R_1 150 Ω	C control pilot line (charging station side)

Annex 1 Examples of approval marks

Model A

(See paragraph 5.2. of this Regulation)





a = 6 mm min

The above approval mark affixed to a vehicle or ESA shows that the vehicle type concerned has, with regard to electromagnetic compatibility, been approved in the Netherlands (E 4) pursuant to Regulation No. 10 under approval No. 07 2439. The approval number indicates that the approval was granted according to the requirements of Regulation No. 10 as amended by the 07 series of amendments.

Model B

(See paragraph 5.2. of this Regulation)





a = 6 mm min

The above approval mark affixed to a vehicle or ESA shows that the vehicle type concerned has, with regard to electromagnetic compatibility, been approved in the Netherlands (E 4) pursuant to UN Regulations Nos. 10 and 33. The approval numbers indicate that, at the date when the respective approvals were given, UN Regulation No. 10 included the 07 series of amendments and UN Regulation No. 33 was still in its original form.

Annex 2A Information document for type approval of a vehicle with respect to electromagnetic compatibility

The following information shall be supplied in triplicate and shall include a list of contents.

Any drawings shall be supplied in appropriate scale and in sufficient detail. If submission is paper based, documents shall be on size A4 or in a folder of A4 format. Electronic submissions may be of any standard size.

Photographs, if any, shall show sufficient detail.

If the systems, components or separate technical units have electronic controls, information concerning their performance shall be supplied.

General

1. Make (trade name of manufacturer):.....

2. Type: .....

3. Category of vehicle: .....

4. Name and address of manufacturer:.....
Name and address of authorised representative, if any: .....

5. Address(es) of assembly plant(s): .....

General construction characteristics of the vehicle

6. Photograph(s) and/or drawing(s) of a representative vehicle: .....

7. Position and arrangement of the engine: .....

Power plant

8. Manufacturer: .....

9. Manufacturer's engine code as marked on the engine: .....

10a. List propulsion systems, auxiliary engines and components of the charging system: .....

10b. List modes of operations (selectable by the driver or the system) which are selected during the type approval test:……

11. Working principle: positive ignition/compression ignition, four-stroke/two stroke[1]

[1] Strike out what does not apply.

12. Number and arrangement of cylinders:.....

13. Fuel feed:.....

14. By fuel injection (compression ignition only): yes/no[1]

[1] Strike out what does not apply.

15. Electronic control unit:.....

16. Make(s): .....

17. Description of the system:.....

18. By fuel injection (positive ignition only): yes/no[1]

[1] Strike out what does not apply.

19. Electrical system:.....

20. Rated voltage: ..... V, positive/negative ground[1]

[1] Strike out what does not apply.

21. Generator:.....

22. Type: .....

23. Ignition:.....

24. Make(s): .....

25. Type(s): .....

26. Working principle: .....

27. LPG fuelling system: yes/no[1]

28. Electronic engine management control unit for LPG fuelling: .....

29. Make(s): .....

30. Type(s): .....

31. NG fuelling system: yes/no[1]

[1] Strike out what does not apply.

32. Electronic engine management control unit for NG fuelling:.....

33. Make(s): .....

34. Type(s): .....

35. Electric motor:.....

36. Type (winding, excitation): .....

37. Operating voltage:.....

Gas fuelled engines (in the case of systems laid-out in a different manner, supply equivalent information)

38. Electronic control unit (ECU):

39. Make(s): .....

40. Type(s): .....

Transmission

41. Type (mechanical, hydraulic, electric, etc.): .....

42. A brief description of the electrical/electronic components (if any): .....

Suspension

43. A brief description of the electrical/electronic components (if any): .....

Steering

44. A brief description of the electrical/electronic components (if any): .....

Brakes

45. Anti-lock braking system: yes/no/optional[1]

---

[1] Strike out what does not apply.

46. For vehicles with anti-lock systems, description of system operation (including any electronic parts), electric block diagram, hydraulic or pneumatic circuit plan:

Bodywork

47. Type of bodywork: .....

48. Materials used and methods of construction: .....

49. Windscreen and other windows:

50. A brief description of the electrical/electronic components (if any) of the window lifting mechanism:

51. Devices for indirect vision in the scope of Regulation No. 46:.....

52. A brief description of the electrical/electronic components (if any): .....

53. Safety belts and/or other restraint systems:

54. A brief description of the electrical/electronic components (if any): .....

55. Suppression of radio interference:

56. Description and drawings/photographs of the shapes and constituent materials of the part of the body forming the engine compartment and the part of the passenger compartment nearest to it:

57. Drawings or photographs of the position of the metal components housed in the engine compartment (e.g. heating appliances, spare wheel, air filter, steering mechanism, etc.):

58. Table and drawing of radio interference control equipment: .....

59. Particulars of the nominal value of the direct current resistance and, in the case of resistive ignition cables, of their nominal resistance per metre:

Lighting and light signalling devices

60. A brief description of electrical/electronic components other than lamps (if any):..

Miscellaneous

61. Devices to prevent unauthorised use of the vehicle: .....

62. A brief description of the electrical/electronic components (if any): .....

63. Table of installation and use of RF transmitters in the vehicle(s), if applicable (see paragraph 3.1.8. of this Regulation):

Frequency bands [Hz]	*Max. output power [W]*	*Antenna position at vehicle, specific conditions for installation and/or use*

64. Vehicle equipped with 24 GHz short-range radar equipment: yes/no/optional.[1]

[1] Strike out what does not apply.

65. Charger: on board/external/without:[1]

[1] Strike out what does not apply.

66. List every available charging mode (direct current / alternating current, number of phases/frequency):
[1].....

[1] Strike out what does not apply.

67. Maximum charging current in each mode: .....

68. Nominal charging voltage in each mode:.....

69. Basic vehicle interface functions: ex: L1/L2/L3/N/E/control pilot:.....

70. Minimum R_{sce} value (see paragraph 7.3.)

71. Charging harness delivered with the vehicle: yes/no[1]

[1] Strike out what does not apply.

72. If charging harness delivered with the vehicle:
Length (m) .....
Cross sectional area (mm²) .....

73. Environment of charging (residential, non-residential)
The applicant for type approval shall also supply, where appropriate:
Appendix 1 A list with make(s) and type(s) of all electrical and/or electronic components concerned by this Regulation (see paragraphs 2.9. and 2.10. of this Regulation) and not previously listed.
Appendix 2: Schematics or drawing of the general arrangement of electrical and/or electronic components (concerned by this Regulation) and the general wiring harness arrangement.
Appendix 3: Description of vehicle chosen to represent the type:
Body style: .....
Left or right hand drive: .....
Wheelbase: .....
Appendix4: Relevant test report(s) supplied by the manufacturer from a test laboratory accredited to ISO 17025 and recognized by the Type-Approval Authority for the purpose of drawing up the type approval certificate.

74. Automated Driving System (ADS):

yes/no/optional[1]……

75. A brief description of the ADS (if any) including its feature(s) and sensors (if any)

…….

Annex 2B Information document for type approval of an electric/electronic sub-assembly (ESA) with respect to electromagnetic compatibility

The following information, if applicable, shall be supplied in triplicate and shall include a list of contents. Any drawings shall be supplied in appropriate scale and in sufficient detail. If submission is paper based, documents shall be on size A4 or in a folder of A4 format. Electronic submissions may be of any standard size. Photographs, if any, shall show sufficient detail.

If the systems, components or separate technical units have electronic controls, information concerning their performance shall be supplied.

1. Make (trade name of manufacturer): .....

2. Type: .....

3. Means of identification of type, if marked on the component/separate technical unit:[1]

[1] If the means of identification of type contains characters not relevant to describe the component or separate technical unit types covered by this information document, such characters shall be represented in the documentation by the symbol "?" (e.g. ABC??123??).

3.1. Location of that marking:.....

4. Name and address of manufacturer: .....

Name and address of authorized representative, if any:.....

.....

5. In the case of components and separate technical units, location and method of affixing of the approval mark:

6. Address(es) of assembly plant(s): .....

7. This ESA shall be approved as a component/STU[2]

[2] Delete where not applicable.

8. Any restrictions of use and conditions for fitting: .....

9. Electrical system rated voltage: …… V, positive/negative[2] ground.....
Appendix 1: Description of the ESA chosen to represent the type (electronic block diagram and list of main component constituting the ESA (e.g. make and type of microprocessor, crystal, etc.).
Appendix 2: Relevant test report(s) supplied by the manufacturer from a test laboratory accredited to ISO 17025 and recognized by the Type Approval Authority for the purpose of drawing up the type approval certificate.
Only applicable for charging systems:.....

[2] Delete where not applicable.

10. Charger: on board/external[2].....

[2] Delete where not applicable.

11. Charging current: direct current/alternating current (number of phases/frequency)[2] ...

[2] Delete where not applicable.

12. Maximal nominal current (in each mode if necessary).....

13. Nominal charging voltage.....

14. Basic ESA interface functions: ex. L1/L2/L3/N/PE/control pilot.....

15. Minimum R_{sce} value (see paragraph 7.11. of this Regulation).....

Annex 3A Communication concerning the approval or extension or refusal or withdrawal of approval or production definitively discontinued of a type of vehicle/component/separate technical unit with regard to UN Regulation No. 10

(Maximum format: A4 (210 x 297 mm))



issued by: Name of administration:
.....
.....
.....

Concerning:[2] Approval granted

Approval extended

Approval refused

Approval withdrawn

Production definitively discontinued

of a type of vehicle/component/separate technical unit[2] with regard to Regulation No. 10.

Approval No.: ……..... Extension No.: .....

[1] Distinguishing number of the country which has granted/extended/refused or withdrawn approval (see Regulation, provisions on approval).

[2] Strike out what does not apply.

1. Make (trade name of manufacturer):.....

2. Type: .....

3. Means of identification of type, if marked on the vehicle/component/separate technical unit[2] .....

[2] Strike out what does not apply.

3.1. Location of that marking:.....

4. Category of vehicle: .....

5. Name and address of manufacturer:.....

6. In the case of components and separate technical units, location and method of affixing of the approval mark: .....

7. Address(es) of assembly plant(s):.....

8. Additional information (where applicable): See appendix below

9. Technical Service responsible for carrying out the tests:.....

10. Date of test report:.....

11. Number of test report:.....

12. Remarks (if any): See appendix below

13. Place:.....

14. Date:.....

15. Signature:.....

16. The index to the information package lodged with the Approval Authority, which may be obtained on request is attached: .....

17. Reasons for extension:.....

Appendix to type approval communication form No..... concerning the type approval of a vehicle under UN Regulation No. 10

1. Additional information:.....

2. Electrical system rated voltage: .....V. pos/neg ground[2]

[2] Strike out what does not apply.

3. Environment of charging for REESS of EV and PHEV:
Type of vehicle valid for residential environment: .....
Type of vehicle valid for non-residential environment: .....

4. Type of bodywork:.....

5. List of electronic systems installed in the tested vehicle(s) not limited to the items in the information document: .....

5.1. Vehicle equipped with 24 GHz short-range radar equipment: yes/no/optional[2]

[2] Strike out what does not apply.

6. Laboratory accredited to ISO 17025 and recognized by the Approval Authority responsible for carrying out the tests: .....

7. Automated Driving System (ADS): yes/no/optional[1]……..…

8. Remarks: (e.g. valid for both left-hand drive and right-hand drive vehicles):.....

Annex 3B Communication concerning the approval or extension or refusal or withdrawal of approval or production definitively discontinued of a type of electrical/electronic sub-assembly (ESA) with regard to UN Regulation No. 10

(Maximum format: A4 (210 x 297 mm))

issued by: Name of administration:
.....
.....
.....



Concerning:[2]

Approval granted

Approval extended

Approval refused

Approval withdrawn

Production definitively discontinued

of a type of electrical/electronic sub-assembly[2] with regard to Regulation No. 10.

Approval No.: ..... Extension No.: .....

[1] Distinguishing number of the country which issued/extended/refused or withdrawn approval. (see Regulation, provisions on approval).

[2] Strike out what does not apply.

1. Make (trade name of manufacturer):.....

2. Type and general commercial description(s): .....

3. Means of identification of type, if marked on the vehicle/component/separate technical unit[2]

[2] Strike out what does not apply.

3.1. Location of that marking: .....

4. Category of vehicle: .....

5. Name and address of manufacturer:.....

6. In the case of components and separate technical units, location and method of affixing of the approval mark:

7. Address(es) of assembly plant(s):.....

8. Additional information (where applicable): See appendix below

9. Technical Service responsible for carrying out the tests:.....

.....

10. Date of test report:.....

11. No. of test report:.....

12. Remarks (if any): See appendix below

13. Place:.....

14. Date:.....

15. Signature:.....

16. The index to the information package lodged with the Approval Authority, which may be obtained on request, is attached: .

17. Reasons for extension:.....

Appendix to type approval communication form No...concerning the type approval of an electrical/electronic sub-assembly under UN Regulation No. 10

1. Additional information:.....

1.1. Electrical system rated voltage: .....V. pos/neg ground[2]

[2] Strike out what does not apply.

1.2. This ESA can be used on any vehicle type with the following restrictions:.....

1.2.1. Installation conditions, if any:.....

1.3. This ESA can be used only on the following vehicle types:.....

1.3.1. Installation conditions, if any:.....

1.4. The specific test method(s) used and the frequency ranges covered to determine immunity were: (Please specify precise method used from Annex 9):

1.5. Laboratory accredited to ISO 17025 and recognized by the Approval Authority esponsible for carrying out the tests:

2. Remarks:.....

.....

Annex 4 Method of measurement of radiated broadband electromagnetic emissions from vehicles

1. General

1.1. The test method described in this annex shall only be applied to vehicles. This method concerns both configurations of the vehicle:

(a) Other than "REESS charging mode coupled to the power grid";

(b) "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the broadband emissions generated by electrical or electronic systems fitted to the vehicle (e.g. ignition system or electric motors).

If not otherwise stated in this annex the test shall be performed according to CISPR 12.

2. Vehicle state during tests

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

2.1. Vehicle in configuration other than "REESS charging mode coupled to the power grid".

2.1.1. Engine

The engine shall be in operation according to CISPR 12.

For vehicle with an electric propulsion motor or hybrid propulsion system, if this is not appropriate (e.g. in case of busses, trucks, two- and three wheel vehicles), transmission shafts, belts or chains may be disconnected to achieve the same operation condition for the propulsion.

If operating mode defined in CISPR 12 (i.e. 40 km/h) does not activate all traction motors or auxiliary battery charging engines, an alternative, steady state operating mode shall be agreed between the Technical Service and vehicle manufacturer.


2.1.2. Other vehicle systems

All equipment capable of generating broadband emissions which can be switched on permanently by the driver, passenger or by the ADS should be in operation in maximum load, e.g. wiper motors or fans. The horn and electric window motors are excluded because they are not used continuously.

2.2. Vehicle in configuration "REESS charging mode coupled to the power grid".

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in the flowchart of Figure 1.

Figure 1 **Charging mode configuration for Annex 4**



In case of multiple batteries the average state of charge shall be considered.

The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode. All other equipment which can be switched ON by the driver or passengers shall be OFF.

The test set-up for the connection of the vehicle in configuration "REESS charging mode coupled to the power grid" is shown in Figures 3a to 3h (depending of AC or DC power charging mode, location of charging plug and charging with or without communication) of Appendix 1 to this Annex.

2.2.1. Vehicle in charging mode 1 or mode 2 (AC power charging without communication).

2.2.1.1. Charging station / Power mains

The power mains socket can be placed anywhere in the test site with the following conditions:

- The socket(s) shall be placed on the ground plane (ALSE) or floor (OTS);

- The length of the harness between the power mains socket and the AMN(s) shall be kept as short as possible, but not necessarily aligned with the charging harness;

- The harness shall be placed as close as possible to the ground plane (ALSE) or floor (OTS).

2.2.1.2. Artificial network

Power mains shall be applied to the vehicle through 50 µH/50 Ω artificial networks (AMN(s)) (see Appendix 8, paragraph 4.).

The AMN(s) shall be mounted directly on the ground plane (ALSE) or floor (OTS). The case of the AMN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AMN shall be terminated with a 50 Ω load.

2.2.1.3. Power charging harness

The power charging harness shall be placed in a straight line between the AMN(s) and the vehicle charging plug and shall be routed perpendicularly to the vehicle longitudinal axis (see Figure 3a and Figure 3c). The projected harness length from the side of the AMN(s) to the side of the vehicle shall be 0,8 (+0,2 / -0) m as shown in Figure 3b and Figure 3d.

For a longer cable, the extraneous length shall be “Z-folded” symmetrically. No contact or overlap is allowed between windings. The width of the Z-folded cable shall be between 500 mm and 1 000 mm. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user's installation, the disposition of the excess cable length shall be precisely noted in the test report.

The charging harness at the vehicle side shall hang vertically at a distance of 100 (+200 / -0) mm from the vehicle body.

The whole harness shall be placed on a non-conductive, low relative permittivity (dielectric-constant) material ($\varepsilon_r \leq 1{,}4$), at (100 ± 25) mm above the ground plane (ALSE) or floor (OTS).

2.2.2. Vehicle in charging mode 3 (AC power charging with communication) or mode 4 (DC power charging with communication).

2.2.2.1. Charging station / Power mains

The charging station may be placed either in the test site or outside the test site.

If the local/private communication between the vehicle and the charging station can be simulated, the charging station may be replaced by a supply from the AC power mains network.

In both cases power mains and communication or signal lines socket(s) shall be placed in the test site with the following conditions:

The socket(s) shall be placed on the ground plane (ALSE) or floor (OTS);The length of the harness between the power mains / local/private communication socket and the AMN(s) / DC-charging-AN(s) / AAN(s) shall be kept as short as possible, but not necessarily aligned with the charging harness; The harness between the power mains / local/private communication socket and the AMN(s) / DC-charging-AN(s) / AAN(s) shall be placed as close as possible of the ground plane (ALSE) or floor (OTS).

If the charging station is placed inside the test site, then the harness between the charging station and the power mains / local/private communication socket shall satisfy the following conditions:

The harness at charging station side shall hang vertically down to the ground plane (ALSE) or floor (OTS);The extraneous length shall be placed as close as possible to the ground plane (ALSE) or floor (OTS) and “Z-folded” if necessary. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user installation, the disposition of the excess cable shall be precisely noted in the test report.
The charging station should be placed outside of the 3 dB beamwidth of the receiving antenna. If this is not technically feasible, the charging station can be placed behind a panel of absorbers but not between the antenna and the vehicle.

2.2.2.2. Artificial network

AC power mains shall be applied to the vehicle through 50 µH/50 Ω AMN(s) (see Appendix 8, paragraph 4.).

DC power mains shall be applied to the vehicle through 5 µH/50 Ω High Voltage Artificial Networks (DC-charging-AN(s)) (see Appendix 8, paragraph 3.).

The AMN(s) / DC-charging-AN(s) shall be mounted directly on the ground plane (ALSE) or floor (OTS). The cases of the AMN(s) / DC-charging-AN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AMN / DC-charging-AN shall be terminated with a 50 Ω load.

2.2.2.3. Asymmetric artificial network

Local/private communication lines connected to signal/control ports and lines connected to wired network ports shall be applied to the vehicle through AAN(s).

The various AAN(s) to be used are defined in Appendix 8, paragraph 5.:

- Paragraph 5.1. for signal/control port with symmetric lines;

- Paragraph 5.2. for wired network port with PLC on power lines;

- Paragraph 5.3. for signal/control port with PLC (technology) on control pilot; and

- Paragraph 5.4. for signal/control port with control pilot.

The AAN(s) shall be mounted directly on the ground plane. The case of the AAN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AAN shall be terminated with a 50 Ω load.

If a charging station is used, AAN(s) are not required for the signal/control ports and/or for the wired network ports. The local/private communication lines between the vehicle and the charging station shall be connected to the auxiliary equipment on the charging station side to work as designed. If communication is emulated and if the presence of the AAN prevents proper communication then no AAN should be used

2.2.2.4. Power charging / local/private communication harness

The power charging local/private communication harness shall be laid out in a straight line between the AMN(s) / DC-charging-AN(s) / AAN(s) and the vehicle charging socket and shall be routed perpendicularly to the vehicle’s longitudinal axis (see Figure 3e and Figure 3g). The projected harness length from the side of the AMN(s) to the side of the vehicle shall be 0,8 (+0,2 / -0) m as shown in Figure 3f and Figure 3h.

For a longer cable, the extraneous length shall be “Z-folded” symmetrically. No contact or overlap is allowed between windings. The width of the Z-folded cable shall be between 500 mm and 1 000 mm. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user's installation, the disposition of the excess cable length shall be precisely noted in the test report.

The power charging local/private communication harness at vehicle side shall hang vertically at a distance of 100 (+200 / -0) mm from the vehicle body.

The whole harness shall be placed on a non-conductive, low relative permittivity (dielectric-constant) material ($\varepsilon_r \leq 1,4$), at (100 ± 25) mm above the ground plane (ALSE) or floor (OTS).

3. Measuring location

3.1. As an alternative to the requirements of CISPR 12 for vehicles of category L, the test surface may be any location that fulfils the conditions shown in Figure 2 of the Appendix to this Annex. In this case the measuring equipment shall lie outside the part shown in Figure 1 of Appendix 1 to this Annex.

3.2. Absorber lined shielded enclosures (ALSE) and outdoor test site (OTS) may be used. An ALSE has the advantage of all all-weather testing, a controlled environment and improved repeatability because of the stable chamber electrical characteristics.

4. Test requirements

4.1. The limits apply throughout the frequency range 30 to 1,000 MHz for measurements performed in an absorber lined shielded enclosure (ALSE) or an outdoor test site (OTS).

4.2. Measurements can be performed with either quasi-peak or peak detectors. The limits given in paragraphs 6.2. and 7.2. of this Regulation are for quasi-peak detectors.

If peak detectors are used**,** a correction factor of 20 dB as defined in CISPR 12 shall be applied.

4.3. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Table 1 and Table 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Peak detector*		*Quasi-peak detector*	
	RBW at -3 dB	*Minimum scan time*	*RBW at -6 dB*	*Minimum Scan time*
30 to 1,000	100/120 kHz	100 ms/MHz	120 kHz	20 s/MHz

Note: If a spectrum analyser is used for peak measurements, the video bandwidth shall be at least three times the resolution bandwidth (RBW).

Table 2 **Scanning receiver parameters**

Frequency range MHz	*Peak detector*			*Quasi-peak detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*
30 to 1,000	120 kHz	60 kHz	5 ms	120 kHz	60 kHz	1 s

[a] For purely broadband disturbances, the maximum frequency step size may be increased up to a value not greater than the bandwidth value.

4.4. Measurements

The Technical Service shall perform the test at the intervals specified in the CISPR 12 standard throughout the frequency range 30 to 1,000 MHz.

Alternatively, if the manufacturer provides measurement data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may divide the frequency range in 14 frequency bands 30-34, 34-45, 45-60, 60-80, 80-100, 100-130, 130-170, 170-225, 225-300, 300-400, 400-525, 525-700, 700-850 and 850-1,000 MHz and perform tests at the 14 frequencies giving the highest emission levels within each band to confirm that the vehicle meets the requirements of this Annex.

For configuration "REESS charging mode coupled to the power grid", if the manufacturer provides measurement data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type-Approval Authority for all the available charging modes configurations defined in 2.2, the Technical Service may perform tests only for one of the available charging mode configuration defined in 2.2 and divide the frequency range in 14 frequency bands 30-34, 34-45, 45-60, 60-80, 80-100, 100-130, 130-170, 170-225, 225-300, 300-400, 400-525, 525-700, 700-850 and 850-1,000 MHz and perform tests at the 14 frequencies giving the highest emission levels within each band to confirm that the vehicle meets the requirements of this Annex.

In the event that the limit is exceeded during the test, investigations shall be made to ensure that this is due to the vehicle and not to background radiation.

4.5. Readings

The maximum of the readings relative to the limit (horizontal and vertical polarization and antenna location on the left and right-hand sides of the vehicle) in each of the 14 frequency bands shall be taken as the characteristic reading at the frequency at which the measurements were made.

4.6. Antenna position

Measurements shall be made on the left and right sides of the vehicle.

The horizontal distance is from the reference point of the antenna to the nearest part of the vehicle body.

Multiple antenna positions may be required (both for 10 m and 3 m antenna distance) depending on the vehicle length. The same positions shall be used for both horizontal and vertical polarization measurements. The number of antenna positions and the position of the antenna with respect to the vehicle shall be documented in the test report.

- If the length of the vehicle is smaller than the 3 dB beamwidth of the antenna, only one antenna position is necessary. The antenna shall be aligned with the middle of the total vehicle (see Figure 4);

- If the length of the vehicle is greater than the 3 dB beamwidth of the antenna, multiple antenna positions are necessary in order to cover the total length of the vehicle (see Figure 5). The number of antenna positions shall allow to meet the following condition:

$$N \cdot 2 \cdot D \cdot \tan(\beta) \geq L \quad (1)$$

with:

N: number of antenna positions;

D: measurement distance (3 m or 10 m);

$2 \cdot \beta$: 3 dB antenna beamwidth angle in the plane parallel to ground (i.e. the E-plane beamwidth angle when the antenna is used in horizontal polarization, and the H-plane beamwidth angle when the antenna is used in vertical polarization);

L: total vehicle length covers the whole dimensions including tires, bumpers and lights, etc.

Depending of the chosen values of N (number of antenna positions) different set-up shall be used:

if N=1 (only one antenna position is necessary), the antenna shall be aligned with the middle of the total vehicle length (see Figure 4).

if N>1 (more than one antenna position is necessary), multiple antenna positions are necessary in order to cover the total length of the vehicle (see Figure 5). The antenna positions shall be symmetric in regard to the vehicle perpendicular axis.

Annex 4 - Appendix 1

Figure 1 **Clear horizontal surface free of electromagnetic reflection delimitation of the surface defined by an ellipse**




Figure 2 **Position of antenna in relation to the vehicle**




Figure 3 **Vehicle in configuration "REESS charging mode" coupled to the power grid:**

Example of test setup for vehicle with socket located on vehicle side (charging mode 1 or 2, AC powered, without communication, all dimensions in mm).

Figure 3a





Figure 3b



Key

1	vehicle under test
2	insulating support
3	charging cable (including EVSE for charging mode 2)
4	artificial mains network(s) grounded
5	power mains socket
6	extraneous length Z-folded

NOTE: The cable between the AC mains and the AMN may not be aligned in the same direction as the cable between the AMN and the EV.

Example of test setup for vehicle with socket located front / rear of vehicle (charging mode 1 or 2, AC powered, without communication).

Figure 3c





Figure 3d



Key

1	vehicle under test
2	insulating support
3	charging cable (including EVSE for charging mode 2)
4	artificial mains network(s) grounded
5	power mains socket

6	extraneous length Z-folded

NOTE: The cable between the AC mains and the AMN may not be aligned in the same direction as the cable between the AMN and the EV.

Example of test setup for vehicle with socket located on vehicle side(charging mode 3 or mode 4, with communication)

Figure 3e





Figure 3f



Key

1	vehicle under test
2	insulating support
3	charging harness with communication lines
4	AMN(s) or DC-charging-AN(s), grounded
5	power mains / supply socket (optional)
6	AAN(s), grounded (optional, not represented in the front view)
7	charging station (can be emulated)
8	communication lines
9	communication module
10	power cable
11	extraneous length Z-folded

NOTE : The cable between the AC/DC mains/supply and the AMN/DC-charging-AN may not be aligned in the same direction as the cable between the AMN/DC-charging-AN and the EV.

Example of test setup for vehicle with socket located front / rear of vehicle (charging mode 3 or mode 4, with communication)

Figure 3g





Figure 3h




Key

1	vehicle under test
2	insulating support
3	charging harness with communication lines
4	AMN(s) or DC-charging-AN(s), grounded
5	power mains / supply socket (optional)
6	AAN(s), grounded (optional, not represented in the front view)
7	charging station (can be emulated)
8	communication lines
9	communication module
10	power cable
11	extraneous length Z-folded

NOTE: The cable between the AC/DC mains/supply and the AMN/DC-charging-AN may not be aligned in the same direction as the cable between the AMN/DC-charging-AN and the EV.

Antenna position

Figure 4 **Antenna position for N = 1 (one antenna position to be used) – Horizontal polarization shown**




Key

1 vehicle under test

2 antenna

Figure 5 **Antenna positions for N = 2 (multiple antenna positions to be used) – Horizontal polarization shown**



Key

1vehicle under test

2 antenna (two positions)

Annex 5 Method of measurement of radiated narrowband electromagnetic emissions from vehicles

1. General

1.1. The test method described in this Annex shall only be applied to vehicles. This method concerns only the configuration of the vehicle other than "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the narrowband electromagnetic emissions that may emanate from microprocessor-based systems or other narrowband source.

If not otherwise stated in this Annex the test shall be performed according to CISPR 12.

1.3. For vehicles of category L the measurement location can be chosen according to Annex 4, paragraphs 3.1. and 3.2.

2. Vehicle state during tests

2.1. The ignition switch shall be switched on. The engine shall not be operating.

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

2.2. The vehicle's electronic systems shall all be in normal operating mode with the vehicle stationary.

2.3. All equipment which can be switched on permanently by the driver, passenger or by the ADS with internal oscillators > 9 kHz or repetitive signals should be in normal operation.

3. Measuring location

3.1. Absorber lined shielded enclosures (ALSE) and outdoor test site (OTS) may be used. An ALSE has the advantage of all all-weather testing, a controlled environment and improved repeatability because of the stable chamber electrical characteristics.

4 Test requirements

4.1. The limits apply throughout the frequency range 30 to 1,000 MHz for measurements performed in an absorber lined shielded enclosure (ALSE) or an outdoor test site (OTS).

4.2. Measurements shall be performed with an average detector.

4.3. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Table 1 and Table 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Average detector*	
	RBW at -3 dB	*Minimum scan time*
30 to 1,000	100/120 kHz	100 ms/MHz

Note: If a spectrum analyser is used for peak measurements, the video bandwidth shall be at least three times the resolution bandwidth (RBW).

Table 2 **Scanning receiver parameters**

Frequency range MHz	*Average detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*
30 to 1,000	120 kHz	60 kHz	5 ms

4.4. Measurements

The Technical Service shall perform the test at the intervals specified in the CISPR 12 standard throughout the frequency range 30 to 1,000 MHz.

Alternatively, if the manufacturer provides measurement data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may divide the frequency range in 14 frequency bands 30-34, 34-45, 45-60, 60-80, 80-100, 100-130, 130-170, 170-225, 225-300, 300-400, 400-525, 525-700, 700-850 and 850-1,000 MHz and perform tests at the 14 frequencies giving the highest emission levels within each band to confirm that the vehicle meets the requirements of this Annex.

In the event that the limit is exceeded during the test, investigations shall be made to ensure that this is due to the vehicle and not to background radiation including broadband radiation from any ESA.

4.5. Readings

The maximum of the readings relative to the limit (horizontal and vertical polarization and antenna location on the left and right-hand sides of the vehicle) in each of the 14 frequency bands shall be taken as the characteristic reading at the frequency at which the measurements were made.

4.6. Antenna position

Measurements shall be made on the left and right sides of the vehicle.

The horizontal distance is from the reference point of the antenna to the nearest part of the vehicle body.

Multiple antenna positions may be required (both for 10 m and 3 m antenna distance) depending on the vehicle length. The same positions shall be used for both horizontal and vertical polarization measurements. The number of antenna positions and the position of the antenna with respect to the vehicle shall be documented in the test report.

- if the length of the vehicle is smaller than the 3 dB beamwidth of the antenna, only one antenna position is necessary. The antenna shall be aligned with the middle of the total vehicle (see Figure 1)

- If the length of the vehicle is greater than the 3 dB beamwidth of the antenna, multiple antenna positions are necessary in order to cover the total length of the vehicle (see Figure 2). The number of antenna positions shall allow to meet the following condition:

$$N \cdot 2 \cdot D \cdot \tan(\beta) \geq L \quad (1)$$

with:

N: number of antenna positions.

D: measurement distance (3 m or 10 m).

$2 \cdot \beta$: 3 dB antenna beamwidth angle in the plane parallel to ground (i.e. the E-plane beamwidth angle when the antenna is used in horizontal polarization, and the H-plane beamwidth angle when the antenna is used in vertical polarization).

L: total vehicle length covers the whole dimensions including tires, bumpers and lights, etc.

Depending of the chosen values of N (number of antenna positions) different set-up shall be used:


if N=1 (only one antenna position is necessary), the antenna shall be aligned with the middle of the total vehicle length (see Figure 1).

if N>1 (more than one antenna position is necessary), multiple antenna positions are necessary in order to cover the total length of the vehicle (see Figure 2). The antenna positions shall be symmetric in regard to the vehicle perpendicular axis.

Annex 5 - Appendix 1

Antenna position

Figure 1 **Antenna position for N = 1 (one antenna position to be used) – Horizontal polarization shown**




Key

1 vehicle under test

2 antenna

Figure 2 **Antenna positions for N = 2 (multiple antenna positions to be used) – Horizontal polarization shown**



Key

1 vehicle under test

2 antenna (two positions)

Annex 6 Method of testing for immunity of vehicles to electromagnetic radiation

1. General

1.1. The test method described in this Annex shall only be applied to vehicles. This method concerns both configurations of vehicle:

(a) Other than "REESS charging mode coupled to the power grid";

(b) "REESS charging mode coupled to the power grid".

A vehicle is considered to be a “large vehicle”, if it is longer than 12 m and/or wider than 2.60 m and/or higher than 4.00 m.

1.2. Regular test method

This test is intended to demonstrate the immunity of the vehicle electronic systems. The vehicle shall be subject to electromagnetic fields as described in this Annex. The vehicle shall be monitored during the tests.

If not otherwise stated in this Annex the test shall be performed according to ISO 11451-2 in an ALSE:

• with front irradiation for vehicle not considered as “large vehicles”. Rear irradiation is specified in paragraph 5.1.3.

• with front irradiation and with additional antenna positions for “large vehicles”. Additional antenna position(s) shall be chosen by the manufacturer in conjunction with the Type-Approval Authority after considering the distribution of electronic systems with immunity related functions and the layout of any wiring harness. Tests shall be performed with levels defined in paragraph 6.4.2.1. of this Regulation. For REESS charging mode, only the electronic systems and wiring harnesses required for charging mode shall be considered for antenna positions.

1.3. Alternative test methods

The test may be alternatively performed in an outdoor test site for all vehicles (including “large vehicles”). The test facility shall comply with (national) legal requirements regarding the emission of electromagnetic fields. The test shall be performed according to ISO 11451-2 in an OTS:

• with front irradiation for vehicle not considered as “large vehicles”. Rear irradiation is specified in paragraph 5.1.3.

• with front irradiation and with additional antenna positions for “large vehicles”. Additional antenna position(s) shall be chosen by the manufacturer in conjunction with the Type Approval Authority after considering the distribution of electronic systems with immunity related functions and the layout of any wiring harness. Tests shall be performed with levels defined in paragraph 6.4.2.1. of this Regulation. For REESS charging mode, only the electronic systems and wiring harnesses required for charging mode shall be considered for antenna positions.

For “large vehicles”, the following alternative methods may be chosen by the manufacturer in conjunction with the Type Approval Authority:

• Harness excitation methods (BCI) according to ISO 11451-4 in the frequency range 20 to 2,000 MHz and immunity to external source saccording to ISO 11451-2 in ALSE or OTS in the frequency range 2,000 to 6,000 MHz with additional antenna position(s). Additional antenna positions shall be chosen by the manufacturer in conjunction with the Type Approval Authority after considering the distribution of electronic systems with immunity related functions and the layout of any wiring harness. Tests shall be performed with levels defined in paragraph 6.4.2.1. of this Regulation.

• Harness excitation methods (BCI) according to ISO 11451-4 in the frequency range 20 to 2,000 MHz and ESA immunity to external sources according to Annex 9 in the frequency range 2,000 to 6,000 MHz for all ESA involved in immunity related functions. ESA involved in immunity related functions shall be chosen by the manufacturer in conjunction with the Type Approval Authority. Vehicle test shall be performed with levels defined in paragraph 6.4.2.1. of this Regulation. ESA shall be performed with levels defined in paragraph 6.8.2.1. of this Regulation.


• Immunity to external sources according to ISO 11451-2 in ALSE or OTS in the frequency range 20 to 6,000 MHz with front irradiation and ESA immunity to external sources according to Annex 9 in the frequency range 20

to 6,000 MHz for ESA with immunity related functions out antenna beamwidth. Concerned ESA shall be chosen by the manufacturer in conjunction with the Type-Approval Authority Vehicle test shall be performed with levels defined in paragraph 6.4.2.1. of this Regulation. ESA tests shall be performed with levels defined in paragraph 6.8.2.1. of this Regulation.

Alternative method using ESA immunity to external sources according to Annex 9 does not require E-marking of the concerned ESA. The test report shall be prepared or approved by a laboratory accredited to ISO 17025 and recognized by the Type Approval Authority responsible for carrying out the tests and provided along with the information document shown in Annex 2B. The same test method (vehicle type approval in combination with ESA test report for Annex9) shall be applied during Conformity of Production test or any applicable test method according to this Annex.

1.4 Applicability of test methods:

Figure 1



2. Vehicle state during tests

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

2.1. Vehicle in configuration other than "REESS charging mode coupled to the power grid.

2.1.1. The vehicle shall be in an unladen condition except for necessary test equipment.

2.1.1.1. The engine shall normally turn the driving wheels at a steady speed of 50 km/h if there is no technical reason due to the vehicle to define a different condition. For vehicles of categories L_1 and L_2 the steady speed shall normally be turned at 25 km/h. The vehicle shall be on an appropriately loaded dynamometer or alternatively

supported on insulated axle stands with minimum ground clearance if no dynamometer is available. Where appropriate, transmission shafts, belts or chains may be disconnected (e.g. trucks, two- and three-wheel vehicles).

2.1.1.2. Basic Vehicle Conditions

The Paragraph defines minimum test conditions (as far as applicable) and failure criteria for vehicle immunity tests. Other vehicle systems, which can affect immunity related functions, shall be tested in a way to be agreed between manufacturer and Technical Service.

"50 km/h mode" vehicle test conditions	*Failure criteria*
Vehicle speed 50 km/h (respectively 25 km/h for **L**$_1$, L$_2$ vehicles) ±20 per cent (vehicle driving the rollers). **If** the vehicle is equipped with a cruise control system, it shall be used to maintain the required constant vehicle speed and maintained without any deactivation.	Speed variation greater than ±10 per cent of the nominal speed. In case of automatic gearbox: change of gear ratio inducing a speed variation greater than ±10 per cent of the nominal speed.
Dipped-beam headlamps ON (manual mode)	Lighting OFF (front light and rear light)
Specific warning (e.g Rotating/flashing light, signaling bar, siren…) ON	Specific warning OFF
Cluster operate in normal mode	Unexpected warning Inconsistent variation of the odometer
Rear view system	Unexpected movement of rear-view mirror Loss or freezing of the display (CMS)
Front wiper ON (manual mode) maximum speed	Complete stop of front wiper
Direction indicator on the side nearest to the opposing traffic ON	Frequency change (lower than 0.75 Hz or greater than 2.25 Hz). Duty cycle change (lower than 25 per cent or greater than 75 per cent).
Adjustable suspension in normal position	Unexpected significant variation
Driver's seat (if fitted) and steering wheel (if fitted) in medium position	Unexpected variation greater than 10 per cent of total range
Alarm unset	Unexpected activation of alarm
Horn OFF	Unexpected activation of horn
Airbag and safety restraint systems operational with inhibited passenger airbag if this function exists	Unexpected activation
Automatic doors closed	Unexpected opening
Adjustable endurance brake lever in normal position	Unexpected activation
Brake pedal not depressed	Unexpected activation of brake and unexpected activation of stop lights
ADS shall be operational but without ADS feature(s) activated	Unexpected behaviour of ADS

"Brake mode" vehicle test conditions	*Failure criteria*
Vehicle in a state that allows the braking system to operate normally, parking brake released, vehicle speed 0 km/h.	Stop lights inactivated during mode Brake warning light ON with loss of brake function.

Brake pedal depressed to activate the brake function and the stop lights without any dynamic cycle.	
Daytime running lamps (DRL) ON	DRL inactivated during mode
ADS shall be operational but without ADS feature(s) activated	Unexpected behaviour of ADS

For vehicles equipped with an ADS, the 'Active ADS Mode' described below shall be applied in addition to the other test conditions specified in this Annex.

"Active ADS Mode" vehicle test conditions (1)	*Failure criteria*
ADS Configuration: The ADS test configuration shall be activated. The ADS feature(s) shall be performing the DDT as defined by the manufacturer's test plan. (1)	Any degradation in ADS performance which impacts immunity related functions.
Vehicle Speed 50 km/h (respectively 25 km/h for L1, L2 vehicles) ±20 per cent (vehicle driving the rollers). Or 80 per cent of V_{max} of the vehicle with the ADS feature activated, when maximum speed with the ADS feature activated is lower than 50 km/h. Or, in case of vehicles other than categories X and Y, vehicle speed 0 km/h.	Speed variation greater than ±10 per cent of the nominal speed. In case of automatic gearbox: change of gear ratio inducing a speed variation greater than ±10 per cent of the nominal speed. Or vehicle sets in motion.
Dipped-beam headlamps ON. (2)	Lighting OFF (front light and rear light).
Specific Warning (e.g. Rotating/flashing light, signalling bar, siren…) ON. (2)	Specific warning OFF.
Cluster and/or ADS status displays operate in normal mode.	Unexpected warning, Inconsistent variation of the odometer.
Front wiper ON at maximum speed. (2)	Complete stop of front wiper.
Direction indicator on the side nearest to the opposing traffic ON. (2)	Frequency change (lower than 0.75 Hz or greater than 2.25 Hz). Duty cycle change (lower than 25 per cent or greater than 75 per cent).
Adjustable Suspension In normal position. (2)	Unexpected significant variation.
Driver's seat (if fitted) and steering wheel (if fitted) in medium position. (2)	Unexpected variation greater than 10 per cent of total range
Alarm Unset. (2)	Unexpected activation of alarm.
Horn OFF. (2)	Unexpected activation of horn.
Airbag and safety restraint systems operational with inhibited passenger airbag if this function exists. (2)	Unexpected activation.
Automatic Doors: Closed. (2) and (3)	Unexpected opening.
Adjustable endurance brake lever in normal position (2)	Unexpected activation
Brake pedal not depressed (2)	Unexpected activation of brake and unexpected activation of stop lights.
ADS steering equipment in straight ahead position (4)	Unexpected variation

(1) For vehicles equipped with an ADS, where the system cannot be fully activated or function normally within the EMC test environment, the alternative procedures and configurations described in paragraph 6.11.3. shall apply.

(2) This function need only to be monitored if the ADS exercises control over the function

(3) To ensure the safety of the test equipment and prevent damage from inadvertent operation, the final stage of mechanical actuation (e.g., brake callipers or automatic doors) may be bypassed, disconnected or inhibited by test software. This may be achieved e.g. by blocking hydraulic lines or disconnecting electrical connections to the brake actuators. In such cases, the ADS braking control logic and command signals shall remain fully active and be monitored for any degradation of performance or unintended activation using an alternative monitoring system (e.g., hydraulic pressure sensors or electrical load simulators). The specific alternative method used shall be subject to the agreement of the Type Approval Authority and shall be documented in the test report.

(4) In addition, ADS steering equipment may be tested in a way to be agreed between manufacturer and Technical Service.

For vehicles equipped with an ADS, for which the braking mode cannot be applied with ADS operational without ADS feature(s) activated, the test mode described below shall be applied in addition to the other test conditions specified in this Annex.

"Brake mode" with active ADS vehicle test conditions	*Failure criteria*
ADS Configuration: The ADS test configuration shall be activated. The ADS feature(s) shall be performing the DDT as defined by the manufacturer's test plan. (1)	Any degradation in ADS performance which impacts immunity related functions.
Vehicle in a state that allows the braking system to operate normally, parking brake released, vehicle speed 0 km/h. Brake and the stop lights are activated by the ADS without any dynamic cycle.	Stop lights inactivated during mode Brake warning light ON with loss of brake function.
Daytime running lamps (DRL) ON (2)	DRL inactivated during mode

(1) For vehicles equipped with an ADS, where the system cannot be fully activated or function normally within the EMC test environment, the alternative procedures and configurations described in paragraph 6.11.3. shall apply.

(2) This function needs only to be monitored if the ADS exercises control over the function.

AECS vehicle test conditions before and after immunity test	*Failure criteria*
A manual emergency call shall be triggered according to the vehicle manufacturer's instructions, both before and after conducting the 50km/h or brake mode test.	An emergency call is not established.
Once the MSD has been received the emergency call is established, voice communication shall be evaluated, but only if voice communications are available in the AECS system.	The voice originating inside the vehicle cannot be heard clearly by the remote listener with satisfactory intelligibility. The speech of the remote speaker cannot be heard clearly in the vehicle with satisfactory intelligibility.
After the evaluation of the voice call, the emergency call shall be terminated. Subsequently, the transmitted Minimum Set of Data (MSD) shall be evaluated.	Vehicle location data is NOT transmitted, or position error is greater than 150m. Time stamp is not transmitted, or time error is greater than 60 seconds.

	Vehicle identification number is not transmitted correctly.

AECSs vehicle test conditions during immunity test	*Failure criteria*
During the 50km/h or brake test mode, the warning signal device (also known as the tell-tale, which provides a failure indication), and all other displays used for indicating AECS faults, shall be monitored. There is no requirement for a cellular network or satellite navigation signals during these tests.	Emergency calling systems does not operate as intended as indicated by: Failure indication of AECS warning signal device or other vehicle displays. Upon completion of the test, diagnostic trouble code, which is related to emergency calling systems failure indication, is stored in the device memory.

AVAS test conditions	*Failure criteria*
Vehicle is tested in an operating state where the AVAS Function/sound is active (if applicable) (1)	Loss of AVAS function (loss of sound or system error indicator)
(1) This test may be incorporated into Brake or 50 km/h mode if AVAS system is active in these modes. If AVAS system is not operational during these two modes, the operating conditions (e.g. vehicle speed) shall be agreed between the Technical Service and the Vehicle Manufacturer.	

2.1.1.3. All equipment which can be switched on permanently by the driver, passenger or the ADS, shall be in normal operation.

2.1.1.4. All other systems which affect the driver's or ADS feature’s control of the vehicle shall be (on) as in normal operation of the vehicle.

2.1.1.6. If the vehicle is equipped with an AECS according to UN Regulation No. 144, it shall be tested over the air for the transmission of Minimum Set of Data (MSD) and voice call via a real Public Land Mobile Network (PLMN) or via a network simulator before and after 50 km/h or brake mode and using a private safety answering point (PSAP).
In case of a voice call via a real PLMN, emergency call number should be changed to dedicated PSAP number in order to avoid false calls to the emergency services. Only one specific cellular configuration, including one frequency band and one channel, within a single cellular technology (e.g. 2G, 3G, 4G, 5G.) shall be tested.
Vehicle manufacturer and Technical Service shall review the AECS warning signal strategy if it will detect AECS system faults even when there is no network coverage. If it is not possible to distinguish between lack of network coverage and a system fault, alternative arrangements shall be made to enable this.

2.1.2. If there are vehicle electrical/electronic systems which form an integral part of the immunity related functions, other than an ADS, which will not operate under the conditions described in paragraph 2.1., it will be permissible for the manufacturer to provide a report or additional evidence to the Technical Service that the vehicle electrical/electronic system meets the requirements of this Regulation. Such evidence shall be retained in the type approval documentation.

2.1.3. Only non-perturbing equipment shall be used while monitoring the vehicle. The vehicle exterior and the passenger compartment shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).


2.2. Vehicle in configuration "REESS charging mode coupled to the power grid".

2.2.1. The vehicle shall be in an unladen condition except for necessary test equipment.

2.2.1.1. The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 2.

Figure 2 **Charging mode configuration for Annex 6**



2.2.1.2. Basic vehicle conditions

The paragraph defines minimum test conditions (as far as applicable) and failures criteria for vehicle immunity tests. Other vehicle systems, which can affect immunity related functions, shall be tested in a way to be agreed between manufacturer and Technical Service.

"REESS charging mode" vehicle test conditions	*Failure criteria*
The REESS shall be in charging mode. The REESS State of charge (SOC) shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole frequency range measurement (this may lead to split the measurement in different sub-bands with the need to discharge the vehicle's	Vehicle sets in motion.

"REESS charging mode" vehicle test conditions	*Failure criteria*
traction battery before starting the next sub-bands). If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum value or to a minimum of 16 A (if the 20 per cent of its maximum value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type Approval Authorities. In case of multiple batteries the average state of charge shall be considered.	Unexpected release of the parking brake. Loss of Parking position for automatic transmission**.**

2.2.1.3. All other equipment which can be switched ON by the driver, passenger or ADS shall be OFF.

2.2.2. Only non-perturbing equipment shall be used while monitoring the vehicle. The vehicle exterior and the passenger compartment shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).

2.2.3. The test set-up for the connection of the vehicle in configuration "REESS charging mode coupled to the power grid" is shown in Figures 4a to 4h (depending of AC or DC power charging mode, location of charging plug and charging with or without communication) of Appendix 1 to this Annex.

2.3. Vehicle in charging mode 1 or mode 2 (AC power charging without communication)

2.3.1. Charging station / Power mains

The power mains socket can be placed anywhere in the test site with the following conditions:

The socket(s) shall be placed on the ground plane (ALSE) or floor (OTS);The length of the harness between the power mains socket and the AMN(s) shall be kept as short as possible, but not necessarily aligned with the charging harness;The harness shall be placed as close as possible to the ground plane (ALSE) or floor (OTS).

2.3.2. Artificial network

Power mains shall be applied to the vehicle through 50 µH/50 Ω artificial networks (AMN(s)) (see Appendix 8, paragraph 4.).

The AMN(s) shall be mounted directly on the ground plane (ALSE) or floor (OTS). The case of the AMN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AMN shall be terminated with a 50 Ω load.

2.3.3. Power charging harness

The power charging harness shall be placed in a straight line between the AMN(s) and the vehicle charging plug and shall be routed perpendicularly to the vehicle longitudinal axis (see Figure 5a and Figure 5c). The projected harness length from the side of the AMN(s) to the side of the vehicle shall be 0,8 (+0,2 / -0) m as shown in Figure 5b and Figure 5d.

For a longer cable, the extraneous length shall be “Z-folded” symmetrically. No contact or overlap is allowed between windings. The width of the Z-folded cable shall be between 500 mm and 1 000 mm. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user's installation, the disposition of the excess cable length shall be precisely noted in the test report.

The charging harness at the vehicle side shall hang vertically at a distance of 100 (+200 / -0) mm from the vehicle body.

The whole harness shall be placed on a non-conductive, low relative permittivity (dielectric-constant) material ($\varepsilon_r \leq 1{,}4$), at (100 ± 25) mm above the ground plane (ALSE) or floor (OTS).

2.4. Vehicle in charging mode 3 (AC power charging with communication) or mode 4 (DC power charging with communication)

2.4.1. Charging station / Power mains

The charging station may be placed either in the test site or outside the test site.

If the local/private communication between the vehicle and the charging station can be simulated, the charging station may be replaced by a supply from the AC power mains network.

In both cases power mains and communication or signal lines socket(s) shall be placed in the test site with the following conditions:

The socket(s) shall be placed on the ground plane (ALSE) or floor (OTS);The length of the harness between the power mains / local/private communication socket and the AMN(s) / DC-charging-AN(s) / AAN(s) shall be kept as short as possible, but not necessarily aligned with the charging harness;The harness between the power mains / local/private communication socket and the AMN(s) / DC-charging-AN(s) / AAN(s) shall be placed as close as possible of the ground plane (ALSE) or floor (OTS).
If the charging station is placed inside the test site then the harness between the charging station and the power mains / local/private communication socket shall satisfy the following conditions:

The harness at charging station side shall hang vertically down to the ground plane (ALSE) or floor (OTS);The extraneous length shall be placed as close as possible to the ground plane (ALSE) or floor (OTS) and “Z-folded” if necessary. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user installation, the disposition of the excess cable shall be precisely noted in the test report;
The charging station should be placed outside the beamwidth of the receiving antenna.

2.4.2. Artificial network

AC power mains shall be applied to the vehicle through 50 µH/50 Ω AMN(s) (see Appendix 8, paragraph 4.).

DC power mains shall be applied to the vehicle through 5 µH/50 Ω High Voltage Artificial Networks (DC-charging-AN(s)) (see Appendix 8, paragraph 3.).

The AMN(s) / DC-charging-AN(s) shall be mounted directly on the ground plane (ALSE) or floor (OTS). The cases of the AMN(s) / DC-charging-AN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AMN / DC-charging-AN shall be terminated with a 50 Ω load.

2.4.3. Asymmetric artificial network

Local/private communication lines connected to signal/control ports and lines connected to wired network ports shall be applied to the vehicle through AAN(s).

The various AAN(s) to be used are defined in Appendix 8, paragraph 5.:

- Paragraph 5.1. for signal/control port with symmetric lines;

- Paragraph 5.2. for wired network port with PLC on power lines;

- Paragraph 5.3. for signal/control port with PLC (technology) on control pilot; and

- Paragraph 5.4. for signal/control port with control pilot.

The AAN(s) shall be mounted directly on the ground plane. The case of the AAN(s) shall be bonded to the ground plane (ALSE) or connected to the protective earth (OTS, e.g. an earth rod).

The measuring port of each AAN shall be terminated with a 50 Ω load.

If a charging station is used, AAN(s) are not required for the signal/control ports and/or for the wired network ports. The local/private communication lines between the vehicle and the charging station shall be connected to

the auxiliary equipment on the charging station side to work as designed. If communication is emulated and if the presence of the AAN prevents proper communication then no AAN should be used

2.4.4. Power charging / local/private communication harness

The power charging local/private communication harness shall be laid out in a straight line between the AMN(s) / DC-charging-AN(s) / AAN(s) and the vehicle charging socket and shall be routed perpendicularly to the vehicle's longitudinal axis (see Figure 5e and Figure 5g). The projected harness length from the side of the AMN(s) to the side of the vehicle shall be 0,8 (+0,2 / - 0) m as shown in Figure 5f and Figure 5h.

For a longer cable, the extraneous length shall be "Z-folded" symmetrically. No contact or overlap is allowed between windings. The width of the Z-folded cable shall be between 500 mm and 1 000 mm. If it is impractical to do so because of cable bulk or stiffness, or because the testing is being done at a user's installation, the disposition of the excess cable length shall be precisely noted in the test report.

The power charging local/private communication harness at vehicle side shall hang vertically at a distance of 100 (+200 / -0) mm from the vehicle body.

The whole harness shall be placed on a non-conductive, low relative permittivity (dielectric-constant) material ($\varepsilon_r \leq 1{,}4$), at (100 ± 25) mm above the ground plane (ALSE) or floor (OTS).

3. Reference point

3.1. For the purposes of this Annex, the reference point is the point at which the field strength shall be established and shall be defined as follows:

3.2. For categories M, N, O, T, R and S vehicles according to ISO 11451-2.

3.3. For category L vehicles:

3.3.1. At least 2 m horizontally from the antenna phase centre or at least 1 m vertically from the radiating elements of a transmission-line-system (TLS);

3.3.2. On the vehicle's centre line (plane of longitudinal symmetry).

3.3.3. At a height of 1.0 ± 0.05 m above the plane on which the vehicle rests or 2.0 ± 0.05 m if the minimum height of the roof of any vehicle in the model range exceeds 3.0 m.

3.3.4. Either at 1.0 ± 0.2 m behind the vertical centreline of the vehicle's front wheel(s) (point C in Figure 1 of Appendix 1 to this Annex) in the case of three-wheeled or four-wheeled vehicles.

Or at 0.2 ± 0.2 m behind the vertical centreline of the vehicle's front wheel (point D in Figure 2 of Appendix 1 to this Annex) in the case of two-wheeled vehicles.

3.3.5. If it is decided to radiate the rear of the vehicle, the reference point shall be established as in paragraphs 3.3.1. to 3.3.4. above. The vehicle shall then be installed facing away from the antenna and positioned as if it had been horizontally rotated 180° around its centre point, i.e. such that the distance from the antenna to the nearest part of the outer body of the vehicle remains the same. This is illustrated in Figure 3 of Appendix 1 to this Annex.

3.4. If a vehicle is longer than 12 m and/or wider than 2.60 m and/or higher than 4.00 m, and tested according to ISO 11451-2, then additional reference point(s) shall be chosen by the manufacturer in conjunction with the Type Approval Authority after considering the distribution of electronic systems with immunity related functions and the layout of any wiring harness (see Appendix 1, Figure 5).

4. Test requirements

4.1. Frequency range, dwell times, polarization.

The vehicle shall be exposed to electromagnetic radiation in the 20 to 6,000 MHz frequency ranges in vertical polarization.

The test signal modulation shall be:

(a) AM (amplitude modulation), with 1 kHz modulation and 80 per cent modulation depth in the 20 to 400 MHz frequency range;

(b) PM2 (pulse modulation type 2), T_{on} 3 µs, period 3,333 µs in the 2,700 to 3,100 MHz frequency range; and

(c) PM3 (pulse modulation type 3), T_{on} 500 µs, period 1,000 µs in the 380 to 2,700 MHz and the 3,100 to 6,000 MHz frequency ranges.

If not otherwise agreed between Technical Service and vehicle manufacturer.

Frequency step size and dwell time shall be chosen according to ISO 11451-1.

4.1.1. The Technical Service shall perform the test at the intervals specified in ISO 11451-1 throughout the frequency range 20 to 6,000 MHz.

Alternatively, if the manufacturer provides measurement to data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may choose a reduced number of spot frequencies in the range (e.g. 27, 45, 65, 90, 120, 150, 190, 230, 280, 380, 450, 600, 750, 900, 1,300, 1,800, 2,360, 2,600, 3,000, 3,600, 5,200 and 5,900 MHz) to confirm that the vehicle meets the requirements of this Annex.

If the manufacturer provides measurement data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type-Approval Authority for all the charging modes configurations defined in paragraph 2.2.1.1, the Technical Service may perform tests only for one charging mode configurations defined in paragraph 2.2.1.2 and for a reduced number of spot frequencies in the range (e.g. 27, 45, 65, 90, 120, 150, 190, 230, 280, 380, 450, 600, 750, 900, 1,300, 1,800 2,360, 2,600, 3,000, 3,600, 5,200 and 5,900 MHz) to confirm that the vehicle meets the requirements of this Annex.

If a vehicle fails the test defined in this Annex, it shall be verified as having failed under the relevant test conditions and not as a result of the generation of uncontrolled fields.

5. Generation of required field strength

5.1. Test methodology

5.1.1. The substitution method according to ISO 11451-1, shall be used to establish the test field conditions.

5.1.2. Calibration

For TLS four horizontal field probes shall be used.

For antennas four field probes at the vehicle reference line shall be used.

5.1.3. Test phase

The vehicle shall be positioned with the centre line of the vehicle on the vehicle reference point or line. The vehicle shall normally face a fixed antenna. However, where electronic control units with immunity related functions and the associated wiring harness are predominantly in the rear half of the vehicle, the test should normally be carried out with the vehicle facing away from the antenna and positioned as if it had been horizontally rotated 180° around its centre point, i.e. such that the distance from the antenna to the nearest part of the outer body of the vehicle remains the same. In the case of “large vehicles” which have electronic control units with immunity related functions and associated wiring harness which are not located in the region illuminated at the default reference point of the regular test method, then additional reference point(s) may be established. The additional point(s) shall be chosen by the manufacturer in conjunction with the Type Approval Authority after considering the distribution of electronic systems and the layout of any wiring harness.

Such testing may only take place if the physical construction of the chamber permits. The antenna location shall be noted in the test report.

Annex 6 - Appendix 1

Figure 1




Figure 2



The reference point is in this plane
0.2 ± 0.2 m
Vertical axis of the front wheel
(point D)

Figure 3





Figure 4 **Example of a selection of antenna placements for lateral illumination of a large vehicle**

Dimensions in metres



Key

θ 3 dB antenna beamwidth

D-bumper the distance between the tip or phase centre of the antenna and the nearest part of the vehicle body without considering small extruding elements (such as side mirrors or fenders)

Figure 5 **Vehicle in configuration "REESS charging mode coupled to the power grid**

Example of test setup for vehicle with socket located on vehicle side (charging mode 1 or 2, AC powered, without communication, all dimensions in mm)

Figure 5a





Figure 5b



Key

1 vehicle under test

2 insulating support

3 charging harness (including EVSE for charging mode 2)

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

NOTE: The cable between the AC mains and the AMN may not be aligned in the same direction as the cable between the AMN and the EV.

Example of test setup for vehicle with socket located front / rear of vehicle side (charging mode 1 or 2, AC powered, without communication)

Figure 5c





Figure 5d



Key

1 vehicle under test

2 insulating support

3 charging harness (including EVSE for charging mode 2)

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

NOTE: The cable between the AC mains and the AMN may not be aligned in the same direction as the cable between the AMN and the EV.

Example of test setup for vehicle with socket located on vehicle side (charging mode 3 or mode 4, with communication)

Figure 5e





Figure 5f



Key

1 vehicle under test

2 insulating support

3 charging harness with local/private communication lines

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

6 AAN(s) grounded (optional)

7 charging station

8 communication lines

9 communication module

10 power cable

NOTE: The cable between the AC/DC mains/supply and the AMN/DC-charging-AN may not be aligned in the same direction as the cable between the AMN/DC-charging-AN and the EV.

Example of test setup for vehicle with socket located front / rear of the vehicle side (charging mode 3 or mode 4, with communication)

Figure 5g





Figure 5h



Key

1	vehicle under test
2	insulating support
3	charging harness with communication lines
4	AMN(s) or DC-charging-AN(s), grounded
5	power mains / supply socket (optional)
6	AAN(s) grounded (optional, not represented in the front view)
7	charging station (can be emulated)
8	communication lines
9	communication module
10	power cable

NOTE: The cable between the AC/DC mains/supply and the AMN/DC-charging-AN may not be aligned in the same direction as the cable between the AMN/DC-charging-AN and the EV.

Annex 7 Method of measurement of radiated broadband electromagnetic emissions from electrical/electronic sub - assemblies (ESAs)

1. General

1.1. The test method described in this Annex may be applied to ESAs, which may be subsequently fitted to vehicles, which comply with Annex 4.

This method concerns both kinds of ESA:

(a) Other ESAs than involved in "REESS charging mode coupled to the power grid".

(b) ESAs involved in "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure broadband electromagnetic emissions from ESAs (e.g. ignition systems, electric motor, onboard battery charging unit, etc.).

If not otherwise stated in this Annex the test shall be performed according CISPR 25.

2. ESA state during tests

2.1. The ESA under test shall be in normal operation mode, preferably in maximum load.

ESAs involved in "REESS charging mode coupled to the power grid" shall be in charging mode.

The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole frequency range measurement (this may lead to split the measurement in different sub-bands with the need to discharge the vehicle's traction battery before starting the next sub-bands).

If the test is not performed with a REESS the ESA should be tested at rated current.

If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the type approval authorities.

3. Test arrangements

3.1. For ESA other than involved in "REESS charging mode coupled to the power grid" the test shall be performed according to the ALSE method described in Clause 6.4 of CISPR 25.

3.2. For ESAs in configuration "REESS charging mode coupled to the power grid" the test arrangement shall be according to Figure 2 of the appendix to this Annex.

3.2.1. The shielding configuration shall be according to the vehicle series configuration. Generally all shielded High Voltage (HV) parts shall be properly connected with low impedance to ground (e.g. AN, cables, connectors etc.). ESAs and loads shall be connected to ground. The external HV power supply shall be connected via feed-through-filtering.

3.2.2. The ESA power supply lead shall be connected to the power supply through an HV-AN (for ESA with DC HV supply) and/or AMN (for ESA with AC supply).

DC HV supply shall be applied to the ESA via a 5 μH/50 Ω HV-AN (see Appendix 8, paragraph 2.).

AC supply shall be applied to the ESA via a 50 μH/50 Ω AMN (see Appendix 8, paragraph 4.).

3.2.3. Unless otherwise specified the length of the Low Voltage (LV) harness and the HV harness parallel to the front edge of the ground plane shall be 1,500 mm (±75 mm). The total length of the test harness including the connector shall be 1,700 mm (+300/-0 mm). The distance between the LV harness and the HV harness shall be 100 mm (+100/-0 mm).

3.2.4. All of the harnesses shall be placed on a non-conductive, low relative permittivity material ($\varepsilon_r \leq 1.4$), at 50 mm (±5 mm) above the ground plane.

3.2.5. Shielded supply lines for HV+ and HV- line and three phase lines may be coaxial cables or in a common shield depending on the used plug system. The original HV-harness from the vehicle may be used optionally.

3.2.6. Unless otherwise specified, the ESA case shall be connected to the ground plane either directly or via defined impedance.

3.2.7. For onboard chargers, the AC/DC power lines shall be placed the furthest from the antenna (behind LV and HV harness). The distance between the AC/DC power lines and the closest harness (LV or HV) shall be 100 mm (+100/-0 mm).

3.3. Alternative measuring location

As an alternative to an absorber lined shielded enclosure (ALSE) an open area test site (OATS), which complies with the requirements of CISPR
16-1-4 may be used (see Figure 1 of the appendix to this Annex).

3.4. Ambient

To ensure that there is no extraneous noise or signal of a magnitude sufficient to affect materially the measurement, measurements shall be taken before or after the main test. In this measurement, the extraneous noise or signal shall be at least 6 dB below the limits of interference given in paragraph 6.5.2.1. of this Regulation, except for intentional narrowband ambient transmissions.

4. Test requirements

4.1. The limits apply throughout the frequency range 30 to 1,000 MHz for measurements performed in an absorber lined shielded enclosure (ALSE) or open area test site (OATS).

4.2. Measurements can be performed with either quasi-peak or peak detectors. The limits given in paragraphs 6.5. and 7.10. of this Regulation are for quasi-peak detectors. If peak detectors are used a correction factor of 20 dB as defined in CISPR 12 shall be applied.

4.3. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Table 1 and Table 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Peak detector*		*Quasi-peak detector*	
	RBW at -3 dB	*Minimum scan time*	*RBW at -6 dB*	*Minimum scan time*
30 to 1,000	100/120 kHz	100 ms/MHz	120 kHz	20 s/MHz

Note: If a spectrum analyser is used for peak measurements, the video bandwidth shall be at least three times the resolution bandwidth (RBW).

Table 2 **Scanning receiver parameters**

Frequency range *MHz*	*Peak detector*			*Quasi-peak detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*
30 to 1,000	120 kHz	60 kHz	5 ms	120 kHz	60 kHz	1 s

[a] For purely broadband disturbances, the maximum frequency step size may be increased up to a value not greater than the bandwidth value.

Note: For emissions generated by brush commutator motors without an electronic control unit, the maximum step size may be increased up to five times the bandwidth.

4.4. Measurements

Unless otherwise specified the configuration with the LV harness closer to the antenna shall be tested.

The phase centre of the antenna shall be in line with the centre of the longitudinal part of the wiring harnesses for frequencies up to 1,000 MHz.

The Technical Service shall perform the test at the intervals specified in the CISPR 12 standard throughout the frequency range 30 to 1,000 MHz.

Alternatively, if the manufacturer provides measurement to data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may divide the frequency range in 14 frequency bands 30-34, 34-45, 45-60, 60-80, 80-100, 100-130, 130-170, 170-225, 225-300, 300-400, 400-525, 525-700, 700-850 and 850- 1,000 MHz and perform tests at the 14 frequencies giving the highest emission levels within each band to confirm that the ESA meets the requirements of this Annex.

In the event that the limit is exceeded during the test, investigations shall be made to ensure that this is due to the ESA and not to background radiation.

4.5. Readings

The maximum of the readings relative to the limit (horizontal/vertical polarization) in each of the 14 frequency bands shall be taken as the characteristic reading at the frequency at which the measurements were made.

Annex 7 - Appendix 1

Figure 1 **Open area test site: Electrical/electronic sub-assembly test area boundary**
Level clear area free from electromagnetic reflecting surfaces





Figure 2 **Test configuration for ESAs involved in "REESS charging mode coupled to the power grid" (example for biconical antenna)**

Dimensions in millimetres

Top view (horizontal polarization)



Key	12 RF absorber material
1 ESA (grounded locally if required in test plan)	13 stimulation and monitoring system
2 LV Test harness	14 HV harness
3 LV Load simulator (placement and ground connection according to CISPR 25, Clause 6.4.2.5)	15 HV load simulator
4 power supply (location optional)	16 HV AN
5 LV Artificial network (AN)	17 HV power supply
6 ground plane (bonded to shielded enclosure)	18 HV feed-through
7 low relative permittivity support ($\varepsilon_r \leq 1.4$)	19 AC/DC charger harness
8 biconical antenna	20 AC/DC load simulator (e.g. Programmable Logic Controller (PLC))

9 high-quality coaxial cable e.g. double-shielded (50 Ω)	21 AMN(s) or DC-charging-AN(s)
10 bulkhead connector	22 AC/DC power supply
11 measuring instrument	23 AC/DC feed-through

Annex 8 Method of measurement of radiated narrowband electromagnetic emissions from electrical/electronic sub - assemblies (ESAs)

1. General

1.1. The test method described in this Annex may be applied to ESAs, which may be subsequently fitted to vehicles, which comply, with Annex 5.

This method concerns only ESA other than those involved in "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the narrowband electromagnetic emissions such as might emanate from a microprocessor-based system.

If not otherwise stated in this Annex the test shall be performed according to CISPR 25.

2. ESA state during tests

The ESA under test shall be in normal operation mode, preferably in maximum load.

3. Test arrangements

3.1. The test shall be performed according to ALSE method described in paragraph 6.4. of CISPR 25.

3.2. Alternative measuring location

As an alternative to an absorber lined shielded enclosure (ALSE) an open area test site (OATS) which complies with the requirements of CISPR 16-1-4 may be used (see Figure 1 of the appendix to Annex 7).

3.3. Ambient

To ensure that there is no extraneous noise or signal of a magnitude sufficient to affect materially the measurement; measurements shall be taken before or after the main test. In this measurement, the extraneous noise or signal shall be at least 6 dB below the limits of interference given in paragraph 6.6.2.1. of this Regulation, except for intentional narrowband ambient transmissions.

4. Test requirements

4.1. The limits apply throughout the frequency range 30 to 1,000 MHz for measurements performed in an absorber lined shielded enclosure (ALSE) or open area test site (OATS).

4.2. Measurements shall be performed with an average detector.

4.3. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Tables 1 and 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Average detector*	
	RBW at -3 dB	*Minimum scan time*

30 to 1,000	100/120 kHz	100 ms/MHz

Note: If a spectrum analyser is used for peak measurements, the video band width shall be at least three times the resolution band width (RBW)

Table 2 **Scanning receiver parameters**

Frequency range MHz	*Average detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*
30 to 1,000	120 kHz	60 kHz	5 ms

4.4. Measurements

The Technical Service shall perform the test at the intervals specified in the CISPR 12 standard throughout the frequency range 30 to 1,000 MHz.

Alternatively, if the manufacturer provides measurement to data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may divide the frequency range in 14 frequency bands 30-34, 34-45, 45-60, 60-80, 80-100, 100-130, 130-170, 170-225, 225-300, 300-400, 400-525, 525-700, 700-850 and 850-1,000 MHz and perform tests at the 14 frequencies giving the highest emission levels within each band to confirm that the ESA meets the requirements of this Annex. In the event that the limit is exceeded during the test, investigations shall be made to ensure that this is due to the ESA and not to background radiation including broadband radiation from the ESA.

4.5. Readings

The maximum of the readings relative to the limit (horizontal/vertical polarisation) in each of the 14 frequency bands shall be taken as the characteristic reading at the frequency at which the measurements were made.

Annex 9 Method(s) of testing for immunity of electrical/electronic sub-assemblies (ESAs) to electromagnetic radiation

1. General

1.1. The test method(s) described in this Annex applies to ESAs.

1.2. Test methods

This method concerns both kinds of ESA:

(a) Other ESAs than involved in "REESS charging mode coupled to the power grid";

(b) ESAs involved in "REESS charging mode coupled to the power grid".

1.2.1. ESAs may comply with the requirements of any combination of the following test methods at the manufacturer's discretion provided that these results in the full frequency range specified in paragraph 3.1. of this Annex being covered:

(a) Absorber chamber test according to ISO 11452-2;

(b) TEM cell testing according to ISO 11452-3;

(c) Bulk current injection testing according to ISO 11452-4;

(d) Stripline testing according to ISO 11452-5;

(e) Reverberation chamber test according to ISO 11452-11;

ESAs in configuration "REESS charging mode coupled to the power grid" shall comply with the requirements of the combination of the Absorber chamber test according to ISO 11452-2 and Bulk current injection testing

according to ISO 11452-4 at the manufacturer's discretion provided that these results in the full frequency range specified in paragraph 3.1. of this Annex being covered.

(Frequency range and general test conditions shall be based on ISO 11452-1).

2. State of ESA during tests

2.1. The test conditions shall be according to ISO 11452-1.

2.2. The ESA under test shall be switched on and shall be stimulated to be in normal operation condition. It shall be arranged as defined in this Annex unless individual test methods dictate otherwise.

2.3. The paragraph defines minimum test conditions for ESAs involved in "REESS charging mode coupled to the power grid

"REESS charging mode" ESA test conditions	*Failure criteria*
The REESS shall be in charging mode. The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle’s traction battery before starting the next time slot). If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type-Approval Authorities. In case of multiple batteries the average state of charge shall be considered.	Temporary loss of charging function is allowed, provided that there is no incorrect charging condition (e.g. over-current, overvoltage) and the function can be restored by a simple intervention, without the use of tools, such as turning off/on the DUT, after the disturbance is removed.

2.4. Any extraneous equipment required to operate the ESA under test shall not be in place during the calibration phase. No extraneous equipment shall be closer than 1 m from the reference point during calibration.

2.5. To ensure reproducible measurement results are obtained when tests and measurements are repeated, the test signal generating equipment and its layout shall be to the same specification as that used during each appropriate calibration phase.

2.6. If the ESA under test consists of more than one unit, the interconnecting cables should ideally be the wiring harnesses as intended for use in the vehicle. If these are not available, the length between the electronic control unit and the AN shall be as defined in the standard. All cables in the wiring harness should be terminated as realistically as possible and preferably with real loads and actuators.

3. General test requirements

3.1. Frequency range, dwell times

Measurements shall be made in the 20 to 6,000 MHz frequency range with frequency steps according to ISO 11452-1.

The test signal modulation shall be:

(a) AM (amplitude modulation), with 1 kHz modulation and 80 per cent modulation depth in the 20 to 400 MHz frequency range;

(b) PM2 (pulse modulation type 2), T_{on} 3 µs, period 3,333 µs in the 2,700 to 3,100 MHz frequency range; and

(c) PM3 (pulse modulation type 3), T_{on} 500 µs, period 1,000 µs in the 380 to 2,700 MHz and the 3,100 to 6,000 MHz frequency ranges.

If not otherwise agreed between Technical Service and ESA manufacturer.

Frequency step size and dwell time shall be chosen according to ISO 11452-1.

3.2. The Technical Service shall perform the test at the intervals specified in ISO 11452-1, throughout the frequency range 20 to 6,000 MHz.

Alternatively, if the manufacturer provides measurement to data for the whole frequency band from a test laboratory accredited to the applicable parts of ISO 17025, and recognized by the Type Approval Authority, the Technical Service may choose a reduced number of spot frequencies in the range (e.g. 27, 45, 65, 90, 120, 150, 190, 230, 280, 380, 450, 600, 750, 900, 1,300, 1,800, 2,360, 2,600, 3,000, 3,600, 5,200 and 5,900 MHz) to confirm that the ESA meets the requirements of this Annex.

3.3. If an ESA fails the tests defined in this Annex, it shall be verified as having failed under the relevant test conditions and not as a result of the generation of uncontrolled fields.

4. Specific test requirements

4.1. Absorber chamber test

4.1.1. Test method

This test method allows the testing of vehicle electrical/electronic systems by exposing an ESA to electromagnetic radiation generated by an antenna.

4.1.2. Test methodology

The "substitution method" shall be used to establish the test field conditions according to ISO 11452-2.

The test shall be performed with vertical polarization.

4.1.2.1. For ESAs in configuration "REESS charging mode coupled to the power grid" the test arrangement shall be according to Appendix 3 to this Annex.

4.1.2.1.1. The shielding configuration shall be according to the vehicle series configuration. Generally all shielded HV parts shall be properly connected with low impedance to ground (e. g. AN, cables, connectors etc.). ESAs and loads shall be connected to ground. The external HV power supply shall be connected via feed-through-filtering.

4.1.2.1.2. Unless otherwise specified the length of the LV harness and the HV harness parallel to the front edge of the ground plane shall be 1,500 mm (±75 mm). The total length of the test harness including the connector shall be 1,700 mm (+300/-0 mm). The distance between the LV harness and the HV harness shall be 100 mm (+100/-0 mm).

4.1.2.1.3. All of the harnesses shall be placed on a non-conductive, low relative permittivity material ($\varepsilon_r \leq 1{,}4$), at 50 mm (±5 mm) above the ground plane.

4.1.2.1.4. Shielded supply lines for HV+ and HV- line and three phase lines may be coaxial cables or in a common shield depending on the used plug system. The original HV-harness from the vehicle may be used optionally.

4.1.2.1.5. Unless otherwise specified, the ESA case shall be connected to the ground plane either directly or via defined impedance.

4.1.2.1.6. For onboard chargers, the AC/DC power lines shall be placed the furthest from the antenna (behind LV and HV harness). The distance between the AC/DC power lines and the closest harness (LV or HV) shall be 100 mm (+100/-0 mm).

4.1.2.1.7. Unless otherwise specified, the configuration with the LV harness closer to the antenna shall be tested.

4.2. TEM cell testing (see Appendix 1 to this Annex)

4.2.1. Test method

The TEM (transverse electromagnetic mode) cell generates homogeneous fields between the internal conductor (septum) and housing (ground plane).

4.2.2. Test methodology

The test shall be performed according to ISO 11452-3.

Depending on the ESA to be tested the Technical Service shall chose the method of maximum field coupling to the ESA or to the wiring harness inside the TEM-cell.

4.3. Bulk current injection testing

4.3.1. Test method

This is a method of carrying out immunity tests by inducing currents directly into a wiring harness using a current injection probe.

4.3.2. Test methodology

The test shall be performed according to ISO 11452-4 on a test bench with the following characteristics:

BCI test method with substitution method and injection probe positioned at 150 mm distance to the ESA;Or BCI test method with closed loop method and injection probe positioned at 900 mm distance to the ESA.
As an alternative the ESA may be tested while installed in the vehicle according to ISO 11451-4 with the following characteristics:

BCI test method with substitution method and injection probe positioned at 150 mm distance to the ESA.

4.3.2.1. For ESAs in configuration "REESS charging mode coupled to the power grid", an example of test arrangement (for substitution method) is given in Appendix 3 to this Annex (Figure 1 for substitution method and Figure 2 for closed loop method).

4.3.2.1.1. The shielding configuration shall be according to the vehicle series configuration. Generally all shielded HV parts shall be properly connected with low impedance to ground (e. g. AN, cables, connectors, etc.). ESAs and loads shall be connected to ground. The external HV power supply shall be connected via feed-through-filtering.

4.3.2.1.2. When using substitution method, unless otherwise specified the length of the LV harness and the HV harness shall be 1,700 mm (+300/-0 mm). The distance between the LV harness and the HV harness shall be 100 mm (+100/-0 mm). The HV/LV wiring harness shall be straight over at least 1,400 mm starting at the ESA for all test methods defined in part 4 of ISO 11452 except for the BCI test method using the closed-loop method with power limitation.

When using closed loop method, unless otherwise specified the length of the LV harness and the HV harness shall be 1,000 mm (+200/-0 mm). The distance between the LV harness and the HV harness shall be 100 mm (+100/-0 mm). The HV/LV wiring harness shall be straight over its entire length for the BCI test method using the closed-loop method with power limitation.

4.3.2.1.3. All of the harnesses shall be placed on a non-conductive, low relative permittivity material ($\varepsilon_r \leq 1.4$), at (50 ± 5) mm above the ground plane.

4.3.2.1.4. Shielded supply lines for HV+ and HV- line and three phase lines may be coaxial cables or in a common shield depending on the used plug system. The original HV-harness from the vehicle may be used optionally.

4.3.2.1.5. Unless otherwise specified, the ESA case shall be connected to the ground plane either directly or via defined impedance.

4.3.2.1.6. Unless otherwise specified the test shall be performed with the injection probe placed around each of the following harnesses:

(a) Low voltage harness;

(b) High voltage harness;

(c) AC power lines if applicable;

(d) DC power lines if applicable.

4.4. Stripline testing

4.4.1. Test method

This test method consists of subjecting the wiring harness connecting the components in an ESA to specified field strengths.

4.4.2. Test methodology

The test shall be performed according to ISO 11452-5.

4.5. Reverberation chamber test

4.5.1. Test method

This test method allows the testing of vehicle electrical/electronic systems by exposing an ESA to statistically homogeneous and isotropic electromagnetic fields created by injected and stirred mechanically.

4.5.2. Test methodology

The test shall be performed according to ISO 11452-11.

Unless otherwise specified, the reverberation chamber testing method shall be carried out using a test setup with ground plane.

Annex 9 - Appendix 1

Typical TEM cell dimensions

The following table shows the dimensions for constructing a cell with specified upper frequency limits:

Upper frequency (MHz)	*Cell form factor W: b*	*Cell form factor L/W*	*Plate separation b (cm)*	*Septum S (cm)*
200	1.69	0.66	56	70
200	1.00	1	60	50


Annex 9 - Appendix 2

Absorber chamber test

Test configuration for ESA's involved in "REESS charging mode coupled to the power grid". The test shall be performed according to ISO 11452-2.

Figure 1 **Example of test set-up for log-periodic antenna**

Top view ***Dimensions in millimetres***





Key			
1	ESA (grounded locally if required in test plan)	16	power line filter
2	ground plane	17	fibre optic feed through
3	low relative permittivity support ($\varepsilon_r \leq 1.4$); thickness 50 mm	18	bulk head connector
4	ground straps	19	stimulating and monitoring system
5	LV harness	20	RF signal generator and amplifier
6	HV lines (HV+, HV-)	21	high quality coaxial cable e.g. double shielded (50 Ω)
7	LV load simulator	22	optical fibre
8	impedance matching network (optional)	23	log-periodic antenna

9	LV AN	24	RF absorber material
10	HV AN	25	AC power mains
11	LV supply lines	26	AMN for AC power mains
12	HV supply lines	27	AC charging load simulator
13	LV power supply 12 V / 24 V / 48 V (placed on the bench)	28	50 Ω load
14	additional shielded box (optional)	29	AC lines
15	HV power supply (should be shielded if placed inside ALSE)		

Figure 2 **Example of test set-up for horn antenna**

Top view ***Dimensions in millimetres***






Key			
1	ESA (grounded locally if required in test plan)	16	power line filter
2	ground plane	17	fibre optic feed through
3	low relative permittivity support ($\varepsilon_r \leq 1.4$); thickness 50 mm	18	bulk head connector
4	ground straps	19	stimulating and monitoring system
5	LV harness	20	RF signal generator and amplifier

6	HV lines (HV+, HV-)	21	high quality coaxial cable e.g. double shielded (50 Ω)
7	LV load simulator	22	optical fibre
8	impedance matching network (optional)	23	horn antenna
9	LV AN	24	RF absorber material
10	HV AN	25	AC power mains
11	LV supply lines	26	AMN for AC power mains
12	HV supply lines	27	AC charging load simulator
13	LV power supply 12 V / 24 V / 48 V (placed on the bench)	28	50 Ω load
14	additional shielded box (optional)	29	AC lines
15	HV power supply (should be shielded if placed inside ALSE)		

Annex 9 - Appendix 3 BCI test

Test configuration for ESAs involved in "REESS charging mode coupled to the power grid". The test shall be performed according to ISO 11452-4.


Figure 1 **Example of test set-up for substitution method - Injection on LV (or HV or AC) lines for ESAs with shielded power supply systems and inverter/charger device (dimensions in millimetres)**



	Key		
1	ESA	14	additional shielded box
2	ground plane	15	HV power supply (should be shielded if placed inside ALSE)
3	low relative permittivity support ($\varepsilon_r \leq 1,4$); thickness 50 mm	16	power line filter
4	ground straps	17	fibre optic feed through
5	LV harness	18	bulk head connector
6	HV lines (HV+, HV-)	19	stimulating and monitoring system
7	LV load simulator	20	injection probe
8	impedance matching network (optional) (see ISO 11452-1)	21	high frequency equipment (generator and amplifier)
9	LV AN	22	optical fibre

10	HV AN	23	50 Ω load
11	LV supply lines	24	AC lines
12	HV supply lines	25	AMN for AC power mains
13	LV power supply 12 V / 24 V / 48 V (should be placed on the bench)	26	AC charging load simulator
		27	AC power mains

Figure 2 **Example of test set-up for closed loop method - Injection on LV (or HV or AC) lines for ESAs with shielded power supply systems and inverter/charger device (dimensions in millimetres)**



	Key		
1	ESA	15	HV power supply (should be shielded if placed inside ALSE)

2	ground plane	16	power line filter
3	low relative permittivity support ($\varepsilon_r \leq 1,4$); thickness 50 mm	17	fibre optic feed through
4	ground straps	18	bulk head connector
5	LV harness	19	stimulating and monitoring system
6	HV lines (HV+, HV-)	20	measuring probe
7	LV load simulator	21	high frequency equipment (generator, amplifier and spectrum analyser)
8	impedance matching network (optional) (see ISO 11452-1)	22	optical fibre
9	LV AN	23	50 Ω load
10	HV AN	24	AC lines
11	LV supply lines	25	AMN for AC power mains
12	HV supply lines	26	AC charging load simulator
13	LV power supply 12 V / 24 V / 48 V (should be placed on the bench)	27	AC power mains
14	additional shielded box	28	injection probe

Annex 10 Method(s) of testing for immunity to and emission of transients of electrical/electronic sub-assemblies (ESAs)

1. General

This test method shall ensure the immunity of ESAs to conducted transients on the vehicle power supply and limit conducted transients from ESAs to the vehicle power supply.

2. Immunity against transient disturbances conducted along 12/24 V supply lines.

Apply the test pulses 1, 2a, 2b, 3a and 3b according to the International Standard ISO 7637-2 to the supply lines as well as to other connections of ESAs which may be operationally connected to supply lines.

Apply the starting profile according to the International Standard ISO 16750-2 to the supply lines as well as to other connections of ESAs which may be operationally connected to supply lines.

ESAs that are exclusively reserved for mounting on electric vehicles (vehicles without 12V/24V starter motor) are not subject to starting profile.

3. Emission of transient conducted disturbances generated by ESAs on 12/24 V supply lines.

Measurement according to the International Standard ISO 7637-2 on supply lines as well as to other connections of ESAs which may be operationally connected to supply lines.

Annex 11 Method(s) of testing for emission of harmonics generated on AC power lines from vehicles

1. General

1.1. The test method described in this Annex shall be applied to vehicles in configuration "REESS charging mode coupled to the power grid"

1.2. Test method

This test is intended to measure the level of harmonics generated by vehicle in configuration "REESS charging mode coupled to the power grid" through its AC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to:

(a) IEC 61000-3-2 for input current in charging mode ≤ 16 A per phase for class A equipment;

(b) IEC 61000-3-12 for input current in charging mode > 16 A and ≤ 75 A per phase.


2. Vehicle state during tests

2.1. The vehicle shall be in configuration "REESS charging mode coupled to the power grid".

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20mm shall be used between stand and ground plane.

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 1**.**

Figure 1 **Charging mode configuration for Annex 11**



The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being splitting into different time slots with the need to discharge the vehicle's traction battery before starting the next

time slot). If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

In case of multiple batteries the average state of charge shall be considered.

The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

All other equipment which can be switched ON by the driver or passengers shall be OFF.

3. Test arrangements

3.1. The observation time to be used for the measurements shall be as for
quasi-stationary equipment as defined in IEC 61000-3-2, Table 4.

3.2. The test set-up for single phase / three-phase vehicle in configuration "REESS charging mode coupled to the power grid" is shown in Figure 1a to 1d of Appendix 1 to this Annex.

4. Test requirements

4.1. The measurements of even and odd current harmonics shall be performed up to the 40th harmonic.

4.2. The limits for single phase or three-phase "REESS charging mode coupled to the power grid" with input current ≤ 16 A per phase are given in Table 4 of paragraph 7.3.2.1. of this Regulation.

4.3. The limits for single phase or other than balanced three-phase "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase are given in Table 5 of paragraph 7.3.2.2. of this Regulation.

4.4. The limits for balanced three-phase "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase are given in Table 6 of paragraph 7.3.2.2. of this Regulation.

4.5. For three-phase "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase, when at least one of the three conditions a), b) or c) described in Clause 5.2 of IEC 61000-3-12 is fulfilled, then the limits given in Table 7 of paragraph 7.3.2.2. of this Regulation can be applied.

Annex 11 - Appendix 1

Figure 1 **Vehicle in configuration "REESS charging mode coupled to the power grid"**

Example of test setup for vehicle with plug located on vehicle side

Figure 1a





Figure 1b



Key

1 vehicle under test

2 insulating support

3 charging harness

4 harmonic analyzer

5 power supply

Example of test setup for vehicle with plug located front/rear of vehicle

Figure 1c





Figure 1d



Key

1 vehicle under test

2 insulating support

3 charging harness

4 harmonic analyzer

5 power supply

Annex 12 Method(s) of testing for emission of voltage changes, voltage fluctuations and flicker on AC power lines from vehicles

1. General

1.1. The test method described in this Annex shall be applied to vehicles in configuration "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the level of voltage changes, voltage fluctuations and flicker generated by vehicle in configuration "REESS charging mode coupled to the power grid" through its AC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to:

(a) IEC 61000-3-3 for rated current in "REESS charging mode" ≤ 16 A per phase and not subjected to conditional connection;

(b) IEC 61000-3-11 for rated current in "REESS charging mode" > 16 A and ≤ 75 A per phase and subjected to conditional connection.


2. Vehicle state during tests

2.1. The vehicle shall be in configuration "REESS charging mode coupled to the power grid".

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 1**.**

Figure 1 **Charging mode configuration for Annex 12**



The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being splitting into different time slots with the need to discharge the vehicle's traction battery before starting the next time slot). If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

In case of multiple batteries the average state of charge shall be considered.

The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

All other equipment which can be switched ON by the driver or passengers shall be OFF.

3. Test arrangements

3.1. The tests for vehicle in configuration "REESS charging mode coupled to the power grid" with rated current ≤ 16 A per phase and not subjected to conditional connection shall be performed according to Clause 6 of IEC 61000-3-3.

3.2. The tests for vehicle in configuration "REESS charging mode coupled to the power grid" with rated current > 16 A and ≤ 75 A per phase and subjected to conditional connection shall be performed according to Clause 6 of IEC 61000-3-11.

3.3. The test set-up for vehicle in configuration "REESS charging mode coupled to the power grid" is shown in Figures 1a to 1d of Appendix 1 to this Annex.

4. Test requirements

4.1. The parameters to be determined in the time-domain are "short duration flicker value", "long duration flicker value" and "voltage relative variation".

4.2. The limits for vehicle in configuration "REESS charging mode coupled to the power grid" with input current ≤ 16 A per phase and not subjected to conditional connection are given in paragraph 7.4.2.1. of this Regulation.

4.3. The limits for vehicle in configuration "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase and subjected to conditional connection are given in paragraph 7.4.2.2. of this Regulation.

Annex 12 - Appendix 1

Figure 1 **Vehicle in configuration "REESS charging mode coupled to the power grid"**

Example of test setup for vehicle with plug located on vehicle side

Figure 1a





Figure 1b



Key

1 vehicle under test

2 insulating support

3 charging harness

4 flicker analyzer

5 impedance simulator

6 power supply

Example of test setup for vehicle with plug located front/rear of vehicle

Figure 1c





Figure 1d



Key

1 vehicle under test

2 insulating support

3 charging harness

4 flicker analyzer

5 impedance simulator

6 power supply

Annex 13 Method(s) of testing for emission of radiofrequency conducted disturbances on AC or DC power lines from vehicles

1. General

1.1. The test method described in this Annex shall be applied to vehicles in configuration "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the level of radio frequency conducted disturbances generated by vehicle in configuration "REESS charging mode coupled to the power grid" through its AC or DC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to CISPR 16-2-1.


2. Vehicle state during tests

2.1. The vehicle shall be in configuration "REESS charging mode coupled to the power grid".

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 1**.**

Figure 1 **Charging mode configuration for Annex 13**


Annex 13: test modes to be selected for REESS coupled to the power grid.
Key
Y yes
N no
Mode 1 available?
Y
Mode 2 or 3 available?
N
Mode 1 test with cable provided by the vehicle manufacturer.
N
Y
Mode 2 available?
Y
Cables delivered with the vehicle?
Y
ICCPD compliant with IEC 61851-21-2[1]?
N
N
N
Y
Mode 2 test with one representative cable provided by the vehicle manufacturer.
Mode 2 test with one representative cable delivered with the vehicle to the customer
Mode 2 test with all ICCPD variants delivered with the vehicle to the customer which do not comply with IEC 61851-21-2
Mode 3 available?
Y
Mode 3 test in both configurations (single and 3-phase), if available
N
Mode 4 available?
Y
Mode 4 test with cable from the test facility
N
End of test REESS coupled to the power grid
[1] IEC 61851-21-2 tests shall be performed by an ISO/IEC 17025 accredited laboratory. The test report shall be provided by the vehicle manufacturer as evidence for the vehicle type approval and accepted by the Type Approval Authority.

The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole frequency range measurement (this may lead to splitting the measurement in different sub-bands with the need to discharge the vehicle's traction battery before starting the next sub-bands).

If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type-Approval Authorities.

In case of multiple batteries the average state of charge shall be considered.

The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

All other equipment which can be switched ON by the driver or passengers shall be OFF.

3. Test arrangements

3.1. The test shall be performed according to Clause 7.4.1 of CISPR 16-2-1 as floor-standing equipment.

3.2. Measuring location

A shielded enclosure or an absorber lined shielded enclosure (ALSE) or an open area test site (OATS) which complies with the requirements of CISPR 16-1-4 may be used.

3.3. The artificial network(s) to be used for the measurement on vehicle are

(a) The AMN(s) defined in Appendix 8, paragraph 4. for AC power lines;

(b) The DC-charging-AN(s) defined in Appendix 8, paragraph 3. for DC power lines.

Artificial networks

The AMN(s)/DC-charging-AN(s) shall be mounted directly on the ground plane. The cases of the AMN(s)/DC-charging-AN(s) shall be bonded to the ground plane.

The conducted emissions on AC and DC power lines are measured successively on each power line by connecting the measuring receiver on the measuring port of the related AMN/DC-charging-AN. The measuring port of the AMN/DC-charging-AN inserted in the other power line shall be terminated with a 50 Ω load.

The AMN(s)/DC-charging-AN(s) shall be placed as defined in Figures 1a to 1d. of Appendix 1 to this Annex.

3.4. The test set-up for the connection of the vehicle in configuration "REESS charging mode coupled to the power grid" is shown in Figure 1a to 1d of Appendix 1 to this Annex.

3.5. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Table 1 and Table 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Peak detector*		*Quasi-peak detector*		*Average detector*	
	RBW at -3 dB	*Minimum scan time*	*RBW at -6 dB*	*Minimum scan time*	*RBW at -3 dB*	*Minimum scan time*
0.15 to 30	9/10 kHz	10 s/MHz	9 kHz	200 s/MHz	9/10 kHz	10 s/MHz

Note: If a spectrum analyser is used for peak measurements, the video bandwidth shall be at least three times the resolution bandwidth (RBW)

Table 2 **Scanning receiver parameters**

Frequency range MHz	*Peak detector*			*Quasi-peak detector*			*Average detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*
0.15 to 30	9 kHz	5 kHz	50 ms	9 kHz	5 kHz	1 s	9 kHz	5 kHz	50 ms

4. Test requirements

4.1. The limits apply throughout the frequency range 0.15 to 30 MHz for measurements performed in a shielded enclosure or an absorber lined shielded enclosure (ALSE) or an open area test site (OATS).

4.2. Measurements shall be performed with average and either quasi-peak or peak detectors. The limits are given in paragraph 7.5. of this Regulation.

Table 8 for AC lines and Table 9 for DC lines. If peak detectors are used a correction factor of 20 dB as defined in CISPR 12 shall be applied.

4.3. If the manufacturer provides measurement data for the whole frequency band for all applicable charging mode configurations from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type-Approval Authority for all the available charging modes configurations defined in paragraph 2.1, the Technical Service may perform tests only for one of the available charging mode configuration defined in paragraph 2.1 to confirm that the vehicle meets the requirements of this Annex.

Annex 13 - Appendix 1

Figure 1 **Vehicle in configuration "REESS charging mode coupled to the power grid"**

Example of test setup for vehicle with plug located on vehicle side (AC powered without communication)

Figure 1a





Figure1b



Key

1 vehicle under test

2 insulating support

3 charging harness

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

6 measuring receiver

Vehicle in configuration "REESS charging mode coupled to the power grid"

Example of test setup for vehicle with plug located front / rear of vehicle (AC powered without communication)

Figure 1c





Figure 1d



Key

1 vehicle under test

2 insulating support

3 charging harness

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

6 measuring receiver

Annex 14 (RESERVED)

Annex 15 Method of testing for immunity of vehicles to electrical fast transient/burst disturbances conducted along AC and DC power lines

1. General

1.1. The test method described in this Annex shall only be applied to vehicles. This method concerns only the configuration of the vehicle with "REESS charging mode coupled to the power grid".

1.2. Test method


This test is intended to demonstrate the immunity of the vehicle electronic systems. The vehicle shall be subject to electrical fast transient/burst disturbances conducted along AC and DC power lines of the vehicle as described in this Annex. The vehicle shall be monitored during the tests.

If not otherwise stated in this Annex the test shall be performed according to IEC 61000-4-4.

2. Vehicle state during tests in configuration "REESS in charging mode coupled to the power grid

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 1.

Figure 1 **Charging mode configuration for Annex 15**


Annex 15: test modes to be selected for REESS coupled to the power grid.
Key
Y yes
N no
Mode 1 available?
Y
Mode 2 or 3 available?
N
Mode 1 test with cable provided by the vehicle manufacturer.
N
Y
Mode 2 available?
Y
Cables delivered with the vehicle?
Y
ICCPD compliant with IEC 61851-21-2[1]?
N
N
N
Y
Mode 2 test with one representative cable provided by the vehicle manufacturer.
Mode 2 test with one representative cable delivered with the vehicle to the customer[1]
Mode 2 test with all ICCPD variants delivered with the vehicle to the customer which do not comply with IEC 61851-21-2[1]
Mode 3 available?
Y
Mode 3 test in only one configuration, 3-phase if available.
N
Mode 4 available?
Y
Mode 4 test with cable from the test facility.
N
End of test REESS coupled to the power grid.
[1] IEC 61851-21-2 tests shall be performed by an ISO/IEC 17025 accredited laboratory. The test report shall be provided by the vehicle manufacturer as evidence for the vehicle type approval and accepted by the Type Approval Authority.

2.1. The vehicle shall be in an unladen condition except for necessary test equipment.

2.1.1. The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

2.1.2. Basic vehicle conditions

The paragraph defines minimum test conditions (as far as applicable) and failures criteria for vehicle immunity tests. Other vehicle systems, which can affect immunity related functions, shall be tested in a way to be agreed between manufacturer and Technical Service.

"REESS charging mode" vehicle test conditions	*Failure criteria*
The REESS shall be in charging mode. The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle's traction battery before starting the next time slot). If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type Approval Authorities. In case of multiple batteries the average state of charge shall be considered.	Vehicle sets in motion. Unexpected release of the parking brake. Loss of Parking position for automatic transmission**.**

2.1.3. All other equipment which can be switched ON by the driver or passengers shall be OFF.

2.2. Only non-perturbing equipment shall be used while monitoring the vehicle. The vehicle exterior and the passenger compartment shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).

3. Test equipment

3.1. The test equipment is composed of a reference ground plane (a shielded room is not required), a transient/burst generator, Coupling/Decoupling Network (CDN) and capacitive coupling clamp.

3.2. The transient/burst generator shall meet the condition defined in Clause 6.1 of IEC 61000-4-4.

3.3. The Coupling/Decoupling Network shall meet the condition defined in Clause 6.2 of IEC 61000-4-4. When the Coupling/Decoupling Network cannot be used on AC or DC power lines, the capacitive coupling clamp defined in Clause 6.3 of IEC 61000-4-4 can be used.

4. Test setup

4.1. The vehicle test setup is based on the laboratory type setup as described in Clause 7.2 of IEC 61000-4-4.

4.2. The vehicle shall be placed directly on the ground plane.

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

4.3. The Technical Service shall perform the test as specified in paragraph 7.8.2.1. of this Regulation.

Alternatively, if the manufacturer provides measurement from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may choose not to perform the test to confirm that the vehicle meets the requirements of this Annex.

5. Generation of required test level

5.1. Test methodology

5.1.1. Test shall be conducted in accordance with IEC 61000-4-4. Test shall be performed only at the severity levels given in paragraph 7.8.2.1.

5.1.2. Test phase

The vehicle shall be positioned on the ground plane. The electrical fast transient/burst (EFT/B) shall be applied on the vehicle on the AC/DC power lines in common modes by using CDN as described in Figure 1a to 1d of Appendix 1 to this Annex.

The test set-up shall be noted in the test report.

6. If the manufacturer provides measurement data for all applicable charging mode configurations from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority for all the available charging modes configurations defined in paragraph 2.1, the Technical Service may perform tests only for one of the available charging mode configuration defined in paragraph 2.1 to confirm that the vehicle meets the requirements of this Annex.

Annex 15 - Appendix 1

Figure 1 **Vehicle in configuration "REESS charging mode coupled to the power grid"**

Example of test setup for vehicle with plug located on vehicle side

Figure 1a





Figure 1b



Key

1 vehicle under test

2 insulating support

3 charging harness

4 CDN

5 fast Transients / burst generator

6 power supply

Example of test setup for vehicle with plug located front/rear of vehicle

Figure 1c





Figure 1d



Key

1 vehicle under test

2 insulating support

3 charging harness

4 CDN

5 fast Transients / burst generator

6 power supply

Annex 16 Method of testing for immunity of vehicles to surges conducted along AC and DC power lines

1. General

1.1. The test method described in this Annex shall only be applied to vehicles. This method concerns only the configuration of the vehicle with "REESS charging mode coupled to the power grid".

1.2. Test method


This test is intended to demonstrate the immunity of the vehicle electronic systems. The vehicle shall be subject to surges conducted along AC and DC power lines of the vehicle as described in this Annex. The vehicle shall be monitored during the tests.

If not otherwise stated in this Annex, the test shall be performed according to IEC 61000-4-5, Clause 4.2 for lightning transients**.**

2. Vehicle state during tests in configuration "REESS in charging mode coupled to the power grid

The vehicle shall be tested in the charging mode configuration (if available on vehicle) as defined in flowchart of Figure 1.

Figure 1 **Charging mode configuration for Annex 16**


Annex 16: test modes to be selected for REESS coupled to the power grid.
Key
Y yes
N no
Mode 1 available?
Y
Mode 2 or 3 available?
N
Mode 1 test with cable provided by the vehicle manufacturer
N
Y
Mode 2 available?
Y
Cables delivered with the vehicle?
Y
ICCPD compliant with IEC 61851-21-2[1]?
N
N
N
Y
Mode 2 test with one representative cable provided by the vehicle manufacturer
Mode 2 test with one representative cable delivered with the vehicle to the customer‡
Mode 2 test with all ICCPD variants delivered with the vehicle to the customer which do not comply with IEC 61851-21-2‡
Mode 3 available?
Y
Mode 3 test in only one configuration, 3-phase if available
N
Mode 4 available?
Y
Mode 4 test with cable from the test facility
N
End of test REESS coupled to the power grid
[1] IEC 61851-21-2 tests shall be performed by an ISO/IEC 17025 accredited laboratory. The test report shall be provided by the vehicle manufacturer as evidence for the vehicle type approval and accepted by the Type Approval Authority.

2.1. The vehicle shall be in an unladen condition except for necessary test equipment.

2.1.1. The vehicle shall be immobilized, the engine(s) (ICE and / or electrical engine) shall be OFF and in charging mode.

2.1.2. Basic vehicle conditions

The paragraph defines minimum test conditions (as far as applicable) and failures criteria for vehicle immunity tests. Other vehicle systems, which can affect immunity related functions, shall be tested in a way to be agreed between manufacturer and Technical Service.

" REESS charging mode" vehicle test conditions	*Failure criteria*
The REESS shall be in charging mode. The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle's traction battery before starting the next time slot).. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type Approval Authorities. In case of multiple batteries the average state of charge shall be considered.	Vehicle sets in motion Unexpected release of the parking brake. Loss of Parking position for automatic transmission**.**

2.1.3. All other equipment which can be switched ON by the driver or passengers shall be OFF.

2.2. Only non-perturbing equipment shall be used while monitoring the vehicle. The vehicle exterior and the passenger compartment shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).

3. Test equipment

3.1. The test equipment is composed of a reference ground plane (a shielded room is not required), a surge generator and a Coupling/Decoupling Network (CDN).

3.2. The surge generator shall meet the condition defined in Clause 6.1 of IEC 61000-4-5.

3.3. The Coupling/Decoupling Network shall meet the condition defined in Clause 6.3 of IEC 61000-4-5.

4. Test setup

4.1. The vehicle test setup is based on the setup described in Clause 7.2 of IEC 61000-4-5.

4.2. The vehicle shall be placed directly on the ground plane.

For two-wheeled vehicles, a non-conductive insulating support with a thickness of 5 – 20 mm shall be used between stand and ground plane.

4.3. The Technical Service shall perform the test as specified in paragraph 7.9.2.1. of this Regulation.

Alternatively, if the manufacturer provides measurement from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may choose not to perform the test to confirm that the vehicle meets the requirements of this Annex.

5. Generation of required test level

5.1. Test methodology

5.1.1. Test shall be performed in accordance with method according to IEC 61000-4-5 only at the severity levels specified in paragraph 7.9.2.1.

5.1.2. Test phase

The vehicle shall be positioned on the ground plane. The electrical surge shall be applied on the vehicle on the AC/DC power lines between each line and earth and between lines by using CDN as described in Figures 1a to 1d of Appendix 1 to this Annex,

The test setup shall be noted in the test report.

6. If the manufacturer provides measurement data for all applicable charging mode configurations from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type-Approval Authority for all the available charging modes configurations defined in paragraph 2.1., the Technical Service may perform tests only for one of the available charging mode configuration defined in paragraph 2.1. to confirm that the vehicle meets the requirements of this Annex.

Annex 16 - Appendix 1 Vehicle in configuration "REESS charging mode coupled to the power grid "

Figure 1 **Vehicle in configuration "REESS charging mode coupled to the power grid"**

Example of test setup for vehicle with plug located on vehicle side

Figure 1a





Figure 1b



Key

1 vehicle under test

2 insulating support

3 charging harness

4 CDN

5 surge generator

6 power supply

Example of test setup for vehicle with plug located front/rear of vehicle

Figure 1c





Figure 1d



Key

1 vehicle under test

2 insulating support

3 charging harness

4 CDN

5 surge generator

6 power supply

Annex 17 Method(s) of testing for emission of harmonics generated on AC power lines from electrical/electronic sub - assemblies (ESAs)

1. General

1.1. The test method described in this Annex shall be applied to ESAs in configuration "REESS charging mode coupled to the power grid"

1.2. Test method

This test is intended to measure the level of harmonics generated by an ESA in configuration "REESS charging mode coupled to the power grid" through its AC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to:

(a) IEC 61000-3-2 for input current in charging mode ≤ 16 A per phase for class A equipment;

(b) IEC 61000-3-12 for input current in charging mode > 16 A and ≤ 75 A per phase.

2. ESA state during tests

2.1. The ESA shall be in configuration "REESS charging mode coupled to the power grid".

The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle’s traction battery before starting the next time slot).

If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

3. Test arrangements

3.1. The observation time to be used for the measurements shall be as for quasi-stationary equipment as defined in Table 4 of IEC 61000-3-2.

3.2. The test set-up for single phase ESA in configuration "REESS charging mode coupled to the power grid" is shown in Figure 1 of Appendix 1 to this Annex.

3.3. The test set-up for three-phase ESA in configuration "REESS charging mode coupled to the power grid" is shown in Figure 2 of Appendix 1 to this Annex.

4. Test requirements

4.1. The measurements of even and odd current harmonics shall be performed up to the 40th harmonic.

4.2. The limits for single phase or three-phase ESAs in configuration "REESS charging mode coupled to the power grid" with input current ≤ 16 A per phase are given in Table 12 of paragraph 7.11.2.1. of this Regulation.

4.3. The limits for single phase or other than balanced three-phase ESAs in configuration "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase are given in Table 13 of paragraph 7.11.2.2. of this Regulation.

4.4. The limits for balanced three-phase ESAs in configuration "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase are given in Table 14 of paragraph 7.11.2.2. of this Regulation.

4.5. For three-phase ESAs in configuration "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase, when at least one of the three conditions a), b) or c) described in Clause 5.2 of IEC 61000-3-12 is fulfilled, then the limits given in Table 15 of paragraph 7.11.2.2. of this Regulation can be applied.

Annex 17 - Appendix 1

Figure 1 **ESA in configuration "REESS charging mode coupled to the power grid" - Single phase test set-up**





Figure 2 **ESA in configuration "REESS charging mode coupled to the power grid" -Three-phase test set-up**



Annex 18 Method(s) of testing for emission of voltage changes, voltage fluctuations and flicker on AC power lines from electrical/electronic sub - assemblies (ESAs)

1. General

1.1. The test method described in this Annex shall be applied to ESAs in configuration "REESS charging mode coupled to the power grid"

1.2. Test method

This test is intended to measure the level of voltage changes, voltage fluctuations and flicker generated by ESA in configuration "REESS charging mode coupled to the power grid" through its AC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to:

(a) IEC 61000-3-3 for rated current in "REESS charging mode" ≤ 16 A per phase and not subjected to conditional connection;

(b) IEC 61000-3-11 for rated current in "REESS charging mode" > 16 A and ≤ 75 A per phase and subjected to conditional connection

2. ESA state during tests

2.1. The ESA shall be in configuration "REESS charging mode coupled to the power grid"

The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle’s traction battery before starting the next time slot).

If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

3. Test Arrangements

3.1. The tests for ESA in configuration "REESS charging mode coupled to the power grid" with rated current ≤ 16 A per phase and not subjected to conditional connection shall be performed according to Clause 4 of IEC 61000-3-3.

3.2. The tests for ESA in configuration "REESS charging mode coupled to the power grid" with rated current > 16 A and ≤ 75 A per phase and subjected to conditional connection shall be performed according to Clause 6 of IEC 61000-3-11.

3.3. The test set-up for ESA in configuration "REESS charging mode coupled to the power grid" is shown in Figures 1a and 1b of Appendix 1 to this Annex.

4. Test requirements

4.1. The parameters to be determined in the time-domain are "short duration flicker value", "long duration flicker value" and "voltage relative variation".

4.2. The limits for ESA in configuration "REESS charging mode coupled to the power grid" with input current ≤ 16 A per phase and not subjected to conditional connection are given in paragraph 7.12.2.1. of this Regulation.

4.3. The limits for ESA in configuration "REESS charging mode coupled to the power grid" with input current > 16 A and ≤ 75 A per phase and subjected to conditional connection are given in paragraph 7.12.2.2. of this Regulation.

Annex 18 - Appendix 1

Figure 1a **ESA in configuration "REESS charging mode coupled to the power grid"- Single phase test set-up**





Figure 1b **ESA in configuration "REESS charging mode coupled to the power grid" - Three-phase test set-up**



Annex 19 Method(s) of testing for emission of radiofrequency conducted disturbances on AC or DC power lines from electrical/electronic sub - assemblies (ESAs)

1. General

1.1. The test method described in this Annex shall be applied to ESAs in configuration "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to measure the level of radio frequency conducted disturbances generated by ESA in configuration "REESS charging mode coupled to the power grid" through its AC or DC power lines in order to ensure it is compatible with residential, commercial and light industrial environments.

If not otherwise stated in this Annex the test shall be performed according to CISPR 16-2-1.

2. ESA state during tests

2.1. The ESA shall be in configuration "REESS charging mode coupled to the power grid".

The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole frequency range measurement (this may lead to split the measurement in different sub-bands with the need to discharge the vehicle's traction battery before starting the next sub-bands).

If the test is not performed with a REESS the ESA should be tested at rated current.

If the current consumption can be adjusted, then the current shall be set to at least 80 per cent of its maximum rated charging/input current value for AC charging.

If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type Approval Authorities.

3. Test arrangements

3.1 The artificialnetwork(s) to be used for the measurement on vehicle are

(a) The AMN(s) defined in Appendix 8, paragraph 4. for AC power lines;

(b) The DC-charging-AN(s) defined in Appendix 8, paragraph 3. for DC power lines.

Artificial networks

The AMN(s)/DC-charging-AN(s) shall be mounted directly on the ground plane. The cases of the AMN(s)/DC-charging-AN(s) shall be bonded to the ground plane.

The conducted emissions on AC and DC power lines are measured successively on each power line by connecting the measuring receiver on the measuring port of the related AMN/DC-charging-AN. The measuring port of the AMN/DC-charging-AN inserted in the other power lines shall be terminated with a 50 Ω load.

The AMN(s)/DC-charging-AN(s) shall be placed in front, aligned and on the same side of the vehicle power charging plug.

CISPR 16-1-4 may be used.

3.2. Measuring location

A shielded enclosure or an absorber lined shielded enclosure (ALSE) or an open area test site (OATS) which complies with the requirements of CISPR 16-1-4 may be used.

3.3. The test set-up (floor-standing equipment) for the connection of the ESAs in configuration "REESS charging mode coupled to the power grid" is shown in Figure 1 of Appendix 1 to this Annex.

3.4. The measurements shall be performed with a spectrum analyser or a scanning receiver. The parameters to be used are defined in Table 1 and Table 2.

Spectrum analysers and FFT-based instruments, that meet the requirements of CISPR 16-1-1, may be used for conformity measurements. FFT-based measuring instruments shall continuously record and evaluate the signal during the measurement time. If using FFT-based instruments, the minimum measurement time shall be 1 s per analysis frequency band (in real-time mode) of the FFT instrument.

Table 1 **Spectrum analyser parameters**

Frequency range MHz	*Peak detector*		*Quasi-peak detector*		*Average detector*	
	RBW at -3 dB	*Minimum scan time*	*RBW at -6 dB*	*Minimum scan time*	*RBW at -3 dB*	*Minimum scan time*
0.15 to 30	9/10 kHz	10 s/MHz	9 kHz	200 s/MHz	9/10 kHz	10 s/MHz

Note: If a spectrum analyser is used for peak measurements, the video bandwidth shall be at least three times the resolution bandwidth (RBW)

Table 2 **Scanning receiver parameters**

Frequency range *MHz*	*Peak detector*			*Quasi-peak detector*			*Average detector*		
	BW at -6 dB	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*	*BW at -6 dB*	*Maximum step size*	*Minimum dwell time*
0.15 to 30	9 kHz	5 kHz	50 ms	9 kHz	5 kHz	1 s	9 kHz	5 kHz	50 ms


4. Test Requirements

4.1. The limits apply throughout the frequency range 0.15 to 30 MHz for measurements performed in a shielded enclosure or an absorber lined shielded enclosure (ALSE) or an open area test site (OATS).

4.2. Measurements shall be performed with average and either quasi-peak or peak detectors. The limits are given in Table 16 of paragraph 7.13.2.1. of this Regulation for AC lines and in Table 17 of paragraph 7.13.2.2. of this Regulation for DC lines. If peak detectors are used a correction factor of 20 dB as defined in CISPR 12 shall be applied.

Annex 19 - Appendix 1

Figure 1 **ESA in configuration "REESS charging mode coupled to the power grid" (floor-standing equipment)**



Key

1 ESA under test

2 insulating support

3 charging harness

4 AMN(s) or DC-charging-AN(s) grounded

5 power mains socket

6 measuring receiver

7 ground plane

Annex 20 (RESERVED)

Annex 21 Method of testing for immunity of electrical/electronic sub - assemblies (ESAs) to electrical fast transient/burst disturbances conducted along AC and DC power lines

1. General

1.1. The test method described in this Annex shall only be applied to ESAs. This method applies only to ESA in configuration "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to demonstrate the immunity of the ESA. The ESA shall be subject to Electrical Fast Transient/Burst disturbances conducted along AC and DC power lines of the ESA as described in this Annex. The ESA shall be monitored during the tests.

If not otherwise stated in this annex the test shall be performed according to IEC 61000-4-4.

2. ESA state during tests in configuration "REESS in charging mode coupled to the power grid"

2.1. Basic ESA conditions

The paragraph defines minimum test conditions (as far as applicable) and failures criteria for ESA immunity tests.

"REESS charging mode" ESA test conditions	*Failure criteria*
ESA shall be in configuration "REESS charging mode coupled to the power grid". The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole time duration of the measurement (this may lead to the measurement being split into different time slots with the need to discharge the vehicle's traction battery before starting the next time slot). If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type Approval Authorities.	Temporary loss of charging function is allowed, provided that there is no incorrect charging condition (e.g. over-current, overvoltage) and the function can be restored by a simple intervention, without the use of tools, such as turning off/on the DUT, after the disturbance is removed.

2.2. Only non-perturbing equipment shall be used while monitoring the ESA. The ESA shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).

3. Test equipment

3.1. The test equipment is composed of a reference ground plane (a shielded room is not required), a transient / burst generator, Coupling/Decoupling Network (CDN) and capacitive coupling clamp.

3.2. The transient/burst generator shall meet the condition defined in Clause 6.1 of IEC 61000-4-4.

3.3. The Coupling/Decoupling Network shall meet the condition defined in Clause 6.2 of IEC 61000-4-4. When the Coupling/Decoupling Network cannot be used on AC or DC power lines, the capacitive coupling clamp defined in Clause 6.3 of IEC 61000-4-4 can be used.

4. Test set-up

4.1. The ESA test setup is based on the laboratory type set-up as described in Clause 7.2 of IEC 61000-4-4.

4.2. The ESA shall be placed directly on the ground plane.

4.3. The Technical Service shall perform the test as specified in paragraph 7.15.2.1. of this Regulation.

Alternatively, if the manufacturer provides measurement from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may choose not to perform

the test to confirm that the ESA meets the requirements of this Annex.

5. Generation of required test level

5.1. Test methodology

5.1.1. Test shall be conducted in accordance with IEC 61000-4-4. Test shall be performed only at the severity levels given in paragraph 7.15.2.1.


5.1.2. Test phase

The ESA shall be positioned on the ground plane. The Electrical Fast Transient/Burst (EFT/B) shall be applied on the ESA on the AC/DC power lines in common modes by using CDN as described in Figure 1 of Appendix 1 to this Annex.

The test setup shall be noted in the test report.

Annex 21 - Appendix 1

Figure 1 **ESA in configuration "REESS charging mode coupled to the power grid"**



Annex 22 Method of testing for immunity of electrical/electronic sub - assemblies (ESAs) to surges conducted along AC and DC power lines

1. General

1.1. The test method described in this Annex shall only be applied to ESAs. This method applies only to ESAs in configuration "REESS charging mode coupled to the power grid".

1.2. Test method

This test is intended to demonstrate the immunity of the ESA. The ESA shall be subject to surges conducted along AC and DC power lines of the ESA as described in this Annex. The ESA shall be monitored during the tests.

If not otherwise stated in this Annex the test shall be performed according to IEC 61000-4-5.

2. ESA state during tests in configuration "REESS in charging mode coupled to the power grid"

2.1. Basic ESA conditions

The paragraph defines minimum test conditions (as far as applicable) and failures criteria for ESA immunity tests.

"REESS charging mode" ESA test conditions	*Failure criteria*
ESA shall be in configuration "REESS charging mode coupled to the power grid". The state of charge (SOC) of the traction battery shall be kept between 20 per cent and 80 per cent of the maximum SOC during the whole frequency range measurement (this may lead to	Temporary loss of charging function is allowed, provided that there is no incorrect charging condition (e.g. over-current, overvoltage) and the function can be restored by a simple intervention, without the use of

"REESS charging mode" ESA test conditions	*Failure criteria*
split the measurement in different sub-bands with the need to discharge the vehicle's traction battery before starting the next sub-bands). If the test is not performed with a REESS the ESA should be tested at rated current. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its maximum rated charging/input current value for AC charging. If the current consumption can be adjusted, then the current shall be set to at least 20 per cent of its nominal value or to a minimum of 16 A (if the 20 per cent of its nominal value cannot be achieved in the test facility) for DC charging unless another value is agreed with the Type-Approval Authorities.	tools, such as turning off/on the DUT, after the disturbance is removed.

2.2. Only non-perturbing equipment shall be used while monitoring the ESA. The ESA shall be monitored to determine whether the requirements of this Annex are met (e.g. by using (a) video camera(s), a microphone, etc.).

3. Test equipment

3.1. The test equipment is composed of a reference ground plane (a shielded room is not required), a surge generator and a Coupling/Decoupling Network (CDN).

3.2. The surge generator shall meet the condition defined in Clause 6.1 of IEC 61000-4-5.

3.3. The Coupling/Decoupling Network shall meet the condition defined in Clause 6.3 of IEC 61000-4-5.

4. Test set-up

4.1. The ESA test set-up is based on the set-up described in Clause 7.2 of IEC 61000-4-5.

4.2. The ESA shall be placed directly on the ground plane.

4.3. The Technical Service shall perform the test as specified in paragraph 7.16.2.1. of this Regulation.

Alternatively, if the manufacturer provides measurement from a test laboratory accredited to the applicable parts of ISO 17025 and recognized by the Type Approval Authority, the Technical Service may choose not to perform the test to confirm that the ESA meets the requirements of this Annex.

5. Generation of required test level

5.1. Test methodology

5.1.1. Test shall be conducted in accordance with IEC 461000-4-5. Test shall be performed only at the severity levels given in 7.16.2.1.

5.1.2. Test phase

The ESA shall be positioned on the ground plane. The electrical surge shall be applied on the ESA on the AC/DC power lines between each line and earth and between lines by using CDN as described in Figures 1 to 4 of Appendix 1 to this Annex.

The test set-up shall be noted in the test report

Annex 22 – Appendix 1 ESAs in configuration "REESS charging mode coupled to the power grid"

Figure 1 **ESA in configuration "REESS charging mode coupled to the power grid" - Coupling between lines for DC or AC (single phase) power lines**




Figure 2 **ESA in configuration "REESS charging mode coupled to the power grid" - Coupling between each line and earth for DC or AC (single phase) power lines**




Figure 3 **ESA in configuration "REESS charging mode coupled to the power grid" - Coupling between lines for AC (three phases) power lines**





Figure 4 **ESA in configuration "REESS charging mode coupled to the power grid" - Coupling between each line and earth for AC (three phases) power lines**


Surge generator
R = 10 Ω
C = 9 µF
S2
1 2 3 4
CDN
L
AC mains
Reference earth
maximum length 2 m
Cable (shall be shortened to appropriate length) (100 ± 25) mm above ground and at least 10 cm from the ESA body
ESA