UN R53 (version 4.1.0)

Consolidated text of this version, rendered by Certivity for the hackathon. Cite pages of THIS file: the page number is printed at the bottom of every page.

Role in the hackathon: latest version.

1. Scope

This Regulation applies to vehicles of category L_3[1] with regard to the installation of lighting and light-signalling devices.

[1] As defined in the Consolidated Resolution on the Construction of Vehicles (R.E.3.), document ECE/TRANS/WP.29/78/Rev.6, para. 2. - www.unece.org/trans/main/wp29/wp29wgs/wp29gen/wp29resolutions.html

2. Definitions

For the purpose of this Regulation, the definitions given in the latest series of amendments to UN Regulation No. 48 in force at the time of application for type approval shall apply, unless otherwise specified in this Regulation.

2.1. "*Vehicle type*" means a category of vehicles which do not differ from each other in such essential respects as:

2.1.1. The dimensions and external shape of the vehicle;

2.1.2. The number and position of the devices;

2.1.3. The following shall likewise not be deemed to be "vehicles of a different type":

2.1.3.1. Vehicles which differ within the meaning of paragraphs 2.1.1. and 2.1.2. above but not in such a way as to entail a change in the kind, number, position and geometric visibility of the lamps prescribed for the vehicle type in question; and

2.1.3.2. Vehicles on which lamps approved under one of the Regulations annexed to the 1958 Agreement, or lamps allowed in the country in which the vehicles are registered, are fitted, or are absent where their fitting is optional;

2.2. "*Unladen vehicle*" means a vehicle without a driver, or passenger, and unladen, but with its fuel tank full and its normal complement of tools;

2.3. "*Lamp*" means a device designed to illuminate the road or to emit a light signal to other road users. Rear registration plate lamp and retro-reflectors are likewise to be regarded as lamps;

2.3.1. "*Equivalent lamps*" means lamps having the same function and authorised in the country in which the vehicle is registered; such lamps may have different characteristics from those of the lamps with which the vehicle is equipped at the time of approval, on condition that they satisfy the requirements of this Regulation;

2.3.2. "*Independent lamp*" means devices having separate apparent surfaces, separate light sources and separate lamp bodies;

2.3.3. "*Grouped lamps*" means devices having separate apparent surfaces and separate light sources, but a common lamp body;

2.3.4. "*Combined*" means devices having separate apparent surfaces, but a common light source and a common lamp body;

2.3.5. "*Reciprocally incorporated*" means devices having separate light sources or a single light source operating under different conditions (for example, optical, mechanical, electrical differences), totally or partially common apparent surfaces and a common lamp body;

2.3.6. "*Direction indicator lamp*" means the lamp used to indicate to other road-users that the driver intends to change direction to the right or to the left;

A direction indicator lamp or lamps may also be used according to provisions of UN Regulation No. 97.

2.3.7. "*Front position lamp*" means the lamp used to indicate the presence of the vehicle when viewed from the front;

2.3.8. "*Rear position lamp*" means the lamp used to indicate the presence of the vehicle when viewed from the rear;

2.3.9. "*Retro-reflector*" means a device used to indicate the presence of a vehicle by the reflection of light emanating from a light source not connected to the vehicle, the observer being situated near the source;

For the purpose of this Regulation, retro-reflecting number plates are not considered as retro-reflectors;

2.4. "*Light-emitting surface*" of a "lighting device", "light-signalling device" or a retro-reflector means all or part of the exterior surface of the transparent material as declared in the request for approval by the manufacturer of the device on the drawing, see Annex 3;

2.5. "*Illuminating surface*" (see Annex 3);

2.5.1. "*Illuminating surface of a lighting device*" (driving beam (main beam) headlamp, passing beam (dipped beam) headlamp, front fog lamp) means the orthogonal projection of the full aperture of the reflector, or in the case of headlamps with an ellipsoidal reflector of the "projection lens", on a transverse plane. If the lighting device has no reflector, the definition of paragraph 2.5.2. below shall be applied. If the light emitting surface of the lamp extends over part only of the full aperture of the reflector, then the projection of that part only is taken into account.

In the case of a passing-beam headlamp, the illuminating surface is limited by the apparent trace of the cut-off on to the lens. If the reflector and lens are adjustable relative to one another, the mean adjustment should be used;

In the case where any combination of a headlamp producing the principal passing-beam and additional lighting units or light sources designed to produce bend lighting are operated together, the individual illuminating surfaces, taken together, constitute the illuminating surface.

2.5.2. "*Illuminating surface of a light-signalling device other than a retro-reflector*" (direction indicator lamp, stop lamp, front position lamp, rear position lamp, hazard warning signal, rear fog lamp) means the orthogonal projection of the lamp in a plane perpendicular to its axis of reference and in contact with the exterior light-emitting surface of the lamp, this projection being bounded by the edges of screens situated in this plane, each allowing only 98 per cent of the total luminous intensity of the light to persist in the direction of the axis of reference. To determine the lower, upper and lateral limits of the illuminating surface, only screens with horizontal or vertical edges shall be used;

2.5.3. "*Illuminating surface of a retro-reflector*" (para. 2.3.9. above) means the orthogonal projection of a retro-reflector in a plane perpendicular to its axis of reference and delimited by planes continuous to the outermost parts of the retro-reflector's optical system and parallel to that axis. For the purposes of determining the lower, upper and lateral edges of the device, only horizontal and vertical planes shall be considered;

2.6. The "*apparent surface*" for a defined direction of observation means, at the request of the manufacturer or his duly accredited representative, the orthogonal projection of:

Either the boundary of the illuminating surface projected on the exterior surface of the lens (a-b);

Or the light-emitting surface (c-d);

In a plane perpendicular to the direction of observation and tangential to the most exterior point of the lens (see Annex 3 to this Regulation);

2.7. "*Centre of reference*" means the intersection of the axis of reference with the exterior light-emitting surface; it is specified by the manufacturer of the lamp;

2.8. "*Extreme outer edge*", on either side of the vehicle means the plane parallel to the median longitudinal plane of the vehicle and touching the lateral extremity of the vehicle, disregarding the projection or projections:

2.8.1. Of rear-view mirrors,

2.8.2. Of direction indicator lamps,

2.8.3. Of front and rear position lamps and retro-reflectors;

2.9. "*Over-all width*" means the distance between the two vertical planes defined in paragraph 2.8. above;

2.10. "*Colour of the light emitted from the device*". The definitions of the colour of the light emitted given in UN Regulation No. 48 and its series of amendments in force at the time of application for type approval shall apply to this Regulation.

2.11. "*Gross vehicle mass*" or "maximum mass" means the technically permissible maximum laden mass as declared by the manufacturer.

2.12. "*Laden*" means so loaded as to attain the gross vehicle mass as defined in paragraph 2.11. above.

2.13. "*Horizontal inclination*" means the angle created between the beam pattern when the motorcycle is set as specified in paragraph 5.4. of this Regulation, and the beam pattern when the motorcycle is banked (see drawing in Annex 6);

2.14. "*Horizontal inclination adjustment system (HIAS)*" means a device that adjusts the horizontal inclination of the headlamp towards zero;

2.15. "*Bank angle*" means the angle made with the vertical by the vertical longitudinal median plane of the motorcycle, when the motorcycle is rotated about its longitudinal axis (see drawing in Annex 6);

2.16. "*HIAS signal*" means any control signal or, any additional control input to the system or, a control output from the system to the motorcycle;

2.17. "*HIAS signal generator*" means a device, reproducing one or more of the HIAS signals for system test;

2.18. "*HIAS test angle*" means the angle δ created by the headlamp cut-off line and HH line (in case of an asymmetrical beam headlamp, the horizontal part of the cut-off shall be used), (see drawing in Annex 6).

2.19. "*Device*" means a component or combination of components used in order to perform one or several functions.

2.20. "*Exterior courtesy lamp*" means a lamp used to provide supplementary illumination to assist the mounting and dismounting of the vehicle driver and passenger or in loading operations.

2.21. "*Adaptive Driving-Beam*" (or "*ADB*") means a front lighting system consisting of driving-beam(s) only and type-approved according to UN Regulation No. 149 that adapts its beam pattern to the presence of oncoming and preceding vehicles in order to improve the long-range visibility for the driver without causing discomfort, distraction or glare to other road users.

Unless otherwise specified, administrative and technical provisions for the driving-beam function of the adaptive front lighting system (AFS) in UN Regulation No. 149 shall apply to ADB.

2.21.1. "ADB neutral state" means the state of the ADB when the driving-beam is in the maximum condition of activation.

2.22. "*Rear-end collision alert signal (RECAS)*" means an automatic signal given by the leading vehicle to the following vehicle. It warns that the following vehicle needs to take emergency action to avoid a collision.

2.23. “*Adaptive front lighting system*” (or ”AFS”) means a lighting device type-approved according to UN Regulation No. 149, providing beams with differing characteristics for automatic adaptation to varying conditions of use of the dipped beam (passing beam).

2.23.1. “*AFS control signal*” (V, E, W) means the input to the AFS in accordance with the paragraph 6.18.6.3. of this Regulation.

2.24. Definitions with regard to AFS:

2.24.1. “*Class*” of the passing beam (C, V, E or W) means the designation of the passing beam, identified by particular provisions according to UN Regulation No. 53 (for explanation only - the provisions of the passing beam classes are dedicated to the conditions as follows: C for the basic passing beam, V for use in lit areas such as towns, E for use on roads such as motorways, W for use in adverse conditions such as wet road);

2.24.2. *“Functional unit*” means a part of a lighting unit providing a specific light distribution which may be used for different modes or classes.

3. Application for approval

3.1. The application for approval of a vehicle type with regard to the installation of its lighting and light-signalling devices shall be submitted by the vehicle manufacturer or by his duly accredited representative.

3.2. It shall be accompanied by the undermentioned documents in triplicate and the following particulars:

3.2.1. A description of the vehicle type with regard to the items mentioned in paragraphs 2.1.1. to 2.1.3. above; the vehicle type duly identified shall be specified;

3.2.2. A list of the devices intended by the manufacturer to form the lighting and light-signalling equipment; the list may include several types of device for each function; each type shall be duly identified (national or international approval mark, if approved, name of manufacturer, etc.); in addition, the list may include in respect of each function the additional annotation "or equivalent devices";

3.2.3. A layout drawing of the lighting and light-signalling installation as a whole, showing the position of the various devices on the vehicle; and

3.2.4. If necessary, in order to verify the conformity to the prescriptions of the present regulation, a layout drawing or drawings of each lamp showing the illuminating surface, as defined in paragraph 2.5.1. above, the light-emitting surface as defined in paragraph 2.4. above, the axis of reference as defined in UN Regulation No. 48 and the centre of reference as defined in UN Regulation No. 48. This information is not necessary in the case of the rear registration plate lamp (as defined in UN Regulation No. 48).

3.2.5. A statement of the method used for the definition of the apparent surface (see paragraph 2.6.);

3.2.6. At the discretion of the manufacturer, a statement indicating whether lamps approved for and equipped with LED substitute light sources are allowed to be installed on the vehicle or not and, if this is allowed, which lamps.

3.2.7. Where an ADB is fitted on the vehicle, the applicant shall submit a detailed description providing the following information:

3.2.7.1. The technical characteristics relevant to the operation of ADB;

3.2.7.2. Special instruction, if any, for the inspection of the light sources and the visual observation of the beam;

3.2.7.3. The lamps that are grouped or combined with or reciprocally incorporated in the ADB.

3.2.8. Where an AFS is fitted on the vehicle, the applicant shall submit a detailed description providing the following information:

3.2.8.1. The lighting functions and modes for which the AFS has been approved;

3.2.8.2. The related AFS control signals and their technical characteristics as defined according to annex 14 to UN Regulation No. 149.

3.2.8.3. The provision being applied to adapt automatically the front lighting functions and modes according to paragraph 6.18.6.3. of this Regulation;

3.2.8.4. Special instruction, if any, for the inspection of the light source and the visual observation of the beam;

3.2.8.5. The documents according to paragraph 6.18.8.1. of this Regulation;

3.2.8.6. The lamps that are grouped or combined with or reciprocally incorporated in the AFS;

3.2.8.7. Lighting units which are designed to comply with the requirements of paragraph 6.18.5. of this Regulation.

3.3. An unladen vehicle fitted with a complete set of lighting and light-signalling equipment, as prescribed in paragraph 3.2.2. above, and representative of the vehicle type to be approved shall be submitted to the Technical Service responsible for conducting approval tests.

4. Approval

4.1. If the vehicle submitted for approval pursuant to this Regulation meets the requirements of the Regulation in respect of all the devices specified in the list, approval of that vehicle type shall be granted.

4.2. An approval number shall be assigned to each type approved. Its first two digits (at present 03 for the Regulation in its 03 series of amendments) shall indicate the series of amendments incorporating the most recent major technical amendments made to the Regulation at the time of issue of the approval.

4.3. Notice of approval or of extension or refusal or withdrawal of approval or production definitively discontinued of a vehicle type pursuant to this Regulation shall be communicated to the Parties to the Agreement which apply this Regulation, by means of a form conforming to the model in Annex 1 to this Regulation.

4.4. There shall be affixed, conspicuously and in a readily accessible place specified on the approval form, to every vehicle conforming to a vehicle type approved under this Regulation an international approval mark consisting of:

4.4.1. A circle surrounding the letter "E" followed by the distinguishing number of country which has granted approval;[2]

[2] The distinguishing numbers of the Contracting Parties to the 1958 Agreement are reproduced in Annex 3 to the Consolidated Resolution on the Construction of Vehicles (R.E.3), document ECE/TRANS/WP.29/78/Rev.6, Annex 3 - www.unece.org/trans/main/wp29/wp29wgs/wp29gen/wp29resolutions.html

4.4.2. The number of this Regulation followed by the letter "R", a dash, and the approval number to the right of the circle prescribed in paragraph 4.4.1. above.

4.5. If the vehicle conforms to a vehicle type approved, under one or more other Regulations annexed to the Agreement, in the country which has granted approval under this Regulation, the symbol prescribed in paragraph 4.4.1. above need not be repeated; in such a case the Regulation and approval numbers and the additional symbols of all the Regulations under which approval has been granted in the country which has granted approval under this Regulation shall be placed in vertical columns to the right of the symbol prescribed in paragraph 4.4.1. above.

4.6. The approval mark shall be clearly legible and be indelible.

4.7. The approval mark shall be placed close to or on the vehicle data plate affixed by the manufacturer.

4.8. Annex 2 to this Regulation gives examples of the arrangement of the approval marks.

5. General specifications

5.1. The lighting and light-signalling devices shall be so fitted that in normal conditions of use, and notwithstanding the vibrations to which they may be subjected, they retain the characteristics prescribed by this Regulation and enable the vehicle to comply with the requirements of this Regulation.

In particular, it shall not be possible for the lamps to be inadvertently maladjusted.

5.2. The illuminating lamps shall be so installed that correct adjustment of their orientation can easily be carried out.

5.3. For all light-signalling devices the reference axis of the lamp when fitted to the vehicle shall be parallel to the bearing plane of the vehicle on the road; in addition, it shall be perpendicular to the median longitudinal plane of the vehicle in the case of side retro-reflectors and parallel to that plane in the case of all light-signalling devices. A tolerance of ∀ 3° shall be allowed in each direction. In addition, if specifications for fitting are provided by the manufacturer they shall be complied with.

5.4. In the absence of specific instructions, the height and orientation of the lamp shall be verified with the vehicle unladen and placed on a flat horizontal surface, its median longitudinal plane being vertical and the handlebars being in the position corresponding to the straight-ahead movement. The tyre pressure shall be those prescribed by the manufacturer for the particular conditions of loading required in this Regulation.

In the case where an ADB or an AFS is installed, with the system in its ADB or AFS neutral state.

5.5. In the absence of specific instructions:

5.5.1. Single lamps or reflectors shall be mounted such that their centre of reference lies in the median longitudinal plane of the vehicle;

5.5.2. Lamps constituting a pair and having the same function shall:

5.5.2.1. Be mounted symmetrically in relation to the median longitudinal plane;

5.5.2.2. Be symmetrical to one another in relation to the median longitudinal plane;

5.5.2.3. Satisfy the same colorimetric requirements; and

5.5.2.4. Have identical nominal photometric characteristics;

5.5.2.5. Come on and go off simultaneously;

5.6. Grouped, combined or reciprocally incorporated or single lamps

5.6.1. Lamps may be grouped, combined or reciprocally incorporated with one another provided that all requirements regarding colour, position, orientation, geometric visibility, electrical connections and other requirements, if any, are fulfilled.

5.6.1.1. The photometric and colorimetric requirements of a lamp shall be fulfilled when all other functions with which this lamp is grouped, combined or reciprocally incorporated are switched OFF.

However, when a front or rear position lamp is reciprocally incorporated with one or more other function(s) which can be activated together with them, the requirements regarding colour of each of these other functions shall be fulfilled when the reciprocally incorporated function(s) and the front or rear position lamps are switched ON.

5.6.1.2. Stop lamps and direction indicator lamps are not permitted to be reciprocally incorporated.

5.6.1.3. However, where stop lamps and direction indicator lamps are grouped, any horizontal or vertical straight line passing through the projections of the apparent surfaces of these functions on a plane perpendicular to the reference axis, shall not intersect more than two borderlines separating adjacent areas of different colour.

5.6.2. Single lamps

5.6.2.1. Single lamps as defined in paragraph 2.16.1. of UN Regulation No. 48, subparagraph (a), composed of two or more distinct parts, shall be installed in such a way that:

(a) Either the total area of the projection of the distinct parts on a plane tangent to the exterior surface of the outer lens and perpendicular to the reference axis shall occupy not less than 60 per cent of the smallest quadrilateral circumscribing the said projection; or

(b) The minimum distance between the facing edges of two adjacent/tangential distinct parts shall not exceed 75 mm when measured perpendicularly to the reference axis.

These requirements shall not apply to a single retro reflector.

5.6.2.2. Single lamps as defined in paragraph 2.16.1. of UN Regulation No. 48, subparagraph (b) or (c), composed of two lamps marked "D" or two independent retro reflectors, shall be installed in such a way that:

(a) Either the projection of the apparent surfaces in the direction of the reference axis of the two lamps or retro reflectors occupies not less than 60 per cent of the smallest quadrilateral circumscribing the projections of the said apparent surfaces in the direction of the reference axis; or

(b) The minimum distance between the facing edges of the apparent surfaces in the direction of the reference axis of two lamps or two independent retro reflectors does not exceed 75 mm when measured perpendicularly to the reference axis.

5.6.2.3. Single lamps as defined in paragraph 2.16.1. of UN Regulation No. 48, subparagraph (d), shall fulfil the requirements of paragraph 5.6.2.1.

Where two or more lamps and/or two or more separate apparent surfaces are included into the same lamp body and/or have a common outer lens, these shall not be considered as an interdependent lamp system.

However, a lamp in the shape of a band or strip may be part of an interdependent lamp system.

5.7. The maximum height above ground shall be measured from the highest point and the minimum height from the lowest point of the apparent surface in the direction of the reference axis. For passing-beam headlamps, the minimum height from the ground shall be measured from the lowest point of the effective outlet of the optical system (e.g. reflector, lens, projection lens) independent of its utilisation.

Where the (maximum and minimum) height above the ground clearly meets the requirements of the Regulation, the exact edges of any surface need not be determined.

When referring to the distance between lamps, the position, as regards width, shall be determined from the inner edges of the apparent surface in the direction of the reference axis.

Where the position, as regards width, clearly meets the requirements of the Regulation, the exact edges of any surface need not be determined.

For the purposes of reducing the geometric visibility angles, the position of a lamp with regard to height above the ground, shall be measured from the H plane.

5.8. In the absence of specific instructions, no lamps other than direction indicator lamps, the vehicle-hazard warning signal lamps and the emergency stop signal shall be flashing lamps.

5.8.1. The photometric characteristics of a direction indicator lamp except for categories 5 and 6 specified in UN Regulation No. 6 or [LSD], and of a direction indicator lamp specified in UN Regulation No. 50 or [LSD] may be varied during a flash by sequential activation of light sources as specified in paragraph 5.6. of UN Regulation No. 6 or paragraph 5.6.11. of UN Regulation No. [LSD] or in paragraph 6.8. of UN Regulation No. 50.

This provision shall not apply when direction indicator lamps of categories 2a and 2b of UN Regulation No. 6 or [LSD] or category 12 of UN Regulation No. 50 or [LSD] are operated as emergency stop signal according to paragraph 6.14. of this Regulation.

5.9. No red light which could give rise to confusion shall be emitted from a lamp as defined in paragraph 2.3. in a forward direction and no white light which could give rise to confusion, shall be emitted from a lamp as defined in paragraph 2.3. in a rearward direction. No account shall be taken of lighting devices fitted for the interior lighting of the vehicle. In case of doubt, this requirement shall be verified as follows (see drawing in Annex 4):

5.9.1. Visibility of red light towards the front: a red lamp shall not be directly visible to an observer moving in zone 1 of a transverse plane situated 25 m forward of the foremost point on the vehicle;

5.9.2. Visibility of white light towards the rear: a white lamp shall not be directly visible to an observer moving in zone 2 of a transverse plane situated 25 m rearward of the rearmost point on the vehicle;

5.9.3. In their respective planes, the zones 1 and 2 explored by the eye of the observer are bound:

5.9.3.1. In height, by two horizontal planes 1 m and 2.2 m respectively above the ground;

5.9.3.2. In width, by two vertical planes which, forming to the front and the rear respectively an angle of 15° outwards from the vehicle's median longitudinal plane, pass through the point or points of contact of vertical planes parallel to the vehicle's median longitudinal plane and delimiting the vehicle's over-all width; if there are several points of contact, the foremost shall correspond to the forward plane and the rearmost to the rearward plane.

5.10. The electrical connections shall be such that the front position lamp or the passing-beam headlamp, if there is no front position lamp, the rear position lamp and the rear-registration-plate illuminating device cannot be switched ON or OFF otherwise than simultaneously, unless otherwise specified.

5.10.1. In the case of an interdependent lamp system, all light sources shall be switched on and off simultaneously.

5.11. In the absence of specific instructions, the electrical connection shall be such that the driving-beam headlamp, the passing-beam headlamp and the fog lamp cannot be switched on unless the lamps referred to in paragraph 5.10. above are likewise switched on. This requirement need not, however, be satisfied in the case of the driving-beam headlamp and passing-beam headlamp where their luminous warnings consist in switching on the passing-beam headlamp intermittently, at short intervals, or in switching on the driving-beam headlamp intermittently, or in switching on the passing-beam headlamp and driving-beam headlamp alternately at short intervals.

5.11.1. If installed, the daytime running lamp shall automatically be ON when the engine is running. If the headlamp is switched ON, the daytime running lamp shall not come ON when the engine is running.

5.11.1.1. If each DRL whose maximum luminous intensity exceeds 700 cd as identified in Annex 1 of UN Regulation No. [148] is fitted on vehicle, the passing beam shall be switched ON and OFF automatically relative to the ambient light conditions (e.g. switch ON during night-time driving conditions, tunnels, etc.) according to the requirements of Annex 8.

5.11.1.2. If each DRL whose maximum luminous intensity does not exceed 700 cd as identified in Annex 1 of UN Regulation No. [148] is fitted on vehicle, the switching ON or OFF of the passing beam may be either manual or automatic. If automatic, conditions of paragraph 5.11.1.1. must be complied with.

5.11.2. If no daytime running lamp is installed, the headlamp shall automatically be ON when the engine is running.

5.12. Tell-tale lamps

5.12.1. Every tell-tale lamp shall be readily visible to a driver in the normal driving position.

5.12.2. Where a "circuit-closed" tell-tale is prescribed by this Regulation, it may be replaced by an "operating" tell-tale.

5.13. Colours of the lights

The colours of the lights referred to in this Regulation shall be as follow:

Driving-beam headlamp:	white
Passing-beam headlamp:	white
Direction-indicator lamp:	amber
Stop lamp:	red
Rear-registration plate lamp:	white
Front position lamp:	white or amber
Rear position lamp:	red
Rear retro-reflector, non-triangular:	red
Side retro-reflector, non-triangular:	amber at the front amber or red at the rear
Vehicle-hazard warning signal:	amber
Front fog lamp:	white or selective yellow
Rear fog lamp:	red
Daytime running lamp	white
Emergency stop signal:	amber or red
Exterior courtesy lamp:	white
Adaptive Driving-Beam (ADB):	white
Rear-end collision alert signal:	amber
Adaptive front lighting system (AFS):	white

5.14. Every vehicle submitted for approval pursuant to this Regulation shall be equipped with the following lighting and light-signalling devices:

5.14.1. Driving-beam headlamp (paragraph 6.1.);

5.14.2. Passing-beam headlamp (paragraph 6.2.);

5.14.3. Direction indicator lamps (paragraph 6.3.);

5.14.4. Stop lamp, S1 category device specified in UN Regulation No. 7 or [LSD] or stop lamp specified in UN Regulation No. 50 (paragraph 6.4.) or stop lamp for category L vehicles in UN Regulation No [LSD];

5.14.5. Rear-registration-plate illuminating device (paragraph 6.5.);

5.14.6. Front position lamp (paragraph 6.6.);

5.14.7. Rear position lamp (paragraph 6.7.);

5.14.8. Rear retro reflector, non-triangular (paragraph 6.8.);

5.14.9. Side retro reflector, non-triangular (paragraph 6.12.);

5.15. It may, in addition, be equipped with the following lighting and light-signalling devices;

5.15.1. Vehicle-hazard warning signal (paragraph 6.9.);

5.15.2. Fog lamps;

5.15.2.1. Front fog lamp (paragraph 6.10.);

5.15.2.2. Rear fog lamp (paragraph 6.11.);

5.15.3. Daytime running lamp (paragraph 6.13.);

5.15.4. Stop lamp, S3 category device specified in UN Regulation No. 7 (paragraph 6.4.) or [LSD];

5.15.5. Emergency stop signal (paragraph 6.14.).

5.15.6. Exterior courtesy lamp (paragraph 6.15.).

5.15.7. Adaptive Driving-Beam (ADB) (paragraph 6.16.).

5.15.8. Rear-end collision alert signal (paragraph 6.17.).

5.15.9. Adaptive front lighting system (AFS) (paragraph 6.18.)

5.16. The fitting of each of the lighting and light-signalling devices mentioned in paragraphs 5.14. and 5.15. above shall be effected in conformity with the relevant requirements in paragraph 6. of this Regulation.

5.17. The fitting of any lighting and light-signalling devices other than those mentioned in paragraphs 5.14. and 5.15. above is prohibited for the purposes of type approval.

5.18. Lighting and light-signalling devices type-approved for four-wheeled vehicles of categories M_1 and N_1 and referred to in paragraphs 5.14. and 5.15. above may also be fitted to motorcycles.

5.19. Rear position lamps, rear direction-indicators and rear retro-reflectors, may be installed on movable components only:

5.19.1. If at all fixed positions of the movable components the lamps on the movable components meet all the position, geometric visibility, colorimetric and photometric requirements for those lamps.

5.19.2. In the case where the functions referred to in paragraph 5.19. are obtained by an assembly of two lamps marked "D" (see paragraph 2.16.1. of UN Regulation No. 48), only one of the lamps needs to meet the position, geometric visibility and photometric requirements for those lamps at all fixed positions of the movable components.

5.19.3. Where additional lamps for the above functions are fitted and are activated, when the movable component is in any fixed open position, provided that these additional lamps satisfy all the position, geometric visibility and photometric requirements applicable to the lamps installed on the movable component.

5.19.4. In the case where the functions referred to in paragraph 5.19. are obtained by an interdependent lamp system either of the following conditions shall apply:

(a) Should the complete interdependent lamp system be mounted on the moving component(s), the requirements of paragraph 5.19.1. shall be satisfied. However, additional lamps for the above functions may be activated, when the movable component is in any fixed open position, provided that these additional lamps satisfy all the position, geometric visibility, colorimetric and photometric requirements applicable to the lamps installed on the movable component.

or

(b) Should the interdependent lamp system be partly mounted on the fixed component and partly mounted on a movable component, the interdependent lamp(s) specified by the Applicant during the device approval procedure shall meet all the position, outwards geometric visibility, colorimetric and photometric requirements for those lamps, at all fixed positions of the movable component(s). The inwards geometric visibility requirement(s) is(are) deemed to be satisfied if this(these) interdependent lamp(s) still conform(s) to the photometric values prescribed in the field of light distribution for the approval of the device, at all fixed positions of the movable component(s).

5.20. General provisions relating to geometric visibility

5.20.1. There shall be no obstacle on the inside of the angles of geometric visibility to the propagation of light from any part of the apparent surface of the lamp observed from infinity. However, no account is taken of obstacles, if they were already presented when the lamp was type-approved.

5.20.2. If measurements are taken closer to the lamp, the direction of observation shall be shifted parallel to achieve the same accuracy.

5.20.3. If, when the lamp is installed, any part of the apparent surface of the lamp is hidden by any further parts of the vehicle, proof shall be furnished that the part of the lamp not hidden by obstacles still conforms to the photometric values prescribed for the approval of the device.

5.20.4. When the vertical angle of geometric visibility below the horizontal may be reduced to 5 degrees (lamp at less than 750 mm above the ground, measured according to the provisions of paragraph 5.7.) the photometric field of measurements of the installed optical unit may be reduced to 5 degrees below the horizontal.

5.20.5. In the case of an interdependent lamp system the geometric visibility requirements shall be fulfilled when all its interdependent lamps are operated together.

5.21. A device type approved according to any preceding series of amendments to UN Regulations Nos. [LSD] and/or [RID] and/or [RRD] is deemed equivalent to one approved according to the latest series of amendments to the pertinent UN Regulations Nos. [LSD] and/or [RID] and/or [RRD], when the change indexes (defined in UN Regulation No. 48) related to each individual lamp (function) do not differ. In this case such a device may be fitted on the vehicle to be type approved without any update of the device type approval documents and device markings.

5.22. The use of lamps approved for and equipped with LED substitute light source(s), is allowed exclusively in the case where the statement indicated in paragraph 3.2.6. is present and positive.

To verify that this statement is respected, both at the type approval and in the conformity of production verification, the presence of the marking on the lamps related to the use of LED substitute light source(s) shall be checked.

5.23. Where an ADB is fitted, it shall be considered equivalent to the driving-beam headlamp(s).

5.24. Where an AFS is fitted, it shall be considered equivalent to the passing-beam headlamp(s).

6. Individual specifications

6.1. Driving-beam headlamp

6.1.1. Number:

6.1.1.1. For motorcycles having a cylinder capacity ≤ 125 cm^3 and a maximum power ≤ 11 kW (*)

One or two, type-approved according to Class A, B, CS or DS of the 01 or subsequent series of amendments to UN Regulation No. 149.

---

* The power limits are based on maximum continuous rated power for electric propelled vehicles and maximum net power for vehicles propelled with a combustion engine.

6.1.1.2. For motorcycles having a cylinder capacity > 125 cm^3 or a maximum power > 11 kW (*)

One or two, type-approved according to Class A, B, or DS of the 01 or subsequent series of amendments to UN Regulation No. 149.

Two, type-approved according to Class CS of the 01 or subsequent series of amendments to UN Regulation No. 149.

---

* The power limits are based on maximum continuous rated power for electric propelled vehicles and maximum net power for vehicles propelled with a combustion engine.

6.1.2. Arrangement

No special requirement.

6.1.3. Position

6.1.3.1. Width

6.1.3.1.1. An independent driving lamp may be fitted above or below or to one side of another front lamp: if these lamps are on top of the other the reference centre of the driving lamp must be located within the median longitudinal plane of the vehicle; if these lamps are side by side their reference centre must be symmetrical in relation to the median longitudinal plane of the vehicle.

6.1.3.1.2. A driving-beam headlamp, that is reciprocally incorporated with another front lamp, shall be fitted in such a way that its reference centre lies within the median longitudinal plane of the vehicle. However, when the vehicle is also fitted with an independent principal passing-beam headlamp, or a principal passing-beam headlamp that is reciprocally incorporated with a front position lamp alongside the driving-beam headlamp, their reference centres shall be symmetrical in relation to the median longitudinal plane of the vehicle.

6.1.3.1.3. Two driving lamps of which either one or both are reciprocally incorporated with another front lamp shall be fitted in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.1.3.2. The length: at the front of the vehicle. This requirement is regarded as satisfied if the light emitted does not cause discomfort to the driver either directly or indirectly by means of the rear-view mirrors and/or reflective surfaces on the vehicle.

6.1.3.3. In any case, the distance between the edge of the illuminating surface of any independent driving lamp and the edge of that of the lamp producing the principal passing-beam shall not exceed 200 mm. The distance between the edge of the illuminating surface of any independent driving lamp and the ground shall be from 500 mm to 1,300 mm.

6.1.3.4. In the case of two driving lamps: the distance separating the illuminating surfaces of two driving lamps shall not exceed 200 mm.

6.1.4. Geometric visibility

The visibility of the illuminating surface, including its visibility in areas which do not appear to be illuminated in the direction of observation considered, shall be ensured within a divergent space defined by generating lines based on the perimeter of the illuminating surface and forming an angle of not less than 5° with the axis of reference of the headlamp.

6.1.5. Orientation

6.1.5.1. Forwards. The lamp(s) may move with the steering angle.

6.1.5.2. An HIAS may be installed for the driving-beam.

6.1.6. Electrical connections

6.1.6.1. The passing-beam(s) may remain switched ON with the driving-beam(s).

However, when the vehicle is fitted with secondary driving-beam(s) approved in accordance with UN Regulation No. 149, at least one of the following lamps shall remain switched ON with the secondary driving- beam(s):

(a) Passing-beam(s);

(b) Driving-beam of Class A or B approved according to the 01 or subsequent series of amendments to UN Regulation No. 149.

6.1.6.2. The control of the driving-beam headlamp(s) may be automatic regarding their switching ON and OFF, the control signals being produced by a sensor system which is capable of detecting and reacting to each of the following inputs:

(a) Ambient lighting conditions;

(b) The light emitted by the front lighting devices and front light-signalling devices of oncoming vehicles;

(c) The light emitted by the rear light-signalling devices of preceding vehicles.

Additional sensor functions to improve performance are allowed.

For the purpose of this paragraph, "vehicles" means vehicles of categories L, M, N, O, T, as well as bicycles, such vehicles being equipped with retro-reflectors, with lighting and light-signalling devices, which are switched ON.

6.1.6.3. It shall always be possible to switch the driving-beam headlamp(s) ON and OFF manually and to manually deactivate the automatic control of the driving-beam headlamp(s). Moreover, the switching OFF, of the driving-beam headlamp(s) and the deactivation of their automatic control, shall be by means of a simple and immediate manual operation; the use of submenus is not allowed.

6.1.7. Tell-tales

6.1.7.1. "Circuit-closed" tell-tale.

Mandatory, non-flashing blue signal lamp.

6.1.7.2. "HIAS failure" tell-tale

Mandatory, flashing amber signal lamp, which may be combined with the telltale referred to in paragraph 6.2.8.2. below. It shall be activated whenever a failure is detected with respect to the HIAS signals. It shall remain activated while the failure is present.

6.1.7.3. If the control of the driving-beam headlamp(s) is automatic, an indication shall be provided to the driver that the automatic control of the driving-beam function is activated. This information shall remain displayed as long as the automatic operation is activated.

6.1.8. Other requirements

6.1.8.1. The aggregate maximum intensity of the driving-beam headlamps which can be switched on simultaneously shall not exceed 430,000 cd which corresponds to a reference number of 100. (The approval value).

6.1.8.2. In the event of a driving-beam HIAS failure, without the use of any special tools, it shall be possible to:

(a) Deactivate the HIAS until it is reset according to the manufacturer’s instructions; and

(b) Re-position the driving-beam so that its horizontal and vertical alignments are the same as a headlamp not equipped with HIAS.

The manufacturer shall provide a detailed description of the procedure for resetting the HIAS.

Alternatively, the manufacturer may choose to install an automatic system that either achieves both the tasks specified above or resets the HIAS. In this case, the manufacturer shall provide the test house with a description of the automatic system and, until such time as harmonized requirements have been developed, demonstrate the means of verifying that the automatic system works as described.

6.1.8.3. Automatic switching ON and OFF of the driving-beam headlamp(s):

6.1.8.3.1. The sensor system used to control the automatic switching ON and OFF of the driving-beam headlamp(s) shall comply with the following requirements:

6.1.8.3.1.1. The boundaries of the minimum fields in which the sensor is able to detect light emitted from other vehicles defined in paragraph 6.1.6.2. above are defined by the angles indicated below.

6.1.8.3.1.1.1. Horizontal angles: 15 degrees to the left and 15 degrees to the right.

Vertical angles: 5 degrees upwards and 2 degrees downwards.

These angles are measured from the centre of the sensor aperture relative to a horizontal straight line through its centre and parallel to the longitudinal median plane of the vehicle.

6.1.8.3.1.2. The sensor system shall be able to detect on a straight level road:

(a) An oncoming power driven vehicle at a distance extending to at least 400 m;

(b) A preceding power driven vehicle or a vehicle-trailers combination at a distance extending to at least 100 m;

(c) An oncoming bicycle at a distance extending to at least 75 m, its illumination represented by a white lamp with a luminous intensity of 150 cd with a light emitting area of 10± 3cm^2 and a height above a ground of 0.8 m.

To verify compliance with (a) and (b) above, the oncoming and preceding power driven vehicle (or vehicle-trailer combination) shall have position lamps (if applicable) and passing-beam headlamp(s) switched ON.

6.1.8.3.2. The transition from driving-beam to passing-beam and vice versa may be performed automatically and shall not cause discomfort, distraction or glare.

6.1.8.3.3. The overall performance of the automatic control shall be verified by:

6.1.8.3.3.1. Means of simulation or other means of verification accepted by the Type Approval Authority, as provided by the applicant.

6.1.8.3.3.2. A test drive according to paragraph 1 in Annex 9. The performance of the automatic control shall be documented and checked against the applicant's description. Any obvious malfunctioning shall be contested (e. g. excessive angular movement or flicker).

6.1.8.3.4. The control of the driving-beam headlamp(s) may be such that the driving-beam headlamp(s) are switched ON automatically only when:

(a) No vehicles, as mentioned in paragraph 6.1.6.2. above, are detected within the fields and distances according to paragraphs 6.1.8.3.1.1. and 6.1.8.3.1.2.; and

(b) The detected ambient lighting levels are as prescribed in paragraph 6.1.8.3.5. below.

6.1.8.3.5. In the case where driving-beam headlamp(s) are switched ON automatically, they shall be switched OFF automatically when oncoming or preceding vehicles, as mentioned in paragraph 6.1.6.2. above, are detected within the fields and distances according to paragraphs 6.1.8.3.1.1. and 6.1.8.3.1.2.

Moreover, they shall be switched OFF automatically when the illuminance produced by ambient lighting conditions exceeds 7000 lx.

Compliance with this requirement shall be demonstrated by the applicant, using simulation or other means of verification accepted by the Type Approval Authority. If necessary the illuminance shall be measured on a horizontal surface, with a cosine corrected sensor on the same height as the mounting position of the sensor on the vehicle. This may be demonstrated by the manufacturer by sufficient documentation or by other means accepted by the Type Approval Authority.

6.2. Passing-beam headlamp

6.2.1. Number:

6.2.1.1. For motorcycles having a cylinder capacity ≤ 125 cm^3 and a maximum power ≤ 11 kW (*)

One or two, type-approved according to Class C, CS or DS of the 01 or subsequent series of amendments to UN Regulation No. 149.

* The power limits are based on maximum continuous rated power for electric propelled vehicles and maximum net power for vehicles propelled with a combustion engine.

6.2.1.2. For motorcycles having a cylinder capacity > 125 cm^3 or a maximum power > 11 kW (*)

One or two, type-approved according to Class C or DS of the 01 or subsequent series of amendments to UN Regulation No. 149.

Two, type-approved according to Class CS of the 01 or subsequent series of amendments to UN Regulation No. 149.

* The power limits are based on maximum continuous rated power for electric propelled vehicles and maximum net power for vehicles propelled with a combustion engine.

6.2.2. Arrangement

No special requirement.

6.2.3. Position

6.2.3.1. Width

6.2.3.1.1. An independent passing lamp may be installed above, below or to one side of another front lamp: if these lamps are one above the other the reference centre of the lamp producing the principal passing-beam shall be located within the median longitudinal plane of the vehicle; if these lamps are side by side their reference centre shall be symmetrical in relation to the median longitudinal plane of the vehicle.

6.2.3.1.2. A headlamp producing the principal passing-beam, that is reciprocally incorporated with another front lamp, shall be fitted in such a way that its reference centre lies within the median longitudinal plane of the vehicle. However, when the vehicle is also fitted with an independent driving-beam headlamp, or a driving-beam headlamp that is reciprocally incorporated with a front position lamp alongside the headlamp producing the principal passing-beam, their reference centres shall be symmetrical in relation to the median longitudinal plane of the vehicle.

6.2.3.1.3. Two headlamps producing the principal passing-beam, of which either one or both are reciprocally incorporated with another front lamp shall be installed in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.2.3.1.4. If installed, additional lighting unit(s) which provide bend lighting, type approved as part of the passing-beam according to UN Regulation No. 149, shall be installed under the following conditions:

In the case of (a) pair(s) of additional lighting units, they shall be installed so that their reference centre(s) are symmetrical in relation to the median longitudinal plane of the vehicle.

In the case of a single additional lighting unit, its reference centre shall be coincident with the median longitudinal plane of the vehicle.

6.2.3.2. Height: a minimum of 500 mm and a maximum of 1,200 mm above the ground.

6.2.3.3. Length: at the front of the vehicle. This requirement is regarded as satisfied if the light emitted does not cause discomfort to the driver either directly or indirectly by means of the rear-view mirrors and/or reflective surfaces of the vehicle.

6.2.3.4. In the case of two headlamps producing the principal passing-beam the distance separating the illuminating surfaces shall not exceed 200 mm.

6.2.4. Geometric visibility

Defined by angles α and β as specified in paragraph 2.13. of UN Regulation No. 48:

α = 15° upwards and 10° downwards;

β = 45° to the left and to the right for a single lamp;

β = 45° outwards and 10° inwards for each pair of lamps.

The presence of partitions or other items of equipment near the headlamp shall not give rise to secondary effects causing discomfort to other road users.

6.2.5. Orientation

6.2.5.1. Forwards. The lamp(s) may move in line with the steering angle.

6.2.5.2. The vertical inclination of the headlamp producing the principal passing-beam shall remain between -0.5 and -2.5 per cent, except in the case where an external adjusting device is present.

6.2.5.3. For headlamp producing the principal passing-beam with a light source having an objective luminous flux which exceeds 2,000 lumens, the vertical inclination of the headlamp shall remain between -0.5 and -2.5 per cent. A headlamp levelling device may be used to satisfy the requirements of this paragraph but its operation shall be automatic.[3]

[3] However, until 60 months after the date of entry into force of Supplement 10 to the 01 series of amendments this operation may be manual without the use of tools. In such case the manufacturer shall provide in the vehicle owners' manual instruction regarding such manual headlamp levelling.

6.2.5.4. The requirement in paragraph 6.2.5.3. above shall be tested on the vehicle in the following conditions:

Condition A (rider alone):

A mass of 75 kg ± 1 kg, simulating the rider, shall be placed on the vehicle in such a way as to reproduce the axle loads declared by the manufacturer for this loading condition.

The vertical inclination (initial aiming) of the headlamp producing the principal passing-beam shall be set, following the manufacturer’s instructions, between -1.0 and -1.5 per cent.

Condition B (fully laden motorcycle):

Masses, simulating the manufacturer's maximum total mass, shall be placed on the vehicle in such a way as to reproduce the axle loads declared by the manufacturer for this loading condition.

Before making the measurements, the vehicle shall be rocked three times up and down and then moved backwards and forwards for at least a complete wheel revolution.

6.2.5.5. An HIAS may be installed for the passing-beam. The HIAS shall not adjust the horizontal inclination by more than the vehicle’s bank angle.

6.2.5.6. The requirement in paragraph 6.2.5.5. above shall be tested under the following conditions:

The test vehicle shall be set as specified in paragraph 5.4. of this Regulation. Incline the vehicle and measure the HIAS test angle.

The vehicle shall be tested in the following two conditions:

(a) The maximum horizontal inclination adjustment angle specified by the manufacturer (to left and to right);

(b) Half of the maximum horizontal inclination adjustment angle specified by the manufacturer (to left and to right).

And when the test vehicle is returned to the position as specified in paragraph 5.4. of this Regulation, the HIAS test angle shall return to zero quickly.

The handlebar may be fixed in the straight ahead position so as not to move during the vehicle inclination.

For the test the HIAS shall be activated by means of an HIAS signal generator.

The system shall be considered to satisfy the requirements of paragraph 6.2.5.5. above, if all measured HIAS test angles are not less than zero. This may be demonstrated by the manufacturer using other means accepted by the Type Approval Authority.

6.2.5.7. Additional light source(s) or additional lighting unit(s) may be activated only in conjunction with the principal passing-beam or the driving-beam to produce bend lighting. The illumination provided by the bend lighting shall not extend above the horizontal plane that is parallel with the ground and containing the reference axis of the headlamp producing the principal passing-beam for all bank angles as specified by the manufacturer during type approval of the device according to UN Regulation No. 149.

6.2.5.8. The requirement in paragraph 6.2.5.7. above shall be tested as follows:

The test vehicle shall be set as specified in paragraph 5.4. of this Regulation. Measure the bank angles on both sides of the vehicle under every condition where the bend lighting is activated. The bank angles to measure are the

bank angles specified by the manufacturer during type approval of the device according to UN Regulation No. 149.

The handlebar may be fixed in the straight ahead position so as not to move during the vehicle inclination.

For the test, the bend lighting may be activated by means of a signal generator provided by the manufacturer.

The system is considered to satisfy the requirements of paragraph 6.2.5.7. above, if all measured bank angles on both sides of the vehicle are greater than or equal to the minimum bank angles given in the communication form for the type approval of the device according to UN Regulation No. 149.

Conformity to paragraph 6.2.5.7. above may be demonstrated by the manufacturer using other means accepted by the Type Approval Authority responsible for type approval.

6.2.6. Electrical connections

The control for changing over to the passing-beam(s) shall switch off the driving-beam(s) simultaneously.

Passing-beam headlamps with a light source approved in accordance with UN Regulation No. 99 shall remain switched on when the driving-beam is illuminated.

6.2.6.1. The additional light source(s) or additional lighting unit(s) used to produce bend lighting shall be so connected that it (they) cannot be activated unless the headlamp(s) producing the principal passing-beam or the driving-beam is (are) also activated.

The additional light source(s) or additional lighting unit(s) used to produce bend lighting on each side of the vehicle may only be automatically activated when the bank angle(s) is(are) greater or equal to the minimum bank angle(s) given in the communication form for the type approval of the device according to UN Regulation No. 49.

However, the additional light source(s) or additional lighting unit(s) shall not be activated when the bank angle is less than three degrees.

The additional light source(s) or additional lighting unit(s) shall be deactivated when the bank angle(s) is (are) less than the minimum bank angle(s) given in the communication form for the type approval of the device according to UN Regulation No. 149.

6.2.7. Telltales

6.2.7.1. "Circuit-closed" tell-tale.

Optional; non-flashing green signal lamp.

6.2.7.2. "HIAS failure" tell-tale.

Mandatory, flashing amber signal lamp, which may be combined with the telltale referred to in paragraph 6.1.7.2. It shall be activated whenever a failure is detected with respect to the HIAS signals. It shall remain activated while the failure is present.

6.2.7.3. In the event of a control system failure, additional light source(s) or additional lighting unit(s) producing bend lighting shall be switched OFF automatically.

6.2.8. Other requirements

In the event of a passing-beam HIAS failure, without the use of any special tools, it shall be possible to:

(a) Deactivate the HIAS until it is reset according to the manufacturers instructions; and

(b) Re-position the passing-beam so that its horizontal and vertical alignments are the same as a headlamp not equipped with HIAS.

The manufacturer shall provide a detailed description of the procedure for resetting the HIAS.

Alternatively, the manufacturer may choose to install an automatic system that either achieves both tasks specified above or resets the HIAS. In this case, the manufacturer shall provide the test house with a description of the

automatic system and, until such time as harmonized requirements have been developed, demonstrate the means of verifying that the automatic system works as described.

6.3. Direction indicator lamp

6.3.1. Number

Two per side.

6.3.2. Arrangement

Two front indicators, type-approved as category 1, 1a or 1b according to the 01 or subsequent series of amendments to UN Regulation No. 6, or to the 00 or subsequent series of amendments to UN Regulation 148; or category 11, 11a, 11b or 11c according to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

Two rear indicators, type-approved as category 2 according to the 01 or subsequent series of amendments to UN Regulation No. 6, or to the 00 or subsequent series of amendments to UN Regulation No. 148; or category 12 according to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

6.3.3. Position

6.3.3.1. In width: For front indicators, the following requirements shall all be met:

(a) There shall be a minimum distance of 240 mm between illuminating surfaces;

(b) The indicators shall be situated outside the longitudinal vertical plane tangential to the outer edges of the illuminating surface of the driving-beam(s) and/or principal passing-beam(s);

(c) There shall be a minimum distance between the illuminating surface of the indicators and headlamp producing the principal passing-beam closest to one another as follows:

Minimum indicator intensity (cd)	*Minimum separation (mm)*
90	75
175	40
250	20
400	≤ 20

For rear indicators, the clearance between the inner edges of the two illuminating surfaces shall be at least 180 mm on the condition that the prescriptions of paragraph 2.13. of UN Regulation No. 48 are applied even when the registration plate is mounted;

6.3.3.2. In height: not less than 350 mm nor more than 1,200 mm above the ground;

6.3.3.3. In length: the forward distance between the centre reference of the rear indicators and the transverse plane which constitutes the rearmost limit of the vehicle's over-all length shall not exceed 300 mm.

6.3.4. Geometric visibility

Horizontal angles: 20° inwards, 80° outwards.

Vertical angles: 15° above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

6.3.5. Orientation

The front direction indicators may move in line with the steering angle.

6.3.6. Electrical connections

6.3.6.1. The direction indicator lamps shall switch on independently of the other lamps. All direction indicator lamps on one side of a vehicle shall be switched on and off by means of one control.

6.3.6.2. The direction indicator lamps may be switched ON to indicate the status of the device for protection of vehicles against unauthorized use.

6.3.6.3. The indication described in paragraph 6.3.6.2. shall be produced by the simultaneous operation of the direction indicator lamps and shall be in accordance to the following conditions.

In case of single indication:	3 seconds maximum
In case of continuous indication:	
Duration:	5 minutes maximum
Frequency:	(2 ± 1) Hz
On time:	Off time ± 10 per cent

This indication shall be allowed only when the device which starts and/or stops the engine (propulsion system) is set in a position which makes it impossible for the engine (propulsion system) to operate.

6.3.7. "Operating" tell-tale

Mandatory. This may be optical or auditory or both. If it is optical it shall be (a) flashing green lamp(s), which, in the event of defective operation of any of the direction indicators, is extinguished, remains alight without flashing, or shows a marked change of frequency.

6.3.8. Other requirements

The characteristics indicated below shall be measured with no other load on the electrical system than that required for the operation of the engine and the lighting devices. For all vehicles:

6.3.8.1. The light flashing frequency shall be 90 ± 30 times per minute;

6.3.8.2. The flashing of the direction indicators on the same side of the vehicle may occur synchronously or alternately;

6.3.8.3. Operation of the light-signal control shall be followed within not more than one second by the appearance of the light and within not more than one-and-one half seconds by the first extinction of the light.

6.3.8.4. In the event of failure, other than a short circuit, of one direction indicator lamp, the other(s) direction indicator lamp(s) indicating the same direction shall continue to flash or remain alight, but the frequency in this condition may be different from that prescribed.

6.4. Stop lamp

6.4.1. Number

One or two, type-approved as a category S1 device according to the 02 or subsequent series of amendments to UN Regulation No. 7, or to the 00 or subsequent series of amendments to UN Regulation No. 148; or as a stop lamp for category L vehicles according to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

Optional one, type-approved as a category S3 device according to the 02 or subsequent series of amendments to UN Regulation No. 7, or to the 00 or subsequent series of amendments to UN Regulation No. 148.

6.4.2. Arrangement

No special requirement.

6.4.3. Position

6.4.3.1. For category S1 device specified in UN Regulation No. 7 or UN Regulation No. [LSD] or stop lamp specified in UN Regulation No. 50 or [LSD]

In height: not less than 250 mm nor more than 1,500 mm above the ground;

In length: at the rear of the vehicle.

6.4.3.2. For the category S3 device specified in UN Regulation No. 7 or [LSD]

In height: The horizontal plane tangential to the lower edge of the apparent surface shall not be less than 850 mm above the ground.

However, the horizontal plane tangential to the lower edge of the apparent surface shall be above the horizontal plane tangential to the upper edge of the apparent surface of the category S1 device specified in UN Regulation No. 7 or [LSD] or stop lamp specified in UN Regulation No. 50 or stop lamp for category L vehicles of UN Regulation No. [LSD].

In length: at the rear of the vehicle.

6.4.4. Geometric visibility

For category S1 device specified in UN Regulation No. 7 or [LSD] or stop lamp specified in UN Regulation No. 50 or stop lamp for category L vehicles of UN Regulation No. [LSD]

Horizontal angle:	45° to left and to right for a single lamp; 45° outwards and 10° inwards for each pair of lamps;
Vertical angle:	15° above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

For category S3 device specified in UN Regulation No. 7 or [LSD]

Horizontal angle:	10° to the left and to the right of the longitudinal axis of the vehicle.
Vertical angle:	10° above and 5° below the horizontal.

6.4.5. Orientation

Towards the rear of the vehicle.

6.4.6. Electrical connections

6.4.6.1. All the stop lamps shall light up simultaneously when the braking system provides the braking signal defined in UN Regulation No. 78.

6.4.6.2. The stop lamps need not to function if the device, which starts and/or stops the engine (propulsion system), is in a position that makes it impossible for the engine (propulsion system) to operate.

6.4.7. "Tell-tale"

Tell-tale optional; where fitted, this tell-tale shall be a tell-tale consisting of a non-flashing warning light which comes on in the event of the malfunctioning of the stop lamps.

6.4.8. Other requirements

None.

6.5. Rear-registration-plate illuminating device

6.5.1. Number

One, type-approved as category 2 according to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

The device may consist of several optical components designed to illuminate the space reserved for the registration plate.

6.5.2. Arrangement } Such that the device illuminates the space reserved for the registration plate.

6.5.3. Position } Such that the device illuminates the space reserved for the registration plate.

6.5.3.1. In width: } Such that the device illuminates the space reserved for the registration plate.

6.5.3.2. In height: } Such that the device illuminates the space reserved for the registration plate.

6.5.4. Geometric visibility } Such that the device illuminates the space reserved for the registration plate.

6.5.5. Orientation } Such that the device illuminates the space reserved for the registration plate.

6.5.6. Tell-tale

Optional: Its function shall be performed by the tell-tale prescribed for the position lamp.

6.5.7. Other requirements

When the rear registration plate lamp is combined with the rear position lamp, reciprocally incorporated in the stop lamp or in the rear fog lamp, the photometric characteristics of the rear registration plate lamp may be modified during the illumination of the stop lamp or the rear fog lamp.

6.6. Front position lamp

6.6.1. Number

One or two	if coloured white
or	
Two (one per side)	if coloured amber

The device(s) shall be type-approved according to the 02 or subsequent series of amendments to UN Regulation No. 7, or to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

6.6.2. Arrangement

No special requirement.

6.6.3. Position

6.6.3.1. Width:

An independent front position lamp may be fitted above or below, or to one side of another front lamp: if these lamps are one above the other, the reference centre of the front position lamp shall be located within the median longitudinal plane of the vehicle; if these lamps are side by side, their reference centres shall be symmetrical in relation to the median longitudinal plane of the vehicle;

A front position lamp, that is reciprocally incorporated with another front lamp, shall be installed in such a way that its reference centre is situated in the median longitudinal plane of the vehicle. However, when the vehicle is also fitted with another front lamp alongside the front position lamp, their reference centres shall be symmetrical in relation to the median longitudinal plane of the vehicle.

Two front position lamps, one or both of them reciprocally incorporated with another front lamp, shall be installed in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.6.3.2. In height: not less than 350 mm nor more than 1,200 mm above the ground.

6.6.3.3. In length: at the front of the vehicle.

6.6.4. Geometric visibility

Horizontal angle:	80° to the left and to the right for a single lamp: the horizontal angle may be 80° outwards and 20° inwards for each pair of lamps.
Vertical angle:	15° above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

6.6.5. Orientation

Forwards. The lamp(s) may move in line with the steering angle.

6.6.6. "Circuit-closed" tell-tale

Mandatory. Non-flashing green signal lamp. This tell-tale shall not be required if the instrument illumination lighting can be switched on or off only simultaneously with the position lamp(s).

6.6.7. Other requirements

If a front position lamp is reciprocally incorporated with a direction indicator, the electrical connection of the front position lamp on the relevant side of the vehicle or the reciprocally incorporated part of it shall be such that it is switched OFF during the entire time (both ON and OFF cycle) of operation of the direction indicator lamp.

6.7. Rear position lamp

6.7.1. Number

One or two, type-approved according to the 02 or subsequent series of amendments to UN Regulation No. 7, or to the 00 or subsequent series of amendments to UN Regulation Nos. 50 or 148.

6.7.2. Arrangement

No special requirements.

6.7.3. Position

6.7.3.1. in height: not less than 250 mm nor more than 1,500 mm above the ground;

6.7.3.2. in length: at the rear of the vehicle.

6.7.4. Geometric visibility

Horizontal angle:	80 ° to left and to right for a single lamp: the horizontal angle may be 80° outwards and 20° inwards for each pair of lamps.
Vertical angle:	15° above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

6.7.5. Orientation

Rearwards.

6.7.6. "Circuit-closed" tell-tale

Optional: Its function shall be performed by the device prescribed for the front position lamp.

6.7.7. Other requirements

If a rear position lamp is reciprocally incorporated with a direction indicator, the electrical connection of the rear position lamp on the relevant side of the vehicle or the reciprocally incorporated part of it may be such that it is switched OFF during the entire period (both ON and OFF cycle) of activation of the direction indicator lamp.

6.8. Rear retro-reflector, non-triangular

6.8.1. Number

One or two, type-approved as Class IA or IB according to the 02 or subsequent series of amendments to UN Regulation No. 3, or to the 00 or subsequent series of amendments to UN Regulation No. 150.

6.8.2. Arrangement

No special requirement.

6.8.3. Position

In height: not less than 250 mm nor more than 900 mm above the ground;

6.8.4. Geometric visibility

Horizontal angle:	30° to left and to right for a single reflector; 30° outwards and 10° inwards for each pair of reflectors;
Vertical angle:	15° above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

6.8.5. Orientation

Rearwards.

6.9. Vehicle-hazard warning signal

6.9.1. The signal shall be given by simultaneous operation of the direction indicator lamps in accordance with the requirements of paragraph 6.3. above.

6.9.2. Electrical connections

The signal shall be given by means of a separate control enabling all the direction indicators to be supplied with current simultaneously. In addition, it may be activated automatically in the event of a vehicle being involved in a collision or after the de-activation of the emergency stop signal, as specified in paragraph 6.14. below. In such cases, it may be turned OFF manually.

In addition, the hazard warning signal may be switched ON automatically to indicate to other road-users the risk of imminent danger as defined by Regulations; in this case, the signal shall remain switched ON until it is manually or automatically switched OFF.

6.9.3. "Circuit-closed" tell-tale

Mandatory. Flashing red signal lamp or, in the case of separate tell-tales, the simultaneous operation of the tell-tale prescribed in paragraph 6.3.8.

6.9.4. Other requirements

Light flashing 90 ± 30 times per minute.

Operation of the lamp-signal control shall be followed within not more than one second by the appearance of the light and within not more than one-and-one-half seconds by the first extinction of the light.

6.10. Front fog lamp

6.10.1. Number

One or two, type-approved as Class “F3” according to the 03 or subsequent series of amendments to UN Regulation No. 19, or to the 00 or subsequent series of amendments to UN Regulation No. 149.

6.10.2. Arrangement

No special requirement.

6.10.3. Position

6.10.3.1. In width: for a single lamp the centre of reference shall be in the median longitudinal plane of the vehicle; or the edge of the illuminating surface which is nearest to that plane shall be not more than 250 mm away from it;

6.10.3.2. In height: not less than 250 mm above the ground. No point on the illuminating surface shall be higher than the highest point on the illuminating surface of the passing-beam headlamp.

6.10.3.3. In length: at the front of the vehicle. This requirement shall be deemed to be satisfied if the light emitted does not cause discomfort to the driver either directly, or indirectly through the rear-view mirrors and/or other reflecting surfaces of the vehicle.

6.10.4. Geometric visibility

Defined by angles α and β as specified in paragraph 2.13. of UN Regulation No. 48:

α = 5° upwards and downwards;

β = 45° to left and to right for a single lamp, except for an off- centre light, in which case the inward angle β = 10°;

β = 45° outwards and 10° inwards for each pair of lamps

6.10.5. Orientation

Forwards. The lamp(s) may move in line with the steering angle.

6.10.6. May not be combined with any other front lamp.

6.10.7. "Circuit-closed" tell-tale

Optional; non-flashing green signal.

6.10.8. Other requirements

None.

6.10.9. Electrical connections

It shall be possible to switch the fog lamp(s) on or off independently of the driving-beam headlamp(s) and/or passing-beam headlamp(s).

6.11. Rear fog lamp

6.11.1. Number

One or two, type-approved according to the 00 or subsequent series of amendments to UN Regulation Nos. 38 or 148.

6.11.2. Arrangement

No special requirement.

6.11.3. Position

6.11.3.1. In height: not less than 250 mm nor more than 900 mm above the ground;

6.11.3.2. In length at the rear of the vehicle.

6.11.3.3. The distance between the illuminating surface of the rear fog lamp and that of the stop lamp shall not be less than 100 mm.

6.11.4. Geometric visibility

Defined by angles α and β as specified in paragraph 2.13. of UN Regulation No. 48:

α = 5° upwards and downwards;

β = 25° to left and to right for a single lamp;

25° outwards and 10° inwards for each pair of lamps.

6.11.5. Orientation

Rearwards.

6.11.6. Electrical connections

They shall be such that the rear fog lamp can light up only when one or more of the following lamps are switched on: driving-beam headlamp, passing-beam headlamp, front fog lamp.

If there is a front fog lamp, it shall be possible to switch off the rear fog lamp independently of the front fog lamp.

The rear fog lamp(s) may continue to operate until the position lamps are switched off and they shall remain off until deliberately switched on again.

6.11.7. "Circuit-closed" tell-tale

Mandatory. Non-flashing amber signal lamp.

6.11.8. Other requirements

None.

6.12. Side retro-reflector, non-triangular

6.12.1. Number per side

One or two, type-approved as Class IA or IB according to the 02 or subsequent series of amendments to UN Regulation No. 3, or to the 00 or subsequent series of amendments to UN Regulation No. 150.

6.12.2. Arrangement

No special requirement.

6.12.3. Position

6.12.3.1. On the side of the vehicle.

6.12.3.2. In height: not less than 300 mm nor more than 900 mm above the ground;

6.12.3.3. In length: should be placed in such a position that under normal conditions it may not be masked by the driver's or passenger's clothes.

6.12.4. Geometric visibility

Horizontal angles $\beta = 30°$ to the front and to the rear.

Vertical angles $\alpha = 15°$ above and below the horizontal.

However, where a lamp is mounted below 750 mm (measured according to the provisions of paragraph 5.7.), the downward angle of 15° may be reduced to 5°.

6.12.5. Orientation

The reference axis of the retro-reflectors shall be perpendicular to the vehicle’s median longitudinal plane and directed outwards. The front side retro-reflectors may move with the steering angle.

6.13. Daytime running lamp

6.13.1. Presence

Optional for motorcycles.

6.13.2. Number

One or two, type-approved according to the 00 or subsequent series of amendments to UN Regulation Nos. 87 or 148.

6.13.3. Arrangement

No special requirement.

6.13.4. Position

6.13.4.1. In width:

6.13.4.1.1. An independent daytime running lamp may be installed above, below or to one side of another front lamp: If these lamps are one above the other, the reference centre of the daytime running lamp shall be located within the median longitudinal plane of the vehicle; if these lamps are side by side, the edge of the illuminating surface shall not be more than 250 mm from the median longitudinal plane of the vehicle.

6.13.4.1.2. A daytime running lamp, that is reciprocally incorporated with another front lamp (driving-beam headlamp or front position lamp), shall be fitted in such a way that the edge of the illuminated surface lies not more than 250 mm from the median longitudinal plane of the vehicle.

6.13.4.1.3. Two daytime running lamps, of which either one or both are reciprocally incorporated with another front lamp, shall be installed in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.13.4.1.4. In the case of two daytime running lamps, the distance separating the illuminating surfaces shall not exceed 420 mm.

6.13.4.1.5. The maximum separation distance is not applicable when the daytime running lamps:

(a) Are grouped, combined or reciprocally incorporated with another headlamp, or

(b) Are within the projection of the frontal silhouette of the motorcycle on an orthogonal plane perpendicular to the longitudinal median plane of the vehicle.

6.13.4.2. In height:

Above the ground not less than 250 mm and not more than 1,500 mm.

6.13.4.3. In length:

At the front of the vehicle.

6.13.5. Geometric visibility

Horizontal: Outwards 20° and inwards 10°.

Vertical: Upwards 10° and downwards 10°.

6.13.6. Orientation

Towards the front. The lamp(s) may move in line with the steering angle.

6.13.7. Electrical connections

6.13.7.1. The daytime running lamp shall switch OFF automatically when the headlamps are switched ON, except when the latter are used to give intermittent luminous warnings at short intervals.

The rear position lamp shall be switched ON when the daytime running lamp(s) is/are switched ON. The front position lamp(s) and the rear-registration-plate illuminating device may be switched ON individually or together, when the daytime running lamp(s) is/are switched ON.

6.13.7.2. If the distance between the front direction indicator lamp and the daytime running lamp is equal or less than 40 mm, the electrical connections of the daytime running lamp on the relevant side of the vehicle may be such that either:

(a) It is switched OFF; or

(b) Its luminous intensity is reduced during the entire period (both ON and OFF cycle) of activation of a front direction indicator lamp.

6.13.7.3. If a direction indicator lamp is reciprocally incorporated with a daytime running lamp, the electrical connections of the daytime running lamp on the relevant side of the vehicle shall be such that the daytime running lamp is switched OFF during the entire period (both ON and OFF cycle) of activation of the direction indicator lamp.

6.13.8. Tell-tale

Closed-circuit green tell-tale, optional.

6.13.9. Other requirements

The DRL symbol in ISO 2575:2004 - Road vehicles. Symbols for controls, indicators and tell-tales, may be used to inform the driver that the daytime running lamp is on.

6.14. Emergency stop signal

6.14.1. Presence

Optional.

The emergency stop signal shall be given by the simultaneous operation of all the stop or direction indicator lamps fitted as described in paragraph 6.14.7.

6.14.2. Number

As specified in paragraph 6.3.1. or 6.4.1.

6.14.3. Arrangement

As specified in paragraph 6.3.2. or 6.4.2.

6.14.4. Position

As specified in paragraph 6.3.3. or 6.4.3.

6.14.5. Geometric visibility

As specified in paragraph 6.3.4. or 6.4.4.

6.14.6. Orientation

As specified in paragraph 6.3.5. or 6.4.5.

6.14.7. Electrical connections

6.14.7.1. All the lamps of the emergency stop signal shall flash in phase at a frequency of 4.0 ± 1.0 Hz.

6.14.7.1.1. However, if any of the lamps of the emergency stop signal to the rear of the vehicle use filament light sources the frequency shall be 4.0 +0.0/-1.0 Hz.

6.14.7.2. The emergency stop signal shall operate independently of other lamps.

6.14.7.3. The emergency stop signal shall be activated and deactivated automatically.

6.14.7.3.1. The emergency stop signal shall be activated only when the vehicle speed is above 50 km/h and the braking system is providing the emergency braking logic signal defined in UN Regulation No. 78.

6.14.7.3.2. The emergency stop signal shall be automatically deactivated if the emergency braking logic signal as defined in UN Regulation No. 78 is no longer provided or if the vehicle-hazard warning signal is activated.

6.14.8. Tell-tale

Optional.

6.14.9. Other requirements

None.

6.15. Exterior courtesy lamp

6.15.1. Presence

Optional for motorcycles.

6.15.2. Number

One or two; however further exterior courtesy lamps to illuminate footrest are permitted. Each footrest shall be illuminated by not more than one lamp.

6.15.3. Arrangement

No special requirement, however the requirements of paragraph 6.15.9.3. apply.

6.15.4. Position

No special requirement.

6.15.5. Geometric visibility

No special requirement.

6.15.6. Orientation

No special requirement.

6.15.7. Electrical connections

No special requirement.

6.15.8. Tell-tale

No special requirement.

6.15.9. Other requirements

6.15.9.1. The exterior courtesy lamp shall not be activated unless the vehicle is stationary and one or more of the following conditions is satisfied:

(a) The device which starts and/or stops the engine (propulsion system) is set in a position which makes it impossible for the engine (propulsion system) to operate; or

(b) A load compartment is opened for access.

The provisions of paragraph 5.9. shall be met in all fixed positions of use.

6.15.9.2. Approved lamps emitting white light with the exception of main beam headlamps and day time running lamps may be activated as courtesy lamp function. They may also be activated together with the exterior courtesy lamps and the condition of paragraphs 5.10. and 5.11. above may not apply.

6.15.9.3. The technical service shall, to the satisfaction of the Type Approval Authority, perform a visual test to verify that there is no direct visibility of the apparent surface of the exterior courtesy lamps, if viewed by an observer moving on the boundary of a zone on a transverse plane 10 m from the front of the vehicle, a transverse plane 10 m from the rear of the vehicle, and two longitudinal planes 10 m from each side of the vehicle; these four planes to extend from 1 m to 3 m above and perpendicular to the ground as shown in Annex 7.

In addition to the conditions described in paragraph 5.4., the requirements prescribed above shall be verified in the following vehicle conditions:

Stand: On a prop stand or a centre stand, and both if applicable

Steering: Straight ahead, and locked in each available position

At the request of the applicant and with the consent of the Technical Service this requirement may be verified by a drawing or simulation.

6.16. Adaptive Driving-Beam (ADB) (UN Regulation No. 149)

Where not otherwise specified below, the requirements for driving-beam headlamp(s) (paragraph 6.1.) of this Regulation apply to the ADB.

6.16.1. Number

6.16.1.1. One, type-approved as adaptive driving-beam (ADB) for vehicles of category L3 according to the 01 or subsequent series to UN Regulation No. 149.

6.16.1.2. Installation units shall be one or two.

6.16.2. Arrangement

No special requirements.

6.16.3. Position

The ADB shall, prior to the subsequent test procedures, be set to the ADB neutral state;

6.16.3.1. In width and height:

All dimensions refer to the nearest edge of the apparent surface(s) observed in the direction of the reference axis, of the installation unit(s).

6.16.3.1.1. An independent ADB installation unit may be fitted above or below or to one side of another front lamp: if these lamps are on top of the other the reference centre of the ADB installation unit must be located within the median longitudinal plane of the vehicle; if these lamps are side by side their reference centre must be symmetrical in relation to the median longitudinal plane of the vehicle.

6.16.3.1.2. An ADB installation unit, that is reciprocally incorporated with another front lamp, must be fitted in such a way that its reference centre lies within the median longitudinal plane of the vehicle. However, when the vehicle is also fitted with an independent principal passing-beam headlamp, or a principal passing-beam headlamp that is reciprocally incorporated with a front position lamp alongside the ADB installation unit, their reference centres must be symmetrical in relation to the median longitudinal plane of the vehicle.

6.16.3.1.3. Two ADB installation units of which either one or both are reciprocally incorporated with another front lamp must be fitted in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.16.3.2. In length: at the front of the vehicle. This requirement is regarded as satisfied if the light emitted does not cause discomfort to the driver either directly or indirectly by means of the rear-view mirrors and/or reflective surfaces on the vehicle.

6.16.3.3. In any case, the distance between the edge of the illuminating surface of any independent ADB installation unit and the edge of that of the lamp producing the principal passing-beam must not exceed 200 mm. The distance between the edge of the illuminating surface of any independent ADB installation unit and the ground must be from 500 mm to 1,300 mm.

6.16.3.4. In the case of two ADB installation units: the distance separating the illuminating surfaces of two ADB installation units must not exceed 200 mm.

6.16.4. Geometric visibility

The angles of geometric visibility specified in paragraph 6.1.4. of this Regulation, shall be met by at least one of the installation units said function, according to the description of the applicant. Individual installation units may be used to comply with the requirements for different angles.

6.16.5. Orientation

Towards the front.

6.16.5.1. The vertical inclination of the center of the area of maximum illumination of ADB shall remain between ± 0.5 per cent, except in the case where an external adjusting device is present.

In case ADB is adjusted together with the passing-beam(s), this provision shall not apply.

6.16.6. Electrical connections

6.16.6.1. For changing over from the ADB to the passing-beam all lighting units for the driving-beam shall be de-activated simultaneously.

6.16.6.2. The ADB shall be designed to be adaptive, subject to the provisions in paragraph 6.16.8.1., the control signals being produced by a sensor system which is capable of detecting and reacting to each of the following inputs:

(a) Ambient lighting conditions;

(b) The light emitted by the front lighting devices and front light-signalling devices of oncoming vehicles;

(c) The light emitted by the rear light-signalling of preceding vehicles;

Additional sensor functions to improve performance are allowed.

For the purpose of this paragraph, "vehicles" means vehicles of categories L, M, N, O, T, as well as bicycles, such vehicles being equipped with retro-reflectors, with lighting and light-signalling devices, which are switched ON.

6.16.6.3. It shall always be possible to activate and deactivate the ADB manually, and to manually deactivate the automatic control.

Moreover, the deactivation, of the ADB and of their automatic control, shall be by means of a simple and immediate manual operation; the use of sub-menus is not allowed.

6.16.6.4. The passing-beam(s) may remain switched ON at the same time as the ADB.

6.16.6.5. It shall always be possible for the driver to set the ADB to the ADB neutral state and to return it to its automatic operation.

6.16.7. Tell-tale:

6.16.7.1. The provisions of paragraphs 6.1.7. (for the driving-beam headlamp(s)) of this Regulation apply to the respective parts of an ADB.

6.16.7.2. A visual failure tell-tale for ADB is mandatory. It shall be non-flashing. It shall be activated whenever a failure signal is received in accordance with paragraph 4.13. of UN Regulation No. 149. It shall remain activated while the failure is present. It may be cancelled temporarily, but shall be repeated whenever the device which starts and stops the engine is switched ON and OFF.

6.16.7.3. A visual tell-tale shall be provided to indicate to the driver that the adaptation of the driving-beam is activated. This information shall remain displayed as long as the adaptation is activated.

6.16.8. Other requirements

6.16.8.1. Adaptation of the driving-beam

6.16.8.1.1. The sensor system used to control the adaptation of the driving-beam, as described in paragraph 6.16.6.2. above, shall comply with the following requirements:

6.16.8.1.1.1. The boundaries of the minimum fields in which the sensor is able to detect light emitted from other vehicles as defined in paragraph 6.16.6.2. above are given by the angles indicated in paragraph 6.1.8.3.1.1. of this Regulation.

6.16.8.1.1.2. The sensor system sensitivity shall comply with the requirements in paragraph 6.1.8.3.1.2. of this Regulation.

6.16.8.1.1.3. The adaptive driving-beam shall be switched OFF when the illuminance produced by ambient lighting conditions exceeds 7,000 lx.

Compliance with this requirement shall be demonstrated by the applicant, using simulation or other means of verification accepted by the Type Approval Authority. If necessary, the illuminance shall be measured on a horizontal surface, with a cosine corrected sensor on the same height as the mounting position of the sensor on the

vehicle. This may be demonstrated by the manufacturer by sufficient documentation or by other means accepted by the Type Approval Authority.

6.16.8.1.1.4. The overall performance of the automatic control shall be demonstrated by the applicant by documentation or by other means accepted by the Type Approval Authority. Furthermore, the manufacturer shall provide a documentation package which gives access to the design of "the safety concept" of the system. This "safety concept" is a description of the measures designed into the system, for example within the electronic units, so as to address system integrity and thereby ensure safe operation even in the event of mechanical or electrical failure which could cause any discomfort, distraction or glare, either to the driver or to oncoming and preceding vehicles. This description shall also give a simple explanation of all the control functions of the "system" and the methods employed to achieve the objectives, including a statement of the mechanism(s) by which control is exercised. The “safety concept” shall describe the measures taken to ensure that failure mode is triggered if any external agent (e.g. caused by dirt) obscures the sensor input.

A list of all input and sensed variables shall be provided and the working range of these shall be defined.

The functions of the system and the safety concept, as laid down by the manufacturer, shall be explained. The documentation shall be brief, yet provide evidence that the design and development has had the benefit of expertise from all the system fields which are involved.

For periodic technical inspections, the documentation shall describe how the current operational status of the "system" can be checked.

For Type Approval purposes this documentation shall be taken as the basic reference for the verification process.

6.16.8.1.1.5. To verify, that the adaptation of the driving-beam does not cause any discomfort, distraction or glare, neither to the driver nor to oncoming and preceding vehicles, the technical service shall perform a test drive according to paragraph 2. in Annex 9. This shall include any situation relevant to the system control on the basis of the applicant's description. The performance of the adaptation of the driving-beam shall be documented and checked against the applicant's description. Any obvious malfunctioning shall be contested (e.g. excessive angular movement or flicker).

6.16.8.2. The aggregate maximum intensity of the lighting units that can be energized simultaneously to provide the driving-beam lighting or its modes, if any, shall not exceed 430,000 cd, which corresponds to a reference value of 100.

This maximum intensity shall be obtained by adding together the individual reference marks indicated on the installation units that are simultaneously used to provide the driving-beam.

6.17. Rear-end collision alert signal

6.17.1. Presence

Optional.

The rear-end collision alert signal shall be given by the simultaneous operation of all the direction indicator lamps fitted as described in paragraph 6.17.7.

6.17.2. Number

As specified in paragraph 6.3.1.

6.17.3. Arrangement

As specified in paragraph 6.3.2.

6.17.4. Position

As specified in paragraph 6.3.3.

6.17.5. Geometric visibility

As specified in paragraph 6.3.4.

6.17.6. Orientation

As specified in paragraph 6.3.5.

6.17.7. Electrical connections

Compliance with these requirements shall be demonstrated by the applicant, by simulation or other means of verification accepted by the Technical Service responsible for type approval.

6.17.7.1. All the lamps of the rear-end collision alert signal shall flash in phase at a frequency of 4.0 +/- 1.0 Hz.

6.17.7.1.1. However, if any of the lamps of the rear-end collision alert signal to the rear of the vehicle use filament light sources the frequency shall be 4.0 +0.0/-1.0 Hz.

6.17.7.2. The rear-end collision alert signal shall operate independently of other lamps.

6.17.7.3. The rear-end collision alert signal shall be switched ON and OFF automatically.

6.17.7.4. The rear-end collision alert signal shall not be switched ON if the direction indicator lamps, the hazard warning signal or the emergency stop signal is activated.

6.17.7.5. The rear-end collision alert signal may only be switched ON under the following conditions:

Vr	*Activation*
Vr > 30 km/h	TTC ≤ 1.4
Vr ≤ 30 km/h	TTC ≤ 1.4 / 30 x Vr

"Vr (Relative Speed)": means the difference in speed between a vehicle with rear-end collision alert signal and a following vehicle in the same lane.

"TTC (Time to collision)": means the estimated time for a vehicle with rear-end collision alert signal and a following vehicle to collide assuming the relative speed at the time of estimation remains constant.

6.17.7.6. The switch ON period of the rear-end collision alert signal shall be not more than 3 seconds.

6.17.8. Tell-tale

Optional.

6.18. Adaptive front lighting system (AFS)

Where not otherwise specified below, the requirements for the passing-beam headlamps (paragraph 6.2.) of this Regulation apply to the relevant part of the AFS.

6.18.1. Presence

Optional

6.18.2. Number

One.

6.18.3. Arrangement

No special requirements

6.18.4. Position

The AFS shall, prior to the subsequent test procedures, be set to the neutral state;

6.18.4.1. In width and height:

6.18.4.1.1. An independent AFS installation unit may be installed above, below or to one side of another front lamp: if these lamps are one above the other the reference centre of the AFS installation unit shall be located

within the median longitudinal plane of the vehicle; if these lamps are side by side their reference centre shall be symmetrical in relation to the median longitudinal plane of the vehicle.

6.18.4.1.2. An AFS installation unit that is reciprocally incorporated with another front lamp, shall be fitted in such a way that its reference centre lies within the median longitudinal plane of the vehicle. However, when the vehicle is also fitted with an independent driving beam headlamp, or a driving-beam headlamp that is reciprocally incorporated with a front position lamp alongside the AFS installation unit, their reference centre shall be symmetrical in relation to the median longitudinal plane of the vehicle.

6.18.4.1.3. Two AFS installation units, of which either one or both are reciprocally incorporated with another front lamp shall be installed in such a way that their reference centres are symmetrical in relation to the median longitudinal plane of the vehicle.

6.18.4.1.4. If installed, additional lighting unit(s) which provide bend lighting, type approved as part of the AFS according to UN Regulation No. 149, shall be installed under the following conditions:

In the case of (a) pair(s) of additional lighting units, they shall be installed so that their reference centre(s) are symmetrical in relation to the median longitudinal plane of the vehicle.

In the case of a single additional lighting unit, its reference centre shall be coincident with the median longitudinal plane of the vehicle.

6.18.4.1.5. Height: a minimum of 500 mm and a maximum of 1,200 mm above the ground.

6.18.4.1.6. In length: at the front of the vehicle. This requirement is regarded as satisfied if the light emitted does not cause discomfort to the driver either directly or indirectly by means of the rear-view mirrors and/or reflective surfaces of the vehicle.

6.18.4.1.7. In the case of two AFS installation units: the distance separating the illuminating surfaces of two AFS installation units must not exceed 200 mm.

6.18.5. Geometric visibility

For each lighting function and mode provided:

The angles of geometric visibility prescribed for the respective lighting functions according to paragraph 6.2.4. of this Regulation, shall be met by at least one lighting unit that is energized to perform said function and mode(s), according to the description of the applicant. Individual lighting units may be used to comply with the requirements for different angles.

6.18.5.1. Vertical orientation:

the vertical inclination of the headlamp shall be set according the procedure described in the paragraphs 6.2.5.1. through 6.2.5.4. of this Regulation.

6.18.5.2. Headlamp levelling system

6.18.5.2.1. In the case where a headlamp levelling device is necessary to satisfy the requirements of paragraph 6.18.5.1., the device shall be automatic.

6.18.5.2.2. In the event of a failure of this device, the passing beam shall not assume a position in which the dip is less than it was at the time when the failure of the device occurred.

6.18.5.2.3. Measuring procedure:

After adjustment of the initial setting of beam orientation, the vertical inclination of the passing beam or, when applicable, the vertical inclination of all different lighting units that provide or contribute to the cut-off(s) of the basic passing beam according to paragraph 6.18.5.1. above, shall be verified for all loading conditions of the vehicle in accordance with the specifications in paragraphs 6.2.5.1. to 6.2.5.4. of this regulation.

6.18.5.3. An HIAS may be installed for the AFS. In this case the requirements as specified in paragraph 6.2.5.5. and 6.2.5.6. of this Regulation shall be fulfilled.

6.18.5.4. Additional lighting unit(s) may be activated in conjunction with the AFS. In this case the requirement as specified in paragraph 6.2.5.7. and 6.2.5.8. of this Regulation shall be fulfilled.

6.18.6. Electrical connections

6.18.6.1. Passing-beam lighting:

(a) The control for changing over to the passing beam shall switch OFF all main-beam headlamps simultaneously;

(b) The passing beam may remain switched ON at the same time as the main-beams;

(c) In the case of lighting units for the passing beam being discharge light sources, the gas discharge light sources shall remain switched ON during the main-beam operation.

6.18.6.2. The passing-beam headlamps switching ON and OFF shall fulfil the requirements for “Electrical connection” in paragraph 5.10. and 6.2.6. of this Regulation.

6.18.6.3. Automatic operation of the AFS

The changes within and between the provided classes and their modes of the AFS lighting functions as specified below, shall be performed automatically without causing discomfort, distraction or glare, neither for the driver nor for the other road users.

The following conditions apply for the activation of the classes and their modes of the passing beam and, where applicable, of the main-beam and/or the adaptation of the main-beam.

6.18.6.3.1. The class C mode(s) of the passing beam shall be activated if no mode of another passing beam class is activated.

6.18.6.3.2. The class V mode(s) of the passing beam shall not operate unless one or more of the following conditions is/are automatically detected (V-signal applies):

(a) Roads in built-up areas and the vehicle’s speed not exceeding 60 km/h;

(b) Roads equipped with a fixed illumination, and the vehicle’s speed not exceeding 60 km/h;

(c) A road surface illumination of 1 cd/m^2 and/or a horizontal road illumination of 10 lx being exceeded continuously;

(d) The vehicle’s speed not exceeding 50 km/h.

6.18.6.3.3. The class E mode(s) of the passing beam shall not operate unless the vehicle’s speed exceed 60 km/h and one or more of the following conditions is /are automatically detected:

(a) The road characteristics correspond to motorway conditions ([1]) or the vehicle’s speed exceeds 110 km/h (E-signal applies);

(b) In case of a class E mode of the passing beam which, according to the system’s approval documents / communication sheet, complies with a “data set” of UN Regulation No. 149, Table 12 only.

Data set E1: The vehicle’s speed exceeds 100 km/h (E1-signal applies);

Data set E2: The vehicle’s speed exceeds 90 km/h (E2-signal applies);

Data set E3: The vehicle’s speed exceeds 80 km/h (E3-signal applies).

[1] Traffic direction being separated by means of road construction, or, a corresponding lateral distance of opposing traffic is identified. This implies a reduction of undue glare from vehicles headlamp in opposing traffic.

6.18.6.3.4. The class W-mode(s) of the passing beam shall not operate unless the front fog lamp, if any, are switched OFF and the wetness of the road has been automatically detected (W-signal applies).

6.18.6.4. It shall always be possible for the driver to set the AFS to the neutral state and to return it to its automatic operation.

6.18.7. Tell-tale:

6.18.7.1. The provision of paragraphs 6.2.7. (for the passing-beam headlamp) of this Regulation apply to the respective parts of an AFS.

6.18.7.2. A visual failure tell-tale for AFS is mandatory. It shall be non-flashing. It shall be activated whenever a failure is detected with respect to the AFS control signals or when a failure signal is received in accordance with paragraph 4.13. of UN Regulation No. 149. It shall remain activated while the failure is present. It may be cancelled temporarily but shall be repeated whenever the device which starts and stop the propulsion system is switched ON and OFF.

6.18.8. Other requirements

6.18.8.1. Verification of compliance with AFS automatic operation requirements

6.18.8.1.1. The applicant shall demonstrate with *a concise description* or other means acceptable to the Type Approval Authority:

(a) The correspondence of the AFS control signals

(i) To the description required in paragraph 3.2.8. of this Regulation; and

(ii) To the respective AFS control signals specified in the AFS type approval documents; and

(b) Compliance with the automatic operating requirements according to paragraph 6.18.6.3.1. through 6.18.6.3.4. above.

6.18.8.1.2. To verify, whether, according to the paragraph 6.18.6.3., the AFS automatic operation of the passing-beam functions does not cause any discomfort, the technical service shall perform a test drive which comprises any situation relevant to the system control on the basis of the applicants description; it shall be notified whether all modes are activated, performing and de-activated according to the applicant's description; obvious malfunctioning, if any, shall be contested (e.g. excessive angular movement or flicker).

6.18.8.1.3. The overall performance of the automatic control shall be demonstrated by the applicant by documentation or by other means acceptable by the Type Approval Authority. Furthermore, the manufacturer shall provide a documentation package which gives access to the design of "safety concept" of the system. This "safety concept" is a description of the measures designed into the system, for example within the electronic units, so as to address system integrity and thereby ensure safe operation even in the event of mechanical or electrical failure which could cause any discomfort, distraction or glare, either to the driver or to oncoming and preceding vehicles. This description shall also give a simple explanation of all the control functions of the "system" and the methods employed to achieve the objectives, including a statement of the mechanism(s) by which control is exercised.

A list of all input and sensed variables shall be provided and the working range of these shall be defined. The possibility of a fallback to the basic passing beam (class C) function shall be a part of the safety concept.

The function of the system and the safety concept, as laid down by the manufacturer, shall be explained. The documentation shall be brief, yet provide evidence that the design and development has had the benefit of expertise from all the system fields which are involved.

For periodic technical inspections, the documentation shall describe how the current operational status of the "system" can be checked.

For type approval purposes this documentation shall be taken as the basis reference for the verification process.

7. Modifications of the vehicle type or of the installation of its lighting and light-signalling devices

7.1. Every modification of the vehicle type, or of the installation of its lighting or light-signalling devices, or of the list referred to in paragraph 3.2.2. above, shall be notified to the Type Approval Authority which approved that vehicle type. The Type Approval Authority may then either;

7.1.1. Consider that the modification made are unlikely to have appreciable adverse effects and that in any case the vehicle still complies with the requirements; or

7.1.2. Require a further test report from the Technical Service responsible for conducting tests.

7.2. Confirmation or refusal of approval, specifying the alternatives, shall be communicated by the procedure specified in paragraph 4.3. above to the Parties to the Agreement which apply this Regulation.

7.3. The Type Approval Authority issuing the extension of approval shall assign a series number for such an extension and inform thereof the other Parties to the 1958 Agreement applying this Regulation by means of a communication form conforming to the model in Annex 1 to this Regulation.

8. Conformity of production

The conformity of production procedures shall comply with those set out in the Agreement, Schedule 1 (E/ECE/TRANS/505/Rev.3), with the following requirements:

8.1. Motorcycles approved under this Regulation shall be so manufactured as to conform to the type approved, by meeting the requirements set out in paragraphs 5. and 6. above.

8.2. The minimum requirements for conformity of production control procedures set forth in Annex 5 to this Regulation shall be complied with.

8.3. The Type Approval Authority which has granted type approval may at any time verify the conformity control methods applied in each production facility. The normal frequency of these verifications shall be once a year.

9. Penalties for non-conformity of production

9.1. The approval granted in respect of a vehicle type pursuant to this Regulation may be withdrawn if the requirement laid down in paragraph 8.1. above is not met or if the vehicle has failed to pass the checks prescribed in paragraph 8. above.

9.2. If a Party to the Agreement which applies this Regulation withdraws an approval it has previously granted, it shall forthwith so notify the other Contracting Parties to the Agreement which apply this Regulation by means of a communication form conforming to the model in Annex 1 to this Regulation.

10. Production definitively discontinued

If the holder of an approval completely ceases to manufacture a vehicle type approved in accordance with this Regulation, he shall so inform the Type Approval Authority which granted the approval. Upon receiving the relevant communication that Authority shall inform thereof the other Parties to the Agreement applying this Regulation, by means of a communication form conforming to the model in Annex 1 to this Regulation.

11. Transitional provisions

11.1. As from the official date of entry into force of Supplement 10 to the 01 series of amendments, no Contracting Party applying this Regulation shall refuse to grant approvals under this Regulation as amended by Supplement 10 to the 01 series of amendments.

11.2. As from 60 months after the date of entry into force mentioned in paragraph 11.1. above, Contracting Parties applying this Regulation shall grant approvals only if the vehicle type with regard to the number and mode of installation of the lighting and light-signalling devices corresponds to the requirements of the Supplement 10 to the 01 series of amendments to this Regulation.

11.3. Existing approvals granted under this Regulation before the date mentioned in paragraph 11.2. above shall remain valid. In the case of vehicles first registered more than 84 months after the date of entry into force mentioned in paragraph 11.1. above Contracting Parties applying this Regulation may refuse the vehicle type with regard to the number and mode of installation of the lighting and light-signalling devices which do not meet the requirements of the Supplement 10 to the 01 series of amendments to this Regulation.

11.4. As from the official date of entry into force of the 02 series of amendments, no Contracting Party applying this Regulation shall refuse to grant approvals under this Regulation as amended by the 02 series of amendments.

11.5. As from 48 months after the date mentioned in paragraph 11.4. above, Contracting Parties applying this Regulation shall grant approvals only if the vehicle type with regard to the number and mode of installation of the lighting and light-signalling devices corresponds to the requirements of the 02 series of amendments to this Regulation.

11.6. Existing approvals granted under this Regulation before the date mentioned in paragraph 11.5. above shall remain valid.

11.7. As from the official date of entry into force of the 03 series of amendments, no Contracting Party applying this UN Regulation shall refuse to grant or refuse to accept UN type approvals under this UN Regulation as amended by the 03 series of amendments.

11.8. As from 1 September 2023, Contracting Parties applying this UN Regulation shall not be obliged to accept UN type approvals to the preceding series of amendments, first issued after 1 September 2023.

11.9. Notwithstanding the transitional provisions above, Contracting Parties who start to apply this UN Regulation after the date of entry into force of the most recent series of amendments are not obliged to accept UN type-approvals which were granted in accordance with any of the preceding series of amendments to this UN Regulation.

11.10. Notwithstanding paragraph 11.8., Contracting Parties applying this UN Regulation shall continue to accept UN type approvals to the preceding series of amendments to this UN Regulation, first issued after 1 September 2023 and extension thereof, for the vehicles which are not affected by the changes introduced by the 03 series of amendments.

11.11. Contracting Parties applying this UN Regulation shall not refuse to grant UN type approvals according to any preceding series of amendments to this UN Regulation or extensions thereof.

11.12. Transitional provisions applicable to the 04 series of amendments

11.12.1. As from the official date of entry into force of the 04 series of amendments, no Contracting Party applying this Regulation shall refuse to grant or refuse to accept type approvals under this Regulation as amended by the 04 series of amendments.

11.12.2. As from 1 September 2028, Contracting Parties applying this Regulation shall not be obliged to accept type approvals to the preceding series of amendments, first issued after 1 September 2028.

11.12.3. Until 1 September 2030, Contracting Parties applying this Regulation shall accept type approvals to the preceding series of amendments, first issued before 1 September 2028.

11.12.4. As from 1 September 2030, Contracting Parties applying this Regulation shall not be obliged to accept type approvals, and extensions thereof, issued to the preceding series of amendments to this Regulation.

11.12.5. Notwithstanding the transitional provisions above, Contracting Parties who start to apply this Regulation after the date of entry into force of the most recent series of amendments are not obliged to accept type approvals which were granted in accordance with any of the preceding series of amendments to this Regulation.

11.12.6. Notwithstanding paragraph 11.12.4., Contracting Parties applying this Regulation shall continue to accept type approvals to the preceding series of amendments to this Regulation and extension thereof, for the vehicles which are not affected by the changes introduced by the 04 series of amendments.

11.12.7. Contracting Parties applying this Regulation may grant type approvals according to any preceding series of amendments to this Regulation.


11.12.8. Contracting Parties applying this Regulation shall continue to grant extensions of existing approvals to any preceding series of amendments to this Regulation.

12. Names and addresses of Technical Services responsible for conducting approval tests, and of Type Approval Authorities

The Contracting Parties to the 1958 Agreement which apply this Regulation shall communicate to the United Nations Secretary-General the names and addresses of the Technical Services responsible for conducting approval tests and of the Type Approval Authorities which grant approval and to which forms certifying approval, extension or refusal or withdrawal of approval, issued, in other countries, are to be sent.

Annex 1 Communication

(maximum format: A4 (210 x 297 mm))



issued by: Name of administration:

.....

.....

.....

Concerning:[2] Approval granted

Approval extended

Approval refused

Approval withdrawn

Production definitively discontinued

of a type of category L_3 vehicle with regard to the installation of lighting and light-signalling devices, pursuant to UN Regulation No. 53.

Approval No. …….. Extension No. ……...

[1] Distinguishing number of the country which has granted/extended/refused/withdrawn approval (see approval provisions in the Regulation).

[2] Strike out what does not apply.

1. Trade name or mark of the vehicle: .....

2. Manufacturer's name for the type of vehicle: .....

3. Manufacturer's name and address: .....

4. If applicable, name and address of the manufacturer's representative: .....

5. Submitted for approval on: .....

6. Technical Service responsible for conducting approval tests: .....

7. Date of test report: .....

8. Number of test report: .....

9. Concise description: .....

Lighting devices on the vehicle:

9.1. Driving lamps: yes/no[2] .....

[2] Strike out what does not apply.

9.2. Passing lamps: yes/no[2]

[2] Strike out what does not apply.

9.3. Front fog lamps: yes/no[2]

[2] Strike out what does not apply.

9.4. -

9.5. Direction indicators: yes/no[2]

[2] Strike out what does not apply.

9.6. -

9.7. Repeating side direction indicators: yes/no[2]

[2] Strike out what does not apply.

9.8. Hazard warning signal: yes/no[2]

[2] Strike out what does not apply.

9.9. Stop lamps: yes/no[2]

[2] Strike out what does not apply.

9.10. Rear-registration-plate illuminating device: yes/no[2]

[2] Strike out what does not apply.

9.11. Front position (side) lamps: yes/no[2]

[2] Strike out what does not apply.

9.12. Rear position (side) lamps: yes/no[2]

[2] Strike out what does not apply.

9.13. Rear fog lamps: yes/no[2]

[2] Strike out what does not apply.

9.14. -

9.15. -

9.16. Rear retro-reflectors, non-triangular: yes/no[2]

[2] Strike out what does not apply.

9.17. -

9.18. -

9.19. Side retro-reflectors, non-triangular: yes/no[2]

[2] Strike out what does not apply.

9.20. Equivalent lamps: yes/no[2]

[2] Strike out what does not apply.

9.21. Emergency stop signal: yes/no[2]

[2] Strike out what does not apply.

9.22. Exterior courtesy lamp: yes/no[2]

[2] Strike out what does not apply.

9.23. Lamps approved for and equipped with LED substitute light source(s) are allowed to be installed on this vehicle type: yes/no[2, 4]

[2] Strike out what does not apply.

[4] If yes, list the applicable lamps.

10. Any comments: .....

11. Masses as declared by the manufacturer[3]

[3] These sections only need to be completed if the test according to paragraph 6.2.5.4. of this Regulation is performed.

11.1. Mass in running order:

Total mass: ..... kg

Mass on the front wheel: ..... kg

Mass on the rear wheel: ..... kg

11.2. Gross vehicle mass:

Total mass: ..... kg

Mass on the front wheel: ..... kg

Mass on the rear wheel: ..... kg

12. Position of the approval mark: .....

13. Reason(s) for extension (if applicable):

14. Approval granted/refused/extended/withdrawn:[2]

[2] Strike out what does not apply.

15. Place: .....

16. Date: .....


17. Signature: .....

18. The list of documents deposited with the Type Approval Authority which has granted the approval is annexed to this communication and may be obtained upon request.

Annex 2 Arrangement of approval marks

Model A

(see paragraph 4.4. of this Regulation)




a = 8 mm min

The above approval mark affixed to a motorcycle shows that the vehicle type concerned has, with regard to the installation of lighting and light-signalling devices, been approved in the Netherlands (E 4), pursuant to UN Regulation No. 53, as amended by the 03 series of amendments. The approval number indicates that the approval was granted in accordance with the requirements of UN Regulation No. 53.

Model B

(see paragraph 4.5. of this Regulation)




a = 8 mm min

The above approval mark affixed to a motorcycle shows that the vehicle type concerned has been approved in the Netherlands (E 4) pursuant to Regulations Nos. 53 and 78.[1] The approval numbers indicate that, at the dates when the respective approvals were granted, UN Regulation No. 53 included the 03 series of amendments and UN Regulation No. 78 already included the 04 series of amendments.

[1] The second number is given merely as an example.

Annex 3 Lamp surfaces, axis and centre of reference, and angles of geometric visibility



Key


1. Illuminating surface
2. Axis of reference
3. Centre of reference
4. Angle of geometric visibility
5. Light-emitting surface
6. Apparent surface based on illuminating surface
7. Apparent surface based on light-emitting surface
8. Direction of visibility

Note: Notwithstanding the drawing, the apparent surface is to be considered as tangent to the light-emitting surface.


Illuminating surface in comparison with light-emitting surface

Sketch A

(See paragraphs 2.9. and 2.8. of this Regulation)



Sketch B



	Illuminating surface	*Light-emitting surface*
Edges are	a and b	c and d

Annex 4 Forward visibility of red lights and rearward visibility of white lights

(See paragraph 5.9. of this Regulation)

Figure 1 **Forward visibility of a red lamp**





Figure 2 **Rearward visibility of a white lamp**



Annex 5 Control of conformity of production

1. Tests

1.1. Position of lamps

The position of the lamps as specified in paragraph 6. of this Regulation shall be checked in accordance with the general requirements set out in paragraph 5. of this Regulation. The values measured for the distances shall be such that the individual specifications applicable to each lamp are fulfilled.

1.2. Visibility of lamps

1.2.1. The angles of geometric visibility shall be checked in accordance with paragraph 2.13. of UN Regulation No. 48. The values measured for the angles shall be such that the individual specifications applicable to each lamp are fulfilled except that the limits of the angles may have an allowance corresponding to the ±3° variation permitted in paragraph 5.3. of this Regulation for the mounting of the light-signalling devices.

1.2.2. The visibility of red light towards the front and of white light towards the rear shall be checked in accordance with paragraph 5.9. of this Regulation.

1.3. Alignment of passing-beam headlamps towards the front

1.3.1. Initial downward inclination

(The initial downward inclination of the cut-off of the passing-beam shall be checked against the requirements of paragraph 6.2.5. of this Regulation).

1.4. Electrical connections and tell-tales

The electrical connections shall be checked by switching on every lamp supplied by the electrical system of the motorcycle.

The lamps and tell-tales shall function in accordance with the provisions set out in paragraphs 5.10. to 5.12. of this Regulation and with the individual specifications, applicable to each lamp.

1.5. Light intensities


1.5.1. Driving-beam headlamps

The aggregate maximum intensity of the driving-beam headlamp(s) shall be such that the requirement in paragraph 6.1.9. of this Regulation is fulfilled.

1.6. The presence, number, colour, arrangement and, where applicable, the category of lamps shall be checked by visual inspection of the lamps and their markings. These shall be such that the requirements set out in paragraph 5.13. of this Regulation and the individual specifications applicable to each lamp are fulfilled.

Annex 6 Explanation about "the horizontal inclination", "the bank angle" and the angle "δ"

Figure 1




Note: This figure shows the motorcycle is banked to the right side.

Annex 7 Observing area towards the apparent surface of exterior courtesy lamps

Zones of observation

This drawing shows the zone from one side, the other zones are from the front, the rear and from the other side of the vehicle.



Annex 8 Ambient light related automatic switching conditions for passing beam

Automatic switching conditions for passing beam[1]		
Ambient light outside the vehicle[2]	Headlamps requirement	Response time for switching
less than 1,000 lux	ON	no more than 2 seconds
1,000 lux and more than 1,000 lux	at manufacturer's discretion	at manufacturer's discretion

[1] Compliance with these conditions shall be demonstrated by the applicant, by simulation or other means of verification accepted by the Type Approval Authority.

[2] The illuminance shall be measured on a horizontal surface, with a cosine corrected sensor on the same height as the mounting position of the sensor on the vehicle. This may be demonstrated by the manufacturer by sufficient documentation or by other means accepted by the Type Approval Authority.

Annex 9 Test drive

1. Test drive specifications for the automatic control of the driving-beam headlamp(s).

1.1. The test drive shall be carried out in clear atmosphere[1] and with clean headlamp(s).

[1] Good visibility (meteorological optical range MOR > 2,000 m defined according to WMO, Guide to Meteorological Instruments and Methods of Observation, Sixth Edition, ISBN: 92-63-16008-2, pp 1. 9. 1/ 1. 9. 11, Geneva 1996).

1.2. The test course shall comprise test sections with traffic conditions, at speed corresponding to the relevant type of road, as described in Table 1 below:

Table 1

Test Section	*Traffic conditions*	*Road type*

		Urban areas	*Multi-lane road, e.g. motorway*	*Country road*
	Speed	*50 ± 10 km/h*	*100 ± 20 km/h*	*80 ± 20 km/h*
	Average percentage of the full test course length	*10 per cent*	*20 per cent*	*70 per cent*
A	Single oncoming vehicle or single preceding vehicle in a frequency so that the driving-beam will switch ON and OFF.		X	X
B	Combined oncoming and preceding traffic situations, in a frequency so that the driving-beam will switch ON and OFF.		X	X
C	Active and passive overtaking manoeuvres, in a frequency so that the driving-beam will switch ON and OFF.		X	X
D	Oncoming bicycle, as described in paragraph 6.1.8.3.1.2.			X
E	Combined oncoming and preceding traffic situations	X		

1.3. Urban areas shall comprise roads with and without illumination.

1.4. Country roads shall comprise sections having two lanes and sections having four or more lanes and shall include junctions, hills and/or slopes, dips and winding roads.

1.5. Multi-lane roads (e.g. motorways) and country roads shall comprise sections having straight level parts with a length of more than 600 m. Additionally they shall comprise sections having curves to the left and to the right.

1.6. Dense traffic situations shall be taken into account.

2. Test drive specifications for adaptive driving-beam headlamp(s)

2.1. The test drive shall be carried out in clear atmosphere[1] and with clean headlamp(s).

[1] Good visibility (meteorological optical range MOR > 2,000 m defined according to WMO, Guide to Meteorological Instruments and Methods of Observation, Sixth Edition, ISBN: 92-63-16008-2, pp 1. 9. 1/ 1. 9. 11, Geneva 1996).

2.2. The test course shall comprise test sections with traffic conditions, at speed corresponding to the relevant type of road, as described in Table 2 below:

Table 2

Test Section	*Traffic conditions*	*Road type*		
		Urban areas	*Multi-lane road, e.g. motorway*	*Country road*
	Speed	*50 ± 10 km/h*	*100 ± 20 km/h*	*80 ± 20 km/h*
	Average percentage of the full test course length	*10 per cent*	*20 per cent*	*70 per cent*
A	Single oncoming vehicle or single preceding vehicle in a frequency so that the adaptive driving-beam will react to demonstrate the adaptation process.		X	X

B	Combined oncoming and preceding traffic situations. In a frequency so that the adaptive driving-beam will react to demonstrate the adaptation process.		X	X
C	Active and passive overtaking manoeuvres, in a frequency so that the adaptive driving-beam will react to demonstrate the adaptation process.		X	X
D	Oncoming bicycle, as described in paragraph 6.16.8.1.1.2.			X
E	Combined oncoming and preceding traffic situations	X		

2.3. Urban areas shall comprise roads with and without illumination.

2.4. Country roads shall comprise sections having two lanes and sections having four or more lanes and shall include junctions, hills and/or slopes, dips and winding roads.

2.5. Multi lane roads (e.g. motorways) and country roads shall comprise sections having straight level parts with a length of more than 600 m. Additionally they shall comprise of sections having curves to the left and to the right.

2.6. Dense traffic situations shall be taken into account.

2.7. For the test sections A and B in the table above the engineers conducting the tests shall evaluate and record the acceptability of the performance of the adaptation process in relation to oncoming and preceding road users. This means that the test engineers shall operate the vehicle being tested and additionally operate the oncoming and preceding vehicles.

At the request of the Type Approval Authority, compliance with traffic scenarios other than the ones listed in Table 2 may be demonstrated by the manufacturer by providing sufficient documentation or by other means accepted by the Type Approval Authority.