

Social network Graph Link Prediction - Facebook Challenge

In [1]:

```
#Importing Libraries
# please do go through this python notebook:
import warnings
warnings.filterwarnings("ignore")

import csv
import pandas as pd#pandas to create small dataframes
import datetime #Convert to unix time
import time #Convert to unix time
# if numpy is not installed already : pip3 install numpy
import numpy as np#Do arithmetic operations on arrays
# matplotlib: used to plot graphs
import matplotlib
import matplotlib.pyplot as plt
import seaborn as sns#Plots
from matplotlib import rcParams#Size of plots
from sklearn.cluster import MiniBatchKMeans, KMeans#Clustering
import math
import pickle
import os
# to install xgboost: pip3 install xgboost
import xgboost as xgb

import warnings
import networkx as nx
import pdb
import pickle
from pandas import HDFStore, DataFrame
from pandas import read_hdf
from scipy.sparse.linalg import svds, eigs
import gc
from tqdm import tqdm
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import f1_score
```

In [6]:

```
#reading
from pandas import read_hdf
df_final_train = read_hdf('data/fea_sample/storage_sample_stage4.h5', 'train_df', mode='r')
df_final_test = read_hdf('data/fea_sample/storage_sample_stage4.h5', 'test_df', mode='r')
```

In [7]:

```
df_final_train.columns
```

Out[7]:

```
Index(['source_node', 'destination_node', 'indicator_link',
      'jaccard_followers', 'jaccard_followees', 'cosine_followers',
      'cosine_followees', 'num_followers_s', 'num_followers_d',
      'num_followees_s', 'num_followees_d', 'inter_followers',
      'inter_followees', 'adar_index', 'p_attach_in', 'p_attach_out',
      'follows_back', 'same_comp', 'shortest_path', 'weight_in', 'weight_out',
      'weight_f1', 'weight_f2', 'weight_f3', 'weight_f4', 'page_rank_s',
      'page_rank_d', 'katz_s', 'katz_d', 'hubs_s', 'hubs_d', 'authorities_s',
      'authorities_d', 'svd_u_s_1', 'svd_u_s_2', 'svd_u_s_3', 'svd_u_s_4',
      'svd_u_s_5', 'svd_u_s_6', 'svd_u_d_1', 'svd_u_d_2', 'svd_u_d_3',
      'svd_u_d_4', 'svd_u_d_5', 'svd_u_d_6', 'svd_v_s_1', 'svd_v_s_2',
      'svd_v_s_3', 'svd_v_s_4', 'svd_v_s_5', 'svd_v_s_6', 'svd_v_d_1',
      'svd_v_d_2', 'svd_v_d_3', 'svd_v_d_4', 'svd_v_d_5', 'svd_v_d_6',
      'svd_dot_u', 'svd_dot_v'],
      dtype='object')
```

In [8]:

```
y_train = df_final_train.indicator_link
y_test = df_final_test.indicator_link
```

In [9]:

```
df_final_train.drop(['source_node', 'destination_node', 'indicator_link'], axis=1, inplace=True)
df_final_test.drop(['source_node', 'destination_node', 'indicator_link'], axis=1, inplace=True)
```

In [10]:

```
estimators = [10, 50, 100, 250, 450]
train_scores = []
```

```

test_scores = []
for i in estimators:
    clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                                max_depth=5, max_features='auto', max_leaf_nodes=None,
                                min_impurity_decrease=0.0, min_impurity_split=None,
                                min_samples_leaf=52, min_samples_split=120,
                                min_weight_fraction_leaf=0.0, n_estimators=i, n_jobs=-1, random_state=25, verbose=0, warm_start=
    clf.fit(df_final_train, y_train)
    train_sc = f1_score(y_train, clf.predict(df_final_train))
    test_sc = f1_score(y_test, clf.predict(df_final_test))
    test_scores.append(test_sc)
    train_scores.append(train_sc)
    print('Estimators = ', i, 'Train Score', train_sc, 'test Score', test_sc)
plt.plot(estimators, train_scores, label='Train Score')
plt.plot(estimators, test_scores, label='Test Score')
plt.xlabel('Estimators')
plt.ylabel('Score')
plt.title('Estimators vs score at depth of 5')


```

```

Estimators = 10 Train Score 0.9260924708866598 test Score 0.9118221166086735
Estimators = 50 Train Score 0.9219917533541243 test Score 0.90859816645847
Estimators = 100 Train Score 0.9224624996069142 test Score 0.9145870688745912
Estimators = 250 Train Score 0.9236840177104158 test Score 0.9112210802351647
Estimators = 450 Train Score 0.9235408051091452 test Score 0.9153713298791019

```

Text(0.5, 1.0, 'Estimators vs score at depth of 5')



Out[10]:

```

depths = [3,9,11,15,20,35,50,70,130]
train_scores = []
test_scores = []
for i in depths:
    clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                                max_depth=i, max_features='auto', max_leaf_nodes=None,
                                min_impurity_decrease=0.0, min_impurity_split=None,
                                min_samples_leaf=52, min_samples_split=120,
                                min_weight_fraction_leaf=0.0, n_estimators=115, n_jobs=-1, random_state=25, verbose=0, warm_star
    clf.fit(df_final_train, y_train)
    train_sc = f1_score(y_train, clf.predict(df_final_train))
    test_sc = f1_score(y_test, clf.predict(df_final_test))
    test_scores.append(test_sc)
    train_scores.append(train_sc)
    print('depth = ', i, 'Train Score', train_sc, 'test Score', test_sc)
plt.plot(depths, train_scores, label='Train Score')
plt.plot(depths, test_scores, label='Test Score')
plt.xlabel('Depth')
plt.ylabel('Score')
plt.title('Depth vs score at depth of 5 at estimators = 115')
plt.show()


```

In [11]:

```

depth = 3 Train Score 0.9015356252487796 test Score 0.8792746666666668
depth = 9 Train Score 0.9590110205252161 test Score 0.9248102817764814
depth = 11 Train Score 0.9615345331236084 test Score 0.9252413443460994
depth = 15 Train Score 0.9636335799948965 test Score 0.9252520129334939
depth = 20 Train Score 0.9650880945106426 test Score 0.9263868382197848
depth = 35 Train Score 0.964963578014365 test Score 0.9260087793347965
depth = 50 Train Score 0.964963578014365 test Score 0.9260087793347965
depth = 70 Train Score 0.964963578014365 test Score 0.9260087793347965
depth = 130 Train Score 0.964963578014365 test Score 0.9260087793347965

```



In [12]:

```

from sklearn.metrics import f1_score
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import f1_score
from sklearn.model_selection import RandomizedSearchCV
from scipy.stats import randint as sp_randint
from scipy.stats import uniform

param_dist = {"n_estimators":sp_randint(105,125),
              "max_depth": sp_randint(10,15),
              "min_samples_split": sp_randint(110,190),
              "min_samples_leaf": sp_randint(25,65)}

clf = RandomForestClassifier(random_state=25,n_jobs=-1)

rf_random = RandomizedSearchCV(clf, param_distributions=param_dist, return_train_score=True,
                               n_iter=5,cv=10,scoring='f1',random_state=25)

rf_random.fit(df_final_train,y_train)
print('mean test scores',rf_random.cv_results_['mean_test_score'])
print('mean train scores',rf_random.cv_results_['mean_train_score'])

mean test scores [0.96300085 0.96261852 0.96075898 0.96260013 0.96439399]
mean train scores [0.96425511 0.96358402 0.96138245 0.96359863 0.96564198]

```

In [13]:

```

print(rf_random.best_estimator_)

RandomForestClassifier(max_depth=14, min_samples_leaf=28, min_samples_split=111,
                       n_estimators=121, n_jobs=-1, random_state=25)

```

In [14]:

```

clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                             max_depth=14, max_features='auto', max_leaf_nodes=None,
                             min_impurity_decrease=0.0, min_impurity_split=None,
                             min_samples_leaf=28, min_samples_split=111,
                             min_weight_fraction_leaf=0.0, n_estimators=121, n_jobs=-1,
                             oob_score=False, random_state=25, verbose=0, warm_start=False)

```

In [15]:

```

clf.fit(df_final_train,y_train)
y_train_pred = clf.predict(df_final_train)
y_test_pred = clf.predict(df_final_test)

```

In [16]:

```

from sklearn.metrics import f1_score
print('Train f1 score',f1_score(y_train,y_train_pred))
print('Test f1 score',f1_score(y_test,y_test_pred))

```

```

Train f1 score 0.9659373344741882
Test f1 score 0.927007299270073

```

In [17]:

```

from sklearn.metrics import confusion_matrix

```

```
def plot_confusion_matrix(test_y, predict_y):
    C = confusion_matrix(test_y, predict_y)

    A = ((C.T)/(C.sum(axis=1))).T

    B = (C/C.sum(axis=0))
    plt.figure(figsize=(20,4))

    labels = [0,1]
    # representing A in heatmap format
    cmap=sns.light_palette("blue")
    plt.subplot(1, 3, 1)
    sns.heatmap(C, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Confusion matrix")

    plt.subplot(1, 3, 2)
    sns.heatmap(B, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Precision matrix")


    plt.subplot(1, 3, 3)
    # representing B in heatmap format
    sns.heatmap(A, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Recall matrix")

    plt.show()
```


In [18]:

```
print('Train confusion_matrix')
plot_confusion_matrix(y_train,y_train_pred)
print('Test confusion_matrix')
plot_confusion_matrix(y_test,y_test_pred)
```

Train confusion_matrix




Test confusion_matrix




In [19]:

```
from sklearn.metrics import roc_curve, auc
fpr, tpr, ths = roc_curve(y_test, y_test_pred)
auc_sc = auc(fpr, tpr)
plt.plot(fpr, tpr, color='navy', label='ROC curve (area = %0.2f)' % auc_sc)
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('Receiver operating characteristic with test data')
plt.legend()
plt.show()
```



In [20]:

```
features = df_final_train.columns
importances = clf.feature_importances_
indices = (np.argsort(importances))[-25:]
plt.figure(figsize=(10,12))
plt.title('Feature Importances')
plt.barh(range(len(indices)), importances[indices], color='r', align='center')
plt.yticks(range(len(indices)), [features[i] for i in indices])
plt.xlabel('Relative Importance')
plt.show()
```



In [21]:

```
from xgboost import XGBClassifier
xgb_clf = XGBClassifier()
params = {'max_depth': [10, 12, 14, 16],
          'n_estimators': [100, 200, 300, 400]}
```

```
rf_random = RandomizedSearchCV(xgb_clf, param_distributions=params, return_train_score=True,
                               n_iter=5,cv=10,scoring='f1',random_state=25)
```

```
rf_random.fit(df_final_train,y_train)
print('mean test scores',rf_random.cv_results_['mean_test_score'])
print('mean train scores',rf_random.cv_results_['mean_train_score'])
print(rf_random.best_estimator_)
```

```
mean test scores [0.98234338 0.9815406 0.98243071 0.98380674 0.98279521]
mean train scores [1. 1. 1. 1. 1.]
XGBClassifier(base_score=0.5, booster='gbtree', colsample_bylevel=1,
              colsample_bynode=1, colsample_bytree=1, gamma=0, gpu_id=-1,
              importance_type='gain', interaction_constraints='',
              learning_rate=0.300000012, max_delta_step=0, max_depth=10,
              min_child_weight=1, missing=nan, monotone_constraints='()',
              n_estimators=400, n_jobs=0, num_parallel_tree=1, random_state=0,
              reg_alpha=0, reg_lambda=1, scale_pos_weight=1, subsample=1,
              tree_method='exact', validate_parameters=1, verbosity=None)
```

In [22]:

```
xg_best_clf = XGBClassifier(objective='reg:logistic', n_estimators= 400, max_depth= 10)
xg_best_clf.fit(df_final_train,y_train)
y_train_pred = xg_best_clf.predict(df_final_train)
y_test_pred = xg_best_clf.predict(df_final_test)
```

In [23]:


```
from sklearn.metrics import f1_score
print('Train f1 score',f1_score(y_train,y_train_pred))
print('Test f1 score',f1_score(y_test,y_test_pred))
```

```
Train f1 score 1.0
Test f1 score 0.9141750914175091
```


In [24]:

```
print('Train confusion_matrix')
plot_confusion_matrix(y_train,y_train_pred)
print('Test confusion_matrix')
plot_confusion_matrix(y_test,y_test_pred)
```

Train confusion_matrix




Test confusion_matrix




In [25]:

```
fpr,tpr,ths = roc_curve(y_test,y_test_pred)
auc_sc = auc(fpr, tpr)
plt.plot(fpr, tpr, color='navy',label='ROC curve (area = %0.2f)' % auc_sc)
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('Receiver operating characteristic with test data')
plt.legend()
plt.show()
```



In [27]:

```
features = df_final_train.columns
importances = xg_best_clf.feature_importances_
indices = (np.argsort(importances))[-25:]
plt.figure(figsize=(10,12))
plt.title('Feature Importances')
plt.barh(range(len(indices)), importances[indices], color='r', align='center')
plt.yticks(range(len(indices)), [features[i] for i in indices])
plt.xlabel('Relative Importance')
plt.show()
```



Train and test scores have been improved by using xgboost. The most important features are follow back and cosine followers according to xgboost. AUC remained same. Precision and recall data were similar to that of Random Forest.

Assignments:

1. Add another feature called Preferential Attachment with followers and followees data of vertex. you can check about Preferential Attachment in below link <http://be.amazd.com/link-prediction/>
2. Add feature called svd_dot. you can calculate svd_dot as Dot product between source node svd and destination node svd features. you can read about this in below pdf https://storage.googleapis.com/kaggle-forum-message-attachments/2594/supervised_link_prediction.pdf
3. Tune hyperparameters for XG boost with all these features and check the error metric.