


CHAPTER 4

Repetition Structures



Topics

- **Introduction to Repetition Structures**
- **The `while` Loop: a Condition-Controlled Loop**
- **The `for` Loop: a Count-Controlled Loop**
- **Calculating a Running Total**
- **Sentinels**
- **Input Validation Loops**
- **Nested Loops**
- **Turtle Graphics: Using Loops to Draw Designs**

Introduction to Repetition Structures

- **Often have to write code that performs the same task multiple times**
 - Disadvantages to duplicating code
 - Makes program large
 - Time consuming
 - May need to be corrected in many places
- **Repetition structure: makes computer repeat included code as necessary**
 - Includes condition-controlled loops and count-controlled loops




The `while` Loop: a Condition-Controlled Loop

- `while` loop: while condition is true, do something
 - Two parts:
 - Condition tested for true or false value
 - Statements repeated as long as condition is true
 - In flow chart, line goes back to previous part
 - General format:

```
while condition:  
    statements
```

The while Loop: a Condition-Controlled Loop (cont'd.)


Figure 4-1 The logic of a while loop



The `while` Loop: a Condition-Controlled Loop (cont'd.)

- In order for a loop to stop executing, something has to happen inside the loop to make the condition false
- Iteration: one execution of the body of a loop
- `while` loop is known as a *pretest* loop
 - Tests condition before performing an iteration
 - Will never execute if condition is false to start with
 - Requires performing some steps prior to the loop

Figure 4-3 Flowchart for Program 4-1



Infinite Loops

- **Loops must contain within themselves a way to terminate**
 - Something inside a `while` loop must eventually make the condition false
- **Infinite loop: loop that does not have a way of stopping**
 - Repeats until program is interrupted
 - Occurs when programmer forgets to include stopping code in the loop




The `for` Loop: a Count-Controlled Loop

- **Count-Controlled loop**: iterates a specific number of times
 - 🍌 Use a `for` statement to write count-controlled loop
 - Designed to work with sequence of data items
 - Iterates once for each item in the sequence
 - General format:

```
for variable in [val1, val2, etc]:  
    statements
```
 - **Target variable**: the variable which is the target of the assignment at the beginning of each iteration



Figure 4-4 The for loop



Using the range Function with the for Loop

- **The range function simplifies the process of writing a for loop**
 - `range` returns an iterable object
 - Iterable: contains a sequence of values that can be iterated over
- **range characteristics:**
 - One argument: used as ending limit
 - Two arguments: starting value and ending limit
 - Three arguments: third argument is step value



Using the Target Variable Inside the Loop

- **Purpose of target variable is to reference each item in a sequence as the loop iterates**
- **Target variable can be used in calculations or tasks in the body of the loop**
 - Example: calculate square root of each number in a range

Letting the User Control the Loop Iterations

- Sometimes the programmer does not know exactly how many times the loop will execute
- Can receive range inputs from the user, place them in variables, and call the `range` function in the `for` clause using these variables
 - 🍌 Be sure to consider the end cases: `range` does not include the ending limit

Generating an Iterable Sequence that Ranges from Highest to Lowest


- The `range` function can be used to generate a sequence with numbers in descending order
 - Make sure starting number is larger than end limit, and step value is negative
 - Example: `range (10, 0, -1)`

Calculating a Running Total

- **Programs often need to calculate a total of a series of numbers**
 - Typically include two elements:
 - A loop that reads each number in series
 - An *accumulator* variable
 - Known as program that keeps a running total: accumulates total and reads in series
 - At end of loop, accumulator will reference the total

Calculating a Running Total (cont'd.)

Figure 4-6 Logic for calculating a running total



The Augmented Assignment Operators

- In many assignment statements, the variable on the left side of the = operator also appears on the right side of the = operator
- Augmented assignment operators: special set of operators designed for this type of job
 - Shorthand operators

The Augmented Assignment Operators (cont'd.)

Table 4-2 Augmented assignment operators

Operator	Example Usage	Equivalent To
<code>+=</code>	<code>x += 5</code>	<code>x = x + 5</code>
<code>-=</code>	<code>y -= 2</code>	<code>y = y - 2</code>
<code>*=</code>	<code>z *= 10</code>	<code>z = z * 10</code>
<code>/=</code>	<code>a /= b</code>	<code>a = a / b</code>
<code>%=</code>	<code>c %= 3</code>	<code>c = c % 3</code>

Sentinels

- **Sentinel: special value that marks the end of a sequence of items**
 - When program reaches a sentinel, it knows that the end of the sequence of items was reached, and the loop terminates
 - Must be distinctive enough so as not to be mistaken for a regular value in the sequence
 - Example: when reading an input file, empty line can be used as a sentinel

Input Validation Loops

- **Computer cannot tell the difference between good data and bad data**
 - If user provides bad input, program will produce bad output
 - GIGO: garbage in, garbage out
 - It is important to design program such that bad input is never accepted


Input Validation Loops (cont'd.)

- **Input validation: inspecting input before it is processed by the program**
 - If input is invalid, prompt user to enter correct data
 - Commonly accomplished using a `while` loop which repeats as long as the input is bad
 - If input is bad, display error message and receive another set of data
 - If input is good, continue to process the input



Input Validation Loops (cont'd.)


Figure 4-7 Logic containing an input validation loop



Nested Loops

- **Nested loop: loop that is contained inside another loop**
 - Example: analog clock works like a nested loop
 - Hours hand moves once for every twelve movements of the minutes hand: for each iteration of the “hours,” do twelve iterations of “minutes”
 - Seconds hand moves 60 times for each movement of the minutes hand: for each iteration of “minutes,” do 60 iterations of “seconds”

Figure 4-8 Flowchart for a clock simulator



Nested Loops (cont'd.)

- **Key points about nested loops:**
 - Inner loop goes through all of its iterations for each iteration of outer loop
 - Inner loops complete their iterations faster than outer loops
 - Total number of iterations in nested loop:
$$\text{number_iterations_inner} \times \text{number_iterations_outer}$$

Summary

- **This chapter covered:**
 - Repetition structures, including:
 - Condition-controlled loops
 - Count-controlled loops
 - Nested loops
 - Infinite loops and how they can be avoided
 - `range` function as used in `for` loops
 - Calculating a running total and augmented assignment operators
 - Use of sentinels to terminate loops
 - Using loops to draw turtle graphic designs

