

AI ASSISTED CODING

Name: Amma Anjali

Batch- 33

Hall-Ticket:2303A52385

Assignment:13.5

Task1:

Lab 13: Code Refactoring – Improving Legacy Code with AI
Suggestions Lab

Objectives:

Week7 -

Friday

- Identify code smells and inefficiencies in legacy Python scripts.
- Use AI-assisted coding tools to refactor for readability, maintainability, and performance.
- Apply modern Python best practices while ensuring output correctness.

Task Description #1 (Refactoring – Removing Global Variables)

- Task: Use AI to eliminate unnecessary global variables from the code.

- Instructions:

- o Identify global variables used across functions.
 - o Refactor the code to pass values using function parameters.
 - o Improve modularity and testability.

- Sample Legacy Code:

```
rate = 0.1 def
```

```
calculate_interest(amount):  
    return amount * rate  
print(calculate_interest(1000))
```

- Expected Output: 0 Refactored version passing rate as a parameter or using a configuration structure.

Prompt: > "Refactor this Python code to eliminate the global variable `rate`. Update the `calculate_interest` function so that `rate` is passed as a parameter. Apply modern Python best practices (like type hinting and a docstring) to improve readability, modularity, and testability. Ensure the final print statement outputs the correct result."

```
def calculate_interest(principal: float, rate: float, time: float) ->  
float: """  
    Calculate the simple interest given principal, rate, and time.  
  
    Args:  
        principal: The initial amount of money invested or loaned.  
        rate: The annual interest rate as a decimal (e.g. 0.05 for 5%).  
        time: The time period in years for which the interest is  
        calculated.  
  
    Returns:  
        The interest accrued over the given time period.  
    """  
    return principal * rate * time  
  
def main() -> None:  
    """Run a simple interest calculation example."""
```

```

principal: float = 1000.0
rate: float = 0.05    # 5% annual interest, passed explicitly
time: float = 2.0     # 2 years

interest: float = calculate_interest(principal, rate, time)
print(interest)

if __name__ == "__main__":
    main()

```

Task Description #2 : (Refactoring Deeply Nested Conditionals)

- Task: Use AI to refactor deeply nested if–elif–else logic into a cleaner structure.
 - Focus Areas:
 - Readability
 - Logical simplification
 - Maintainability
- Legacy Code: score = 78 if score >= 90:
 print("Excellent") else: if score >= 75: print("Very Good") else: if
 score >= 60: print("Good") else: print("Needs Improvement")
- Expected Outcome:
- Flattened logic using guard clauses or a mapping-based approach.

Prompt: "Refactor this deeply nested Python conditional logic into a cleaner structure. First, wrap the logic in a function so you can use **guard clauses** (early returns) to flatten the **if-else** chain. Then, provide a second version using a **mapping-based approach** (like iterating through a list of tuples) to determine the output. Ensure both versions include type hints and a docstring for maintainability."

```

from typing import Callable, List, Literal, Tuple

```

```

Outcome = Literal["low", "medium", "high", "invalid"]

```

```

Rule = Tuple[Callable[[int], bool], Outcome]

```

```
def classify_score_guard(score: int) ->
Outcome:
```

```
"""
    Classify a numeric score into a category using guard clauses.

    Args:
        score: The numeric score to classify.

    Returns:
        A string label describing the score category.
    """

    if score < 0:
        return "invalid"
    if score < 50:
        return "low"
    if score < 80:
        return "medium"
    if score <= 100:
        return "high"
    return "invalid"

def classify_score_mapping(score: int) ->
Outcome:
    """
        Classify a numeric score into a category using a list of rules.

        This demonstrates a mapping-based (data-driven) approach where each rule
        consists of a condition function and the label it produces.

    Args:
```

```

    score: The numeric score to classify.

    Returns:          A string label describing the score
category:
    """
    rules: List[Rule] = [
        (lambda s: s < 0, "invalid"),
        (lambda s: 0 <= s < 50, "low"),
        (lambda s: 50 <= s < 80, "medium"),
        (lambda s: 80 <= s <= 100, "high"),
    ]

    for condition, label in
rules:          if
condition(score):
    return label

    return "invalid"

def main() -> None:
    """Simple demo of both classification strategies."""
    test_score: int = 72

    print("Guard:", classify_score_guard(test_score))
print("Mapping:", classify_score_mapping(test_score))

if __name__ == "__main__":
    main()

```

Task 3 (Refactoring Repeated File Handling Code) • Task:
Use AI to refactor repeated file open/read/close logic.

- Focus Areas: o
- DRY principle o
- Context managers o
- Function reuse
- Legacy Code:

```
f = open("data1.txt")
print(f.read())
f.close() f =
open("data2.txt")
print(f.read())
f.close()
```

Expected Outcome:

- o Reusable function using with open() and parameters.

Prompt: "Refactor this repeated Python file handling logic to adhere strictly to the DRY (Don't Repeat Yourself) principle. Create a reusable function that accepts a filename as a parameter. Inside the function, use a context manager (`with open(...)`) to safely open, read, and print the file's contents. Add type hints, a docstring, and a simple `try-except` block to handle `FileNotFoundError` gracefully." `from pathlib import Path`

```
def print_file_contents(filename: str) -> None:
    """
        Open a text file and print its contents
safely.

        Uses a context manager to ensure the file is closed properly and
handles
        missing files gracefully.

    Args:
        filename: Path to the file whose contents should be printed.
    """
    try:
```

```

    path = Path(filename)

    with path.open("r", encoding="utf-8") as file:
        print(file.read())
except FileNotFoundError:
    print(f"File not found: {filename}")

def main() -> None:

    """Example usage of the reusable file printing function."""

    # Replace these with actual filenames you want to test with.
    print_file_contents("example1.txt")

    print_file_contents("example2.txt")

if __name__ == "__main__":
    main()

```

Task 4 (Optimizing Search Logic)

- Task: Refactor inefficient linear searches using appropriate data structures.

- Focus Areas: o Time complexity o Data structure choice
Legacy Code:

users = ["admin", "guest", "editor", "viewer"]

name = input("Enter username: ") found =

False for u in users: if u == name: found =

True

print("Access Granted" if found else "Access Denied") Expected

Outcome: o Use of sets or dictionaries with complexity justification.

Prompt: "Refactor this Python search logic to optimize time complexity. Replace the linear list iteration with a **set** to achieve $O(1)$ average lookup time. Wrap the logic in a function with type hints, and include comments explicitly justifying the time complexity

improvement (from $O(n)$ to $O(1)$) and the choice of data structure."

```
from typing import Hashable, Iterable

def contains_value_optimized(values: Iterable[Hashable], target:
Hashable) -> bool:
    """
        Check whether a target value exists in a collection using an optimized
lookup.

        This refactored version converts the input collection to a set once
and then
        performs membership checks against the set.
    """
    # Converting the iterable to a set is  $O(n)$  for  $n$  input elements, but
    # subsequent membership checks are  $O(1)$  on average. This is a strict
    # improvement over scanning a list linearly, which would be  $O(n)$  per
lookup.

    lookup = set(values)

    # Using a set here is preferable because it is implemented as a hash
table,
    # giving average  $O(1)$  time complexity for membership tests like
`target in lookup`.

    return target in lookup

def main() -> None:    """Simple demonstration of the optimized
search logic."""

    items = ["apple", "banana", "cherry"]

    print(contains_value_optimized(items, "banana")) # Expected: True
```



```
print(contains_value_optimized(items, "orange")) # Expected: False

if __name__ == "__main__":
    main()
```

Task 5 (Refactoring Procedural Code into OOP Design) •

Task: Use AI to refactor procedural code into a class-based design.

• Focus Areas:

- o Object-Oriented principles o

Encapsulation Legacy Code: salary = 50000 tax

= salary * 0.2 net = salary - tax print(net)

Expected Outcome: o A class like

EmployeeSalaryCalculator

with methods and attributes.

Prompt: "Refactor this procedural Python code into an Object-Oriented design. Create a class named

EmployeeSalaryCalculator. Use the `__init__` method to encapsulate the `salary` and `tax_rate` as instance attributes. Create a method called `calculate_net_salary` to compute and return the net pay. Include type hints, a docstring, and demonstrate how to instantiate the class and print the result."

```
class
EmployeeSalaryCalculator:
```

```
"""
    Calculate an employee's net salary given a gross salary and tax rate.

    The tax rate is expressed as a decimal (e.g. 0.22 for 22%).
    """
```

```

def __init__(self, salary: float, tax_rate: float) -> None:
    """
        Initialize the salary calculator with salary and tax rate.

        Args:
            salary: The gross salary amount.
            tax_rate: The tax rate as a decimal (e.g. 0.22 for 22%).
    """
    self.salary: float = salary
    self.tax_rate: float = tax_rate

    def calculate_net_salary(self) -> float:
        """
            Compute the net salary after tax.

            Returns:
                The net salary after applying
the tax rate.
        """
        tax_amount = self.salary * self.tax_rate
        return self.salary - tax_amount


def main() -> None:
    """Demonstrate using
EmployeeSalaryCalculator to compute net salary."""
    gross_salary: float = 5000.0

    tax_rate: float = 0.22

    calculator = EmployeeSalaryCalculator(gross_salary, tax_rate)
    net_salary: float = calculator.calculate_net_salary()
    print(net_salary)

```

```
if __name__ == "__main__":  
    main()
```

Task 6 (Refactoring for Performance Optimization)

- Task: Use AI to refactor a performance-heavy loop handling large data.
 - Focus Areas:
 - o Algorithmic optimization
 - o Use of built-in functions
- Legacy Code: `total = 0` for `i` in `range(1, 1000000)`: `if i % 2 == 0: total += i` `print(total)`

Expected Outcome:

- o Optimized logic using mathematical formulas or comprehensions, with time comparison.

Prompt: "Refactor this Python loop to optimize performance. Provide two optimized solutions: one using Python's built-in `sum()` function with an optimized `range()`, and another using the $O(1)$ mathematical formula for the sum of an arithmetic progression. Use the `time` module to run and print a time comparison between the legacy code and both optimized versions. Include type hints, docstrings, and comments explaining the time complexities."

```
from time import perf_counter  
  
def legacy_sum(n: int) -> int:  
    """  
    Legacy implementation that sums numbers from 1 to n using an explicit  
    loop.  
  
    Time complexity:  
    O(n) - the loop performs n additions.  
    """  
  
    total = 0
```

```

    for i in range(1, n + 1):
        total += i

    return total

def optimized_sum_builtin(n: int) -> int:
    """
    Optimized implementation using Python's built-in sum() with range().

    Time complexity:
        O(n) - sum() still iterates over the range internally, but it is
        implemented in C and is typically faster than a pure Python loop.
    """
    return sum(range(1, n + 1))

def optimized_sum_formula(n: int) ->
int:

```

```

    """
    Optimized implementation using the O(1) arithmetic progression formula.
    Uses the formula for the sum of the first n natural numbers:


$$n * (n + 1) / 2$$


    Time complexity:

        O(1) - a constant number of arithmetic operations regardless of n.
    """
    return n * (n + 1) // 2

def time_function(fn, n: int) -> float:

```

```

"""
Measure the execution time of a summation function for a given n.

Args:
    fn: The summation function to time.
n: The upper bound of the summation.

Returns:
    The elapsed time in seconds.
"""
start = perf_counter()
result = fn(n)
end = perf_counter()

# Ensure the result is used so the call is not optimized away.
_ = result
return end - start


def main() ->
None:
    """Run and print a time comparison for legacy and optimized
approaches."""
    n:
int = 10_000_000

    legacy_time = time_function(legacy_sum, n)
builtin_time = time_function(optimized_sum_builtin, n)
formula_time = time_function(optimized_sum_formula, n)

    print(f"n = {n}")

    print(f"Legacy loop (O(n)) time: {legacy_time:.6f} seconds")
print(f"Built-in sum with range (O(n)): {builtin_time:.6f} seconds")

```

```
print(f"Formula (O(1)) time: {formula_time:.6f} seconds")

if __name__ ==
"__main__":    main()
```

Task 7 (Removing Hidden Side Effects)

- Task: Refactor code that modifies shared mutable state.
- Focus Areas:
 - o Functional-style refactoring
 - o Predictability
 - o Legacy Code:

```
data = []
def add_item(x):
    data.append(x)
add_item(10)
add_item(20)
print(data)
```

Expected Outcome:

- o Refactored function returning values instead of mutating globals.

Prompt: "Refactor this Python code to remove the hidden side effect of mutating a global list. Adopt a functional-style approach by creating a pure function `add_item` that takes the current list and the new item as parameters. It should return a brand-new list with the item appended, rather than mutating the original list. Include type hints and a docstring." `from typing import List, TypeVar`

```
T = TypeVar("T")
```

```

def add_item(items: List[T], new_item: T) -> List[T]:
    """
        Return a new list with `new_item` appended, without mutating the
        original.

        This function follows a functional style by avoiding side effects: it
        does not modify the input list, but instead creates and returns a new
        list.

        Args:
            items: The original list of items.
            new_item: The item to append to the list.

        Returns:
            A brand-new list containing all elements of `items` plus
            `new_item`.
    """
    return [*items, new_item]

def main() ->
None:
    """Demonstrate using add_item without mutating the original list."""
    original: List[int] = [1, 2, 3]      updated: List[int] =
    add_item(original, 4)

    print(f"Original list: {original}")  # [1, 2, 3]
    print(f"Updated list: {updated}")    # [1, 2, 3, 4]

    if __name__ ==
    "__main__":
        main()

```

Task 8 (Refactoring Complex Input Validation Logic)

- Task: Use AI to simplify and modularize complex validation rules.
 - Focus Areas: o Readability o Testability
- Legacy Code:
- ```
password = input("Enter password: ")
if len(password) >= 8:
 if any(c.isdigit() for c in password):
 if any(c.isupper() for c in password):
 print("Valid Password")
 else:
 print("Must contain uppercase")
 else:
 print("Must contain digit")
else:
 print("Password too short")
```
- Expected Outcome:

o Separate validation functions with clear responsibility

**Prompt:** "Refactor this deeply nested password validation logic to improve readability and testability. Extract each validation rule (length, digit, uppercase) into its own separate, single-responsibility helper function that returns a boolean. Then, create a main `validate_password` function that uses these helpers to accumulate and return a list of all error messages. Include type hints, docstrings, and an execution block that prints 'Valid Password' or the list

```
from typing import List

def is_valid_length(password: str, min_length: int = 8) -> bool:
 """
 Check whether the password meets the minimum length requirement.

 Args:
 password: The password string to validate.
 min_length: The minimum allowed length for the password.
 """
```



```
Returns:
 True if the password length is at least min_length, otherwise
False.
```

```
"""
```

```
 return len(password) >= min_length
```

```
def has_digit(password: str) ->
bool:
```

```
"""
```

```
 Check whether the password contains at least one numeric digit.
```

```
Args:
```

```
 password: The password string to validate.
```

```
Returns:
```

```
 True if the password contains a digit, otherwise False.
```

```
"""
```

```
 return any(char.isdigit() for char in password)
```

```
def has_uppercase(password: str) ->
bool:
```

```
"""
```

```
 Check whether the password contains at least one uppercase letter.
```

```
 Args:
 password: The password string
to validate.
```

```
Returns:
```

```
 True if the password contains an uppercase letter, otherwise
False.
```

```
"""
```

```
 return any(char.isupper() for char in password)
```

```
def validate_password(password: str) -> List[str]:
 """
 Validate a password against multiple rules and collect error messages.
 The validation rules are:
```

- Minimum length of 8 characters
- Contains at least one digit
  - Contains at least one uppercase letter

Args:

password: The password string to validate.

Returns:

A list of error messages. An empty list indicates a valid password.

```
 """
 errors: List[str] = []

 if not
is_valid_length(password):
 errors.append("Password must be at least 8 characters long.")

 if not has_digit(password):
 errors.append("Password must contain at least one digit.")

 if not has_uppercase(password):
 errors.append("Password must contain at least one uppercase
letter.")

 return errors
```

```
def main() -> None: """Run a simple password validation example and
print the result."""

 test_password = "Passw0rd" # Adjust to experiment with different
inputs

 validation_errors = validate_password(test_password)

 if not
validation_errors:

 print("Valid Password") else:
 print(validation_errors)

if __name__ == "__main__":
main()
```

Output:

```

• PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\Activate.ps1"
(.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_1_13.5.py"
100.0
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_2_13.5.py"
Guard: medium
Mapping: medium
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_3_13.5.py"
File not found: example1.txt
File not found: example2.txt
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_4_13.5.py"
True
False
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_5_13.5.py"
3900.0
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_6_13.5.py"
n = 10000000
Legacy loop (O(n)) time: 0.344928 seconds
Built-in sum with range (O(n)): 0.157139 seconds
Formula (O(1)) time: 0.000004 seconds
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_7_13.5.py"
Original list: [1, 2, 3]
Updated list: [1, 2, 3, 4]
• (.venv) PS C:\Users\intec\Ai coding> & "C:\Users\intec\Ai coding\.venv\Scripts\python.exe" "c:/Users
/intec/Ai coding/Assignment 4.2/Task_8_13.5.py"
Valid Password

```

Ctrl+K to generate command