

Assaignment.ioc - Pinout & Configuration

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

I2C2 Mode and Configuration

Mode

I2C I2C

Configuration

Reset Configuration

NVIC Settings

DMA Settings

GPIO Settings

Parameter Settings

User Constants

Configure the below parameters :

Search (Ctrl+F)

Master Features

I2C Speed Mode

Standard Mode

I2C Clock Speed (Hz)

100000

Slave Features

Clock No Stretch Mode

Disabled

Pinout view

System view

VDD

VSS

PB9

PB8

BOOT

PB7

PB6

PB5

PB4

PB3

PA15

PA14

VBAT

PC13

PC14

PC15

PD0

PD1

NRST

VSSA

VDDA

PA0

PA1

PA2

PA3

PA4

PA5

PA6

PA7

PB0

PB1

PB2

PB10

PB11

VSS

VDD

VDD

VSS

PA13

PA12

PA11

PA10

PA9

PA8

PB15

PB14

PB13

PB12

STM32F103C8Tx

LQFP48

2C2_SCL

2C2_SDA

SYS_JTMS-SWDIO

Updates Available

Updates are available for your software.

Click to review and install updates.

Assaignment.ioc - Pinout & Configuration

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

Categories A->Z

System Core >

Analog >

Timers >

RTC

TIM1

TIM2

TIM3

TIM4

Connectivity >

Computing >

Middleware >

TIM3 Mode and Configuration

Mode

Slave Mode Disable

Trigger Source Disable

Internal Clock

Channel1 Disable

Channel2 Disable

Channel3 Disable

Channel4 Disable

Combined Channels Disable

Configuration

Reset Configuration

User Constants

NVIC Settings

DMA Settings

Parameter Settings

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
TIM3 global interrupt	✓	0	0

Pinout view

System view

Pinout diagram of STM32F103C8Tx LQFP48. The diagram shows the chip with its pins labeled. The top row includes VDD, VSS, PB9, PB8, BOO, PB7, PB6, PB5, PB4, PB3, PA15, and PA14. The left side includes VBAT, PC13, PC14, PC15, PD0, PD1, NRST, VSSA, VDDA, Button_1 (PA0), Button_2 (PA1), and Button_3 (PA2). The bottom row includes PA3, PA4, PA5, PA6, PA7, PB0, PB1, PB2, PB10, PB11, VSS, and VDD. The right side includes VDD, VSS, PA13, PA12, PA11, PA10, PA9 (FAN), PA8, PB15, PB14, PB13, and PB12. The chip is labeled STM32F103C8Tx LQFP48.

Assaignment.ioc - Clock Configuration

Pinout & Configuration Clock Configuration Project Manager Tools

