Date:

# Activity-1

SJN

| P4 | P2 | P1 | P3 | P5 |
|---|---|---|---|---|

50 110 230 410 710

RR → $\boxed{\text{time slice} = 50}$

| P1 | P2 | P3 | P4 | P5 | P1 | P2 | P3 | P5 | P1 | P3 | P5 | P3 | P5 | P5 | P5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

50 100 150 200 250 300 310 360 410 430 480 530 560 610 660 710

Hence Average turnaround time

$$= \frac{710}{16} = 44.375$$

# Activity -2

| First fit column | | | Best fit column | |
|---|---|---|---|---|
| J1 | 4Kb | 8Kb | J3 | 6KB |
| J2 | 30Kb | 100Kb | J6 | 100KB |
| J3 | 6Kb | 1024Kb | J7 | 200 Kb |
| J4 | 9Kb | 56 Kb | J5 | 10 Kb |
| J8 | 2Kb | 2 Kb | J8 | 2 Kb |
| J5 | 10Kb | 48 Kb | J2 | 30 Kb |
| J6 | 100Kb | 2048 Kb | | |
| J10 | 1 Kb | 4 Kb | J1 | 4 Kb |
| J9 | 5 Kb | 8 Kb | J9 | 5 Kb |
| | | 12 Kb | J4 | 9 Kb |
| | | 56 Kb | J10 | 1 Kb |

Date:

Activity-3 - 52 blocks of memory

a) first fit (60 blocks)
b) best fit (52 blocks)
c) worst fit (100 blocks)

| |
|---|
| Operating System |
| Process 1 |
| Empty 60 blocks |
| (a) 52 block - remainder = 8 |
| Process 2 |
| Process 3 |
| Empty 52 blocks |
| (b) 52 block |
| Empty 100 blocks |
| (c) 52 block - remainder = 48 |

Activity-4 - 52 block of memory - dynamic partitions

| | | | | |
|---|---|---|---|---|
| Operating System | Process 1 | Empty 60 block | Process 2 | Process 3 |

Empty 52 blocks (a), (b) & (c)

Empty 100 blocks

Activity-5 worst fit allocates the largest partition, so we lose space as a result.