



```
#!/usr/bin/env python
```

```
"""demo.py - Demo script for py2pdf 0.5.
```

The main idea is: take one Python file and make a whole bunch of PDFs out of it for test purposes.

```
Dinu Gherman
"""
```

```
import string, re, os, os.path, sys, shutil
from py2pdf import *
```

```
### Custom layouter class used with test3().
```

```
class ImgPDFLayouter (PythonPDFLayouter):
    "A custom layouter displaying an image on each page."
```

```
def setMainFrame(self, frame=None):
    "Make a frame in the right half of the page."
```

```
width, height = self.options.realPaperFormat.size
self.frame = height - 2*cm, 2*cm, 250, width-1*cm

self.makeForm()
```

```
def makeForm(self):
    "Use the experimental ReportLab form support."
```

```
width, height = self.options.realPaperFormat.size
tm, bm, lm, rm = self.frame
c = self.canvas
```

```
# Define a PDF form containing an image frame
# that will be included on every page, but
# stored only once in the resulting file.
```

```
c.beginForm0("imageFrame")
c.saveState()
x, y = 219.0, 655.0 # Known size of the picture.
c.scale((lm - 1*cm)/x, height/y)
path = 'vertpython.jpg'
c.drawInlinImage(path, 0, 0)
c.restoreState()
c.endForm0()
```

```
def putPageDecoration(self):
```



```
"Draw the left border image and page number."
```

```
width, height = self.options.realPaperFormat.size  
tm, bm, lm, rm = self.frame  
c = self.canvas
```

```
# Footer.
```

```
x, y = lm + 0.5 * (rm - lm), 0.5 * bm  
c.setFill(Color(0, 0, 0))  
c.setFont('Times-Italic', 12)  
label = "Page %d" % self.pageNum  
c.drawCentredString(x, y, label)
```

```
# Call the previously stored form.  
c.doForm0("imageFrame")
```

```
### Helpers.
```

```
def modifyPath(path, new, ext='.py'):  
    "Modifying the base name of a file."
```

```
    rest, ext = os.path.splitext(path)  
    path, base = os.path.split(rest)  
    format = "%s-%s%s" % (base, new, ext)  
    return os.path.join(path, format)
```

```
def getAllTestFunctions():  
    "Return a list of all test functions available."
```

```
    globs = globals().keys()  
    tests = filter(lambda g: re.match('test[0-9]+', g), globs)  
    tests.sort()  
    return map(lambda t: globals()[t], tests)
```

```
### Test functions.
```

```
###
```

```
### In order to be automatically found and applied to  
### a Python file all test functions must follow the  
### following naming pattern: 'test[0-9]+' and contain  
### a doc string.
```

```
def test0(path):  
    "Creating a PDF assuming an ASCII file."
```

```
    p = PDFPrinter()  
    p.process(path)
```



```
def test1(path):  
    "Creating a PDF using only default options."
```

```
    p = PythonPDFPrinter()  
    p.process(path)
```

```
def test2(path):  
    "Creating a PDF with some modified options."
```

```
    p = PythonPDFPrinter()  
    p.options.updateOption('landscape', 1)  
    p.options.updateOption('fontName', 'Helvetica')  
    p.options.updateOption('fontSize', '14')  
    p.options.display()  
    p.process(path)
```

```
def test3(path):  
    "Creating several PDFs as 'magazine listings'."
```

```
    p = PythonPDFPrinter()  
    p.Layouter = EmptyPythonPDFLayouter  
    p.options.updateOption('paperSize', '(250,400)')  
    p.options.updateOption('multiPage', 1)  
    p.options.updateOption('lineNum', 1)  
    p.process(path)
```

```
def test4(path):  
    "Creating a PDF in monochrome mode."
```

```
    p = PythonPDFPrinter()  
    p.options.updateOption('mode', 'mono')  
    p.process(path)
```

```
def test5(path):  
    "Creating a PDF with options from a config file."
```

```
    p = PythonPDFPrinter()  
    i = string.find(path, 'test5')  
    newPath = modifyPath(path[:i-1], 'config') + '.txt'
```

```
    try:
```

```
        p.options.updateWithContentsOfFile(newPath)  
        p.options.display()  
        p.process(path)
```

```
    except IOError:
```



```
print "Skipping test5() due to IOError."
```

```
def test6(path):  
    "Creating a PDF with modified layout."  
  
    p = PythonPDFPrinter()  
    p.Layouter = ImgPDFLayouter  
    p.options.updateOption('fontName', 'Helvetica')  
    p.options.updateOption('fontSize', '12')  
    p.options.display()  
    p.process(path)
```

```
### Main.
```

```
def main(inPath, *tests):  
    "Apply various tests to one Python source file."
```

```
    for t in tests:  
        newPath = modifyPath(inPath, t.__name__)  
        shutil.copyfile(inPath, newPath)  
        print t.__doc__  
        t(newPath)  
        os.remove(newPath)  
    print
```

```
if __name__ == '__main__':  
    # Usage: "python demo.py <file> <test1> [<test2> ...]"  
    try:  
        try:  
            tests = map(lambda a: globals()[a], sys.argv[2:])  
        except IndexError:  
            tests = getAllTestFunctions()  
  
        fileName = sys.argv[1]  
        apply(main, [fileName]+tests)
```

```
    # Usage: "python demo.py" (implicitly does this:  
    # "python demo.py demo.py" <allTestsAvailable>)  
    except IndexError:  
        print "Performing self-test..."  
        fileName = sys.argv[0]  
        tests = getAllTestFunctions()  
        apply(main, [fileName]+tests)
```