## APC\_BOMnonSMD

Comment	Reference	Footprint	Mouser order number	Reichelt.de order number
Speakers	10J2	Molex4	Use Mouser part number	
Volume	10J4	Molex4	538-26-48-1245	
Diag Sw	1J4	Molex4	for all Molex connectors. These parts	
Display Segments 1	1J5	Molex12	have 24 pins and you can cut them as	
Display Strobes 2	1J6	Molex9	required. You need 204 pins if you want to be able	
Display Strobes 1	1J7	Molex9	to use the APC in all kinds of games	
Special Sol Drivers	2J12	Molex9	from Sys3 to Sys11c.	
Special Sol Triggers	2J13	Molex9	eyee to eyezze.	
Switch Inputs	sys11_1J10	Molex9	If you want to use it only in Sys3-Sys7	Only needed for Sys9 - Sys11
Solenoid Drivers 1	sys11 1J11	Molex9	OR Sys9-Sys11 games you can spare 6	Only needed for Sys9 - Sys11
Solenoid Drivers 2	sys11 1J12	Molex9	connectors with each one having 9 pins.	Only needed for Sys9 - Sys11
Lamp Rows	sys11 1J6	Molex9	That means 54 pins less which leads to	Only needed for Sys9 - Sys11
Lamp Strobes	sys11 1J7	Molex9	150 pins.	Only needed for Sys9 - Sys11
Switch Drivers	sys11 1J8	Molex9		Only needed for Sys9 - Sys11
Logic PWR/GND	sys7 1J2	Molex9		, , ,
Solenoid GND	sys7 2J10	Molex9		
Solenoid Drivers 1	sys7_2J11	Molex9		Only needed for Sys3 - Sys7
Switch Drivers	sys7_2J2	Molex9		Only needed for Sys3 – Sys7
Switch Inputs	sys7 2J3	Molex9		Only needed for Sys3 – Sys7
Lamp B+	sys7_2J4	Molex9		. ,
Lamp Strobes	sys7 2J5	Molex9		Only needed for Sys3 – Sys7
Lamp GND	sys7_2J6	Molex9		. ,
Lamp Rows	sys7_2J7	Molex9		Only needed for Sys3 – Sys7
Solenoid Drivers 2	sys7 2J9	Molex9		Only needed for Sys3 – Sys7
CONN 36	P4	pin array 18x2	538-10-89-7501	SL 2X25G 2,54
Lisy Jumper	P12	pin array 6x2	use rest from above	use rest from above
Display Segments 2		pin_array_13x2	538-10-89-7501	SL 2X13G 2,54
Sys11 J21	P11	pin array 8x2	use rest from above	SL 2X10G 2,54
Raspberry Pi	J1	Socket 2x20	474-PRT-16763	MPE 094-2-040
CONN 3X2	P7	Socket 3x2	571-215309-3	MPE 094-2-006
SD card	P8	Socket 1x6	200-SLW11001TS	BL 1X10G 2,54
Ardu pwr	P9	PINHEAD1-4	538-22-30-3364	SL 1X36G 2,54
CONN 2	P6	PINHEAD1-2	use rest from above	use rest from above
CONN 6	P1	PINHEAD1-6	use rest from above	use rest from above
CONN 7	P2	PINHEAD1-7	use rest from above	use rest from above
CONN 8	P5	PINHEAD1-8	use rest from above	use rest from above
CONN_2	P13	PINHEAD1-2	use rest from above	use rest from above
Lisy serial	P10	PINHEAD1-5	optional	optional
470u	C11		667-EEU-EB1V471B	RAD 470/35
100u	C2	Radial D5 L11 P2.5		RAD 100/25
1000u	C9		667-EEU-FR1C102L	RAD FR 1.000/16
10000	Q24,Q36,Q13,Q19,Q25,Q31,Q14,		00. 220	10.511(1000/10
	Q20,Q26,Q32,Q15,Q21,Q27,Q33,			
IRL540	Q16,Q22,Q28,Q34,Q17,Q23,Q29,	TO220	942-IRL540NPBF	IRL 540N
4,7K	Q35,Q18,Q30 RR1,RR7	SIP9	652-4609X-1LF-4.7K	SIL 9-8 4,7K
,	'	SIP9		•
18K Shutdown	RR8 SW1	Taster3301	652-4609X-1LF-18K 653-B3F-1000	SIL 9-8 18K TASTER 3301
74BCT760	U19	DIP-20	595-SN74BCT760N	IVOLEK 990T
74BC1760 TDA7496	U21	Multiwatt15V	511-TDA7496	
10/1430	021	widinwalltyv	JII-1 DA1430	