

# Finite difference methods for vibration problems

Hans Petter Langtangen<sup>1,2</sup>

<sup>1</sup>Center for Biomedical Computing, Simula Research Laboratory

<sup>2</sup>Department of Informatics, University of Oslo

Feb 11, 2016

## Contents

<b>1</b>	<b>Finite difference discretization</b>	<b>3</b>
1.1	A basic model for vibrations . . . . .	3
1.2	A centered finite difference scheme . . . . .	4
<b>2</b>	<b>Implementation</b>	<b>6</b>
2.1	Making a solver function . . . . .	6
2.2	Verification . . . . .	8
2.3	Scaled model . . . . .	11
<b>3</b>	<b>Long time simulations</b>	<b>11</b>
3.1	Using a moving plot window . . . . .	12
3.2	Making animations . . . . .	13
3.3	Using Bokeh to compare graphs . . . . .	16
3.4	Using a line-by-line ascii plotter . . . . .	18
3.5	Empirical analysis of the solution . . . . .	19
<b>4</b>	<b>Analysis of the numerical scheme</b>	<b>21</b>
4.1	Deriving a solution of the numerical scheme . . . . .	21
4.2	Exact discrete solution . . . . .	23
4.3	Convergence . . . . .	24
4.4	The global error . . . . .	25
4.5	Stability . . . . .	26
4.6	About the accuracy at the stability limit . . . . .	27

<b>5</b>	<b>Alternative schemes based on 1st-order equations</b>	<b>29</b>
5.1	The Forward Euler scheme . . . . .	29
5.2	The Backward Euler scheme . . . . .	30
5.3	The Crank-Nicolson scheme . . . . .	30
5.4	Comparison of schemes . . . . .	32
5.5	Runge-Kutta methods . . . . .	33
5.6	Analysis of the Forward Euler scheme . . . . .	35
<b>6</b>	<b>Energy considerations</b>	<b>37</b>
6.1	Derivation of the energy expression . . . . .	37
6.2	An error measure based on energy . . . . .	39
<b>7</b>	<b>The Euler-Cromer method</b>	<b>41</b>
7.1	Forward-backward discretization . . . . .	41
7.2	Equivalence with the scheme for the second-order ODE . . . . .	42
7.3	Implementation . . . . .	43
7.4	The velocity Verlet algorithm . . . . .	45
<b>8</b>	<b>Generalization: damping, nonlinear spring, and external excitation</b>	<b>46</b>
8.1	A centered scheme for linear damping . . . . .	47
8.2	A centered scheme for quadratic damping . . . . .	47
8.3	A forward-backward discretization of the quadratic damping term . . . . .	48
8.4	Implementation . . . . .	49
8.5	Verification . . . . .	50
8.6	Visualization . . . . .	51
8.7	User interface . . . . .	51
8.8	The Euler-Cromer scheme for the generalized model . . . . .	53
<b>9</b>	<b>Exercises and Problems</b>	<b>53</b>
<b>10</b>	<b>Applications of vibration models</b>	<b>83</b>
10.1	Oscillating mass attached to a spring . . . . .	83
10.2	General mechanical vibrating system . . . . .	85
10.3	A sliding mass attached to a spring . . . . .	87
10.4	A jumping washing machine . . . . .	87
10.5	Motion of a pendulum . . . . .	88
10.6	Dynamic free body diagram during pendulum motion . . . . .	90
10.7	Motion of an elastic pendulum . . . . .	95
10.8	Vehicle on a bumpy road . . . . .	99
10.9	Bouncing ball . . . . .	101
10.10	Electric circuits . . . . .	102
<b>11</b>	<b>Exercises</b>	<b>102</b>
	<b>References</b>	<b>124</b>

Vibration problems lead to differential equations with solutions that oscillate in time, typically in a damped or undamped sinusoidal fashion. Such solutions put certain demands on the numerical methods compared to other phenomena whose solutions are monotone or very smooth. Both the frequency and amplitude of the oscillations need to be accurately handled by the numerical schemes. Most of the reasoning and specific building blocks introduced in the forthcoming text can be reused to construct sound methods for partial differential equations of wave nature in multiple spatial dimensions.

**hpl 1:** Need to discuss errors also for the damped and nonlinear models. At least the frequency errors must be illustrated here as well and investigated numerically, either in text or exercises.

## 1 Finite difference discretization

Many of the numerical challenges faced when computing oscillatory solutions to ODEs and PDEs can be captured by the very simple ODE  $u'' + u = 0$ . This ODE is thus chosen as our starting point for method development, implementation, and analysis.

### 1.1 A basic model for vibrations

The simplest model of a vibrating mechanical system has the following form:

$$u'' + \omega^2 u = 0, \quad u(0) = I, \quad u'(0) = 0, \quad t \in (0, T]. \quad (1)$$

Here,  $\omega$  and  $I$  are given constants. Section 10.1 derives (1) from physical principles and explains what the constants mean.

The exact solution of (1) is

$$u(t) = I \cos(\omega t). \quad (2)$$

That is,  $u$  oscillates with constant amplitude  $I$  and angular frequency  $\omega$ . The corresponding period of oscillations (i.e., the time between two neighboring peaks in the cosine function) is  $P = 2\pi/\omega$ . The number of periods per second is  $f = \omega/(2\pi)$  and measured in the unit Hz. Both  $f$  and  $\omega$  are referred to as frequency, but  $\omega$  is more precisely named *angular frequency*, measured in rad/s.

In vibrating mechanical systems modeled by (1),  $u(t)$  very often represents a position or a displacement of a particular point in the system. The derivative  $u'(t)$  then has the interpretation of velocity, and  $u''(t)$  is the associated acceleration. The model (1) is not only applicable to vibrating mechanical systems, but also to oscillations in electrical circuits.

## 1.2 A centered finite difference scheme

To formulate a finite difference method for the model problem (1) we follow the four steps explained in Section 1.1.2 in [1].

**Step 1: Discretizing the domain.** The domain is discretized by introducing a uniformly partitioned time mesh. The points in the mesh are  $t_n = n\Delta t$ ,  $n = 0, 1, \dots, N_t$ , where  $\Delta t = T/N_t$  is the constant length of the time steps. We introduce a mesh function  $u^n$  for  $n = 0, 1, \dots, N_t$ , which approximates the exact solution at the mesh points. The mesh function will be computed from algebraic equations derived from the differential equation problem.

**Step 2: Fulfilling the equation at discrete time points.** The ODE is to be satisfied at each mesh point:

$$u''(t_n) + \omega^2 u(t_n) = 0, \quad n = 1, \dots, N_t. \quad (3)$$

**Step 3: Replacing derivatives by finite differences.** The derivative  $u''(t_n)$  is to be replaced by a finite difference approximation. A common second-order accurate approximation to the second-order derivative is

$$u''(t_n) \approx \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2}. \quad (4)$$

Inserting (4) in (3) yields

$$\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} = -\omega^2 u^n. \quad (5)$$

We also need to replace the derivative in the initial condition by a finite difference. Here we choose a centered difference, whose accuracy is similar to the centered difference we used for  $u''$ :

$$\frac{u^1 - u^{-1}}{2\Delta t} = 0. \quad (6)$$

**Step 4: Formulating a recursive algorithm.** To formulate the computational algorithm, we assume that we have already computed  $u^{n-1}$  and  $u^n$  such that  $u^{n+1}$  is the unknown value, which we can readily solve for:

$$u^{n+1} = 2u^n - u^{n-1} - \Delta t^2 \omega^2 u^n. \quad (7)$$

The computational algorithm is simply to apply (7) successively for  $n = 1, 2, \dots, N_t - 1$ . This numerical scheme sometimes goes under the name Störmer's method or Verlet integration<sup>1</sup>.

---

<sup>1</sup>[http://en.wikipedia.org/wiki/Verlet\\_integration](http://en.wikipedia.org/wiki/Verlet_integration)

**Computing the first step.** We observe that (7) cannot be used for  $n = 0$  since the computation of  $u^1$  then involves the undefined value  $u^{-1}$  at  $t = -\Delta t$ . The discretization of the initial condition then comes to our rescue: (6) implies  $u^{-1} = u^1$  and this relation can be combined with (7) for  $n = 0$  to yield a value for  $u^1$ :

$$u^1 = 2u^0 - u^1 - \Delta t^2 \omega^2 u^0,$$

which reduces to

$$u^1 = u^0 - \frac{1}{2} \Delta t^2 \omega^2 u^0. \quad (8)$$

Exercise 5 asks you to perform an alternative derivation and also to generalize the initial condition to  $u'(0) = V \neq 0$ .

**The computational algorithm.** The steps for solving (1) become

1.  $u^0 = I$
2. compute  $u^1$  from (8)
3. for  $n = 1, 2, \dots, N_t - 1$ : compute  $u^{n+1}$  from (7)

The algorithm is more precisely expressed directly in Python:

```
t = linspace(0, T, Nt+1) # mesh points in time
dt = t[1] - t[0]         # constant time step
u = zeros(Nt+1)          # solution

u[0] = I
u[1] = u[0] - 0.5*dt**2*w**2*u[0]
for n in range(1, Nt):
    u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n]
```

**Remark on using  $w$  for  $\omega$  in computer code.**

In the code, we use  $w$  as the symbol for  $\omega$ . The reason is that the authors prefer  $w$  for readability and comparison with the mathematical  $\omega$  instead of the full word **omega** as variable name.

**Operator notation.** We may write the scheme using a compact difference notation (see also Section 1.1.8 in [1]). The difference (4) has the operator notation  $[D_t D_t u]^n$  such that we can write:

$$[D_t D_t u + \omega^2 u = 0]^n. \quad (9)$$

Note that  $[D_t D_t u]^n$  means applying a central difference with step  $\Delta t/2$  twice:

$$[D_t(D_t u)]^n = \frac{[D_t u]^{n+\frac{1}{2}} - [D_t u]^{n-\frac{1}{2}}}{\Delta t}$$

which is written out as

$$\frac{1}{\Delta t} \left( \frac{u^{n+1} - u^n}{\Delta t} - \frac{u^n - u^{n-1}}{\Delta t} \right) = \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2}.$$

The discretization of initial conditions can in the operator notation be expressed as

$$[u = I]^0, \quad [D_{2t} u = 0]^0, \quad (10)$$

where the operator  $[D_{2t} u]^n$  is defined as

$$[D_{2t} u]^n = \frac{u^{n+1} - u^{n-1}}{2\Delta t}. \quad (11)$$

## 2 Implementation

### 2.1 Making a solver function

The algorithm from the previous section is readily translated to a complete Python function for computing and returning  $u^0, u^1, \dots, u^{N_t}$  and  $t_0, t_1, \dots, t_{N_t}$ , given the input  $I, \omega, \Delta t$ , and  $T$ :

```
import numpy as np
import matplotlib.pyplot as plt

def solver(I, w, dt, T):
    """
    Solve u'' + w**2*u = 0 for t in (0,T], u(0)=I and u'(0)=0,
    by a central finite difference method with time step dt.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)

    u[0] = I
    u[1] = u[0] - 0.5*dt**2*w**2*u[0]
    for n in range(1, Nt):
        u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n]
    return u, t
```

We have imported `numpy` and `matplotlib` under the names `np` and `plt`, respectively, as this is very common in the Python scientific computing community and a good programming habit (since we explicitly see where the different functions come from). An alternative is to do `from numpy import *` and a similar “import all” for Matplotlib to avoid the `np` and `plt` prefixes and make the code as close as possible to MATLAB. (See Section 5.1.4 in [1] for a discussion of the two types of import in Python.)

A function for plotting the numerical and the exact solution is also convenient to have:

```

def u_exact(t, I, w):
    return I*np.cos(w*t)

def visualize(u, t, I, w):
    plt.plot(t, u, 'r--o')
    t_fine = np.linspace(0, t[-1], 1001) # very fine mesh for u_e
    u_e = u_exact(t_fine, I, w)
    plt.hold('on')
    plt.plot(t_fine, u_e, 'b-')
    plt.legend(['numerical', 'exact'], loc='upper left')
    plt.xlabel('t')
    plt.ylabel('u')
    dt = t[1] - t[0]
    plt.title('dt=%g' % dt)
    umin = 1.2*u.min(); umax = -umin
    plt.axis([t[0], t[-1], umin, umax])
    plt.savefig('tmp1.png'); plt.savefig('tmp1.pdf')

```

A corresponding main program calling these functions to simulate a given number of periods (`num_periods`) may take the form

```

I = 1
w = 2*pi
dt = 0.05
num_periods = 5
P = 2*pi/w # one period
T = P*num_periods
u, t = solver(I, w, dt, T)
visualize(u, t, I, w, dt)

```

Adjusting some of the input parameters via the command line can be handy. Here is a code segment using the `ArgumentParser` tool in the `argparse` module to define option value (`-option value`) pairs on the command line:

```

import argparse
parser = argparse.ArgumentParser()
parser.add_argument('--I', type=float, default=1.0)
parser.add_argument('--w', type=float, default=2*pi)
parser.add_argument('--dt', type=float, default=0.05)
parser.add_argument('--num_periods', type=int, default=5)
a = parser.parse_args()
I, w, dt, num_periods = a.I, a.w, a.dt, a.num_periods

```

Such parsing of the command line is explained in more detail in Section 5.2.3 in [1].

A typical execution goes like

---

Terminal

---

```
Terminal> python vib_undamped.py --num_periods 20 --dt 0.1
```

---

**Computing  $u'$ .** In mechanical vibration applications one is often interested in computing the velocity  $v(t) = u'(t)$  after  $u(t)$  has been computed. This can be done by a central difference,

$$v(t_n) = u'(t_n) \approx v^n = \frac{u^{n+1} - u^{n-1}}{2\Delta t} = [D_{2t}u]^n. \quad (12)$$

This formula applies for all inner mesh points,  $n = 1, \dots, N_t - 1$ . For  $n = 0$ ,  $v(0)$  is given by the initial condition on  $u'(0)$ , and for  $n = N_t$  we can use a one-sided, backward difference:

$$v^n = [D_t^- u]^n = \frac{u^n - u^{n-1}}{\Delta t}.$$

Typical (scalar) code is

```
v = np.zeros_like(u) # or v = np.zeros(len(u))
# Use central difference for internal points
for i in range(1, len(u)-1):
    v[i] = (u[i+1] - u[i-1])/(2*dt)
# Use initial condition for u'(0) when i=0
v[0] = 0
# Use backward difference at the final mesh point
v[-1] = (u[-1] - u[-2])/dt
```

Since the loop is slow for large  $N_t$ , we can get rid of the loop by vectorizing the central difference. The above code segment goes as follows in its vectorized version (see Problem 1.2 in [1] for explanation of details):

```
v = np.zeros_like(u)
v[1:-1] = (u[2:] - u[:-2])/(2*dt) # central difference
v[0] = 0 # boundary condition u'(0)
v[-1] = (u[-1] - u[-2])/dt # backward difference
```

## 2.2 Verification

**Manual calculation.** The simplest type of verification, which is also instructive for understanding the algorithm, is to compute  $u^1$ ,  $u^2$ , and  $u^3$  with the aid of a calculator and make a function for comparing these results with those from the `solver` function. The `test_three_steps` function in the file `vib_undamped.py`<sup>2</sup> shows the details of how we use the hand calculations to test the code:

```
def test_three_steps():
    from math import pi
    I = 1; w = 2*pi; dt = 0.1; T = 1
    u_by_hand = np.array([1.0000000000000000,
                          0.802607911978213,
                          0.288358920740053])
    u, t = solver(I, w, dt, T)
    diff = np.abs(u_by_hand - u[:3]).max()
    tol = 1E-14
    assert diff < tol
```

This function is a proper *test function*, compliant with the `pytest` and `nose` testing framework for Python code, because

<sup>2</sup>[http://tinyurl.com/nm5587k/vib/vib\\_undamped.py](http://tinyurl.com/nm5587k/vib/vib_undamped.py)



- the function name begins with `test_`
- the function takes no arguments
- the test is formulated as a boolean condition and executed by `assert`

See Section 5.3.2 in [1] for more details on how to construct test functions and utilize nose or pytest for automatic execution of tests. Our recommendation is to use pytest and run all test functions in `vib_undamped.py` by

---

Terminal

---

```
Terminal> py.test -s -v vib_undamped.py
===== test session starts =====...
platform linux2 -- Python 2.7.9 -- ...
collected 2 items

vib_undamped.py::test_three_steps PASSED
vib_undamped.py::test_convergence_rates PASSED

===== 2 passed in 0.19 seconds ===...
```

---

**Testing very simple polynomial solutions.** Constructing test problems where the exact solution is constant or linear helps initial debugging and verification as one expects any reasonable numerical method to reproduce such solutions to machine precision. Second-order accurate methods will often also reproduce a quadratic solution. Here  $[D_t D_t t^2]^n = 2$ , which is the exact result. A solution  $u = t^2$  leads to  $u'' + \omega^2 u = 2 + (\omega t)^2 \neq 0$ . We must therefore add a source in the equation:  $u'' + \omega^2 u = f$  to allow a solution  $u = t^2$  for  $f = 2 + (\omega t)^2$ . By simple insertion we can show that the mesh function  $u^n = t_n^2$  is also a solution of the discrete equations. Problem 1 asks you to carry out all details to show that linear and quadratic solutions are solutions of the discrete equations. Such results are very useful for debugging and verification. You are strongly encouraged to do this problem now!

**Checking convergence rates.** Empirical computation of convergence rates yields a good method for verification. The method and its computational details are explained in detail in Section 3.1.6 in [1]. Readers not familiar with the concept should look up this reference before proceeding.

In the present problem, computing convergence rates means that we must

- perform  $m$  simulations, halving the time steps as:  $\Delta t_i = 2^{-i} \Delta t_0$ ,  $i = 0, \dots, m-1$ ,
- compute the  $L^2$  norm of the error,  $E_i = \sqrt{\Delta t_i \sum_{n=0}^{N_t-1} (u^n - u_e(t_n))^2}$  in each case,

- estimate the convergence rates  $r_i$  based on two consecutive experiments  $(\Delta t_{i-1}, E_{i-1})$  and  $(\Delta t_i, E_i)$ , assuming  $E_i = C(\Delta t_i)^r$  and  $E_{i-1} = C(\Delta t_{i-1})^r$ . From these equations it follows that  $r = \ln(E_{i-1}/E_i) / \ln(\Delta t_{i-1}/\Delta t_i)$ . Since this  $r$  will vary with  $i$ , we equip it with an index and call it  $r_{i-1}$ , where  $i$  runs from 1 to  $m - 1$ .

The computed rates  $r_0, r_1, \dots, r_{m-2}$  hopefully converge to the number 2 in the present problem, because theory (from Section 4) shows that the error of the numerical method we use behaves like  $\Delta t^2$ . The convergence of the sequence of rates  $r_0, r_1, \dots, r_{m-2}$  demands that the time steps  $\Delta t_i$  are sufficiently small for the error model  $E_i = C(\Delta t_i)^r$  to be valid.

All the implementational details of computing the sequence  $r_0, r_1, \dots, r_{m-2}$  appear below.

```
def convergence_rates(m, solver_function, num_periods=8):
    """
    Return m-1 empirical estimates of the convergence rate
    based on m simulations, where the time step is halved
    for each simulation.
    solver_function(I, w, dt, T) solves each problem, where T
    is based on simulation for num_periods periods.
    """
    from math import pi
    w = 0.35; I = 0.3          # just chosen values
    P = 2*pi/w                 # period
    dt = P/30                  # 30 time step per period 2*pi/w
    T = P*num_periods

    dt_values = []
    E_values = []
    for i in range(m):
        u, t = solver_function(I, w, dt, T)
        u_e = u_exact(t, I, w)
        E = np.sqrt(dt*np.sum((u_e-u)**2))
        dt_values.append(dt)
        E_values.append(E)
        dt = dt/2

    r = [np.log(E_values[i-1]/E_values[i])/
          np.log(dt_values[i-1]/dt_values[i])
          for i in range(1, m, 1)]
    return r
```

The error analysis in Section 4 is quite detailed and results in  $r = 2$ , but other methods like truncation error analysis also points to  $r = 2$ , as well as the related quick reasoning that we have used a second-order accurate finite difference approximation  $[D_t D_t u]^n$  to the ODE and a second-order accurate finite difference formula for the initial condition for  $u'$ .

In the present problem, when  $\Delta t_0$  corresponds to 30 time steps per period, the returned `r` list has all its values equal to 2.00 (if rounded to two decimals). This amazingly accurate result means that all  $\Delta t_i$  values are well into the asymptotic regime where the error model  $E_i = C(\Delta t_i)^r$  is valid.

We can now construct a proper test function that computes convergence rates and checks that the final (and usually the best) estimate is sufficiently close to 2. Here, a rough tolerance of 0.1 is enough. This unit test goes like

```
def test_convergence_rates():
    r = convergence_rates(m=5, solver_function=solver, num_periods=8)
    # Accept rate to 1 decimal place
    tol = 0.1
    assert abs(r[-1] - 2.0) < tol
```

The complete code appears in the file `vib_undamped.py`.

### 2.3 Scaled model

It is advantageous to use dimensionless variables in simulations, because fewer parameters need to be set. The present problem is made dimensionless by introducing dimensionless variables  $\bar{t} = t/t_c$  and  $\bar{u} = u/u_c$ , where  $t_c$  and  $u_c$  are characteristic scales for  $t$  and  $u$ , respectively. We refer to Section ?? in [2] for all details about this scaling.

The scaled ODE problem reads

$$\frac{u_c}{t_c^2} \frac{d^2 \bar{u}}{d\bar{t}^2} + u_c \bar{u} = 0, \quad u_c \bar{u}(0) = I, \quad \frac{u_c}{t_c} \frac{d\bar{u}}{d\bar{t}}(0) = 0.$$

A common choice is to take  $t_c$  as one period of the oscillations,  $t_c = 2\pi/\omega$ , and  $u_c = I$ . This gives the dimensionless model

$$\frac{d^2 \bar{u}}{d\bar{t}^2} + 4\pi^2 \bar{u} = 0, \quad \bar{u}(0) = 1, \quad \bar{u}'(0) = 0. \quad (13)$$

Observe that there are no physical parameters in (13)! We can therefore perform a single numerical simulation  $\bar{u}(\bar{t})$  and afterwards recover any  $u(t; \omega, I)$  by

$$u(t; \omega, I) = u_c \bar{u}(t/t_c) = I \bar{u}(\omega t / (2\pi)).$$

We can easily check this assertion: the solution of the scaled problem is  $\bar{u}(\bar{t}) = \cos(2\pi\bar{t})$ . The formula for  $u$  in terms of  $\bar{u}$  gives  $u = I \cos(\omega t)$ , which is nothing but the solution of the original problem with dimensions.

The scaled model can be run by calling `solver(I=1, w=2*pi, dt, T)`. Each period is now 1 and `T` simply counts the number of periods. Choosing `dt` as  $1./M$  gives `M` time steps per period.

## 3 Long time simulations

Figure 1 shows a comparison of the exact and numerical solution for the scaled model (13) with  $\Delta t = 0.1, 0.05$ . From the plot we make the following observations:

- The numerical solution seems to have correct amplitude.
- There is a angular frequency error which is reduced by reducing the time step.
- The total angular frequency error grows with time.

By angular frequency error we mean that the numerical angular frequency differs from the exact  $\omega$ . This is evident by looking at the peaks of the numerical solution: these have incorrect positions compared with the peaks of the exact cosine solution. The effect can be mathematically expressed by writing the numerical solution as  $I \cos \tilde{\omega} t$ , where  $\tilde{\omega}$  is not exactly equal to  $\omega$ . Later, we shall mathematically quantify this numerical angular frequency  $\tilde{\omega}$ .




Figure 1: Effect of halving the time step.

### 3.1 Using a moving plot window

In vibration problems it is often of interest to investigate the system's behavior over long time intervals. Errors in the angular frequency accumulate and become more visible as time grows. We can investigate long time series by introducing a moving plot window that can move along with the  $p$  most recently computed periods of the solution. The SciTools<sup>3</sup> package contains a convenient tool for this: `MovingPlotWindow`. Typing `pydoc scitools.MovingPlotWindow` shows a demo and a description of its use. The function below utilizes the moving plot window and is in fact called by the `main` function the `vib_undamped` module if the number of periods in the simulation exceeds 10.

```
def visualize_front(u, t, I, w, savefig=False, skip_frames=1):
    """
    Visualize u and the exact solution vs t, using a
    moving plot window and continuous drawing of the
    curves as they evolve in time.
    Makes it easy to plot very long time series.
    Plots are saved to files if savefig is True.
    Only each skip_frames-th plot is saved (e.g., if
    skip_frame=10, only each 10th plot is saved to file;
    this is convenient if plot files corresponding to
    different time steps are to be compared).
    """
    import scitools.std as st
    from scitools.MovingPlotWindow import MovingPlotWindow
    from math import pi
```

<sup>3</sup><https://github.com/hplgit/scitools>

```

# Remove all old plot files tmp_*.png
import glob, os
for filename in glob.glob('tmp_*.png'):
    os.remove(filename)

P = 2*pi/w # one period
umin = 1.2*u.min(); umax = -umin
dt = t[1] - t[0]
plot_manager = MovingPlotWindow(
    window_width=8*P,
    dt=dt,
    yaxis=[umin, umax],
    mode='continuous drawing')
frame_counter = 0
for n in range(1,len(u)):
    if plot_manager.plot(n):
        s = plot_manager.first_index_in_plot
        st.plot(t[s:n+1], u[s:n+1], 'r-1',
            t[s:n+1], I*cos(w*t)[s:n+1], 'b-1',
            title='t=%6.3f' % t[n],
            axis=plot_manager.axis(),
            show=not savefig) # drop window if savefig
        if savefig and n % skip_frames == 0:
            filename = 'tmp_%04d.png' % frame_counter
            st.savefig(filename)
            print 'making plot file', filename, 'at t=%g' % t[n]
            frame_counter += 1
        plot_manager.update(n)

```

We run the scaled problem (the default values for the command-line arguments `-I` and `-w` correspond to the scaled problem) for 40 periods with 20 time steps per period:

---

```

Terminal
Terminal> python vib_undamped.py --dt 0.05 --num_periods 40

```

---

The moving plot window is invoked, and we can follow the numerical and exact solutions as time progresses. From this demo we see that the angular frequency error is small in the beginning, but it becomes more prominent with time. A new run with  $\Delta t = 0.1$  (i.e., only 10 time steps per period) clearly shows that the phase errors become significant even earlier in the time series, deteriorating the solution further.

## 3.2 Making animations

**Producing standard video formats.** The `visualize_front` function stores all the plots in files whose names are numbered: `tmp_0000.png`, `tmp_0001.png`, `tmp_0002.png`, and so on. From these files we may make a movie. The Flash format is popular,

---

```

Terminal
Terminal> ffmpeg -r 12 -i tmp_%04d.png -c:v flv movie.flv

```

---

The `ffmpeg` program can be replaced by the `avconv` program in the above command if desired (but at the time of this writing it seems to be more momentum in the `ffmpeg` project). The `-r` option should come first and describes the number of frames per second in the movie. The `-i` option describes the name of the plot files. Other formats can be generated by changing the video codec and equipping the video file with the right extension:

Format	Codec and filename
Flash	<code>-c:v flv movie.flv</code>
MP4	<code>-c:v libx264 movie.mp4</code>
WebM	<code>-c:v libvpx movie.webm</code>
Ogg	<code>-c:v libtheora movie.ogg</code>

The video file can be played by some video player like `vlc`, `mplayer`, `gxine`, or `totem`, e.g.,

---

Terminal

---

```
Terminal> vlc movie.webm
```

---

A web page can also be used to play the movie. Today's standard is to use the HTML5 video tag:

```
<video autoplay loop controls
      width='640' height='365' preload='none'>
<source src='movie.webm' type='video/webm; codecs="vp8, vorbis"'>
</video>
```

Modern browsers do not support all of the video formats. MP4 is needed to successfully play the videos on Apple devices that use the Safari browser. WebM is the preferred format for Chrome, Opera, Firefox, and Internet Explorer v9+. Flash was a popular format, but older browsers that required Flash can play MP4. All browsers that work with Ogg can also work with WebM. This means that to have a video work in all browsers, the video should be available in the MP4 and WebM formats. The proper HTML code reads

```
<video autoplay loop controls
      width='640' height='365' preload='none'>
<source src='movie.mp4' type='video/mp4;
      codecs="avc1.42E01E, mp4a.40.2"'>
<source src='movie.webm' type='video/webm;
      codecs="vp8, vorbis"'>
</video>
```

The MP4 format should appear first to ensure that Apple devices will load the video correctly.

**Caution: number the plot files correctly.**

To ensure that the individual plot frames are shown in correct order, it is important to number the files with zero-padded numbers (0000, 0001, 0002, etc.). The printf format `%04d` specifies an integer in a field of width 4, padded with zeros from the left. A simple Unix wildcard file specification like `tmp_*.png` will then list the frames in the right order. If the numbers in the filenames were not zero-padded, the frame `tmp_11.png` would appear before `tmp_2.png` in the movie.

**Paying PNG files in a web browser.** The `scitools movie` command can create a movie player for a set of PNG files such that a web browser can be used to watch the movie. This interface has the advantage that the speed of the movie can easily be controlled, a feature that scientists often appreciate. The command for creating an HTML with a player for a set of PNG files `tmp_*.png` goes like

---

Terminal

---

```
Terminal> scitools movie output_file=vib.html fps=4 tmp_*.png
```

---

The `fps` argument controls the speed of the movie (“frames per second”). To watch the movie, load the video file `vib.html` into some browser, e.g.,

---

Terminal

---

```
Terminal> google-chrome vib.html # invoke web page
```

---

Clicking on **Start movie** to see the result. Moving this movie to some other place requires moving `vib.html` *and all the PNG files* `tmp_*.png`:

---

Terminal

---

```
Terminal> mkdir vib_dt0.1
Terminal> mv tmp_*.png vib_dt0.1
Terminal> mv vib.html vib_dt0.1/index.html
```

---

**Making animated GIF files.** The `convert` program from the ImageMagick software suite can be used to produce animated GIF files from a set of PNG files:

---

Terminal

---

```
Terminal> convert -delay 25 tmp_vib*.png tmp_vib.gif
```

---

The `-delay` option needs an argument of the delay between each frame, measured in 1/100 s, so 4 frames/s here gives 25/100 s delay. Note, however, that in this particular example with  $\Delta t = 0.05$  and 40 periods, making an animated GIF file

out of the large number of PNG files is a very heavy process and not considered feasible. Animated GIFs are best suited for animations with not so many frames and where you want to see each frame and play them slowly.

**hpl 2:** Combine two simulations side by side!

### 3.3 Using Bokeh to compare graphs

Instead of a moving plot frame, one can use tools that allows panning by the mouse. For example, we can show four periods of several signals in several plots and then scroll with the mouse through the rest of the simulation *simultaneously* in all the plot windows. The Bokeh<sup>4</sup> plotting library offers such tools, but the plots must be displayed in a web browser. The documentation of Bokeh is excellent, so here we just show how the library can be used to compare a set of  $u$  curves corresponding to long time simulations. (By the way, the guidance to correct pronunciation of Bokeh in the documentation<sup>5</sup> and on Wikipedia<sup>6</sup> is not directly compatible with a YouTube video<sup>7</sup>...).

Imagine we have performed experiments for a set of  $\Delta t$  values. We want each curve, together with the exact solution, to appear in a plot, and then arrange all plots in a grid-like fashion:



Furthermore, we want the axes to couple such that if we move into the future in one plot, all the other plots follows (note the displaced  $t$  axes!):


<sup>4</sup><http://bokeh.pydata.org/en/latest/docs/quickstart.html>

<sup>5</sup><http://bokeh.pydata.org/en/0.10.0/docs/faq.html#how-do-you-pronounce-bokeh>

<sup>6</sup><https://en.wikipedia.org/wiki/Bokeh>

<sup>7</sup><https://www.youtube.com/watch?v=OR8HSHevQTM>





A function for creating a Bokeh plot, given a list of  $u$  arrays and corresponding  $t$  arrays, from different simulations, described compactly in a list of strings  $legends$ , is implemented below.

```
def bokeh_plot(u, t, legends, I, w, t_range, filename):
    """
    Make plots for u vs t using the Bokeh library.
    u and t are lists (several experiments can be compared).
    legends contain legend strings for the various u,t pairs.
    """
    if not isinstance(u, (list,tuple)):
        u = [u] # wrap in list
    if not isinstance(t, (list,tuple)):
        t = [t] # wrap in list
    if not isinstance(legends, (list,tuple)):
        legends = [legends] # wrap in list

    import bokeh.plotting as plt
    plt.output_file(filename, mode='cdn', title='Comparison')
    # Assume that all t arrays have the same range
    t_fine = np.linspace(0, t[0][-1], 1001) # fine mesh for u_e
    tools = 'pan,wheel_zoom,box_zoom,reset,'\
            'save,box_select,lasso_select'
    u_range = [-1.2*I, 1.2*I]
    font_size = '8pt'
    p = [] # list of plot objects
    # Make the first figure
    p_ = plt.figure(
        width=300, plot_height=250, title=legends[0],
        x_axis_label='t', y_axis_label='u',
        x_range=t_range, y_range=u_range, tools=tools,
        title_text_font_size=font_size)
    p_.axis.axis_label_text_font_size=font_size
    p_.yaxis.axis_label_text_font_size=font_size
    p_.line(t[0], u[0], line_color='blue')
    # Add exact solution
    u_e = u_exact(t_fine, I, w)
    p_.line(t_fine, u_e, line_color='red', line_dash='4 4')
    p.append(p_)
    # Make the rest of the figures and attach their axes to
```

```

# the first figure's axes
for i in range(1, len(t)):
    p_ = plt.figure(
        width=300, plot_height=250, title=legends[i],
        x_axis_label='t', y_axis_label='u',
        x_range=p[0].x_range, y_range=p[0].y_range, tools=tools,
        title_text_font_size=font_size)
    p_.axis(axis_label_text_font_size = font_size)
    p_.yaxis(axis_label_text_font_size = font_size)
    p_.line(t[i], u[i], line_color='blue')
    p_.line(t_fine, u_e, line_color='red', line_dash='4 4')
    p.append(p_)

# Arrange all plots in a grid with 3 plots per row
grid = [[]]
for i, p_ in enumerate(p):
    grid[-1].append(p_)
    if (i+1) % 3 == 0:
        # New row
        grid.append([])
plot = plt.gridplot(grid, toolbar_location='left')
plt.save(plot)
plt.show(plot)

```

A particular example using the `bokeh_plot` function appears below.

```

def demo_bokeh():
    """Solve a scaled ODE  $u'' + u = 0$ ."""
    from math import pi
    w = 1.0 # Scaled problem (frequency)
    P = 2*np.pi/w # Period
    num_steps_per_period = [5, 10, 20, 40, 80]
    T = 40*P # Simulation time: 40 periods
    u = [] # List of numerical solutions
    t = [] # List of corresponding meshes
    legends = []
    for n in num_steps_per_period:
        dt = P/n
        u_, t_ = solver(I=1, w=w, dt=dt, T=T)
        u.append(u_)
        t.append(t_)
        legends.append('# time steps per period: %d' % n)
    bokeh_plot(u, t, legends, I=1, w=w, t_range=[0, 4*P],
               filename='tmp.html')

```

### 3.4 Using a line-by-line ascii plotter

Plotting functions vertically, line by line, in the terminal window using ascii characters only is a simple, fast, and convenient visualization technique for long time series. Note that the time axis then is positive downwards on the screen. The tool `scitools.avplotter.Plotter` makes it easy to create such plots:

```

def visualize_front_ascii(u, t, I, w, fps=10):
    """
    Plot u and the exact solution vs t line by line in a
    terminal window (only using ascii characters).
    Makes it easy to plot very long time series.
    """

```


```

from scitools.avplotter import Plotter
import time
from math import pi
P = 2*pi/w
umin = 1.2*u.min(); umax = -umin

p = Plotter(ymin=umin, ymax=umax, width=60, symbols='+o')
for n in range(len(u)):
    print p.plot(t[n], u[n], I*cos(w*t[n])), \
          '%.1f' % (t[n]/P)
    time.sleep(1/float(fps))

```

The call `p.plot` returns a line of text, with the  $t$  axis marked and a symbol `+` for the first function ( $u$ ) and `o` for the second function (the exact solution). Here we append to this text a time counter reflecting how many periods the current time point corresponds to. A typical output ( $\omega = 2\pi$ ,  $\Delta t = 0.05$ ) looks like this:



### 3.5 Empirical analysis of the solution

For oscillating functions like those in Figure 1 we may compute the amplitude and frequency (or period) empirically. That is, we run through the discrete solution points  $(t_n, u_n)$  and find all maxima and minima points. The distance between two consecutive maxima (or minima) points can be used as estimate of the local period, while half the difference between the  $u$  value at a maximum and a nearby minimum gives an estimate of the local amplitude.

The local maxima are the points where

$$u^{n-1} < u^n > u^{n+1}, \quad n = 1, \dots, N_t - 1, \quad (14)$$

and the local minima are recognized by

$$u^{n-1} > u^n < u^{n+1}, \quad n = 1, \dots, N_t - 1. \quad (15)$$

In computer code this becomes

```
def minmax(t, u):
    minima = []; maxima = []
    for n in range(1, len(u)-1, 1):
        if u[n-1] > u[n] < u[n+1]:
            minima.append((t[n], u[n]))
        if u[n-1] < u[n] > u[n+1]:
            maxima.append((t[n], u[n]))
    return minima, maxima
```

Note that the two returned objects are lists of tuples.

Let  $(t_i, e_i)$ ,  $i = 0, \dots, M - 1$ , be the sequence of all the  $M$  maxima points, where  $t_i$  is the time value and  $e_i$  the corresponding  $u$  value. The local period can be defined as  $p_i = t_{i+1} - t_i$ . With Python syntax this reads

```
def periods(maxima):
    p = [extrema[n][0] - maxima[n-1][0]
          for n in range(1, len(maxima))]
    return np.array(p)
```

The list `p` created by a list comprehension is converted to an array since we probably want to compute with it, e.g., find the corresponding frequencies  $2\pi/p$ .

Having the minima and the maxima, the local amplitude can be calculated as the difference between two neighboring minimum and maximum points:

```
def amplitudes(minima, maxima):
    a = [(abs(maxima[n][1] - minima[n][1]))/2.0
          for n in range(min(len(minima), len(maxima)))]
    return np.array(a)
```

The code segments are found in the file `vib_empirical_analysis.py`<sup>8</sup>.

Since `a[i]` and `p[i]` correspond to the  $i$ -th amplitude estimate and the  $i$ -th period estimate, respectively, it is most convenient to visualize the `a` and `p` values with the index `i` on the horizontal axis. (There is no unique time point associated with either of these estimate since values at two different time points were used in the computations.)

In the analysis of very long time series, it is advantageous to compute and plot `p` and `a` instead of  $u$  to get an impression of the development of the oscillations. Let us do this for the scaled problem and  $\Delta t = 0.1, 0.05, 0.01$ . A ready-made function

```
plot_empirical_freq_and_amplitude(u, t, I, w)
```

computes the empirical amplitudes and periods, and creates a plot where the amplitudes and angular frequencies are visualized together with the exact amplitude `I` and the exact angular frequency `w`. We can make a little program for creating the plot:

---

<sup>8</sup>[http://tinyurl.com/nm5587k/vib/vib\\_empirical\\_analysis.py](http://tinyurl.com/nm5587k/vib/vib_empirical_analysis.py)

```

from vib_undamped import solver, plot_empirical_freq_and_amplitude
from math import pi
dt_values = [0.1, 0.05, 0.01]
u_cases = []
t_cases = []
for dt in dt_values:
    # Simulate scaled problem for 40 periods
    u, t = solver(I=1, w=2*pi, dt=dt, T=40)
    u_cases.append(u)
    t_cases.append(t)
plot_empirical_freq_and_amplitude(u_cases, t_cases, I=1, w=2*pi)

```

Figure 2 shows the result: we clearly see that lowering  $\Delta t$  improves the angular frequency significantly, while the amplitude seems to be more accurate. The lines with  $\Delta t = 0.01$ , corresponding to 100 steps per period, can hardly be distinguished from the exact values. The next section shows how we can get mathematical insight into why amplitudes are good and frequencies are more inaccurate.



Figure 2: Empirical amplitude and angular frequency for three cases of time steps.

## 4 Analysis of the numerical scheme

### 4.1 Deriving a solution of the numerical scheme

After having seen the phase error grow with time in the previous section, we shall now quantify this error through mathematical analysis. The key tool in the analysis will be to establish an exact solution of the discrete equations. The difference equation (7) has constant coefficients and is homogeneous. Such equations are known to have solutions on the form  $u^n = CA^n$ , where  $A$  is some number to be determined from the difference equation and  $C$  is found as the initial condition ( $C = I$ ). Recall that  $n$  in  $u^n$  is a superscript labeling the time level, while  $n$  in  $A^n$  is an exponent.

With oscillating functions as solutions, the algebra will be considerably simplified if we seek an  $A$  on the form

$$A = e^{i\tilde{\omega}\Delta t},$$

and solve for the numerical frequency  $\tilde{\omega}$  rather than  $A$ . Note that  $i = \sqrt{-1}$  is the imaginary unit. (Using a complex exponential function gives simpler arithmetics than working with a sine or cosine function.) We have

$$A^n = e^{i\tilde{\omega}\Delta t n} = e^{i\tilde{\omega}t_n} = \cos(\tilde{\omega}t_n) + i \sin(\tilde{\omega}t_n).$$

The physically relevant numerical solution can be taken as the real part of this complex expression.

The calculations go as

$$\begin{aligned} [D_t D_t u]^n &= \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} \\ &= I \frac{A^{n+1} - 2A^n + A^{n-1}}{\Delta t^2} \\ &= \frac{I}{\Delta t^2} (e^{i\tilde{\omega}(t_n+\Delta t)} - 2e^{i\tilde{\omega}t_n} + e^{i\tilde{\omega}(t_n-\Delta t)}) \\ &= I e^{i\tilde{\omega}t_n} \frac{1}{\Delta t^2} (e^{i\tilde{\omega}\Delta t} + e^{i\tilde{\omega}(-\Delta t)} - 2) \\ &= I e^{i\tilde{\omega}t_n} \frac{2}{\Delta t^2} (\cosh(i\tilde{\omega}\Delta t) - 1) \\ &= I e^{i\tilde{\omega}t_n} \frac{2}{\Delta t^2} (\cos(\tilde{\omega}\Delta t) - 1) \\ &= -I e^{i\tilde{\omega}t_n} \frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) \end{aligned}$$

The last line follows from the relation  $\cos x - 1 = -2 \sin^2(x/2)$  (try `cos(x)-1` in [wolframalpha.com](http://www.wolframalpha.com)<sup>9</sup> to see the formula).

The scheme (7) with  $u^n = I e^{i\tilde{\omega}\Delta t n}$  inserted now gives

$$-I e^{i\tilde{\omega}t_n} \frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) + \omega^2 I e^{i\tilde{\omega}t_n} = 0, \quad (16)$$

which after dividing by  $I e^{i\tilde{\omega}t_n}$  results in

$$\frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = \omega^2. \quad (17)$$

The first step in solving for the unknown  $\tilde{\omega}$  is

$$\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = \left(\frac{\omega\Delta t}{2}\right)^2.$$

Then, taking the square root, applying the inverse sine function, and multiplying by  $2/\Delta t$ , results in

$$\tilde{\omega} = \pm \frac{2}{\Delta t} \sin^{-1}\left(\frac{\omega\Delta t}{2}\right). \quad (18)$$

---

<sup>9</sup><http://www.wolframalpha.com>

The first observation of (18) tells that there is a phase error since the numerical frequency  $\tilde{\omega}$  never equals the exact frequency  $\omega$ . But how good is the approximation (18)? That is, what is the error  $\omega - \tilde{\omega}$  or  $\tilde{\omega}/\omega$ ? Taylor series expansion for small  $\Delta t$  may give an expression that is easier to understand than the complicated function in (18):

```
>>> from sympy import *
>>> dt, w = symbols('dt w')
>>> w_tilde_e = 2/dt*asin(w*dt/2)
>>> w_tilde_series = w_tilde_e.series(dt, 0, 4)
>>> print w_tilde_series
w + dt**2*w**3/24 + O(dt**4)
```

This means that

$$\tilde{\omega} = \omega \left( 1 + \frac{1}{24} \omega^2 \Delta t^2 \right) + \mathcal{O}(\Delta t^4). \quad (19)$$

The error in the numerical frequency is of second-order in  $\Delta t$ , and the error vanishes as  $\Delta t \rightarrow 0$ . We see that  $\tilde{\omega} > \omega$  since the term  $\omega^3 \Delta t^2 / 24 > 0$  and this is by far the biggest term in the series expansion for small  $\omega \Delta t$ . A numerical frequency that is too large gives an oscillating curve that oscillates too fast and therefore “lags behind” the exact oscillations, a feature that can be seen in the left plot in Figure 1.

Figure 3 plots the discrete frequency (18) and its approximation (19) for  $\omega = 1$  (based on the program `vib_plot_freq.py`<sup>10</sup>). Although  $\tilde{\omega}$  is a function of  $\Delta t$  in (19), it is misleading to think of  $\Delta t$  as the important discretization parameter. It is the product  $\omega \Delta t$  that is the key discretization parameter. This quantity reflects the *number of time steps per period* of the oscillations. To see this, we set  $P = N_P \Delta t$ , where  $P$  is the length of a period, and  $N_P$  is the number of time steps during a period. Since  $P$  and  $\omega$  are related by  $P = 2\pi/\omega$ , we get that  $\omega \Delta t = 2\pi/N_P$ , which shows that  $\omega \Delta t$  is directly related to  $N_P$ .

The plot shows that at least  $N_P \sim 25 - 30$  points per period are necessary for reasonable accuracy, but this depends on the length of the simulation ( $T$ ) as the total phase error due to the frequency error grows linearly with time (see Exercise 2).

## 4.2 Exact discrete solution

Perhaps more important than the  $\tilde{\omega} = \omega + \mathcal{O}(\Delta t^2)$  result found above is the fact that we have an exact discrete solution of the problem:

$$u^n = I \cos(\tilde{\omega} n \Delta t), \quad \tilde{\omega} = \frac{2}{\Delta t} \sin^{-1} \left( \frac{\omega \Delta t}{2} \right). \quad (20)$$

We can then compute the error mesh function

$$e^n = u_e(t_n) - u^n = I \cos(\omega n \Delta t) - I \cos(\tilde{\omega} n \Delta t). \quad (21)$$

<sup>10</sup>[http://tinyurl.com/nm5587k/vib/vib\\_plot\\_freq.py](http://tinyurl.com/nm5587k/vib/vib_plot_freq.py)



Figure 3: Exact discrete frequency and its second-order series expansion.

From the formula  $\cos 2x - \cos 2y = -2 \sin(x - y) \sin(x + y)$  we can rewrite  $e^n$  so the expression is easier to interpret:

$$e^n = -2I \sin\left(t \frac{1}{2} (\omega - \tilde{\omega})\right) \sin\left(t \frac{1}{2} (\omega + \tilde{\omega})\right). \quad (22)$$

The error mesh function is ideal for verification purposes and you are strongly encouraged to make a test based on (20) by doing Exercise 10.

### 4.3 Convergence

We can use (19), (21), or (22) to show *convergence* of the numerical scheme, i.e.,  $e^n \rightarrow 0$  as  $\Delta t \rightarrow 0$ , which implies that the numerical solution approaches the exact solution as  $\Delta t$  approaches to zero. We have that

$$\lim_{\Delta t \rightarrow 0} \tilde{\omega} = \lim_{\Delta t \rightarrow 0} \frac{2}{\Delta t} \sin^{-1}\left(\frac{\omega \Delta t}{2}\right) = \omega,$$

by L'Hopital's rule. This result could also be computed WolframAlpha<sup>11</sup>, or we could use the limit functionality in `sympy`:

<sup>11</sup>[http://www.wolframalpha.com/input/?i=%282%2F%29\\*asin%28w\\*x%2F2%29+as+x-%3E0](http://www.wolframalpha.com/input/?i=%282%2F%29*asin%28w*x%2F2%29+as+x-%3E0)



```
>>> import sympy as sym
>>> dt, w = sym.symbols('x w')
>>> sym.limit((2/dt)*sym.asin(w*dt/2), dt, 0, dir='+')
w
```

Also (19) can be used to establish this result that  $\tilde{\omega} \rightarrow \omega$ . It then follows from the expression(s) for  $e^n$  that  $e^n \rightarrow 0$ .

#### 4.4 The global error

To achieve more analytical insight into the nature of the global error, we can Taylor expand the error mesh function (21). Since  $\tilde{\omega}$  in (18) contains  $\Delta t$  in the denominator we use the series expansion for  $\tilde{\omega}$  inside the cosine function. A relevant sympy session is

```
>>> from sympy import *
>>> dt, w, t = symbols('dt w t')
>>> w_tilde_e = 2/dt*asin(w*dt/2)
>>> w_tilde_series = w_tilde_e.series(dt, 0, 4)
>>> w_tilde_series
w + dt**2*w**3/24 + O(dt**4)
```

Series expansions in sympy have the inconvenient  $O()$  term that prevents further calculations with the series. We can use the `removeO()` command to get rid of the  $O()$  term:

```
>>> w_tilde_series = w_tilde_series.removeO()
>>> w_tilde_series
dt**2*w**3/24 + w
```

Using this `w_tilde_series` expression for  $\tilde{w}$  in (21), dropping  $I$  (which is a common factor), and performing a series expansion of the error yields

```
>>> error = cos(w*t) - cos(w_tilde_series*t)
>>> error.series(dt, 0, 6)
dt**2*t*w**3*sin(t*w)/24 + dt**4*t**2*w**6*cos(t*w)/1152 + O(dt**6)
```

Since we are mainly interested in the leading-order term in such expansions (the term with lowest power in  $\Delta t$ , which goes most slowly to zero), we use the `.as_leading_term(dt)` construction to pick out this term:

```
>>> error.series(dt, 0, 6).as_leading_term(dt)
dt**2*t*w**3*sin(t*w)/24
```

The last result means that the leading order global (true) error at a point  $t$  is proportional to  $\omega^3 t \Delta t^2$ . Considering only the discrete  $t_n$  values for  $t$ ,  $t_n$  is related to  $\Delta t$  through  $t_n = n \Delta t$ . The factor  $\sin(\omega t)$  can at most be 1, so we use this value to bound the leading-order expression to its maximum value

$$e^n = \frac{1}{24} n \omega^3 \Delta t^3.$$

This is the dominating term of the error *at a point*.

We are interested in the accumulated global error, which can be taken as the  $\ell^2$  norm of  $e^n$ . The norm is simply computed by summing contributions from all mesh points:

$$\|e^n\|_{\ell^2}^2 = \Delta t \sum_{n=0}^{N_t} \frac{1}{24^2} n^2 \omega^6 \Delta t^6 = \frac{1}{24^2} \omega^6 \Delta t^7 \sum_{n=0}^{N_t} n^2.$$

The sum  $\sum_{n=0}^{N_t} n^2$  is approximately equal to  $\frac{1}{3} N_t^3$ . Replacing  $N_t$  by  $T/\Delta t$  and taking the square root gives the expression

$$\|e^n\|_{\ell^2} = \frac{1}{24} \sqrt{\frac{T^3}{3}} \omega^3 \Delta t^2.$$

This is our expression for the global (or integrated) error. The main result from this expression is that the global error is proportional to  $\Delta t^2$ .

## 4.5 Stability

Looking at (20), it appears that the numerical solution has constant and correct amplitude, but an error in the angular frequency. A constant amplitude is not necessarily the case, however! To see this, note that if only  $\Delta t$  is large enough, the magnitude of the argument to  $\sin^{-1}$  in (18) may be larger than 1, i.e.,  $\omega \Delta t / 2 > 1$ . In this case,  $\sin^{-1}(\omega \Delta t / 2)$  has a complex value and therefore  $\tilde{\omega}$  becomes complex. Type, for example, `asin(x)` in `wolframalpha.com`<sup>12</sup> to see basic properties of  $\sin^{-1}(x)$ .

A complex  $\tilde{\omega}$  can be written  $\tilde{\omega} = \tilde{\omega}_r + i\tilde{\omega}_i$ . Since  $\sin^{-1}(x)$  has a *negative* imaginary part for  $x > 1$ ,  $\tilde{\omega}_i < 0$ , which means that  $e^{i\tilde{\omega}t} = e^{-\tilde{\omega}_i t} e^{i\tilde{\omega}_r t}$  will lead to exponential growth in time because  $e^{-\tilde{\omega}_i t}$  with  $\tilde{\omega}_i < 0$  has a positive exponent.

### Stability criterion.

We do not tolerate growth in the amplitude since such growth is not present in the exact solution. Therefore, we must impose a *stability criterion* so that the argument in the inverse sine function leads to real and not complex values of  $\tilde{\omega}$ . The stability criterion reads

$$\frac{\omega \Delta t}{2} \leq 1 \quad \Rightarrow \quad \Delta t \leq \frac{2}{\omega}. \quad (23)$$

With  $\omega = 2\pi$ ,  $\Delta t > \pi^{-1} = 0.3183098861837907$  will give growing solutions. Figure 4 displays what happens when  $\Delta t = 0.3184$ , which is slightly above the critical value:  $\Delta t = \pi^{-1} + 9.01 \cdot 10^{-5}$ .

<sup>12</sup><http://www.wolframalpha.com>



Figure 4: Growing, unstable solution because of a time step slightly beyond the stability limit.

#### 4.6 About the accuracy at the stability limit

An interesting question is whether the stability condition  $\Delta t < 2/\omega$  is unfortunate, or more precisely: would it be meaningful to take larger time steps to speed up computations? The answer is a clear no. At the stability limit, we have that  $\sin^{-1} \omega \Delta t / 2 = \sin^{-1} 1 = \pi/2$ , and therefore  $\tilde{\omega} = \pi / \Delta t$ . (Note that the approximate formula (19) is very inaccurate for this value of  $\Delta t$  as it predicts  $\tilde{\omega} = 2.34/\pi$ , which is a 25 percent reduction.) The corresponding period of the numerical solution is  $\tilde{P} = 2\pi / \tilde{\omega} = 2\Delta t$ , which means that there is just one time step  $\Delta t$  between a peak (maximum) and a through<sup>13</sup> (minimum) in the numerical solution. This is the shortest possible wave that can be represented in the mesh! In other words, it is not meaningful to use a larger time step than the stability limit.

Also, the error in angular frequency when  $\Delta t = 2/\omega$  is severe: Figure 5 shows a comparison of the numerical and analytical solution with  $\omega = 2\pi$  and  $\Delta t = 2/\omega = \pi^{-1}$ . Already after one period, the numerical solution has a through while the exact solution has a peak (!). The error in frequency when  $\Delta t$  is at the stability limit becomes  $\omega - \tilde{\omega} = \omega(1 - \pi/2) \approx -0.57\omega$ . The corresponding error in the period is  $P - \tilde{P} \approx 0.36P$ . The error after  $m$  periods is then  $0.36mP$ . This error has reached half a period when  $m = 1/(2 \cdot 0.36) \approx 1.38$ , which theoretically confirms the observations in Figure 5 that the numerical solution is a through

<sup>13</sup>[https://simple.wikipedia.org/wiki/Wave\\_\(physics\)](https://simple.wikipedia.org/wiki/Wave_(physics))

ahead of a peak already after one and a half period. Consequently,  $\Delta t$  should be chosen much less than the stability limit to achieve meaningful numerical computations.



Figure 5: Numerical solution with  $\Delta t$  exactly at the stability limit.

### Summary.

From the accuracy and stability analysis we can draw three important conclusions:

1. The key parameter in the formulas is  $p = \omega\Delta t$ . The period of oscillations is  $P = 2\pi/\omega$ , and the number of time steps per period is  $N_P = P/\Delta t$ . Therefore,  $p = \omega\Delta t = 2\pi/N_P$ , showing that the critical parameter is the number of time steps per period. The smallest possible  $N_P$  is 2, showing that  $p \in (0, \pi]$ .
2. Provided  $p \leq 2$ , the amplitude of the numerical solution is constant.
3. The ratio of the numerical angular frequency and the exact one is  $\tilde{\omega}/\omega \approx 1 + \frac{1}{24}p^2$ . The error  $\frac{1}{24}p^2$  leads to wrongly displaced peaks of the numerical solution, and the error in peak location grows linearly with time (see Exercise 2).

## 5 Alternative schemes based on 1st-order equations

A standard technique for solving second-order ODEs is to rewrite them as a system of first-order ODEs and then choose a solution strategy from the vast collection of methods for first-order ODE systems. Given the second-order ODE problem

$$u'' + \omega^2 u = 0, \quad u(0) = I, \quad u'(0) = 0,$$

we introduce the auxiliary variable  $v = u'$  and express the ODE problem in terms of first-order derivatives of  $u$  and  $v$ :

$$u' = v, \tag{24}$$

$$v' = -\omega^2 u. \tag{25}$$

The initial conditions become  $u(0) = I$  and  $v(0) = 0$ .

### 5.1 The Forward Euler scheme

A Forward Euler approximation to our  $2 \times 2$  system of ODEs (24)-(25) becomes

$$[D_t^+ u = v]^n, [D_t^+ v = -\omega^2 u]^n, \tag{26}$$

or written out,

$$u^{n+1} = u^n + \Delta t v^n, \tag{27}$$

$$v^{n+1} = v^n - \Delta t \omega^2 u^n. \tag{28}$$

Let us briefly compare this Forward Euler method with the centered difference scheme for the second-order differential equation. We have from (27) and (28) applied at levels  $n$  and  $n - 1$  that

$$u^{n+1} = u^n + \Delta t v^n = u^n + \Delta t (v^{n-1} - \Delta t \omega^2 u^{n-1}).$$

Since from (27)

$$v^{n-1} = \frac{1}{\Delta t} (u^n - u^{n-1}),$$

it follows that

$$u^{n+1} = 2u^n - u^{n-1} - \Delta t^2 \omega^2 u^{n-1},$$

which is very close to the centered difference scheme, but the last term is evaluated at  $t_{n-1}$  instead of  $t_n$ . Rewriting, so that  $\Delta t^2 \omega^2 u^{n-1}$  appears alone on the right-hand side, and then dividing by  $\Delta t^2$ , the new left-hand side is an approximation to  $u''$  at  $t_n$ , while the right-hand side is sampled at  $t_{n-1}$ . All terms should be sampled at the same mesh point, so using  $\omega^2 u^{n-1}$  instead of  $\omega^2 u^n$  points to a kind of mathematical error in the derivation of the scheme. This error turns out to be rather crucial for the accuracy of the Forward Euler method applied to vibration problems (Section 5.4 has examples).

The reasoning above does not imply that the Forward Euler scheme is not correct, but more that it is almost equivalent to a second-order accurate scheme for the second-order ODE formulation, and that the error committed has to do with a wrong sampling point.

## 5.2 The Backward Euler scheme

A Backward Euler approximation to the ODE system is equally easy to write up in the operator notation:

$$[D_t^- u = v]^{n+1}, \quad (29)$$

$$[D_t^- v = -\omega u]^{n+1}. \quad (30)$$

This becomes a coupled system for  $u^{n+1}$  and  $v^{n+1}$ :

$$u^{n+1} - \Delta t v^{n+1} = u^n, \quad (31)$$

$$v^{n+1} + \Delta t \omega^2 u^{n+1} = v^n. \quad (32)$$

We can compare (31)-(32) with the centered scheme (7) for the second-order differential equation. To this end, we eliminate  $v^{n+1}$  in (31) using (32) solved with respect to  $v^{n+1}$ . Thereafter, we eliminate  $v^n$  using (31) solved with respect to  $v^{n+1}$  and also replacing  $n+1$  by  $n$  and  $n$  by  $n-1$ . The resulting equation involving only  $u^{n+1}$ ,  $u^n$ , and  $u^{n-1}$  can be ordered as

$$\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} = -\omega^2 u^{n+1},$$

which has almost the same form as the centered scheme for the second-order differential equation, but the right-hand side is evaluated at  $u^{n+1}$  and not  $u^n$ . This inconsistent sampling of terms has a dramatic effect on the numerical solution, as we demonstrate in Section 5.4.

## 5.3 The Crank-Nicolson scheme

The Crank-Nicolson scheme takes this form in the operator notation:

$$[D_t u = \bar{v}^t]^{n+\frac{1}{2}}, \quad (33)$$

$$[D_t v = -\omega^2 \bar{u}^t]^{n+\frac{1}{2}}. \quad (34)$$

Writing the equations out and rearranging terms, shows that this is also a coupled system of two linear equations at each time level:

$$u^{n+1} - \frac{1}{2}\Delta t v^{n+1} = u^n + \frac{1}{2}\Delta t v^n, \quad (35)$$

$$v^{n+1} + \frac{1}{2}\Delta t \omega^2 u^{n+1} = v^n - \frac{1}{2}\Delta t \omega^2 u^n. \quad (36)$$

We may compare also this scheme to the centered discretization of the second-order ODE. It turns out that the Crank-Nicolson scheme is equivalent to the discretization

$$\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} = -\omega^2 \frac{1}{4}(u^{n+1} + 2u^n + u^{n-1}) = -\omega^2 u^n + \mathcal{O}(\Delta t^2). \quad (37)$$

That is, the Crank-Nicolson is equivalent to (7) for the second-order ODE, apart from an extra term of size  $\Delta t^2$ , but this is an error of the same order as in the finite difference approximation on the left-hand side of the equation anyway. The fact that the Crank-Nicolson scheme is so close to (7) makes it a much better method than the Forward or Backward Euler methods for vibration problems, as will be illustrated in Section 5.4.

Deriving (37) is a bit tricky. We start with rewriting the Crank-Nicolson equations as follows

$$u^{n+1} - u^n = \frac{1}{2}\Delta t(v^{n+1} + v^n), \quad (38)$$

$$v^{n+1} = v^n - \frac{1}{2}\Delta t \omega^2(u^{n+1} + u^n), \quad (39)$$

and add the latter at the previous time level as well:

$$v^n = v^{n-1} - \frac{1}{2}\Delta t \omega^2(u^n + u^{n-1}) \quad (40)$$

We can also rewrite (38) at the previous time level as

$$v^n + v^{n-1} = \frac{2}{\Delta t}(u^n - u^{n-1}). \quad (41)$$

Inserting (39) for  $v^{n+1}$  in (38) and (40) for  $v^n$  in (38) yields after some reordering:

$$u^{n+1} - u^n = \frac{1}{2}\left(-\frac{1}{2}\Delta t \omega^2(u^{n+1} + 2u^n + u^{n-1}) + v^n + v^{n-1}\right).$$

Now,  $v^n + v^{n-1}$  can be eliminated by means of (41). The result becomes

$$u^{n+1} - 2u^n + u^{n-1} = -\Delta t^2 \omega^2 \frac{1}{4}(u^{n+1} + 2u^n + u^{n-1}). \quad (42)$$

It can be shown that

$$\frac{1}{4}(u^{n+1} + 2u^n + u^{n-1}) \approx u^n + \mathcal{O}(\Delta t^2),$$

meaning that (42) is an approximation to the centered scheme (7) for the second-order ODE where the sampling error in the term  $\Delta t^2 \omega^2 u^n$  is of the same order as the approximation errors in the finite differences, i.e.,  $\mathcal{O}(\Delta t^2)$ . The Crank-Nicolson scheme written as (42) therefore has consistent sampling of all terms at the same time point  $t_n$ .

## 5.4 Comparison of schemes

We can easily compare methods like the ones above (and many more!) with the aid of the Odespy<sup>14</sup> package. Below is a sketch of the code.

```
import odespy
import numpy as np

def f(u, t, w=1):
    # v, u numbering for EulerCromer to work well
    v, u = u # u is array of length 2 holding our [v, u]
    return [-w**2*u, v]

def run_solvers_and_plot(solvers, timesteps_per_period=20,
                        num_periods=1, I=1, w=2*np.pi):
    P = 2*np.pi/w # duration of one period
    dt = P/timesteps_per_period
    Nt = num_periods*timesteps_per_period
    T = Nt*dt
    t_mesh = np.linspace(0, T, Nt+1)

    legends = []
    for solver in solvers:
        solver.set(f_kwargs={'w': w})
        solver.set_initial_condition([0, I])
        u, t = solver.solve(t_mesh)
```

There is quite some more code dealing with plots also, and we refer to the source file `vib_undamped_odespy.py`<sup>15</sup> for details. Observe that keyword arguments in `f(u,t,w=1)` can be supplied through a solver parameter `f_kwargs` (dictionary of additional keyword arguments to `f`).

Specification of the Forward Euler, Backward Euler, and Crank-Nicolson schemes is done like this:

<sup>14</sup><https://github.com/hplgit/odespy>

<sup>15</sup>[http://tinyurl.com/nm5587k/vib/vib\\_undamped\\_odespy.py](http://tinyurl.com/nm5587k/vib/vib_undamped_odespy.py)



```

solvers = [
    odespy.ForwardEuler(f),
    # Implicit methods must use Newton solver to converge
    odespy.BackwardEuler(f, nonlinear_solver='Newton'),
    odespy.CrankNicolson(f, nonlinear_solver='Newton'),
]

```

The `vib_undamped_odespy.py` program makes two plots of the computed solutions with the various methods in the `solvers` list: one plot with  $u(t)$  versus  $t$ , and one *phase plane plot* where  $v$  is plotted against  $u$ . That is, the phase plane plot is the curve  $(u(t), v(t))$  parameterized by  $t$ . Analytically,  $u = I \cos(\omega t)$  and  $v = u' = -\omega I \sin(\omega t)$ . The exact curve  $(u(t), v(t))$  is therefore an ellipse, which often looks like a circle in a plot if the axes are automatically scaled. The important feature, however, is that the exact curve  $(u(t), v(t))$  is closed and repeats itself for every period. Not all numerical schemes are capable of doing that, meaning that the amplitude instead shrinks or grows with time.

Figure 6 show the results. Note that Odespy applies the label `MidpointImplicit` for what we have specified as `CrankNicolson` in the code (`CrankNicolson` is just a synonym for class `MidpointImplicit` in the Odespy code). The Forward Euler scheme in Figure 6 has a pronounced spiral curve, pointing to the fact that the amplitude steadily grows, which is also evident in Figure 7. The Backward Euler scheme has a similar feature, except that the spiral goes inward and the amplitude is significantly damped. The changing amplitude and the spiral form decreases with decreasing time step. The Crank-Nicolson scheme looks much more accurate. In fact, these plots tell that the Forward and Backward Euler schemes are not suitable for solving our ODEs with oscillating solutions.




Figure 6: Comparison of classical schemes in the phase plane for two time step values.

## 5.5 Runge-Kutta methods

We may run two other popular standard methods for first-order ODEs, the 2nd- and 4th-order Runge-Kutta methods, to see how they perform. Figures 8 and 9




Figure 7: Comparison of solution curves for classical schemes.

show the solutions with larger  $\Delta t$  values than what was used in the previous two plots.




Figure 8: Comparison of Runge-Kutta schemes in the phase plane.




Figure 9: Comparison of Runge-Kutta schemes.

The visual impression is that the 4th-order Runge-Kutta method is very accurate, under all circumstances in these tests, while the 2nd-order scheme suffers from amplitude errors unless the time step is very small.

The corresponding results for the Crank-Nicolson scheme are shown in Figure 10. It is clear that the Crank-Nicolson scheme outperforms the 2nd-order Runge-Kutta method. Both schemes have the same order of accuracy  $\mathcal{O}(\Delta t^2)$ , but their differences in the accuracy that matters in a real physical application is very clearly pronounced in this example. Exercise 12 invites you to investigate how the amplitude is computed by a series of famous methods for first-order ODEs.




Figure 10: Long-time behavior of the Crank-Nicolson scheme in the phase plane.

## 5.6 Analysis of the Forward Euler scheme

We may try to find exact solutions of the discrete equations (27)-(28) in the Forward Euler method to better understand why this otherwise useful method has so bad performance for vibration ODEs. An “ansatz” for the solution of the discrete equations is

$$\begin{aligned} u^n &= IA^n, \\ v^n &= qIA^n, \end{aligned}$$

where  $q$  and  $A$  are scalars to be determined. We could have used a complex exponential form  $e^{i\tilde{\omega}n\Delta t}$  since we get oscillatory solutions, but the oscillations grow in the Forward Euler method, so the numerical frequency  $\tilde{\omega}$  will be complex anyway (producing an exponentially growing amplitude). Therefore, it is easier to just work with potentially complex  $A$  and  $q$  as introduced above.

The Forward Euler scheme leads to

$$A = 1 + \Delta t q,$$

$$A = 1 - \Delta t \omega^2 q^{-1}.$$

We can easily eliminate  $A$ , get  $q^2 + \omega^2 = 0$ , and solve for

$$q = \pm i\omega,$$

which gives

$$A = 1 \pm \Delta t i\omega.$$

We shall take the real part of  $A^n$  as the solution. The two values of  $A$  are complex conjugates, and the real part of  $A^n$  will be the same for both roots. This is easy to realize if we rewrite the complex numbers in polar form, which is also convenient for further analysis and understanding. The polar form  $re^{i\theta}$  of a complex number  $x + iy$  has  $r = \sqrt{x^2 + y^2}$  and  $\theta = \tan^{-1}(y/x)$ . Hence, the polar form of the two values for  $A$  becomes

$$1 \pm \Delta t i\omega = \sqrt{1 + \omega^2 \Delta t^2} e^{\pm i \tan^{-1}(\omega \Delta t)}.$$

Now it is very easy to compute  $A^n$ :

$$(1 \pm \Delta t i\omega)^n = (1 + \omega^2 \Delta t^2)^{n/2} e^{\pm n i \tan^{-1}(\omega \Delta t)}.$$

Since  $\cos(\theta n) = \cos(-\theta n)$ , the real parts of the two numbers become the same. We therefore continue with the solution that has the plus sign.

The general solution is  $u^n = C A^n$ , where  $C$  is a constant determined from the initial condition:  $u^0 = C = I$ . We have  $u^n = I A^n$  and  $v^n = q I A^n$ . The final solutions are just the real part of the expressions in polar form:

$$u^n = I(1 + \omega^2 \Delta t^2)^{n/2} \cos(n \tan^{-1}(\omega \Delta t)), \quad (43)$$

$$v^n = -\omega I(1 + \omega^2 \Delta t^2)^{n/2} \sin(n \tan^{-1}(\omega \Delta t)). \quad (44)$$

The expression  $(1 + \omega^2 \Delta t^2)^{n/2}$  causes growth of the amplitude, since a number greater than one is raised to a positive exponent  $n/2$ . We can develop a series expression to better understand the formula for the amplitude. Introducing  $p = \omega \Delta t$  as the key variable and using `sympy` gives

```
>>> from sympy import *
>>> p = symbols('p', real=True)
>>> n = symbols('n', integer=True, positive=True)
>>> amplitude = (1 + p**2)**(n/2)
>>> amplitude.series(p, 0, 4)
1 + n*p**2/2 + O(p**4)
```

The amplitude goes like  $1 + \frac{1}{2}n\omega^2 \Delta t^2$ , clearly growing linearly in time (with  $n$ ).

We can also investigate the error in the angular frequency by a series expansion:

```
>>> n*atan(p).series(p, 0, 4)
n*(p - p**3/3 + O(p**4))
```

This means that the solution for  $u^n$  can be written as

$$u^n = \left(1 + \frac{1}{2}n\omega^2\Delta t^2 + \mathcal{O}(\Delta t^4)\right) \cos\left(\omega t - \frac{1}{3}\omega t\Delta t^2 + \mathcal{O}(\Delta t^4)\right).$$

The error in the angular frequency is of the same order as in the scheme (7) for the second-order ODE, but the error in the amplitude is severe.

## 6 Energy considerations

The observations of various methods in the previous section can be better interpreted if we compute a quantity reflecting the total *energy of the system*. It turns out that this quantity,

$$E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2,$$

is *constant* for all  $t$ . Checking that  $E(t)$  really remains constant brings evidence that the numerical computations are sound. It turns out that  $E$  is proportional to the mechanical energy in the system. Conservation of energy is much used to check numerical simulations, so it is well invested time to dive into this subject.

### 6.1 Derivation of the energy expression

We start out with multiplying

$$u'' + \omega^2 u = 0,$$

by  $u'$  and integrating from 0 to  $T$ :

$$\int_0^T u'' u' dt + \int_0^T \omega^2 u u' dt = 0.$$

Observing that

$$u'' u' = \frac{d}{dt} \frac{1}{2} (u')^2, \quad u u' = \frac{d}{dt} \frac{1}{2} u^2,$$

we get

$$\int_0^T \left( \frac{d}{dt} \frac{1}{2} (u')^2 + \frac{d}{dt} \frac{1}{2} \omega^2 u^2 \right) dt = E(T) - E(0) = 0,$$

where we have introduced

$$E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2. \tag{45}$$

The important result from this derivation is that the total energy is constant:

$$E(t) = E(0).$$

**$E(t)$  is closely related to the system's energy.**

The quantity  $E(t)$  derived above is physically not the mechanical energy of a vibrating mechanical system, but the energy per unit mass. To see this, we start with Newton's second law  $F = ma$  ( $F$  is the sum of forces,  $m$  is the mass of the system, and  $a$  is the acceleration). The displacement  $u$  is related to  $a$  through  $a = u''$ . With a spring force as the only force we have  $F = -ku$ , where  $k$  is a spring constant measuring the stiffness of the spring. Newton's second law then implies the differential equation

$$-ku = mu'' \Rightarrow mu'' + ku = 0.$$

This equation of motion can be turned into an energy balance equation by finding the work done by each term during a time interval  $[0, T]$ . To this end, we multiply the equation by  $du = u'dt$  and integrate:

$$\int_0^T muu'dt + \int_0^T ku u'dt = 0.$$

The result is

$$\tilde{E}(t) = E_k(t) + E_p(t) = 0,$$

where

$$E_k(t) = \frac{1}{2}mv^2, \quad v = u', \quad (46)$$

is the *kinetic energy* of the system, and

$$E_p(t) = \frac{1}{2}ku^2 \quad (47)$$

is the *potential energy*. The sum  $\tilde{E}(t)$  is the total mechanical energy. The derivation demonstrates the famous energy principle that, under the right physical circumstances, any change in the kinetic energy is due to a change in potential energy and vice versa. (This principle breaks down when we introduce damping in the system, as we do in Section 8.)

The equation  $mu'' + ku = 0$  can be divided by  $m$  and written as  $u'' + \omega^2 u = 0$  for  $\omega = \sqrt{k/m}$ . The energy expression  $E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2$  derived earlier is then  $\tilde{E}(t)/m$ , i.e., mechanical energy per unit mass.

**Energy of the exact solution.** Analytically, we have  $u(t) = I \cos \omega t$ , if  $u(0) = I$  and  $u'(0) = 0$ , so we can easily check the energy evolution and confirm that  $E(t)$  is constant:

$$E(t) = \frac{1}{2}I^2(-\omega \sin \omega t)^2 + \frac{1}{2}\omega^2 I^2 \cos^2 \omega t = \frac{1}{2}\omega^2(\sin^2 \omega t + \cos^2 \omega t) = \frac{1}{2}\omega^2 I^2.$$

## 6.2 An error measure based on energy

The constant energy is well expressed by its initial value  $E(0)$ , so that the error in mechanical energy can be computed as a mesh function by

$$e_E^n = \frac{1}{2} \left( \frac{u^{n+1} - u^{n-1}}{2\Delta t} \right)^2 + \frac{1}{2}\omega^2 (u^n)^2 - E(0), \quad n = 1, \dots, N_t - 1, \quad (48)$$

where

$$E(0) = \frac{1}{2}V^2 + \frac{1}{2}\omega^2 I^2,$$

if  $u(0) = I$  and  $u'(0) = V$ . Note that we have used a centered approximation to  $u'$ :  $u'(t_n) \approx [D_{2t}u]^n$ .

A useful norm of the mesh function  $e_E^n$  for the discrete mechanical energy can be the maximum absolute value of  $e_E^n$ :

$$\|e_E^n\|_{\ell^\infty} = \max_{1 \leq n < N_t} |e_E^n|.$$

Alternatively, we can compute other norms involving integration over all mesh points, but we are often interested in worst case deviation of the energy, and then the maximum value is of particular relevance.

A vectorized Python implementation of  $e_E^n$  takes the form

```
# import numpy as np and compute u, t
dt = t[1]-t[0]
E = 0.5*((u[2:] - u[:-2])/(2*dt))**2 + 0.5*w**2*u[1:-1]**2
E0 = 0.5*V**2 + 0.5*w**2*I**2
e_E = E - E0
e_E_norm = np.abs(e_E).max()
```

The convergence rates of the quantity `e_E_norm` can be used for verification. The value of `e_E_norm` is also useful for comparing schemes through their ability to preserve energy. Below is a table demonstrating the relative error in total energy for various schemes (computed by the `vib_undamped_odespy.py`<sup>16</sup> program). The test problem is  $u'' + 4\pi^2 u = 0$  with  $u(0) = 1$  and  $u'(0) = 0$ , so the period is 1 and  $E(t) \approx 4.93$ . We clearly see that the Crank-Nicolson and the Runge-Kutta schemes are superior to the Forward and Backward Euler schemes already after one period.

<sup>16</sup>[http://tinyurl.com/nm5587k/vib/vib\\_undamped\\_odespy.py](http://tinyurl.com/nm5587k/vib/vib_undamped_odespy.py)

Method	$T$	$\Delta t$	$\max  e_E^n /e_E^0$
Forward Euler	1	0.025	$1.678 \cdot 10^0$
Backward Euler	1	0.025	$6.235 \cdot 10^{-1}$
Crank-Nicolson	1	0.025	$1.221 \cdot 10^{-2}$
Runge-Kutta 2nd-order	1	0.025	$6.076 \cdot 10^{-3}$
Runge-Kutta 4th-order	1	0.025	$8.214 \cdot 10^{-3}$

However, after 10 periods, the picture is much more dramatic:

Method	$T$	$\Delta t$	$\max  e_E^n /e_E^0$
Forward Euler	10	0.025	$1.788 \cdot 10^4$
Backward Euler	10	0.025	$1.000 \cdot 10^0$
Crank-Nicolson	10	0.025	$1.221 \cdot 10^{-2}$
Runge-Kutta 2nd-order	10	0.025	$6.250 \cdot 10^{-2}$
Runge-Kutta 4th-order	10	0.025	$8.288 \cdot 10^{-3}$

The Runge-Kutta and Crank-Nicolson methods hardly change their energy error with  $T$ , while the error in the Forward Euler method grows to huge levels and a relative error of 1 in the Backward Euler method points to  $E(t) \rightarrow 0$  as  $t$  grows large.

Running multiple values of  $\Delta t$ , we can get some insight into the convergence of the energy error:

Method	$T$	$\Delta t$	$\max  e_E^n /e_E^0$
Forward Euler	10	0.05	$1.120 \cdot 10^8$
Forward Euler	10	0.025	$1.788 \cdot 10^4$
Forward Euler	10	0.0125	$1.374 \cdot 10^2$
Backward Euler	10	0.05	$1.000 \cdot 10^0$
Backward Euler	10	0.025	$1.000 \cdot 10^0$
Backward Euler	10	0.0125	$9.928 \cdot 10^{-1}$
Crank-Nicolson	10	0.05	$4.756 \cdot 10^{-2}$
Crank-Nicolson	10	0.025	$1.221 \cdot 10^{-2}$
Crank-Nicolson	10	0.0125	$3.125 \cdot 10^{-3}$
Runge-Kutta 2nd-order	10	0.05	$6.152 \cdot 10^{-1}$
Runge-Kutta 2nd-order	10	0.025	$6.250 \cdot 10^{-2}$
Runge-Kutta 2nd-order	10	0.0125	$7.631 \cdot 10^{-3}$
Runge-Kutta 4th-order	10	0.05	$3.510 \cdot 10^{-2}$
Runge-Kutta 4th-order	10	0.025	$8.288 \cdot 10^{-3}$
Runge-Kutta 4th-order	10	0.0125	$2.058 \cdot 10^{-3}$

A striking fact from this table is that the error of the Forward Euler method is reduced by the same factor as  $\Delta t$  is reduced by, while the error in the Crank-Nicolson method has a reduction proportional to  $\Delta t^2$  (we cannot say anything for the Backward Euler method). However, for the RK2 method, halving  $\Delta t$  reduces the error by almost a factor of 10 (!), and for the RK4 method the reduction seems proportional to  $\Delta t^2$  only (and the trend is confirmed by running smaller time steps, so for  $\Delta t = 3.9 \cdot 10^{-4}$  the relative error of RK2 is a factor 10 smaller than that of RK4!).



## 7 The Euler-Cromer method

While the Runge-Kutta methods and the Crank-Nicolson scheme work well for the vibration equation modeled as a first-order ODE system, both were inferior to the straightforward centered difference scheme for the second-order equation  $u'' + \omega^2 u = 0$ . However, there is a similarly successful scheme available for the first-order system  $u' = v$ ,  $v' = -\omega^2 u$ , to be presented next.

### 7.1 Forward-backward discretization

The idea is to apply a Forward Euler discretization to the first equation and a Backward Euler discretization to the second. In operator notation this is stated as

$$[D_t^+ u = v]^n, \quad (49)$$

$$[D_t^- v = -\omega^2 u]^{n+1}. \quad (50)$$

We can write out the formulas and collect the unknowns on the left-hand side:

$$u^{n+1} = u^n + \Delta t v^n, \quad (51)$$

$$v^{n+1} = v^n - \Delta t \omega^2 u^{n+1}. \quad (52)$$

We realize that after  $u^{n+1}$  has been computed from (51), it may be used directly in (52) to compute  $v^{n+1}$ .

In physics, it is more common to update the  $v$  equation first, with a forward difference, and thereafter the  $u$  equation, with a backward difference that applies the most recently computed  $v$  value:

$$v^{n+1} = v^n + \Delta t \omega^2 u^n, \quad (53)$$

$$u^{n+1} = u^n + \Delta t v^{n+1}. \quad (54)$$

The advantage of ordering the ODEs as in (53)-(54) becomes evident when considering complicated models. Such models are included if we write our vibration ODE more generally as

$$u'' + g(u, u', t) = 0.$$

We can rewrite this second-order ODE as two first-order ODEs,

$$\begin{aligned} v' &= -g(u, v, t), \\ u' &= v. \end{aligned}$$

This rewrite allows the following scheme to be used:

$$\begin{aligned}v^{n+1} &= v^n - \Delta t g(u^n, v^n, t), \\u^{n+1} &= u^n + \Delta t v^{n+1}.\end{aligned}$$

We realize that the first update works well with any  $g$  since old values  $u^n$  and  $v^n$  are used. Switching the equations would demand  $u^{n+1}$  and  $v^{n+1}$  values in  $g$  and result in nonlinear algebraic equations to be solved at each time level.

The scheme (53)-(54) goes under several names: forward-backward scheme, semi-implicit Euler method<sup>17</sup>, semi-explicit Euler, symplectic Euler, Newton-Störmer-Verlet, and Euler-Cromer. We shall stick to the latter name. Since both time discretizations are based on first-order difference approximation, one may think that the scheme is only of first-order, but this is not true: the use of a forward and then a backward difference make errors cancel so that the overall error in the scheme is  $\mathcal{O}(\Delta t^2)$ . This is explained below.

How does the Euler-Cromer method preserve the total energy? We may run the example from Section 6.2:

Method	$T$	$\Delta t$	$\max  e_E^n /e_E^0$
Euler-Cromer	10	0.05	$2.530 \cdot 10^{-2}$
Euler-Cromer	10	0.025	$6.206 \cdot 10^{-3}$
Euler-Cromer	10	0.0125	$1.544 \cdot 10^{-3}$

The relative error in the total energy decreases as  $\Delta t^2$ , and the error level is slightly lower than for the Crank-Nicolson and Runge-Kutta methods.

## 7.2 Equivalence with the scheme for the second-order ODE

We shall now show that the Euler-Cromer scheme for the system of first-order equations is equivalent to the centered finite difference method for the second-order vibration ODE (!).

We may eliminate the  $v^n$  variable from (51)-(52) or (53)-(54). The  $v^{n+1}$  term in (53) can be eliminated from (54):

$$u^{n+1} = u^n + \Delta t(v^n - \omega^2 \Delta t u^n). \quad (55)$$

The  $v^n$  quantity can be expressed by  $u^n$  and  $u^{n-1}$  using (54):

$$v^n = \frac{u^n - u^{n-1}}{\Delta t},$$

and when this is inserted in (55) we get

$$u^{n+1} = 2u^n - u^{n-1} - \Delta t^2 \omega^2 u^n, \quad (56)$$

which is nothing but the centered scheme (7)! The two seemingly different numerical methods are mathematically equivalent. Consequently, the previous

<sup>17</sup>[http://en.wikipedia.org/wiki/Semi-implicit\\_Euler\\_method](http://en.wikipedia.org/wiki/Semi-implicit_Euler_method)

analysis of (7) also applies to the Euler-Cromer method. In particular, the amplitude is constant, given that the stability criterion is fulfilled, but there is always an angular frequency error (19). Exercise 17 gives guidance on how to derive the exact discrete solution of the two equations in the Euler-Cromer method.

Although the Euler-Cromer scheme and the method (7) are equivalent, there could be differences in the way they handle the initial conditions. Let us look into this topic. The initial condition  $u' = 0$  means  $u' = v = 0$ . From (53) we get

$$v^1 = v^0 - \Delta t \omega^2 u^0 = \Delta t \omega^2 u^0,$$

and from (54) it follows that

$$u^1 = u^0 + \Delta t v^1 = u^0 - \omega^2 \Delta t^2 u^0.$$

When we previously used a centered approximation of  $u'(0) = 0$  combined with the discretization (7) of the second-order ODE, we got a slightly different result:  $u^1 = u^0 - \frac{1}{2}\omega^2 \Delta t^2 u^0$ . The difference is  $\frac{1}{2}\omega^2 \Delta t^2 u^0$ , which is of second order in  $\Delta t$ , seemingly consistent with the overall error in the scheme for the differential equation model.

A different view can also be taken. If we approximate  $u'(0) = 0$  by a backward difference,  $(u^0 - u^{-1})/\Delta t = 0$ , we get  $u^{-1} = u^0$ , and when combined with (7), it results in  $u^1 = u^0 - \omega^2 \Delta t^2 u^0$ . This means that the Euler-Cromer method based on (54)-(53) corresponds to using only a first-order approximation to the initial condition in the method from Section 1.2.

Correspondingly, using the formulation (51)-(52) with  $v^n = 0$  leads to  $u^1 = u^0$ , which can be interpreted as using a forward difference approximation for the initial condition  $u'(0) = 0$ . Both Euler-Cromer formulations lead to slightly different values for  $u^1$  compared to the method in Section 1.2. The error is  $\frac{1}{2}\omega^2 \Delta t^2 u^0$  and of the same order as the overall scheme.

### 7.3 Implementation

The function below, found in `vib_EulerCromer.py`<sup>18</sup>, implements the Euler-Cromer scheme (53)-(54):

```
import numpy as np

def solver(I, w, dt, T):
    """
    Solve v' = - w**2*u, u'=v for t in (0,T], u(0)=I and v(0)=0,
    by an Euler-Cromer method.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    v = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)
```

<sup>18</sup>[http://tinyurl.com/nm5587k/vib/vib\\_EulerCromer.py](http://tinyurl.com/nm5587k/vib/vib_EulerCromer.py)

```

v[0] = 0
u[0] = I
for n in range(0, Nt):
    v[n+1] = v[n] - dt*w**2*u[n]
    u[n+1] = u[n] + dt*v[n+1]
return u, v, t

```

Since the Euler-Cromer scheme is equivalent to the finite difference method for the second-order ODE  $u'' + \omega^2 u = 0$  (see Section 7.2), the performance of the above `solver` function is the same as for the `solver` function in Section 2. The only difference is the formula for the first time step, as discussed above. This deviation in the Euler-Cromer scheme means that the discrete solution listed in Section 4.2 is not a solution of the Euler-Cromer scheme!

To verify the implementation of the Euler-Cromer method we can adjust `v[1]` so that the computer-generated values can be compared with the formula (20) from in Section 4.2. This adjustment is done in an alternative solver function, `solver_ic_fix` in `vib_EulerCromer.py`. Since we now have an exact solution of the discrete equations available, we can write a test function `test_solver` for checking the equality of computed values with the formula (20):

```

def test_solver():
    """
    Test solver with fixed initial condition against
    equivalent scheme for the 2nd-order ODE  $u'' + u = 0$ .
    """
    I = 1.2; w = 2.0; T = 5
    dt = 2/w # longest possible time step
    u, v, t = solver_ic_fix(I, w, dt, T)
    from vib_undamped import solver as solver2 # 2nd-order ODE
    u2, t2 = solver2(I, w, dt, T)
    error = np.abs(u - u2).max()
    tol = 1E-14
    assert error < tol

```

Another function, `demo`, visualizes the difference between the Euler-Cromer scheme and the scheme (7) for the second-order ODE, arising from the mismatch in the first time level.

The Euler-Cromer method is also available in the Odespy package. The important thing to remember is that we must order the unknowns as  $v$  and  $u$ , so the `u` vector at each time level consists of the velocity  $v$  as first component and the displacement  $u$  as second component:

```

# Define ODE
def f(u, t, w=1):
    v, u = u
    return [-w**2*u, v]

# Initialize solver
I = 1
w = 2*np.pi
import odespy
solver = odespy.EulerCromer(f, f_kwargs={'w': w})
solver.set_initial_condition([0, I])

# Compute time mesh

```

```

P = 2*np.pi/w # duration of one period
dt = P/timesteps_per_period
Nt = num_periods*timesteps_per_period
T = Nt*dt
import numpy as np
t_mesh = np.linspace(0, T, Nt+1)

# Solve ODE
u, t = solver.solve(t_mesh)
u = u[:,1] # Extract displacement

```

## 7.4 The velocity Verlet algorithm

Another very popular algorithm for vibration problems  $u'' + \omega^2 u = 0$  can be derived as follows. First, we step  $u$  forward from  $t_n$  to  $t_{n+1}$  using a three-term Taylor series,

$$u(t_{n+1}) = u(t_n) + u'(t_n)\Delta t + \frac{1}{2}u''(t_n)\Delta t^2.$$

Using  $u' = v$  and  $u'' = -\omega^2 u$ , we get the updating formula

$$u^{n+1} = u^n + v^n \Delta t - \frac{1}{2}\Delta t^2 \omega^2 u^n.$$

Second, the first-order equation for  $v$ ,

$$v' = -\omega^2 u,$$

is discretized by a centered difference in a Crank-Nicolson fashion at  $t_{n+\frac{1}{2}}$ :

$$\frac{v^{n+1} - v^n}{\Delta t} = -\omega^2 \frac{1}{2}(u^n + u^{n+1}).$$

To summarize, we have the scheme

$$u^{n+1} = u^n + v^n \Delta t - \frac{1}{2}\Delta t^2 \omega^2 u^n \quad (57)$$

$$v^{n+1} = v^n - \frac{1}{2}\Delta t \omega^2 (u^n + u^{n+1}), \quad (58)$$

known as the *velocity Verlet* algorithm. Observe that this scheme is explicit since  $u^{n+1}$  in (58) is already computed from (57).

The algorithm can be straightforwardly implemented as shown below (the code appears in the file `vib_undamped_velocity_Verlet.py`<sup>19</sup>).

```

from vib_undamped import convergence_rates, main

def solver(I, w, dt, T, return_v=False):
    """
    Solve u'=v, v'=-w**2*u for t in (0,T], u(0)=I and v(0)=0,

```

<sup>19</sup>[http://tinyurl.com/nm5587k/vib/vib\\_undamped\\_velocity\\_Verlet.py](http://tinyurl.com/nm5587k/vib/vib_undamped_velocity_Verlet.py)

```

by the velocity Verlet method with time step dt.
"""
dt = float(dt)
Nt = int(round(T/dt))
u = np.zeros(Nt+1)
v = np.zeros(Nt+1)
t = np.linspace(0, Nt*dt, Nt+1)

u[0] = I
v[0] = 0
for n in range(Nt):
    u[n+1] = u[n] + v[n]*dt - 0.5*dt**2*w**2*u[n]
    v[n+1] = v[n] - 0.5*dt*w**2*(u[n] + u[n+1])
if return_v:
    return u, v, t
else:
    # Return just u and t as in the vib_undamped.py's solver
    return u, t

```

We provide the option that this `solver` function returns the same data as the `solver` function from Section 2.1 (if `return_v` is `False`), but alternatively, it may return `v` along with `u` and `t`.

The error in the Taylor series expansion behind (57) is  $\mathcal{O}(\Delta t^3)$ , while the error in the central difference for  $v$  is  $\mathcal{O}(\Delta t^2)$ . The overall error is then no better than  $\mathcal{O}(\Delta t^2)$ , which can be verified empirically using the `convergence_rates` function from 2.2:

```

>>> import vib_undamped_velocity_Verlet as m
>>> m.convergence_rates(4, solver_function=m.solver)
[2.0036366687367346, 2.0009497328124835, 2.000240105995295]

```

## 8 Generalization: damping, nonlinear spring, and external excitation

We shall now generalize the simple model problem from Section 1 to include a possibly nonlinear damping term  $f(u')$ , a possibly nonlinear spring (or restoring) force  $s(u)$ , and some external excitation  $F(t)$ :

$$mu'' + f(u') + s(u) = F(t), \quad u(0) = I, \quad u'(0) = V, \quad t \in (0, T]. \quad (59)$$

We have also included a possibly nonzero initial value of  $u'(0)$ . The parameters  $m$ ,  $f(u')$ ,  $s(u)$ ,  $F(t)$ ,  $I$ ,  $V$ , and  $T$  are input data.

There are two main types of damping (friction) forces: linear  $f(u') = bu$ , or quadratic  $f(u') = bu'|u'|$ . Spring systems often feature linear damping, while air resistance usually gives rise to quadratic damping. Spring forces are often linear:  $s(u) = cu$ , but nonlinear versions are also common, the most famous is the gravity force on a pendulum that acts as a spring with  $s(u) \sim \sin(u)$ .

## 8.1 A centered scheme for linear damping

Sampling (59) at a mesh point  $t_n$ , replacing  $u''(t_n)$  by  $[D_t D_t u]^n$ , and  $u'(t_n)$  by  $[D_{2t} u]^n$  results in the discretization

$$[m D_t D_t u + f(D_{2t} u) + s(u) = F]^n, \quad (60)$$

which written out means

$$m \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + f\left(\frac{u^{n+1} - u^{n-1}}{2\Delta t}\right) + s(u^n) = F^n, \quad (61)$$

where  $F^n$  as usual means  $F(t)$  evaluated at  $t = t_n$ . Solving (61) with respect to the unknown  $u^{n+1}$  gives a problem: the  $u^{n+1}$  inside the  $f$  function makes the equation *nonlinear* unless  $f(u')$  is a linear function,  $f(u') = bu'$ . For now we shall assume that  $f$  is linear in  $u'$ . Then

$$m \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + b \frac{u^{n+1} - u^{n-1}}{2\Delta t} + s(u^n) = F^n, \quad (62)$$

which gives an explicit formula for  $u$  at each new time level:

$$u^{n+1} = (2mu^n + (\frac{b}{2}\Delta t - m)u^{n-1} + \Delta t^2(F^n - s(u^n)))(m + \frac{b}{2}\Delta t)^{-1}. \quad (63)$$

For the first time step we need to discretize  $u'(0) = V$  as  $[D_{2t} u = V]^0$  and combine with (63) for  $n = 0$ . The discretized initial condition leads to

$$u^{-1} = u^1 - 2\Delta t V, \quad (64)$$

which inserted in (63) for  $n = 0$  gives an equation that can be solved for  $u^1$ :

$$u^1 = u^0 + \Delta t V + \frac{\Delta t^2}{2m}(-bV - s(u^0) + F^0). \quad (65)$$

## 8.2 A centered scheme for quadratic damping

When  $f(u') = bu'|u'|$ , we get a quadratic equation for  $u^{n+1}$  in (61). This equation can be straightforwardly solved by the well-known formula for the roots of a quadratic equation. However, we can also avoid the nonlinearity by introducing an approximation with an error of order no higher than what we already have from replacing derivatives with finite differences.

We start with (59) and only replace  $u''$  by  $D_t D_t u$ , resulting in

$$[m D_t D_t u + bu'|u'| + s(u) = F]^n. \quad (66)$$

Here,  $u'|u'|$  is to be computed at time  $t_n$ . The idea is now to introduce a *geometric mean*, defined by

$$(w^2)^n \approx w^{n-\frac{1}{2}} w^{n+\frac{1}{2}},$$

for some quantity  $w$  depending on time. The error in the geometric mean approximation is  $\mathcal{O}(\Delta t^2)$ , the same as in the approximation  $u'' \approx D_t D_t u$ . With  $w = u'$  it follows that

$$[u'|u']^n \approx u'(t_{n+\frac{1}{2}})|u'(t_{n-\frac{1}{2}})|.$$

The next step is to approximate  $u'$  at  $t_{n\pm 1/2}$ , and fortunately a centered difference fits perfectly into the formulas since it involves  $u$  values at the mesh points only. With the approximations

$$u'(t_{n+1/2}) \approx [D_t u]^{n+\frac{1}{2}}, \quad u'(t_{n-1/2}) \approx [D_t u]^{n-\frac{1}{2}}, \quad (67)$$

we get

$$[u'|u']^n \approx [D_t u]^{n+\frac{1}{2}} |[D_t u]^{n-\frac{1}{2}}| = \frac{u^{n+1} - u^n}{\Delta t} \frac{|u^n - u^{n-1}|}{\Delta t}. \quad (68)$$

The counterpart to (61) is then

$$m \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + b \frac{u^{n+1} - u^n}{\Delta t} \frac{|u^n - u^{n-1}|}{\Delta t} + s(u^n) = F^n, \quad (69)$$

which is linear in the unknown  $u^{n+1}$ . Therefore, we can easily solve (69) with respect to  $u^{n+1}$  and achieve the explicit updating formula

$$u^{n+1} = (m + b|u^n - u^{n-1}|)^{-1} \times (2mu^n - mu^{n-1} + bu^n|u^n - u^{n-1}| + \Delta t^2(F^n - s(u^n))). \quad (70)$$

In the derivation of a special equation for the first time step we run into some trouble: inserting (64) in (70) for  $n = 0$  results in a complicated nonlinear equation for  $u^1$ . By thinking differently about the problem we can easily get away with the nonlinearity again. We have for  $n = 0$  that  $b[u'|u']^0 = bV|V|$ . Using this value in (66) gives

$$[mD_t D_t u + bV|V| + s(u) = F]^0. \quad (71)$$

Writing this equation out and using (64) results in the special equation for the first time step:

$$u^1 = u^0 + \Delta t V + \frac{\Delta t^2}{2m} (-bV|V| - s(u^0) + F^0). \quad (72)$$

### 8.3 A forward-backward discretization of the quadratic damping term

The previous section first proposed to discretize the quadratic damping term  $|u'|u'$  using centered differences:  $[|D_{2t} D_{2t} u|^n]$ . As this gives rise to a nonlinearity



in  $u^{n+1}$ , it was instead proposed to use a geometric mean combined with centered differences. But there are other alternatives. To get rid of the nonlinearity in  $[|D_{2t}|D_{2t}u]^n$ , one can think differently: apply a backward difference to  $|u'|$ , such that the term involves known values, and apply a forward difference to  $u'$  to make the term linear in the unknown  $u^{n+1}$ . With mathematics,

$$[\beta|u'|u']^n \approx \beta|[D_t^- u]^n|[D_t^+ u]^n = \beta \left| \frac{u^n - u^{n-1}}{\Delta t} \right| \frac{u^{n+1} - u^n}{\Delta t}. \quad (73)$$

The forward and backward differences have both an error proportional to  $\Delta t$  so one may think the discretization above leads to a first-order scheme. However, by looking at the formulas, we realize that the forward-backward differences in (73) result in exactly the same scheme as in (69) where we used a geometric mean and centered differences and committed errors of size  $\mathcal{O}(\Delta t^2)$ . Therefore, the forward-backward differences in (73) act in a symmetric way and actually produce a second-order accurate discretization of the quadratic damping term.

## 8.4 Implementation

The algorithm arising from the methods in Sections 8.1 and 8.2 is very similar to the undamped case in Section 1.2. The difference is basically a question of different formulas for  $u^1$  and  $u^{n+1}$ . This is actually quite remarkable. The equation (59) is normally impossible to solve by pen and paper, but possible for some special choices of  $F$ ,  $s$ , and  $f$ . On the contrary, the complexity of the nonlinear generalized model (59) versus the simple undamped model is not a big deal when we solve the problem numerically!

The computational algorithm takes the form

1.  $u^0 = I$
2. compute  $u^1$  from (65) if linear damping or (72) if quadratic damping
3. for  $n = 1, 2, \dots, N_t - 1$ :
  - (a) compute  $u^{n+1}$  from (63) if linear damping or (70) if quadratic damping

Modifying the `solver` function for the undamped case is fairly easy, the big difference being many more terms and if tests on the type of damping:

```
def solver(I, V, m, b, s, F, dt, T, damping='linear'):
    """
    Solve m*u'' + f(u') + s(u) = F(t) for t in (0,T],
    u(0)=I and u'(0)=V,
    by a central finite difference method with time step dt.
    If damping is 'linear', f(u')=b*u, while if damping is
    'quadratic', f(u')=b*u'*abs(u').
    F(t) and s(u) are Python functions.
    """
    dt = float(dt); b = float(b); m = float(m) # avoid integer div.
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
```

```

t = np.linspace(0, Nt*dt, Nt+1)

u[0] = I
if damping == 'linear':
    u[1] = u[0] + dt*V + dt**2/(2*m)*(-b*V - s(u[0]) + F(t[0]))
elif damping == 'quadratic':
    u[1] = u[0] + dt*V + \
        dt**2/(2*m)*(-b*V*abs(V) - s(u[0]) + F(t[0]))

for n in range(1, Nt):
    if damping == 'linear':
        u[n+1] = (2*m*u[n] + (b*dt/2 - m)*u[n-1] +
            dt**2*(F(t[n]) - s(u[n])))/(m + b*dt/2)
    elif damping == 'quadratic':
        u[n+1] = (2*m*u[n] - m*u[n-1] + b*u[n]*abs(u[n] - u[n-1])
            + dt**2*(F(t[n]) - s(u[n])))/(
            m + b*abs(u[n] - u[n-1]))

return u, t

```

The complete code resides in the file `vib.py`<sup>20</sup>.

## 8.5 Verification

**Constant solution.** For debugging and initial verification, a constant solution is often very useful. We choose  $u_e(t) = I$ , which implies  $V = 0$ . Inserted in the ODE, we get  $F(t) = s(I)$  for any choice of  $f$ . Since the discrete derivative of a constant vanishes (in particular,  $[D_{2t}I]^n = 0$ ,  $[D_t I]^n = 0$ , and  $[D_t D_t I]^n = 0$ ), the constant solution also fulfills the discrete equations. The constant should therefore be reproduced to machine precision. The function `test_constant` in `vib.py` implements this test.

**hpl 3:** Add verification tests for constant, linear, quadratic. Check how many bugs that are caught by these tests.

**Linear solution.** Now we choose a linear solution:  $u_e = ct + d$ . The initial condition  $u(0) = I$  implies  $d = I$ , and  $u'(0) = V$  forces  $c$  to be  $V$ . Inserting  $u_e = Vt + I$  in the ODE with linear damping results in

$$0 + bV + s(Vt + I) = F(t),$$

while quadratic damping requires the source term

$$0 + b|V|V + s(Vt + I) = F(t).$$

Since the finite difference approximations used to compute  $u'$  all are exact for a linear function, it turns out that the linear  $u_e$  is also a solution of the discrete equations. Exercise 9 asks you to carry out all the details.

**Quadratic solution.** Choosing  $u_e = bt^2 + Vt + I$ , with  $b$  arbitrary, fulfills the initial conditions and fits the ODE if  $F$  is adjusted properly. The solution also solves the discrete equations with linear damping. However, this quadratic

<sup>20</sup><http://tinyurl.com/nm5587k/vib/vib.py>

polynomial in  $t$  does not fulfill the discrete equations in case of quadratic damping, because the geometric mean used in the approximation of this term introduces an error. Doing Exercise 9 will reveal the details. One can fit  $F^n$  in the discrete equations such that the quadratic polynomial is reproduced by the numerical method (to machine precision).

## 8.6 Visualization

The functions for visualizations differ significantly from those in the undamped case in the `vib_undamped.py` program because, in the present general case, we do not have an exact solution to include in the plots. Moreover, we have no good estimate of the periods of the oscillations as there will be one period determined by the system parameters, essentially the approximate frequency  $\sqrt{s'(0)/m}$  for linear  $s$  and small damping, and one period dictated by  $F(t)$  in case the excitation is periodic. This is, however, nothing that the program can depend on or make use of. Therefore, the user has to specify  $T$  and the window width to get a plot that moves with the graph and shows the most recent parts of it in long time simulations.

The `vib.py` code contains several functions for analyzing the time series signal and for visualizing the solutions.

## 8.7 User interface

The `main` function is changed substantially from the `vib_undamped.py` code, since we need to specify the new data  $c$ ,  $s(u)$ , and  $F(t)$ . In addition, we must set  $T$  and the plot window width (instead of the number of periods we want to simulate as in `vib_undamped.py`). To figure out whether we can use one plot for the whole time series or if we should follow the most recent part of  $u$ , we can use the `plot_empricial_freq_and_amplitude` function's estimate of the number of local maxima. This number is now returned from the function and used in `main` to decide on the visualization technique.

```
def main():
    import argparse
    parser = argparse.ArgumentParser()
    parser.add_argument('--I', type=float, default=1.0)
    parser.add_argument('--V', type=float, default=0.0)
    parser.add_argument('--m', type=float, default=1.0)
    parser.add_argument('--c', type=float, default=0.0)
    parser.add_argument('--s', type=str, default='u')
    parser.add_argument('--F', type=str, default='0')
    parser.add_argument('--dt', type=float, default=0.05)
    parser.add_argument('--T', type=float, default=140)
    parser.add_argument('--damping', type=str, default='linear')
    parser.add_argument('--window_width', type=float, default=30)
    parser.add_argument('--savefig', action='store_true')
    a = parser.parse_args()
    from scitools.std import StringFunction
    s = StringFunction(a.s, independent_variable='u')
    F = StringFunction(a.F, independent_variable='t')
    I, V, m, c, dt, T, window_width, savefig, damping = \
```

```

a.I, a.V, a.m, a.c, a.dt, a.T, a.window_width, a.savefig, \
a.damping

u, t = solver(I, V, m, c, s, F, dt, T)
num_periods = empirical_freq_and_amplitude(u, t)
if num_periods <= 15:
    figure()
    visualize(u, t)
else:
    visualize_front(u, t, window_width, savefig)
show()

```

The program `vib.py` contains the above code snippets and can solve the model problem (59). As a demo of `vib.py`, we consider the case  $I = 1$ ,  $V = 0$ ,  $m = 1$ ,  $c = 0.03$ ,  $s(u) = \sin(u)$ ,  $F(t) = 3 \cos(4t)$ ,  $\Delta t = 0.05$ , and  $T = 140$ . The relevant command to run is

---

Terminal

---

```
Terminal> python vib.py --s 'sin(u)' --F '3*cos(4*t)' --c 0.03
```

---

This results in a moving window following the function<sup>21</sup> on the screen. Figure 11 shows a part of the time series.




Figure 11: Damped oscillator excited by a sinusoidal function.

---

<sup>21</sup>[http://tinyurl.com/opdfafk/pub/mov-vib/vib\\_generalized\\_dt0.05/index.html](http://tinyurl.com/opdfafk/pub/mov-vib/vib_generalized_dt0.05/index.html)

## 8.8 The Euler-Cromer scheme for the generalized model

The ideas of the Euler-Cromer method from Section 7 carry over to the generalized model. We write (59) as two equations for  $u$  and  $v = u'$ . The first equation is taken as the one with  $v'$  on the left-hand side:

$$v' = \frac{1}{m}(F(t) - s(u) - f(v)), \quad (74)$$

$$u' = v. \quad (75)$$

The idea is to step (74) forward using a standard Forward Euler method, while we update  $u$  from (75) with a Backward Euler method, utilizing the recent, computed  $v^{n+1}$  value. In detail,

$$\frac{v^{n+1} - v^n}{\Delta t} = \frac{1}{m}(F(t_n) - s(u^n) - f(v^n)), \quad (76)$$

$$\frac{u^{n+1} - u^n}{\Delta t} = v^{n+1}, \quad (77)$$

resulting in the explicit scheme

$$v^{n+1} = v^n + \Delta t \frac{1}{m}(F(t_n) - s(u^n) - f(v^n)), \quad (78)$$

$$u^{n+1} = u^n + \Delta t v^{n+1}. \quad (79)$$

We immediately note one very favorable feature of this scheme: all the nonlinearities in  $s(u)$  and  $f(v)$  are evaluated at a previous time level. This makes the Euler-Cromer method easier to apply and hence much more convenient than the centered scheme for the second-order ODE (59).

The initial conditions are trivially set as

$$v^0 = V, \quad (80)$$

$$u^0 = I. \quad (81)$$

**hpl 4:** odespy for the generalized problem

## 9 Exercises and Problems

### Problem 1: Use linear/quadratic functions for verification

Consider the ODE problem

$$u'' + \omega^2 u = f(t), \quad u(0) = I, \quad u'(0) = V, \quad t \in (0, T].$$

**a)** Discretize this equation according to  $[D_t D_t u + \omega^2 u = f]^n$  and derive the equation for the first time step ( $u^1$ ).

**Solution.** For the requested discretization, we get

$$\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + \omega^2 u^n = f^n.$$

To derive the equation for  $u^1$ , we first find the expression for  $u^{n+1}$  from the discretized form of the equation. Isolating  $u^{n+1}$ , we get

$$u^{n+1} = (2 - (\Delta t \omega)^2) u^n - u^{n-1} + \Delta t^2 f^n.$$

With  $n = 0$ , this expression gives

$$u^1 = (2 - (\Delta t \omega)^2) u^0 - u^{-1} + \Delta t^2 f^0.$$

Here, however, we get a problem with  $u^{-1}$ , which appears on the right hand side. To get around that problem, we realize that the initial condition  $u' = V$  might be approximated by use of a centered difference approximation as

$$\frac{u^1 - u^{-1}}{2\Delta t} = V,$$

which means that

$$u^{-1} = u^1 - 2\Delta t V.$$

Inserting this expression for  $u^{-1}$  into the expression for  $u^1$ , we get

$$u^1 = (2 - (\Delta t \omega)^2) u^0 - (u^1 - 2\Delta t V) + \Delta t^2 f^0.$$

Finally, after isolating  $u^1$  on the left hand side, we arrive at

$$u^1 = \left(1 - \frac{1}{2}(\Delta t \omega)^2\right) u^0 + \Delta t V + \frac{1}{2}\Delta t^2 f^0.$$

**b)** For verification purposes, we use the method of manufactured solutions (MMS) with the choice of  $u_e(t) = ct + d$ . Find restrictions on  $c$  and  $d$  from the initial conditions. Compute the corresponding source term  $f$ . Show that  $[D_t D_t t]^n = 0$  and use the fact that the  $D_t D_t$  operator is linear,  $[D_t D_t (ct + d)]^n = c[D_t D_t t]^n + [D_t D_t d]^n = 0$ , to show that  $u_e$  is also a perfect solution of the discrete equations.

**Solution.** The initial conditions  $u(0) = I$  and  $u'(0) = V$  give demands  $u_e(0) = I$  and  $u'_e(0) = V$ , which imply that  $d = I$  and  $c = V$ .

To compute the source term  $f$ , we insert the chosen solution  $u_e$  into the ODE. This gives

$$0 + \omega^2(ct + d) = f(t),$$

which implies that

$$f(t) = \omega^2(Vt + I).$$

To show that  $[D_t D_t t]^n = 0$ , we proceed as

$$\begin{aligned} [D_t D_t t]^n &= \frac{t^{n+1} - 2t^n + t^{n-1}}{\Delta t^2}, \\ &= \frac{(n+1)\Delta t - 2n\Delta t + (n-1)\Delta t}{\Delta t^2}, \\ &= \frac{n\Delta t + \Delta t - 2n\Delta t + n\Delta t - \Delta t}{\Delta t^2}, \\ &= 0. \end{aligned}$$

Finally, we show that the chosen  $u_e$  is also a perfect solution of the discrete equations. If we start by inserting  $u_e$  into

$$[D_t D_t u + \omega^2 u = f]^n,$$

as well as the expression found for  $f$ . We get

$$[D_t D_t (Vt + I) + \omega^2 (Vt + I) = \omega^2 (Vt + I)]^n,$$

which can be rewritten as

$$[D_t D_t (Vt + I)]^n + [\omega^2 (Vt + I)]^n = [\omega^2 (Vt + I)]^n.$$

Now, since the first term here is zero, we see that the discrete equation is fulfilled exactly for the chosen  $u_e$  function.

c) Use `sympy` to do the symbolic calculations above. Here is a sketch of the program `vib_undamped_verify_mms.py`:

```
import sympy as sym
V, t, I, w, dt = sym.symbols('V t I w dt') # global symbols
f = None # global variable for the source term in the ODE

def ode_source_term(u):
    """Return the terms in the ODE that the source term
    must balance, here u'' + w**2*u.
    u is symbolic Python function of t."""
    return sym.diff(u(t), t, t) + w**2*u(t)

def residual_discrete_eq(u):
    """Return the residual of the discrete eq. with u inserted."""
    R = ...
    return sym.simplify(R)

def residual_discrete_eq_step1(u):
    """Return the residual of the discrete eq. at the first
    step with u inserted."""
    R = ...
    return sym.simplify(R)

def DtDt(u, dt):
    """Return 2nd-order finite difference for u_tt.
```

```

u is a symbolic Python function of t.
"""
return ...

def main(u):
    """
    Given some chosen solution u (as a function of t, implemented
    as a Python function), use the method of manufactured solutions
    to compute the source term f, and check if u also solves
    the discrete equations.
    """
    print '=== Testing exact solution: %s ===' % u
    print "Initial conditions u(0)=%s, u'(0)=%s:" % \
        (u(t).subs(t, 0), sym.diff(u(t), t).subs(t, 0))

    # Method of manufactured solution requires fitting f
    global f # source term in the ODE
    f = sym.simplify(ode_lhs(u))

    # Residual in discrete equations (should be 0)
    print 'residual step1:', residual_discrete_eq_step1(u)
    print 'residual:', residual_discrete_eq(u)

def linear():
    main(lambda t: V*t + I)

if __name__ == '__main__':
    linear()

```

Fill in the various functions such that the calls in the `main` function works.

**Solution.** See final code presented below.

**d)** The purpose now is to choose a quadratic function  $u_e = bt^2 + ct + d$  as exact solution. Extend the `sympy` code above with a function `quadratic` for fitting `f` and checking if the discrete equations are fulfilled. (The function is very similar to `linear`.)

**Solution.** Yes, a quadratic function will fulfill the discrete equations exactly. See output from final code presented below.

**e)** Will a polynomial of degree three fulfill the discrete equations?

**Solution.** No, when running the final code presented below, the printout shows that the step1 residual for the cubic function is not zero.

**f)** Implement a `solver` function for computing the numerical solution of this problem.

**Solution.** See final code presented below.

**g)** Write a test function for checking that the quadratic solution is computed correctly (to machine precision, but the round-off errors accumulate and increase with  $T$ ) by the `solver` function.



```

import sympy as sym
import numpy as np

V, t, I, w, dt = sym.symbols('V t I w dt') # global symbols
f = None # global variable for the source term in the ODE

def ode_source_term(u):
    """Return the terms in the ODE that the source term
    must balance, here u'' + w**2*u.
    u is symbolic Python function of t."""
    return sym.diff(u(t), t, t) + w**2*u(t)

def residual_discrete_eq(u):
    """Return the residual of the discrete eq. with u inserted."""
    R = DtDt(u, dt) + w**2*u(t) - f
    return sym.simplify(R)

def residual_discrete_eq_step1(u):
    """Return the residual of the discrete eq. at the first
    step with u inserted."""
    half = sym.Rational(1,2)
    R = u(t+dt) - u(t) - dt*V - \
        half*dt**2*f.subs(t, 0) + half*dt**2*w**2*I
    R = R.subs(t, 0) # t=0 in the rhs of the first step eq.
    return sym.simplify(R)

def DtDt(u, dt):
    """Return 2nd-order finite difference for u_tt.
    u is a symbolic Python function of t.
    """
    return (u(t+dt) - 2*u(t) + u(t-dt))/dt**2

def main(u):
    """
    Given some chosen solution u (as a function of t, implemented
    as a Python function), use the method of manufactured solutions
    to compute the source term f, and check if u also solves
    the discrete equations.
    """
    print '=== Testing exact solution: %s ===' % u(t)
    print "Initial conditions u(0)=%s, u'(0)=%s:" % \
        (u(t).subs(t, 0), sym.diff(u(t), t).subs(t, 0))

    # Method of manufactured solution requires fitting f
    global f # source term in the ODE
    f = sym.simplify(ode_source_term(u))

    # Residual in discrete equations (should be 0)
    print 'residual step1:', residual_discrete_eq_step1(u)
    print 'residual:', residual_discrete_eq(u)

def linear():
    def u_e(t):
        """Return chosen linear exact solution."""
        # General linear function u_e = c*t + d
        # Initial conditions u(0)=I, u'(0)=V require c=V, d=I
        return V*t + I

    main(u_e)

def quadratic():
    # Extend with quadratic functions

```

```

b = sym.Symbol('b') # arbitrary constant in quadratic term

def u_e(t):
    return b*t**2 + V*t + I

main(u_e)

def cubic():
    a, b = sym.symbols('a b')

    main(lambda t: a*t**3 + b*t**2 + V*t + I)

def solver(I, V, f, w, dt, T):
    """
    Solve u'' + w**2*u = f for t in (0,T], u(0)=I and u'(0)=V,
    by a central finite difference method with time step dt.
    f(t) is a callable Python function.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)

    u[0] = I
    u[1] = u[0] - 0.5*dt**2*w**2*u[0] + 0.5*dt**2*f(t[0]) + dt*V
    for n in range(1, Nt):
        u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n] + dt**2*f(t[n])
    return u, t

import nose.tools as nt

def test_quadratic_exact_solution():
    # Transform global symbolic variables to functions and numbers
    # for numerical computations
    global b, V, I, w
    b, V, I, w = 2.3, 0.9, 1.2, 1.5
    global f, t
    u_e = lambda t: b*t**2 + V*t + I # compute with b, V, I, w as numbers
    f = ode_source_term(u_e)         # fit source term
    f = sym.lambdify(t, f)           # turn to numerical Python function

    dt = 2./w
    u, t = solver(I=I, V=V, f=f, w=w, dt=dt, T=3)
    u_e = u_e(t)
    error = np.abs(u - u_e).max()
    nt.assert_almost_equal(error, 0, delta=1E-12)
    print 'Error in computing a quadratic solution:', error

if __name__ == '__main__':
    linear()
    quadratic()
    cubic()
    test_quadratic_exact_solution()

```

### Solution.

Filename: vib\_undamped\_verify\_mms.

## Exercise 2: Show linear growth of the phase with time

Consider an exact solution  $I \cos(\omega t)$  and an approximation  $I \cos(\tilde{\omega} t)$ . Define the phase error as the time lag between the peak  $I$  in the exact solution and the corresponding peak in the approximation after  $m$  periods of oscillations. Show that this phase error is linear in  $m$ .

**Solution.** From (19) we have that

$$\tilde{\omega} = \omega \left( 1 + \frac{1}{24} \omega^2 \Delta t^2 \right) + \mathcal{O}(\Delta t^4).$$

Dropping the  $\mathcal{O}(\Delta t^4)$  term, and since  $\omega = \frac{2\pi}{P}$  and  $\tilde{\omega} = \frac{2\pi}{\tilde{P}}$ , we have that

$$\frac{2\pi}{\tilde{P}} \approx \frac{2\pi}{P} \left( 1 + \frac{1}{24} \omega^2 \Delta t^2 \right).$$

Now,  $2\pi$  cancels and the remaining equation may be rewritten as

$$P - \tilde{P} \approx \frac{1}{24} \omega^2 \Delta t^2.$$

This implies that the periods differ by a constant. Since the exact and the numerical solution start out identically, the phase error  $P - \tilde{P}$  will become  $m \frac{1}{24} \omega^2 \Delta t^2$  after  $m$  periods, i.e. the phase error is linear in  $m$ .

Filename: `vib_phase_error_growth`.

## Exercise 3: Improve the accuracy by adjusting the frequency

According to (19), the numerical frequency deviates from the exact frequency by a (dominating) amount  $\omega^3 \Delta t^2 / 24 > 0$ . Replace the `w` parameter in the algorithm in the `solver` function in `vib_undamped.py` by `w*(1 - (1./24)*w**2*dt**2)` and test how this adjustment in the numerical algorithm improves the accuracy (use  $\Delta t = 0.1$  and simulate for 80 periods, with and without adjustment of  $\omega$ ).

**Solution.** The modified code (below) was run for 80 periods with, and without, the given adjustment of  $\omega$ . A substantial difference in accuracy was observed between the two, showing that the frequency adjustment improves the situation.

```
from numpy import *
from matplotlib.pyplot import *

def solver(I, w, dt, T, adjust_w=True):
    """
    Solve u'' + w**2*u = 0 for t in (0,T], u(0)=I and u'(0)=0,
    by a central finite difference method with time step dt.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
```

```

u = zeros(Nt+1)
t = linspace(0, Nt*dt, Nt+1)
if adjust_w:
    w = w*(1 - 1./24*w**2*dt**2)

u[0] = I
u[1] = u[0] - 0.5*dt**2*w**2*u[0]
for n in range(1, Nt):
    u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n]
return u, t

def exact_solution(t, I, w):
    return I*cos(w*t)

def visualize(u, t, I, w):
    plot(t, u, 'r--o')
    t_fine = linspace(0, t[-1], 1001) # very fine mesh for u_e
    u_e = exact_solution(t_fine, I, w)
    hold('on')
    plot(t_fine, u_e, 'b-')
    legend(['numerical', 'exact'], loc='upper left')
    xlabel('t')
    ylabel('u')
    dt = t[1] - t[0]
    title('dt=%g' % dt)
    umin = -1.2*I; umax = -umin
    axis([t[0], t[-1], umin, umax])
    savefig('vib1.png')
    savefig('vib1.pdf')
    savefig('vib1.eps')
    show()

def convergence_rates(m, num_periods=8, adjust_w=True):
    """
    Return m-1 empirical estimates of the convergence rate
    based on m simulations, where the time step is halved
    for each simulation.
    """
    w = 0.35; I = 0.3
    dt = 2*pi/w/30 # 30 time step per period 2*pi/w
    T = 2*pi/w*num_periods
    dt_values = []
    E_values = []
    for i in range(m):
        u, t = solver(I, w, dt, T, adjust_w)
        u_e = exact_solution(t, I, w)
        E = sqrt(dt*sum((u_e-u)**2))
        dt_values.append(dt)
        E_values.append(E)
        dt = dt/2

    r = [log(E_values[i-1]/E_values[i])/
        log(dt_values[i-1]/dt_values[i])
        for i in range(1, m, 1)]
    return r

import nose.tools as nt

def test_convergence_rates():
    r = convergence_rates(m=5, num_periods=8)
    # Accept rate to 1 decimal place
    nt.assert_almost_equal(r[-1], 4.0, places=1)

def main():

```

```

import argparse
parser = argparse.ArgumentParser()
parser.add_argument('--adjust_w', type=str, default='yes')
parser.add_argument('--I', type=float, default=1.0)
parser.add_argument('--w', type=float, default=2*pi)
parser.add_argument('--dt', type=float, default=0.05)
parser.add_argument('--num_periods', type=int, default=5)
# Hack to allow --SCITTOOLS options (read when importing scitools.std)
parser.add_argument('--SCITTOOLS_easyviz_backend', default='matplotlib')
a = parser.parse_args()
adjust_w, I, w, dt, num_periods = a.adjust_w, a.I, a.w, a.dt, a.num_periods
adjust_w = True if adjust_w == 'yes' else False

P = 2*pi/w # one period
T = P*num_periods
u, t = solver(I, w, dt, T, adjust_w)
if num_periods <= 10:
    visualize(u, t, I, w)
else:
    visualize_front(u, t, I, w)
    #visualize_front_ascii(u, t, I, w)

def visualize_front(u, t, I, w, savefig=False):
    """
    Visualize u and the exact solution vs t, using a
    moving plot window and continuous drawing of the
    curves as they evolve in time.
    Makes it easy to plot very long time series.
    """
    import scitools.std as st
    from scitools.MovingPlotWindow import MovingPlotWindow

    P = 2*pi/w # one period
    umin = -1.2*I; umax = -umin
    plot_manager = MovingPlotWindow(
        window_width=8*P,
        dt=t[1]-t[0],
        yaxis=[umin, umax],
        mode='continuous drawing')
    for n in range(1, len(u)):
        if plot_manager.plot(n):
            s = plot_manager.first_index_in_plot
            st.plot(t[s:n+1], u[s:n+1], 'r-1',
                    t[s:n+1], I*cos(w*t)[s:n+1], 'b-1',
                    title='t=%6.3f' % t[n],
                    axis=plot_manager.axis(),
                    show=not savefig) # drop window if savefig
            if savefig:
                st.savefig('tmp_vib%04d.png' % n)
    plot_manager.update(n)

def visualize_front_ascii(u, t, I, w, fps=10):
    """
    Plot u and the exact solution vs t line by line in a
    terminal window (only using ascii characters).
    Makes it easy to plot very long time series.
    """
    from scitools.avplotter import Plotter
    import time
    P = 2*pi/w
    umin = -1.2*I; umax = -umin

    p = Plotter(ymin=umin, ymax=umax, width=60, symbols='+o')

```

```

        for n in range(len(u)):
            print p.plot(t[n], u[n], I*cos(w*t[n])), \
                    '%.1f' % (t[n]/P)
            time.sleep(1/float(fps))

    if __name__ == '__main__':
        main()
        #r = convergence_rates(m=5, num_periods=8, adjust_w=True)
        #print 'convergence rate: %.1f' % r[-1]

```

Filename: vib\_adjust\_w.

#### Exercise 4: See if adaptive methods improve the phase error

Adaptive methods for solving ODEs aim at adjusting  $\Delta t$  such that the error is within a user-prescribed tolerance. Implement the equation  $u'' + u = 0$  in the Odespy<sup>22</sup> software. Use the example from Section 3.2.11 in [1]. Run the scheme with a very low tolerance (say  $10^{-14}$ ) and for a long time, check the number of time points in the solver's mesh (`len(solver.t_all)`), and compare the phase error with that produced by the simple finite difference method from Section 1.2 with the same number of (equally spaced) mesh points. The question is whether it pays off to use an adaptive solver or if equally many points with a simple method gives about the same accuracy.

**Solution.** The code:

```

import odespy
import numpy as np
import sys
#import matplotlib.pyplot as plt
import scitools.std as plt

def f(s, t):
    u, v = s
    return np.array([v, -u])

def u_exact(t):
    return I*np.cos(w*t)

I = 1; V = 0; u0 = np.array([I, V])
w = 1; T = 100
tol = float(sys.argv[1])
solver = odespy.DormandPrince(f, atol=tol, rtol=0.1*tol)

Nt = 1 # just one step - let scheme find its intermediate points
t_mesh = np.linspace(0, T, Nt+1)
t_fine = np.linspace(0, T, 10001)

solver.set_initial_condition(u0)
u, t = solver.solve(t_mesh)

# u and t will only consist of [I, u^Nt] and [0,T], i.e. 2 values each, while
# solver.u_all and solver.t_all contain all computed points.

```

<sup>22</sup><https://github.com/hplgit/odespy>

```

# solver.u_all is a list with arrays, one array (with 2 values) for
# each point in time.
u_adaptive = np.array(solver.u_all)

# For comparison, we solve also with simple FDM method
Nt_simple = len(solver.t_all) # get no of time steps from adaptive method
t_simple = np.linspace(0, T, Nt_simple+1) # create equally spaced steps
dt = t_simple[1] - t_simple[0] # constant time step
u_simple = np.zeros(Nt_simple+1)
u_simple[0] = I
u_simple[1] = u_simple[0] - 0.5*dt**2*w**2*u_simple[0]
for n in range(1, Nt_simple):
    u_simple[n+1] = 2*u_simple[n] - u_simple[n-1] - dt**2*w**2*u_simple[n]

plt.plot(solver.t_all, u_adaptive[:,0], 'k-')
plt.hold('on')
plt.plot(t_simple, u_simple, 'r--')
plt.plot(t_fine, u_exact(t_fine), 'b-')
plt.legend(['tol=%0E' % tol, 'u simple', 'exact'])
plt.savefig('tmp_odespy_adaptive.png')
plt.savefig('tmp_odespy_adaptive.pdf')
plt.show()

```

The program produces the plot seen in Figure 12, which shows how the adaptive solution clearly outperforms the simpler method.




Figure 12: Result of solving the problem by two different approaches, one adaptive and one simpler difference method.

Filename: vib\_undamped\_adaptive.

### Exercise 5: Use a Taylor polynomial to compute $u^1$

As an alternative to computing  $u^1$  by (8), one can use a Taylor polynomial with three terms:

$$u(t_1) \approx u(0) + u'(0)\Delta t + \frac{1}{2}u''(0)\Delta t^2$$

With  $u'' = -\omega^2 u$  and  $u'(0) = 0$ , show that this method also leads to (8). Generalize the condition on  $u'(0)$  to be  $u'(0) = V$  and compute  $u^1$  in this case with both methods.

**Solution.** With  $u''(0) = -\omega^2 u(0)$  and  $u'(0) = 0$ , the given Taylor series becomes

$$u(t_1) \approx u(0) + \frac{1}{2}(-\omega^2 u(0))\Delta t^2$$

which may be written as

$$u^1 \approx u^0 - \frac{1}{2}\Delta t^2 \omega^2 u^0$$

but this is nothing but (8).

Now, consider  $u'(0) = V$ . With a centered difference approximation, this initial condition becomes

$$\frac{u^1 - u^{-1}}{2\Delta t} \approx V$$

which implies that

$$u^{-1} \approx u^1 - 2\Delta t V$$

When  $n = 0$ , (7) reads

$$u^1 = 2u^0 - u^{-1} - \Delta t^2 \omega^2 u^0$$

Inserting the expression for  $u^{-1}$ , we get

$$u^1 = 2u^0 - (u^1 - 2\Delta t V) - \Delta t^2 \omega^2 u^0$$

which implies that

$$u^1 = u^0 + \Delta t V - \frac{1}{2}\Delta t^2 \omega^2 u^0$$

With the Taylor series approach, we now get

$$u(t_1) \approx u(0) + V\Delta t + \frac{1}{2}(-\omega^2 u(0))\Delta t^2$$

which also gives

$$u^1 = u^0 + \Delta t V - \frac{1}{2}\Delta t^2 \omega^2 u^0$$

Filename: vib\_first\_step.



### Exercise 6: Find the minimal resolution of an oscillatory function

Sketch the function on a given mesh which has the highest possible frequency. That is, this oscillatory "cos-like" function has its maxima and minima at every two grid points. Find an expression for the frequency of this function, and use the result to find the largest relevant value of  $\omega\Delta t$  when  $\omega$  is the frequency of an oscillating function and  $\Delta t$  is the mesh spacing.

**Solution.** The smallest period must be  $2\Delta t$ , which means that  $\omega = \frac{2\pi}{2\Delta t} = \frac{\pi}{\Delta t}$ . This means that the largest value for  $\omega\Delta t$  is  $\pi$ .

Filename: vib\_largest\_wdt.

### Exercise 7: Visualize the accuracy of finite differences for a cosine function

We introduce the error fraction

$$E = \frac{[D_t D_t u]^n}{u''(t_n)}$$

to measure the error in the finite difference approximation  $D_t D_t u$  to  $u''$ . Compute  $E$  for the specific choice of a cosine/sine function of the form  $u = \exp(i\omega t)$  and show that

$$E = \left(\frac{2}{\omega\Delta t}\right)^2 \sin^2\left(\frac{\omega\Delta t}{2}\right).$$

Plot  $E$  as a function of  $p = \omega\Delta t$ . The relevant values of  $p$  are  $[0, \pi]$  (see Exercise 6 for why  $p > \pi$  does not make sense). The deviation of the curve from unity visualizes the error in the approximation. Also expand  $E$  as a Taylor polynomial in  $p$  up to fourth degree (use, e.g., `sympy`).

**Solution.**

$$\begin{aligned} E &= \frac{[D_t D_t u]^n}{u''(t_n)}, \\ &= \frac{u^{n+1} - 2u^n + u^{n-1}}{u''(t_n)\Delta t^2}, \end{aligned}$$

Since  $u(t) = \exp(i\omega t)$ , we have that  $u'(t) = i\omega \exp(i\omega t)$  and  $u''(t) = (i\omega)^2 \exp(i\omega t) = -\omega^2 \exp(i\omega t)$ , so we may proceed with  $E$  as

$$\begin{aligned}
E &= \frac{e^{i\omega(t_n+\Delta t)} - 2e^{i\omega t_n} + e^{i\omega(t_n-\Delta t)}}{-\omega^2 e^{i\omega t_n} \Delta t^2}, \\
&= \frac{e^{i\omega t_n} e^{i\omega \Delta t} - 2e^{i\omega t_n} + e^{i\omega t_n} e^{-i\omega \Delta t}}{-\omega^2 e^{i\omega t_n} \Delta t^2}, \\
&= \frac{e^{i\omega \Delta t} - 2 + e^{-i\omega \Delta t}}{-\omega^2 \Delta t^2}, \\
&= \frac{1}{-\omega^2 \Delta t^2} \frac{4}{4} (e^{i\omega \Delta t} - 2 + e^{-i\omega \Delta t}), \\
&= \left(\frac{2}{\omega \Delta t}\right)^2 \left(-\frac{e^{i\omega \Delta t} - 2 + e^{-i\omega \Delta t}}{4}\right), \\
&= \left(\frac{2}{\omega \Delta t}\right)^2 \left(-\frac{1}{2} \left(\frac{1}{2} e^{i\omega \Delta t} + e^{-i\omega \Delta t} - 1\right)\right), \\
&= \left(\frac{2}{\omega \Delta t}\right)^2 \left(-\frac{1}{2} (\cos(\omega \Delta t) - 1)\right).
\end{aligned}$$

Now, since  $\cos(\omega \Delta t) = 1 - 2\sin^2\left(\frac{\omega \Delta t}{2}\right)$ , we finally get

$$\begin{aligned}
E &= \left(\frac{2}{\omega \Delta t}\right)^2 \left(-\frac{1}{2} \left(\left(1 - 2\sin^2\left(\frac{\omega \Delta t}{2}\right)\right) - 1\right)\right), \\
&= \left(\frac{2}{\omega \Delta t}\right)^2 \sin^2\left(\frac{\omega \Delta t}{2}\right).
\end{aligned}$$

```

import matplotlib.pyplot as plt
import numpy as np
import sympy as sym

def E_fraction(p):
    return (2./p)**2*(np.sin(p/2.))**2

a = 0; b = np.pi
p = np.linspace(a, b, 100)
E_values = np.zeros(len(p))

# create 4th degree Taylor polynomial (also plotted)
p_ = sym.symbols('p_')
E = (2./p_)**2*(sym.sin(p_/2.))**2
E_series = E.series(p_, 0, 4).removeO()
print E_series
E_pyfunc = sym.lambdify([p_], E_series, modules='numpy')

# To avoid division by zero when p is 0, we rather take the limit
E_values[0] = sym.limit(E, p_, 0, dir='+') # ...when p --> 0, E --> 1
E_values[1:] = E_fraction(p[1:])

plt.plot(p, E_values, 'k-', p, E_pyfunc(p), 'k--')
plt.xlabel('p'); plt.ylabel('Error fraction')
plt.legend(['E', 'E Taylor'])
plt.savefig('tmp_error_fraction.png')

```

```
plt.savefig('tmp_error_fraction.pdf')
plt.show()
```

From the plot seen in Figure 13, we see how the error fraction  $E$  deviates from unity as  $p$  grows.




Figure 13: The error fraction as a function of  $p$ .

Filename: vib\_plot\_fd\_exp\_error.

### Exercise 8: Verify convergence rates of the error in energy

We consider the ODE problem  $u'' + \omega^2 u = 0$ ,  $u(0) = I$ ,  $u'(0) = V$ , for  $t \in (0, T]$ . The total energy of the solution  $E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2$  should stay constant. The error in energy can be computed as explained in Section 6.

Make a test function in a file `test_error_conv.py`, where code from `vib_undamped.py` is imported, but the `convergence_rates` and `test_convergence_rates` functions are copied and modified to also incorporate computations of the error in energy and the convergence rate of this error. The expected rate is 2.

**Solution.** The code:

```

import numpy as np
import matplotlib.pyplot as plt
from vib_undamped import solver, u_exact, visualize

def convergence_rates(m, solver_function, num_periods=8):
    """
    Return m-1 empirical estimates of the convergence rate
    based on m simulations, where the time step is halved
    for each simulation.
    solver_function(I, w, dt, T) solves each problem, where T
    is based on simulation for num_periods periods.
    """
    from math import pi
    w = 0.35; I = 0.3          # just chosen values
    P = 2*pi/w                 # period
    dt = P/30                  # 30 time step per period 2*pi/w
    T = P*num_periods
    Energy_const = 0.5*I**2*w**2 # initial energy when V = 0

    dt_values = []
    E_u_values = []           # error in u
    E_Energy_values = []      # error in energy
    for i in range(m):
        u, t = solver_function(I, w, dt, T)
        u_e = u_exact(t, I, w)
        E_u = np.sqrt(dt*np.sum((u_e-u)**2))
        E_u_values.append(E_u)
        Energy = 0.5*((u[2:] - u[:-2])/(2*dt))**2 + 0.5*w**2*u[1:-1]**2
        E_Energy = Energy - Energy_const
        E_Energy_norm = np.abs(E_Energy).max()
        E_Energy_values.append(E_Energy_norm)
        dt_values.append(dt)
        dt = dt/2

    r_u = [np.log(E_u_values[i-1]/E_u_values[i])/
           np.log(dt_values[i-1]/dt_values[i])
           for i in range(1, m, 1)]
    r_E = [np.log(E_Energy_values[i-1]/E_Energy_values[i])/
           np.log(dt_values[i-1]/dt_values[i])
           for i in range(1, m, 1)]
    return r_u, r_E

def test_convergence_rates():
    r_u, r_E = convergence_rates(m=5, solver_function=solver, num_periods=8)
    # Accept rate to 1 decimal place
    tol = 0.1
    assert abs(r_u[-1] - 2.0) < tol
    assert abs(r_E[-1] - 2.0) < tol

def main(solver_function=solver):
    import argparse
    from math import pi
    parser = argparse.ArgumentParser()
    parser.add_argument('--I', type=float, default=1.0)
    parser.add_argument('--w', type=float, default=2*pi)
    parser.add_argument('--dt', type=float, default=0.05)
    parser.add_argument('--num_periods', type=int, default=5)
    parser.add_argument('--savefig', action='store_true')
    # Hack to allow --SCITools options (read when importing scitools.std)
    parser.add_argument('--SCITools_easyviz_backend', default='matplotlib')
    a = parser.parse_args()
    I, w, dt, num_periods, savefig = \
        a.I, a.w, a.dt, a.num_periods, a.savefig

```

```

P = 2*pi/w # one period
T = P*num_periods
u, t = solver_function(I, w, dt, T)
visualize(u, t, I, w)
plt.show()

if __name__ == '__main__':
    #main()
    test_convergence_rates()

```

Filename: test\_error\_conv.

### Exercise 9: Use linear/quadratic functions for verification

This exercise is a generalization of Problem 1 to the extended model problem (59) where the damping term is either linear or quadratic. Solve the various subproblems and see how the results and problem settings change with the generalized ODE in case of linear or quadratic damping. By modifying the code from Problem 1, `sympy` will do most of the work required to analyze the generalized problem.

**Solution.** With a linear spring force, i.e.  $s(u) = cu$ , our model problem becomes

$$mu'' + f(u') + cu = F(t), \quad u(0) = I, \quad u'(0) = V, \quad t \in (0, T].$$

First we consider linear damping, i.e., when  $f(u') = bu'$ , and follow the text in Chapter 8.1. Discretizing the equation according to

$$[mD_t D_t u + f(D_{2t} u) + cu = F]^n,$$

implies that

$$m \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + b \frac{u^{n+1} - u^{n-1}}{2\Delta t} + cu^n = F^n.$$

The explicit formula for  $u$  at each new time level then becomes

$$u^{n+1} = (2mu^n + (\frac{b}{2}\Delta t - m)u^{n-1} + \Delta t^2(F^n - cu^n))(m + \frac{b}{2}\Delta t)^{-1}.$$

For the first time step, we use  $n = 0$  and a centered difference approximation for the initial condition on the derivative. This gives

$$u^1 = u^0 + \Delta t V + \frac{\Delta t^2}{2m}(-bV - cu^0 + F^0).$$

Next, we consider quadratic damping, i.e., when  $f(u') = bu'|u'|$ , and follow the text in Chapter 8.2. Discretizing the equation according to

$$[mD_t D_t u + bD_{2t} u |D_{2t} u| + cu = F]^n.$$

gives us

$$m \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + b \frac{u^{n+1} - u^n}{\Delta t} \frac{|u^n - u^{n-1}|}{\Delta t} + cu^n = F^n.$$

We solve for  $u^{n+1}$  to get the explicit updating formula as

$$u^{n+1} = (m + b|u^n - u^{n-1}|)^{-1} \times (2mu^n - mu^{n-1} + bu^n|u^n - u^{n-1}| + \Delta t^2(F^n - cu^n)) .$$

and the equation for the first time step as

$$u^1 = u^0 + \Delta t V + \frac{\Delta t^2}{2m} (-bV|V| - cu^0 + F^0) .$$

Turning to verification with MMS and  $u_e(t) = ct + d$ , we get  $d = I$  and  $c = V$  independent of the damping term, so these parameter values stay as for the undamped case.

Proceeding with linear damping, we get from chapter 8.5 that

$$F(t) = bV + c(Vt + I) .$$

(Note that there are two different  $c$  parameters here, one from  $u_e = ct + d$  and one from the spring force  $cu$ . The first one disappears, however, as it is switched with  $V$ .)

To show that  $u_e$  is a perfect solution also to the discrete equations, we insert  $u_e$  and  $F$  into

$$[mD_t D_t u + bD_{2t} u + cu = F]^n .$$

This gives

$$[mD_t D_t (Vt + I) + bD_{2t} (Vt + I) + c(Vt + I) = bV + c(Vt + I)]^n ,$$

which may be split up as

$$m[D_t D_t (Vt + I)]^n + b[D_{2t} (Vt + I)]^n + c[(Vt + I)]^n = b[V]^n + c[(Vt + I)]^n .$$

Simplifying, we note that the first term is zero and that  $c[(Vt + I)]^n$  appears with the same sign on each side of the equation. Thus, dropping these terms, and cancelling the common factor  $b$ , we are left with

$$[D_{2t} (Vt + I)]^n = [V]^n .$$

It therefore remains to show that  $[D_{2t} (Vt + I)]^n$  is equal to  $[V]^n = V$ . We write out the left hand side as

$$\begin{aligned} [D_{2t} (Vt + I)]^n &= \frac{(Vt_{n+1} + I) - (Vt_{n-1} + I)}{2\Delta t} \\ &= \frac{V(t_{n+1} - t_{n-1})}{2\Delta t} \\ &= \frac{V((t_n + \Delta t) - (t_n - \Delta t))}{2\Delta t} \\ &= V, \end{aligned}$$

which shows that the two sides of the equation are equal and that the discrete equations are fulfilled exactly for the given  $u_e$  function.

If the damping is rather quadratic, we find from chapter 8.5 that

$$F(t) = b|V|V + c(Vt + I).$$

As with linear damping, we show that  $u_e$  is a perfect solution also to the discrete equations by inserting  $u_e$  and  $F$  into

$$[mD_t D_t u + bD_{2t} u |D_{2t} u| + cu = F]^n.$$

We then get

$$[mD_t D_t (Vt + I) + bD_{2t} (Vt + I) |D_{2t} (Vt + I)| + c(Vt + I) = b|V|V + c(Vt + I)]^n,$$

which simplifies to

$$[bD_{2t} (Vt + I) |D_{2t} (Vt + I)| = b|V|V]^n$$

and further to

$$[D_{2t} (Vt + I)]^n [|D_{2t} (Vt + I)|]^n = |V|V$$

which simply states that

$$V|V| = |V|V.$$

Thus,  $u_e$  fulfills the discrete equations exactly also when the damping term is quadratic.

When the exact solution is changed to become quadratic or cubic, the situation is more complicated.

For a quadratic solution  $u_e$  combined with (zero damping or) linear damping, the output from the program below shows that the discrete equations are fulfilled exactly. However, this is not the case with nonlinear damping, where only the first step gives zero residual.

For a cubic solution  $u_e$ , we get a nonzero residual for (zero damping and) linear and nonlinear damping.

```
import sympy as sym
import numpy as np

# The code in vib_undamped_verify_mms.py is here generalized
# to treat the model m*u'' + f(u') + c*u = F(t), where the
# damping term f(u') = 0, b*u' or b*V*abs(V).

def ode_source_term(u, damping):
    """Return the terms in the ODE that the source term
    must balance, here m*u'' + f(u') + c*u.
    u is a symbolic Python function of t."""
    if damping == 'zero':
        return m*sym.diff(u(t), t, t) + c*u(t)
    elif damping == 'linear':
        return m*sym.diff(u(t), t, t) + \
            b*sym.diff(u(t), t) + c*u(t)
    else: # damping is nonlinear
```

```

        return m*sym.diff(u(t), t, t) + \
            b*sym.diff(u(t), t)*abs(sym.diff(u(t), t)) + c*u(t)

def residual_discrete_eq(u, damping):
    """Return the residual of the discrete eq. with u inserted."""
    if damping == 'zero':
        R = m*DtDt(u, dt) + c*u(t) - F
    elif damping == 'linear':
        R = m*DtDt(u, dt) + b*D2t(u, dt) + c*u(t) - F
    else:
        # damping is nonlinear
        R = m*DtDt(u, dt) + b*Dt_p_half(u, dt)*\
            abs(Dt_m_half(u, dt)) + c*u(t) - F
    return sym.simplify(R)

def residual_discrete_eq_step1(u, damping):
    """Return the residual of the discrete eq. at the first
    step with u inserted."""
    half = sym.Rational(1,2)
    if damping == 'zero':
        R = u(t+dt) - u(t) - dt*V - \
            half*dt**2*(F.subs(t, 0)/m) + half*dt**2*(c/m)*I
    elif damping == 'linear':
        R = u(t+dt) - (I + dt*V + \
            half*(dt**2/m)*(-b*V - c*I + F.subs(t, 0)))
    else:
        # damping is nonlinear
        R = u(t+dt) - (I + dt*V + \
            half*(dt**2/m)*(-b*V*abs(V) - c*I + F.subs(t, 0)))
    R = R.subs(t, 0) # t=0 in the rhs of the first step eq.
    return sym.simplify(R)

def DtDt(u, dt):
    """Return 2nd-order finite difference for u_tt.
    u is a symbolic Python function of t.
    """
    return (u(t+dt) - 2*u(t) + u(t-dt))/dt**2

def D2t(u, dt):
    """Return 2nd-order finite difference for u_t.
    u is a symbolic Python function of t.
    """
    return (u(t+dt) - u(t-dt))/(2.0*dt)

def Dt_p_half(u, dt):
    """Return 2nd-order finite difference for u_t, sampled at n+1/2,
    i.e, n pluss one half... u is a symbolic Python function of t.
    """
    return (u(t+dt) - u(t))/dt

def Dt_m_half(u, dt):
    """Return 2nd-order finite difference for u_t, sampled at n-1/2,
    i.e, n minus one half.... u is a symbolic Python function of t.
    """
    return (u(t) - u(t-dt))/dt

def main(u, damping):
    """
    Given some chosen solution u (as a function of t, implemented
    as a Python function), use the method of manufactured solutions
    to compute the source term f, and check if u also solves
    the discrete equations.
    """
    print '=== Testing exact solution: %s ===' % u(t)
    print "Initial conditions u(0)=%s, u'(0)=%s:" % \
        (u(t).subs(t, 0), sym.diff(u(t), t).subs(t, 0))

```



```

# Method of manufactured solution requires fitting F
global F # source term in the ODE
F = sym.simplify(ode_source_term(u, damping))

# Residual in discrete equations (should be 0)
print 'residual step1:', residual_discrete_eq_step1(u, damping)
print 'residual:', residual_discrete_eq(u, damping)

def linear(damping):
    def u_e(t):
        """Return chosen linear exact solution."""
        # General linear function u_e = c*t + d
        # Initial conditions u(0)=I, u'(0)=V require c=V, d=I
        return V*t + I

    main(u_e, damping)

def quadratic(damping):
    # Extend with quadratic functions
    q = sym.Symbol('q') # arbitrary constant in quadratic term

    def u_e(t):
        return q*t**2 + V*t + I

    main(u_e, damping)

def cubic(damping):
    r, q = sym.symbols('r q')

    main(lambda t: r*t**3 + q*t**2 + V*t + I, damping)

def solver(I, V, F, b, c, m, dt, T, damping):
    """
    Solve m*u'' + f(u') + c*u = F for t in (0,T], u(0)=I and u'(0)=V,
    by a central finite difference method with time step dt.
    F(t) is a callable Python function.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)

    if damping == 'zero':
        u[0] = I
        u[1] = u[0] - 0.5*dt**2*(c/m)*u[0] + \
            0.5*dt**2*(F(t[0])/m + dt*V)
        for n in range(1, Nt):
            u[n+1] = 2*u[n] - u[n-1] - \
                dt**2*(c/m)*u[n] + dt**2*(F(t[n])/m)
    elif damping == 'linear':
        u[0] = I
        u[1] = u[0] + dt*V + \
            0.5*(dt**2/m)*(-b*V - c*u[0] + F(t[0]))
        for n in range(1, Nt):
            u[n+1] = (2*m*u[n] + (b*dt/2.-m)*u[n-1] + \
                dt**2*(F(t[n])-c*u[n]))/(m+b*dt/2.)
    else: # damping is quadratic
        u[0] = I
        u[1] = u[0] + dt*V + \
            0.5*(dt**2/m)*(-b*V*abs(V) - c*u[0] + F(t[0]))
        for n in range(1, Nt):

```

```

        u[n+1] = 1./(m+b*abs(u[n]-u[n-1])) * \
            (2*m*u[n] - m*u[n-1] + b*u[n]*\
            abs(u[n]-u[n-1])+dt**2*(F(t[n])-c*u[n]))

    return u, t

import nose.tools as nt

def test_quadratic_exact_solution(damping):
    # Transform global symbolic variables to functions and numbers
    # for numerical computations

    global p, V, I, b, c, m
    p, V, I, b, c, m = 2.3, 0.9, 1.2, 2.1, 1.6, 1.3 # i.e., as numbers
    global F, t
    u_e = lambda t: p*t**2 + V*t + I
    F = ode_source_term(u_e, damping) # fit source term
    F = sym.lambdify(t, F) # ...numerical Python function

    from math import pi, sqrt
    dt = 2*pi/sqrt(c/m)/10 # 10 steps per period 2*pi/w, w=sqrt(c/m)
    u, t = solver(I=I, V=V, F=F, b=b, c=c, m=m, dt=dt,
        T=(2*pi/sqrt(c/m))*2, damping=damping)

    u_e = u_e(t)
    error = np.abs(u - u_e).max()
    nt.assert_almost_equal(error, 0, delta=1E-12)
    print 'Error in computing a quadratic solution:', error

if __name__ == '__main__':
    damping = ['zero', 'linear', 'quadratic']
    for e in damping:
        V, t, I, dt, m, b, c = sym.symbols('V t I dt m b c') # global
        F = None # global variable for the source term in the ODE
        print '-----Damping:', e
        linear(e) # linear solution used for MMS
        quadratic(e) # quadratic solution for MMS
        cubic(e) # ... and cubic
        test_quadratic_exact_solution(e)

```

Filename: vib\_verify\_mms.

## Exercise 10: Use an exact discrete solution for verification

Write a test function in a separate file that employs the exact discrete solution (20) to verify the implementation of the `solver` function in the file `vib_undamped.py`.

**Solution.** The code:

```

"""Verify exact solution of vib_undamped.solver function."""
from vib_undamped import solver
from numpy import arcsin as asin, pi, cos, abs
from scitools.std import plot

def test_solver_exact_discrete_solution():
    def tilde_w(w, dt):
        return (2./dt)*asin(w*dt/2.)

    def u_numerical_exact(t):
        return I*cos(tilde_w(w, dt)*t)

    w = 2.5

```

```

I = 1.5

# Estimate period and time step
P = 2*pi/w
num_periods = 4
T = num_periods*P
N = 5          # time steps per period
dt = P/N
u, t = solver(I, w, dt, T)
u_e = u_numerical_exact(t)
diff = abs(u_e - u).max()
# Make a plot in a file, but not on the screen
plot(t, u, 'bo', t, u_e, 'r-',
      legend=('numerical', 'exact'), show=False, savefig='tmp.png')

assert diff < 1E-14

test_solver_exact_discrete_solution()

```

Filename: test\_vib\_undamped\_exact\_discrete\_sol.

### Exercise 11: Use analytical solution for convergence rate tests

The purpose of this exercise is to perform convergence tests of the problem (59) when  $s(u) = \omega^2 u$  and  $F(t) = A \sin \phi t$ . Find the complete analytical solution to the problem in this case (most textbooks on mechanics or ordinary differential equations list the various elements you need to write down the exact solution). Modify the `convergence_rate` function from the `vib_undamped.py` program to perform experiments with the extended model. Verify that the error is of order  $\Delta t^2$ .

**Solution.** The code:

```

import numpy as np
import matplotlib.pyplot as plt
from vib_verify_mms import solver

def u_exact(t, I, V, A, f, c, m):
    '''Found by solving mu'' + cu = F in Wolfram alpha'''
    k_1 = I
    k_2 = (V - A*2*np.pi*f/(c - 4*np.pi**2*f**2*m))*np.sqrt(m/float(c))
    return A*np.sin(2*np.pi*f*t)/(c - 4*np.pi**2*f**2*m) + \
        k_2*np.sin(np.sqrt(c/float(m))*t) + \
        k_1*np.cos(np.sqrt(c/float(m))*t)

def convergence_rates(N_est, solver_function, num_periods=8):
    """
    Returns N_est-1 empirical estimates of the convergence rate
    based on N_est simulations, where the time step is halved
    for each simulation.
    solver_function(I, V, F, c, m, dt, T, damping) solves
    each problem, where T is based on simulation for
    num_periods periods.
    """

    def F(t):

```

```

        """External driving force"""
        return A*np.sin(2*np.pi*f*t)

    b, c, m = 0, 1.6, 1.3 # just some chosen values
    I = 0                 # init. cond. u(0)
    V = 0                 # init. cond. u'(0)
    A = 1.0               # amplitude of driving force
    f = 1.0               # chosen frequency of driving force
    damping = 'zero'

    P = 1/f
    dt = P/30             # 30 time step per period 2*pi/w
    T = P*num_periods

    dt_values = []
    E_values = []
    for i in range(N_est):
        u, t = solver_function(I, V, F, b, c, m, dt, T, damping)
        u_e = u_exact(t, I, V, A, f, c, m)
        E = np.sqrt(dt*np.sum((u_e-u)**2))
        dt_values.append(dt)
        E_values.append(E)
        dt = dt/2

    #plt.plot(t, u, 'b--', t, u_e, 'r-'); plt.grid(); plt.show()

    r = [np.log(E_values[i-1]/E_values[i])/
         np.log(dt_values[i-1]/dt_values[i])
         for i in range(1, N_est, 1)]
    print r
    return r

def test_convergence_rates():

    r = convergence_rates(N_est=5, solver_function=solver, num_periods=8)
    # Accept rate to 1 decimal place
    tol = 0.1
    assert abs(r[-1] - 2.0) < tol

if __name__ == '__main__':
    test_convergence_rates()

```

The output from the program shows that  $r$  approaches 2.  
 Filename: vib\_conv\_rate.

## Exercise 12: Investigate the amplitude errors of many solvers

Use the program `vib_undamped_odespy.py` from Section 5.4 and the amplitude estimation from the `amplitudes` function in the `vib_undamped.py` file (see Section 3.5) to investigate how well famous methods for 1st-order ODEs can preserve the amplitude of  $u$  in undamped oscillations. Test, for example, the 3rd- and 4th-order Runge-Kutta methods (RK3, RK4), the Crank-Nicolson method (CrankNicolson), the 2nd- and 3rd-order Adams-Bashforth methods (AdamsBashforth2, AdamsBashforth3), and a 2nd-order Backwards scheme (Backward2Step). The relevant governing equations are listed in the beginning of Section 5.

**Solution.** The code:

```
import scitools.std as plt
#import matplotlib.pyplot as plt
from vib_empirical_analysis import minmax, amplitudes
import sys
import odespy
import numpy as np

def f(u, t, w=1):
    # v, u numbering for EulerCromer to work well
    v, u = u # u is array of length 2 holding our [v, u]
    return [-w**2*u, v]

def run_solvers_and_check_amplitudes(solvers, timesteps_per_period=20,
                                     num_periods=1, I=1, w=2*np.pi):
    P = 2*np.pi/w # duration of one period
    dt = P/timesteps_per_period
    Nt = num_periods*timesteps_per_period
    T = Nt*dt
    t_mesh = np.linspace(0, T, Nt+1)

    file_name = 'Amplitudes' # initialize filename for plot
    for solver in solvers:
        solver.set(f_kwargs={'w': w})
        solver.set_initial_condition([0, I])
        u, t = solver.solve(t_mesh)

        solver_name = \
            'CrankNicolson' if solver.__class__.__name__ == \
            'MidpointImplicit' else solver.__class__.__name__
        file_name = file_name + '_' + solver_name

        minima, maxima = minmax(t, u[:,0])
        a = amplitudes(minima, maxima)
        plt.plot(range(len(a)), a, '-', label=solver_name)
        plt.hold('on')

    plt.xlabel('Number of periods')
    plt.ylabel('Amplitude (absolute value)')
    plt.legend(loc='upper left')
    plt.savefig(file_name + '.png')
    plt.savefig(file_name + '.pdf')
    plt.show()

# Define different sets of experiments
solvers_CNB2 = [odespy.CrankNicolson(f, nonlinear_solver='Newton'),
                odespy.Backward2Step(f)]
solvers_RK34 = [odespy.RK3(f),
                odespy.RK4(f)]
solvers_AB = [odespy.AdamsBashforth2(f),
              odespy.AdamsBashforth3(f)]

if __name__ == '__main__':
    # Default values
    timesteps_per_period = 30
    solver_collection = 'CNB2'
    num_periods = 100
    # Override from command line
    try:
        # Example: python vib_undamped_odespy.py 30 RK34 50
        timesteps_per_period = int(sys.argv[1])
```

```

solver_collection = sys.argv[2]
num_periods = int(sys.argv[3])
except IndexError:
    pass # default values are ok
solvers = eval('solvers_' + solver_collection) # list of solvers
run_solvers_and_check_amplitudes(solvers,
                                timesteps_per_period,
                                num_periods)

```

Running the code, we get the plots seen in Figure 14, Figure 15 and Figure 16. They show that RK4 is superior to the others, but that also **CrankNicolson** performs well. In fact, with RK4 the amplitude changes by less than 0.1 per cent over the interval.




Figure 14: The amplitude as it changes over 100 periods for RK3 and RK4.

Filename: vib\_amplitude\_errors.

### Exercise 13: Minimize memory usage of a vibration solver

The program `vib.py`<sup>23</sup> stores the complete solution  $u^0, u^1, \dots, u^{N_t}$  in memory, which is convenient for later plotting. Make a memory minimizing version of this program where only the last three  $u^{n+1}$ ,  $u^n$ , and  $u^{n-1}$  values are stored in memory. Write each computed  $(t_{n+1}, u^{n+1})$  pair to file. Visualize the data in

<sup>23</sup><http://tinyurl.com/nm5587k/vib/vib.py>




Figure 15: The amplitude as it changes over 100 periods for Crank-Nicolson and Backward 2 step.

the file (a cool solution is to read one line at a time and plot the  $u$  value using the line-by-line plotter in the `visualize_front_ascii` function - this technique makes it trivial to visualize very long time simulations).

**Solution.** The code:

```
import numpy as np
import scitools.std as plt

def solve_and_store(filename, I, V, m, b, s, F, dt, T, damping='linear'):
    """
    Solve  $m u'' + f(u') + s(u) = F(t)$  for  $t$  in  $(0, T]$ ,  $u(0)=I$  and  $u'(0)=V$ ,
    by a central finite difference method with time step  $dt$ .
    If damping is 'linear',  $f(u')=b*u$ , while if damping is
    'quadratic',  $f(u')=b*u'*abs(u')$ .  $F(t)$  and  $s(u)$  are Python functions.
    The solution is written to file (filename).
    Naming convention: we use the name  $u$  for the new solution to be
    computed,  $u_1$  for the solution one time step prior to that and  $u_2$ 
    for the solution two time steps prior to that.
    Returns min and max  $u$  values needed for subsequent plotting.
    """
    dt = float(dt); b = float(b); m = float(m) # avoid integer div.
    Nt = int(round(T/dt))
    outfile = open(filename, 'w')
    outfile.write('Time          Position\n')
```




Figure 16: The amplitude as it changes over 100 periods for Adams-Bashforth 2 and 3.

```

u_2 = I
u_min = u_max = u_2
outfile.write('%6.3f          %7.5f\n' % (0*dt, u_2))
if damping == 'linear':
    u_1 = u_2 + dt*V + dt**2/(2*m)*(-b*V - s(u_2) + F(0*dt))
elif damping == 'quadratic':
    u_1 = u_2 + dt*V + \
        dt**2/(2*m)*(-b*V*abs(V) - s(u_2) + F(0*dt))
if u_1 < u_2:
    u_min = u_1
else: # either equal or u_1 > u_2
    u_max = u_1
outfile.write('%6.3f          %7.5f\n' % (1*dt, u_1))

for n in range(1, Nt):
    # compute solution at next time step
    if damping == 'linear':
        u = (2*m*u_1 + (b*dt/2 - m)*u_2 +
            dt**2*(F(n*dt) - s(u_1)))/(m + b*dt/2)
    elif damping == 'quadratic':
        u = (2*m*u_1 - m*u_2 + b*u_1*abs(u_1 - u_2)
            + dt**2*(F(n*dt) - s(u_1)))/\
            (m + b*abs(u_1 - u_2))
    if u < u_min:
        u_min = u
    elif u > u_max:
        u_max = u

```



```

        # write solution to file
        outfile.write('%6.3f          %7.5f\n' % ((n+1)*dt, u))
        # switch references before next step
        u_2, u_1, u = u_1, u, u_2

    outfile.close()
    return u_min, u_max

def main():
    import argparse
    parser = argparse.ArgumentParser()
    parser.add_argument('--I', type=float, default=1.0)
    parser.add_argument('--V', type=float, default=0.0)
    parser.add_argument('--m', type=float, default=1.0)
    parser.add_argument('--b', type=float, default=0.0)
    parser.add_argument('--s', type=str, default='u')
    parser.add_argument('--F', type=str, default='0')
    parser.add_argument('--dt', type=float, default=0.05)
    parser.add_argument('--T', type=float, default=10)
    parser.add_argument('--window_width', type=float, default=30.,
                        help='Number of periods in a window')
    parser.add_argument('--damping', type=str, default='linear')
    parser.add_argument('--savefig', action='store_true')
    # Hack to allow --SCITools options (scitools.std reads this argument
    # at import)
    parser.add_argument('--SCITools_easyviz_backend', default='matplotlib')
    a = parser.parse_args()
    from scitools.std import StringFunction
    s = StringFunction(a.s, independent_variable='u')
    F = StringFunction(a.F, independent_variable='t')
    I, V, m, b, dt, T, window_width, savefig, damping = \
        a.I, a.V, a.m, a.b, a.dt, a.T, a.window_width, a.savefig, \
        a.damping

    filename = 'vibration_sim.dat'
    u_min, u_max = solve_and_store(filename, I, V, m, b, s, F, dt, T, damping)

    read_and_plot(filename, u_min, u_max)

def read_and_plot(filename, u_min, u_max):
    """
    Read file and plot u vs t line by line in a
    terminal window (only using ascii characters).
    """
    from scitools.avplotter import Plotter
    import time
    umin = 1.2*u_min; umax = 1.2*u_max
    p = Plotter(ymin=umin, ymax=umax, width=60, symbols='+o')
    fps = 10
    infile = open(filename, 'r')

    # read and treat one line at a time
    infile.readline() # skip header line
    for line in infile:
        time_and_pos = line.split() # gives list with 2 elements
        t = float(time_and_pos[0])
        u = float(time_and_pos[1])
        #print 'time: %g position: %g' % (time, pos)
        print p.plot(t, u), '%.2f' % (t)
        time.sleep(1/float(fps))

if __name__ == '__main__':
    main()

```

Filename: `vib_memsave`.

### Exercise 14: Implement the solver via classes

Reimplement the `vib.py` program using a class `Problem` to hold all the physical parameters of the problem, a class `Solver` to hold the numerical parameters and compute the solution, and a class `Visualizer` to display the solution.

**Hint.** Use the ideas and examples from Section ?? and ?? in [1]. More specifically, make a superclass `Problem` for holding the scalar physical parameters of a problem and let subclasses implement the  $s(u)$  and  $F(t)$  functions as methods. Try to call up as much existing functionality in `vib.py` as possible.

Filename: `vib_class`.

### Exercise 15: Interpret $[D_t D_t u]^n$ as a forward-backward difference

Show that the difference  $[D_t D_t u]^n$  is equal to  $[D_t^+ D_t^- u]^n$  and  $D_t^- D_t^+ u]^n$ . That is, instead of applying a centered difference twice one can alternatively apply a mixture forward and backward differences. Filename: `vib_DtDt_fw_bw`.

### Exercise 16: Use a backward difference for the damping term

As an alternative to discretizing the damping terms  $\beta u'$  and  $\beta |u'|u'$  by centered differences, we may apply backward differences:

$$\begin{aligned} [u']^n &\approx [D_t^- u]^n, \\ [|u'|u']^n &\approx [|D_t^- u| D_t^- u]^n = |[D_t^- u]^n| [D_t^- u]^n. \end{aligned}$$

The advantage of the backward difference is that the damping term is evaluated using known values  $u^n$  and  $u^{n-1}$  only. Extend the `vib.py`<sup>24</sup> code with a scheme based on using backward differences in the damping terms. Add statements to compare the original approach with centered difference and the new idea launched in this exercise. Perform numerical experiments to investigate how much accuracy that is lost by using the backward differences. Filename: `vib_gen_bwdamping`.

### Exercise 17: Analysis of the Euler-Cromer scheme

The Euler-Cromer scheme for the model problem  $u'' + \omega^2 u = 0$ ,  $u(0) = I$ ,  $u'(0) = 0$ , is given in (54)-(53). Find the exact discrete solutions of this scheme and show that the solution for  $u^n$  coincides with that found in Section 4.

<sup>24</sup><http://tinyurl.com/nm5587k/vib/vib.py>

**Hint.** Use an “ansatz”  $u^n = I \exp(i\tilde{\omega}\Delta t n)$  and  $v^n = qu^n$ , where  $\tilde{\omega}$  and  $q$  are unknown parameters. The following formula is handy:

$$e^{i\tilde{\omega}\Delta t} + e^{i\tilde{\omega}(-\Delta t)} - 2 = 2(\cosh(i\tilde{\omega}\Delta t) - 1) = -4\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right).$$

**Solution.** We follow the ideas in Section 4. Inserting  $u^n = I \exp(i\tilde{\omega}\Delta t n)$  and  $v^n = qu^n$  in (54)-(53) and dividing by  $I \exp(i\tilde{\omega}\Delta t n)$  gives

$$q \exp(i\tilde{\omega}\Delta t) = q - \omega^2 \Delta t, \quad (82)$$

$$\exp(i\tilde{\omega}\Delta t) = 1 + \Delta t q \exp(i\tilde{\omega}\Delta t). \quad (83)$$

Solving (83) with respect to  $q$  gives

$$q = \frac{1}{\Delta t} (1 - \exp(i\tilde{\omega}\Delta t)).$$

Inserting this expression for  $q$  in (82) results in

$$\exp(i\tilde{\omega}\Delta t) + \exp(-i\tilde{\omega}\Delta t) - 2 = -\omega^2 \Delta t^2.$$

Using the relation  $\exp(i\tilde{\omega}(\Delta t)) + \exp(i\tilde{\omega}(-\Delta t)) - 2 = -4\sin^2(\frac{\tilde{\omega}\Delta t}{2})$  gives

$$-4\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = -\omega^2 \Delta t^2,$$

or after dividing by 4,

$$\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = \left(\frac{1}{2}\omega\Delta t\right)^2,$$

which is the same equation for  $\tilde{\omega}$  as found in Section 4, such that  $\tilde{\omega}$  is the same. The accuracy, stability, and formula for the exact discrete solution are then all the same as derived in Section 4.

## 10 Applications of vibration models

The following text derives some of the most well-known physical problems that lead to second-order ODE models of the type addressed in this document. We consider a simple spring-mass system; thereafter extended with nonlinear spring, damping, and external excitation; a spring-mass system with sliding friction; a simple and a physical (classical) pendulum; and an elastic pendulum.

### 10.1 Oscillating mass attached to a spring

The most fundamental mechanical vibration system is depicted in Figure 17. A body with mass  $m$  is attached to a spring and can move horizontally without friction (in the wheels). The position of the body is given by the vector  $\mathbf{r}(t) =$




Figure 17: Simple oscillating mass.

$u(t)\mathbf{i}$ , where  $\mathbf{i}$  is a unit vector in  $x$  direction. There is only one force acting on the body: a spring force  $\mathbf{F}_s = -ku\mathbf{i}$ , where  $k$  is a constant. The point  $x = 0$ , where  $u = 0$ , must therefore correspond to the body's position where the spring is neither extended nor compressed, so the force vanishes.

The basic physical principle that governs the motion of the body is Newton's second law of motion:  $\mathbf{F} = m\mathbf{a}$ , where  $\mathbf{F}$  is the sum of forces on the body,  $m$  is its mass, and  $\mathbf{a} = \ddot{\mathbf{r}}$  is the acceleration. We use the dot for differentiation with respect to time, which is usual in mechanics. Newton's second law simplifies here to  $-\mathbf{F}_s = m\ddot{u}\mathbf{i}$ , which translates to

$$-ku = m\ddot{u}.$$

Two initial conditions are needed:  $u(0) = I$ ,  $\dot{u}(0) = V$ . The ODE problem is normally written as

$$m\ddot{u} + ku = 0, \quad u(0) = I, \quad \dot{u}(0) = V. \quad (84)$$

It is not uncommon to divide by  $m$  and introduce the frequency  $\omega = \sqrt{k/m}$ :

$$\ddot{u} + \omega^2 u = 0, \quad u(0) = I, \quad \dot{u}(0) = V. \quad (85)$$

This is the model problem in the first part of this chapter, with the small difference that we write the time derivative of  $u$  with a dot above, while we used  $u'$  and  $u''$  in previous parts of the document.

Since only one scalar mathematical quantity,  $u(t)$ , describes the complete motion, we say that the mechanical system has one degree of freedom (DOF).

**Scaling.** For numerical simulations it is very convenient to scale (85) and thereby get rid of the problem of finding relevant values for all the parameters  $m$ ,  $k$ ,  $I$ , and  $V$ . Since the amplitude of the oscillations are dictated by  $I$  and  $V$  (or more precisely,  $V/\omega$ ), we scale  $u$  by  $I$  (or  $V/\omega$  if  $I = 0$ ):

$$\bar{u} = \frac{u}{I}, \quad \bar{t} = \frac{t}{t_c}.$$

The time scale  $t_c$  is normally chosen as the inverse period  $2\pi/\omega$  or angular frequency  $1/\omega$ , most often as  $t_c = 1/\omega$ . Inserting the dimensionless quantities  $\bar{u}$  and  $\bar{t}$  in (85) results in the scaled problem

$$\frac{d^2\bar{u}}{d\bar{t}^2} + \bar{u} = 0, \quad \bar{u}(0) = 1, \quad \frac{\bar{u}}{\bar{t}}(0) = \beta = \frac{V}{I\omega},$$

where  $\beta$  is a dimensionless number. Any motion that starts from rest ( $V = 0$ ) is free of parameters in the scaled model!

**The physics.** The typical physics of the system in Figure 17 can be described as follows. Initially, we displace the body to some position  $I$ , say at rest ( $V = 0$ ). After releasing the body, the spring, which is extended, will act with a force  $-kI\mathbf{i}$  and pull the body to the left. This force causes an acceleration and therefore increases velocity. The body passes the point  $x = 0$ , where  $u = 0$ , and the spring will then be compressed and act with a force  $kx\mathbf{i}$  against the motion and cause retardation. At some point, the motion stops and the velocity is zero, before the spring force  $kx\mathbf{i}$  accelerates the body in positive direction. The result is that the body accelerates back and forth. As long as there is no friction forces to damp the motion, the oscillations will continue forever.

## 10.2 General mechanical vibrating system




Figure 18: General oscillating system.

The mechanical system in Figure 17 can easily be extended to the more general system in Figure 18, where the body is attached to a spring and a dashpot, and also subject to an environmental force  $F(t)\mathbf{i}$ . The system has still only one degree of freedom since the body can only move back and forth parallel to the  $x$  axis. The spring force was linear,  $\mathbf{F}_s = -ku\mathbf{i}$ , in Section 10.1, but in more general cases it can depend nonlinearly on the position. We therefore set  $\mathbf{F}_s = s(u)\mathbf{i}$ . The dashpot, which acts as a damper, results in a force  $\mathbf{F}_d$  that depends on the body's velocity  $\dot{u}$  and that always acts against the motion. The mathematical model of the force is written  $\mathbf{F}_d = f(\dot{u})\mathbf{i}$ . A positive  $\dot{u}$  must

result in a force acting in the positive  $x$  direction. Finally, we have the external environmental force  $\mathbf{F}_e = F(t)\mathbf{i}$ .

Newton's second law of motion now involves three forces:

$$F(t)\mathbf{i} + f(\dot{u})\mathbf{i} - s(u)\mathbf{i} = m\ddot{u}\mathbf{i}.$$

The common mathematical form of the ODE problem is

$$m\ddot{u} + f(\dot{u}) + s(u) = F(t), \quad u(0) = I, \quad \dot{u}(0) = V. \quad (86)$$

This is the generalized problem treated in the last part of the present chapter, but with prime denoting the derivative instead of the dot.

The most common models for the spring and dashpot are linear:  $f(\dot{u}) = b\dot{u}$  with a constant  $b \geq 0$ , and  $s(u) = ku$  for a constant  $k$ .

**Scaling.** A specific scaling requires specific choices of  $f$ ,  $s$ , and  $F$ . Suppose we have

$$f(\dot{u}) = b|\dot{u}|\dot{u}, \quad s(u) = ku, \quad F(t) = A \sin(\phi t).$$

We introduce dimensionless variables as usual,  $\bar{u} = u/u_c$  and  $\bar{t} = t/t_c$ . The scale  $u_c$  depends both on the initial conditions and  $F$ , but as time grows, the effect of the initial conditions die out and  $F$  will drive the motion. Inserting  $\bar{u}$  and  $\bar{t}$  in the ODE gives

$$m \frac{u_c}{t_c^2} \frac{d^2 \bar{u}}{d\bar{t}^2} + b \frac{u_c^2}{t_c^2} \left| \frac{d\bar{u}}{d\bar{t}} \right| \frac{d\bar{u}}{d\bar{t}} + k u_c \bar{u} = A \sin(\phi t_c \bar{t}).$$

We divide by  $u_c/t_c^2$  and demand the coefficients of the  $\bar{u}$  and the forcing term from  $F(t)$  to have unit coefficients. This leads to the scales

$$t_c = \sqrt{\frac{m}{k}}, \quad u_c = \frac{A}{k}.$$

The scaled ODE becomes

$$\frac{d^2 \bar{u}}{d\bar{t}^2} + 2\beta \left| \frac{d\bar{u}}{d\bar{t}} \right| \frac{d\bar{u}}{d\bar{t}} + \bar{u} = \sin(\gamma \bar{t}), \quad (87)$$

where there are two dimensionless numbers:

$$\beta = \frac{Ab}{2mk}, \quad \gamma = \phi \sqrt{\frac{m}{k}}.$$

The  $\beta$  number measures the size of the damping term (relative to unity) and is assumed to be small, basically because  $b$  is small. The  $\phi$  number is the ratio of the time scale of free vibrations and the time scale of the forcing. The scaled initial conditions have two other dimensionless numbers as values:

$$\bar{u}(0) = \frac{Ik}{A}, \quad \frac{d\bar{u}}{d\bar{t}} = \frac{t_c}{u_c} V = \frac{V}{A} \sqrt{mk}.$$

### 10.3 A sliding mass attached to a spring

Consider a variant of the oscillating body in Section 10.1 and Figure 17: the body rests on a flat surface, and there is sliding friction between the body and the surface. Figure 19 depicts the problem.




Figure 19: Sketch of a body sliding on a surface.

The body is attached to a spring with spring force  $-s(u)\mathbf{i}$ . The friction force is proportional to the normal force on the surface,  $-mg\mathbf{j}$ , and given by  $-f(\dot{u})\mathbf{i}$ , where

$$f(\dot{u}) = \begin{cases} -\mu mg, & \dot{u} < 0, \\ \mu mg, & \dot{u} > 0, \\ 0, & \dot{u} = 0 \end{cases}$$

Here,  $\mu$  is a friction coefficient. With the signum function

$$\text{sign}(x) = \begin{cases} -1, & x < 0, \\ 1, & x > 0, \\ 0, & x = 0 \end{cases}$$

we can simply write  $f(\dot{u}) = \mu mg \text{sign}(\dot{u})$  (the sign function is implemented by `numpy.sign`).

The equation of motion becomes

$$m\ddot{u} + \mu mg \text{sign}(\dot{u}) + s(u) = 0, \quad u(0) = I, \quad \dot{u}(0) = V. \quad (88)$$

### 10.4 A jumping washing machine

A washing machine is placed on four springs with efficient dampers. If the machine contains just a few clothes, the circular motion of the machine induces a sinusoidal external force and the machine will jump up and down if the frequency of the external force is close to the natural frequency of the machine and its spring-damper system.

**hpl 5:** Not finished. This is a good example on resonance.

## 10.5 Motion of a pendulum

**Simple pendulum.** A classical problem in mechanics is the motion of a pendulum. We first consider a simple pendulum<sup>25</sup> (sometimes also called a mathematical pendulum): a small body of mass  $m$  is attached to a massless wire and can oscillate back and forth in the gravity field. Figure 20 shows a sketch of the problem.



Figure 20: Sketch of a simple pendulum.

The motion is governed by Newton's 2nd law, so we need to find expressions for the forces and the acceleration. Three forces on the body are considered: an unknown force  $S$  from the wire, the gravity force  $mg$ , and an air resistance force,  $\frac{1}{2}C_D\rho A|v|v$ , hereafter called the drag force, directed against the velocity of the body. Here,  $C_D$  is a drag coefficient,  $\rho$  is the density of air,  $A$  is the cross section area of the body, and  $v$  is the magnitude of the velocity.

We introduce a coordinate system with polar coordinates and unit vectors  $\mathbf{i}_r$  and  $\mathbf{i}_\theta$  as shown in Figure 21. The position of the center of mass of the body is

$$\mathbf{r}(t) = x_0\mathbf{i} + y_0\mathbf{j} + L\mathbf{i}_r,$$

where  $\mathbf{i}$  and  $\mathbf{j}$  are unit vectors in the corresponding Cartesian coordinate system in the  $x$  and  $y$  directions, respectively. We have that  $\mathbf{i}_r = \cos\theta\mathbf{i} + \sin\theta\mathbf{j}$ .

The forces are now expressed as follows.

- Wire force:  $-S\mathbf{i}_r$

<sup>25</sup><https://en.wikipedia.org/wiki/Pendulum>






Figure 21: Forces acting on a simple pendulum.

- Gravity force:  $-mg\mathbf{j} = mg(-\sin\theta\mathbf{i}_\theta + \cos\theta\mathbf{i}_r)$
- Drag force:  $-\frac{1}{2}C_D\rho A|v|v\mathbf{i}_\theta$

Since a positive velocity means movement in the direction of  $\mathbf{i}_\theta$ , the drag force must be directed along  $-\mathbf{i}_\theta$  so it works against the motion.

The velocity of the body is found from  $\mathbf{r}$ :

$$\mathbf{v}(t) = \dot{\mathbf{r}}(t) = \frac{d}{d\theta}(x_0\mathbf{i} + y_0\mathbf{j} + L\mathbf{i}_r)\frac{d\theta}{dt} = L\dot{\theta}\mathbf{i}_\theta,$$

since  $\frac{d}{d\theta}\mathbf{i}_r = \mathbf{i}_\theta$ . It follows that  $v = |\mathbf{v}| = L\dot{\theta}$ . The acceleration is

$$\mathbf{a}(t) = \dot{\mathbf{v}}(t) = \frac{d}{dt}(L\dot{\theta}\mathbf{i}_\theta) = L\ddot{\theta}\mathbf{i}_\theta + L\dot{\theta}\frac{d\mathbf{i}_\theta}{dt} = L\ddot{\theta}\mathbf{i}_\theta - L\dot{\theta}^2\mathbf{i}_r,$$

since  $\frac{d}{d\theta}\mathbf{i}_\theta = -\mathbf{i}_r$ .

Newton's 2nd law of motion becomes

$$-S\mathbf{i}_r + mg(-\sin\theta\mathbf{i}_\theta + \cos\theta\mathbf{i}_r) - \frac{1}{2}C_D\rho AL^2|\dot{\theta}|\dot{\theta}\mathbf{i}_\theta = mL\ddot{\theta}\mathbf{i}_\theta - L\dot{\theta}^2\mathbf{i}_r,$$

leading to two component equations

$$-S + mg \cos \theta = -L\dot{\theta}^2, \quad (89)$$

$$-mg \sin \theta - \frac{1}{2}C_D \varrho AL^2 |\dot{\theta}| \dot{\theta} = mL\ddot{\theta}. \quad (90)$$

From (89) we get an expression for  $S = mg \cos \theta + L\dot{\theta}^2$ , and from (90) we get a differential equation for the angle  $\theta(t)$ . This latter equation is ordered as

$$m\ddot{\theta} + \frac{1}{2}C_D \varrho AL |\dot{\theta}| \dot{\theta} + \frac{mg}{L} \sin \theta = 0. \quad (91)$$

Two initial conditions are needed:  $\theta = \Theta$  and  $\dot{\theta} = \Omega$ . Normally, the pendulum motion is started from rest, which means  $\Omega = 0$ .

Equation (91) fits the general model used in (59) in Section 8 if we define  $u = \theta$ ,  $f(u') = \frac{1}{2}C_D \varrho AL |\dot{u}| \dot{u}$ ,  $s(u) = L^{-1}mg \sin u$ , and  $F = 0$ . If the body is a sphere with radius  $R$ , we can take  $C_D = 0.4$  and  $A = \pi R^2$ . Exercise 21 asks you to scale the equations and carry out specific simulations with this model.

**Physical pendulum.** The motion of a compound or physical pendulum where the wire is a rod with mass, can be modeled very similarly. The governing equation is  $I\mathbf{a} = \mathbf{T}$  where  $I$  is the moment of inertia of the entire body about the point  $(x_0, y_0)$ , and  $\mathbf{T}$  is the sum of moments of the forces with respect to  $(x_0, y_0)$ . The vector equation reads


$$\mathbf{r} \times (-S\mathbf{i}_r + mg(-\sin \theta \mathbf{i}_\theta + \cos \theta \mathbf{i}_r)) - \frac{1}{2}C_D \varrho AL^2 |\dot{\theta}| \dot{\theta} \mathbf{i}_\theta = I(L\ddot{\theta} \mathbf{i}_\theta - L\dot{\theta}^2 \mathbf{i}_r).$$

The component equation in  $\mathbf{i}_\theta$  direction gives the equation of motion for  $\theta(t)$ :

$$I\ddot{\theta} + \frac{1}{2}C_D \varrho AL^3 |\dot{\theta}| \dot{\theta} + mgL \sin \theta = 0. \quad (92)$$

## 10.6 Dynamic free body diagram during pendulum motion

Usually one plots the mathematical quantities as functions of time to visualize the solution of ODE models. Exercise 21 asks you to do this for the motion of a pendulum in the previous section. However, sometimes it is more instructive to look at other types of visualizations. For example, we have the pendulum and the free body diagram in Figures 20 and 21. We may think of these figures as animations in time instead. Especially the free body diagram will show both the motion of the pendulum *and* the size of the forces during the motion. The present section exemplifies how to make such a dynamic body diagram. Two typical snapshots of free body diagrams are displayed below (the drag force is magnified 5 times to become more visual!).



Dynamic physical sketches, coupled to the numerical solution of differential equations, requires a program to produce a sketch for the situation at each time level. Pysketcher<sup>26</sup> is such a tool. In fact (and not surprising!) Figures 20 and 21 were drawn using Pysketcher. The details of the drawings are explained in the Pysketcher tutorial<sup>27</sup>. Here, we outline how this type of sketch can be used to create an animated free body diagram during the motion of a pendulum.

Pysketcher is actually a layer of useful abstractions on top of standard plotting packages. This means that we in fact apply Matplotlib to make the animated free body diagram, but instead of dealing with a wealth of detailed Matplotlib commands, we can express the drawing in terms of more high-level objects, e.g., objects for the wire, angle  $\theta$ , body with mass  $m$ , arrows for forces, etc. When the position of these objects are given through variables, we can just couple those variables to the dynamic solution of our ODE and thereby make a unique drawing for each  $\theta$  value in a simulation.

**Writing the solver.** Let us start with the most familiar part of the current problem: writing the solver function. We use Odespy for this purpose. We also work with dimensionless equations. Since  $\theta$  can be viewed as dimensionless, we only need to introduce a dimensionless time, here taken as  $\bar{t} = t/\sqrt{L/g}$ . The resulting dimensionless mathematical model for  $\theta$ , the dimensionless angular velocity  $\omega$ , the dimensionless wire force  $\bar{S}$ , and the dimensionless drag force  $\bar{D}$  is then

<sup>26</sup><https://github.com/hplgit/pysketcher>

<sup>27</sup><http://hplgit.github.io/pysketcher/doc/web/index.html>

$$\frac{d\omega}{dt} = -\alpha|\omega|\omega - \sin\theta, \quad (93)$$

$$\frac{d\theta}{dt} = \omega, \quad (94)$$

$$\bar{S} = \omega^2 + \cos\theta, \quad (95)$$

$$\bar{D} = -\alpha|\omega|\omega, \quad (96)$$

with

$$\alpha = \frac{C_D \varrho \pi R^2 L}{2m}.$$

as a dimensionless parameter expressing the ratio of the drag force and the gravity force.

A suitable function for computing (93)-(96) is listed below.

```
def simulate(alpha, Theta, dt, T):
    import odespy

    def f(u, t, alpha):
        omega, theta = u
        return [-alpha*omega*abs(omega) - sin(theta),
                omega]

    import numpy as np
    Nt = int(round(T/float(dt)))
    t = np.linspace(0, Nt*dt, Nt+1)
    solver = odespy.RK4(f, f_args=[alpha])
    solver.set_initial_condition([0, Theta])
    u, t = solver.solve(
        t, terminate=lambda u, t, n: abs(u[n,1]) < 1E-3)
    omega = u[:,0]
    theta = u[:,1]
    S = omega**2 + np.cos(theta)
    drag = -alpha*np.abs(omega)*omega
    return t, theta, omega, S, drag
```

**Drawing the free body diagram.** The `sketch` function below applies Pysketcher objects to build a diagram like that in Figure 21, except that we have removed the rotation point  $(x_0, y_0)$  and the unit vectors in polar coordinates as these objects are not important for an animated free body diagram.

```
import sys
try:
    from pysketcher import *
except ImportError:
    print 'Pysketcher must be installed from'
    print 'https://github.com/hplgit/pysketcher'
    sys.exit(1)

# Overall dimensions of sketch
H = 15.
```

```

W = 17.

drawing_tool.set_coordinate_system(
    xmin=0, xmax=W, ymin=0, ymax=H,
    axis=False)

def sketch(theta, S, mg, drag, t, time_level):
    """
    Draw pendulum sketch with body forces at a time level
    corresponding to time t. The drag force is in
    drag[time_level], the force in the wire is S[time_level],
    the angle is theta[time_level].
    """
    import math
    a = math.degrees(theta[time_level]) # angle in degrees
    L = 0.4*H # Length of pendulum
    P = (W/2, 0.8*H) # Fixed rotation point

    mass_pt = path.geometric_features()['end']
    rod = Line(P, mass_pt)

    mass = Circle(center=mass_pt, radius=L/20.)
    mass.set_filled_curves(color='blue')
    rod_vec = rod.geometric_features()['end'] - \
        rod.geometric_features()['start']
    unit_rod_vec = unit_vec(rod_vec)
    mass_symbol = Text('$m$', mass_pt + L/10*unit_rod_vec)

    rod_start = rod.geometric_features()['start'] # Point P
    vertical = Line(rod_start, rod_start + point(0,-L/3))

    def set_dashed_thin_blackline(*objects):
        """Set linestyle of objects to dashed, black, width=1."""
        for obj in objects:
            obj.set_linestyle('dashed')
            obj.set_linecolor('black')
            obj.set_linewidth(1)

    set_dashed_thin_blackline(vertical)
    set_dashed_thin_blackline(rod)
    angle = Arc_wText(r'$\theta$', rod_start, L/6, -90, a,
        text_spacing=1/30.)

    magnitude = 1.2*L/2 # length of a unit force in figure
    force = mg[time_level] # constant (scaled eq: about 1)
    force *= magnitude
    mg_force = Force(mass_pt, mass_pt + force*point(0,-1),
        '', text_pos='end')

    force = S[time_level]
    force *= magnitude
    rod_force = Force(mass_pt, mass_pt - force*unit_vec(rod_vec),
        '', text_pos='end',
        text_spacing=(0.03, 0.01))

    force = drag[time_level]
    force *= magnitude
    air_force = Force(mass_pt, mass_pt -
        force*unit_vec((rod_vec[1], -rod_vec[0])),
        '', text_pos='end',
        text_spacing=(0.04,0.005))

    body_diagram = Composition(
        {'mg': mg_force, 'S': rod_force, 'air': air_force,
         'rod': rod, 'body': mass
         'vertical': vertical, 'theta': angle,})

```

```
body_diagram.draw(verbose=0)
drawing_tool.savefig('tmp_%04d.png' % time_level, crop=False)
# (No cropping: otherwise movies will be very strange!)
```

**Making the animated free body diagram.** It now remains to couple the `simulate` and `sketch` functions. We first run `simulate`:

```
from math import pi, radians, degrees
import numpy as np
alpha = 0.4
period = 2*pi # Use small theta approximation
T = 12*period # Simulate for 12 periods
dt = period/40 # 40 time steps per period
a = 70 # Initial amplitude in degrees
Theta = radians(a)

t, theta, omega, S, drag = simulate(alpha, Theta, dt, T)
```

The next step is to run through the time levels in the simulation and make a sketch at each level:

```
for time_level, t_ in enumerate(t):
    sketch(theta, S, mg, drag, t_, time_level)
```

The individual sketches are (by the `sketch` function) saved in files with names `tmp_%04d.png`. These can be combined to videos using (e.g.) `ffmpeg`. A complete function `animate` for running the simulation and creating video files is listed below.

```
def animate():
    # Clean up old plot files
    import os, glob
    for filename in glob.glob('tmp_*.png') + glob.glob('movie.*'):
        os.remove(filename)
    # Solve problem
    from math import pi, radians, degrees
    import numpy as np
    alpha = 0.4
    period = 2*pi # Use small theta approximation
    T = 12*period # Simulate for 12 periods
    dt = period/40 # 40 time steps per period
    a = 70 # Initial amplitude in degrees
    Theta = radians(a)

    t, theta, omega, S, drag = simulate(alpha, Theta, dt, T)

    # Visualize drag force 5 times as large
    drag *= 5
    mg = np.ones(S.size) # Gravity force (needed in sketch)

    # Draw animation
    import time
    for time_level, t_ in enumerate(t):
        sketch(theta, S, mg, drag, t_, time_level)
        time.sleep(0.2) # Pause between each frame on the screen
```

```

# Make videos
prog = 'ffmpeg'
filename = 'tmp_%04d.png'
fps = 6
codecs = {'flv': 'flv', 'mp4': 'libx264',
          'webm': 'libvpx', 'ogg': 'libtheora'}
for ext in codecs:
    lib = codecs[ext]
    cmd = '%(prog)s -i %(filename)s -r %(fps)s ' % vars()
    cmd += '-vcodec %(lib)s movie.%(ext)s' % vars()
    print(cmd)
    os.system(cmd)

```

## 10.7 Motion of an elastic pendulum

Consider a pendulum as in Figure 20, but this time the wire is elastic. The length of the wire when it is not stretched is  $L_0$ , while  $L(t)$  is the stretched length at time  $t$  during the motion.

Stretching the elastic wire a distance  $\Delta L$  gives rise to a spring force  $k\Delta L$  in the opposite direction of the stretching. Let  $\mathbf{n}$  be a unit normal vector along the wire from the point  $\mathbf{r}_0 = (x_0, y_0)$  and in the direction of  $\mathbf{i}_\theta$ , see Figure 21 for definition of  $(x_0, y_0)$  and  $\mathbf{i}_\theta$ . Obviously, we have  $\mathbf{n} = \mathbf{i}_\theta$ , but in this modeling of an elastic pendulum we do not need polar coordinates. Instead, it is more straightforward to develop the equation in Cartesian coordinates.

A mathematical expression for  $\mathbf{n}$  is

$$\mathbf{n} = \frac{\mathbf{r} - \mathbf{r}_0}{L(t)},$$

where  $L(t) = \|\mathbf{r} - \mathbf{r}_0\|$  is the current length of the elastic wire. The position vector  $\mathbf{r}$  in Cartesian coordinates reads  $\mathbf{r}(t) = x(t)\mathbf{i} + y(t)\mathbf{j}$ , where  $\mathbf{i}$  and  $\mathbf{j}$  are unit vectors in the  $x$  and  $y$  directions, respectively. It is convenient to introduce the Cartesian components  $n_x$  and  $n_y$  of the normal vector:

$$\mathbf{n} = \frac{\mathbf{r} - \mathbf{r}_0}{L(t)} = \frac{x(t) - x_0}{L(t)}\mathbf{i} + \frac{y(t) - y_0}{L(t)}\mathbf{j} = n_x\mathbf{i} + n_y\mathbf{j}.$$

The stretch  $\Delta L$  in the wire is

$$\Delta L = L(t) - L_0.$$

The force in the wire is then  $-S\mathbf{n} = -k\Delta L\mathbf{n}$ .

The other forces are the gravity and the air resistance, just as in Figure 21. The main difference is that we have a *model* for  $S$  in terms of the motion (as soon as we have expressed  $\Delta L$  by  $\mathbf{r}$ ). For simplicity, we drop the air resistance term (but Exercise 23 asks you to include it).

Newton's second law of motion applied to the body now results in

$$m\ddot{\mathbf{r}} = -k(L - L_0)\mathbf{n} - mg\mathbf{j} \quad (97)$$

The two components of (97) are

$$\ddot{x} = -\frac{k}{m}(L - L_0)n_x, \quad (98)$$

$$(99)$$

$$\ddot{y} = -\frac{k}{m}(L - L_0)n_y - g. \quad (100)$$

**Remarks about an elastic vs a non-elastic pendulum.** Note that the derivation of the ODEs for an elastic pendulum is more straightforward than for a classical, non-elastic pendulum, since we avoid the details with polar coordinates, but instead work with Newton's second law directly in Cartesian coordinates. The reason why we can do this is that the elastic pendulum undergoes a general two-dimensional motion where all the forces are known or expressed as functions of  $x(t)$  and  $y(t)$ , such that we get two ordinary differential equations. The motion of the non-elastic pendulum, on the other hand, is constrained: the body has to move along a circular path, and the force  $S$  in the wire is unknown.

The non-elastic pendulum therefore leads to a *differential-algebraic* equation, i.e., ODEs for  $x(t)$  and  $y(t)$  combined with an extra constraint  $(x - x_0)^2 + (y - y_0)^2 = L^2$  ensuring that the motion takes place along a circular path. The extra constraint (equation) is compensated by an extra unknown force  $-S\mathbf{n}$ . Differential-algebraic equations are normally hard to solve, especially with pen and paper. Fortunately, for the non-elastic pendulum we can do a trick: in polar coordinates the unknown force  $S$  appears only in the radial component of Newton's second law, while the unknown degree of freedom for describing the motion, the angle  $\theta(t)$ , is completely governed by the azimuthal component. This allows us to decouple the unknowns  $S$  and  $\theta$ . But this is a kind of trick and not a widely applicable method. With an elastic pendulum we use straightforward reasoning with Newton's 2nd law and arrive at a standard ODE problem that (after scaling) is easy solve on a computer.

**Initial conditions.** What is the initial position of the body? We imagine that first the pendulum hangs in equilibrium in its vertical position, and then it is displaced an angle  $\Theta$ . The equilibrium position is governed by the ODEs with the accelerations set to zero. The  $x$  component leads to  $x(t) = x_0$ , while the  $y$  component gives

$$0 = -\frac{k}{m}(L - L_0)n_y - g = \frac{k}{m}(L(0) - L_0) - g \quad \Rightarrow \quad L(0) = L_0 + mg/k,$$

since  $n_y = -1$  in this position. The corresponding  $y$  value is then from  $n_y = -1$ :

$$y(t) = y_0 - L(0) = y_0 - (L_0 + mg/k).$$

Let us now choose  $(x_0, y_0)$  such that the body is at the origin in the equilibrium position:



$$x_0 = 0, \quad y_0 = L_0 + mg/k.$$

Displacing the body an angle  $\Theta$  to the right leads to the initial position

$$x(0) = (L_0 + mg/k) \sin \Theta, \quad y(0) = (L_0 + mg/k)(1 - \cos \Theta).$$

The initial velocities can be set to zero:  $x'(0) = y'(0) = 0$ .

**The complete ODE problem.** We can summarize all the equations as follows:

$$\begin{aligned} \ddot{x} &= -\frac{k}{m}(L - L_0)n_x, \\ \ddot{y} &= -\frac{k}{m}(L - L_0)n_y - g, \\ L &= \sqrt{(x - x_0)^2 + (y - y_0)^2}, \\ n_x &= \frac{x - x_0}{L}, \\ n_y &= \frac{y - y_0}{L}, \\ x(0) &= (L_0 + mg/k) \sin \Theta, \\ x'(0) &= 0, \\ y(0) &= (L_0 + mg/k)(1 - \cos \Theta), \\ y'(0) &= 0. \end{aligned}$$

We insert  $n_x$  and  $n_y$  in the ODEs:

$$\ddot{x} = -\frac{k}{m} \left(1 - \frac{L_0}{L}\right) (x - x_0), \tag{101}$$

$$\ddot{y} = -\frac{k}{m} \left(1 - \frac{L_0}{L}\right) (y - y_0) - g, \tag{102}$$

$$L = \sqrt{(x - x_0)^2 + (y - y_0)^2}, \tag{103}$$

$$x(0) = (L_0 + mg/k) \sin \Theta, \tag{104}$$

$$x'(0) = 0, \tag{105}$$

$$y(0) = (L_0 + mg/k)(1 - \cos \Theta), \tag{106}$$

$$y'(0) = 0. \tag{107}$$

**Scaling.** The elastic pendulum model can be used to study both an elastic pendulum and a classic, non-elastic pendulum. The latter problem is obtained by letting  $k \rightarrow \infty$ . Unfortunately, a serious problem with the ODEs (101)-(102) is that for large  $k$ , we have a very large factor  $k/m$  multiplied by a very small number  $1 - L_0/L$ , since for large  $k$ ,  $L \approx L_0$  (very small deformations of the wire).

The product is subject to significant round-off errors for many relevant physical values of the parameters. To circumvent the problem, we introduce a scaling. This will also remove physical parameters from the problem such that we end up with only one dimensionless parameter, closely related to the elasticity of the wire. Simulations can then be done by setting just this dimensionless parameter.

The characteristic length can be taken such that in equilibrium, the scaled length is unity, i.e., the characteristic length is  $L_0 + mg/k$ :

$$\bar{x} = \frac{x}{L_0 + mg/k}, \quad \bar{y} = \frac{y}{L_0 + mg/k}.$$

We must then also work with the scaled length  $\bar{L} = L/(L_0 + mg/k)$ .

Introducing  $\bar{t} = t/t_c$ , where  $t_c$  is a characteristic time we have to decide upon later, one gets

$$\begin{aligned} \frac{d^2 \bar{x}}{d\bar{t}^2} &= -t_c^2 \frac{k}{m} \left( 1 - \frac{L_0}{L_0 + mg/k} \frac{1}{\bar{L}} \right) \bar{x}, \\ \frac{d^2 \bar{y}}{d\bar{t}^2} &= -t_c^2 \frac{k}{m} \left( 1 - \frac{L_0}{L_0 + mg/k} \frac{1}{\bar{L}} \right) (\bar{y} - 1) - t_c^2 \frac{g}{L_0 + mg/k}, \\ \bar{L} &= \sqrt{\bar{x}^2 + (\bar{y} - 1)^2}, \\ \bar{x}(0) &= \sin \Theta, \\ \bar{x}'(0) &= 0, \\ \bar{y}(0) &= 1 - \cos \Theta, \\ \bar{y}'(0) &= 0. \end{aligned}$$

For a non-elastic pendulum with small angles, we know that the frequency of the oscillations are  $\omega = \sqrt{L/g}$ . It is therefore natural to choose a similar expression here, either the length in the equilibrium position,

$$t_c^2 = \frac{L_0 + mg/k}{g}.$$

or simply the unstretched length,

$$t_c^2 = \frac{L_0}{g}.$$

These quantities are not very different (since the elastic model is valid only for quite small elongations), so we take the latter as it is the simplest one.

The ODEs become

$$\begin{aligned} \frac{d^2 \bar{x}}{d\bar{t}^2} &= -\frac{L_0 k}{mg} \left( 1 - \frac{L_0}{L_0 + mg/k} \frac{1}{\bar{L}} \right) \bar{x}, \\ \frac{d^2 \bar{y}}{d\bar{t}^2} &= -\frac{L_0 k}{mg} \left( 1 - \frac{L_0}{L_0 + mg/k} \frac{1}{\bar{L}} \right) (\bar{y} - 1) - \frac{L_0}{L_0 + mg/k}, \\ \bar{L} &= \sqrt{\bar{x}^2 + (\bar{y} - 1)^2}. \end{aligned}$$

We can now identify a dimensionless number

$$\beta = \frac{L_0}{L_0 + mg/k} = \frac{1}{1 + \frac{mg}{L_0 k}},$$

which is the ratio of the unstretched length and the stretched length in equilibrium. The non-elastic pendulum will have  $\beta = 1$  ( $k \rightarrow \infty$ ). With  $\beta$  the ODEs read

$$\frac{d^2 \bar{x}}{dt^2} = -\frac{\beta}{1-\beta} \left(1 - \frac{\beta}{\bar{L}}\right) \bar{x}, \quad (108)$$

$$\frac{d^2 \bar{y}}{dt^2} = -\frac{\beta}{1-\beta} \left(1 - \frac{\beta}{\bar{L}}\right) (\bar{y} - 1) - \beta, \quad (109)$$

$$\bar{L} = \sqrt{\bar{x}^2 + (\bar{y} - 1)^2}, \quad (110)$$

$$\bar{x}(0) = (1 + \epsilon) \sin \Theta, \quad (111)$$

$$\frac{d\bar{x}}{dt}(0) = 0, \quad (112)$$

$$\bar{y}(0) = 1 - (1 + \epsilon) \cos \Theta, \quad (113)$$

$$\frac{d\bar{y}}{dt}(0) = 0, \quad (114)$$

We have here added a parameter  $\epsilon$ , which is an additional downward stretch of the wire at  $t = 0$ . This parameter makes it possible to do a desired test: vertical oscillations of the pendulum. Without  $\epsilon$ , starting the motion from  $(0, 0)$  with zero velocity will result in  $x = y = 0$  for all times (also a good test!), but with an initial stretch so the body's position is  $(0, \epsilon)$ , we will have oscillatory vertical motion with amplitude  $\epsilon$  (see Exercise 22).

**Remark on the non-elastic limit.** We immediately see that as  $k \rightarrow \infty$  (i.e., we obtain a non-elastic pendulum),  $\beta \rightarrow 1$ ,  $\bar{L} \rightarrow 1$ , and we have very small values  $1 - \beta\bar{L}^{-1}$  divided by very small values  $1 - \beta$  in the ODEs. However, it turns out that we can set  $\beta$  very close to one and obtain a path of the body that within the visual accuracy of a plot does not show any elastic oscillations. (Should the division of very small values become a problem, one can study the limit by L'Hospital's rule:

$$\lim_{\beta \rightarrow 1} \frac{1 - \beta\bar{L}^{-1}}{1 - \beta} = \frac{1}{\bar{L}},$$

and use the limit  $\bar{L}^{-1}$  in the ODEs for  $\beta$  values very close to 1.)

## 10.8 Vehicle on a bumpy road

We consider a very simplistic vehicle, on one wheel, rolling along a bumpy road. The oscillatory nature of the road will induce an external forcing on the spring system in the vehicle and cause vibrations. Figure 22 outlines the situation.




Figure 22: Sketch of one-wheel vehicle on a bumpy road.

To derive the equation that governs the motion, we must first establish the position vector of the black mass at the top of the spring. Suppose the spring has length  $L$  without any elongation or compression, suppose the radius of the wheel is  $R$ , and suppose the height of the black mass at the top is  $H$ . With the aid of the  $\mathbf{r}_0$  vector in Figure 22, the position  $\mathbf{r}$  of the center point of the mass is

$$\mathbf{r} = \mathbf{r}_0 + 2R\mathbf{j} + L\mathbf{j} + u\mathbf{j} + \frac{1}{2}H\mathbf{j}, \quad (115)$$

where  $u$  is the elongation or compression in the spring according to the (unknown and to be computed) vertical displacement  $u$  relative to the road. If the vehicle travels with constant horizontal velocity  $v$  and  $h(x)$  is the shape of the road, then the vector  $\mathbf{r}_0$  is

$$\mathbf{r}_0 = vt\mathbf{i} + h(vt)\mathbf{j},$$

if the motion starts from  $x = 0$  at time  $t = 0$ .

The forces on the mass is the gravity, the spring force, and an optional damping force that is proportional to the vertical velocity  $\dot{u}$ . Newton's second law of motion then tells that

$$m\ddot{\mathbf{r}} = -mg\mathbf{j} - s(u) - b\dot{u}\mathbf{j}.$$

This leads to

$$m\ddot{u} = -s(u) - b\dot{u} - mg - mh''(vt)v^2$$

To simplify a little bit, we omit the gravity force  $mg$  in comparison with the other terms. Introducing  $u'$  for  $\dot{u}$  then gives a standard damped, vibration equation with external forcing:

$$mu'' + bu' + s(u) = -mh''(vt)v^2. \quad (116)$$

Since the road is normally known just as a set of array values,  $h''$  must be computed by finite differences. Let  $\Delta x$  be the spacing between measured values  $h_i = h(i\Delta x)$  on the road. The discrete second-order derivative  $h''$  reads

$$q_i = \frac{h_{i-1} - 2h_i + h_{i+1}}{\Delta x^2}, \quad i = 1, \dots, N_x - 1.$$

We may for maximum simplicity set the end points as  $q_0 = q_1$  and  $q_{N_x} = q_{N_x-1}$ . The term  $-mh''(vt)v^2$  corresponds to a force with discrete time values

$$F^n = -mq_n v^2, \quad \Delta t = v^{-1} \Delta x.$$

This force can be directly used in a numerical model

$$[mD_t D_t u + bD_{2t} u + s(u) = F]^n.$$

Software for computing  $u$  and also making an animated sketch of the motion like we did in Section 10.6 is found in a separate project on the web: <https://github.com/hplgit/bumpy>. You may start looking at the tutorial<sup>28</sup>.

## 10.9 Bouncing ball

A bouncing ball is a ball in free vertically fall until it impacts the ground, but during the impact, some kinetic energy is lost, and a new motion upwards with reduced velocity starts. After the motion is retarded, a new free fall starts, and the process is repeated. At some point the velocity close to the ground is so small that the ball is considered to be finally at rest.

The motion of the ball falling in air is governed by Newton's second law  $F = ma$ , where  $a$  is the acceleration of the body,  $m$  is the mass, and  $F$  is the sum of all forces. Here, we neglect the air resistance so that gravity  $-mg$  is the only force. The height of the ball is denoted by  $h$  and  $v$  is the velocity. The relations between  $h$ ,  $v$ , and  $a$ ,

$$h'(t) = v(t), \quad v'(t) = a(t),$$

combined with Newton's second law gives the ODE model

$$h''(t) = -g, \tag{117}$$

or expressed alternatively as a system of first-order equations:

$$v'(t) = -g, \tag{118}$$

$$h'(t) = v(t). \tag{119}$$

These equations govern the motion as long as the ball is away from the ground by a small distance  $\epsilon_h > 0$ . When  $h < \epsilon_h$ , we have two cases.

<sup>28</sup><http://hplgit.github.io/bumpy/doc/pub/bumpy.pdf>

1. The ball impacts the ground, recognized by a sufficiently large negative velocity ( $v < -\epsilon_v$ ). The velocity then changes sign and is reduced by a factor  $C_R$ , known as the coefficient of restitution<sup>29</sup>. For plotting purposes, one may set  $h = 0$ .
2. The motion stops, recognized by a sufficiently small velocity ( $|v| < \epsilon_v$ ) close to the ground.

## 10.10 Electric circuits

Although the term “mechanical vibrations” is used in the present document, we must mention that the same type of equations arise when modeling electric circuits. The current  $I(t)$  in a circuit with an inductor with inductance  $L$ , a capacitor with capacitance  $C$ , and overall resistance  $R$ , is governed by

$$\ddot{I} + \frac{R}{L}\dot{I} + \frac{1}{LC}I = \dot{V}(t), \quad (120)$$

where  $V(t)$  is the voltage source powering the circuit. This equation has the same form as the general model considered in Section `refrefvib:model2` if we set  $u = I$ ,  $f(u' = bu'$  and define  $b = R/L$ ,  $s(u) = L^{-1}C^{-1}u$ , and  $F(t) = \dot{V}(t)$ .

## 11 Exercises

### Exercise 18: Simulate resonance

We consider the scaled ODE model (87) from Section 10.2. After scaling, the amplitude of  $u$  will have a size about unity as time grows and the effect of the initial conditions die out due to damping. However, as  $\gamma \rightarrow 1$ , the amplitude of  $u$  increases, especially if  $\beta$  is small. This effect is called *resonance*. The purpose of this exercise is to explore resonance.

**a)** Figure out how the `solver` function in `vib.py` can be called for the scaled ODE (87).

**Solution.** Comparing the scaled ODE (87) with the ODE (86) with dimensions, we realize that the parameters in the latter must be set as

- $m = 1$
- $f(\dot{u}) = 2\beta|\dot{u}|\dot{u}$
- $s(u) = ku$
- $F(t) = \sin(\gamma t)$
- $I = Ik/A$

---

<sup>29</sup>[http://en.wikipedia.org/wiki/Coefficient\\_of\\_restitution](http://en.wikipedia.org/wiki/Coefficient_of_restitution)

- $V = \sqrt{mk}V/A$

The expected period is  $2\pi$ , so simulating for  $N$  periods means  $T = 2\pi N$ . Having  $m$  time steps per period means  $\Delta t = 2\pi/m$ .

Suppose we just choose  $I = 1$  and  $V = 0$ . Simulating for 20 periods with 60 time steps per period, implies the following `solver` call to run the scaled model:

```
u, t = solver(I=1, V=0, m=1, b=2*beta, s=lambda u: u,
              F=lambda t: sin(gamma*t), dt=2*pi/60,
              T=2*pi*20, damping='quadratic')
```





b) Run  $\gamma = 5, 1.5, 1.1, 1$  for  $\beta = 0.005, 0.05, 0.2$ . For each  $\beta$  value, present an image with plots of  $u(t)$  for the four  $\gamma$  values.

**Solution.** An appropriate program is





```
from vib import solver, visualize, plt
from math import pi, sin
import numpy as np

beta_values = [0.005, 0.05, 0.2]
beta_values = [0.00005]
gamma_values = [5, 1.5, 1.1, 1]
for i, beta in enumerate(beta_values):
    for gamma in gamma_values:
        u, t = solver(I=1, V=0, m=1, b=2*beta, s=lambda u: u,
                      F=lambda t: sin(gamma*t), dt=2*pi/60,
                      T=2*pi*20, damping='quadratic')
        visualize(u, t, title='gamma=%g' % gamma,
                  gamma, filename='tmp_%s' % gamma)
        print gamma, 'max u amplitude:', np.abs(u).max()
    for ext in 'png', 'pdf':
        cmd = 'doconce combine_images '
        cmd += ' '.join(['tmp_%s.' % gamma + ext for gamma in gamma_values])
        cmd += ' resonance%d.' % (i+1) + ext
        os.system(cmd)
raw_input()
```

For  $\beta = 0.2$  we see that the amplitude is not far from unity:




For  $\beta = 0.05$  we see that as  $\gamma \rightarrow 1$ , the amplitude grows:





Finally, a small damping ( $\beta = 0.005$ ) amplifies the amplitude significantly (by a factor of 10) for  $\gamma = 1$ :



For a very small  $\beta = 0.00005$ , the amplitude grows linearly up to about 60 for  $t \in [0, 120]$ .

Filename: `resonance`.

### Exercise 19: Simulate oscillations of a sliding box

Consider a sliding box on a flat surface as modeled in Section 10.3. As spring force we choose the nonlinear formula

$$s(u) = \frac{k}{\alpha} \tanh(\alpha u) = ku + \frac{1}{3}\alpha^2 ku^3 + \frac{2}{15}\alpha^4 ku^5 + \mathcal{O}(u^6).$$

a) Plot  $g(u) = \alpha^{-1} \tanh(\alpha u)$  for various values of  $\alpha$ . Assume  $u \in [-1, 1]$ .

**Solution.** Here is a function that does the plotting:


```
import scitools.std as plt
import numpy as np

def plot_spring():
    alpha_values = [1, 2, 3, 10]
    s = lambda u: 1.0/alpha*np.tanh(alpha*u)
    u = np.linspace(-1, 1, 1001)
    for alpha in alpha_values:
```

```

print alpha, s(u)
plt.plot(u, s(u))
plt.hold('on')
plt.legend([r'$\alpha=%g$' % alpha for alpha in alpha_values])
plt.xlabel('u'); plt.ylabel('Spring response $s(u)$')
plt.savefig('tmp_s.png'); plt.savefig('tmp_s.pdf')

```



b) Scale the equations using  $I$  as scale for  $u$  and  $\sqrt{m/k}$  as time scale.

**Solution.** Inserting the dimensionless dependent and independent variables,

$$\bar{u} = \frac{u}{I}, \quad \bar{t} = \frac{t}{\sqrt{m/k}},$$

in the problem

$$m\ddot{u} + \mu mg \text{sign}(\dot{u}) + s(u) = 0, \quad u(0) = I, \quad \dot{u}(0) = V,$$

gives

$$\frac{d^2 \bar{u}}{d\bar{t}^2} + \frac{\mu mg}{kI} \text{sign}\left(\frac{d\bar{u}}{d\bar{t}}\right) + \frac{1}{\alpha I} \tanh(\alpha I \bar{u}) = 0, \quad \bar{u}(0) = 1, \quad \frac{d\bar{u}}{d\bar{t}}(0) = \frac{V\sqrt{mk}}{kI}.$$

We can now identify three dimensionless parameters,

$$\beta = \frac{\mu mg}{kI}, \quad \gamma = \alpha I, \quad \delta = \frac{V\sqrt{mk}}{kI}.$$

The scaled problem can then be written

$$\frac{d^2\bar{u}}{d\bar{t}^2} + \beta \text{sign}\left(\frac{d\bar{u}}{d\bar{t}}\right) + \gamma^{-1} \tanh(\gamma\bar{u}) = 0, \quad \bar{u}(0) = 1, \quad \frac{d\bar{u}}{d\bar{t}}(0) = \delta.$$

The initial set of 7 parameters  $(\mu, m, g, k, \alpha, I, V)$  are reduced to 3 dimensionless combinations.

c) Implement the scaled model in b). Run it for some values of the dimensionless parameters.

**Solution.** We use Odespy to solve the ODE, which requires rewriting the ODE as a system of two first-order ODEs:



$$v' = -\beta \text{sign}(v) - \gamma^{-1} \tanh(\gamma\bar{u}), \quad u' = v,$$


with initial conditions  $v(0) = \delta$  and  $u(0) = 1$ . Here,  $u(t)$  corresponds to the previous  $\bar{u}(\bar{t})$ , while  $v(t)$  corresponds to  $d\bar{u}/d\bar{t}(\bar{t})$ . The code can be like this:

```
def simulate(beta, gamma, delta=0,
            num_periods=8, time_steps_per_period=60):
    # Use oscillations without friction to set dt and T
    P = 2*np.pi
    dt = P/time_steps_per_period
    T = num_periods*P
    t = np.linspace(0, T, time_steps_per_period*num_periods+1)
    import odespy
    def f(u, t, beta, gamma):
        # Note the sequence of unknowns: v, u (v=du/dt)
        v, u = u
        return [-beta*np.sign(v) - 1.0/gamma*np.tanh(gamma*u), v]
    #return [-beta*np.sign(v) - u, v]

    solver = odespy.RK4(f, f_args=(beta, gamma))
    solver.set_initial_condition([delta, 1]) # sequence must match f
    uv, t = solver.solve(t)
    u = uv[:,1] # recall sequence in f: v, u
    v = uv[:,0]
    return u, t
```

We simulate for an almost linear spring in the regime of  $\bar{u}$  (recall that  $\bar{u} \in [0, 1]$  since  $u$  is scaled with  $I$ ), which corresponds to  $\alpha = 1$  in a) and therefore  $\gamma = 1$ . Then we can try a spring whose force quickly flattens out like  $\alpha = 5$  in a), which corresponds to  $\gamma = 5$  in the scaled model. A third option is to have a truly linear spring, e.g.,  $\gamma = 0.1$ . After some experimentation we realize that  $\beta = 0, 0.05, 0.1$  are relevant values.





Filename: sliding\_box.

## Exercise 20: Simulate a bouncing ball

Section 10.9 presents a model for a bouncing ball. Choose one of the two ODE formulation, (117) or (118)-(119), and simulate the motion of a bouncing ball. Plot  $h(t)$ . Think about how to plot  $v(t)$ .

**Hint.** A naive implementation may get stuck in repeated impacts for large time step sizes. To avoid this situation, one can introduce a state variable that holds the mode of the motion: free fall, impact, or rest. Two consecutive impacts imply that the motion has stopped.

**Solution.** A tailored solver function and some plotting statements go like

```
import numpy as np

def solver(H, C_R, dt, T, eps_v=0.01, eps_h=0.01):
    """
    Simulate bouncing ball until it comes to rest. Time step dt.
    h(0)=H (initial height). T: maximum simulation time.
    Method: Euler-Cromer.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    h = np.zeros(Nt+1)
    v = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)
    g = 0.81

    v[0] = 0
    h[0] = H
    mode = 'free fall'
```



```

for n in range(Nt):
    v[n+1] = v[n] - dt*g
    h[n+1] = h[n] + dt*v[n+1]

    if h[n+1] < eps_h:
        #if abs(v[n+1]) > eps_v: # handles large dt, but is wrong
        if v[n+1] < -eps_v:
            # Impact
            v[n+1] = -C_R*v[n+1]
            h[n+1] = 0
            if mode == 'impact':
                # impact twice
                return h[:n+2], v[:n+2], t[:n+2]
            mode = 'impact'
        elif abs(v[n+1]) < eps_v:
            mode = 'rest'
            v[n+1] = 0
            h[n+1] = 0
            return h[:n+2], v[:n+2], t[:n+2]
        else:
            mode = 'free fall'
    else:
        mode = 'free fall'
    print '%4d v=%8.5f h=%8.5f %s' % (n, v[n+1], h[n+1], mode)
    raise ValueError('T=%g is too short simulation time' % T)

import matplotlib.pyplot as plt
h, v, t = solver(H=1, C_R=0.8, T=100, dt=0.0001, eps_v=0.01, eps_h=0.01)
plt.plot(t, h)
plt.legend('h')
plt.savefig('tmp_h.png'); plt.savefig('tmp_h.pdf')
plt.figure()
plt.plot(t, v)
plt.legend('v')
plt.savefig('tmp_v.png'); plt.savefig('tmp_v.pdf')
plt.show()

```



Filename: bouncing\_ball.

## Exercise 21: Simulate a simple pendulum

Simulation of simple pendulum can be carried out by using the mathematical model derived in Section 10.5 and calling up functionality in the `vib.py`<sup>30</sup> file (i.e., solve the second-order ODE by centered finite differences).

<sup>30</sup><http://tinyurl.com/nm5587k/vib/vib.py>

a) Scale the model. Set up the dimensionless governing equation for  $\theta$  and expressions for dimensionless drag and wire forces.

**Solution.** The angle is measured in radians so we may think of this quantity as dimensionless, or we may scale it by the initial condition to obtain a primary unknown that lies in  $[-1, 1]$ . We go for the former strategy here.

Dimensionless time  $\bar{t}$  is introduced as  $t/t_c$  for some suitable time scale  $t_c$ . Inserted in the two governing equations (91) and (89), for the two unknowns  $\theta$  and  $S$ , respectively, we achieve

$$\begin{aligned} -S + mg \cos \theta &= -\frac{1}{t_c} L \frac{d\theta}{d\bar{t}}, \\ \frac{1}{t_c^2} m \frac{d^2\theta}{d\bar{t}^2} + \frac{1}{2} C_D \varrho A L \frac{1}{t_c^2} \left| \frac{d\theta}{d\bar{t}} \right| \frac{d\theta}{d\bar{t}} + \frac{mg}{L} \sin \theta &= 0. \end{aligned}$$

We multiply the latter equation by  $t_c^2/m$  to make each term dimensionless:

$$\frac{d^2\theta}{d\bar{t}^2} + \frac{1}{2m} C_D \varrho A L \left| \frac{d\theta}{d\bar{t}} \right| \frac{d\theta}{d\bar{t}} + \frac{t_c^2 g}{L} \sin \theta = 0.$$

Assuming that the acceleration term and the gravity term to be the dominating terms, these should balance, so  $t_c^2 g/L = 1$ , giving  $t_c = \sqrt{g/L}$ . With  $A = \pi R^2$  we get the dimensionless ODEs

$$\frac{d^2\theta}{d\bar{t}^2} + \alpha \left| \frac{d\theta}{d\bar{t}} \right| \frac{d\theta}{d\bar{t}} + \sin \theta = 0, \quad (121)$$

$$\frac{S}{mg} = \left( \frac{d\theta}{d\bar{t}} \right)^2 + \cos \theta, \quad (122)$$

where  $\alpha$  is a dimensionless drag coefficient

$$\alpha = \frac{C_D \varrho \pi R^2 L}{2m}.$$

Note that in (122) we have divided by  $mg$ , which is in fact a force scale, making the gravity force unity and also  $S/mg = 1$  in the equilibrium position  $\theta = 0$ . We may introduce

$$\bar{S} = S/mg$$

as a dimensionless drag force.

The parameter  $\alpha$  is about the ratio of the drag force and the gravity force:

$$\frac{|\frac{1}{2} C_D \varrho \pi R^2 |v||}{|mg|} \sim \frac{C_D \varrho \pi R^2 L^2 t_c^{-2}}{mg} \left| \frac{d\bar{\theta}}{d\bar{t}} \right| \frac{d\bar{\theta}}{d\bar{t}} \sim \frac{C_D \varrho \pi R^2 L}{2m} \Theta^2 = \alpha \Theta^2.$$

(We have that  $\theta(t)/d\Theta$  is in  $[-1, 1]$ , so we expect since  $\Theta^{-1}d\bar{\theta}/d\bar{t}$  to be around unity. Here,  $\Theta = \theta(0)$ .)

Let us introduce  $\omega$  for the dimensionless angular velocity,

$$\omega = \frac{d\theta}{d\bar{t}}.$$

When  $\theta$  is computed, the dimensionless wire and drag forces are computed by

$$\begin{aligned}\bar{S} &= \omega^2 + \cos \theta, \\ \bar{D} &= -\alpha|\omega|\omega.\end{aligned}$$

b) Write a function for computing  $\theta$  and the dimensionless drag force and the force in the wire, using the `solver` function in the `vib.py` file. Plot these three quantities below each other (in subplots) so the graphs can be compared. Run two cases, first one in the limit of  $\Theta$  small and no drag, and then a second one with  $\Theta = 40$  degrees and  $\alpha = 0.8$ .

**Solution.** The first step is to realize how to utilize the `solver` function for our dimensionless model. Introducing `Theta` for  $\Theta$ , the arguments to `solver` must be set as

```
I = Theta
V = 0
m = 1
b = alpha
s = lambda u: sin(u)
F = lambda t: 0
damping = 'quadratic'
```

After computing  $\theta$ , we need to find  $\omega$  by finite differences:

$$\omega^n = \frac{\theta^{n+1} - \theta^{n-1}}{2\Delta t}, \quad n = 1, \dots, N_t - 1, \quad \omega^0 = \frac{\theta^1 - \theta^0}{\Delta t}, \quad \omega^{N_t} = \frac{\theta^{N_t} - \theta^{N_t-1}}{\Delta t}.$$

The duration of the simulation and the time step can be computed on basis of the analytical insight we have for small  $\theta$  ( $\theta \approx \Theta \cos(t)$ ). A complete function then reads

```
def simulate(Theta, alpha, num_periods=10):
    # Dimensionless model requires the following parameters:
    from math import sin, pi

    I = Theta
    V = 0
    m = 1
    b = alpha
    s = lambda u: sin(u)
    F = lambda t: 0
    damping = 'quadratic'
```



```

# Estimate T and dt from the small angle solution
P = 2*pi # One period (theta small, no drag)
dt = P/40 # 40 intervals per period
T = num_periods*P

theta, t = solver(I, V, m, b, s, F, dt, T, damping)
omega = np.zeros(theta.size)
omega[1:-1] = (theta[2:] - theta[:-2])/(2*dt)
omega[0] = (theta[1] - theta[0])/dt
omega[-1] = (theta[-1] - theta[-2])/dt

S = omega**2 + np.cos(theta)
D = alpha*np.abs(omega)*omega
return t, theta, S, D

```

Assuming imports like

```

import numpy as np
import matplotlib.pyplot as plt

```

the following function visualizes  $\theta$ ,  $\bar{S}$ , and  $\bar{D}$  with three subplots:

```

def visualize(t, theta, S, D, filename='tmp'):
    f, (ax1, ax2, ax3) = plt.subplots(3, sharex=True, sharey=False)
    ax1.plot(t, theta)
    ax1.set_title(r'$\theta(t)$')
    ax2.plot(t, S)
    ax2.set_title(r'Dimensionless force in the wire')
    ax3.plot(t, D)
    ax3.set_title(r'Dimensionless drag force')
    plt.savefig('%s.png' % filename)
    plt.savefig('%s.pdf' % filename)

```

A suitable main program is


```

import math
# Rough verification that small theta and no drag gives cos(t)
Theta = 1.0
alpha = 0
t, theta, S, D = simulate(Theta, alpha, num_periods=4)
# Scale theta by Theta (easier to compare with cos(t))
theta /= Theta
visualize(t, theta, S, D, filename='pendulum_verify')


Theta = math.radians(40)
alpha = 0.8
t, theta, S, D = simulate(Theta, alpha)
visualize(t, theta, S, D, filename='pendulum_alpha0.8_Theta40')
plt.show()

```

The “verification” case looks good (at least when the `solver` function has been thoroughly verified in other circumstances):



The “real case” shows how quickly the drag force is reduced, even when we set  $\alpha$  to a significant value (0.8):



Filename: `simple_pendulum.`

## Exercise 22: Simulate an elastic pendulum

Section 10.7 describes a model for an elastic pendulum, resulting in a system of two ODEs. The purpose of this exercise is to implement the scaled model, test the software, and generalize the model.

a) Write a function `simulate` that can simulate an elastic pendulum using the scaled model. The function should have the following arguments:

```
def simulate(
    beta=0.9,          # dimensionless parameter
    Theta=30,          # initial angle in degrees
    epsilon=0,          # initial stretch of wire
    num_periods=6,      # simulate for num_periods
    time_steps_per_period=60, # time step resolution
    plot=True,          # make plots or not
):
```

To set the total simulation time and the time step, we use our knowledge of the scaled, classical, non-elastic pendulum:  $u'' + u = 0$ , with solution  $u = \Theta \cos \bar{t}$ . The period of these oscillations is  $P = 2\pi$  and the frequency is unity. The time for simulation is taken as `num_periods` times  $P$ . The time step is set as  $P$  divided by `time_steps_per_period`.

The `simulate` function should return the arrays of  $x$ ,  $y$ ,  $\theta$ , and  $t$ , where  $\theta = \tan^{-1}(x/(1-y))$  is the angular displacement of the elastic pendulum corresponding to the position  $(x, y)$ .

If `plot` is `True`, make a plot of  $\bar{y}(\bar{t})$  versus  $\bar{x}(\bar{t})$ , i.e., the physical motion of the mass at  $(\bar{x}, \bar{y})$ . Use the equal aspect ratio on the axis such that we get a physically correct picture of the motion. Also make a plot of  $\theta(\bar{t})$ , where  $\theta$  is measured in degrees. If  $\Theta < 10$  degrees, add a plot that compares the solutions of the scaled, classical, non-elastic pendulum and the elastic pendulum ( $\theta(t)$ ).

Although the mathematics here employs a bar over scaled quantities, the code should feature plain names `x` for  $\bar{x}$ , `y` for  $\bar{y}$ , and `t` for  $\bar{t}$  (rather than `x_bar`, etc.). These variable names make the code easier to read and compare with the mathematics.

**Hint 1.** Equal aspect ratio is set by `plt.gca().set_aspect('equal')` in Matplotlib (import `matplotlib.pyplot` as `plt`) and by `plot(..., daspect=[1,1,1], daspectmode='equal')` in SciTools (import `scitools.std` as `plt`).

**Hint 2.** If you want to use Odespy to solve the equations, order the ODEs like  $\dot{\bar{x}}, \dot{\bar{x}}, \dot{\bar{y}}, \dot{\bar{y}}$  such that the Euler-Cromer scheme can (also) be used (`odespy.EulerCromer`).

**Solution.** Here is a suggested `simulate` function:

```
import odespy
import numpy as np
import scitools.std as plt

def simulate(
```

```

beta=0.9,                # dimensionless parameter
Theta=30,                # initial angle in degrees
epsilon=0,               # initial stretch of wire
num_periods=6,           # simulate for num_periods
time_steps_per_period=60, # time step resolution
plot=True,               # make plots or not
):
from math import sin, cos, pi
Theta = Theta*np.pi/180 # convert to radians
# Initial position and velocity
# (we order the equations such that Euler-Cromer in odespy
# can be used, i.e., vx, x, vy, y)
ic = [0,                  # x'=vx
      (1 + epsilon)*sin(Theta), # x
      0,                  # y'=vy
      1 - (1 + epsilon)*cos(Theta), # y
      ]

def f(u, t, beta):
    vx, x, vy, y = u
    L = np.sqrt(x**2 + (y-1)**2)
    h = beta/(1-beta)*(1 - beta/L) # help factor
    return [-h*x, vx, -h*(y-1) - beta, vy]

# Non-elastic pendulum (scaled similarly in the limit beta=1)
# solution Theta*cos(t)
P = 2*pi
dt = P/time_steps_per_period
T = num_periods*P
omega = 2*pi/P

time_points = np.linspace(
    0, T, num_periods*time_steps_per_period+1)

solver = odespy.EulerCromer(f, f_args=(beta,))
solver.set_initial_condition(ic)
u, t = solver.solve(time_points)
x = u[:,1]
y = u[:,3]
theta = np.arctan(x/(1-y))

if plot:
    plt.figure()
    plt.plot(x, y, 'b-', title='Pendulum motion',
             daspect=[1,1,1], daspectmode='equal',
             axis=[x.min(), x.max(), 1.3*y.min(), 1])
    plt.savefig('tmp_xy.png')
    plt.savefig('tmp_xy.pdf')
    # Plot theta in degrees
    plt.figure()
    plt.plot(t, theta*180/np.pi, 'b-',
             title='Angular displacement in degrees')
    plt.savefig('tmp_theta.png')
    plt.savefig('tmp_theta.pdf')
    if abs(Theta) < 10*pi/180:
        # Compare theta and theta_e for small angles (<10 degrees)
        theta_e = Theta*np.cos(omega*t) # non-elastic scaled sol.
        plt.figure()
        plt.plot(t, theta, t, theta_e,
                 legend=['theta elastic', 'theta non-elastic'],
                 title='Elastic vs non-elastic pendulum, \'
                        \'beta=%g\' % beta)
        plt.savefig('tmp_compare.png')
        plt.savefig('tmp_compare.pdf')

```

```
# Plot y vs x (the real physical motion)
return x, y, theta, t
```

b) Write a test function for testing that  $\Theta = 0$  and  $\epsilon = 0$  gives  $x = y = 0$  for all times.

**Solution.** Here is the code:

```
def test_equilibrium():
    """Test that starting from rest makes x=y=theta=0."""
    x, y, theta, t = simulate(
        beta=0.9, Theta=0, epsilon=0,
        num_periods=6, time_steps_per_period=10, plot=False)
    tol = 1E-14
    assert np.abs(x.max()) < tol
    assert np.abs(y.max()) < tol
    assert np.abs(theta.max()) < tol
```

c) Write another test function for checking that the pure vertical motion of the elastic pendulum is correct. Start with simplifying the ODEs for pure vertical motion and show that  $\bar{y}(t)$  fulfills a vibration equation with frequency  $\sqrt{\beta/(1-\beta)}$ . Set up the exact solution.

Write a test function that uses this special case to verify the `simulate` function. There will be numerical approximation errors present in the results from `simulate` so you have to believe in correct results and set a (low) tolerance that corresponds to the computed maximum error. Use a small  $\Delta t$  to obtain a small numerical approximation error.

**Solution.** For purely vertical motion, the ODEs reduce to  $\ddot{x} = 0$  and

$$\ddot{\bar{y}} = -\frac{\beta}{1-\beta}\left(1 - \beta \frac{1}{\sqrt{(\bar{y}-1)^2}}\right)(\bar{y}-1) - \beta = -\frac{\beta}{1-\beta}(\bar{y}-1+\beta) - \beta.$$

We have here used that  $(\bar{y}-1)/\sqrt{(\bar{y}-1)^2} = -1$  since  $\bar{y}$  cannot exceed 1 (the pendulum's wire is fixed at the scaled point  $(0, 1)$ ). In fact,  $\bar{y}$  will be around zero. (As a consistency check, we realize that in equilibrium,  $\ddot{\bar{y}} = 0$ , and multiplying by  $(1-\beta)/\beta$  leads to the expected  $\bar{y} = 0$ .) Further calculations easily lead to

$$\ddot{\bar{y}} = -\frac{\beta}{1-\beta}\bar{y} = -\omega^2\bar{y},$$

where we have introduced the frequency  $\omega = \sqrt{\beta/(1-\beta)}$ . Solving this standard ODE, with an initial stretching  $\bar{y}(0) = \epsilon$  and no velocity, results in

$$\bar{y}(t) = \epsilon \cos(\omega t).$$

Note that the oscillations we describe here are very different from the oscillations used to set the period and time step in function `simulate`. The latter

type of oscillations are due to gravity when a classical, non-elastic pendulum oscillates back and forth, while  $\bar{y}(\bar{t})$  above refers to vertical *elastic* oscillations in the wire around the equilibrium point in the gravity field. The angular frequency of the vertical oscillations are given by  $\omega$  and the corresponding period is  $\hat{P} = 2\pi/\omega$ . Suppose we want to simulate for  $T = N\hat{P} = N2\pi/\omega$  and use  $n$  time steps per period,  $\Delta\bar{t} = \hat{P}/n$ . The `simulate` function operates with a simulation time of `num_periods` times  $2\pi$ . This means that we must set `num_periods=N/omega` if we want to simulate to time  $T = N\hat{P}$ . The parameter `time_steps_per_period` must be set to  $\omega n$  since `simulate` has  $\Delta t$  as  $2\pi$  divided by `time_steps_per_period` and we want  $\Delta t = 2\pi\omega^{-1}n^{-1}$ .

The corresponding test function can be written as follows.

```
def test_vertical_motion():
    beta = 0.9
    omega = np.sqrt(beta/(1-beta))
    # Find num_periods. Recall that P=2*pi for scaled pendulum
    # oscillations, while here we don't have gravity driven
    # oscillations, but elastic oscillations with frequency omega.
    period = 2*np.pi/omega
    # We want T = N*period
    N = 5
    # simulate function has T = 2*pi*num_periods
    num_periods = 5/omega
    n = 600
    time_steps_per_period = omega*n

    y_exact = lambda t: -0.1*np.cos(omega*t)
    x, y, theta, t = simulate(
        beta=beta, Theta=0, epsilon=0.1,
        num_periods=num_periods,
        time_steps_per_period=time_steps_per_period,
        plot=False)


    tol = 0.00055 # ok tolerance for the above resolution
    # No motion in x direction is expected
    assert np.abs(x.max()) < tol
    # Check motion in y direction
    y_e = y_exact(t)
    diff = np.abs(y_e - y).max()
    if diff > tol: # plot
        plt.plot(t, y, t, y_e, legend=['y', 'exact'])
        raw_input('Error in test_vertical_motion; type CR:')
    assert diff < tol, 'diff=%g' % diff
```


d) Make a function `demo(beta, Theta)` for simulating an elastic pendulum with a given  $\beta$  parameter and initial angle  $\Theta$ . Use 600 time steps per period to get every accurate results, and simulate for 3 periods.

**Solution.** The `demo` function is just

```
def demo(beta=0.999, Theta=40, num_periods=3):
    x, y, theta, t = simulate(
        beta=beta, Theta=Theta, epsilon=0,
        num_periods=num_periods, time_steps_per_period=600,
        plot=True)
```

Below are plots corresponding to  $\beta = 0.999$  (3 periods) and  $\beta = 0.93$  (one period):





Filename: `elastic_pendulum`.

### Exercise 23: Simulate an elastic pendulum with air resistance

This is a continuation Exercise 23. Air resistance on the body with mass  $m$  can be modeled by the force  $-\frac{1}{2}\varrho C_D A |\boldsymbol{v}| \boldsymbol{v}$ , where  $C_D$  is a drag coefficient (0.2 for a sphere),  $\varrho$  is the density of air ( $1.2 \text{ kg m}^{-3}$ ),  $A$  is the cross section area ( $A = \pi R^2$  for a sphere, where  $R$  is the radius), and  $\boldsymbol{v}$  is the velocity of the body. Include air resistance in the original model, scale the model, write a function `simulate_drag` that is a copy of the `simulate` function from Exercise 23, but



with the new ODEs included, and show plots of how air resistance influences the motion.

**Solution.** We start with the model (101)-(107). Since  $\mathbf{v} = \dot{x}\mathbf{i} + \dot{y}\mathbf{j}$ , the air resistance term can be written

$$-q(\dot{x}\mathbf{i} + \dot{y}\mathbf{j}), \quad q = \frac{1}{2}\varrho C_D A \sqrt{\dot{x}^2 + \dot{y}^2}.$$

Note that for positive velocities, the pendulum is moving to the right and the air resistance works against the motion, i.e., in direction of  $-\mathbf{v}$ .

We can easily include the terms in the ODEs:

$$\ddot{x} = -\frac{q}{m}\dot{x} - \frac{k}{m}\left(1 - \frac{L_0}{L}\right)(x - x_0), \quad (123)$$

$$\ddot{y} = \frac{q}{m}\dot{y} - \frac{k}{m}\left(1 - \frac{L_0}{L}\right)(y - y_0) - g, \quad (124)$$

$$L = \sqrt{(x - x_0)^2 + (y - y_0)^2}, \quad (125)$$

$$(126)$$

The initial conditions are not affected.

The next step is to scale the model. We use the same scales as in Exercise 23. The new scaled term (after dividing by the length scale) in the  $x$  component is

$$t_c^{-2} \frac{1}{2m} \varrho C_D A \sqrt{\frac{(L_0 + mg/k)^2}{t_c^2} \left( \left( \frac{d\bar{x}}{d\bar{t}} \right)^2 + \left( \frac{d\bar{y}}{d\bar{t}} \right)^2 \right)} t_c^{-1} \dot{x} = \frac{1}{2} \varrho C_D A (L_0 + mg/k) \sqrt{\dot{x}^2 + \dot{y}^2} \frac{x}{L}.$$

We can introduce the  $\beta$  parameter and use  $A = \pi R^2$  to simplify a bit:

$$\frac{L_0}{2m} \varrho C_D R^2 \beta^{-1} \sqrt{\left( \frac{d\bar{x}}{d\bar{t}} \right)^2 + \left( \frac{d\bar{y}}{d\bar{t}} \right)^2} = \gamma \beta^{-1} \sqrt{\left( \frac{d\bar{x}}{d\bar{t}} \right)^2 + \left( \frac{d\bar{y}}{d\bar{t}} \right)^2},$$

where  $\gamma$  is a second dimensionless parameter:

$$\gamma = \frac{L_0}{2m} \varrho C_D R^2.$$

The final set of scaled equations are then

$$\frac{d^2\bar{x}}{d\bar{t}^2} = -\gamma\beta^{-1}\sqrt{\left(\frac{d\bar{x}}{d\bar{t}}\right)^2 + \left(\frac{d\bar{y}}{d\bar{t}}\right)^2}\frac{d\bar{x}}{d\bar{t}} - \frac{\beta}{1-\beta}\left(1 - \frac{\beta}{\bar{L}}\right)\bar{x}, \quad (127)$$

$$\frac{d^2\bar{y}}{d\bar{t}^2} = -\gamma\beta^{-1}\sqrt{\left(\frac{d\bar{x}}{d\bar{t}}\right)^2 + \left(\frac{d\bar{y}}{d\bar{t}}\right)^2}\frac{d\bar{y}}{d\bar{t}} - \frac{\beta}{1-\beta}\left(1 - \frac{\beta}{\bar{L}}\right)(\bar{y} - 1) - \beta, \quad (128)$$

$$\bar{L} = \sqrt{\bar{x}^2 + (\bar{y} - 1)^2}, \quad (129)$$

$$\bar{x}(0) = (1 + \epsilon)\sin\Theta, \quad (130)$$

$$\frac{d\bar{x}}{d\bar{t}}(0) = 0, \quad (131)$$

$$\bar{y}(0) = 1 - (1 + \epsilon)\cos\Theta, \quad (132)$$

$$\frac{d\bar{y}}{d\bar{t}}(0) = 0, \quad (133)$$

The new `simulate_drag` function becomes

```
def simulate_drag(
    beta=0.9,                # dimensionless elasticity parameter
    gamma=0,                 # dimensionless drag parameter
    Theta=30,                # initial angle in degrees
    epsilon=0,               # initial stretch of wire
    num_periods=6,           # simulate for num_periods
    time_steps_per_period=60, # time step resolution
    plot=True,               # make plots or not
):
    from math import sin, cos, pi
    Theta = Theta*np.pi/180 # convert to radians
    # Initial position and velocity
    # (we order the equations such that Euler-Cromer in odespy
    # can be used, i.e., vx, x, vy, y)
    ic = [0,                 # x'=vx
          (1 + epsilon)*sin(Theta), # x
          0,                 # y'=vy
          1 - (1 + epsilon)*cos(Theta), # y
          ]

    def f(u, t, beta, gamma):
        vx, x, vy, y = u
        L = np.sqrt(x**2 + (y-1)**2)
        v = np.sqrt(vx**2 + vy**2)
        h1 = beta/(1-beta)*(1 - beta/L) # help factor
        h2 = gamma/beta*v
        return [-h2*vx - h1*x, vx, -h2*vy - h1*(y-1) - beta, vy]

    # Non-elastic pendulum (scaled similarly in the limit beta=1)
    # solution Theta*cos(t)
    P = 2*pi
    dt = P/time_steps_per_period
    T = num_periods*P
    omega = 2*pi/P

    time_points = np.linspace(
        0, T, num_periods*time_steps_per_period+1)

    solver = odespy.EulerCromer(f, f_args=(beta, gamma))
```


```

solver.set_initial_condition(ic)
u, t = solver.solve(time_points)
x = u[:,1]
y = u[:,3]
theta = np.arctan(x/(1-y))

if plot:
    plt.figure()
    plt.plot(x, y, 'b-', title='Pendulum motion',
             daspect=[1,1,1], daspectmode='equal',
             axis=[x.min(), x.max(), 1.3*y.min(), 1])
    plt.savefig('tmp_xy.png')
    plt.savefig('tmp_xy.pdf')
    # Plot theta in degrees
    plt.figure()
    plt.plot(t, theta*180/np.pi, 'b-',
             title='Angular displacement in degrees')
    plt.savefig('tmp_theta.png')
    plt.savefig('tmp_theta.pdf')
    if abs(Theta) < 10*pi/180:
        # Compare theta and theta_e for small angles (<10 degrees)
        theta_e = Theta*np.cos(omega*t) # non-elastic scaled sol.
        plt.figure()
        plt.plot(t, theta, t, theta_e,
                 legend=['theta elastic', 'theta non-elastic'],
                 title='Elastic vs non-elastic pendulum, '\
                        'beta=%g' % beta)
        plt.savefig('tmp_compare.png')
        plt.savefig('tmp_compare.pdf')
    # Plot y vs x (the real physical motion)
    return x, y, theta, t

```

The plot of  $\theta$  shows the damping ( $\beta = 0.999$ ):



Test functions for equilibrium and vertical motion are also included. These are as in Exercise 23, except that they call `simulate_drag` instead of `simulate`. Filename: `elastic_pendulum_drag`.

**Remarks.** Test functions are challenging to construct for the problem with air resistance. You can reuse the tests from Exercise 23 for `simulate_drag`, but these tests does not verify the new terms arising from air resistance.

## References

- [1] H. P. Langtangen. *Finite Difference Computing with Exponential Decay Models*. Springer, 2015. <http://tinyurl.com/nclmcng/web>.
- [2] H. P. Langtangen and G. K. Pedersen. *Scaling of Differential Equations*. 2015. <http://tinyurl.com/qfjgxmfw/web>.

## Index

- animation, 13
- `argparse` (Python module), 51
- `ArgumentParser` (Python class), 51
- averaging
  - geometric, 47
- centered difference, 4
- DOF (degree of freedom), 84
- energy principle, 37
- error
  - global, 25
- finite differences
  - centered, 4
- Flash (video format), 13
- forced vibrations, 46
- forward-backward Euler-Cromer scheme,
  - 41
- frequency (of oscillations), 3
- geometric mean, 47
- HTML5 video tag, 14
- Hz (unit), 3
- making movies, 13
- mechanical energy, 37
- mechanical vibrations, 3
- mesh
  - finite differences, 4
- mesh function, 4
- MP4 (video format), 13
- nonlinear restoring force, 46
- nonlinear spring, 46
- nose, 8
- Ogg (video format), 13
- oscillations, 3
- period (of oscillations), 3
- phase plane plot, 33
- pytest, 8
- resonance, 102
- `scitools movie` command, 15
- stability criterion, 26
- test function, 8
- unit testing, 8
- verification
  - convergence rates, 9
  - hand calculations, 8
  - polynomial solutions, 9
- vibration ODE, 3
- video formats, 13
- WebM (video format), 13