Study guide: Finite difference methods for vibration problems

Hans Petter Langtangen[1,2]

Svein Linge[3,1]

[1]Center for Biomedical Computing, Simula Research Laboratory
[2]Department of Informatics, University of Oslo
[3]Department of Process, Energy and Environmental Technology, University College of Southeast Norway

Aug 15, 2017

A simple vibration problem

$$u''(t) + \omega^2 u = 0, \quad u(0) = I, \ u'(0) = 0, \ t \in (0, T]$$

Exact solution:

$$u(t) = I \cos(\omega t)$$

$u(t)$ oscillates with constant amplitude I and (angular) frequency ω. Period: $P = 2\pi/\omega$.

A centered finite difference scheme; step 1 and 2

- Strategy: follow the four steps of the finite difference method.

- Step 1: Introduce a time mesh, here uniform on $[0, T]$: $t_n = n\Delta t$

- Step 2: Let the ODE be satisfied at each mesh point:

$$u''(t_n) + \omega^2 u(t_n) = 0, \quad n = 1, \ldots, N_t$$

A centered finite difference scheme; step 3

Step 3: Approximate derivative(s) by finite difference approximation(s). Very common (standard!) formula for u'':

$$u''(t_n) \approx \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2}$$

Use this discrete initial condition together with the ODE at $t = 0$ to eliminate u^{-1}:

$$\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} = -\omega^2 u^n$$

A centered finite difference scheme; step 4

Step 4: Formulate the computational algorithm. Assume u^{n-1} and u^n are known, solve for unknown u^{n+1}:

$$u^{n+1} = 2u^n - u^{n-1} - \Delta t^2 \omega^2 u^n$$

Nick names for this scheme: Störmer's method or Verlet integration.

Computing the first step

- The formula breaks down for u^1 because u^{-1} is unknown and outside the mesh!

- And: we have not used the initial condition $u'(0) = 0$.

Discretize $u'(0) = 0$ by a centered difference

$$\frac{u^1 - u^{-1}}{2\Delta t} = 0 \quad \Rightarrow \quad u^{-1} = u^1$$

Inserted in the scheme for $n = 0$ gives

$$u^1 = u^0 - \frac{1}{2}\Delta t^2 \omega^2 u^0$$

The computational algorithm

1. $u^0 = I$

2. compute u^1

3. for $n = 1, 2, \ldots, N_t - 1$:

    (a) compute u^{n+1}

More precisly expressed in Python:

```
t = linspace(0, T, Nt+1)   # mesh points in time
dt = t[1] - t[0]           # constant time step.
u = zeros(Nt+1)            # solution

u[0] = I
u[1] = u[0] - 0.5*dt**2*w**2*u[0]
for n in range(1, Nt):
    u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n]
```

Note: `w` is consistently used for ω in my code.

Operator notation; ODE

With $[D_t D_t u]^n$ as the finite difference approximation to $u''(t_n)$ we can write

$$[D_t D_t u + \omega^2 u = 0]^n$$

$[D_t D_t u]^n$ means applying a central difference with step $\Delta t/2$ twice:

$$[D_t(D_t u)]^n = \frac{[D_t u]^{n+\frac{1}{2}} - [D_t u]^{n-\frac{1}{2}}}{\Delta t}$$

which is written out as

$$\frac{1}{\Delta t}\left(\frac{u^{n+1} - u^n}{\Delta t} - \frac{u^n - u^{n-1}}{\Delta t}\right) = \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2}.$$

Operator notation; initial condition

$$[u = I]^0, \quad [D_{2t} u = 0]^0$$

where $[D_{2t} u]^n$ is defined as

$$[D_{2t} u]^n = \frac{u^{n+1} - u^{n-1}}{2\Delta t}.$$

Computing u'

u is often displacement/position, u' is velocity and can be computed by

$$u'(t_n) \approx \frac{u^{n+1} - u^{n-1}}{2\Delta t} = [D_{2t} u]^n$$

Implementation

Core algorithm

```
import numpy as np
import matplotlib.pyplot as plt

def solver(I, w, dt, T):
    """
    Solve u'' + w**2*u = 0 for t in (0,T], u(0)=I and u'(0)=0,
    by a central finite difference method with time step dt.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)

    u[0] = I
    u[1] = u[0] - 0.5*dt**2*w**2*u[0]
    for n in range(1, Nt):
        u[n+1] = 2*u[n] - u[n-1] - dt**2*w**2*u[n]
    return u, t

def solver_adjust_w(I, w, dt, T, adjust_w=True):
    """
    Solve u'' + w**2*u = 0 for t in (0,T], u(0)=I and u'(0)=0,
    by a central finite difference method with time step dt.
    """
    dt = float(dt)
    Nt = int(round(T/dt))
    u = np.zeros(Nt+1)
    t = np.linspace(0, Nt*dt, Nt+1)
    w_adj = w*(1 - w**2*dt**2/24.) if adjust_w else w

    u[0] = I
    u[1] = u[0] - 0.5*dt**2*w_adj**2*u[0]
    for n in range(1, Nt):
        u[n+1] = 2*u[n] - u[n-1] - dt**2*w_adj**2*u[n]
    return u, t
```

Plotting

```
def u_exact(t, I, w):
    return I*np.cos(w*t)

def visualize(u, t, I, w):
    plt.plot(t, u, 'r--o')
    t_fine = np.linspace(0, t[-1], 1001)  # very fine mesh for u_e
```

```
    u_e = u_exact(t_fine, I, w)
    plt.hold('on')
    plt.plot(t_fine, u_e, 'b-')
    plt.legend(['numerical', 'exact'], loc='upper left')
    plt.xlabel('t')
    plt.ylabel('u')
    dt = t[1] - t[0]
    plt.title('dt=%g' % dt)
    umin = 1.2*u.min();   umax = -umin
    plt.axis([t[0], t[-1], umin, umax])
    plt.savefig('tmp1.png');  plt.savefig('tmp1.pdf')
```

Main program

```
I = 1
w = 2*pi
dt = 0.05
num_periods = 5
P = 2*pi/w    #  one period
T = P*num_periods
u, t = solver(I, w, dt, T)
visualize(u, t, I, w, dt)
```

User interface: command line

```
import argparse
parser = argparse.ArgumentParser()
parser.add_argument('--I', type=float, default=1.0)
parser.add_argument('--w', type=float, default=2*pi)
parser.add_argument('--dt', type=float, default=0.05)
parser.add_argument('--num_periods', type=int, default=5)
a = parser.parse_args()
I, w, dt, num_periods = a.I, a.w, a.dt, a.num_periods
```

Running the program

vib_undamped.py:

```
Terminal> python vib_undamped.py --dt 0.05 --num_periods 40
```

Generates frames `tmp_vib%04d.png` in files. Can make movie:

```
Terminal> ffmpeg -r 12 -i tmp_vib%04d.png -c:v flv movie.flv
```

Can use `avconv` instead of `ffmpeg`.

Format	Codec and filename
Flash	`-c:v flv movie.flv`
MP4	`-c:v libx264 movie.mp4`
Webm	`-c:v libvpx movie.webm`
Ogg	`-c:v libtheora movie.ogg`

Verification

First steps for testing and debugging

- **Testing very simple solutions**: $u = \text{const}$ or $u = ct + d$ do not apply here (without a force term in the equation: $u'' + \omega^2 u = f$).

- **Hand calculations**: calculate u^1 and u^2 and compare with program.

Checking convergence rates

The next function estimates convergence rates, i.e., it

- performs m simulations with halved time steps: $2^{-k}\Delta t$, $k = 0, \ldots, m-1$,

- computes the L_2 norm of the error, $E = \sqrt{\Delta t_i \sum_{n=0}^{N_t-1} (u^n - u_{\mathrm{e}}(t_n))^2}$ in each case,

- estimates the rates r_i from two consecutive experiments $(\Delta t_{i-1}, E_{i-1})$ and $(\Delta t_i, E_i)$, assuming $E_i = C\Delta t_i^{r_i}$ and $E_{i-1} = C\Delta t_{i-1}^{r_i}$:

Implementational details

```
def convergence_rates(m, solver_function, num_periods=8):
    """
    Return m-1 empirical estimates of the convergence rate
    based on m simulations, where the time step is halved
    for each simulation.
    solver_function(I, w, dt, T) solves each problem, where T
    is based on simulation for num_periods periods.
    """
    from math import pi
    w = 0.35; I = 0.3        # just chosen values
    P = 2*pi/w               # period
    dt = P/30                # 30 time step per period 2*pi/w
    T = P*num_periods

    dt_values = []
    E_values = []
    for i in range(m):
        u, t = solver_function(I, w, dt, T)
        u_e = u_exact(t, I, w)
        E = np.sqrt(dt*np.sum((u_e-u)**2))
        dt_values.append(dt)
        E_values.append(E)
        dt = dt/2

    r = [np.log(E_values[i-1]/E_values[i])/
         np.log(dt_values[i-1]/dt_values[i])
         for i in range(1, m, 1)]
    return r, E_values, dt_values
```

Result: `r` contains values equal to 2.00 - as expected!

Unit test for the convergence rate

Use final `r[-1]` in a unit test:

```
def test_convergence_rates():
    r, E, dt = convergence_rates(
        m=5, solver_function=solver, num_periods=8)
    # Accept rate to 1 decimal place
    tol = 0.1
    assert abs(r[-1] - 2.0) < tol
    # Test that adjusted w obtains 4th order convergence
    r, E, dt = convergence_rates(
        m=5, solver_function=solver_adjust_w, num_periods=8)
    print 'adjust w rates:', r
    assert abs(r[-1] - 4.0) < tol
```

```
def plot_convergence_rates():
    r2, E2, dt2 = convergence_rates(
        m=5, solver_function=solver, num_periods=8)
    plt.loglog(dt2, E2)
    r4, E4, dt4 = convergence_rates(
        m=5, solver_function=solver_adjust_w, num_periods=8)
    plt.loglog(dt4, E4)
    plt.legend(['original scheme', r'adjusted $\omega$'],
               loc='upper left')
    plt.title('Convergence of finite difference methods')
    from plotslopes import slope_marker
    slope_marker((dt2[1], E2[1]), (2,1))
    slope_marker((dt4[1], E4[1]), (4,1))
    plt.savefig('tmp_convrate.png'); plt.savefig('tmp_convrate.pdf')
    plt.show()
```

Complete code in `vib_undamped.py`.

Long time simulations

Effect of the time step on long simulations

- The numerical solution seems to have right amplitude.

- There is an angular frequency error (reduced by reducing the time step).

- The total angular frequency error seems to grow with time.

Using a moving plot window

- In long time simulations we need a plot window that follows the solution.

- Method 1: `scitools.MovingPlotWindow`.

- Method 2: `scitools.avplotter` (ASCII vertical plotter).

Example:

```
Terminal> python vib_undamped.py --dt 0.05 --num_periods 40
```

Movie of the moving plot window.
!splot

Long time simulations visualized with aid of Bokeh: coupled panning of multiple graphs

- Bokeh is a Python plotting library for fancy web graphics

- Example here: long time series with many coupled graphs that can move simultaneously

!splot

How does Bokeh plotting code look like?

```python
def bokeh_plot(u, t, legends, I, w, t_range, filename):
    """
    Make plots for u vs t using the Bokeh library.
    u and t are lists (several experiments can be compared).
    legens contain legend strings for the various u,t pairs.
    """
    if not isinstance(u, (list,tuple)):
        u = [u]   # wrap in list
    if not isinstance(t, (list,tuple)):
```

```
        t = [t]  # wrap in list
    if not isinstance(legends, (list,tuple)):
        legends = [legends]  # wrap in list

    import bokeh.plotting as plt
    plt.output_file(filename, mode='cdn', title='Comparison')
    # Assume that all t arrays have the same range
    t_fine = np.linspace(0, t[0][-1], 1001)  # fine mesh for u_e
    tools = 'pan,wheel_zoom,box_zoom,reset,'\
            'save,box_select,lasso_select'
    u_range = [-1.2*I, 1.2*I]
    font_size = '8pt'
    p = []  # list of plot objects
    # Make the first figure
    p_ = plt.figure(
        width=300, plot_height=250, title=legends[0],
        x_axis_label='t', y_axis_label='u',
        x_range=t_range, y_range=u_range, tools=tools,
        title_text_font_size=font_size)
    p_.xaxis.axis_label_text_font_size=font_size
    p_.yaxis.axis_label_text_font_size=font_size
    p_.line(t[0], u[0], line_color='blue')
    # Add exact solution
    u_e = u_exact(t_fine, I, w)
    p_.line(t_fine, u_e, line_color='red', line_dash='4 4')
    p.append(p_)
    # Make the rest of the figures and attach their axes to
    # the first figure's axes
    for i in range(1, len(t)):
        p_ = plt.figure(
            width=300, plot_height=250, title=legends[i],
            x_axis_label='t', y_axis_label='u',
            x_range=p[0].x_range, y_range=p[0].y_range, tools=tools,
            title_text_font_size=font_size)
        p_.xaxis.axis_label_text_font_size = font_size
        p_.yaxis.axis_label_text_font_size = font_size
        p_.line(t[i], u[i], line_color='blue')
        p_.line(t_fine, u_e, line_color='red', line_dash='4 4')
        p.append(p_)

    # Arrange all plots in a grid with 3 plots per row
    grid = [[]]
    for i, p_ in enumerate(p):
        grid[-1].append(p_)
        if (i+1) % 3 == 0:
            # New row
            grid.append([])
    plot = plt.gridplot(grid, toolbar_location='left')
    plt.save(plot)
```

```
plt.show(plot)
```

Analysis of the numerical scheme

Can we understand the frequency error?

Movie of the angular frequency error

$u'' + \omega^2 u = 0$, $u(0) = 1$, $u'(0) = 0$, $\omega = 2\pi$, $u_e(t) = \cos(2\pi t)$, $\Delta t = 0.05$ (20 intervals per period)

Movie 1: `mov-vib/vib_undamped_movie_dt0.05/movie.ogg`

We can derive an exact solution of the discrete equations

- We have a linear, homogeneous, difference equation for u^n.

- Has solutions $u^n \sim IA^n$, where A is unknown (number).

- Here: $u_e(t) = I\cos(\omega t) \sim I\exp(i\omega t) = I(e^{i\omega \Delta t})^n$

- Trick for simplifying the algebra: $u^n = IA^n$, with $A = \exp(i\tilde{\omega}\Delta t)$, then find $\tilde{\omega}$

- $\tilde{\omega}$: unknown *numerical frequency* (easier to calculate than A)

- $\omega - \tilde{\omega}$ is the angular *frequency error*

- Use the real part as the physical relevant part of a complex expression

Calculations of an exact solution of the discrete equations

$$u^n = I A^n = I \exp\left(\tilde\omega \Delta t\, n\right) = I \exp\left(\tilde\omega t\right) = I \cos(\tilde\omega t) + iI \sin(\tilde\omega t)\,.$$

$$
\begin{aligned}
[D_t D_t u]^n &= \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} \\
&= I \frac{A^{n+1} - 2A^n + A^{n-1}}{\Delta t^2} \\
&= I \frac{\exp\left(i\tilde\omega(t+\Delta t)\right) - 2\exp\left(i\tilde\omega t\right) + \exp\left(i\tilde\omega(t-\Delta t)\right)}{\Delta t^2} \\
&= I \exp\left(i\tilde\omega t\right)\frac{1}{\Delta t^2}\left(\exp\left(i\tilde\omega(\Delta t)\right) + \exp\left(i\tilde\omega(-\Delta t)\right) - 2\right) \\
&= I \exp\left(i\tilde\omega t\right)\frac{2}{\Delta t^2}\left(\cosh(i\tilde\omega \Delta t) - 1\right) \\
&= I \exp\left(i\tilde\omega t\right)\frac{2}{\Delta t^2}\left(\cos(\tilde\omega \Delta t) - 1\right) \\
&= -I \exp\left(i\tilde\omega t\right)\frac{4}{\Delta t^2}\sin^2(\frac{\tilde\omega \Delta t}{2})
\end{aligned}
$$

Solving for the numerical frequency

The scheme with $u^n = I \exp\left(i\omega \tilde\Delta t\, n\right)$ inserted gives

$$-I \exp\left(i\tilde\omega t\right)\frac{4}{\Delta t^2}\sin^2(\frac{\tilde\omega \Delta t}{2}) + \omega^2 I \exp\left(i\tilde\omega t\right) = 0$$

which after dividing by $I \exp\left(i\tilde\omega t\right)$ results in

$$\frac{4}{\Delta t^2}\sin^2(\frac{\tilde\omega \Delta t}{2}) = \omega^2$$

Solve for $\tilde\omega$:

$$\tilde\omega = \pm\frac{2}{\Delta t}\sin^{-1}\left(\frac{\omega \Delta t}{2}\right)$$

- Frequency error because $\tilde\omega \neq \omega$.

- Note: dimensionless number $p = \omega \Delta t$ is the key parameter
  (i.e., no of time intervals per period is important, not Δt itself)

- But how good is the approximation $\tilde\omega$ to ω?

Polynomial approximation of the frequency error

Taylor series expansion for small Δt gives a formula that is easier to understand:

```
>>> from sympy import *
>>> dt, w = symbols('dt w')
>>> w_tilde = asin(w*dt/2).series(dt, 0, 4)*2/dt
>>> print w_tilde
(dt*w + dt**3*w**3/24 + O(dt**4))/dt   # note the final "/dt"
```

$$\tilde{\omega} = \omega \left(1 + \frac{1}{24} \omega^2 \Delta t^2 \right) + \mathcal{O}(\Delta t^3)$$

The numerical frequency is too large (to fast oscillations).

Plot of the frequency error

Recommendation: 25-30 points per period.

Exact discrete solution

$$u^n = I \cos\left(\tilde{\omega} n \Delta t \right), \quad \tilde{\omega} = \frac{2}{\Delta t} \sin^{-1} \left(\frac{\omega \Delta t}{2} \right)$$

The error mesh function,

$$e^n = u_{\mathrm{e}}(t_n) - u^n = I \cos\left(\omega n \Delta t \right) - I \cos\left(\tilde{\omega} n \Delta t \right)$$

is ideal for verification and further analysis!

$$e^n = I\cos\left(\omega n\Delta t\right) - I\cos\left(\tilde{\omega}n\Delta t\right) = -2I\sin\left(t\frac{1}{2}\left(\omega - \tilde{\omega}\right)\right)\sin\left(t\frac{1}{2}\left(\omega + \tilde{\omega}\right)\right)$$

Convergence of the numerical scheme

Can easily show *convergence*:

$$e^n \to 0 \text{ as } \Delta t \to 0,$$

because

$$\lim_{\Delta t \to 0} \tilde{\omega} = \lim_{\Delta t \to 0} \frac{2}{\Delta t}\sin^{-1}\left(\frac{\omega\Delta t}{2}\right) = \omega,$$

by L'Hopital's rule or simply asking `sympy`: or WolframAlpha:

```
>>> import sympy as sym
>>> dt, w = sym.symbols('x w')
>>> sym.limit((2/dt)*sym.asin(w*dt/2), dt, 0, dir='+')
w
```

Stability

Observations:

- Numerical solution has constant amplitude (desired!), but an angular frequency error

- Constant amplitude requires $\sin^{-1}(\omega\Delta t/2)$ to be real-valued $\Rightarrow |\omega\Delta t/2| \leq 1$

- $\sin^{-1}(x)$ is complex if $|x| > 1$, and then $\tilde{\omega}$ becomes complex

What is the consequence of complex $\tilde{\omega}$?

- Set $\tilde{\omega} = \tilde{\omega}_r + i\tilde{\omega}_i$

- Since $\sin^{-1}(x)$ has a *negative* imaginary part for $x > 1$, $\exp\left(i\omega\tilde{t}\right) = \exp\left(-\tilde{\omega}_i t\right)\exp\left(i\tilde{\omega}_r t\right)$ leads to exponential growth $e^{-\tilde{\omega}_i t}$ when $-\tilde{\omega}_i t > 0$

- This is *instability* because the qualitative behavior is wrong

14

The stability criterion

Cannot tolerate growth and must therefore demand a *stability criterion*

$$\frac{\omega \Delta t}{2} \leq 1 \quad \Rightarrow \quad \Delta t \leq \frac{2}{\omega}$$

Try $\Delta t = \frac{2}{\omega} + 9.01 \cdot 10^{-5}$ (*slightly* too big!):

Summary of the analysis

We can draw three important conclusions:

1. The key parameter in the formulas is $p = \omega \Delta t$ (dimensionless)

   (a) Period of oscillations: $P = 2\pi/\omega$

   (b) Number of time steps per period: $N_P = P/\Delta t$

   (c) $\Rightarrow$ $p = \omega \Delta t = 2\pi/N_P \sim 1/N_P$

   (d) The smallest possible N_P is $2 \Rightarrow p \in (0, \pi]$

2. For $p \leq 2$ the amplitude of u^n is constant (stable solution)

3. u^n has a relative frequency error $\tilde{\omega}/\omega \approx 1 + \frac{1}{24}p^2$, making numerical peaks occur too early

Alternative schemes based on 1st-order equations

Rewriting 2nd-order ODE as system of two 1st-order ODEs

The vast collection of ODE solvers (e.g., in Odespy) cannot be applied to

$$u'' + \omega^2 u = 0$$

unless we write this higher-order ODE as a system of 1st-order ODEs.
Introduce an auxiliary variable $v = u'$:

$$u' = v, \tag{1}$$
$$v' = -\omega^2 u. \tag{2}$$

Initial conditions: $u(0) = I$ and $v(0) = 0$.

The Forward Euler scheme

We apply the Forward Euler scheme to each component equation:

$$[D_t^+ u = v]^n,$$
$$[D_t^+ v = -\omega^2 u]^n,$$

or written out,

$$u^{n+1} = u^n + \Delta t v^n, \tag{3}$$
$$v^{n+1} = v^n - \Delta t \omega^2 u^n. \tag{4}$$

The Backward Euler scheme

We apply the Backward Euler scheme to each component equation:

$$[D_t^- u = v]^{n+1}, \tag{5}$$
$$[D_t^- v = -\omega u]^{n+1}. \tag{6}$$

Written out:

$$u^{n+1} - \Delta t v^{n+1} = u^n, \tag{7}$$
$$v^{n+1} + \Delta t \omega^2 u^{n+1} = v^n. \tag{8}$$

This is a *coupled* 2×2 system for the new values at $t = t_{n+1}$!

The Crank-Nicolson scheme

$$[D_t u = \overline{v}^t]^{n+\frac{1}{2}},\tag{9}$$

$$[D_t v = -\omega \overline{u}^t]^{n+\frac{1}{2}}.\tag{10}$$

The result is also a coupled system:

$$u^{n+1} - \frac{1}{2}\Delta t v^{n+1} = u^n + \frac{1}{2}\Delta t v^n,\tag{11}$$

$$v^{n+1} + \frac{1}{2}\Delta t \omega^2 u^{n+1} = v^n - \frac{1}{2}\Delta t \omega^2 u^n.\tag{12}$$

Comparison of schemes via Odespy

Can use Odespy to compare many methods for first-order schemes:

```python
import odespy
import numpy as np

def f(u, t, w=1):
    # v, u numbering for EulerCromer to work well
    v, u = u  # u is array of length 2 holding our [v, u]
    return [-w**2*u, v]

def run_solvers_and_plot(solvers, timesteps_per_period=20,
                         num_periods=1, I=1, w=2*np.pi):
    P = 2*np.pi/w  # duration of one period
    dt = P/timesteps_per_period
    Nt = num_periods*timesteps_per_period
    T = Nt*dt
    t_mesh = np.linspace(0, T, Nt+1)

    legends = []
    for solver in solvers:
        solver.set(f_kwargs={'w': w})
        solver.set_initial_condition([0, I])
        u, t = solver.solve(t_mesh)
```

## Forward and Backward Euler and Crank-Nicolson

```python
solvers = [
    odespy.ForwardEuler(f),
    # Implicit methods must use Newton solver to converge
```

```
    odespy.BackwardEuler(f, nonlinear_solver='Newton'),
    odespy.CrankNicolson(f, nonlinear_solver='Newton'),
    ]
```

Two plot types:

- $u(t)$ vs t

- Parameterized curve $(u(t), v(t))$ in *phase space*

- Exact curve is an ellipse: $(I \cos \omega t, -\omega I \sin \omega t)$, closed and periodic

Phase plane plot of the numerical solutions

Note: CrankNicolson in Odespy leads to the name MidpointImplicit in plots.

Plain solution curves

Figure 1: Comparison of classical schemes.

Observations from the figures

- Forward Euler has growing amplitude and outward (u, v) spiral - pumps energy into the system.

- Backward Euler is opposite: decreasing amplitude, inward sprial, extracts energy.

- **Forward and Backward Euler are useless for vibrations.**

- Crank-Nicolson (MidpointImplicit) looks much better.

## Runge-Kutta methods of order 2 and 4; short time series

Runge-Kutta methods of order 2 and 4; longer time series

Crank-Nicolson; longer time series

(MidpointImplicit means CrankNicolson in Odespy)

Observations of RK and CN methods

- 4th-order Runge-Kutta is very accurate, also for large Δt.

- 2th-order Runge-Kutta is almost as bad as Forward and Backward Euler.

- Crank-Nicolson is accurate, but the amplitude is not as accurate as the difference scheme for $u'' + \omega^2 u = 0$.

Energy conservation property

The model

$$u'' + \omega^2 u = 0, \quad u(0) = I, \ u'(0) = V,$$

has the nice *energy conservation property* that

$$E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2 = \text{const}.$$

This can be used to check solutions.

Derivation of the energy conservation property

Multiply $u'' + \omega^2 u = 0$ by u' and integrate:

$$\int_0^T u'' u' dt + \int_0^T \omega^2 u u' dt = 0.$$

Observing that

$$u'' u' = \frac{d}{dt}\frac{1}{2}(u')^2, \quad uu' = \frac{d}{dt}\frac{1}{2}u^2,$$

we get

$$\int_0^T (\frac{d}{dt}\frac{1}{2}(u')^2 + \frac{d}{dt}\frac{1}{2}\omega^2 u^2)dt = E(T) - E(0),$$

where

$$E(t) = \frac{1}{2}(u')^2 + \frac{1}{2}\omega^2 u^2$$

Remark about $E(t)$

$E(t)$ does not measure energy, energy per mass unit.

Starting with an ODE coming directly from Newton's 2nd law $F = ma$ with a spring force $F = -ku$ and $ma = mu''$ (a: acceleration, u: displacement), we have

$$mu'' + ku = 0$$

Integrating this equation gives a physical energy balance:

$$E(t) = \underbrace{\frac{1}{2}mv^2}_{\text{kinetic energy}} + \underbrace{\frac{1}{2}ku^2}_{\text{potential energy}} = E(0), \quad v = u'$$

Note: the balance is not valid if we add other terms to the ODE.

The Euler-Cromer method; idea

2x2 system for $u'' + \omega^2 u = 0$:

$$v' = -\omega^2 u$$
$$u' = v$$

Forward-backward discretization:

- Update v with Forward Euler

- Update u with Backward Euler, using latest v

$$[D_t^+ v = -\omega^2 u]^n \tag{13}$$
$$[D_t^- u = v]^{n+1} \tag{14}$$

The Euler-Cromer method; complete formulas

Written out:

$$u^0 = I, \tag{15}$$
$$v^0 = 0, \tag{16}$$
$$v^{n+1} = v^n - \Delta t \omega^2 u^n \tag{17}$$
$$u^{n+1} = u^n + \Delta t v^{n+1} \tag{18}$$

Names: Forward-backward scheme, Semi-implicit Euler method, symplectic Euler, semi-explicit Euler, Newton-Stormer-Verlet, and *Euler-Cromer*.

Euler-Cromer is equivalent to the scheme for $u'' + \omega^2 u = 0$

- Forward Euler and Backward Euler have error $\mathcal{O}(\Delta t)$

- What about the overall scheme? Expect $\mathcal{O}(\Delta t)$...

We can eliminate v^n and v^{n+1}, resulting in

$$u^{n+1} = 2u^n - u^{n-1} - \Delta t^2 \omega^2 u^n$$

which is the centered finite differrence scheme for $u'' + \omega^2 u = 0$!

The schemes are not equivalent wrt the initial conditions

$$u' = v = 0 \quad \Rightarrow \quad v^0 = 0,$$

so

$$v^1 = v^0 - \Delta t \omega^2 u^0 = -\Delta t \omega^2 u^0$$

$$u^1 = u^0 + \Delta t v^1 = u^0 - \Delta t \omega^2 u^0! = \qquad \underbrace{u^0 - \frac{1}{2}\Delta t \omega^2 u^0}$$
$$\text{from } [D_t D_t u + \omega^2 u = 0]^n \text{ and } [D_{2t} u = 0]^0$$

The exact discrete solution derived earlier does not fit the Euler-Cromer scheme because of mismatch for u^1.

Generalization: damping, nonlinear spring, and external excitation

$$mu'' + f(u') + s(u) = F(t), \quad u(0) = I, \ u'(0) = V, \ t \in (0, T]$$

Input data: m, $f(u')$, $s(u)$, $F(t)$, I, V, and T.
Typical choices of f and s:

- linear damping $f(u') = bu$, or

- quadratic damping $f(u') = bu'|u'|$

- linear spring $s(u) = cu$

- nonlinear spring $s(u) \sim \sin(u)$ (pendulum)

A centered scheme for linear damping

$$[mD_tD_tu + f(D_{2t}u) + s(u) = F]^n$$

Written out

$$m\frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} + f(\frac{u^{n+1} - u^{n-1}}{2\Delta t}) + s(u^n) = F^n$$

Assume $f(u')$ is linear in $u' = v$:

$$u^{n+1} = \left(2mu^n + (\frac{b}{2}\Delta t - m)u^{n-1} + \Delta t^2(F^n - s(u^n))\right)(m + \frac{b}{2}\Delta t)^{-1}$$

Initial conditions

$u(0) = I$, $u'(0) = V$:

$$[u = I]^0 \quad \Rightarrow \quad u^0 = I$$
$$[D_{2t}u = V]^0 \quad \Rightarrow \quad u^{-1} = u^1 - 2\Delta t V$$

End result:

$$u^1 = u^0 + \Delta t\, V + \frac{\Delta t^2}{2m}(-bV - s(u^0) + F^0)$$

Same formula for u^1 as when using a centered scheme for $u'' + \omega u = 0$.

Linearization via a geometric mean approximation

- $f(u') = bu'|u'|$ leads to a quadratic equation for u^{n+1}

- Instead of solving the quadratic equation, we use a geometric mean approximation

In general, the geometric mean approximation reads

$$(w^2)^n \approx w^{n-\frac{1}{2}}w^{n+\frac{1}{2}} \,.$$

For $|u'|u'$ at t_n:

$$[u'|u'|]^n \approx u'(t_n + \frac{1}{2})|u'(t_n - \frac{1}{2})|.$$

For u' at $t_{n\pm 1/2}$ we use centered difference:

$$u'(t_{n+1/2}) \approx [D_t u]^{n+\frac{1}{2}}, \quad u'(t_{n-1/2}) \approx [D_t u]^{n-\frac{1}{2}}$$

A centered scheme for quadratic damping

After some algebra:

$$u^{n+1} = \left(m + b|u^n - u^{n-1}|\right)^{-1} \times$$
$$\left(2mu^n - mu^{n-1} + bu^n|u^n - u^{n-1}| + \Delta t^2(F^n - s(u^n))\right)$$

Initial condition for quadratic damping

Simply use that $u' = V$ in the scheme when $t = 0$ ($n = 0$):

$$[mD_t D_t u + bV|V| + s(u) = F]^0$$

which gives

$$u^1 = u^0 + \Delta t V + \frac{\Delta t^2}{2m}\left(-bV|V| - s(u^0) + F^0\right)$$

Algorithm

1. $u^0 = I$

2. compute u^1 (formula depends on linear/quadratic damping)

3. for $n = 1, 2, \ldots, N_t - 1$:

   (a) compute u^{n+1} from formula (depends on linear/quadratic damping)

Implementation

```
def solver(I, V, m, b, s, F, dt, T, damping='linear'):
    dt = float(dt); b = float(b); m = float(m) # avoid integer div.
    Nt = int(round(T/dt))
    u = zeros(Nt+1)
    t = linspace(0, Nt*dt, Nt+1)

    u[0] = I
    if damping == 'linear':
```

```
            u[1] = u[0] + dt*V + dt**2/(2*m)*(-b*V - s(u[0]) + F(t[0]))
    elif damping == 'quadratic':
        u[1] = u[0] + dt*V + \
               dt**2/(2*m)*(-b*V*abs(V) - s(u[0]) + F(t[0]))

    for n in range(1, Nt):
        if damping == 'linear':
            u[n+1] = (2*m*u[n] + (b*dt/2 - m)*u[n-1] +
                      dt**2*(F(t[n]) - s(u[n])))/(m + b*dt/2)
        elif damping == 'quadratic':
            u[n+1] = (2*m*u[n] - m*u[n-1] + b*u[n]*abs(u[n] - u[n-1])
                      + dt**2*(F(t[n]) - s(u[n])))/\
                      (m + b*abs(u[n] - u[n-1]))
    return u, t
```

Verification

- Constant solution $u_e = I$ ($V = 0$) fulfills the ODE problem and the discrete equations. Ideal for debugging!

- Linear solution $u_e = Vt + I$ fulfills the ODE problem and the discrete equations.

- Quadratic solution $u_e = bt^2 + Vt + I$ fulfills the ODE problem and the discrete equations with linear damping, but not for quadratic damping. A special discrete source term can allow u_e to also fulfill the discrete equations with quadratic damping.

Demo program

vib.py supports input via the command line:

```
 Terminal> python vib.py --s 'sin(u)' --F '3*cos(4*t)' --c 0.03
```

This results in a moving window following the function on the screen.

Euler-Cromer formulation

We rewrite

$$mu'' + f(u') + s(u) = F(t), \quad u(0) = I, \ u'(0) = V, \ t \in (0, T]$$

as a first-order ODE system

$$u' = v$$
$$v' = m^{-1} \left(F(t) - f(v) - s(u) \right)$$

Staggered grid

- u is unknown at t_n: u^n

- v is unknown at $t_{n+1/2}$: $v^{n+\frac{1}{2}}$

- All derivatives are approximated by centered differences

$$[D_t u = v]^{n-\frac{1}{2}}$$
$$[D_t v = m^{-1} \left(F(t) - f(v) - s(u) \right)]^n$$

Written out,

$$\frac{u^n - u^{n-1}}{\Delta t} = v^{n-\frac{1}{2}}$$

$$\frac{v^{n+\frac{1}{2}} - v^{n-\frac{1}{2}}}{\Delta t} = m^{-1}\left(F^n - f(v^n) - s(u^n)\right)$$

Problem: $f(v^n)$

Linear damping

With $f(v) = bv$, we can use an arithmetic mean for bv^n a la Crank-Nicolson schemes.

$$u^n = u^{n-1} + \Delta t v^{n-\frac{1}{2}},$$

$$v^{n+\frac{1}{2}} = \left(1 + \frac{b}{2m}\Delta t\right)^{-1}\left(v^{n-\frac{1}{2}} + \Delta t m^{-1}\left(F^n - \frac{1}{2}f(v^{n-\frac{1}{2}}) - s(u^n)\right)\right).$$

Quadratic damping

With $f(v) = b|v|v$, we can use a geometric mean

$$b|v^n|v^n \approx b|v^{n-\frac{1}{2}}|v^{n+\frac{1}{2}},$$

resulting in

$$u^n = u^{n-1} + \Delta t v^{n-\frac{1}{2}},$$

$$v^{n+\frac{1}{2}} = (1 + \frac{b}{m}|v^{n-\frac{1}{2}}|\Delta t)^{-1}\left(v^{n-\frac{1}{2}} + \Delta t m^{-1}\left(F^n - s(u^n)\right)\right).$$

Initial conditions

$$u^0 = I$$

$$v^{\frac{1}{2}} = V - \frac{1}{2}\Delta t \omega^2 I$$