

# **Harcom**

**Hardware complexity model for microarchitecture  
exploration**

Pierre Michaud

June 20, 2025



# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
<b>2</b>	<b>Overview of Harcom</b>	<b>7</b>
<b>3</b>	<b>The Harcom language</b>	<b>11</b>
3.1	Harcom data types . . . . .	11
3.1.1	The val type . . . . .	11
3.1.2	The reg type . . . . .	12
3.1.3	The arr type . . . . .	13
3.1.4	The hard type . . . . .	15
3.2	The ram type . . . . .	15
3.3	The rom type . . . . .	16
3.4	Arithmetic and logical operators . . . . .	16
3.5	Free functions . . . . .	16
3.6	The hardware cost of reading values . . . . .	17
3.6.1	The fanout function . . . . .	19
3.6.2	The fo1 function . . . . .	19
3.6.3	The split type . . . . .	19
<b>4</b>	<b>The panel</b>	<b>21</b>
<b>5</b>	<b>The Harcom superuser</b>	<b>23</b>
<b>6</b>	<b>Hardware complexity model</b>	<b>25</b>
6.1	Limitations of the model . . . . .	25
<b>7</b>	<b>Programming tips</b>	<b>27</b>



# Chapter 1

## Introduction

Microarchitecture exploration is generally conducted with performance simulators written in general-purpose programming languages such as C or C++. For example, *gem5* [7, 3] and *ChampSim* [5, 2] are two popular open-source performance simulators. A performance simulation outputs various statistics, such as execution time, number of cache misses, number of branch mispredictions, etc. A performance simulator does not need to simulate all the details of the hardware implementation. It is often sufficient to simulate the events that can impact performance significantly, such as cache misses, branch mispredictions, data dependences, etc. Performance simulators often use approximations and abstractions. This is what allows them to simulate the execution of many instructions in a short amount of time, which is important for estimating millisecond-scale performance and for design space exploration.

People using performance simulators are generally engineers, researchers or students, hereafter referred to collectively as *microarchitects*. In a typical situation, a microarchitect needs to study the effects of modifying a part of the microarchitecture. Performance simulators are easily modifiable to conduct such study. The constraints for modifying the simulator are generally few besides those of the programming language itself (e.g., C++). Microarchitects generally try to achieve their goal with minimal modifications to the simulator, so they are practically constrained by how the simulator is structured and how the part they want to modify communicates with the rest of the simulator. Otherwise, microarchitects can use whatever approximation or abstraction they like. Such flexibility comes with a drawback: there is no guarantee that a modification corresponds to realistic hardware.

In general, microarchitects are aware of hardware constraints and try to simulate realistic mechanisms. Nevertheless, assessing the hardware complexity of a mechanism which only exists as a piece of C++ code in a performance simulator can be difficult. Hardware complexity is a multidimensional quantity including silicon area, energy consumption and delay. A simple, oft-used estimate of hardware complexity is the amount of storage (typically, SRAM capacity) used by a mechanism. Indeed, the silicon area, energy and access latency of an SRAM increases with its size, and a substantial part of the hardware complexity of processors comes from on-chip SRAMs. Still, there is more to hardware complexity than storage. For instance, the delay of a branch predictor depends not only on the size of its SRAMs but also on the logic circuits processing the information retrieved from the SRAMs.

Microarchitects, especially in academia, often use high-level complexity models such as *CACTI* [10, 1] and *McPAT* [6, 4]. These tools are distinct from the performance simulator: the microarchitect must manually configure *CACTI*/*McPAT* to reflect the hardware modification. Moreover, these tools have limited configurability. For instance, the branch predictor modeled in *McPAT* is the one implemented in the Alpha 21264. Modeling a different predictor requires



Figure 1.1: Hardware complexity estimation is off the main microarchitecture exploration loop.

to hack McPAT’s source code.

The most general solution for estimating the hardware complexity of a microarchitectural part is to use a hardware description language (HDL) such as SystemVerilog, write a RTL (Register Transfer Level) description of the part and run EDA (Electronic Design Automation) tools to assess the hardware complexity. However, this is a time-consuming process, and hardware complexity estimation is generally off the main microarchitecture exploration loop (Figure 1.1).

Harcom is not a HDL. The goal is not to synthesize hardware. The purpose of Harcom is to provide a hardware complexity model directly inside the performance simulator. The hope is that Harcom improves the process of selecting solutions to implement in HDL and reduces the burden of designers.

Harcom tries to find a useful middle ground between several contradictory objectives: hardware complexity model accuracy, simulation speed, flexibility and ease of use. This implies tradeoffs that make Harcom’s complexity model a very rough approximation of what a designer can obtain with RTL/EDA. Nevertheless, an approximate model can still be useful if it provides sufficient qualitative accuracy and if the microarchitect understands the sources of error and the model’s limitations.

# Chapter 2

## Overview of Harcom

Harcom is a C++20 library consisting of a single header file ("harcom.hpp"). Most performance simulators today are written in C++, so incorporating Harcom in existing simulators should be straightforward.

Harcom's basic data type is called `val`. A `val` object is declared with a parameter `N` and represents an `N`-bit integer value<sup>1</sup> which can also be viewed merely as a bundle of `N` bits. Listing 2.1 shows a simple C++ program using Harcom's `vals`. Each `val` has a value and a timing in picoseconds which are both printed with the method `print()`. Vals `x` and `y` both have a null timing, as they are initialized from hardwired values, i.e., values known when designing the hardware. However, operations on `vals` generally increase the timing: `val z`, the sum of `x` and `y`, has a timing corresponding to the latency of an 8-bit adder. In the general case, the timing of the result of a two-input operation is the maximum of the timing of the two inputs plus the latency of the hardware operator, as illustrated in Figure 2.1. The function `panel.print()` prints the total number of transistors used and the total energy consumption.

Figure 2.2 illustrates a typical usage of Harcom, where only the part of the performance simulator modeling the processor component that we want to study is rewritten to use Harcom `vals` in place of C++ integers. The rest of the simulator remains unchanged. The outputs of the component are `vals`, whose timing, along with the total number of transistors and total energy consumption, is a measure of the hardware complexity of the component.

Performance simulators sometimes use abstractions that do not correspond to an actual hardware implementation. In order to estimate hardware complexity, Harcom restricts what users can do with `vals`. These constraints can be called the *Harcom language*.

In particular, the actual value of a `val` is a private member of the `val` C++ class: trying to read or write this value directly triggers a compilation error. While C++ makes it possible to circumvent the *private* access specifier if that is the user's intention, this is, hopefully, unlikely

---

<sup>1</sup>Future versions of Harcom might provide floating-point values.




Figure 2.1: The timing of the result of a two-input operation is the maximum of the timing of the two inputs plus the latency of the hardware operator.

Listing 2.1: A simple C++ program using Harcom's vals

---

```

#include "harcom.hpp"
using namespace hcm;

int main()
{
    val<8> x = 1; // 8-bit unsigned integer
    val<4> y = 2; // 4-bit unsigned integer
    auto z = x + y; // 9-bit unsigned integer
    z.print("sum=");
    panel.print();
}

// prints on the standard output:
//   sum=3 (t=42 ps)
//   storage (bits): 0
//   transistors: 406
//   dynamic energy (fJ): 9.04
//   static power (mW): 0.000152

```

---




Figure 2.2: Harcom's typical usage: only the part of the performance simulator modeling the processor component that we want to study is rewritten.



to happen accidentally.

Nevertheless, the outputs of a component modeled with Harcom must be communicated to the rest of the performance simulator as normal C++ integers. Harcom distinguishes the *user* from the *superuser*. The superuser is whoever owns (i.e., is allowed to modify) the class called `harcom_superuser`. While the user is constrained by the Harcom language, the superuser can access private members and is responsible for implementing the interface between the component modeled with Harcom and the rest of the simulator. For example, in the context of a branch prediction championship, the superuser would be the championship's organizers and the user would be a contestant. Otherwise, the user and superuser might be a single person or a group of people willing to use Harcom the way it was intended to be used, as explained in this document.



# Chapter 3

## The Harcom language

The Harcom language is not a proper programming language, it is just C++ programming with Harcom vals. However, there are strong constraints associated with vals, and programming with them can be viewed as a distinct language, with C++ as a metaprogramming language.

Throughout this document, *rightmost* bits refers to the least significant bits of an integer and *leftmost* bits refers to the most significant bits.

### 3.1 Harcom data types

#### 3.1.1 The val type

The val type represents a **transient** value, i.e., a value existing at a certain time, and with a limited lifetime. A val takes two template parameters N and T, where N is the number of bits and T is the underlying C++ **integer** type. For example:

```
val<10,u64> x = 1; // 10 bits; underlying type is std::uint64_t;
val<6,i64> y = -1; // 6 bits; underlying type is std::int64_t;
val<8> z = 1; // equivalent to val<8,u64>
```

Note that u64 and i64 are convenient aliases for std::uint64\_t and std::int64\_t that we use throughout this document.<sup>1</sup> While it is possible to use smaller integer types (int, short,...) to save a little memory, u64 and i64 are sufficient most of the time. If type T is omitted in the declaration, the underlying type is u64 by default (see the example above). The value of N must not exceed type T's number of bits. In any case, N must not exceed 64.

A val must be initialized with a value, which can be a C++ integer literal, a C++ integer variable, another val or a reg (see section 3.1.2). When initializing from another val (or reg), the destination and source vals do not need to have the same size:<sup>2</sup> the value is truncated if the source val is longer than the destination val, it is sign extended if shorter:

```
val<8> x = 0b11111111; // 255
val<4> y = x; // truncated: 0b1111 (15)
val<8> z = y; // sign extended: 0b00001111 (15)
```

**The Harcom user cannot change the value of a val.**<sup>3</sup>

---

<sup>1</sup>They are actually defined in the "harcom.hpp" header file.

<sup>2</sup>They do not need to have the same type either: Harcom uses the same implicit conversions as C++.

<sup>3</sup>Attempting to change the value of a val triggers a compilation error.

name	type	description	example
size	C++ int	number of bits	
maxval	C++ int	maximum value	<code>val&lt;4&gt; x = val&lt;4&gt;::maxval</code>
minval	C++ int	minimum value	<code>val&lt;4,i64&gt; x = val&lt;4,i64&gt;::minval;</code>
print	function	print value	see Section 3.1.1
printb	function	binary printing	see Section 3.1.1
<b>fanout</b>	function	set fanout	<code>val&lt;1&gt; x = 1;</code> <code>x.fanout(hard&lt;4&gt;{});</code>
fo1	function	set fanout of 1	<code>val&lt;3&gt; x = 1;</code> <code>val&lt;3&gt; y = x.fo1() + 1;</code>
make_array	function	make an array from the value bits	<code>val&lt;12&gt; x = 0b101011110011;</code> <code>auto A = x.make_array(val&lt;4&gt;{});</code>
reverse	function	reverse bits	<code>val&lt;8&gt;{43}.reverse().printb();</code>
rotate_left	function	rotate bits	<code>val&lt;8&gt;{43}.rotate_left(-1).printb();</code>
<b>ones</b>	function	bit count	<code>val&lt;8&gt;{43}.ones().print();</code>
<b>one_hot</b>	function	reset all bits but the rightmost 1	<code>val&lt;8&gt;{44}.one_hot().printb();</code>
<b>replicate</b>	function	replicate the value (generate an array)	<code>val&lt;1&gt; x = 1;</code> <code>x.replicate(hard&lt;4&gt;{}).print();</code>

Table 3.1: Public members of class `val` besides constructors. The functions highlighted in red have a non-null hardware cost. Class `reg` inherits the same members.

While the value of a `val` is a private member that the Harcom user should not try to access directly, it is possible to print the value to the standard output, in decimal or binary representation:

```
x.print(); // prints "255 (t=3 ps)"
y.printb(); // prints "1111 (t=6 ps)"
```

Functions `print` and `printb` have default parameters that can be overridden:

```
z.print("z=", "\n", false, std::cerr);
// prints "z=15" to the error stream
```

Table 3.1 lists the public members of class `val` that the Harcom user can access (constructors are omitted). Functions with a non-null hardware cost are highlighted in red.

### 3.1.2 The `reg` type

The `reg` type is derived (in the C++ sense) from the `val` type. A `reg` (for *register*) represents a **persistent** value, i.e., a value that is associated with storage. Unlike a `val`, a `reg` can be modified:

```
reg<4> x = -1; // 4-bit unsigned register, initialized with 15
reg<4,i64> y = x; // 4-bit signed register, initialized with -1
x = 0; // a reg can be modified
```

If a `reg` is not initialized explicitly, it is initialized implicitly with zero. Regs must obey the following two rules:

- **All regs must have the same lifetime.** That is, a `reg` cannot be created after another `reg`

has been destroyed.<sup>4</sup>

- **A reg can be modified at most once per clock cycle.**

Violating these rules triggers an error at execution time. Besides the properties mentioned above, a reg is akin to a val, as illustrated by the example below:

```
auto increment = [] (val<2> &x) -> val<2>
{
    return x+1;
};
reg<2> y = 1;
y = increment(y); // equivalent to y=y+1
y.print();
```

In this document, the term **valtype** refers to both vals and regs.<sup>5</sup> The public members of class val, listed in Table 3.1, are also public members of class reg.

### 3.1.3 The arr type

The arr type represents an array of valtype objects. An arr takes two template parameters T and N, where T is a valtype and N is an unsigned integer:

```
arr<val<3>,4> A = {1,2,3,4};
A[2].print(); // print the third element
arr<val<3>,4> B = [] (u64 i){return i+1;};
arr<reg<1>,4> C = B;
C.print(); // print all the elements
```

The subscript operator [] returns a reference to a particular element (second line). The first element has index 0 (like C arrays).

In the example above, array B is initialized from a C++ lambda (third line). It is sometimes necessary to use a lambda or a function to initialize an array of vals, as vals, unlike regs, cannot be changed after their creation.

Table 3.2 lists the public members of class arr that the Harcom user can access (constructors and operators are omitted). Functions with a non-null hardware cost are highlighted in red. The functions concat, make\_array, shift\_left, shift\_right treat array elements as consecutive chunks of a bit vector. The first array element (index 0) corresponds to the rightmost bits of this bit vector.

The array assignment operator is public. However, if the Harcom user tries to modify an array of vals, this triggers a compilation error. The subscript operator [] already mentioned in Section 3.1.3 takes C++ integers as argument. An array with a single element is implicitly convertible to a val:

```
arr<val<4>,1> A = {10};
val<4> x = A;
```

---

<sup>4</sup>To make sure that this rule is not violated, it is sufficient (but not necessary) to declare all regs as static variables.

<sup>5</sup>The "harcom.hpp" header file defines a C++ concept of that name (static\_assert(valtype<reg<8>>);)

name	type	description	example
size	C++ int	number of elements	
print	function	print all the elements	same syntax as valtype
printb	function	binary printing	same syntax as valtype
<b>select</b>	function	read a selected element	arr<val<2>,4> A = {1,3,0,2}; A.select(A[1]).print();
concat	function	concatenate all bits into single val	arr<val<3>,3> A = {0b000,0b111,0b010}; A.concat().printb();
<b>fanout</b>	function	set fanout	A.fanout(hard<16>{});
fo1	function	set fanout of 1	A.fo1().concat().printb();
append	function	generate array with one extra element	A.append(7).print();
truncate	function	truncate the array	A.truncate(hard<2>{}).print();
make_array	function	concatenate all bits & make new array	arr<val<3>,2> A = {0b000,0b111}; A.make_array(val<2>{}).printb();
shift_left	function	insert bits, shift left	arr<val<3>,2> A = {0b000,0b111}; A.shift_left(val<2>{0b11}).printb();
shift_right	function	insert bits, shift right	arr<val<3>,2> A = {0b000,0b111}; A.shift_right(val<2>{0}).printb();
<b>fold_xor</b>	function	XOR all elements	arr<val<3>,3> A = {0b100,0b110,0b111}; val<3> x = A.fold_xor();
<b>fold_or</b>	function	OR all elements	val<3> x = A.fold_or();
<b>fold_and</b>	function	AND all elements	val<3> x = A.fold_and();
<b>fold_xnor</b>	function	XOR all elements, then complement	val<3> x = A.fold_xnor();
<b>fold_nor</b>	function	OR all elements, then complement	val<3> x = A.fold_nor();
<b>fold_nand</b>	function	AND all elements, then complement	val<3> x = A.fold_nand();
<b>fold_add</b>	function	add all elements	arr<val<3>,3> A = {4,6,7}; val<5> x = A.fold_add();

Table 3.2: Public members of class `arr` besides constructors and operators. The functions highlighted in red have a non-null hardware cost. The functions `concat`, `make_array`, `shift_left`, `shift_right` treat array elements as chunks of a bit vector. The first array element (index 0) corresponds to the rightmost bits of this bit vector.

### 3.1.4 The hard type

The hard type represents hardware parameters, that is, values that are fixed and known. It takes a single template parameter N which is the value of the hardware parameter. That is, object `hard<N>{}` represents value N. For example:

```
val<8> x = -1;
val<8> y = x << hard<4>{}; // shift left by 4 bits
```

In many situations, it is possible to substitute a C++ integer (variable or literal) for a hard parameter:

```
val<8> y = x << 4; // equivalent to y = x << hard<4>{}
```

While convenient, this is not always possible though. For example the modulo operation requires the modulus to be a hard parameter.<sup>6</sup>

```
val<4> x = -1;
auto y = x % hard<4>{};
```

## 3.2 The ram type

The ram type emulates a random access memory (RAM). It takes two template parameters T and N, where T is the type of data stored in the RAM and N is the memory size in number of such data. Type T can be `val` or `array of val`.<sup>7</sup> For example:

```
ram<val<3>,32> mem; // 3-bit data, 32 data
val<5> addr = 10;
val<3> data = 7;
mem.write(addr,data); // RAM write
val<3> readval = mem.read(addr); // RAM read
readval.print(); // prints 7
```

In the Harcom language, the value produced by an operation on vals generally does not depend on the timing of the input vals. That is, the timing of inputs only affects the timing of the output, not the value. However, there is one exception, which is when reading a RAM. Harcom's RAM model assumes that the time at which a write occurs is the maximum of the address and data timings. When reading a RAM at a given address A, the data returned by the read operation is the data written by the most recent write whose timing is less than or equal to the timing of A. In other words, we cannot read a value that will be written in the future. For example:

```
ram<arr<val<64>,2>,1024> mem;
val<10> addr = 100;
arr<val<64>,2> data = {addr,addr+1};
mem.write(addr,data);
mem.read(addr).print(); // prints 0 0
```

The RAM write is effective when the addition operation (`addr+1`) is finished, which happens in the future compared to the RAM read operation. So the RAM read returns the old data, which is zero in this example (the value with which the RAM is automatically initialized).

<sup>6</sup>A compilation error occurs if the modulus is a C++ integer.

<sup>7</sup>T is the type of the data returned by a read operation.

name	description	example
<b>write</b>	<code>write(addr,data)</code> writes data (valtype or arr) at address addr	<code>ram&lt;arr&lt;val&lt;64&gt;,2&gt;,256&gt; mem;</code> <code>val&lt;8&gt; addr = 100;</code> <code>arr&lt;reg&lt;64&gt;,2&gt; data = {1,2};</code> <code>mem.write(addr,data);</code>
<b>read</b>	<code>read(addr)</code> returns the data stored at address addr	<code>data = mem.read(addr+1);</code>
<b>reset</b>	reset the RAM with zeros	<code>mem.reset();</code>
<b>print</b>	prints delay and energy	<code>mem.print();</code>

Table 3.3: Public functions of class `ram`.

**Only a single RAM read and a single RAM write are allowed per clock cycle** (otherwise there is an error at execution).

Public members of class `ram` are listed in Table 3.3.

### 3.3 The rom type

The `rom` type emulates a read-only memory (ROM). It takes two template parameters `T` and `N`, where `T` is a `val` type (the type returned by a ROM read) and `N` is the ROM size in number of such vals. A `rom` object must be initialized at creation:

```
rom<val<3>,16> bitcount = {0,1,1,2,1,2,2,3,1,2,2,3,2,3,3,4};
val<4> bitvec = 7;
bitcount(bitvec).print(); // prints 3
```

The first element has index 0. The ROM is read with operator `()`. Despite the name, a ROM is not a memory but is akin to a function.

ROMs are initialized like arrays. In particular, they can be initialized from a function or a lambda:

```
rom<val<3>,16> bitcount = [](u64 i){return std::popcount(i);};
```

### 3.4 Arithmetic and logical operators

Many operators of the C language can be used with valtypes and have the same meaning as in C. These operators are listed in Table 3.4. Each operator takes one or two valtypes (`val` or `reg`) as input. Some binary operators allow to substitute a single hard value for an input valtype. Some binary operators *require* one of the two inputs to be a hard value. The output of an operator is always a `val`.

### 3.5 Free functions

Table 3.5 lists the free functions that are part of the Harcom language.

The `execute_if` function is an essential primitive allowing conditional execution. It takes two inputs: a valtype `mask` and a C++ lambda `F` that can have a C++ integer parameter `i`. The `execute_if` primitive executes `F(i)` for each `i` corresponding to a mask bit that is set. If `F` returns a `val`, `execute_if` returns an array of vals whose elements corresponding to null mask bits are zeros. For example, `execute_if` can be used to access a RAM conditionally:



operator	operation	input type	output type
==	equal	two vals of same size or one val and one hard	val<1>
!=	not equal		
>	greater than		
<	less than		
>=	greater than or equal		
<=	less than or equal		
&	bitwise AND	two vals or one val and <b>one hard</b>	same as longest of the input vals
	bitwise OR		
^	bitwise XOR		
~	bitwise NOT	one val	same as input
<<	shift left	one val and one hard shift count	same as input val
>>	shift right		
+	add	two vals or one val and one hard	one bit longer than the longest input val
-	subtract		
-	change sign	one val	same as input
*	multiplication	two vals or one val and one hard	val with enough bits ( $\leq 64$ bits)
/	integer division	unsigned val dividend hard divisor	val with enough bits
%	modulo (remainder)		

Table 3.4: Arithmetic/logical operators. Inputs are valtypes or hard values. Outputs are vals. All operators have a hardware cost except <<, **unsigned** >>, and & and | with a **hard** value.

```

ram<val<2>,64> mem;
val<1> cond = false;
val<6> addr = 42;
val<2> data = 3;
execute_if(cond,[&]() {mem.write(addr,data);});
val<2> x = execute_if(cond,[&]() {return mem.read(addr);});
x.print();

```

The functions at the bottom of Table 3.5 are called "utilities" because they are written in the Harcom language. Harcom users could write them themselves, without superuser privilege. Their implementation is located at the end of the "harcom.hpp" file.

## 3.6 The hardware cost of reading values

The Harcom user focuses first on the functional behavior of the microarchitectural algorithm, which is generally independent of timing<sup>8</sup> unless the timing information is used explicitly by the algorithm. Once the algorithm is bug-free and works as expected, the Harcom user tries to reduce the hardware cost.

Reading a val or a reg is associated with a hardware cost, especially a read delay. Harcom does not know at compile time how many times a named value will be read. Therefore, a pessimistic situation is assumed where each read incurs an extra delay, which Harcom models as that of a fanout-of-two (FO2) inverter. The read delay increases linearly with the number of reads.<sup>9</sup> While the delay of a single read can be considered negligible, the accumulation of read

<sup>8</sup>Except for RAM reads, as explained in Section 3.2

<sup>9</sup>This corresponds to chaining FO2 inverters.

name	description	example
<code>a_plus_bc</code>	compute $a + b \times c$	<code>a_plus_bc(a,b,c).print();</code>
<code>concat</code>	concatenate multiple vals into a single val	<code>val&lt;3&gt; left = 0b111; val&lt;4&gt; right = 0b0011; val&lt;7&gt; z = concat(left,right);</code>
<code>select</code>	<code>select(cond,x1,x0)</code> equals <code>x1</code> if <code>cond</code> is true, <code>x0</code> otherwise	<code>val&lt;1&gt; incr = true; val&lt;4&gt; x = 0; val&lt;4&gt; y = select(incr,val&lt;4&gt;{x+1},x);</code>
<code>execute_if</code>	<code>execute_if(mask,F)</code> executes the C++ lambda <code>F</code> for each mask bit that is set	<code>val&lt;4&gt; x = 11; auto pp = execute_if(x, [&amp;](u64 i){return val&lt;8&gt;{x}&lt;&lt;i;}); pp.fold_add().print("x^2=");</code>
<b>utilities</b>		
<code>absolute_value</code>	if signed value is negative, make it positive	<code>val&lt;8,int&gt; x = -3; absolute_value(x).print();</code>
<code>encode</code>	encode a one-hot bit vector	<code>val&lt;8&gt; ask = 0b01000100; val&lt;8&gt; onehot = ask.one_hot(); val&lt;3&gt; index = encode(onehot);</code>
<code>fold</code>	<code>fold(A,op)</code> folds array <code>A</code> with binary associative operation <code>op</code>	<code>auto max = [] (val&lt;4&gt; x, val&lt;4&gt; y) {     return select(x&gt;y,x,y); }; arr&lt;val&lt;4&gt;,4&gt; A = {8,2,13,7}; fold(A,max).print();</code>
<code>scan</code>	<code>scan(A,op)</code> yields the prefix-sum array of array <code>A</code> with binary associative operation <code>op</code>	<code>auto add = [] (val&lt;4&gt; x, val&lt;4&gt; y) {     return x+y; }; arr&lt;val&lt;4&gt;,8&gt; A = [] (){return 1;}; scan(A,add).print();</code>

Table 3.5: Free functions. They all have a hardware cost except `concat`. For `execute_if`, `fold` and `scan`, the hardware cost depends on the function/lambda that is passed as argument.

delays can be quite significant.

In real circuits, a high fanout (i.e., reading the same value many times) means that we must drive a high capacitance, which takes some time. However, with optimal buffering and gate sizing, delay grows roughly logarithmically with fanout [8, 9], not linearly.

### 3.6.1 The fanout function

Reading an unnamed value (aka *rvalue*) incurs no hardware cost, as it is known at compile time that such value will be read only once. However, it is not known at compile time how many times a named value (aka *lvalue*) is read. To make the delay of reading a named value logarithmic instead of linear, the Harcom user must use the fanout function:

```
val<4> x = 1;
x.fanout(hard<8>{}); // make delay logarithmic
arr<val<1>,8> A = x.replicate(hard<8>{});
A.print();
```

If the value is actually read more than what was promised with the fanout function, no error is triggered. Instead, the read delay simply grows linearly after the initial logarithmic growth. Compiling with the option `-DCHECK_FANOUT` forces an error at execution if the actual fanout exceeds the declared one.

### 3.6.2 The fo1 function

To the extent possible, transient values (vals) that are read only once should remain unnamed. Nevertheless, for program readability, the Harcom user may wish to give a name to a val even though it is read only once. In this situation, if the read delay is deemed non-negligible, it is possible to use function fo1 to "unname" a named value:

```
val<4> x = 1;
arr<val<1>,8> A = x.fo1().replicate(hard<8>{});
A.print();
x.print(); // x has been reset!
```

Attempting to apply fo1 to a reg triggers a compilation error (a reg cannot be unnamed).

The fo1 function should be used very cautiously. By using fo1, the programmer promises that the value will not be read again. To make it impossible to obtain an unrealistic advantage from a misuse of fo1, a read through fo1 is destructive, that is, the value is reset.

The compiler option `-DFREE_FANOUT` disables destructive reads and removes all read delays. This option is useful for detecting some misuses of fo1 and for checking whether there is much to gain from optimizing fanouts.

### 3.6.3 The split type

The split type allows to split the bits of a val into two parts without any read penalty:

```
val<8> x = 0b11000100;
split<3,5> y = x.fo1();
y.left.printb(); // 3 bits (0b110)
y.right.printb(); // 5 bits (0b00100)
```

Or, using structured binding (C++17):

```
auto [left,right] = split<3,5>(x.fo1());  
left.printb();  
right.printb();
```

# Chapter 4

## The panel

The *panel* is a global object shared by all the files where "harcom.hpp" is included. The panel contains some global variables that the user can read. For example, the global variable `energy_fJ` gives the total energy (in femtojoules) dissipated so far:

```
val<64> x = 0;
x+1;
panel.energy_fJ.print("val+hard:␣");
f64 e = panel.energy_fJ;
x+x;
std::cout << "val+val:␣" << panel.energy_fJ - e << std::endl;
```

Global variables can be read but cannot be modified by the Harcom user. Only the superuser can modify them. Global variable are implicitly convertible to their C++ underlying type, which is `f64` (i.e., `double`) for `energy_fJ` and `u64` for all the other variables.

Table 4.1 lists the panel variables and functions that the user and the superuser can utilize.

name	type	description	example
clock_cycle_ps	variable	clock cycle (picoseconds)	<code>panel.clock_cycle_ps.print();</code>
cycle	variable	current cycle	<code>panel.cycle.print();</code>
storage	variable	total storage (bits)	<code>panel.storage.print();</code>
storage_sram	variable	total SRAM bits	<code>panel.storage_sram.print();</code>
energy_fJ	variable	total energy (femtojoules)	<code>panel.energy_fJ.print();</code>
storage_xtors	variable	total storage transistors	<code>panel.storage_xtors.print();</code>
logic_xtors[0]	variable	total logic transistors (0 = current cycle; 1 = previous)	<code>panel.logic_xtors[0].print();</code>
logic_xtors[1]	variable		
total_xtors	function	total transistors	<code>u64 x = panel.total_xtors();</code>
dyn_power_mW	function	dynamic power (milliwatt)	<code>f64 p = panel.dyn_power_mW();</code>
sta_power_mW	function	static power (milliwatt)	<code>f64 p = panel.sta_power_mW();</code>
print	function	print total	<code>panel.print();</code>
next_cycle	function	increment cycle	<code>panel.next_cycle();</code>

Table 4.1: Panel variables and functions for the user and the superuser. The user can read variables but cannot modify them. Function `next_cycle` is for the superuser only.

## **Chapter 5**

### **The Harcom superuser**





# **Chapter 6**

## **Hardware complexity model**

### **6.1 Limitations of the model**



## **Chapter 7**

### **Programming tips**



# Bibliography

- [1] CACTI. <https://github.com/HewlettPackard/cacti>.
- [2] ChampSim. <https://github.com/ChampSim/ChampSim>.
- [3] gem5. <https://www.gem5.org/>.
- [4] McPAT. <https://github.com/HewlettPackard/mcpat>.
- [5] N. Guber, G. Chacon, L. Wang, P. V. Gratz, D. A. Jiménez, E. Teran, S. Pugsley, and J. Kim. The Championship Simulator: architectural simulation for education and competition. <https://arxiv.org/abs/2210.14324>, 2022.
- [6] S. Li, J. H. Ahn, R. D. Strong, J. B. Brockman, D. M. Tullsen, and N. P. Jouppi. The McPAT framework for multicore and manycore architectures: simultaneously modeling power, area, and timing. *ACM Transactions on Architecture and Code Optimization*, 10(1), April 2013.
- [7] Jason Lowe-Power, Abdul Mutaal Ahmad, Ayaz Akram, Mohammad Alian, Rico Am-slinger, Matteo Andreozzi, Adrià Armejach, Nils Asmussen, Srikant Bharadwaj, Gabe Black, Gedare Bloom, Bobby R. Bruce, Daniel Rodrigues Carvalho, Jerónimo Castrillón, Lizhong Chen, Nicolas Derumigny, Stephan Diestelhorst, Wendy Elsasser, Marjan Fari-borz, Amin Farmahini Farahani, Pouya Fotouhi, Ryan Gambord, Jayneel Gandhi, Dibakar Gope, Thomas Grass, Bagus Hanindhito, Andreas Hansson, Swapnil Haria, Austin Harris, Timothy Hayes, Adrian Herrera, Matthew Horsnell, Syed Ali Raza Jafri, Radhika Jagtap, Hanhwi Jang, Reiley Jeyapaul, Timothy M. Jones, Matthias Jung, Subash Kan-noth, Hamidreza Khaleghzadeh, Yuetsu Kodama, Tushar Krishna, Tommaso Marinelli, Christian Menard, Andrea Mondelli, Tiago Mück, Omar Naji, Krishnendra Nathella, Hoa Nguyen, Nikos Nikoleris, Lena E. Olson, Marc S. Orr, Binh Pham, Pablo Prieto, Trivikram Reddy, Alec Roelke, Mahyar Samani, Andreas Sandberg, Javier Setoain, Boris Shingarov, Matthew D. Sinclair, Tuan Ta, Rahul Thakur, Giacomo Travaglini, Michael Upton, Nilay Vaish, Ilias Vougioukas, Zhengrong Wang, Norbert Wehn, Christian Weis, David A. Wood, Hongil Yoon, and Éder F. Zulian. The gem5 simulator: Version 20.0+. <https://arxiv.org/abs/2007.03152>, 2020.
- [8] C. Mead and L. Conway. *Introduction to VLSI systems*. Addison-Wesley, 1980.
- [9] I. E. Sutherland, R. F. Sproull, and D. Harris. *Logical effort: designing fast CMOS cir-cuits*. Morgan Kaufmann, 1999.
- [10] S. J. E. Wilton and N. P. Jouppi. CACTI: an enhanced cache access and cycle time model. *IEEE Journal of Solid-State Circuits*, 31(5), May 1996.