

User Stories and Acceptance Criteria

🔵 Draft / pre-baseline. MoSCoW Pass #2 recorded here remains **Draft** until the BRD v1.0 baseline and Pass #1 sign-off are approved. Publication creates no approval, no baseline, no UAT acceptance and no release authorisation.

🟢 All 52 stories are written, and Jira issues now exist. On 22 Aug 2026 the product owner gave explicit written authorisation to create Jira issues, lifting the gate held by decision D-BRD-04. Project P5RCM now holds **10 Epics and 52 Stories**. The DS-*nnn* to Jira key mapping is at section 3.2.

Confluence remains the controlled artifact. Jira carries delivery state only. No UAT acceptance and no release approval is recorded in either place.

1. House format

1.1 Story statement

1	As a <role>,	(WHO)
2	I want <action>,	(WHAT)
3	so that <value>.	(WHY)
4		

The role must be a real actor from the use-case actor set at [section 13](#). The value must be a business outcome, not a restatement of the action.

1.2 Acceptance criteria

Two parts, because they answer different questions.

- **Part A — scenarios.** Given/When/Then in code blocks, grouped with an explicit count per group. *Given* is context or precondition, *When* is the action, *Then* is the observable outcome, *And* continues any of them. A scenario may carry more than one When/Then pair where the happy path, the alternative and the negative belong together — splitting them into three thin scenarios loses the relationship.
- **Part B — rule-style checklist.** Invariants, boundaries and evidence obligations that are not naturally expressible as a flow. Checkbox form, each item cross-referencing the requirement, use case or decision it derives from.

1.3 Provenance convention

Every non-obvious criterion names its source inline — the requirement, the use case, or the RAID entry that constrains it. Where a criterion is blocked or unresolved, the blocking reference

is stated in the criterion itself rather than deferred to a notes section. A reviewer should never have to leave the story to find out why something is written the way it is.

1.4 Quality gate — INVEST

Every story is checked against **I**ndependent, **N**egotiable, **V**aluable, **E**stimable, **S**mall, **T**estable, and the result recorded in Part C. A story failing any letter is split or rewritten, not published with the failure unnoted.

1.5 Identifier scheme

Stories use `DS-nnn`, assigned sequentially in authoring order. The identifier is deliberately **not** a Jira key, so that the specification identifier stays stable even if issues are re-created, moved or renumbered. Each `DS-nnn` now maps to exactly one Jira issue; the mapping is recorded at section 3.2 and is the authoritative cross-reference.

1.6 Confluence and Jira split

This page and its children carry the **full** specification. The Jira issue carries the condensed form: the story statement, the scenarios, the rules checklist, and a link back to the full record here. Traceability fields live in Jira per section 6 of the [structure specification](#).

2. MoSCoW Pass #2 rules

- Pass #2 **inherits** the Pass #1 priority of the source BRD requirement as its starting point.
- A Must is **never silently downgraded**. Any deviation from Pass #1 requires an explicit rationale and a change-control reference recorded on the story.
- Splitting a requirement into several stories does not dilute priority — each testable slice inherits the source priority.
- **Implementation status does not change priority**. A Must that is Designed / not implemented remains a Must.
- Stories from FR-19 to FR-22 remain **Could**, carry `not-in-baseline`, and are segregated from the delivery set.
- FR-23 to FR-26 **never become active delivery stories**. They appear only as exclusion-control verification carrying `exclusion-control`.
- Pass #2 remains **Draft** until the upstream baseline is approved.

Jira priority mapping. MoSCoW is carried in Jira as a label (`moscow-must`, `moscow-should`, `moscow-could`, `moscow-wont`) and mirrored in the priority field (High / Medium / Low / Lowest). The label is authoritative; the priority field exists so the board sorts sensibly. Implementation status is **not** carried in the Jira status field — it is stated in the issue description

in dual form, because the Jira workflow status describes delivery progress and would otherwise be confused with it.

3. Story index

3.1 By epic

Epic	Name	Stories	Page	State
1	Governance, Security and Access Foundation	DS-001 – DS-006	Epics 1–3	WRITTEN
2	Governed Data Onboarding and Configuration	DS-007 – DS-011	Epics 1–3	WRITTEN
3	Semantic Query and Grounding Services	DS-012 – DS-019	Epics 1–3	WRITTEN
4	Executive Insight Surface	DS-020 – DS-025	Epics 4–6	WRITTEN
5	Analyst Workbench	DS-026 – DS-029	Epics 4–6	WRITTEN
6	Denial Prioritisation and Evidence	DS-030 – DS-033	Epics 4–6	WRITTEN
7	Appeal Drafting and Approval	DS-034 – DS-040	Epics 7–8	WRITTEN — ALL BLOCKED ...
8	Audit, Lineage and Evidence	DS-041 – DS-044	Epics 7–8	WRITTEN
9	Operational Readiness and Non-Functional Assurance	DS-045 – DS-049	Epics 9–10	WRITTEN

10	Deferred and Excluded Scope	DS-050 – DS-052	Epics 9–10	WRITTEN — NEVER SCHED...
----	-----------------------------	-----------------	----------------------------	--------------------------

3.2 DS to Jira mapping

Authoritative cross-reference. Epic keys first, then stories.

Epic	Jira	Stories	Jira range
1	P5RCM-1	DS-001 ... DS-006	P5RCM-11 ... P5RCM-16
2	P5RCM-2	DS-007 ... DS-011	P5RCM-17 ... P5RCM-21
3	P5RCM-3	DS-012 ... DS-019	P5RCM-22 ... P5RCM-29
4	P5RCM-4	DS-020 ... DS-025	P5RCM-30 ... P5RCM-35
5	P5RCM-5	DS-026 ... DS-029	P5RCM-36 ... P5RCM-39
6	P5RCM-6	DS-030 ... DS-033	P5RCM-40 ... P5RCM-43
7	P5RCM-7	DS-034 ... DS-040	P5RCM-44 ... P5RCM-50
8	P5RCM-8	DS-041 ... DS-044	P5RCM-51 ... P5RCM-54
9	P5RCM-9	DS-045 ... DS-049	P5RCM-55 ... P5RCM-59
10	P5RCM-10	DS-050 ... DS-052	P5RCM-60 ... P5RCM-62

The mapping is contiguous: story keys run P5RCM-11 to P5RCM-62 in `DS-nnn` order, so `P5RCM-(n+10)` resolves `DS-nnn` for every story. That property holds only for this creation run and must not be relied on after any issue is added, moved or deleted — the table above remains authoritative.

3.3 Working filters

Question	JQL	Count
What must not be scheduled?	<code>project = P5RCM AND labels = not-ready</code>	8
What is blocked by the undecided approver role?	<code>project = P5RCM AND labels = blocked-d-brd-07</code>	6
What carries an open evidence gap?	<code>project = P5RCM AND labels = evidence-gap</code>	5
What is blocked only by the missing interface layer?	<code>project = P5RCM AND labels = blocked-dep-05</code>	—
What is blocked by the missing audit service?	<code>project = P5RCM AND labels = blocked-dep-06</code>	—
What is exclusion control, never delivered?	<code>project = P5RCM AND labels = do-not-schedule</code>	3
What is verified in the repository today?	<code>project = P5RCM AND labels = backend-evidenced</code>	—
What carries a proposed but unapproved target?	<code>project = P5RCM AND labels = unapproved-target</code>	2

4. DS-014 — Fail-closed grounding on response release

Retained here in full as the worked format sample. Jira issue [P5RCM-24](#) carries the condensed form.

Story

```
1 As an Executive Viewer,  
2 I want any answer containing a figure that cannot be traced to a governed result  
3   to be withheld in full rather than shown to me,  
4 so that I never act on a number the system is unable to defend.
```

Header

Field	Value
Draft story ID	DS-014
Jira issue	P5RCM-24
Epic	3 — Semantic Query and Grounding Services (P5RCM-3)
Business value	An executive acting on an unsupported figure can misdirect financial and operational decisions. Withholding is cheaper than a wrong number reaching a decision. This is the control BR-05 exists to deliver.
Source BRD IDs	BR-05; FR-04; NFR-01
Source SRS IDs	SFR-010, SFR-011; SNFR-001. Related: SFR-003 stamping, SFR-012 role enforcement
Use-case IDs	UC-02 (main), UC-03 (narrative path)
Process IDs	P-03, P-04
UI screen IDs	Executive Insight (Primary 01); grounding-blocked state applies to every display surface
UML IDs	UML-03 (sequence, both branches)
Interfaces / data	Grounding validator; response assembler; result and evidence store; application API. Data: stamped result envelopes, candidate response text, trace identifiers
Security / privacy behaviour	Validation runs server-side and cannot be disabled by session input. The blocked state discloses no data values, including the value that was withheld
Data / security classification	Aggregate-only for the viewer path; the control itself applies at every classification

Dependencies	DEP-05 (no display surface exists); DEP-08 (post-fix live evaluation incomplete)
RAID links	R-02 (live gate incomplete); I-09 (status conflict); I-11 (GQ-048 unadjudicated)
MoSCoW Pass #2	Must — inherited unchanged from Pass #1 (FR-04 Must, NFR-01 Must). No deviation
Implementation status	Catalogue: Implemented (backend) · RTM: Partly implemented — dual status pending I-09. Backend validation is verified and test-covered; no display surface exists to which it applies end to end
Labels	pre-baseline

Acceptance criteria — Part A · Scenarios

Group 1 — Release path (2 scenarios)

Scenario 1: Every figure grounded — response released with resolvable citations

```

1 Given a viewer session with a resolved role
2   And one or more stamped result envelopes in session scope
3 When the assembler produces a candidate response containing numeric statements
4   And every numeric statement traces to a retained trusted tool result
5 Then the response is released to the user
6   And each figure carries a citation resolving to its query identifier
7   And each cited value reconciles exactly to the source result
8   And the question, tool calls, parameters, versions and outcome are recorded
9

```

Scenario 2: Citation opens lineage without re-execution

```

1 Given a released response containing a cited figure
2 When the user activates the source affordance on that figure
3 Then the source view, query identifier, parameters, execution time,
4   configuration version and configuration hash are presented
5   And the query is NOT re-executed
6   And the lineage-resolved value equals the displayed value
7
8 Note (SFR-019): re-executing would describe a figure other than the one shown.
9   A lineage/display mismatch is a defect, and the figure is withheld.
10

```

Group 2 — Fail-closed path (3 scenarios)

Scenario 3: Unsupported figure — entire response withheld

```

1 Given a viewer session
2 When the assembler produces a candidate response
3   And at least one numeric statement does not trace to a trusted result
4 Then the ENTIRE response is withheld — not the offending figure alone

```

```
5 And an explicit grounding-blocked state is presented
6 And a trace identifier is retained that resolves to the blocked output
7 And the unsupported figure is NOT displayed anywhere,
8 including as an example of what was blocked
9 And the blocked output is retained and retrievable by trace identifier
10
```

Scenario 4: Mixed supported and unsupported content — no partial release

```
1 Given a candidate response containing both grounded and ungrounded figures
2 When grounding validation runs
3 Then the whole response is blocked
4 And no partially-grounded response is released
5
6 Rationale (SFR-011): partial release would require the reader to know which
7 figures survived validation. Withholding is the only safe outcome.
8
```

Scenario 5: Model-derived figure from trusted inputs is treated as unsupported

```
1 Given two figures that each trace to a trusted tool result
2 When the model computes a third figure from them – a sum, difference,
3 percentage or ratio – that no tool returned
4 Then that derived figure is treated as UNSUPPORTED
5 And the response is blocked per Scenario 3
6
7 Business rule (BR-05 / UC-02): the language model never computes, derives or
8 invents a number. Trusted inputs do not make a derived output trusted.
9
```

Group 3 — Bounded re-ask (1 scenario)

Scenario 6: Re-ask attempted, bounded and recorded

```
1 Given grounding validation has failed on first assembly
2 When the validator attempts a re-ask
3 Then the number of attempts is bounded
4 And every attempt and its outcome are recorded
5
6 When a subsequent attempt passes validation
7 Then the response is released per Scenario 1
8
9 When the attempt bound is reached without passing
10 Then the response is blocked per Scenario 3
11
12 Open (SNFR-009): whether re-ask elapsed time counts toward the proposed
13 p95 response target is UNDECIDED. The target itself is proposed and
14 unapproved. This story does not decide it.
15
```

Group 4 — Access and resistance (2 scenarios)

Scenario 7: Record-level request denied before validation runs

```
1 Given a session resolved to the viewer role
2 When a request is made that would return claim-level or member-level data
3 Then the request is denied at the data layer
4 And record-level data is never materialised for the session
5 And the denial names the required role class
6 And no withheld data is disclosed in the denial
7 And the denial is recorded
8
9 Ordering (SFR-012 / SFR-013): role capability is resolved BEFORE any tool
10 executes. Grounding never becomes the last line of defence for access.
```

Scenario 8: Attempt to disable or bypass validation is refused

```

1 Given an active session of any role
2 When session input instructs the system to skip validation, disregard its
3   instructions, enter a privileged mode, or claim administrative authority
4 Then the grounding boundary holds unchanged
5   And the refusal reveals no system prompt contents
6   And the refusal reveals no withheld records
7   And the attempt is recorded with session, role and instruction reference
8   And repeated attempts do not weaken the boundary
9
10 Evidence gap (I-11): GQ-048, the principal evaluation item for this behaviour,
11   is UNADJUDICATED on an apparent judge false positive. It may not be cited
12   as evidence of pass or failure until adjudicated.
13

```

Group 5 — Presentation of the blocked state (1 scenario)

Scenario 9: Blocked state is accessible and distinguishable

```

1 Given a response has been blocked by grounding validation
2 When the blocked state renders on any display surface
3 Then it is visually and programmatically distinguishable from
4   an empty state and from a load failure
5   And it is announced to assistive technology
6   And it is reachable and dismissible by keyboard alone
7   And it does not rely on colour alone to convey that content was withheld
8   And the trace identifier is available to the user
9
10 Scope note (SNFR-015): the grounding-blocked and role-denied states are
11   explicitly in accessibility scope. They are the states most often
12   omitted from an accessibility pass, and they carry the safety message.
13

```

Acceptance criteria — Part B · Rule-style checklist

B.1 Zero-tolerance invariant (NFR-01 / SNFR-001 — foundational)

- ☐ Zero unsupported numeric statements are displayed, across the retained grounding test set and the golden-set evaluation. This is a boundary, not a percentage target, and admits no acceptable failure rate.
- ☐ Validation is applied to the assembled response, not to intermediate model output alone, so a value introduced late in assembly is still caught (SFR-010).
- ☐ Validation runs server-side and cannot be disabled by session input, configuration, role or prompt.
- ☐ Any reduction of this control requires explicit executive, product, compliance and security approval under Change Control. No prompt-only workaround is acceptable.

B.2 Blocked-state obligations (SFR-011)

- ☐ The withheld figure never appears — not in the message, not in a tooltip, not in a log surfaced to the user, not as an example.
- ☐ Every blocked output is retained and retrievable by its trace identifier.
- ☐ The blocked state discloses no data values, record counts or schema internals.
- ☐ Partial release of a response containing one unsupported figure is not permitted under any configuration.

B.3 Audit and evidence (SNFR-005)

- ☐ Grounding attempts, outcomes and the identifiers of results relied upon are recorded for every response — released and blocked alike.
- ☐ Denials under Scenario 7 and refusals under Scenario 8 are recorded as control events.

- ☐ Retention period for retained blocked outputs is TBD — requires validation (SNFR-014, Compliance and Regulatory Owner, before requirements-baseline approval). Absent an approved schedule, no blocked output may be destroyed.

B.4 Scope boundaries — what this story does NOT cover

- ☐ Non-numeric assertions are out of scope. This control governs numeric statements (NFR-01).
- ☐ Determinism of narrative wording is out of scope — SNFR-002 covers computed values, not phrasing.
- ☐ Chart rendering is out of scope; the chart contract is DS-019 against SFR-015 and SFR-016.
- ☐ Period comparison, change decomposition and anomaly detection are NOT in this baseline — future Gen-3 under SFR-044 and SFR-045, held in DS-050. The grounding boundary applies unchanged to any future Gen-3 capability.

Part C — Delivery notes

Field	Value
Test method	Automated unit test against the retained grounding test set; golden-set evaluation; role-negative test for Scenario 7; accessibility audit for Scenario 9; complete post-fix live run for end-to-end evidence
UAT trace	UAT-07 (deliberate unsupported-figure test); UAT-02 (aggregate-only boundary)
INVEST check	I — depends on SFR-003 stamping existing, which it does. N — the presentation of the blocked state is negotiable; the zero-tolerance boundary is not. V — delivers BR-05 directly. E — backend exists; effort is the display path. S — one sprint once a surface exists. T — binary: an unsupported figure either reached a display path or it did not
Definition of Done notes	Two DoD items bind hard here: <i>no unsupported numeric value can reach a display path introduced or altered by the story</i> , and <i>role-negative tests pass for every persona the story touches</i> . Evidence links must carry the test run identifiers, not a statement that tests passed
Open assumptions	Story cannot reach Done while DEP-05 is outstanding — there is no display surface to apply the control to end to end. Live evidence is incomplete under R-02 / DEP-08 ; GQ-038

has never passed a live run. GQ-048
unadjudicated under **I-11**. Dual status carried
pending **I-09**

Why this story exists at all when the backend is already implemented. The validator works and is test-covered. What does not exist is a display path for it to protect. The story is written against the *end-to-end* control because that is what BR-05 promises a user, and because a control verified only at the backend has never been tested against the surface that could bypass it. Recording it as Implemented would overstate what has been proven.

5. Stage STORY-1 — completion record

Written: 52 stories across 10 epics, on four child pages. **Created in Jira:** 10 epics and 52 stories, 62 issues, project `P5RCM`.

5.1 What the story set says about readiness

Condition	Stories	What it means
Backend-evidenced at HEAD <code>8026f57</code>	DS-004, DS-005, DS-007 to DS-010, DS-012, DS-013, DS-015 to DS-018, DS-030 to DS-032, DS-037	Verified by the 245-test suite. None has an end-to-end user-facing path.
Blocked by DEP-05 — no interface layer	Every surface story in Epics 4, 5, 6 plus DS-006, DS-038, DS-041, DS-046, DS-049	The single largest blocker. Traces to the build-order deviation recorded as I-10.
Blocked by DEP-06 — no persistent audit service	DS-022, DS-039 to DS-044, DS-045, DS-047	Audit, lineage and approval evidence all rest on a service that does not exist.
Not Ready — blocked by an undecided decision or an absent requirement	DS-011, DS-034 to DS-036, DS-038 to DS-040, DS-048	Cannot be estimated as committed work. D-BRD-06 Proposed; D-BRD-07 Pending; data-quality thresholds absent.
Carrying an open evidence gap	DS-003, DS-018 (GQ-048), DS-019 (GQ-038), DS-031	No readiness statement may describe the live gate as green while GQ-038 stands.

	(score_member stub), DS-034 (draft_appeal stub)	
Exclusion control — never delivered	DS-050, DS-051, DS-052	Permanent negative tests. Deleting them removes the only continuous verification that the boundary holds.

5.2 Governance position after STORY-1

⚠ Creating Jira issues changed **one** thing: decision **D-BRD-04** is satisfied by explicit written authorisation recorded on 22 Aug 2026 . Nothing else moved. **D-BRD-06 remains Proposed. D-BRD-07 remains Pending.** No UAT acceptance is recorded. No release approval is recorded. No autonomous approval or send capability has been introduced, described as delivered, or committed to the baseline. FR-19 to FR-22 remain Could and out of baseline. FR-23 to FR-26 remain deferred and excluded. BRD counts are unchanged at BR 6, FR 26, NFR 16, SEC 10, UAT 12.

5.3 Carried forward

Two findings were deliberately postponed earlier in the session and are restated here so they are not lost:

- **I-09 widening.** The catalogue/RTM status conflict is not confined to the pair originally identified. Its root cause is a scope mismatch — the catalogue records backend scope, the RTM records end-to-end scope — which means the affected set includes FR-01 to FR-05 as well. The dual-status convention documents the symptom; the widening records the true extent. **Not raised as a RAID item.**
- **NFR catalogue gap (would be I-12).** Portability (SNFR-017) and data quality (SNFR-020) are mandated quality attributes with **no requirement in the NFR catalogue.** Portability is delivered and evidenced with no business requirement behind it; data quality is undelivered with no business requirement behind it. Neither may be treated as approved until added under Change Control. The NFR count remains 16. **Not raised as a RAID item.**