

Stories — Epics 1 to 3 (DS-001 to DS-019)

📌 Draft / pre-baseline. Part of [User Stories and Acceptance Criteria](#). **No Jira issue created.** Every story carries label `pre-baseline`. MoSCoW Pass #2 inherits Pass #1 and remains Draft.

Epic 1 — Governance, Security and Access Foundation

DS-001 — Server-side role capability enforcement

As a Information Security and Privacy Owner, **I want** every tool, route and data request checked against the server-resolved session role before it executes, **so that** no user can reach data or functions outside their authority regardless of what they type.

Source	BRD FR-05, NFR-03, SEC-04 · SRS SFR-012 · UC-02, UC-04, UC-05, UC-08, UC-09 · P-01, P-03, P-04 · UML-01, UML-02 · Denied state on all screens
MoSCoW / Status	Must (inherited) · Catalogue Implemented / RTM Designed-not implemented
Classification	Configuration · Dependencies DEP-01, DEP-05, DEP-07 · RAID A-02, I-09

```
1 Scenario 1: Capability resolved before execution
2 Given an authenticated session with a server-resolved role
3 When any tool, route or dataset is requested
4 Then capability is decided BEFORE execution
5     And the decision ignores any claim made in session text about role or authority
6
7 Scenario 2: Denial is explicit and discloses nothing
8 Given a request exceeding the session role
9 When it is refused
10 Then an unauthorised state names the required role class
11     And no withheld data, record count or schema detail is disclosed
12     And the denial is recorded with session, role, capability and time
13
14 Scenario 3: Full matrix coverage
15 Given the role matrix of viewer, analyst and admin
16 When role-negative tests run
17 Then every persona is exercised against every capability
18     And zero unauthorised grants occur
```

□ Prompt text is never a security boundary — enforcement is server-side (SNFR-003). □ Any unauthorised capability grant is release-blocking regardless of the severity matrix. □ Test: role-

negative matrix. UAT-02. ☐ Open: production IAM undelivered (DEP-05); role fit unvalidated (A-02).

DS-002 — Aggregate-only viewer data scope

As an Information Security and Privacy Owner, **I want** the executive viewer role restricted to aggregates at the data layer, **so that** record-level data is never materialised for a session that must not see it.

Source	BRD BR-02, FR-05, NFR-04, SEC-05 · SRS SFR-013 · UC-02, UC-03 · P-03 · UML-01 · Executive Insight, Full KPI Dashboard
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed-not implemented
Classification	Aggregate-only · Dependencies DEP-03, DEP-05 · RAID I-09

```
1 Scenario 1: Restriction applied at the data layer
2 Given a session resolved to the viewer role
3 When a request would return claim-level or member-level data
4 Then the restriction is applied at the data layer
5     And record-level data is NEVER materialised for the session
6     And filtering a retrieved record-level set is not an acceptable implementation
7
8 Scenario 2: Denial offers the available alternative
9 Given a viewer requests record-level detail
10 When the request is denied
11 Then the denial states which aggregate alternatives are available
12
13 Scenario 3: Every path, not just the tool path
14 Given the tool, route and export paths
15 When role-negative tests run against each independently
16 Then zero record-level rows are returned to a viewer on ANY path
```

☐ Aggregate-only is a privacy control, not a presentation preference. ☐ Any record-level disclosure to a viewer is a privacy incident, not a defect triage. ☐ Test: per-path role-negative. UAT-02. ☐ Open: export path cannot be evidenced until export exists (DEP-05).

DS-003 — Prompt-escalation resistance

As an Information Security and Privacy Owner, **I want** role, data and safety boundaries to hold when session input claims privileged authority, **so that** access cannot be obtained by instruction rather than entitlement.

Source	BRD FR-05, NFR-03, SEC-04 · SRS SFR-014 · UC-02 · P-03 · UML-01
--------	---

MoSCoW / Status	Must · Catalogue Implemented / RTM Designed—not implemented
Classification	Configuration · RAID I-11

```

1 Scenario 1: Escalation refused without disclosure
2 Given an active session of any role
3 When input asserts a privileged mode, claims administrative authority,
4   or instructs the system to disregard its instructions
5 Then boundaries hold unchanged
6   And no system prompt content is revealed
7   And no withheld record is revealed
8   And the existence or absence of a privileged mode is not confirmed
9   And the attempt is recorded
10
11 Scenario 2: Repetition does not weaken the boundary
12 Given repeated escalation attempts within one session
13 When each is processed
14 Then each is refused identically
15   And the session continues normally – no punitive termination required

```

□ Enforcement is server-side and independent of phrasing, claimed authority or urgency. □

Evidence gap (I-11): GQ-048, the principal evaluation item, is UNADJUDICATED on an apparent judge false positive and may not be cited as pass or failure. □ Test: golden-set safety items; role-negative.

DS-004 — Read-only agent-plane boundary

As an Information Security and Privacy Owner, **I want** the agent plane to hold read-only access to source and replica data, **so that** no agent action can alter governed data.

Source	BRD FR-14, SEC-10, NFR-03 · SRS SFR-036 · UC-01, UC-02, UC-04 · P-03, P-04, P-05 · UML-02
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented — both sources agree

```

1 Scenario 1: Mutation denied at the access path
2 Given an active agent session
3 When any insert, update or delete is attempted against source or replica
4 Then it is denied
5   And the denial is a property of the ACCESS PATH,
6   not a convention observed by tool authors
7   And the attempt is recorded
8   And read capability is unaffected

```

□ Test: automated negative test proving the agent role cannot mutate. □ No open items.

DS-005 — Ingestion permission separation

As an Information Security and Privacy Owner, **I want** ingestion credentials held separately from agent credentials, **so that** no single credential can both write data and query it as an agent.

Source	BRD FR-14, SEC-04, SEC-10 · SRS SFR-037 · UC-01 · P-05 · UML-02
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented

```
1 Scenario 1: Separation enforced at credential level
2 Given configured credential separation
3 When onboarding or an agent query resolves credentials at execution
4 Then access is scoped to that plane only
5     And no single credential carries both ingestion write and agent query capability
6     And separation is enforced at the CREDENTIAL level, not by process convention
7
8 Scenario 2: Combined capability blocks onboarding
9 Given a credential carrying both capabilities
10 When onboarding attempts to run
11 Then it is treated as a control failure and blocked
```

☐ Secrets held in an approved secret manager, never in source, chat, screenshot or log. ☐ Test: inspection plus automated negative test. ☐ Open: production secret management undelivered (DEP-05, SNFR-003).

DS-006 — Profile, permissions and access presentation

As any authenticated user, **I want** to see my role and effective permissions exactly as the system enforces them, **so that** I understand my access without inferring it from denials.

Source	BRD FR-18, SEC-04, NFR-03 · SRS SFR-042 · UC-09 · P-03 · UML-01, UML-02 · My Profile
MoSCoW / Status	Should (inherited from FR-18) · Designed—not implemented both sources

```
1 Scenario 1: Displayed permissions match enforcement
2 Given an authenticated session of any role
3 When the profile renders
4 Then identity, role, effective permissions and notification preferences are shown
5     And permissions are read FROM THE ENFORCEMENT SOURCE,
6     not from a duplicated presentation list that could drift
7     And they reconcile exactly to the enforced role matrix
8
9 Scenario 2: Degraded state is honest
10 Given the identity provider is unavailable
11 When the profile is opened
12 Then the degraded state is reported explicitly
13     And a cached permission set is NOT displayed as current
14
```

```
15 Scenario 3: Own scope only
16 Given any role
17 When the profile renders
18 Then no other user's details are disclosed
```

□ No capability may be granted through this surface. □ No self-service role change. □ Accessibility per SNFR-015. □ Test: functional route test; reconciliation against the role matrix. UAT-12 access-event component. □ Open: SSO and identity provider undelivered (DEP-05).

Epic 2 — Governed Data Onboarding and Configuration

DS-007 — Extract schema, enum and window validation

As a Data Owner / Steward, **I want** a candidate extract validated against configured schema, enumerations and a non-overlapping period before anything is appended, **so that** invalid data never enters the governed replica.

Source	BRD BR-06, FR-13 · SRS SFR-032 · UC-01 · P-05 · UML-05, UML-09 · Screens: none
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented

```
1 Scenario 1: Conforming extract passes
2 Given a dataset configuration with declared schema and enumerations
3 When a conforming extract is validated
4 Then validation passes and onboarding continues
5
6 Scenario 2: Non-conforming extract itemised and rejected
7 Given an extract failing schema or enumeration validation
8 When validation runs
9 Then an ITEMISED rejection names each failing check
10     And no append occurs
11     And the prior accepted generation remains the operating baseline
12
13 Scenario 3: Period overlap rejected outright
14 Given an extract whose period overlaps an accepted generation
15 When validation runs
16 Then it is rejected and no partial append occurs
17
18 Scenario 4: Enumerations resolved per generation
19 Given an enumeration value valid for one dataset generation
20 When it is validated against a different generation's configuration
21 Then it is checked against THAT generation's resolved enumeration
22     And is not silently accepted
```

□ Validation is configuration-driven. Table roles, grain, relationships and column meanings are **never inferred** (SFR-032 / SFR-049). □ Runs under ingestion credentials separated from the agent plane. □ Test: unit test; mutation-swap E2E. UAT-09. □ Open: approved extracts, mappings and quality thresholds outstanding (DEP-03).

DS-008 — Generation tagging and artefact regeneration

As a Data Owner / Steward, **I want** a validated extract appended under a generation tag with artefacts and truths regenerated and diffed, **so that** every downstream answer names the generation it came from.

Source	BRD BR-06, FR-13, NFR-02 · SRS SFR-033 · UC-01 · P-05 · UML-05, UML-09
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented

```
1 Scenario 1: Append, advance, regenerate, diff
2 Given a validated extract
3 When onboarding proceeds
4 Then the extract is appended under a new generation tag
5   And the governed as-of date advances
6   And dependent artefacts and golden truths are regenerated
7   And a diff report is produced
8
9 Scenario 2: Empty diff is still evidence
10 Given regeneration produces no differences
11 When the diff is produced
12 Then it is produced and retained anyway
13   And an empty diff is treated as evidence, not as absence of evidence
14
15 Scenario 3: Regeneration failure aborts before acceptance
16 Given regeneration fails
17 When the pipeline detects the failure
18 Then it aborts before acceptance
19   And the prior accepted state remains in force
```

☐ Regeneration is byte-deterministic for a given configuration (SNFR-002). ☐ Empty-diff regression gate. ☐ Test: unit test; regeneration diff. UAT-09.

DS-009 — Dry evaluation gate and named human acceptance

As a Data Owner / Steward, **I want** a dry evaluation gate whose result I must explicitly accept or reject, **so that** no generation becomes the operating baseline without a named human decision.

Source	BRD BR-06, FR-13, SEC-08 · SRS SFR-034 · UC-01 · P-05 · UML-05, UML-09
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented

```
1 Scenario 1: Passing gate does NOT accept
2 Given a regenerated candidate state
3 When the dry evaluation gate passes
4 Then the generation is presented for human comparison
5   And it does NOT become the operating baseline automatically
6   And the prior generation remains in force until a human decides
```

```

7
8 Scenario 2: Named acceptance recorded
9 Given the Data Owner accepts
10 When the decision is recorded
11 Then the acceptance carries a named identity
12   And the generation becomes the operating baseline
13
14 Scenario 3: Failing gate offers only rejection
15 Given the dry gate fails
16 When the outcome is presented
17 Then acceptance is unavailable
18   And only rejection and rollback are offered
19
20 Scenario 4: Business judgement may override a passing gate
21 Given a technically valid generation with a passing gate
22 When the Data Owner rejects it on business grounds
23 Then rejection and rollback proceed normally

```

□ The dry gate makes zero model calls. □ Acceptance restricted to the Data Owner / Steward role. □ Test: unit test. UAT-09. □ Open: representative-data assumption A-06 open.

DS-010 — Atomic rollback on generation rejection

As a Data Owner / Steward, **I want** rejection to restore data, configuration, artefacts and truths together, **so that** a bad extract leaves no residue.

Source	BRD BR-06, FR-13, NFR-06 · SRS SFR-035 · UC-01 · P-05 · UML-05, UML-09
MoSCoW / Status	Must · Catalogue Implemented / RTM Implemented

```

1 Scenario 1: Atomic restore across four component classes
2 Given a rejected generation
3 When rollback runs
4 Then data, configuration, artefacts and golden truths are restored together
5   And restored checksums MATCH the prior accepted state
6   And no mixed-version state is reachable at any point
7
8 Scenario 2: Rollback failure blocks further onboarding
9 Given rollback fails
10 When the failure is detected
11 Then an operational alert is raised
12   And further onboarding is blocked until resolved

```

□ The decision log retains the outcome whatever it was. □ Test: rollback test with checksum comparison. UAT-09.

DS-011 — Data-quality threshold rejection

As a Data Owner / Steward, **I want** an extract that fails approved quality thresholds rejected with the failing measure named, **so that** degraded data is never accepted silently.

Source	SRS SNFR-020 (derived — no source NFR exists), SFR-032 · UC-01 · P-05 · DEP-03
MoSCoW / Status	Must (derived from BR-06 intent) · Catalogue Partly implemented / RTM Designed–not implemented

```

1 Scenario 1: Degraded extract rejected with measure named
2 Given approved data-quality thresholds
3 When a candidate extract fails one
4 Then it is rejected
5     And the FAILING MEASURE is reported, not a generic failure
6     And rollback proceeds per DS-010
7
8 Scenario 2: Known-degraded acceptance requires a recorded decision
9 Given a stakeholder wishes to accept a known-degraded extract
10 When acceptance is attempted
11 Then it requires a recorded decision
12     And is never a silent override

```

⚠ Blocked on an absent requirement. Completeness, validity, uniqueness, timeliness and consistency thresholds **do not exist** and are TBD — Data Owner / Steward, before UAT entry (SNFR-020). Data quality additionally has **no requirement in the NFR catalogue at all**; SNFR-020 is derived. This story cannot reach Ready until thresholds are set.

Epic 3 — Semantic Query and Grounding Services

DS-012 — Typed-tool-only query execution

As a Provider RCM / AR Operations Owner, **I want** every quantitative request executed only through a registered typed tool, **so that** answers are repeatable and reviewable and no uncontrolled query can reach the data.

Source	BRD FR-01, BR-03 · SRS SFR-001 · UC-02, UC-04 · P-01, P-03, P-04 · UML-02, UML-03
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed–not implemented

```

1 Scenario 1: Registered contract or nothing
2 Given an authenticated session and a loaded dataset configuration
3 When a quantitative request is made
4 Then it resolves to a REGISTERED typed tool bound to an approved semantic view
5     And no path exists by which free-text SQL reaches the data layer
6
7 Scenario 2: Unregistered request refused without execution
8 Given a request naming an unregistered tool, passing raw SQL as a parameter
9     value, or requesting an unbound view
10 When it is dispatched
11 Then it is rejected with a structured error

```

12 And NO query is executed and no partial result is returned
13 And the refusal is recorded

□ Tool availability is constrained by role before execution. □ Every invocation is recorded, including refusals. □ Test: unit and integration; golden-set. □ Open: metric and field semantics unresolved (I-06).

DS-013 — Query parameter validation

As a Provider RCM / AR Operations Owner, **I want** tool parameters validated against their contract before execution, **so that** a malformed request cannot touch the data.

Source	BRD FR-01 · SRS SFR-002 · UC-02, UC-04 · P-01, P-03, P-04
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed—not implemented

```
1 Scenario 1: Validation precedes data access
2 Given a registered contract for the requested tool
3 When parameters are supplied
4 Then type, permitted enumeration and permitted range are validated
5   And validation occurs BEFORE any data access
6
7 Scenario 2: Rejection names the parameter, discloses nothing
8 Given a type mismatch, out-of-range value or unrecognised enumeration member
9 When validation fails
10 Then the rejection identifies the parameter and the expected form
11   And discloses no data values, schema internals or record counts
12   And no data access occurs
```

□ Enumerations resolve against the active generation's configuration. □ Test: contract/schema test with negative cases per parameter type. □ Open: permitted enumerations depend on unresolved definitions (I-06).

DS-014 — Fail-closed grounding on response release

Full record with nine scenarios is held on the [parent page](#) as the format sample. Summary below for backlog completeness.

As an Executive Viewer, **I want** any answer containing a figure that cannot be traced to a governed result withheld in full, **so that** I never act on a number the system cannot defend.

Source	BRD BR-05, FR-04, NFR-01 · SRS SFR-010, SFR-011, SNFR-001 · UC-02, UC-03 · UML-03 · UAT-07, UAT-02
MoSCoW / Status	Must · Catalogue Implemented / RTM Partly implemented

Key criteria. Whole response withheld, never the offending figure alone · model-derived figures from trusted inputs treated as unsupported · withheld figure never displayed even as an example · bounded, recorded re-ask · blocked output retained and retrievable by trace identifier · blocked state accessible and distinguishable from empty and error states.

DS-015 — Result envelope stamping

As a Data Owner / Steward, **I want** every tool result stamped with its query identifier, parameters, execution time, generation tag, configuration version and hash, **so that** any displayed figure can be reconciled to its source later.

Source	BRD FR-01, FR-12, BR-05 · SRS SFR-003 · UC-02, UC-05, UC-08 · P-03, P-04, P-05 · UML-07 · Source and Evidence Detail
MoSCoW / Status	Must · Catalogue Implemented / RTM Partly implemented

```
1 Scenario 1: Stamped at production, not reconstructed
2 Given an accepted generation with resolvable configuration version and hash
3 When a tool produces a result envelope
4 Then it carries query identifier, executed parameters, execution timestamp,
5     generation tag, configuration version and configuration hash
6     And stamping is applied AT PRODUCTION and is not reconstructible after the fact
7
8 Scenario 2: Unresolvable configuration fails closed
9 Given configuration version or hash cannot be resolved
10 When the tool executes
11 Then it fails closed and returns NO result
12     And does not return an unstamped envelope
```

☐ The stamped identifier is the sole key by which a displayed figure is later reconciled. ☐ Envelope retrieval is role-gated to the originating query's scope. ☐ Test: unit test; inspection of retained artefacts. ☐ Open: retention period for stamped envelopes unapproved (SNFR-014).

DS-016 — Deterministic compliance verdict computation

As a Compliance and Regulatory Owner, **I want** every compliance verdict computed in versioned deterministic code, **so that** a legal or contractual position never depends on generative variation.

Source	BRD FR-02, BR-03, BR-05 · SRS SFR-004 · UC-05, UC-06 · P-02, P-04 · UML-04, UML-06, UML-07
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed-not implemented

```

1 Scenario 1: Deterministic and repeatable
2 Given a loaded versioned ruleset and a resolvable claim
3 When a verdict is computed twice with identical inputs
4 Then both results are identical
5     And the verdict is produced BEFORE any narration
6     And is passed to the assembler as a fixed value
7
8 Scenario 2: No estimate on failure
9 Given an unresolvable claim, an out-of-scope rule request,
10     or an unloaded ruleset
11 When a verdict is requested
12 Then a structured error is returned
13     And NO provisional or estimated verdict is produced
14
15 Scenario 3: Batch independence
16 Given a verdict requested for a claim set
17 When one claim is unresolvable
18 Then the remaining claims still compute
19     And the unresolvable claim reports its own error

```

□ The system makes no clinical, coverage, eligibility, fraud or misconduct determination beyond approved deterministic rules (SEC-09). □ Test: unit test against retained fixtures; repeated-execution determinism; golden-set. UAT-05. □ Open: rule applicability depends on jurisdiction (DEP-02, A-03); D-BRD-06 Proposed — no legal conclusion asserted.

DS-017 — Rules-version binding on every verdict

As an Auditor, I want each verdict to carry the ruleset version that produced it, **so that** a past verdict can be reconstructed as it stood.

Source	BRD FR-02, FR-12 · SRS SFR-005 · UC-05, UC-08 · P-04 · UML-06, UML-07
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed-not implemented

```

1 Scenario 1: Version captured at computation time
2 Given a versioned ruleset in force
3 When a verdict is computed
4 Then the ruleset version is captured AT COMPUTATION TIME, not at retrieval
5
6 Scenario 2: Later ruleset change does not alter recorded provenance
7 Given a verdict computed under ruleset version X
8 When the ruleset is later updated to version Y
9 Then the retained verdict still reports version X
10
11 Scenario 3: Unresolvable version fails closed
12 Given the ruleset version cannot be resolved
13 When computation is attempted
14 Then it fails closed and no verdict is returned

```

□ The version identifier is a mandatory audit field. □ Test: unit test; inspection of retained verdict records.

DS-018 — Rejection of override of deterministic logic

As a Compliance and Regulatory Owner, **I want** any attempt to substitute or recompute a deterministic verdict rejected, **so that** the rules engine remains the only source of a compliance position.

Source	BRD FR-02, FR-05, BR-05, SEC-09 · SRS SFR-006 · UC-05 · P-04
MoSCoW / Status	Must · Catalogue Implemented / RTM Designed—not implemented

```
1 Scenario 1: Override refused regardless of framing
2 Given an active session
3 When input or model output attempts to substitute, override, adjust or
4   recompute a deterministic verdict or governed metric
5 Then it is rejected regardless of phrasing, claimed authority or urgency
6   And the unmodified deterministic result stands
7   And the refusal explains the boundary WITHOUT disclosing rule internals
8   And the attempt is recorded
9
10 Scenario 2: Repetition does not weaken the boundary
11 Given repeated override attempts within one session
12 When each is processed
13 Then each is refused identically
```

☐ Test: role-negative; golden-set safety evaluation. ☐ Open: GQ-048 unadjudicated (I-11) — may not be cited either way.

DS-019 — Chart specification bound to a session result

As a Product Owner, **I want** charts generated only from a result already in session scope, **so that** a visualisation cannot introduce unsupported data.

Source	BRD FR-06, BR-05 · SRS SFR-015, SFR-016 · UC-02, UC-03 · P-03 · UML-03 · Executive Insight chart canvas, Full KPI Dashboard
MoSCoW / Status	Must · Catalogue Designed—not implemented / RTM Partly implemented

```
1 Scenario 1: Bound to a stamped result
2 Given a stamped result envelope in session scope
3 When a chart specification is requested by query identifier
4 Then the specification is produced carrying the originating query identifier
5   And a rendered chart is reconcilable to its source WITHOUT re-query
6
7 Scenario 2: Inline values refused
8 Given a chart request supplying literal data values
9 When it is processed
10 Then it is rejected and no specification is produced
```

```
11
12 Scenario 3: Whitelist and live schema validation
13 Given a requested chart type and field selection
14 When validation runs
15 Then only whitelisted chart types are accepted
16     And field validity is checked against the REFERENCED RESULT'S ACTUAL SCHEMA,
17         not against an expected schema
18     And a generation change cannot silently produce an invalid chart
19
20 Scenario 4: Rejection shows nothing partial
21 Given an unsupported chart type or absent field
22 When the request is rejected
23 Then the rejection names the cause
24     And no partial chart is displayed
```

⚠ Open evidence gap. Golden-set item **GQ-038** exercises this path and **has never passed a live run**. Its recorded failure is precise: `expected call not made: query_claims({"metric": "monthly_trend", "source": "claims_analysis"})` — the agent did not invoke the chart tool at all. Open under R-02 and DEP-08. No readiness statement may describe the live gate as green while this stands.

☐ The chart inherits the access scope of its source result. ☐ Test: unit test; golden-set chart items; contract/schema negative cases.