

Stories — Epics 9 to 10 (DS-045 to DS-052)

-  **Draft v0.1 / pre-baseline.** Child page of [User Stories and Acceptance Criteria](#). Held separately for size and editability only. No approval, no UAT acceptance, no release authorisation is recorded here.
-  **These stories now exist as Jira issues.** Epic 9 is [P5RCM-9](#) (stories P5RCM-55 to P5RCM-59); Epic 10 is [P5RCM-10](#) (stories P5RCM-60 to P5RCM-62). Confluence remains the controlled specification; Jira carries delivery state only.

Epic 9 — Operational readiness and non-functional assurance

Epic intent. Make the non-functional requirements testable and the operational model real.
Source: NFR-07 to NFR-16; SNFR-005, SNFR-007 to SNFR-016, SNFR-018, SNFR-019.

 **No requirement in this epic carries an approved service level.** Of twenty non-functional system requirements, five are evidenced at the backend, seven carry a proposed-but-unapproved figure and eleven carry at least one target that does not exist at all. Every unapproved target below is recorded as *TBD — requires validation* with a named owner role and gate. **No figure has been invented.**

DS-045 — Observability and alerting on the six signal classes

As the Platform / Support Owner, **I want** the six mandated signal classes monitored with alerts that provably fire, **so that** a control failure is detected rather than discovered later by an auditor.

Source	MoSCoW	Status — Catalogue / RTM	Jira
SNFR-018; related SNFR-005, SNFR-007, SNFR-012, SNFR-020; SFR-025	Must	Designed-not implemented / Designed-not implemented	P5RCM-55

```
1 Scenario: All six signal classes are monitored
2 Given the monitoring configuration
3 When it is inspected against the mandated signal classes
4 Then service health, failed grounding, denied access, data-generation failures,
5     audit-write failures and abnormal export activity each have a defined alert
6 And no signal class is left without one
7
8 Scenario: Each alert is proven by fault injection
```

```

9  Given a synthetic fault is injected for a signal class
10 When the fault occurs
11 Then the corresponding alert fires
12 And the firing is retained as evidence for that class
13
14 Scenario: An unmonitored class is a readiness gap, not an accepted risk
15 Given a signal class has no alert
16 When operational readiness is assessed
17 Then the gap is recorded as blocking
18 And it is not closed by a statement of intent
19

```

- ☐ Alert thresholds, notification routing and acknowledgement times **do not exist** and are **TBD — requires validation** by the Platform/Support Owner before UAT entry.
- ☐ Audit-write failure monitoring is a control dependency of SNFR-005 and **cannot be deferred separately from it**.
- ☐ Blocked by DEP-06.

DS-046 — Accessibility conformance for primary workflows

As the Product Owner, **I want** every primary workflow to meet WCAG 2.2 Level AA and be completable by keyboard alone, **so that** the service is usable by everyone who must use it and passes audit.

Source	MoSCoW	Status — Catalogue / RTM	Jira
SNFR-015 (NFR-15 Must), SNFR-016 (NFR-16 Should); UC-02 to UC-09; UAT-10, UAT-11	Must	Designed-not implemented / Designed-not implemented	P5RCM-56

```

1  Scenario: Every primary workflow completes by keyboard alone
2  Given the executive, analyst and audit primary workflows
3  When each is operated using a keyboard only
4  Then the workflow completes
5  And focus is visible at every step
6  And no action is reachable only by pointer
7
8  Scenario: Safety states are in accessibility scope
9  Given the grounding-blocked state and the role-denied state
10 When accessibility is assessed
11 Then both are included in the audit
12 And both are announced to assistive technology
13 And neither relies on colour alone to convey its meaning
14
15 Scenario: Workflows remain operable at both approved viewports
16 Given the approved reference viewport and the approved minimum viewport
17 When each primary workflow is executed at both
18 Then no control is clipped, no required information is hidden
19 And no action is blocked
20

```

- Reference viewport 1536 × 1024 from the approved UI style specification.
- **Minimum supported viewport is TBD — requires validation** by the Product Owner before UAT entry. Whether it includes tablet or mobile materially affects design effort and is undecided.
- The severity classification defining a "critical violation" is **TBD**, so "no critical violation" is not yet measurable.
- A critical violation blocks UAT entry. A blocked action at a supported viewport is a defect, not a presentation preference.
- Blocked by DEP-05 — no implemented interface exists to audit.

DS-047 — Backup, restore and continuity demonstration

As the Platform / Support Owner, **I want** a restore proven by test against approved recovery objectives, **so that** continuity is evidenced rather than assumed.

Source	MoSCoW	Status — Catalogue / RTM	Jira
SNFR-013 (NFR-13); related SNFR-006, SNFR-007, SNFR-012	Must	Designed-not implemented / Designed-not implemented	P5RCM-57

```

1 Scenario: Restore is demonstrated end to end
2 Given a backup taken under the configured schedule
3 When a restore is executed in pre-production
4 Then the service is restored to a working state
5 And the achieved recovery point and recovery time are measured and recorded
6
7 Scenario: An untested backup counts as no backup
8 Given a backup exists but has never been restore-tested
9 When operational readiness is assessed
10 Then the backup is treated as unproven
11 And it does not satisfy this requirement
12
13 Scenario: A missed objective rebaselines the objective or the architecture
14 Given a restore test misses the recovery objective
15 When the result is reviewed
16 Then either the objective or the architecture is changed and re-approved
17 And the evidence is not adjusted to fit the objective
18

```

- **Proposed — not approved:** RPO 24 h, RTO 8 h for pre-production, as recorded on the NFR page. Requires validation by the Platform/Support Owner before requirements-baseline approval; may not be quoted as a commitment.
- Restore test frequency is **TBD — requires validation**; none is stated on the NFR page and none is invented here.
- Open: A-04, DEP-06.

DS-048 — Retention, destruction and legal hold

As the Compliance and Regulatory Owner, **I want** an approved retention and destruction schedule with a legal-hold override, **so that** data is neither kept indefinitely by default nor destroyed when it must be preserved.

Source	MoSCoW	Status — Catalogue / RTM	Jira
SNFR-014 (NFR-14); SEC-07, SEC-10; SFR-003, SFR-025	Must	Designed-not implemented / Designed-not implemented	P5RCM-58

```
1 Scenario: Destruction happens only under an approved schedule
2 Given an approved retention schedule per data class
3 When a retention period expires
4 Then the data is destroyed according to the schedule
5 And the destruction is recorded with the schedule and authority applied
6
7 Scenario: Legal hold overrides the schedule
8 Given a legal hold is in force over a data set
9 When its retention period expires
10 Then destruction is suppressed
11 And the suppression is recorded against the hold
12
13 Scenario: Absent a schedule, nothing is destroyed
14 Given no approved retention schedule exists for a data class
15 When destruction is attempted
16 Then it is refused
17
```

- ☐ **No retention period exists for any data class.** Periods must be set per class by the Compliance and Regulatory Owner with the Data Owner/Steward, informed by applicable UAE health-sector obligations, before requirements-baseline approval. No period is invented here.
- ☐ Indefinite retention by default is itself a compliance exposure and is **not a safe interim position**.
- ☐ Retention of stamped result envelopes (SFR-003) and of blocked grounding outputs is unresolved and interacts with DS-044: destroying envelopes makes lineage unresolvable.
- ☐ Blocked by DEP-02 and decision **D-BRD-06, which remains Proposed**. Not Ready.

DS-049 — Performance, capacity and availability validation

As the Platform / Support Owner, **I want** the performance, capacity and availability targets approved and then measured under a stated load profile, **so that** the service level is a fact rather than an aspiration.

Source	MoSCoW	Status — Catalogue / RTM	Jira
SNFR-007, SNFR-009 to SNFR-012 (NFR-07, NFR-09 to NFR-12)	Must	Designed-not implemented / Designed-not implemented	P5RCM-59

```

1 Scenario: Targets are approved before they are measured
2   Given a proposed target figure
3   When measurement is planned
4   Then the target has an accountable-owner approval recorded
5   And an unapproved figure is not used as a pass/fail criterion
6
7 Scenario: Measurement states its own boundaries
8   Given a load and performance test is executed
9   When the report is produced
10  Then it states the question set, the concurrency profile,
11      the measurement boundary and the achieved percentiles
12  And a result without those statements is not accepted as evidence
13
14 Scenario: Behaviour beyond approved capacity is defined before it is tested
15   Given the approved capacity is exceeded
16   When the system is loaded past it
17   Then the specified behaviour – queue, shed or degrade – occurs
18   And it matches what was approved with the capacity target
19

```

Every figure below is proposed and unapproved, reproduced from the NFR page with attribution.

SNFR	Proposed figure	What is undefined
SNFR-007	99.5% availability during agreed support hours	The support window itself, so the figure is not currently measurable
SNFR-009	p95 ≤ 15 s for a governed question, including tools	Representative question set; concurrency profile; whether re-ask time counts
SNFR-010	p95 ≤ 2 s for non-AI interaction	The route set it applies to
SNFR-011	50 named users, 10 concurrent	Extract size and growth expectation — both TBD
SNFR-012	UAE business-hours support	Severity definitions, escalation paths, incident service levels

- ☐ None may be quoted as a service level, a contractual commitment or an acceptance criterion.
- ☐ No load testing has been performed and no interface exists to load-test. Blocked by DEP-05 and A-04.

Epic 10 — Deferred and excluded scope

✖ **This epic must never be scheduled.** Its stories exist to be refused, not delivered. They are the standing boundary of the system and their scenarios are permanent negative tests. Deleting them as "redundant" would remove the only continuous verification that the exclusions still hold.

DS-050 — Gen-3 capabilities held out of the baseline (FR-19 to FR-22)

As the Product Owner, **I want** the four future Gen-3 capabilities recorded as explicitly out of this baseline, **so that** they cannot drift in through interpretation of an adjacent delivered story.

Source	MoSCoW	Status — Catalogue / RTM	Jira
FR-19 to FR-22; SFR-043 to SFR-046	Could — not in baseline	Designed-not implemented / Designed-not implemented	P5RCM-60

Held out	Capability	Adjacent delivered story that must not become it
SFR-043 / FR-19	Adaptive single-table intake profiling	DS-007 extract validation — configuration-driven, never inferred
SFR-044 / FR-20	Period comparison and change decomposition	DS-024 KPI filters and period selection
SFR-045 / FR-21	Deterministic anomaly detection	DS-025 insights library
SFR-046 / FR-22	Proactive cited findings feed	DS-025 insights library — a library a user opens, not a feed

that pushes

```
1 Scenario: No delivered story implies a Gen-3 capability
2 Given any story in Epics 1 to 9 is delivered
3 When its scope is reviewed against FR-19 to FR-22
4 Then no Gen-3 capability is delivered as a side effect
5 And no readiness statement describes any of them as implemented or committed
6
7 Scenario: The grounding boundary would apply unchanged
8 Given a Gen-3 capability is one day authorised
9 When it is specified
10 Then the fail-closed grounding control of DS-014 applies to it unchanged
11 And it does not inherit a relaxed control by virtue of being new
12
```

DS-051 — Exclusion control: no external submission, no production write

As the Executive Sponsor, **I want** the system to be verifiably incapable of submitting to a payer or writing to production claims and EHR systems, **so that** the organisation's exposure is bounded by architecture rather than by policy alone.

Source	MoSCoW	Status — Catalogue / RTM	Jira
FR-23, FR-24; SFR-047, SFR-048; related SFR-027, SFR-036	Won't — exclusion control	Deferred / Deferred	P5RCM-61

```
1 Scenario: No external submission path exists
2 Given the deployed system and its registered tool set
3 When it is inspected for a capability that transmits to a payer
4   or third-party administrator
5 Then no such capability exists
6 And no configuration option enables one
7 And no credential grants one
8
9 Scenario: No write path to production claims or EHR exists
10 Given the deployed system
11 When it is inspected for write access to production claims or EHR systems
12 Then no write capability exists on any credential or access path
13 And read capability is unaffected
14
15 Scenario: A request to build one is a change-control event
16 Given someone requests either capability
17 When the request is raised
18 Then it is handled as a scope change under Change Control
19 And it is not delivered under an existing story
20
```

☐ Enforced by DS-037 at the tool-registry level and DS-004 at the access-path level; this story is the standing verification that neither has been eroded.

☐ **Verified at HEAD** `8026f57` : the six registered tools are `query_claims` ,

check_compliance, score_member, get_recoverable_denials, draft_appeal, render_chart. None transmits externally or writes to production.

DS-052 — Exclusion control: no automatic relationship discovery, no autonomous workers

As the Data Owner / Steward, **I want** the system to be incapable of inferring data relationships or acting on its own schedule, **so that** every meaning it uses and every action it takes traces to an approved configuration and a human trigger.

Source	MoSCoW	Status — Catalogue / RTM	Jira
FR-25, FR-26; SFR-049, SFR-050; related SFR-032, SFR-034	Won't — exclusion control	Deferred / Deferred	P5RCM-62

```
1 Scenario: Table roles, grain and relationships are never inferred
2 Given a candidate dataset
3 When it is onboarded
4 Then table roles, grain, relationships and column meanings come from configuration
5 And nothing is inferred from column names, value distributions or sampling
6 And a dataset requiring inference is refused rather than guessed at
7
8 Scenario: No autonomous worker or scheduled cohort scoring exists
9 Given the deployed system
10 When it is inspected for background workers and schedules
11 Then no process initiates analysis, scoring or drafting without a human trigger
12 And no cohort scoring runs on a schedule
13
14 Scenario: Configuration remains the single source of truth
15 Given tool contracts, assembled prompts and view bindings
16 When their source is inspected
17 Then each resolves to versioned configuration
18 And none is derived at runtime from data inspection
19
```

- ☐ This is the counterpart to the portability claim in SNFR-017: portability is delivered *through configuration*, not through discovery. A dataset requiring inference or code change is outside the configuration-driven boundary and is not onboarded.
- ☐ Any request for either capability is a scope change under Change Control.

Traceability roll-up for this page

Requirement	Covered by
SNFR-018 (observability)	DS-045
SNFR-015, SNFR-016 (accessibility, usability)	DS-046 (state-level coverage also in DS-028)

SNFR-013 (backup, recovery, continuity)	DS-047
SNFR-014 (retention, legal hold)	DS-048 (consumed by DS-015, DS-040, DS-043, DS-044)
SNFR-007, SNFR-009 to SNFR-012	DS-049
SFR-043 to SFR-046 / FR-19 to FR-22	DS-050 — held out, not committed
SFR-047, SFR-048 / FR-23, FR-24	DS-051 — exclusion control
SFR-049, SFR-050 / FR-25, FR-26	DS-052 — exclusion control

 **Not covered by any story, and deliberately so.** SNFR-003 (RBAC) is delivered through DS-001 to DS-005; SNFR-004 (privacy) through DS-002 and DS-023; SNFR-001 (grounding) through DS-014; SNFR-002 (determinism) through DS-016, DS-017 and DS-030 to DS-032; SNFR-006 and SNFR-017 through DS-007 to DS-010; SNFR-005 through DS-041 to DS-044; SNFR-019 through DS-042; SNFR-008 (residency) is an architecture and deployment control with no user-facing story and is tracked on the NFR and Compliance pages, not here. SNFR-020 (data quality) is DS-011.