

Name: AMRITANSU SINGH AMRITANSU SINGH | Reg. No: RA2511003011028

Unit “ 1 : Session “ 4 : SLO “ 2 | Implementation of Structures Using Pointers “ Fill in the Blanks

■ I. Fill in the Blanks

1. * (asterisk) “ a structure pointer is declared using the * operator: struct S *ptr;
2. -> (arrow) “ the arrow operator is used to access members via a pointer.
3. the address “ a structure pointer stores the address of a structure variable.
4. &var “ ptr = &var; assigns the address.
5. direct (efficient member) “ pointers enable direct access to the structure's members without copying.
6. allocated (initialized) “ memory for the pointed structure must be allocated before use.
7. in-place (permanent) “ passing a pointer to a function lets it modify the original structure.
8. ptr->member “ (*ptr).member is the same as ptr->member.
9. structure (data) “ pointers reduce structure copying overhead.
10. malloc “ dynamic allocation: ptr = malloc(sizeof(struct S));
11. size (amount of memory) “ sizeof(struct) ensures the correct allocation size.
12. freed “ unused structure pointers' memory should be freed.
13. dynamic “ pointers enable dynamic structures like linked lists.
14. dangling pointers (undefined behavior) “ always initialize to NULL or a valid address.
15. member access (the dot) “ the arrow operator combines dereference and member access.