

FINAL 10 FACTORS - QUICK REFERENCE

THE DECISION

Use 10 factors. NOT 5, NOT 6, NOT 15+. Exactly 10.

THE 10 FACTORS (In Order of Importance)

TIER 1: MUST INCLUDE (3 factors)

1. **pH (3.0 - 9.0)** - Effect: 30-40% capacity variance - Why: Largest single effect, controls mechanism - Reason to include: Bell curve (optimal at 6.5) - Can't skip: No, 100% of papers test this
 2. **Initial Concentration C (1 - 10 mg/L)** - Effect: 20-50% (Langmuir isotherm) - Why: Defines equilibrium relationship - Reason to include: Shows saturation behavior - Can't skip: No, fundamental to adsorption
 3. **Contact Time (10 - 120 minutes)** - Effect: 70% at 30 min → 95% at 120 min - Why: Biggest gap in Langmuir (assumes instant equilibrium) - Reason to include: Shows kinetic approach to equilibrium - Can't skip: No, this is what ML learns to correct
-

TIER 2: HIGH PRIORITY (4 factors)

4. **Adsorbent Dose (0.5 - 5.0 g/L)** - Effect: 30-40% linear increase - Why: Practical design - how much adsorbent needed? - Reason to include: Interactions with pH and time are non-linear - Added vs 5-factor: Yes (now possible with unlimited compute)
 5. **Temperature (20 - 40°C)** - Effect: 5-10% per 20°C (Arrhenius exponential) - Why: Validates thermodynamic model - Reason to include: Real groundwater varies seasonally - Added vs 5-factor: Yes (validates E_a)
 6. **Flow Rate (0.5 - 2.0 L/min)** - Effect: 20-30% efficiency change - Why: Critical for column operation - Reason to include: Inverse with residence time - Added vs 5-factor: No (already in 5-factor)
 7. **Competing Anions - Chloride (0 - 100 mg/L)** - Effect: 15-30% capacity reduction - Why: Real groundwater has chloride - Reason to include: Bridge to field applicability - Added vs 5-factor: Yes (real water chemistry)
-

TIER 3: REAL-WORLD RELEVANCE (3 factors)

8. **Water Hardness (0 - 500 mg/L as CaCO₃)** - Effect: 5-15% capacity reduction - Why: Divalent cations (Ca²⁺, Mg²⁺) compete - Reason to include: Every groundwater has hardness - Added vs 5-factor: Yes (universal in water)
9. **Carbonate Concentration (0 - 100 mg/L HCO₃⁻)** - Effect: 20-30% reduction at high concentrations - Why: STRONGEST competing anion - Reason to include: Carbonate-rich regions

have major issues - Added vs 5-factor: Yes (geochemical importance)

10. Natural Organic Matter - Humic Acid (0 - 50 mg/L) - Effect: 10-20% through surface fouling - Why: Real water degrades performance - Reason to include: Shows long-term practical performance - Added vs 5-factor: Yes (fouling mechanism)

WHY NOT THE OTHERS?

TIER 3 FACTORS NOT INCLUDED

Particle Size - Fixed by adsorbent preparation, can't vary during experiment **Adsorbent Type** - You chose coconut husk; that's a material selection, not a process variable **Pre-treatment Method** - Fixed by synthesis (KOH vs H₂SO₄ activation) **Surface Area (BET)** - Measured property, not varied, redundant **Ionic Strength** - Redundant with Cl⁻ + Hardness + CO₃²⁻ testing **pH Buffer Capacity** - Already controlled in your protocol **Agitation/Mixing** - Redundant with flow rate in column model

TIER 4 FACTORS NOT INCLUDED (Zero or Negligible Effect)

Dissolved Oxygen - Fluoride is not redox-active, zero effect **Pressure** - No effect at practical atmospheric pressures **Light Exposure** - Coconut AC not photocatalytic **Vessel Material** - Negligible (<1%) effect **Storage Time** - Not a process variable, handled by using fresh adsorbent **Gravity, Centrifugation, Water Source, etc.** - Either irrelevant or out of scope

NUMBERS

Metric	Value
Total Factors	10
Design Type	Box-Behnken
Experimental Runs	180-220
Expected R ² (Hybrid)	0.94-0.96
RMSE Improvement	20-35% vs Langmuir
Timeline	4 weeks
ML Features	12-15 engineered
Overfitting Risk	Low
Interpretability	High
Field Applicability	High

MECHANISTIC COVERAGE

Tier 1 (3 factors): What Langmuir misses most - pH effect (bell curve) - Concentration relationship (saturation) - Time kinetics (approach to equilibrium)

Tier 2 (4 factors): Major process variables - Dose (site availability) - Temperature (kinetic rate & equilibrium) - Flow (residence time) - Chloride (anion competition)

Tier 3 (3 factors): Real-world complexity - Hardness (cation competition) - Carbonate (pH buffering + competition) - NOM (fouling/degradation)

WHY NOT MORE?

Why not 15+ factors? 1. Overfitting: 15 factors = 1000+ interactions, only 250 samples 2. Curse of dimensionality: Sparse data, ML learns noise 3. Material properties: Can't vary without separate studies 4. Simulation: Becomes full geochemical model, loses simplicity 5. Scope creep: Becomes "universal calculator" not "hybrid validation"

Why not fewer? 1. 5 factors: Only covers Tier 1-2, no real water chemistry 2. 6 factors: Still pure water, missing competing ions 3. 9 factors: Missing fouling mechanism (NOM)

Why exactly 10? - Covers all major mechanistic gaps - Includes real-world complexity (ions + fouling) - Avoids overfitting (10 factors, 200 samples = good ratio) - Still interpretable (can explain each factor) - 4-week timeline (balanced scope) - Field-applicable (handles actual groundwater) - Publishable (focused, coherent story)

THE DECISION PROCESS

1. **Started with 5 factors** (safe, conservative)
 2. **You said unlimited compute available** → opened expansion
 3. **Analyzed ALL 30 testable factors** → ranked by importance
 4. **Identified material properties vs process variables** → eliminated fixed ones
 5. **Avoided overfitting limit** → capped at 10
 6. **Added real-world relevance** → included ions + fouling
 7. **Final decision: 10 factors** ← THIS IS IT
-

NEXT STEPS

Step 1: Generate Box-Behnken Design Matrix (10 factors)

- Create 180-220 run experimental matrix
- Scales to physical units
- Ready for simulation

Step 2: Physics-Based Simulation

- Run Langmuir + mechanisms for each condition
- Generate synthetic dataset
- Incorporate measurement noise

Step 3: Langmuir Model Fitting

- Fit chemical model to 200 samples
- Get R^2 0.85-0.87

- Calculate residuals

Step 4: ML Training

- Train on residuals
- Learn corrections (pH, time, interactions)
- Cross-validate

Step 5: Hybrid Integration

- Combine Langmuir + ML corrections
- Achieve $R^2 = 0.94$
- 20-35% RMSE improvement

Step 6: Validation & Deployment

- Create Streamlit dashboard
- Visualize response surfaces
- Document findings

FINAL ANSWER TO ORIGINAL QUESTION

“Are 5 factors enough?”

Original answer: Yes, 5 is optimal (if compute-limited)

With unlimited compute: No, use 10 instead - 5 factors: Only academic validation - 10 factors: Field-deployable model

Why 10 specifically? - 9 would miss fouling (NOM) - 11+ starts overfitting - 10 is the Goldilocks zone

DECISION STATUS: FINAL

Ready to generate Box-Behnken design for 10 factors.

Proceed to Step 1 when ready.