Posted on 13.08.2025 @ 2:30 pm and due on 14.08.2025 @ 5:45 pm

- 1. Use the iterative equation  $x_{i+1} = c x_i (1 x_i)$  to generate 1,000 random numbers. Show the correlation among them by plotting  $x_i$  vs  $x_{i+k}$ . Use seed  $x_0 = 0.1$  but choose your own five different c. Try various k, say 3, 5 and 10. [5]
- 2. Write your own LCG random generator with the following set of parameters  $a=1103515245,\, c=12345,\, m=32768$  and again check for correlation by plotting for k=5. You must store your LCG code in the library file for all future use till Endsem. [5]
- 3. Determine the value of  $\pi$  using throwing method by choosing a quarter circle of unit radius in the first quadrant. Plot the value of  $\pi$  versus number of throws  $20 \le N \le 2,000$ . [5]
- 4. Generate pRNG having exponential distribution of the form  $\exp(-x)$  from pRNG having uniform distribution in [0,1). Generate at least 5,000 random numbers [5]

```
import matplotlib.pyplot as plt
import numpy as np
from mylib import *

# Generate random data for the histogram
myrand01=[]

for in range(N):
        myrand=(foat)mylib.lcg()/(float)m
        myrand01.append(myrand)

# Plotting a basic histogram
plt.hist(myrand, bins=40, color='skyblue', edgecolor='black')

# Display the plot
plt.show()
```