

Student 3 **AMRUTHA YAZHINI A** 192320026RD

2 / 2 submitted

Level 3 — 25 marks/question

L3-Q1. Root (H)

c

CODE

```
#include<stdio.h>
#include<math.h>

void findRoots(double a,double b,double c){
    double d,root1,root2;
    d=b*b-4*a*c;

    if(d>0){
        root1 = (-b+sqrt(d))/(2*a);
        root2 = (-b-sqrt(d))/(2*a);
        printf("Roots of the quadratic equation are %.2f and %.2f",root1,root2);
    }
    else if(d==0){
        root1 = -b/(2*a);
        printf("Roots of the quadratic equation are %.2f and %.2f",root1,root1);
    }
    else{
        printf("Roots are imaginary");
    }
}

int main(){
    double a,b,c;
    scanf("%lf%lf%lf",&a,&b,&c);

    findRoots(a,b,c);

    return 0;
}
```

INPUT

1 -3 2

OUTPUT

Roots of the quadratic equation are 2.00 and 1.00

L3-Q2. swap (H)**C****CODE**

```
#include<stdio.h>

void swap(int *a,int *b){
    int temp;
    temp = *a;
    *a = *b;
    *b = temp;
}

int main(){
    int a,b;

    scanf("%d%d",&a,&b);

    swap(&a,&b);
    printf("After swapping, a = %d, b = %d",a,b);

    return 0;
}
```

INPUT

3 5

OUTPUT

After swapping, a = 5, b = 3