Text Data in Economics Warwick QAPEC Summer School


10. Some Extras about Recent NLP

Outline


The Transformer Architecture

Advanced NLP Tasks

Bias in NLP Systems




Input sequence → word embedding




- ▶ Input sequence of tokens $\{w_1, ..., w_i, ..., w_{n_L}\}$
- ▶ Trainable embedding vectors $[x_1...,x_i...x_{n_L}]$

 $\dots \rightarrow \mathsf{document} \ \mathsf{embedding} \rightarrow \mathsf{sentiment} \ \mathsf{score}$



- ightharpoonup output sequence $\{h_1^y,...,h_i^y,...,h_{n_l}^y\}$
- ightharpoonup averaged to produce **document vector** \vec{d}
- final output layer with sigmoid activation to produce probabilities \hat{y} across positive and negative output classes.

 $\dots \rightarrow \mathsf{position} \; \mathsf{embedding} \rightarrow \dots$



Position Embeddings


- ► To add word order information, transformers add a **position embedding** along with the **word embedding** as input to the attention layer.
- input to transformer block is

$$h^0 = \begin{bmatrix} x_1 & \dots & x_i & \dots & x_{n_L} \\ t_1 & \dots & t_i & \dots & t_{n_I} \end{bmatrix}$$


which includes

- word embeddings $\{x_1,...,x_i,...,x_{n_l}\}$ with dimension n_E
- **>** stacked with $\{t_1, ..., t_{i_l}, ..., t_{n_l}\}$, learnable categorical embeddings with dimension n_t for each index number i itself.
- Note:
 - puts a hard limit on sequence lengths
 - Positional encodings (or any direct information on word order) often not necessary after all (Irie et al 2019; Schlag et al 2021, Sinha et al 2021).


 $\dots \rightarrow \mathsf{transformer} \; \mathsf{blocks} \rightarrow \dots$



A transformer consists of stacked transformer blocks




Transformer block (input and output)



▶ Each transformer block $l \in \{0,...,n_y\}$ takes as input a sequence of vectors $h'_{1:n_L}$ and outputs a sequence of vectors $h'_{1:n_L}$, which become the input for the next transformer block.

Transformer Block (Self-Attention Layer)




the "self attention" layer:


- ▶ input:
 - ightharpoonup for the first block, includes the word embeddings and position embeddings h^0
 - ▶ for the later blocks, includes the output of the previous block h^I
- output:
 - matrix of self-attention-transformed vectors where item i is

$$\sum_{i=1}^{n_L} a(h_i^l, h_j^l) h_j^l$$

The Transformer Block (Dense Layers)



- self-attention layer's outputs are normalized
 - ▶ we will come back to residual connections (blue line with ⊕) and "layer normalization" next week.
- piped to a multi-layer perceptron (MLP) with two hidden layers, with ReLU activation after the first layer.
- **normalized** again then output to h^{l+1} :
 - \triangleright either to the next transformer block, or to the output layer h^{n_y} .



will get state-of-the-art performance, and much faster to train than a bidirectional LSTM.

Outline


The Transformer Architecture

Advanced NLP Tasks

Bias in NLP Systems

Interpreting Black Box Text Classifiers using LIME

- 1. Generate new texts by randomly *removing* words from the original document.
- 2. Form predictions \hat{y} from black box model for these perturbed documents.
- 3. Train lasso on dataset of binary features for each word, equaling one if word appears, to predict \hat{y} .
 - weight by proximity to initial data point (one minus the proportion of words dropped)



Extractive summarization:

- create the summary from phrases or sentences in the source document(s)
- e.g. MemSum (Gu et al, ACL 2022) is a light-weight reinforcement-learning model that scores sentences and then stops summarizing based on the extraction history.

Extractive summarization:

- create the summary from phrases or sentences in the source document(s)
- e.g. MemSum (Gu et al, ACL 2022) is a light-weight reinforcement-learning model that scores sentences and then stops summarizing based on the extraction history.

Abstractive summarization:

- express the ideas in the source documents using (at least in part) different words
- e.g., fine-tune **Big Bird Pegasus** to reconstruct provided summaries.

Open Question Answering and Claim Verification

Perhaps the most difficult global semantics tasks:

- ► Open question answering:
 - Answer any question.
 - "What are the responsibilities of the mayor of Zurich?"
- Open claim verification:
 - Check whether a plain-text claim is true or false.
 - ▶ "Zurich has the second-highest per-capita income of any city in Europe."

Open Question Answering and Claim Verification

Perhaps the most difficult global semantics tasks:

- ► Open question answering:
 - Answer any question.
 - "What are the responsibilities of the mayor of Zurich?"
- Open claim verification:
 - Check whether a plain-text claim is true or false.
 - "Zurich has the second-highest per-capita income of any city in Europe."
- ▶ Both problems are solved using information retrieval pipelines:
 - search large corpora or knowledge graphs for evidence
 - use evidence to answer the question or check the claim

Outline

The Transformer Architecture

Advanced NLP Tasks

Bias in NLP Systems

Bias in NLP Systems

Sentiment Analysis


```
text_to_sentiment("Let's go get Italian food")
2.0429166109
text_to_sentiment("Let's go get Chinese food")
1.4094033658
text_to_sentiment("Let's go get Mexican food")
0.3880198556
text to sentiment("My name is Emily")
2.2286179365
text to sentiment("My name is Heather")
1.3976291151
text to sentiment("My name is Yvette")
0.9846380213
text_to_sentiment("My name is Shaniqua")
-0.4704813178
```

Is this sentiment model racist?

Source: Kareem Carr slides.

Bias in NLP Systems

Toxicity Detection



	Within dataset proportions				
7			% false identification		
W17	Group	Acc.	None	Offensive	Hate
DWMW17	AAE White Overall	94.3 87.5 91.4	1.1 7.9 2.9	46.3 9.0 17.9	0.8 3.8 2.3
	% false identification				
FDCL18	Group	Acc.	None	Abusive	Hateful
	AAE White Overall	81.4 82.7 81.4	4.2 30.5 20.9	26.0 4.5 6.6	1.7 0.8 0.8

Is this toxicity detection model racist?


Source: Jacobs and Wallach slides.

NLP "Bias" is statistical bias

➤ Sentiment scores that are trained on annotated datasets also learn from the correlated non-sentiment information.


NLP "Bias" is statistical bias

➤ Sentiment scores that are trained on annotated datasets also learn from the correlated non-sentiment information.




- Supervised sentiment models are confounded by correlated language factors.
 - e.g., in the training set maybe people complain about Mexican food more often than Italian food.

This is a universal problem



- ▶ supervised models (classifiers, regressors) learn features that are correlated with the label being annotated.
- unsupervised models (topic models, word embeddings) learn correlations between topics / contexts.

This is a universal problem



- supervised models (classifiers, regressors) learn features that are correlated with the label being annotated.
- unsupervised models (topic models, word embeddings) learn correlations between topics / contexts.
- An important exception: dictionary methods (perhaps explaining why they are often used by economists). But they have other serious limitations.

What quantity do we care about? vs. What do we measure?

What quantity do we care about? vs. What do we measure?

- Positive/negative sentiment → Count positive/negative words, or predict text annotations.
- ► Toxicity → Count toxic words, or predict text annotations.

What quantity do we care about? vs. What do we measure?

- Positive/negative sentiment \rightarrow Count positive/negative words, or predict text annotations.
- lacktriangle Toxicity ightarrow Count toxic words, or predict text annotations.

confounders?

- lacktriangle Student performance ightarrow predicted essay grade based on labeled essay documents.
- ▶ Credit worthiness → predicted probability of default based on loan application documents.

What quantity do we care about? vs. What do we measure?

- Positive/negative sentiment \rightarrow Count positive/negative words, or predict text annotations.
- lacktriangle Toxicity ightarrow Count toxic words, or predict text annotations.

confounders?

- lacktriangle Student performance ightarrow predicted essay grade based on labeled essay documents.
- ▶ Credit worthiness → predicted probability of default based on loan application documents.

confounders?

lackbox Political partisanship ightarrow predicted probability being Democrat/Republican based on speeches.

What quantity do we care about? vs. What do we measure?

- Positive/negative sentiment \rightarrow Count positive/negative words, or predict text annotations.
- ightharpoonup Toxicity ightharpoonup Count toxic words, or predict text annotations.

confounders?

- lacktriangle Student performance ightarrow predicted essay grade based on labeled essay documents.
- ▶ Credit worthiness → predicted probability of default based on loan application documents.

confounders?

lackbox Political partisanship o predicted probability being Democrat/Republican based on speeches.


confounders?

Policy priorities → predicted probability of speeches/laws being about a particular policy topic.


- By itself, producing measurements that are biased by confounders might not be a problem.
- e.g.:
 - ightharpoonup an NLP-based credit score that learns confounders ightharpoonup not a problem unless debtors learn about it and strategically alter their documents.
 - similarly with automated essay grading

- ▶ By itself, producing measurements that are biased by confounders might not be a problem.
- e.g.:
 - ightharpoonup an NLP-based credit score that learns confounders ightharpoonup not a problem unless debtors learn about it and strategically alter their documents.
 - similarly with automated essay grading
- for measuring political divisiveness or policy priorities
 - probably won't matter for in-domain summary statistics
 - but would matter a lot for summary statistics in a new domain

- By itself, producing measurements that are biased by confounders might not be a problem.
- e.g.:
 - ightharpoonup an NLP-based credit score that learns confounders ightharpoonup not a problem unless debtors learn about it and strategically alter their documents.
 - similarly with automated essay grading
- for measuring political divisiveness or policy priorities
 - probably won't matter for in-domain summary statistics
 - but would matter a lot for summary statistics in a new domain
- even in domain, will matter for assessing the causal effect of a treatment, e.g. the electoral cycle:
 - elections might cause politicians to focus on social issues rather than economic issues.
 - if social/economic issues are confounded with partisanship, the resulting estimates are biased.



- When text is outcome, the confounders cannot be correlated with the treatment.
- ▶ When text is treatment, the confounders cannot be correlated with the outcome.



- When text is outcome, the confounders cannot be correlated with the treatment.
- When text is treatment, the confounders cannot be correlated with the outcome.
 - e.g.: estimating the effect of politician speech sentiment on his/her reelection chances?

Steps for de-biasing

- Language features that are often confounded with the quantity of interest:
 - stopwords
 - named entities: person/organization/place names
- These can be dropped during pre-processing to reduce the influence of confounders in subsequent measurements.
- ▶ Can control for topic or style features or other potential confounders in regressions.