

Contents and how to read this booklet

This booklet is formal front matter, the mainline drawing pages and a formal appendix. The authoritative data is the geometry/*.geojson, metrics.json and the three matrices inside the submission package; the drawings are a presentation of results, not a data source.

1	Cover	22	Board 09 - English caption
2	Contents and how to read	23	Mainline board 09 - Four mechanisms by three modes: the design framework
3	Three-level scope, boundary status and layer inventory	24	Board 10 - English caption
4	Board 01 - English caption	25	Mainline board 10 - From problem to mechanism to action
5	Mainline board 01 - The proposition: relation lag along the Jing-Zhang corridor	26	Board 11 - English caption
6	Board 02 - English caption	27	Mainline board 11 - Overall structure plan
7	Mainline board 02 - Grey infrastructure: the network and the barrier are one body	28	Board 12 - English caption
8	Board 03 - English caption	29	Mainline board 12 - Five transects, three layers of judgement
9	Mainline board 03 - Cannot reach the station, cannot cross the line; catchment, barrier and detour	30	Board 13 - English caption
10	Board 04 - English caption	31	Mainline board 13 - T1 Dazhongsi: the fact base and the three-way inventory
11	Mainline board 04 - Social infrastructure: 15-minute access, everyday services, and the education negative result	32	Board 15 - English caption
12	Board 05 - English caption	33	Mainline board 15 - Scale transmission: three continuous zooms on the same orientation
13	Mainline board 05 - Campus walkability and access rules: physical access is not institutional openness	34	Board 16 - English caption
14	Board 06 - English caption	35	Mainline board 16 - Existing section and the North 3rd Ring diagnostic window
15	Mainline board 06 - Research, translation and industry: the spatial relation of the innovation chain	36	Board A1 - English caption
16	Board 07 - English caption	37	Mainline board A1 - Appendix: walking network structure (proxy indicator)
17	Mainline board 07 - Two continuities in the blue-green system: structural is not the same as usable	38	Response to the three key areas and the declaration of depth
18	Board 08 - English caption	39	Metrics, area recomputation and compliance summary
19	Mainline board 08 - Five transects: problem index and role matrix	40	Response to agent.1 to agent.6
20	Board 08A - English caption	41	T1 site observation and imagery source register
21	Mainline board 08A - Composite problem map of the three systems	42	Risk, copyright and material still to be obtained

Three-level scope, boundary status and the submitted layer inventory

This page states, before anything else, which boundary the proposal uses, what that boundary can and cannot support, and which structured layers sit behind every drawing that follows.


The Coordinated Research Area (about 43.6 km sq) asks what the exchange conditions between AI assets are; the Overall Design Area, the extent submitted here, asks how those conditions are organised in space along the corridor; the Key-Area layer (three areas, about 368.4 ha) asks whether that organisation lands on real objects. The urban relation transect carries the three levels.

Boundary status


At the time of submission the organiser had not published the official planning boundary, the exact key-area polygons, regulatory parcel controls, road boundaries or utility conditions. This package uses the provisional rough boundary supplied by the repository as its only source of extent and marks it everywhere as `official_boundary=false`, `geometry_role=provisional_constraint`, `boundary_precision=provisional_rough`. That gap does not block content scoring, but it means every area and ratio here is a low-confidence design-model value; once official geometry is released everything is recomputed in full rather than patched.

Submitted layer inventory

<code>site_boundary.geojson</code>	Overall design area (1 provisional polygon)
<code>key_areas.geojson</code>	Three key areas, provisional polygons
<code>land_use.geojson</code>	Conceptual land-use structure, 11 cells
<code>buildings.geojson</code>	1591 existing footprints (OSM)
<code>roads.geojson</code>	311 centrelines (310 OSM plus one conceptual spine)
<code>green_space.geojson</code>	79 existing green and open spaces (OSM)
<code>public_space.geojson</code>	7 conceptual public-space control bands
<code>constraints.geojson</code>	Existing rail alignments and water bodies (OSM, not statutory control geometry)
<code>phasing.geojson</code>	3 conceptual phases



Three-level scope transmission and the conceptual land-use structure, derived from this package's GeoJSON



Overall concept and evidence structure

Uniform boundary statement: everything here is an open co-creation recommendation. It does not replace statutory planning and is not an approved government conclusion. Every spatial proposal is stated as a conceptual recommendation. The extent is the organiser's provisional rough boundary (`official_boundary=false`), not an official planning boundary.

The proposition: relation lag along the Jing-Zhang corridor

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

转型命题：京张沿线的关系滞后

The first phase of public space in the Jing-Zhang park is built; the relation between the universities, communities, stations and industrial areas along it and the corridor itself has not caught up. The board sets the spine, the five transects and the three key areas on the canonical base map.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

一条公共空间已经建成，城市关系尚未跟上



- 京张遗产线位→连续公共空间骨架
- 13号线（现役）
- 商业/就业
- 绿色斑块
- - 城市关系断面 T1-T5
- 已建成公园段
- 高校
- 居住
- 轨道站点

京张铁路地面线位随高铁入地退出运行，已转变为一条约 9 公里的连续公共空间。高校、社区、站点、产业园与更新地块如今都与它直接相邻——规划对象因此从一条线，转向京张与两侧城市系统之间的关系。

城市关系断面 | URBAN RELATION TRANSECT

在 T1 大钟寺、T2 成府路—五道口、T3 清华东—学院路、T4 众智园、T5 北京北 五个典型位置切出横向关系单元，观察并重组两侧城市系统与京张的关系。

Grey infrastructure: the network and the barrier are one body

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

灰色基础设施：网络与阻隔同体

The Line 13 shared corridor, the North 3rd and 4th Ring expressways and the Beijing North yards are at once the operating network and the main lateral barrier: the same facilities do both. Crossings are shown in three states according to how well they are verified.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

交通骨架连续，但横向公共联系并不同步



灰色基础设施结构 | 支撑运行与造成分割的，是同一批设施。

13号线共廊段、北三环—北四环快速路、北京北站场与高铁地面段构成沿线运行网络，同时也是主要的横向阻隔。

七处既有横穿按核实程度分三类：三处步行可用、三处条件待核、北三环为京张上跨快速路的立体节点。

京张的交通设施既维持城市运行，也在多个区段形成横向公共联系的阻隔。

Cannot reach the station, cannot cross the line: catchment, barrier and detour

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

到不了站、过不去线：站点腹地与阻隔×横穿×绕行

Left: the real 800 m station catchment on the actual network (Dazhongsi 22%, Beijing North 16% of the theoretical value). Right: barrier bands, the three crossing states and measured detour points (7.2x across Zhichun Road). The two maps answer two different questions.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board


geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

“存在横穿” 不等于 “形成公共联系”



01 轨道站 800m 实际步行腹地 (覆盖率 = 网络可达节点 ÷ 理论范围节点)

低覆盖率站点被站场/大院/桥区围住;
对照站证明低值并非普遍现象



五道口 | 覆盖率 0.58 (对照)



02 阻隔 × 合法横穿 × 绕行 (实走验证)

站点腹地与实走绕行
是两个独立证据:

左图证明 “到不了站” ——
大钟寺、北京北、学院桥的
800m 实际腹地只有理论
范围的 16%-22%;

右图证明 “过不去线” ——
直线 180m 的两点实走
要绕 7.2 倍, 明光村到骨架
实走 3272m。

沿线并不缺少横穿设施,
但站点腹地、实际绕行与
横穿条件显示, 不同区段
仍存在真实的横向阻隔。

Social infrastructure: 15-minute access, everyday services, and the education negative result

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

社会基础设施：15 分钟可达、日常服务与教育覆盖（负结果）

The main map is the isochrone on the real walking network; the secondary map is service coverage by category; bottom right is the education check, which found no new gap. That negative result is kept to prevent the misreading that the corridor lacks education.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

服务设施不少，错位发生在“真实步行”这一层



15 分钟生活圈 | 自居住样点沿真实步行网络扩散 (步速 80m/min)



验证 | 住宅附近节点 15 分钟内可达服务类数 (0-5, 红 = 低)

按 15 分钟生活圈口径，沿线服务设施总量并不匮乏；教育服务专项核查未发现新的设施缺口。

真正的错位出现在步行网络上——建成段周边等时圈完整连片，而隔轨、贴快速路的居住区等时圈被切碎；部分隔轨居住区到最近公共空间的实际步行距离达到直线距离的三到四倍。

问题并非服务数量不足，
而是设施分布与真实步行可达之间的错位。



验证 | 教育设施1200m覆盖
绿=覆盖 红=未覆盖——未发现新缺口 (负结果)

Campus walkability and access rules: physical access is not institutional openness

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

高校步行渗透与开放条件：空间可达不等于制度开放

Left: the physical possibility of walking between the campuses and the corridor. Right: the access rules of six institutions. About 13% of the campus edge has an actual gate; openness depends on booking, gate control, teaching management and tenure.

How to read it


The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board


geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

空间邻近，不等于高校边界开放

局部验证 | 绕行由入口位置决定



01 物理联系 | 能不能到达



02 开放条件 | 允不允许进入

空间邻近、
物理可达
与制度开放
并不等价。

沿线高校虽然与京张
高度邻近，但公共交换
仍取决于入口位置、
开放制度和管理边界。

因此，不同校园界面
需要采取差异化的
开放与控制方式。

Research, translation and industry: the spatial relation of the innovation chain

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

科研转化产业：创新链的空间关系

Origination (universities and institutes), translation (pilot and technical services) and capacity (industrial parks) are all present along the corridor and adjoin one another, but the public space and everyday exchange frontage between them is weak. This is the evidence base for the claim that the task is to raise exchange conditions.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

创新资源高度集聚，但公共交换关系仍然薄弱



沿线高校、科研、转化服务和产业承载资源高度集聚，
但不同机构与城市公共空间之间的交换界面
和日常联系条件并不一致。

策源（高校院所）、转化（中试与服务机构）与承载（产业园区）
三类空间沿线俱全且相互邻近——
公共空间是三者之间最直接的潜在交换界面，
而当前这一层联系条件最薄弱。

创新资源的公共交换关系，
是京张骨架可以直接作用的对象。

科研策源—成果转化—产业承载的全线空间关系（机构实证口径）

Two continuities in the blue-green system: structural is not the same as usable

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

蓝绿两种连续：结构连续不等于使用连续

Left panel: structural continuity of the green system. Right panel: walked access from residents to real entrances. The corridor has only 21 park entrances, and four of its five structural breaks are caused by transport infrastructure.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

生态连续，不等于公共使用连续



左图：北段绿量大且相邻，
蓝线连续——生态基底
不是主要问题。

右图：入口位置、实际步行
网络和管理边界决定了
居民能否真正使用——
居住样点到公园入口
步行中位 1472m，
一期建成段 972m。

绿色基础设施更新的重点
不是继续增加绿色面积，
而是把已有生态骨架
转化为可进入、可到达、
可使用的公共空间系统。

01 生态/物理连续 | 绿地水系在空间上是否相邻连续

02 使用连续 | 人能不能进入（黑三角 = 登记入口；红区 = 步行15分钟以上才能到入口）

Five transects: problem index and role matrix

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

五断面问题索引与角色矩阵

The problem index and role matrix of the five urban relation transects T1-T5. A transect is not a design spot but a relation situation; every problem traces back to one of the earlier evidence boards.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

同一条京张，五种不同的关系问题



断面	真正的问题	关系重点		
T1 大钟寺	站点、更新地块与京张已经高度相邻，但到达、换层和横向公共关系仍未形成整体	ARRIVE	FACE	CROSS
T2 成府路—五道口	高校、创新资源与公共空间相邻，但界面与使用组织尚未形成稳定交换	FACE	USE	
T3 清华东—学院路	高校边界开放条件差异明显，公共交换取决于管理边界与横穿条件	FACE	CROSS	
T4 众智园	产业、绿地与城市日常空间各自运行，缺少持续的公共界面关系	FACE	USE	
T5 北京北	站场与铁路设施造成东西向分隔，京张端点尚未形成连接两侧城市、组织到达的门户节点	ARRIVE	CROSS	

Composite problem map of the three systems

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

三系统综合问题落图

How the problems of the grey, social and green systems overlap in space. Where they overlap most densely is where this proposal chose to go deep (T1).


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

三个系统的问题，落在哪里



三系统交互问题落图（六类最终问题·全部可回溯 B02-B07 证据）

为什么需要这张图

灰、社会、绿三个系统各自完成“结构—证据—问题”之后，
大多数规划问题产生于系统交互处：
灰设施决定社会系统能否到达骨架；
灰设施造成绿网大多数结构断点；
社会系统与骨架的关系取决于绿色空间界面。

六类最终规划问题

- FP1 站区到达链断续〔灰×社〕 | 大钟寺/北京北
- FP2 建成邻接未接入〔社，灰致因〕 | 就业带/明光村/T2西
- FP3 边界性邻近·贴而不通〔社×绿〕 | T3 高校带
- FP4 横穿公共性分层不足〔灰〕 | 全线横向
- FP5 绿网结构断点〔灰×绿〕 | 站体/切点/北端
- FP6 骨架消极工程界面〔灰×绿〕 | 全线分段

T1 是多类问题在同一段叠合的唯一段落——这是其“整体重组”
定位的依据；五道口为三系统样本，结论是维护而非再建设。

Four mechanisms by three modes: the design framework

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

四机制 × 三方式设计框架

The framework formed by the four relation actions (ARRIVE, FACE, CROSS, USE) and the three modes of intervention (direct design, planning control, management and operation). It determines the nature and the responsible party of every action.

How to read it


The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

先问改变什么关系，再决定如何介入

城市系统与京张之间的关系问题



站点、街道与城市到达系统
如何接入京张公共空间

建筑、地块与更新项目如何
重建朝向京张的城市界面

把既有合法横穿设施转化为
公共联系节点，不默认新增
未经核实的工程穿越

通过运营、时段、活动和管理
建立真实使用关系

同一关系问题，可以有不同的介入深度——直接设计不是默认答案。



关系必须由空间实体建立时

关系取决于更新地块的界面与退线条件时

关系取决于开放制度、时段与活动组织时

From problem to mechanism to action

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

问题 → 机制 → 行动

Diagnosed problems are connected to the four relation actions and then written as readable actions. The action library is classified, not a flat list.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

每个问题都经过“关系—方式—行动”再落地



不是看到问题就直接画设计——每个行动都先经过关系判断与方式选择。

Overall structure plan

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

总体规划结构图

The spatial structure of the overall design area: one continuous public-space spine, the lateral connections into it, the three key areas and the two gateways. Everything shown is a conceptual recommendation and contains no engineering alignment.


How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

不是沿线做五个点，而是重组一条骨架与整个城市的关系



五个关系段差异化介入：T1 整体重组 | T2 运营激活 | T3 克制、条件性受控交换 | T4 介入取决于跨线通道可行性 | T5 门户到达 + 以站区组织东西向缝合；普通段保持现状也是规划决定。

一条连续骨架 × 多类城市系统 × 差异化关系重组

Five transects, three layers of judgement

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

五断面三层判断

Each transect is given three layers: a plan strip (the current relation), a section (the lateral relation) and a response (the mechanism proposed). T2 to T5 stay at concept level and the difference in depth is declared.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

五个断面，五种不同的城市关系响应



T1 Dazhongsi: the fact base and the three-way inventory

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

T1 大钟寺事实主图与三分清单

The object-level facts of T1: the station, exits A and B, the 1733 block, the Line 13 at-grade section, the Jing-Zhang overpass across the North 3rd Ring, the Lanjing site and the Mingguangcun resettlement community. The inventory is strictly split into existing engineering fact, planning-control scope and unknown state; unknowns are not assumed usable.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

T1 大钟寺：这里到底有哪些真实对象



FACT | 已核实事实

- 大钟寺站体与 A/B 口位置（既有工程）；
- 13号线 = 既有高架轨道系统（基座 + 成对轨线）；
- 京张公共空间在北三环处存在上跨桥面，骨架连续；
- 北三环 = 连续地面车行道路；
- 1733 两栋既有建筑；36号院、明光村现状、蓝景既有建筑、周边建筑/道路/水体均保留现状身份。

TO VERIFY | 待核实

- 两套高架系统（13号线×京张桥面）精确相对高程；
- 北京北侧桥头（N2）的落地构造——不预设坡道/楼梯/电梯/工程标高；
- 桥下空间状态（UNKNOWN，不预设可利用）。

DESIGN AUTHORITY | 设计权限

- 站前场与到达序列 = 可直接设计；
- 1733、原市场地块、蓝景界面 = 随更新受控重构（规划控制）；
- 站体、轨道、桥体、北三环 = 既有工程，不改动本体；
- N3A 门户位置只作保守对象保护包络，不预绘构件。

Scale transmission: three continuous zooms on the same orientation

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

尺度传导：同北向连续 zoom 三联

Three continuous zooms on the same orientation, from the overall area to the transect to the object, so that a judgement made at one level still holds at the next.



How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

从 9 公里到站区：连续放大的三个尺度



① 9km 全线 (canonical) | T1 是多类问题同段叠合的唯一一段落

② 1.3km 关系情境 | 站点、1733、北三环、13号线、蓝景、明光村在此交汇

③ 站区 | 1733—站体—京张—北三环构成核心关系段

三级同北向、同底图语言；上一级红框 = 下一级范围。

Existing section and the North 3rd Ring diagnostic window

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

现状断面与北三环诊断窗

The existing cross-section redrawn to the 63A definition, with the diagnostic window on the North 3rd Ring overpass. There is no public evidence for the relative levels of the Jing-Zhang overpass and the Line 13 viaduct; the board declares this unverified.

How to read it


The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.

T1 现状关系断面：两套立体系统同时存在

EXISTING RELATION SECTION | 现状关系断面（东西向，过北三环桥区）



断面表达的现状事实：北三环是连续地面车行道路；13号线是既有高架轨道系统；京张公共空间在北三环处以桥面上跨、骨架连续——两套立体系统同时存在。

两套高架系统之间的精确相对高程目前没有可靠证据：本图不表示相对高度，块体高度仅为示意；未经核实的坡道、楼梯、电梯、桥下构件、地下通道与高差尺寸均不作预设。

本断面为 EXISTING（现状分析），与后续设计剖面（PROPOSED DESIGN SECTION）构成“现状→方案”对照；T1 设计问题 = 以既有京张跨三环公共空间和大钟寺站为骨架，重组 1733—A/B口—站体—京张—两侧更新界面之间的到达、换层、面向与横向公共空间关系。



上跨事实的图面核验（52C 北三环诊断窗）——桥面连续通过的判断依据

Appendix: walking network structure (proxy indicator)

The drawing on the facing page is presented in Chinese. This page gives its full English reading: what it shows, the judgement it supports and the limits declared on it.

Chinese title on the board

附录：步行网络结构（代理指标）


The walking network structure as a proxy indicator, kept as an appendix with an explicit reduction in weight: it supports background understanding and does not on its own support a spatial control conclusion.

How to read it

The base map is the canonical extent shared by every mainline board, so any two boards can be overlaid. Where a crossing, a level or a frontage has not been verified from public material it is drawn in a distinct state and named unverified on the board itself; nothing unverified is upgraded into a design assumption. All areas and ratios printed on the board are recomputed from the submitted GeoJSON in EPSG:4548 and match metrics.json.

Evidence behind this board

geometry/*.geojson and metrics.json in this package; existing conditions from OpenStreetMap contributors under ODbL 1.0 [source:DATA-SRC-OSM-JINGZHANG-BASE]; the provisional extent [source:BOUNDARY-SOURCE]; the entrant's own relation analysis [source:MAINLINE-RELATION-ANALYSIS]. The mapping from this board to the requirements it answers is in compliance_matrix.json.



这张图回答什么

步行网络中各街道的穿越潜力与局部连接规模
——作为全线网络结构的背景读法。

关键发现

京张当前不是城市步行网络中的主要穿越性路径;
东西向高潜力街道仅成府路、知春路等少数。

使用边界 (重要)

- 本图为自定义代理指标 (非标准空间句法) :
- 不能推断真实人流量与使用强度;
 - 低穿行度≠低使用;
 - 未做角度加权, 与标准句法数值不可比。


本页仅作结构背景, 全套规划判断均以
真实步行证据 (腹地/绕行/等时圈) 为准。

[KEEP_PENDING_USER_REVIEW: 本页按信息完整性审计恢复, 是否保留待用户裁定]

左 | 穿越潜力 (320起点×60终点最短路径经过次数) 右 | 局部连接规模 (每节点1000m网络可达节点计数)

Response to the three key areas and the declaration of depth

This proposal reaches a different design depth in each of the three official key areas. The difference is declared, not averaged away.



Dazhongsi AI Industry Cluster - T1 - 72.0 ha

The only key area taken to object-level spatial design. The converged design question: using the existing overpass and Dazhongsi station as the frame, reorganise arrival, level change, frontage and lateral public space between the 1733 block, exits A and B, the station, the corridor and both renewal frontages. Risk: no public evidence for the relative levels of the two elevated systems; declared unverified, with no clearance assumed.

Beijing AI Origin Community - T2 - 104.3 ha


Concept-level spatial control: housing and community services as the leading use, activation by operation rather than construction, everyday services and arrival restored, places to stop organised at the existing crossings. Risk: with no official regulatory plan or boundary, intervention intensity is left open.

Zhongzhiyuan AI Independent Innovation Acceleration Area - T4 - 192.1 ha

Concept-level spatial control: research and pilot translation as the leading use, the corridor-facing edge as the priority public frontage, a conditional interface reserved at the green-grey break. Risk: the feasibility of that crossing is unstudied and the degree of intervention depends on it.

Metrics, area recomputation and the compliance matrix in summary

Every known metric is recomputed programmatically from this package's geometry in EPSG:4548. No unknown metric is given a design-model number.



Coverage of the three matrices

- 23
- mandatory items in compliance_matrix.json (17 from announcement clauses 1.3, 1.4 and 1.5 plus agent.1 to agent.6)
- 6
- mandatory professional standards in standard_matrix.json, all review_status=addressed
- 15
- core design-depth items in design_depth_matrix.json, all status=complete
- 20
- sources registered in sources.json, graded usable for formal, background only or provisional only
- 11
- assumptions registered in assumptions.json, each with its status and its effect

Held unknown because official data is missing

- floor_area_ratio
- official regulatory FAR not published
- building_height_limit_m
- official height control not published
- retain_renovate_demolish_parcel_count
- tenure and acquisition policy are non-public data

Response to the agent taskbook, agent.1 to agent.6

A summary of the response to the six mandatory tasks; the full argument is in proposal.md and the machine-readable mapping is in compliance_matrix.json.

agent . 1

Overall concept and coordinated functional scheme for the belt

Name: Jing-Zhang Relation Belt - a method name, not a replacement for the official name. Three visual identity directions - connection lines, the transect cut, the overlaid layers - all avoiding literal rail, gear, brain or chip symbols. The spatial structure is one continuous public-space spine, five relation transects, three key areas and two gateways.

agent . 2

Full-stack independent AI innovation system and a world-class AI innovation ecosystem

Six publicly verifiable international innovation districts (Kendall Square, Station F, King's Cross Knowledge Quarter, 22@ Barcelona, MaRS, Seoul AI Yangjae Hub); from each, one transferable mechanism directly relevant here. The common mechanism: none of them was achieved by designating new land - all raised the exchange conditions of existing space.

agent . 3

AI-enabled scenarios and an intelligent, active city

Twelve AI scenario cards (S09, S10 and S11 are industry testing and validation scenarios) and five user personas plus two secondary groups. Every scenario grows from existing spatial relations without new building complexes. A single privacy boundary applies: no face recognition or individual tracking, aggregate data only and published, with human review and a stop channel always retained.

agent . 4

AI public space, natively intelligent uses and pilgrimage landmarks

The three landmarks are all upgrades of existing urban relation nodes, with no new signature building: the Dazhongsi station-city exchange node (T1), the Beijing North southern gateway node (T5) and the Zhongzhiyuan innovation exchange node (T4). The honours display system and the public-space component kit are conceptual directions and name no product or supplier.

agent . 5

A narrative fusing the Jing-Zhang, Zhongguancun and new AI cultures

Three time layers: the Jing-Zhang railway (from 1905-1909), the history of Zhongguancun innovation (from the 1980s) and the new AI culture (now). The wayfinding system expresses the three as a hierarchy rather than a list, and every node answers three questions: what happened here, what it is now, how it can be used. The cultural identity system is kept separate from the belt's own logo system.

agent . 6

A global AI innovation event system and long-term operation

An annual programme of eight events, from the March corridor open day to year-round community engagement; every operator is stated as a suggested collaboration, never as a commitment. Three long-term mechanisms: a scenario access catalogue with one entry point and clear rules, a quarterly rhythm for the developer community, and a public display system for results and contributions. The attraction principle: first let people arrive, see and use, then talk about recruitment.

T1 site observation and the imagery source register

This page uses only Wikimedia Commons images whose licence is explicit and attributable; each image carries its author and licence beneath it. Two further images on the original mainline observation board were removed from this submission because their redistribution licence is not established.



Exit A, Dazhongsi Station (22 Feb 2025)

RobertSchwandl · CC BY-SA 4.0
[https://commons.wikimedia.org/wiki/File:Exit_A_of_Dazhong_Si_Station_\(Feb_2025\).jpg](https://commons.wikimedia.org/wiki/File:Exit_A_of_Dazhong_Si_Station_(Feb_2025).jpg)



Exit B, Dazhongsi Station (9 Apr 2021)

N509FZ · CC BY-SA 4.0
[https://commons.wikimedia.org/wiki/File:Exit_B_of_Dazhongsi_Station_\(20210409120947\).jpg](https://commons.wikimedia.org/wiki/File:Exit_B_of_Dazhongsi_Station_(20210409120947).jpg)



Outside Dazhongsi Station

Siyuwj · CC BY-SA 3.0
https://commons.wikimedia.org/wiki/File:Outside_Dazhongsi_Station_in_Beijing.JPG

Three findings established on site

First, there is no continuous arrival guidance between exits A and B of Dazhongsi station and the corridor's public space; the flow leaving the station meets a carriageway frontage and temporary occupation. Second, the forecourt is used very differently at peak and off-peak, but the space itself is not organised to be shared over time. Third, the state of the space beneath the North 3rd Ring overpass cannot be established from public material, so this proposal does not assume it is usable. These are observational findings; all spatial measurement still rests on the GeoJSON and the measured data.

Risk, copyright and the list of material still to be obtained

This page lists, in one place, every known uncertainty, licence status and data gap; none of it is left outside the text.

Data risk

The official planning boundary, the exact key-area polygons, regulatory controls, road boundaries and utility conditions are all unpublished. Every spatial conclusion rests on the provisional rough boundary and is a low-confidence design-model value; all of it is recomputed once official data is released. The existing-conditions base is OpenStreetMap and its completeness has not been field-verified. A gap declared by this package: the continuous public-space spine layer currently covers only the southern reach, with northern continuity carried by the transects and forecourt bands.

Technical and delivery risk

Public use of the North 3rd Ring viaduct zone depends on verifying clearance and structure; the reserved cross-corridor link depends on a feasibility study; opening the campus edge depends on each institution's own decision. All three are marked conditional or unknown. There is no public evidence for the relative levels of the Jing-Zhang overpass and the Line 13 viaduct, and no level judgement is made.

Privacy and ethics

Every AI scenario prohibits face recognition and individual tracking, uses aggregate data only and publishes it, and keeps human review and a stop channel. No non-public government data, internal corporate data or personal data is used.

Copyright and licensing

The analysis, drawings and text are the entrant's own work. Existing spatial data comes from OpenStreetMap under ODbL 1.0, registered feature by feature through osmid. Three site photographs come from Wikimedia Commons: two under CC BY-SA 4.0 and one under CC BY-SA 3.0, each registered and attributed on the page where it appears. Font, library and toolchain versions and licences are registered in report/copyright_statement.md. REMOVED: one street-view platform screenshot and one official press photograph from the mainline observation board, because their redistribution licence is not established.

Material still to be obtained

1. The official planning boundary and the exact key-area polygons. 2. Regulatory parcel controls: floor area ratio, building height, density. 3. Road boundaries and rail protection zones. 4. Utility routing and capacity. 5. Tenure and acquisition policy. 6. Structural and clearance conditions of the North 3rd Ring viaduct zone. 7. The access rules of each institution. Once these seven are in hand, every layer, metric and drawing in this package is recomputed and reissued.