MINOW YOUR HTTP STATUS CODES!

HTTP status codes are returned in the response. They each consist of a three digit numerical code and a text description (the text description is simply advisory, and may be translated to other languages). The codes are categorized such that general classes of errors have the same most-significant digit, so if a client does not recognize a status code it may still infer the code's category.

1XX Informational

Status Code	Description
100 Continue	The server has received the request headers, and the client should begin to send the request body
101 Switching Protocols	The server has received a request to switch protocols and is doing so

102 Processing (WebDAV) Indicates that the server has received the request, used by WebDAV to avoid timeouts for long-running requests

2XX Success

201 Created

Status Code Description

200 OK Standard response for successful HTTP requests

The request was accepted for processing, but the job hasn't actually been completed. It is possible that the request will be rejected once processing takes 202 Accepted

The request was successful, and a new resource has been created

203 Non-Authoritative Information The request was successfully processed, but the returned information may be from an untrusted third party

204 No Content The request was processed and no content is being returned

206 Partial Content Only part of the request body is being delivered (for example, when resuming an interrupted download) 207 Multi-Status (WebDAV) The message body is an XML document and may contain multiple status codes per sub-requests 208 Already Reported (WebDAV) The response has already been enumerated in a previous reply and will not be reported again

3XX Redirection

Status Code Description

300 Multiple Choices Indicates that there are multiple locations which the client may follow

The resource has moved permantly, and all future requests should use the give URL instead 301 Moved Permanently

The resource has been found (or moved temporarily). The HTTP/1.0 specification requires that the redirect uses the same verb, but in practice clients use 302 Found

a GET as in a 303. See 303 and 307

The resource has been found, and should be accessed using a GET method. Added in HTTP/1.1 to clarify the ambiguity in the behavior of status 302. See 303 See Other 302 and 307

The resource has not been modified since the last time the client has cached it 304 Not Modified

The resource should be accessed through a specified proxy 305 Use Proxy

The request should be repeated with the same request method at the given address. Added in HTTP/1.1 to clarify the ambiguity in the behavior of status 307 Temporary Redirect

302. See 302 and 303

4XX Client Error

410 Gone

412 Precondition Failed

Status Code	Description
400 Bad Request	The request can not be fulfilled because the request contained bad syntax
401 Unauthorized	The client needs to authenticate in order to access this resource
402 Payment Required	This code is intended to be used for a micropayment system, but the specifics for this system are unspecified and this code is rarely used
403 Forbidden	The client is not allowed to access this resource. Generally, the client is authenticated and does not have sufficient permission

404 Not Found The resource was not found, though its existence in the future is possible 405 Method Not Allowed The method used in the request is not supported by the resource

The server can not generate content which is acceptable to the client according to the request's "Accept" header 406 Not Acceptable

The client must authenticate with the proxy 407 Proxy Authentication Required

408 Request Timeout The client did not complete its request in a reasonable timeframe

409 Conflict The request could not be completed due to a conflict in state (for example, attempting to update a resource when it has changed since last access)

The server can not meet preconditions specified in the client request

The resource is gone, and will always be gone; the client should not request the resource again

The request is missing its "Content-Length" header, which is required by this resource 411 Length Required

The request body is larger than the server will process 413 Request Entity Too Large 414 Request-URI Too Long The request URI is too long for the server to process

415 Unsupported Media Type The server can not process the request body because it is of an unsupported MIME type

416 Requested Range Not Satisfiable The client has asked for portion of a file that the server can not supply (ie, a range of bytes outside the size of the requested file)

The server can not meet the requirements of the "Expect" header in the request 417 Expectation Failed 418 I'm a teapot (HTCPCP) Returned by teapots implementing the HyperText Coffee Pot Control Protocol

420 Enhance Your Calm (Twitter) The client is being rate-limited; a reference to cannabis culture 422 Unprocessable Entity (WebDAV) The server can not process the request due to semantic errors 423 Locked (WebDAV) The resource is currently locked

424 Failed Dependency (WebDAV) The request failed because of a previously-failed request 429 Too Many Requests The client is being rate-limited

431 Request Header Fields Too Large Either a single request header is too large, or all the header fields as a group are too large

444 No Response (Nginx) Used in Nginx logs. Indicates that the server closed the connection without sending any response whatsoever

449 Retry With (Microsoft) The request should be retried after performing some action

450 Blocked by Windows Parental Controls (Microsoft) Windows Parental Controls are turned on and are blocking access to the resource

451 Unavailable For Legal Reasons (Internet Draft) Intended to be used when a resource is being censored or blocked; a reference to Fahrenheit 451

5XX Server Error

509 Bandwidth Limit Exceeded

Status Code	Description
500 Internal Server Error	A generic server error message, for when no other more specific message is suitable
501 Not Implemented	The server can not process the request method
502 Bad Gateway	The server is a gateway or proxy, and received a bad response from the upstream server (such as a socket hangup)
503 Service Unavailable	The resource is temporarily unavailable, usually because it is overloaded or down for maintenence
504 Gateway Timeout	The server is a gateway or proxy, and the upstream server did not respond in a reasonable timeframe
505 HTTP Version Not Supported	The server does not support the request's specified HTTP version
507 Insufficient Storage (WebDAV)	The server is out of storage space and can not complete the request
508 Loop Detected (WebDAV)	The server has detected an infinite loop while processing the request

A convention used to report that bandwidth limits have been exceeded, and not part of any RFC or spec