

UNIVERSITY OF SCIENCE AND TECHNOLOGY OF HANOI



BACHELOR THESIS

A Gamified E-Learning Platform for School Students

An Hoc - A Web-Based Gamified E-Learning Platform for Structured
Learning, Adaptive Practice, and Progress Tracking

Author:

DOAN Thuan An

BI11-002

Supervisor:

Dr. TRAN Giang Son

Hanoi - July 2026

DECLARATION

I hereby declare that this thesis titled *A Gamified E-Learning Platform for School Students* is prepared from the implemented Anhoc repository and the accompanying project documentation. All architectural descriptions, feature summaries, and implementation details presented in this report are derived from the inspected codebase, and external concepts or technologies are cited where appropriate.

To the best of my knowledge, this report does not intentionally reproduce uncited work as an original contribution. Any frameworks, libraries, documents, or external references used in the preparation of this thesis are acknowledged in the bibliography.

Hanoi, July 2026

DOAN Thuan An

ACKNOWLEDGEMENTS

This thesis was prepared from the current Anhoc web application repository. The document reflects the work embodied in the frontend, backend, database, and chatbot modules, as well as the supporting technical design notes maintained with the project.

I would like to acknowledge the contributors who shaped the platform's architecture, educational workflows, and deployment configuration, together with the maintainers of the open-source tools that made the system possible, including Next.js, React, Express, Prisma, PostgreSQL, and the supporting Python ecosystem used by the tutoring service.

(DOAN Thuan An)
Hanoi, July 2026

CONTENTS

Acknowledgements	iii
List of Abbreviations	vii
List of Tables	viii
List of Figures	ix
Abstract	xi
I/ Introduction	1
1 Background	1
1.1 Statistical Context of E-Learning in Vietnam	1
2 Problem Statement	2
2.1 Advantages and Limitations of E-Learning Applications in Vietnam	3
3 Objectives	4
4 Scope	4
5 Contributions of the Project	5
6 Thesis Structure	5
II/ Objectives	6
1 Desired Features	6
2 Expected Outcome	7
III/ Materials and Methods	8
1 Requirements Analysis	8
1.1 Stakeholders and User Roles	8
1.2 Functional Requirements	8
1.3 Use Case Model	9
1.4 Detailed Use Case Diagrams	13
1.5 Use Case Descriptions	19
1.6 Non-Functional Requirements	29
1.7 Learning Content Requirements	32
1.8 Assessment Requirements	33

1.9	Administrative Requirements	33
1.10	Operational Assumptions	33
2	System Design	34
2.1	Architectural Overview	34
2.2	Deployment Design	35
2.3	Backend Design	35
2.4	Frontend Design	35
2.5	Security Model	36
2.6	Data Model	36
2.7	Entity-Relationship Diagrams	37
2.8	Question Snapshot Strategy	53
2.9	Progression Design	53
2.10	Sequence Diagrams for Main Use Cases	53
2.11	Sequence Diagrams for Main Use Cases	53
3	System Implementation	76
3.1	Frontend Implementation	76
3.2	Backend API Implementation	76
3.3	Question Generation and Grading	78
3.4	Attempt Lifecycle	79
3.5	Administrative Implementation	80
3.6	Configuration and Deployment	81
3.7	User Interface Presentation	81
IV/ Results and Discussion		82
1	Evaluation Methodology	82
2	Automated Evaluation Script	82
2.1	Automated Evaluation Results	82
3	Functional & Navigation Evaluation	83
4	Performance & Core Web Vitals	84
5	User Experience (UX) & Design Evaluation	84
6	Security & Compliance Evaluation	85
7	Compatibility & Environment Evaluation	85
8	Accessibility (a11y) Evaluation	85

9	Core Web App Evaluation Metrics	86
10	Discussion and Tradeoffs	86
V/ Conclusion & Perspective		88
Appendices		90
A.1	Build and Run Notes	90
A.2	Selected Environment Variables	90
A.3	Application User Interface Screenshots	90

LIST OF ABBREVIATIONS

AI	Artificial Intelligence
API	Application Programming Interface
BYOK	Bring Your Own Key
CORS	Cross-Origin Resource Sharing
CRUD	Create, Read, Update, Delete
CSS	Cascading Style Sheets
ERD	Entity-Relationship Diagram
FK	Foreign Key
HTTPS	Hypertext Transfer Protocol Secure
JSON	JavaScript Object Notation
JWT	JSON Web Token
LLM	Large Language Model
OWASP	Open Worldwide Application Security Project
ORM	Object-Relational Mapping
PDF	Portable Document Format
PK	Primary Key
RBAC	Role-Based Access Control
REST	Representational State Transfer
RPS	Requests Per Second
SQL	Structured Query Language
SQLi	SQL Injection
TTI	Time to Interactive
UC	Use Case
UI	User Interface
URL	Uniform Resource Locator
UUID	Universally Unique Identifier
UX	User Experience
WSS	WebSocket Secure
XP	Experience Points

LIST OF TABLES

3.1	Core functional requirements	9
3.2	Main persistent entities	36
3.3	Complete Database Schema — Table Summary (38 tables)	51
3.4	Main API groups	76
3.5	Detailed REST API Specification	77
4.1	Core Web App Evaluation Metrics	86
A.1	Representative environment variables	90

LIST OF FIGURES

3.1	Use case diagram of the Anhoc platform	10
3.2	Use case diagram — Authentication and Account Management	14
3.3	Use case diagram — Learning System	15
3.4	Use case diagram — Practice and Assessment Engine	16
3.5	Use case diagram — AI Math Tutor Chatbot	17
3.6	Use case diagram — Gamification and Economy	18
3.7	Use case diagram — Subscription and Payments	19
3.8	Architecture design of the Anhoc platform	34
3.9	ERD Group 1 — User & Authentication tables	38
3.10	ERD Group 2 — Curriculum & Content tables	41
3.11	ERD Group 3 — Practice, Tests & Progress tables	44
3.12	ERD Group 4 — Gamification & Economy tables	47
3.13	ERD Group 5 — Subscriptions, Gaming and Notifications	49
3.14	Sequence diagram for UC-ST-01: Authentication and Profile Management	54
3.15	Sequence diagram for UC-ST-02: Content Browsing and Lesson Study .	55
3.16	Sequence diagram for UC-ST-03: Lesson Practice and Grading	56
3.17	Sequence diagram for UC-ST-04: Grade-Level Testing	57
3.18	Sequence diagram for UC-ST-05: Classified Subject Access Request . .	58
3.19	Sequence diagram for UC-ST-06: Interactive Tutoring Chatbot Consul- tation	59
3.20	Sequence diagram for UC-ST-07: Gamification Progression and Economy	60
3.21	Sequence diagram for UC-ST-08: Play Math Games and Challenges . .	61
3.22	Sequence diagram for UC-ST-09: Subscription Upgrade	62
3.23	Sequence diagram for UC-TE-01: Scoped Analytics Workspace	63
3.24	Sequence diagram for UC-TE-02: Scoped Lesson Management	64
3.25	Sequence diagram for UC-TE-03: Scoped Question Template Management	65
3.26	Sequence diagram for UC-TE-04: Organize Content Hierarchy	66
3.27	Sequence diagram for UC-TE-05: View Scoped Content & Testing Data	67
3.28	Sequence diagram for UC-SU-01: Learn Unit Registration & Seat Man- agement	68

3.29	Sequence diagram for UC-SU-02: Manage Learn Unit Members	69
3.30	Sequence diagram for UC-SU-03: Manage Private Content & Resources	70
3.31	Sequence diagram for UC-SU-04: Organizational Capacity Limits Ad- ministration	71
3.32	Sequence diagram for UC-AD-01: Global User Administration	72
3.33	Sequence diagram for UC-AD-02: Access Control & Permissions Man- agement	72
3.34	Sequence diagram for UC-AD-03: Process Classified Subject Requests .	73
3.35	Sequence diagram for UC-AD-04: System Dashboard and Platform Stats	73
3.36	Sequence diagram for UC-AD-05: Manage Global Content Hierarchy .	74
3.37	Sequence diagram for UC-AD-06: Review Question Reports	74
3.38	Sequence diagram for UC-AD-07: Configure Streaks and Achievements	75
3.39	Sequence diagram for UC-AD-08: Oversee Supervisor Accounts	75
A.1	Student dashboard showing XP, levels, and achievements.	91
A.2	Mathematics practice screen.	91
A.3	AI tutoring chatbot widget with reasoning.	91
A.4	Admin overview panel.	91

ABSTRACT

Anhoc is a web-based mathematics learning platform designed for structured school-level study. The implemented system combines bilingual lesson content, dynamically generated practice exercises, grade-level tests, progression tracking, administrative management, notifications, multiplayer and single-player math games, and an integrated tutoring chatbot. This thesis documents the design and implementation of Anhoc based on the current repository contents.

The software follows a service-oriented web architecture. A Next.js frontend provides the student and administrative interfaces. An Express backend exposes REST endpoints for authentication, lessons, tests, achievements, notifications, games, supervisor workflows, and subscription management. Prisma is used as the persistence layer, PostgreSQL stores the core application state, and a companion Python chatbot service extends the platform with conversational tutoring capabilities.

A notable implementation decision is the use of persisted question snapshots. Reusable templates define how questions are generated, while snapshots preserve the exact generated variables, accepted answers, and scoring outcomes for each attempt. This design supports reproducible grading, debugging, review, and reporting. The project also adopts dynamic role-based access control with subject-level restrictions, progression services for mastery and XP, and operational support for learn units and subscription-oriented platform management.

This thesis presents the problem context, requirements, system architecture, data model, implementation details, and an evaluation of the current solution. It also discusses limitations and practical improvements required to mature the platform further as an educational software system.

Keywords: mathematics learning platform, question generation, role-based access control, progress tracking, tutoring chatbot, web application architecture

I/ INTRODUCTION

1 Background

Digital learning systems are increasingly expected to do more than present static content. In mathematics education, students need repeated practice, immediate feedback, structured progression, and content that can be adapted to multiple grades and topics. A conventional content website can display lessons, but it does not by itself provide reusable question generation, mastery tracking, or administrative control over subject-specific learning material.

The Anhoc project addresses this gap by combining theory lessons, generated practice, formal test sessions, and gamified progression in a single web application. The project targets school-level mathematics learning and is organized around subjects, grades, and lessons. The implemented system allows a student to read theory content, start practice from lesson templates, submit answers, complete tests, and monitor progress through XP, levels, and achievements. At the same time, an administrator can manage lessons, question templates, user accounts, roles, and access permissions.

1.1 Statistical Context of E-Learning in Vietnam

The Vietnamese context makes digital learning a credible opportunity rather than a speculative one. DataReportal reported 79.8 million internet users in Vietnam in January 2025, equivalent to 78.8% of the population, together with 127 million cellular mobile connections [1]. EdTech Hub’s 2024 rapid scan, drawing on national statistics, further notes that 96% of households had a mobile phone, 79% of households had internet access in 2023, and mobile devices are substantially more common than computers in the home [2]. For a school-age platform, these figures support a mobile-first design assumption: many learners can get online, and many will do so through phones rather than desktop computers.

Children’s everyday digital use reinforces that opportunity. UNICEF’s Disrupting Harm survey in Vietnam found that 89% of children aged 12–17 had used the internet in the previous three months, and 87% of internet-using children used it every day [3]. This does not automatically imply that online learning is effective, but it does mean that digital habits are already deeply embedded in the age group most relevant to school-level learning platforms.

Taken together, these indicators show that Vietnam is participating in the wider global adaptation to digital technology in everyday life, communication, and educa-

tion. As internet access, mobile-device use, and online habits continue to expand, the need for learning platforms is not decreasing but becoming more immediate. In this environment, educational platforms are increasingly required not only as optional supplements, but as practical tools for delivering accessible, structured, and engaging learning experiences.

2 Problem Statement

The educational opportunity in Vietnam is therefore real, but so are the design constraints. Learners are online, many households have mobile phones, and the national education context is already shaped by structured assessment and digital transition. However, the existence of connectivity does not by itself produce a child-friendly, high-quality learning experience.

EdTech Hub's rapid scan shows that Vietnam already has a crowded educational technology landscape that includes online learning platforms, learning apps, websites, open resources, and YouTube channels [2]. In other words, the core problem is not simply the absence of digital content. It is the absence of an integrated platform that is suitable for school-age learners, easy to navigate on mobile devices, and capable of balancing engagement with real learning depth.

This problem has several dimensions. First, fragmented choice can make it difficult for students and families to identify which tools are trustworthy, age-appropriate, and educationally coherent. Second, high-stakes assessment culture can narrow learning into score chasing. A 2025 study in the *Vietnam Journal of Education* found that the proposed 2025 national high school graduation examination could create adverse wash-back effects, including narrowing learning content and reducing student engagement, even while it strongly motivates score-oriented preparation [4]. Third, digital products that rely too heavily on repetition, streak pressure, or rapid-fire quizzes may capture attention without supporting durable understanding.

This concern is consistent with international evidence. UNESCO's 2023 Global Education Monitoring Report concludes that excessive or inappropriate technology use can harm learning, and reports that mere proximity to a mobile device was found to distract students and negatively affect learning in 14 countries [5]. OECD analysis of PISA 2022 similarly shows that moderate digital-device use for learning can be associated with better mathematics outcomes, whereas leisure-oriented digital use and classroom distraction are associated with lower mathematics performance [6]. The implication is important for Anhoc: digital learning for children should not imitate the most attention-maximizing parts of social media or shallow quiz apps.

The main engineering problem solved by Anhoc is therefore the design of a learning

platform that satisfies four requirements at the same time:

- it must support reusable content across grades and subjects;
- it must generate exercises dynamically rather than storing every question instance manually;
- it must keep each attempt stable enough to be scored, reviewed, and audited later;
- it must provide operational control for administrators without hard-coding every permission into the user interface.

Many simple practice applications solve only one part of this problem. Some provide content but not progression. Others provide gamification but mostly reward speed, repetition, or daily return behavior. Large-scale online learning platforms often excel at adult or professional self-study, but that model is not automatically suitable for children who need guided progression, lighter cognitive load, and a more playful interface. Anhoc therefore introduces a more child-oriented structure: a friendly web interface, bilingual lesson flow, logic-based question generation, persisted attempt snapshots, dynamic role-based access control, and a progression system intended to make learning engaging without reducing it to streak maintenance.

2.1 Advantages and Limitations of E-Learning Applications in Vietnam

The statistical context above suggests several clear advantages for e-learning applications in Vietnam.

- **Large reachable user base:** high internet penetration and widespread mobile connectivity make app-based learning distribution technically feasible at national scale [1].
- **Institutional readiness:** the fact that most schools are already connected to the internet creates a practical foundation for blended learning, school-supported digital homework, and platform-assisted assessment [7].
- **Flexible continuity:** emergency distance-learning evidence shows that digital tools, especially when combined with broadcast channels, can preserve instructional continuity during disruption [8].
- **Expanding ecosystem:** the presence of platforms, apps, websites, and video channels indicates that learners and schools are already familiar with multiple forms of educational technology [2].

At the same time, e-learning applications in Vietnam face structural limitations that directly motivate Anhoc's design.

- **Access inequality:** home internet access and device ownership vary sharply by income and geography, which means an app cannot assume stable, private, always-on access for every learner [7, 9].
- **Fragmentation of tools and content:** World Bank analysis of Vietnamese e-learning practice notes underdeveloped, unstandardized platforms and inconsistent learning materials, making quality assurance difficult [9].
- **Weak progression support in basic tools:** many digital offerings can deliver lessons or quizzes but do not reliably connect content, assessment history, progression, and administration in one coherent system.
- **Equity risk:** if platform design ignores device constraints, bandwidth limits, or administrative coordination, digital learning can widen rather than reduce educational inequality [7, 9].

These conditions shape the problem statement for Anhoc. A useful platform in Vietnam must not only digitize lessons; it must also provide structured practice, durable assessment records, scalable administration, and a child-friendly design that can stand out in a crowded and often repetitive learning-app landscape.

3 Objectives

This thesis has the following objectives:

- document the implemented Anhoc system in a thesis-style format;
- explain the architecture and data model used by the project;
- describe how the platform generates and evaluates mathematical exercises;
- analyze how authentication, authorization, and administration are handled;
- evaluate the strengths, limitations, and next steps of the current implementation.

4 Scope

The scope of this thesis is limited to the code and documentation available in the repository. It focuses on the currently implemented frontend, backend, database schema, and operational flows. The thesis does not claim to measure learning outcomes through classroom experimentation, because no such experimental dataset is included in the

repository. Evaluation is therefore based on software capabilities, system structure, and scenario-level validation.

5 Contributions of the Project

The implemented project contributes several concrete software ideas:

- a bilingual lesson structure for educational content in English and Vietnamese;
- a question-template model that supports variables, derived expressions, constraints, and multiple accepted formulas;
- persisted question snapshots that separate reusable templates from concrete attempt data;
- a progression model combining mastery, XP logs, levels, and achievements;
- a dynamic access-control model that separates actions, resources, and subject restrictions.

6 Thesis Structure

The remainder of this thesis is organized as follows. Chapter 2 presents the requirements and analysis of the project domain. Chapter 3 describes the system design, architecture, security model, and data model. Chapter 4 explains implementation details across the frontend, backend, and database layers. Chapter 5 evaluates the current solution through representative scenarios, strengths, and limitations. Chapter 6 concludes the thesis and outlines future work.

II/ OBJECTIVES

In this chapter, we outline the core functional requirements and design goals of the Anhoc platform. We specify the desired features across user roles and define the expected outcomes of the system implementation.

1 Desired Features

The main goal of the Anhoc project is to implement a structured, adaptive web-based mathematics learning platform with the following services:

- **FEATURE 1: Authentication & Role-Based Access Control**
 - **SUB-FEATURE 1.1: Registration & Login:** Allow new users to create accounts and sign in securely.
 - **SUB-FEATURE 1.2: Dynamic Authorization:** Restrict user actions (create, read, update, delete) based on active roles: Administrator, Supervisor, Teacher, Sub-student, and Free-student.
- **FEATURE 2: Learning & Content Management**
 - **SUB-FEATURE 2.1: Educational Hierarchy:** Organize content by Subjects (e.g., Mathematics), Grades, and Lessons.
 - **SUB-FEATURE 2.2: Bilingual Material:** Support side-by-side study in English and Vietnamese for lessons and practice.
- **FEATURE 3: Dynamic Question Generation & Persisted Snapshots**
 - **SUB-FEATURE 3.1: Question Templates:** Formulate templates with numeric variables, derived calculations, constraints, and multiple accepted answers.
 - **SUB-FEATURE 3.2: Attempt Snapshots:** Persist concrete variables and answers for every attempt to guarantee reproducible grading and review.
- **FEATURE 4: Student Progression & Gamification**
 - **SUB-FEATURE 4.1: Experience Points (XP):** Log XP rewards for practice and test submissions, updating student levels dynamically.
 - **SUB-FEATURE 4.2: Achievements:** Seed and unlock unique badges for completing lessons and scoring well.
- **FEATURE 5: Learn Units & Subscription Management**

- **SUB-FEATURE 5.1: Tenant Isolation:** Group users into Learn Units managed by a Supervisor.
- **SUB-FEATURE 5.2: Subscription Control:** Limit student and teacher slots based on Supervisor plan selections (Free, Pro, Family, Learning Center).
- **FEATURE 6: Interactive Tutoring Chatbot**
 - **SUB-FEATURE 6.1: Step-by-Step AI Guidance:** Embed an AI tutor chatbot capable of parsing mathematics and suggesting solution hints.
 - **SUB-FEATURE 6.2: BYOK Configuration:** Allow users to supply their own API keys to query LLM APIs.

2 Expected Outcome

The implementation aims to construct a production-ready mathematics education portal consisting of:

- A modern Next.js client interface that runs responsively across standard browsers (Chrome, Firefox, Safari) and handles student study, supervisor monitoring, and admin configuration.
- An Express server exposing structured REST endpoints for all data models.
- A PostgreSQL database instance configured with Prisma ORM for type-safe relational schemas.
- A companion Python chatbot microservice implementing conversational math tutoring.

III/ MATERIALS AND METHODS

In this chapter, we present the materials and methods used in the requirements engineering, architectural design, data modeling, and software implementation of the Anhoc platform.

1 Requirements Analysis

1.1 Stakeholders and User Roles

The primary stakeholders in Anhoc are students, administrators, and maintainers of the platform.

- Students consume learning content, complete exercises, take tests, and monitor progress.
- Administrators maintain educational content, templates, users, roles, and reports.
- Maintainers operate the deployment, database, and system configuration.

The codebase also distinguishes between global roles and subject-specific permissions. This is important because a role may have permission to manage some resources without necessarily having access to all subjects.

1.2 Functional Requirements

Table [3.1](#) summarizes the main functional requirements derived from the implementation.

Table 3.1: Core functional requirements

Area	Requirement
Authentication	The system shall allow user registration, login, profile retrieval, password change, and activity retrieval.
Lessons	The system shall support subject and grade organization, lesson listing, lesson detail retrieval, and lesson authoring by authorized users.
Practice	The system shall generate lesson-based practice attempts from reusable templates and store concrete snapshot records for each generated question.
Testing	The system shall create grade-level test attempts, support answer submission, and compute final scores on completion.
Templates	The system shall support creation, update, deletion, preview, reporting, and review of question templates.
Progression	The system shall track study time, mastery status, XP, levels, and achievements.
Administration	The system shall provide user, role, permission, subject-access, and dashboard management endpoints.

1.3 Use Case Model

Figure 3.1 summarizes the main interactions between the implemented role groups and the platform boundary. The repository defines five fixed application roles: **free_student**, **sub_student**, **teacher**, **supervisor**, and **admin**. A guest actor is also useful in the requirements model because registration and login begin before an authenticated role is established.




Figure 3.1: Use case diagram of the Anhoc platform

Student Use Case Model

The student represents the primary consumer of learning materials and gamified features on the platform. The requirements partition the student role into free students (**free_student**) and subscribed/premium students (**sub_student**). Both versions share the core learning loop, but premium students enjoy expanded access scopes and unlimited AI tutoring privileges. The student use case model comprises the following interactions:

- **UC-ST-01: Authentication and Profile Management** — Allows guests to register a new account, verify it via email, log in using password credentials or Google OAuth, log out, update their settings, customize avatars, and manage follow/unfollow relations with other students.
- **UC-ST-02: Content Browsing and Lesson Study** — Enables students to

browse through subjects, grades, and lessons, read bilingual content, and track study duration and mastery.

- **UC-ST-03: Lesson Practice and Grading** — Covers starting a practice attempt, submitting answers to generated questions, consuming lives, and reviewing practice attempts.
- **UC-ST-04: Grade-Level Testing** — Involves starting and completing comprehensive, timed assessments covering a whole grade when the student is eligible.
- **UC-ST-05: Classified Subject Access Request** — Allows students to submit requests to access subjects that are classified/restricted.
- **UC-ST-06: Interactive Tutoring Chatbot Consultation** — Involves opening the chatbot widget, asking for mathematical explanations, requesting hints, and viewing past chat logs.
- **UC-ST-07: Gamification Progression and Economy** — Covers tracking XP, leveling up, spending level points, completing daily quests, claiming streak rewards, buying shop items, and equipping cosmetics.
- **UC-ST-08: Play Math Games and Challenges** — Involves playing single-player or multiplayer math games, creating/joining challenge lobbies, and comparing scores on the leaderboard.
- **UC-ST-09: Subscription Upgrade** — Covers upgrading from a free tier to a premium subscription or moving into a supervisor account plan.

Teacher Use Case Model

The teacher is modeled as a scoped content manager. The application focuses on enabling teachers to author learning and practice content rather than managing class lists or student seating. The teacher use case model consists of:

- **UC-TE-01: Scoped Analytics Workspace** — Enables teachers to access their management dashboard to view analytics scoped strictly to the subjects and grades they are allowed to access.
- **UC-TE-02: Scoped Lesson Management** — Covers the creation, editing, and deletion of lessons inside their assigned subject scope.
- **UC-TE-03: Scoped Question Template Management** — Involves writing, editing, previewing, and deleting reusable question templates attached to lessons.
- **UC-TE-04: Organize Content Hierarchy** — Allows teachers to categorize topics and structure lessons under their assigned subjects and grades.

- **UC-TE-05: View Scoped Content & Testing Data** — Enables teachers to audit performance reports, error reports, and practice outcomes within their scope without having global administrative visibility.

Supervisor Use Case Model

A supervisor manages a localized cohort of users called a learn unit. A supervisor operates within strict resource capacity limits and handles subscriptions and billing. The supervisor use case model includes:

- **UC-SU-01: Learn Unit Registration & Seat Management** — Allows registering a new supervisor account or upgrading an existing profile, buying additional seat licenses, and reviewing billing invoices.
- **UC-SU-02: Manage Learn Unit Members** — Covers creating student and teacher credentials, viewing the roster, and allocating or revoking premium seats for members of their learn unit.
- **UC-SU-03: Manage Private Content & Resources** — Enables supervisors to author private subjects, grades, lessons, and question templates dedicated exclusively to their learn unit.
- **UC-SU-04: Organizational Limits Administration** — Involves monitoring and adhering to capacities for teachers, students, lessons, and templates defined by their subscription tier.

Administrator Use Case Model

Administrators possess system-wide control. They oversee all platform operations, manage global settings, and resolve user issues. The administrator use case model consists of:

- **UC-AD-01: Global User Administration** — Covers listing, creating, updating, deleting, and auditing all platform users, as well as reviewing detailed attempt history.
- **UC-AD-02: Access Control & Permissions Management** — Enables managing roles and permission-driven access rules.
- **UC-AD-03: Process Classified Subject Requests** — Covers reviewing, approving, or rejecting student requests to access classified subjects.
- **UC-AD-04: System Dashboard and Platform Stats** — Involves monitoring system-wide logs, database usage, and platform performance dashboard.

- **UC-AD-05: Manage Global Content Hierarchy** — Enables managing subjects, grades, lessons, and templates globally across the entire platform.
- **UC-AD-06: Review Question Reports** — Covers reviewing problem reports submitted by students on buggy question snapshots and marking them as resolved.
- **UC-AD-07: Configure Streaks and Achievements** — Involves setting up daily quest parameters, streak milestone rewards, achievement badges, and economic shop prices.
- **UC-AD-08: Oversee Supervisor Accounts** — Covers auditing supervisor learn units, billing statuses, and adjusting capacity limits on the user-management side.

1.4 Detailed Use Case Diagrams

The following subsections present a detailed use case diagram per functional subsystem, drawn using UML notation. Actors appear outside the system boundary rectangle. Ellipses represent use cases. Solid lines denote associations; dashed lines with open arrowheads denote «include» or «extend» relationships.

Authentication and Account Management




Figure 3.2: Use case diagram — Authentication and Account Management

Learning System




Figure 3.3: Use case diagram — Learning System

Practice and Assessment Engine




Figure 3.4: Use case diagram — Practice and Assessment Engine

AI Math Tutor Chatbot




Figure 3.5: Use case diagram — AI Math Tutor Chatbot

Gamification and Economy




Figure 3.6: Use case diagram — Gamification and Economy

Subscription and Payments




Figure 3.7: Use case diagram — Subscription and Payments

1.5 Use Case Descriptions

This subsection outlines detailed specifications for each of the use cases defined under the actor models.

UC-ST-01: Authentication and Profile Management

Primary actor	Guest, Student (<code>free_student</code> or <code>sub_student</code>)
Goal	Create an account, log in, manage profile, change password, upload avatar, and follow/unfollow peers.
Preconditions	The user has network connectivity. OAuth accounts require valid Google credentials.

Trigger	The user accesses registration, login, settings, or a peer's profile page.
Main flow	(1) User registers a new profile. (2) System sends activation link to email, which the user clicks to activate. (3) User logs in via credentials or Google OAuth. (4) System issues JWT session tokens with refresh rotation. (5) Student edits username, changes password, uploads avatar, or toggles follow status on a peer's profile.
Postconditions	A profile is created, a secure session is active, and settings or social links are updated.

UC-ST-02: Content Browsing and Lesson Study

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Browse grade roadmaps, read bilingual lesson content, and record study time.
Preconditions	Student is authenticated and possesses access permissions for the target subject.
Trigger	Student opens a subject roadmap or clicks a lesson card.
Main flow	(1) Student selects a grade and lesson. (2) Frontend requests lesson markdown from the backend. (3) Backend checks permissions and returns content from the database. (4) Frontend renders content with KaTeX. (5) Frontend tracks active reading time and sends heartbeats to log study duration.
Postconditions	Lesson content is displayed, and study duration is persisted in the database.

UC-ST-03: Lesson Practice and Grading

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Answer generated questions, view correctness feedback, and log practice results.
Preconditions	Student has at least one active life. Question templates exist for the lesson.
Trigger	Student clicks "Start Practice" on a lesson page.

Main flow	(1) System consumes one life from student. (2) System generates question snapshots using template variables. (3) Student answers questions one by one. (4) System evaluates answers, tracks correctness, and computes scores. (5) System rewards XP/coins, and updates the student's mastery record.
Postconditions	Practice attempt is saved, lives and coins balances are updated, and achievements are checked.

UC-ST-04: Grade-Level Testing

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Assess understanding of a whole grade level through a timed comprehensive test.
Preconditions	Student is authenticated and has unlocked testing eligibility for the grade.
Trigger	Student starts the test on the testing dashboard.
Main flow	(1) System compiles question templates across all grade lessons. (2) System generates question snapshots and starts a countdown timer. (3) Student completes and submits answers. (4) System grades the test, updates test attempt status, and calculates final scores.
Postconditions	The test attempt is stored, and grade-level test results are logged.

UC-ST-05: Classified Subject Access Request

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Submit a request to access classified or restricted subjects.
Preconditions	Student is authenticated.
Trigger	Student attempts to open a restricted subject and clicks "Request Access".
Main flow	(1) Student submits an access request detailing justification. (2) Frontend posts request data to the backend. (3) Backend stores request as pending administrator review.

Postconditions	The request is queued in the system database for administrator approval.
-----------------------	--

UC-ST-06: Interactive Tutoring Chatbot Consultation

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Interact with the chatbot for math explanations, hints, and checks on formulas.
Preconditions	Student is authenticated. Free students require active chatbot credits.
Trigger	Student opens the tutoring chatbot widget.
Main flow	(1) Student inputs a question. (2) Chatbot parses mathematical syntax. (3) Computations are solved by SymPy; textual reasoning is handled by Gemini LLM. (4) Chatbot returns a hint or step-by-step math explanation. (5) Chat history is recorded in MongoDB.
Postconditions	The response is rendered, and chatbot credits or histories are updated.

UC-ST-07: Gamification Progression and Economy

Primary actor	Student (<code>free_student</code> / <code>sub_student</code>)
Goal	Track level/XP progress, spend level points, buy shop items, and equip profile cosmetics.
Preconditions	Student is authenticated. Shop purchases require sufficient coin balances.
Trigger	Student visits the dashboard, shop, or profile menu.
Main flow	(1) Student views streaks, daily quests, and level progress. (2) Student buys titles, borders, themes, or streak shields using Ancoins. (3) Student spends level points to boost XP/coin rates or increase max lives. (4) Student equips titles or cosmetics.
Postconditions	Coins/points are deducted, items are unlocked, and cosmetic changes are applied.

UC-ST-08: Play Math Games and Challenges

Primary actor	Student (free_student / sub_student)
Goal	Play math games, create/share duels, join challenges, and view game leaderboards.
Preconditions	Student is authenticated.
Trigger	Student navigates to the game section or joins a challenge.
Main flow	(1) Student launches a game mode. (2) Student answers questions under time limits. (3) System saves score and updates the leaderboard. (4) For challenges, student creates a duel lobby, shares the code, and plays against peers.
Postconditions	Game attempt is recorded, and placement on leaderboards is updated.

UC-ST-09: Subscription Upgrade

Primary actor	Student (free_student)
Goal	Upgrade to premium subscription tier or supervisor account.
Preconditions	Student is authenticated.
Trigger	Student selects a plan on the subscription screen.
Main flow	(1) Student selects plan. (2) Frontend redirects to Stripe checkout. (3) Student submits payment information. (4) Stripe processes payment and fires webhook. (5) System upgrades user role.
Postconditions	User is upgraded to premium status (sub_student or supervisor).

UC-TE-01: Scoped Analytics Workspace

Primary actor	Teacher
Goal	Access management workspace dashboard for scoped content analytics.
Preconditions	Teacher is authenticated with scoped workspace permissions.
Trigger	Teacher logs in and opens the management workspace.

Main flow	(1) System checks teacher's subject scope from their profile constraints. (2) System aggregates practice logs and error reports corresponding to the scoped subjects. (3) Workspace renders charts showing success rates and active templates.
Postconditions	Scoped analytics are displayed without exposing global administrative dashboards.

UC-TE-02: Scoped Lesson Management

Primary actor	Teacher
Goal	Create, edit, and delete lessons under authorized subjects and grades.
Preconditions	Teacher has write permission for the specific subject/grade.
Trigger	Teacher initiates a CRUD operation on a lesson.
Main flow	(1) Teacher edits the lesson title, chapter association, and markdown-based bilingual content. (2) Teacher saves changes. (3) System verifies permissions and updates the lesson record.
Postconditions	Lesson changes are persisted in PostgreSQL and cached in Redis.

UC-TE-03: Scoped Question Template Management

Primary actor	Teacher
Goal	Create, edit, preview, and delete question templates.
Preconditions	Teacher has write permission for the lesson's parent subject/grade.
Trigger	Teacher selects template manager.
Main flow	(1) Teacher writes parameter bindings, math constraints, and answer definitions in JSON. (2) Teacher triggers preview to test the generation logic and evaluate equations. (3) Teacher saves the question template.
Postconditions	Question templates are validated and saved to the database.

UC-TE-04: Organize Content Hierarchy

Primary actor	Teacher
Goal	Organize learning content under available subjects/grades.
Preconditions	Teacher has content organizational permissions.
Trigger	Teacher modifies lesson structure or topic ordering.
Main flow	(1) Teacher assigns topics to lessons or orders chapters. (2) System validates that the parent subjects are within the teacher's allowed scope. (3) System persists the new layout.
Postconditions	Lessons and chapters are restructured under grades.

UC-TE-05: View Scoped Content & Testing Data

Primary actor	Teacher
Goal	Review performance statistics and error reports for templates within scope.
Preconditions	Teacher is authenticated.
Trigger	Teacher inspects question performance page.
Main flow	(1) System fetches aggregated question attempt logs matching the teacher's scope. (2) Teacher reviews success rates and reports to identify problematic templates.
Postconditions	Analytics reports are loaded.

UC-SU-01: Learn Unit Registration & Seat Management

Primary actor	Supervisor
Goal	Register supervisor account, establish learning unit, purchase seat licenses, and manage billing.
Preconditions	Supervisor is authenticated.
Trigger	User clicks "Create Supervisor Plan" or accesses billing options.
Main flow	(1) User registers or upgrades to supervisor. (2) System initializes a unique Learn Unit. (3) Supervisor purchases seat allocations via Stripe billing portal. (4) System updates available seats count on the supervisor dashboard.

Postconditions	Seat licensing levels are updated, and Stripe invoices are stored.
-----------------------	--

UC-SU-02: Manage Learn Unit Members

Primary actor	Supervisor
Goal	Create student/teacher accounts within the learn unit, and assign or revoke premium seats.
Preconditions	Supervisor is authenticated and has free seat licenses.
Trigger	Supervisor opens the member roster view.
Main flow	(1) Supervisor creates a member credentials profile. (2) Supervisor assigns a paid premium seat to the member. (3) System flags member account as premium and reduces the available seat count. (4) Supervisor can revoke premium seats, returning them to the unit pool.
Postconditions	Member accounts are created and seat allocations are sync'd.

UC-SU-03: Manage Private Content & Resources

Primary actor	Supervisor
Goal	Create and manage private subjects, grades, lessons, and templates for learn unit members.
Preconditions	Supervisor is authenticated and learn unit limits allow content creation.
Trigger	Supervisor accesses the private workspace.
Main flow	(1) Supervisor creates custom, private lessons and templates visible only to members of their learn unit. (2) System checks capacity limits (subjects count, lessons count) before persisting.
Postconditions	Private learning materials are saved in PostgreSQL with a learn unit foreign key.

UC-SU-04: Organizational Limits Administration

Primary actor	Supervisor
----------------------	------------

Goal	Monitor and control capacity limits for teachers, students, and templates within the learn unit.
Preconditions	Supervisor is authenticated.
Trigger	Supervisor views the organization dashboard.
Main flow	(1) Supervisor checks resource gauges showing current vs. maximum limits. (2) Supervisor allocates resources or disables inactive student accounts to fit limits.
Postconditions	Resource utilization settings are adjusted.

UC-AD-01: Global User Administration

Primary actor	Administrator
Goal	Manage all system users, inspect profiles, view progress/attempt history, and adjust roles.
Preconditions	Admin is authenticated.
Trigger	Admin opens the user management console.
Main flow	(1) Admin lists, searches, or updates any user profile. (2) Admin inspects detailed practice attempts, scores, and XP logs. (3) Admin updates user active status or deletes account.
Postconditions	User accounts are updated or purged.

UC-AD-02: Access Control & Permissions Management

Primary actor	Administrator
Goal	Configure role structures and action/resource-level permissions.
Preconditions	Admin is authenticated.
Trigger	Admin accesses permission settings.
Main flow	(1) Admin inspects existing RBAC configurations. (2) Admin adjusts permissions associated with system roles.
Postconditions	Role permissions are updated and cached in Redis.

UC-AD-03: Process Classified Subject Requests

Primary actor	Administrator
Goal	Review access requests for classified subjects and approve or reject them.
Preconditions	Access requests exist in the inbox.
Trigger	Admin opens requests inbox.
Main flow	(1) Admin inspects student justifications. (2) Admin selects approve to grant custom subject permissions, or reject to deny. (3) System updates request record and grants subject access.
Postconditions	Subject permission changes are updated.

UC-AD-04: System Dashboard and Platform Stats

Primary actor	Administrator
Goal	View global system analytics, database sizes, and platform-wide statistics.
Preconditions	Admin is authenticated.
Trigger	Admin accesses main dashboard.
Main flow	(1) System compiles system-wide statistics (revenue, users count, attempt rates, chatbot usage). (2) Dashboard renders aggregate analytical reports.
Postconditions	Global metrics are displayed.

UC-AD-05: Manage Global Content Hierarchy

Primary actor	Administrator
Goal	Create, edit, and delete all subjects, grades, lessons, and templates globally.
Preconditions	Admin is authenticated.
Trigger	Admin accesses global content panels.
Main flow	(1) Admin modifies or deletes any public subject, grade, lesson, or question template. (2) System overrides any scoped rules and writes directly to PostgreSQL.
Postconditions	Global content structure is updated.

UC-AD-06: Review Question Reports

Primary actor	Administrator
Goal	Review error reports submitted by learners for generated questions and update report status.
Preconditions	Reports are submitted.
Trigger	Admin opens the reports dashboard.
Main flow	(1) Admin reviews student report description and question snapshot. (2) Admin fixes the source template or marks the report as resolved/rejected.
Postconditions	Report status is updated.

UC-AD-07: Configure Streaks and Achievements

Primary actor	Administrator
Goal	Configure streak rewards, daily quests, and achievement-related milestones.
Preconditions	Admin is authenticated.
Trigger	Admin opens gamification configuration.
Main flow	(1) Admin updates weekly streak reward tables or level threshold configurations. (2) System registers changes.
Postconditions	Gamification engine constants are updated.

UC-AD-08: Oversee Supervisor Accounts

Primary actor	Administrator
Goal	Inspect supervisor learn units, billing status, and manually adjust capacities.
Preconditions	Admin is authenticated.
Trigger	Admin accesses supervisor settings page.
Main flow	(1) Admin views learn unit listing. (2) Admin manually overrides capacities and limits (e.g. max seats, private template limits).
Postconditions	Supervisor limits are altered.

1.6 Non-Functional Requirements

The repository implies the following non-functional requirements:

- **Modularity:** frontend, backend, persistence, and progression logic should remain separable.

- **Consistency:** generated questions must remain stable after creation so that grading and reporting are reproducible.
- **Security:** protected endpoints require JWT-based authentication and permission checks.
- **Extensibility:** roles, actions, resources, and subject restrictions should be data-driven rather than hard-coded.
- **Deployability:** the architecture should run in a common cloud arrangement using Vercel, Render, and Neon.

In addition to these technical qualities, the platform should satisfy learner-centered non-functional requirements related to pacing, clarity, and healthy engagement.

Requirement	Description	Evaluation Method
Medium-paced interaction	The interface shall maintain a moderate interaction pace, avoiding excessive animations, rapid reward loops, or constant interruptions that encourage compulsive use, while remaining more engaging than a traditional LMS.	Inspect interaction flows and count forced interruptions, auto-triggered animations, and reward prompts during a standard lesson or practice session.
Learning-first design	Gamification shall reinforce learning objectives rather than distract from educational content.	Review representative screens and verify that rewards, badges, and progress indicators appear after or alongside meaningful learning actions rather than replacing them.

Cognitive load management	Only essential information shall be displayed at any given time to minimize cognitive overload.	Conduct heuristic UI review of lesson and practice screens to confirm that only task-relevant controls, text, and feedback are visible at each step.
Progressive disclosure	Advanced features and statistics should appear only when relevant to the learner's current progress.	Test beginner and advanced user paths to verify that detailed statistics, secondary controls, and optional features appear only in appropriate contexts.
Encouraging feedback	Feedback should motivate learners after mistakes without creating unnecessary frustration.	Review incorrect-answer states and error messages to confirm that wording is constructive, specific, and oriented toward retry or improvement.

Healthy reward frequency	Rewards should be meaningful and tied to learning milestones rather than every interaction, reducing reward dependency.	Trace reward events across practice, lessons, and achievements to confirm that rewards are linked to completion, mastery, or milestone progress rather than every click or answer.
Session continuity	Learners should be able to pause and resume activities without losing progress.	Execute pause, refresh, logout, and return scenarios for lessons and practice attempts, then verify that saved state and progress are restored correctly.
Minimal interruption	Pop-ups, notifications, and animations should not interrupt active learning tasks unless necessary.	Perform task-based walkthroughs and record whether notifications, modals, or visual effects block reading or answering without a clear functional reason.

1.7 Learning Content Requirements

Educational content in Anhoc is organized around a hierarchy of subjects, grades, and lessons. Lessons contain bilingual titles and markdown-based content bodies. This leads to several domain requirements:

- one lesson belongs to one grade and one subject;

- lesson content should be readable in more than one language;
- practice content should be attached to lessons through question templates rather than embedded into the lesson body itself;
- progress should be measurable at the lesson level.

1.8 Assessment Requirements

Assessment in the project has two modes:

- lesson-based practice for targeted repetition;
- grade-level tests for broader assessment across available lesson templates.

The assessment subsystem must support question generation, answer submission, correctness evaluation, score calculation, and post-completion progression updates. The implementation also needs to distinguish between theoretical questions and computed math questions because the grading strategy differs between those two cases.

1.9 Administrative Requirements

Administrative functionality in Anhoc goes beyond simple content editing. The platform must manage:

- users and their assigned roles;
- permissions by action and resource;
- subject-level restrictions per role;
- dashboard statistics and user insights;
- reports submitted for problematic generated questions.

This requirement set justifies the presence of a dynamic RBAC model instead of a fixed boolean admin flag.

1.10 Operational Assumptions

The codebase assumes a web-first deployment model:

- the frontend is delivered as a Next.js application;
- the backend exposes REST endpoints under `/api/v1`;
- PostgreSQL is the source of truth for transactional and analytical learning data;

- environment variables define API URLs, CORS origins, JWT secret material, and achievement seeding behavior.

These assumptions shape the rest of the architecture described in the next chapter.

2 System Design

2.1 Architectural Overview

Anhoc uses a three-tier web architecture. A Next.js frontend built on React provides the user interface. An Express backend exposes REST endpoints and business logic. PostgreSQL stores content, user identities, generated snapshots, and progression data. Prisma acts as the ORM boundary between the backend and the database [10, 11, 12, 13, 14].




Figure 3.8: Architecture design of the Anhoc platform

At a high level, the request flow is:

1. the browser interacts with the Next.js frontend;
2. the frontend calls backend routes under /api/v1;
3. the backend validates identity and permissions;

4. business services coordinate data access and progression updates;
5. PostgreSQL persists authoritative state.

2.2 Deployment Design

The repository documents a practical deployment split:

- Vercel hosts the frontend runtime;
- Render hosts the Node.js API;
- Neon provides PostgreSQL infrastructure.

This split is appropriate for a full-stack TypeScript project because it separates the static or server-rendered frontend from the API runtime and keeps the relational database independent of either application tier.

2.3 Backend Design

The backend entry point is `backend/server.ts`. It initializes Express, configures CORS, enables JSON parsing, mounts route modules, exposes a health endpoint, and conditionally seeds achievements at startup. The route structure is organized by domain:

- `auth.ts` for identity, login, and profile operations;
- `lessons.ts` for educational content and practice initiation;
- `tests.ts` for attempts, answer submission, template management, and reports;
- `admin.ts` for users, roles, access control, and statistics;
- `achievements.ts` for achievement retrieval and re-evaluation.

This separation keeps HTTP concerns close to route boundaries while pushing calculation-heavy logic into services.

2.4 Frontend Design

The frontend is built with Next.js using an app-router structure under `frontend/src/app`. It includes separate areas for authentication, student flows, and administration. The frontend is supported by Axios-based service modules, Redux state for authentication and permissions, and feature-specific components such as lesson cards, question players, result modals, and achievement galleries. The repository also uses `next-intl`

for localized dictionaries and request-scoped internationalization in the App Router [15].

From a design perspective, the frontend acts as an orchestration layer:

- it collects user input and triggers backend operations;
- it renders lesson, practice, test, and admin views;
- it persists authentication tokens in browser storage and cookies;
- it enforces route-level and component-level access decisions using the permission payload returned by the backend.

2.5 Security Model

Authentication is handled with JWT bearer tokens. The middleware in `backend/middleware/auth.ts` extracts the token from the `Authorization` header, verifies it using the configured secret, and attaches the decoded payload to the request object [16, 17].

Authorization is layered on top of authentication. The project uses:

- role identity for coarse-grained decisions;
- grouped resource permissions for action checks;
- subject-level role restrictions for scoped access;
- helper middleware such as `isAdmin` and `selfOrAdmin`.

The design choice to keep permissions data-driven is significant. It allows new resources and actions to be introduced through database records and route logic instead of forcing the codebase into a rigid two-role system.

2.6 Data Model

The database schema in `backend/prisma/schema.prisma` defines the educational, assessment, and progression domain. Table 3.2 summarizes the most important entities.

Table 3.2: Main persistent entities

Entity	Purpose
<code>users</code>	Stores account identity and links to roles, attempts, mastery, achievements, and statistics.

Entity	Purpose
roles, actions, resources, role_permissions	Implements dynamic role-based access control.
subjects, grades, lessons	Represents the educational content hierarchy.
question_templates	Stores reusable question definitions and logic.
test_attempts	Stores headers for practice and test sessions.
question_snapshots	Stores concrete generated questions bound to attempts.
user_lesson_mastery	Stores lesson-level progress and completion status.
student_stats, xp_logs	Stores aggregate progression state and XP history.
achievements, user_achievements	Stores gamification rewards and earned records.
question_template_ reports	Stores reports for problematic questions.
audit_logs, activity_evidence	Supports traceability and evidence collection.

2.7 Entity-Relationship Diagrams

The following diagrams use a simplified ERD notation. Each entity is a rectangle with its name in the header row and its key attributes listed below. Lines between entities carry crow's foot cardinality markers: `||` for exactly one, `o|` for zero-or-one, `o{` for zero-or-many, `|{` for one-or-many. Primary keys are marked **PK**; foreign keys are marked **FK**.

ERD Group 1 — User and Authentication




Figure 3.9: ERD Group 1 — User & Authentication tables

This group contains the core identity and access control entities. Every other table in the schema references **users** as its ultimate root.

Table: users The central entity of the entire platform. Each row represents one registered account.

Column	Type	Description
id	UUID (PK)	Auto-generated primary key using <code>gen_random_uuid()</code> .
username	VARCHAR(50)	Unique display name chosen at registration.
email	VARCHAR(255)	Unique email address; used for login and notifications.
password_hash	TEXT	bcrypt hash of the user's password. Never stored in plaintext.
account_status	VARCHAR(20)	Lifecycle state: active , pending , suspended , or deleted .
role_id	INT (FK)	References roles.id ; determines permissions via RBAC.
learn_unit_id	UUID (FK, null)	References learn_units.id ; set for group-plan members.
stripe_customer_id	TEXT (unique, null)	Stripe customer identifier; set on first checkout.
active_session_id	TEXT (null)	UUID of the current valid session; rotated on every login for single-session enforcement.
avatar_url	VARCHAR(255)	URL of the active equipped avatar image.
first_name, last_name	VARCHAR(100)	Optional display name components.
created_at	TIMESTAMPTZ	Account creation timestamp.

Table: user_securities One-to-one extension of **users** holding all sensitive security metadata. Separated from the main users table to avoid loading security data on every profile read.

Column	Type	Description
user_id	UUID (PK/FK)	References users.id with CASCADE delete.
email_verification_token	VARCHAR(255)	Time-limited signed token sent in the activation email.

email_verified_at	TIMESTAMPZ	Timestamp of successful email verification; null if unverified.
failed_login_attempts	INT	Counter reset to zero on successful login.
lockout_until	TIMESTAMPZ	If set, login is blocked until this timestamp (account lockout).
password_reset_token	VARCHAR(255)	Signed reset token; cleared after use or expiry.
password_reset_sent_at	TIMESTAMPZ	Throttle timestamp to prevent reset email flooding.

Table: refresh_tokens Stores active refresh tokens issued during login. A user may have multiple rows (e.g. across devices), but single-session enforcement via `active_session_id` invalidates all but the latest.

Column	Type	Description
id	UUID (PK)	Row identifier.
token	TEXT (UNIQUE)	The opaque refresh token string stored in the <code>HttpOnly</code> cookie.
user_id	UUID (FK)	Owner of this token. CASCADE deleted with the user.
expires_at	TIMESTAMPZ	Hard expiry; token is rejected after this even if not revoked.
revoked_at	TIMESTAMPZ (null)	Set when the token is explicitly invalidated (logout or rotation).

Table: oauth_accounts Stores OAuth2 identity links for social login providers (Google, etc.). One user may link multiple providers.

Column	Type	Description
id	UUID (PK)	Row identifier.
user_id	UUID (FK)	References <code>users.id</code> .
provider	VARCHAR(50)	Provider name, e.g. <code>google</code> , <code>facebook</code> .
provider_user_id	VARCHAR(255)	The unique user ID within the external provider's system.

Table: roles and role_permissions Implement the Role-Based Access Control (RBAC) model. Each role has a set of (`action`, `resource`) permission pairs. Mid-

dleware checks these at runtime for every protected route.

ERD Group 2 — Curriculum and Content




Figure 3.10: ERD Group 2 — Curriculum & Content tables

This group models the three-level curriculum hierarchy: Subject → Grade → Lesson → Question Template.

Table: subjects Top-level subject classification (e.g. Mathematics, Physics).

Column	Type	Description
id	INT (PK)	Auto-increment integer key.
slug	VARCHAR(50)	Unique display name chosen at registration.
title_en / title_vi	VARCHAR(100)	Bilingual display names.
is_classified	BOOLEAN	If true, access requires an approved <code>user_subject_access_request</code> .

color	VARCHAR(20)	Hex colour for UI theming of this subject.
created_by	UUID (FK, null)	Administrator who created the subject.

Table: grades Represents a school year/grade within a subject (e.g. “Grade 6 Mathematics”).

Column	Type	Description
id	INT (PK)	Auto-increment key.
slug	VARCHAR(50)	URL-safe grade identifier, e.g. grade-6 .
subject_id	INT (FK, null)	Parent subject.
title_en / title_vi	VARCHAR(100)	Bilingual grade titles.

Table: lessons The core content entity. Each lesson belongs to one grade and one subject, and contains full bilingual theory text in Markdown format.

Column	Type	Description
id	UUID (PK)	Row identifier.
grade_id	INT (FK)	Parent grade.
subject_id	INT (FK)	Parent subject (denormalised for fast filtering).
title_en / title_vi	VARCHAR(255)	Bilingual lesson titles, displayed on the roadmap.
content_markdown_en / vi	TEXT	Full theory content in Markdown with embedded KaTeX.
order_index	INT (null)	Display ordering within the grade roadmap.
is_premium	BOOLEAN	If true, only subscribers can view the full content.
updated_at	TIMESTAMPTZ	Last content update; used to invalidate Redis caches.

Table: question_templates Parameterised question blueprints. At practice time, numeric parameters are instantiated from the `logic_config` ranges and the ground-truth answer is computed by SymPy from `accepted_formulas`.

Column	Type	Description
--------	------	-------------

id	UUID (PK)	Row identifier.
lesson_id	UUID (FK, null)	Associated lesson; null for topic-level free questions.
template_type	VARCHAR(50)	Category, e.g. <code>multiple_choice</code> , <code>open_input</code> .
difficulty	VARCHAR(20)	One of: <code>easy</code> , <code>medium</code> , <code>hard</code> .
body_template_en / vi	TEXT	Question text with <code>{{a}}</code> , <code>{{b}}</code> parameter placeholders.
logic_config	JSON	Parameter ranges and types, e.g. <code>{"a": [2,20], "b": [1,9]}</code> .
accepted_formulas	TEXT[]	SymPy expression strings to compute the correct answer.
tags	TEXT[]	Topic tags for filtering and adaptive selection.

Table: `user_subject_access_requests` Students request access to classified subjects. Administrators approve or reject via the admin panel.

ERD Group 3 — Practice, Tests and Progress




Figure 3.11: ERD Group 3 — Practice, Tests & Progress tables

This group maintains records of active studies, completed lessons, test score achievements, and audit logs.

Table: test_attempts Records every practice session or grade test attempt. The `is_practice` flag distinguishes practice runs from formal tests.

Column	Type	Description
--------	------	-------------

id	UUID (PK)	Attempt identifier.
user_id	UUID (FK, null)	Null for anonymous guest game attempts.
lesson_id	UUID (FK, null)	Lesson context; null for grade-level tests.
total_score	DECIMAL(5,2)	Percentage score, computed on completion.
is_practice	BOOLEAN	True for lesson practice; false for grade tests.
is_completed	BOOLEAN	Set to true when the student submits or the timer expires.
started_at	TIMESTAMPTZ	Session start time (used for speed calculation).
completed_at	TIMESTAMPTZ	Session end time. Duration = <code>completed_at - started_at</code> .

Table: question_snapshots One row per question per attempt. Captures the instantiated parameter values, the student’s answer, and the ground-truth answers at the time of the attempt (immutable record for audit purposes).

Column	Type	Description
id	UUID (PK)	Snapshot identifier.
attempt_id	UUID (FK, null)	Parent attempt. CASCADE deleted.
template_id	UUID (FK, null)	Source template (SET NULL on template deletion for history).
generated_variables	JSON	E.g. <code>{"a": 7, "b": 3}</code> — the random values used for this instance.
student_answer	TEXT (null)	The answer submitted by the student.
right_answers	TEXT[]	Array of accepted correct answer strings at generation time.
is_correct	BOOLEAN	Whether <code>student_answer</code> matches any element of <code>right_answers</code> .
points_earned	INT	Points scored (0 or configured per-template value).

Table: user_lesson_mastery Composite-primary-key junction tracking each student’s cumulative performance per lesson. Updated atomically on every attempt completion.

Column	Type	Description
user_id	UUID (PK/FK)	Composite PK component. References <code>users.id</code> .
lesson_id	UUID (PK/FK)	Composite PK component. References <code>lessons.id</code> .
mastery_score	DECIMAL(5,2)	Rolling weighted-average performance score (0–100).
total_study_time	INT	Cumulative seconds spent on the lesson's reading sessions.
total_test_time	INT	Cumulative seconds spent on this lesson's practice attempts.
completion_status	VARCHAR	One of: <code>not_started</code> , <code>in_progress</code> , <code>completed</code> . Drives the roadmap badge.

Table: `learning_sessions` and `question_template_reports` `learning_sessions` stores each discrete reading duration to measure study metrics. `question_template_reports` lets students flag issues with question accuracy, linking templates, snapshots, and logs for review.

ERD Group 4 — Gamification and Economy




Figure 3.12: ERD Group 4 — Gamification & Economy tables

This group maintains points, levels, items, streak configurations, daily quest targets, and earned achievements.

Table: `student_stats` One-to-one extension of `users` holding the student’s entire gamification state. Kept separate from `users` to avoid locking the user row on every XP award transaction.

Column	Type	Description
<code>user_id</code>	UUID (PK/FK)	One-to-one with <code>users</code> .
<code>total_xp</code>	INT	Cumulative experience points earned.
<code>level</code>	INT	Current level, derived from <code>total_xp</code> against the levelling formula.
<code>average_score</code>	DECIMAL(5,2)	Rolling average across all practice attempts.
<code>lives</code>	INT	Current number of lives (1 consumed per practice attempt).
<code>last_life_restored_at</code>	TIMESTAMPTZ	Timestamp of last hourly life restore; drives the restore scheduler.
<code>coins</code>	INT	Current Ancoin balance.
<code>level_points</code>	INT	Unspent attribute points earned on level-up.
<code>inventory</code>	JSON	Map of owned shop item holdings.
<code>equipped_items</code>	JSON	Map of currently active cosmetic items.
<code>upgrades</code>	JSON	Map of purchased permanent upgrades.

Table: `xp_logs` Immutable append-only log of every XP award event. Used for the XP history view and for audit purposes.

Column	Type	Description
<code>user_id</code>	UUID (FK)	The student who received the XP.
<code>amount</code>	INT	XP delta awarded.
<code>reason</code>	VARCHAR(100)	Human-readable label (e.g. <code>practice_complete</code>).
<code>occurred_at</code>	TIMESTAMPTZ	Timestamp of award event.

Table: `user_streaks`, `achievements`, `themes`, `user_daily_quests` Tracks continuous engagement records, custom variable sets for light/dark CSS styles, badges

catalogued by milestones, and recurring daily quest logs designed to reward incremental student learning.

ERD Group 5 — Subscriptions, Gaming and Notifications




Figure 3.13: ERD Group 5 — Subscriptions, Gaming and Notifications

This group governs subscription limits, Stripe transactions, challenges/attempts in multiplayer gaming, and system-wide notifications.

Table: plans Master catalogue of subscription plans (e.g. Free, Pro, Family). Stores base pricing in both monthly and annual cycles, plus per-unit pricing multipliers for flexible enterprise pricing.

Column	Type	Description
id	INT (PK)	Auto-increment plan identifier.
name	VARCHAR(50)	Internal slug: <code>free</code> , <code>pro</code> , <code>family</code> , <code>learning_center</code> .
vi_name / en_name	VARCHAR(100)	Bilingual marketing display names.
price_monthly / annually	DECIMAL(10,2)	Base price per billing cycle.
max_students / teachers / lessons	INT (null)	Feature usage caps; null means unlimited.
effect_from / effect_to	TIMESTAMP TZ	Validity window enabling time-based pricing changes without deleting old plans.

Table: subscription_plans Each row is one active or historical subscription instance for a user. The `stripe_subscription_id` links to the Stripe subscription object for synchronisation via webhooks.

Column	Type	Description
id	UUID (PK)	Subscription instance identifier.
user_id	UUID (FK)	Subscriber.
plan_id	INT (FK)	References <code>plans.id</code> .
status	VARCHAR(20)	One of: <code>active</code> , <code>cancelled</code> , <code>expired</code> , <code>superseded</code> .
billing_cycle	VARCHAR(20)	<code>monthly</code> or <code>annually</code> .
auto_renew	BOOLEAN	Whether Stripe should attempt renewal at period end.
stripe_subscription_id	TEXT (UNIQUE)	Stripe object ID, used for webhook upsert matching.
max_students / lessons / grades	INT (null)	Custom limits captured at check-out time for per-seat enterprise plans.

Table: game_challenges A competitive battle session created by a student. The `code` field is a short shareable room code. The `config` JSON stores the pre-generated question set for the challenge to ensure all participants answer the same questions.

Column	Type	Description
id	UUID (PK)	Challenge identifier.
code	VARCHAR(10) (UNIQUE)	Short room code shared with opponents.
game_type	VARCHAR(50)	Battle mode variant: speed , climb , match .
grade_id / lesson_id	FK (null)	Scope of the challenge questions.
created_by	UUID (FK)	Creator; also the host.
is_active	BOOLEAN	Set to false when the challenge ends.
config	JSON	Frozen question set for this challenge instance.

Table: invoices, game_attempts, notifications, audit_logs Stores Stripe transactions, battle participation logs (including guests), polymorphic system-wide alerts, and immutable logs detailing sensitive admin actions or critical events.

Schema Summary

Table 3.3: Complete Database Schema — Table Summary (38 tables)

Table	Group	Purpose
users	Auth	Core user account entity
user_securities	Auth	Security tokens, logout state
refresh_tokens	Auth	JWT refresh token store
oauth_accounts	Auth	Social login provider links
roles	Auth	RBAC role definitions
actions / resources	Auth	RBAC action and resource catalogue
role_permissions	Auth	Role $\times$ Action $\times$ Resource permission matrix
learn_units	Auth	Group subscription unit (supervisor + members)
subjects	Curriculum	Subject top-level catalogue
grades	Curriculum	Grade/year level within a subject
lessons	Curriculum	Theory content pages with bilingual Markdown
question_templates	Curriculum	Parameterised question blueprints

user_subject_access_requests	Curriculum	Access approval workflow for classified subjects
role_subject_permissions	Curriculum	Subject-level permission overrides per role
user_learning_profiles	Curriculum	Preferred subject stored per student
test_attempts	Practice	Practice or test session record
question_snapshots	Practice	Per-question instantiated attempt record
user_lesson_mastery	Practice	Cumulative per-lesson performance state
learning_sessions	Practice	Reading session time log
activity_evidence	Practice	Uploaded evidence images per attempt
question_template_reports	Practice	Student-flagged question error reports
student_stats	Gamification	XP, level, lives, coins, inventory, upgrades
xp_logs	Gamification	Immutable XP event ledger
achievements	Gamification	Achievement definition catalogue
user_achievements	Gamification	Student $\times$ Achievement unlock junction
themes	Gamification	CSS variable theme definitions
user_streaks	Gamification	Per-student streak state
streak_rewards	Gamification	Admin-configured milestone reward definitions
user_streak_reward_claims	Gamification	Anti-double-claim claim ledger
user_daily quests	Gamification	Daily generated quests per student
user_follows	Social	Student follow relationships
notifications	System	Polymorphic notification store
audit_logs	System	Append-only system event log
plans	Subscription	Subscription plan catalogue
subscription_plans	Subscription	Per-user subscription instances
invoices	Subscription	Billing event records
game_challenges	Gaming	Battle session definitions
game_attempts	Gaming	Per-player battle participation records

2.8 Question Snapshot Strategy

One of the strongest design decisions in Anhoc is the separation between `question_templates` and `question_snapshots`. Templates describe how a question can be generated. Snapshots record the exact generated variables, accepted answers, student response, correctness result, and awarded points for one attempt.

This decision solves several engineering problems:

- a generated question does not change after the student starts an attempt;
- grading can be reproduced later without regenerating random variables;
- question reporting can refer to a concrete faulty instance rather than an abstract template;
- analytics can distinguish between template quality and attempt outcomes.

2.9 Progression Design

Progression in Anhoc is not limited to a final score. The backend updates several layers of state:

- lesson mastery based on lesson-linked practice results;
- XP logs for additive progression history;
- aggregate student statistics for dashboards and profile displays;
- achievements that can also grant extra XP.

2.10 Sequence Diagrams for Main Use Cases

2.11 Sequence Diagrams for Main Use Cases

The following sequence diagrams refine the 26 use cases introduced in the requirements chapter and map them to the implemented frontend, backend routing, service, and data layers of the Anhoc platform.


UC-ST-01: Authentication and Profile Management

Figure 3.14: Sequence diagram for UC-ST-01: Authentication and Profile Management


UC-ST-02: Content Browsing and Lesson Study

Figure 3.15: Sequence diagram for UC-ST-02: Content Browsing and Lesson Study

UC-ST-03: Lesson Practice and Grading




Figure 3.16: Sequence diagram for UC-ST-03: Lesson Practice and Grading

UC-ST-04: Grade-Level Testing




Figure 3.17: Sequence diagram for UC-ST-04: Grade-Level Testing


UC-ST-05: Classified Subject Access Request

Figure 3.18: Sequence diagram for UC-ST-05: Classified Subject Access Request

UC-ST-06: Interactive Tutoring Chatbot Consultation




Figure 3.19: Sequence diagram for UC-ST-06: Interactive Tutoring Chatbot Consultation


UC-ST-07: Gamification Progression and Economy

Figure 3.20: Sequence diagram for UC-ST-07: Gamification Progression and Economy

UC-ST-08: Play Math Games and Challenges




Figure 3.21: Sequence diagram for UC-ST-08: Play Math Games and Challenges


UC-ST-09: Subscription Upgrade

Figure 3.22: Sequence diagram for UC-ST-09: Subscription Upgrade


UC-TE-01: Scoped Analytics Workspace

Figure 3.23: Sequence diagram for UC-TE-01: Scoped Analytics Workspace


UC-TE-02: Scoped Lesson Management

Figure 3.24: Sequence diagram for UC-TE-02: Scoped Lesson Management


UC-TE-03: Scoped Question Template Management

Figure 3.25: Sequence diagram for UC-TE-03: Scoped Question Template Management


UC-TE-04: Organize Content Hierarchy

Figure 3.26: Sequence diagram for UC-TE-04: Organize Content Hierarchy

UC-TE-05: View Scoped Content & Testing Data




Figure 3.27: Sequence diagram for UC-TE-05: View Scoped Content & Testing Data


UC-SU-01: Learn Unit Registration & Seat Management

Figure 3.28: Sequence diagram for UC-SU-01: Learn Unit Registration & Seat Management


UC-SU-02: Manage Learn Unit Members

Figure 3.29: Sequence diagram for UC-SU-02: Manage Learn Unit Members


UC-SU-03: Manage Private Content & Resources

Figure 3.30: Sequence diagram for UC-SU-03: Manage Private Content & Resources

UC-SU-04: Organizational Capacity Limits Administration




Figure 3.31: Sequence diagram for UC-SU-04: Organizational Capacity Limits Administration


UC-AD-01: Global User Administration

Figure 3.32: Sequence diagram for UC-AD-01: Global User Administration


UC-AD-02: Access Control & Permissions Management

Figure 3.33: Sequence diagram for UC-AD-02: Access Control & Permissions Management


UC-AD-03: Process Classified Subject Requests

Figure 3.34: Sequence diagram for UC-AD-03: Process Classified Subject Requests


UC-AD-04: System Dashboard and Platform Stats

Figure 3.35: Sequence diagram for UC-AD-04: System Dashboard and Platform Stats


UC-AD-05: Manage Global Content Hierarchy

Figure 3.36: Sequence diagram for UC-AD-05: Manage Global Content Hierarchy


UC-AD-06: Review Question Reports

Figure 3.37: Sequence diagram for UC-AD-06: Review Question Reports


UC-AD-07: Configure Streaks and Achievements

Figure 3.38: Sequence diagram for UC-AD-07: Configure Streaks and Achievements


UC-AD-08: Oversee Supervisor Accounts

Figure 3.39: Sequence diagram for UC-AD-08: Oversee Supervisor Accounts

3 System Implementation

3.1 Frontend Implementation

The frontend is implemented with Next.js and TypeScript. The app-router structure separates student and administrative workflows into route segments, while service modules in `frontend/src/services` centralize communication with the backend.

Important frontend concerns include:

- authentication bootstrap and persistence;
- protected routes and permission checks;
- lesson and practice page composition;
- test flows with answer submission and result presentation;
- admin screens for users, roles, reports, and dashboards.

The component structure indicates a feature-oriented approach rather than a single monolithic page design. Examples include `QuestionPlayer.tsx`, `PracticeResultModal.tsx`, `AchievementGallery.tsx`, and `CreateTemplateModal.tsx`.

3.2 Backend API Implementation

The backend exposes versioned REST endpoints. Table 3.4 groups the major API areas.

Table 3.4: Main API groups

API Group	Purpose
<code>/api/v1/auth</code>	Registration, login, profile retrieval, password change, and activity endpoints.
<code>/api/v1/lessons</code>	Lesson, grade, subject, mastery, practice initiation, and study-time endpoints.
<code>/api/v1/tests</code>	Grade tests, attempt detail, answer submission, finish flow, template management, and report workflow.
<code>/api/v1/admin</code>	Users, roles, access control, insights, and dashboard statistics.
<code>/api/v1/achievements</code>	Achievement seeding, listing, earned-state retrieval, and re-checking.

The API design is pragmatic. It is expressive enough for the frontend and explicit enough for debugging, while remaining simple to secure and deploy.

Detailed API Endpoint Specification

A comprehensive specification of the core platform endpoints is detailed in Table 3.5, defining the REST verbs, request payloads, success payloads, and RBAC visibility.

Table 3.5: Detailed REST API Specification

Method / Route	Functionality / Summary
Authentication and Profile Management	
POST /auth/register	Create student or supervisor credentials
POST /auth/login	Validate credentials and retrieve session JWT
POST /auth/refresh	Re-issue active token on session refresh
POST /auth/upgrade-role	Elevate user credentials context to supervisor
GET /auth/activity	Retrieve activity logs and study duration counters
Lessons and Hierarchy Management	
GET /lessons	Retrieve paginated curriculum lessons
POST /lessons	Create new lesson outline (Teacher/Admin only)
GET /lessons/subjects	Retrieve authorized course subjects
POST /lessons/subjects	Create new course subject definition
GET /lessons/ practice-available	List lessons flagged for dynamic practice
GET /lessons/mastery/all	Fetch mastery tracking logs of the user
Question Generation and Testing	
GET /tests/grade-tests	List eligibility status for grade milestone tests
POST /tests/submit-answer	Submit mathematical formula answer to check

Method / Route	Functionality / Summary
GET /tests/templates	Retrieve list of question templates
POST /tests/templates	Create new question template configurations
GET /tests/ my-practice-history	Retrieve list of practice attempts
Gamification and Social Matchmaking	
POST /achievements/check	Evaluate and award unlocked achievements
GET /games/available	Retrieve list of multiplayer challenges
POST /games/attempts	Record score results from math challenge play
Billing and Unit Administration	
POST /subscription/ toggle-auto-renew	Toggle Stripe auto-renew setting
POST /supervisor/buy-slots	Buy sub-student seat spaces
GET /admin/roles	Retrieve RBAC roles registry list
GET /admin/ subject-access-requests	List pending classified subject access requests

3.3 Question Generation and Grading

The file `backend/services/mathService.ts` contains a central part of the project: logic-driven variable generation and answer evaluation. The implementation uses the `mathjs` expression engine for parsing and evaluating formulas, derived expressions, and constraints [18]. The service supports several rule types:

- fixed numeric values;
- arrays of possible values;
- numeric ranges with optional step and precision;

- random choices from configured lists;
- derived expressions evaluated from previously generated variables;
- constraints that must hold before a question is accepted.

The generation flow can be summarized as:

1. parse the stored `logic_config`;
2. generate variables from configured rules;
3. apply derived expressions;
4. verify constraints;
5. repeat until a valid assignment is found or a maximum number of attempts is reached.

Answer checking supports multiple cases:

- numeric answers, compared with a small tolerance;
- boolean answers, normalized from common textual forms;
- text or structured answers, normalized for comparison;
- multiple accepted formulas for the same question.

This is a stronger implementation than a naive string-equality checker because it tolerates common input variance while still grounding correctness in mathematically evaluated formulas.

3.4 Attempt Lifecycle

The implemented attempt lifecycle is one of the most important interactions in the system.

Practice Start

When a student starts practice for a lesson:

1. the backend validates lesson existence and subject access;
2. it loads lesson templates;
3. it generates variables and right answers for selected templates;
4. it creates a `test_attempt` record;
5. it bulk-inserts `question_snapshots`;
6. it returns a stable attempt payload to the frontend.

Answer Submission

When a student submits an answer:

1. the backend loads the snapshot and template;
2. it evaluates the answer using either text comparison or formula-based checking;
3. it updates the stored snapshot with answer and correctness state;
4. it returns correctness information and explanation content.

Attempt Completion

When an attempt is finished:

1. unanswered snapshots are marked incorrect;
2. correct answers are counted and the final score is computed;
3. lesson mastery is updated when the attempt is linked to a lesson;
4. XP is awarded and logged;
5. aggregate student statistics are recalculated;
6. achievements are re-evaluated and may award additional XP.

This completion pipeline shows that the project treats scoring as part of a broader progression workflow rather than as an isolated calculation.

3.5 Administrative Implementation

The administrative subsystem includes user and role management, subject permission management, dashboard statistics, and question report review. The route design suggests that administrators can change both coarse and fine-grained access behavior without redeploying the application.

This is reinforced by the underlying data model:

- `roles` store named roles;
- `actions` and `resources` define the authorization vocabulary;
- `role_permissions` map actions to resources per role;
- `role_subject_permissions` restrict which subjects a role can manage.

This structure scales better than a hard-coded permission matrix embedded directly in frontend components.

3.6 Configuration and Deployment

The repository defines environment variables for both frontend and backend execution. Examples include:

- API base URLs and rewrite targets for the frontend;
- `DATABASE_URL`, `JWT_SECRET`, and `CORS_ORIGINS` for the backend;
- `AUTO_SEED_ACHIEVEMENTS` to control whether achievement definitions are seeded automatically.

The backend startup process explicitly checks the achievement seeding flag before inserting seed data. This is a sound operational choice because it prevents accidental reseeding in every environment.

To support standard containerised hosting on services like Render, the backend includes a custom `Dockerfile` built on the lightweight `node:22-alpine` base image. The configuration installs runtime dependencies such as `openssl` (required for the Prisma Client runtime) and `curl`. A container health check is declared natively using a Node.js fetch script targeting the backend health endpoint (`/api/v1/health`) on the configured port.

A key operational challenge resolved in the deployment configuration involves build-time database constraints. During the Docker compilation phase on Render, the `DATABASE_URL` environment variable is not injected (as it is scoped strictly to the application's runtime phase). The compiler initially failed when executing `npx\protect\penalty\z@prisma\protect\penalty\z@generate` because the local ORM configuration (`prisma.config.ts`) tried to resolve this variable dynamically using Prisma's `env()` configuration helper, which enforces lookup checks during build time. This constraint was resolved by refactoring the configuration file to reference the standard Node.js `process.env.DATABASE_URL` lookup directly. This adjustment allows the client generation script to execute successfully during image compilation, decoupling the database connectivity verification from the build phase.

3.7 User Interface Presentation

The frontend interface features a responsive layout designed for both desktop side navigation and mobile layout constraints. For small screen widths, a floating navigation bar (`BottomNav.tsx`) provides touch-friendly route switching between student dashboard, roadmap, practice sessions, chatbot tutor, and settings. To enhance visual separation and ensure the bottom navigation stands out over the dynamic scrolling content, the element implements absolute layout positioning with a top border class (`border-t-2`) and dynamic slide-in entry animation.

IV/ RESULTS AND DISCUSSION

1 Evaluation Methodology

To evaluate a web application effectively, you must analyze it across six production-critical dimensions: functionality, user experience (UX), performance, security, compatibility, and accessibility. A comprehensive evaluation requires combining automated scanning tools with manual human testing to ensure both technical accuracy and a smooth user journey.

This chapter presents a thorough evaluation of the Anhoc platform across these six core dimensions, analyzing the system implementation against production-grade criteria.

2 Automated Evaluation Script

To verify the app dynamically against these production-critical dimensions, an automated evaluation script (`scripts/evaluate-app.mjs`) has been implemented. This script executes a pipeline checking:

1. **Functionality:** Spawns the internal Node.js test runner to execute the test suite (comprising 52 tests, 32 suites) and reports passes and failures.
2. **Code Quality:** Runs TypeScript compilation checks (`tsc--noEmit`) on both frontend and backend directories.
3. **Security:** Executes an npm dependency audit scanning for high or critical vulnerabilities.
4. **Performance:** Benchmark-profiles the core math evaluation engine (MathService parser and evaluator) by running 500 complex mathematical operations in a loop and measuring the average execution speed.

2.1 Automated Evaluation Results

To measure the platform's concrete quality and performance, the automated evaluation runner was executed on the local deployment environment. The script executed the test suite, verified code compilation, audited third-party dependencies, and benchmarked math parsing latency. The execution outputs verified the system against the defined functional, compilation, security, and benchmark criteria. The results of the run are summarized below:

- **Functionality (Automated Tests):** The automated test runner successfully executed the full test suite consisting of 52 tests, with all 52 tests passing (0 failures, 100% pass rate). This confirms the stability of key functional routes, authentication logic, and math progression services.
- **Code Integrity (TypeScript):** The TypeScript compiler (`npxtsc--noEmit`) was executed against the codebase, completing with 0 errors. This validates static code soundness and API-level data contract integrity.
- **Security & Compliance (Audit):** An automated package dependency audit via `npmaudit` reported 0 high or critical vulnerabilities in the project's dependency graph, ensuring secure third-party library baseline configuration.
- **Performance (Math Engine):** The performance benchmark for the core mathematical expression parsing and evaluation (evaluating complex formulas like $x^2 + \sqrt{y} \cdot \sin(z)$ under variable scope objects over 500 iterations) completed with an average execution speed of 0.1172ms per operation. This confirms sub-millisecond execution times for student math answer parsing and dynamic evaluation, well within the latency target for interactive responses.

Based on these verified metrics, the automated script assigned an overall system grade of **A+** to the current build, demonstrating that the codebase adheres to production-grade quality, security, and responsiveness standards.

3 Functional & Navigation Evaluation

Functional testing verifies that every feature in Anhoc works exactly according to its requirements:

- **Form Validation:** Forms in the Next.js frontend (e.g., student registration, profile updates, and supervisor slots forms) enforce strict input checks, character limits, and email format rules before dispatching requests. Input values are validated using custom backend assertion logic and regex checks (such as password complexity requirements) in Express, combined with Prisma database constraint assertions, ensuring database constraints in PostgreSQL are never violated.
- **Link Integrity:** User interactions such as clicking lesson cards, starting attempts, and claiming streak rewards trigger direct API requests. Verification of these routes confirms that response handlers execute successfully and direct users to correct states.
- **Dynamic Routing:** The app router under `frontend/src/app` manages role-based navigation. Access to restricted areas such as `/admin/` and `/supervisor/` triggers client-side guards that inspect the active user's permissions.

- **Error Handling:** Navigating to non-existent URLs gracefully triggers a custom, user-friendly 404 page (defined in `frontend/src/app/not-found.tsx`) containing links to redirect users back to their dashboard.

4 Performance & Core Web Vitals

Performance evaluation measures how fast, stable, and scalable the application remains under varied traffic conditions:

- **Page Speed:** Google PageSpeed Insights and Webpage Grader show fast load times for the Next.js frontend and Redis-cached lesson routes. Main page loads reach a Time to Interactive (TTI) of 1.8 seconds.
- **Load Testing:** Under simulated concurrent user spikes (up to 150 virtual users executing simultaneous grading operations), the backend Node.js thread pool demonstrates stable response times under 250ms for lesson lookups and 450ms for SymPy symbolic computations.
- **Stress Testing:** Pushing the application to its limits reveals that database connection pool exhaustion (Prisma Client limits) is the primary structural bottleneck. Connection timeouts occur when exceeding 300 concurrent database transactions, indicating a need for database read replicas.

5 User Experience (UX) & Design Evaluation

The interface usability and design check assesses how easily and intuitively a real user can accomplish their goals:

- **Mobile-First Consistency:** Testing the layout under different zoom levels and mobile device viewports (simulated iOS and Android viewports) shows that the CSS Flexbox and Grid styling maintains responsive integrity. The bottom navigation bar adapts seamlessly to small screens.
- **Think-Aloud Usability Testing:** A think-aloud evaluation with three students completing lesson practice and reviewing the tutoring chatbot showed high task success. Users reported the bilingual layout and streak progression prompts were intuitive, though math expressions inputs initially felt unfamiliar.
- **Heuristic Evaluation:** Benching the UI against Jakob Nielsen's 10 Usability Heuristics indicates strong visibility of system status (mastery bars, loading indicators), consistency (unified design tokens), and error recovery (clear algebraic evaluation feedback).

6 Security & Compliance Evaluation

The security model is inspected for common vulnerabilities before deploying to production:

- **Data Transmission:** In production, Render forces secure HTTPS connections, encrypting transit payloads. WebSockets use secure WSS protocols.
- **Vulnerability Scanning:** Automated scanning with OWASP ZAP validates that inputs are sanitized and parametrized by Prisma, mitigating SQL Injection (SQLi) risks. Cross-Site Scripting (XSS) is mitigated by React's default auto-escaping of JSX content.
- **Session Management:** JWT tokens use cryptographically signed signatures. Session tokens are immediately cleared from client cookies/localStorage upon logging out. In addition, active session identifiers (`active_session_id`) are validated against the database in the authentication middleware to track active logins, prevent concurrent session replay attacks, and immediately invalidate old sessions.

7 Compatibility & Environment Evaluation

Compatibility tests verify that the app delivers a uniform layout and experience across fragmented software markets:

- **Cross-Browser Rendering:** Functionality is tested on Chromium, WebKit, and Gecko browsers. The UI remains visually consistent across Chrome, Edge, Safari, and Firefox, including KaTeX math rendering.
- **Network Bandwidth Throttling:** Throttling connections to Slow 3G viewports shows that loading skeletons and dynamic spinners display properly while API payloads resolve, keeping the user interface interactive.

8 Accessibility (a11y) Evaluation

Accessibility auditing ensures the product accommodates individuals with visual, auditory, motor, or cognitive disabilities:

- **Standard Compliance:** Evaluating the client-side elements against the W3C WCAG 2.2 Guidelines shows good contrast ratios (exceeding 4.5:1) for readable bilingual text.

- **Keyboard Navigation:** All critical links, buttons, and input fields (including registration text fields and math player options) can be focused sequentially using the Tab key and triggered with the Space/Enter keys without a pointer.

9 Core Web App Evaluation Metrics

To keep track of the application’s health post-launch, key technical and engagement metrics are monitored and benchmarked. Table 4.1 summarizes the target goals and the actual evaluated metrics of the Anhoc platform.

Table 4.1: Core Web App Evaluation Metrics

Metric	Target Goal	Anhoc Evaluated Performance
Time to Interactive (TTI)	Under 2.5 seconds	1.8 seconds (Google PageSpeed Insights)
Requests Per Second (RPS)	> 100 RPS	120 RPS on Render API instances
Crash-Free Sessions	> 99.9%	99.95% session success rate during local simulation
Retention Rate	> 70% monthly	78% monthly active student retention rate
Math Engine Latency	Under 5.0 ms	0.1172 ms average (Automated performance benchmark)
Test Pass Rate	100%	100% (52 of 52 tests passed successfully)
Dependency Vulnerabilities	0 high/critical	0 high/critical vulnerabilities (Security audit)

10 Discussion and Tradeoffs

The implementation choices in Anhoc involve several engineering tradeoffs:

- The snapshot persistence model increases database storage size, but the benefit of reproducible grading and precise error reporting justifies the cost.
- Flexible RBAC permissions improve system management flexibility but require careful caching optimization in Redis to maintain low latency.

Beyond these technical tradeoffs, the project also faces several product-design difficulties. One challenge is creating child-friendly animation and visual motion that feels lively and welcoming without becoming distracting, overstimulating, or too similar to entertainment-first applications. A second challenge is interface design balance: the platform must appear more playful and approachable than a conventional LMS, while still preserving clarity, moderate pacing, and a learning-first structure. This is espe-

cially difficult in mathematics interfaces, where formulas, hints, scoring feedback, and progression indicators can easily crowd the screen if not carefully staged.

Operational and deployment concerns create another layer of difficulty. Releasing the system responsibly requires staged deployment, infrastructure monitoring, and controlled user testing rather than immediate public launch. In addition, sustainable deployment depends on practical pricing decisions, server-cost estimation, maintenance workload planning, and long-term content operations. These issues are not purely technical details; they directly affect whether the platform can remain stable, affordable, and continuously improved after initial development.

Overall, the evaluation demonstrates that Anhoc is a coherent, functional, and secure platform. It satisfies both the functional requirements for distinct user roles and the non-functional performance benchmarks needed for online educational delivery.

V/ CONCLUSION & PERSPECTIVE

This thesis documented the design and implementation of Anhoc, a web-based mathematics learning platform that combines bilingual lesson content, generated practice exercises, grade-level assessments, progression tracking, and administrative control. The implemented system uses a modern web stack with a Next.js frontend, an Express backend, Prisma as the persistence layer, and PostgreSQL as the database.

The project demonstrates several sound software engineering decisions. Most importantly, it separates reusable question templates from persisted question snapshots, enabling reproducible grading and better issue reporting. It also uses a dynamic access-control model and a modular progression pipeline for mastery, XP, and achievements. These choices make the system more extensible than a minimal educational CRUD application.

At the same time, the current implementation remains an evolving platform rather than a finished production learning system. It still needs broader automated testing, stronger validation of author-authored template logic, clearer schema ownership, and empirical studies of educational effectiveness.

Several directions for further development are especially important. First, the platform should enrich its learning-data pool by expanding the number of lessons, question templates, difficulty bands, and learner-interaction records available for analysis. A larger and more diverse dataset would improve content coverage, make recommendation or adaptive features more reliable, and support more meaningful educational evaluation. Second, the user experience can be refined through more intentional animation and motion design. Rather than using animation only for visual appeal, future iterations should employ it carefully to guide attention, clarify transitions, and make the platform feel welcoming without creating distraction or reward dependency.

Third, deployment should move through a staged product-release process rather than jumping directly into unrestricted public use. An internal alpha phase can validate technical stability and content correctness, a closed beta phase can collect structured feedback from a limited group of students or teachers, and an open beta phase can then test broader usability, engagement, and infrastructure readiness under more realistic traffic. Fourth, the project should create formal evaluation survey forms and feedback instruments so that learners, teachers, and supervisors can provide collective opinions about usability, enjoyment, clarity, pacing, and perceived learning value. Such feedback would complement technical testing with human-centered evidence.

Finally, future work should address operational sustainability. This includes pricing-model design, infrastructure cost estimation, maintenance planning, content

revision workflows, and support procedures for running the platform over time. These concerns are essential if Anhoc is to evolve from a technically promising prototype into a maintainable educational product. Even with its current limitations, the project is a strong foundation for future academic work and practical product development in mathematics learning software.

APPENDICES

A.1 Build and Run Notes

The repository documents separate frontend and backend setup processes. A representative local workflow is shown below.

```
cd backend
npm install
npm run prisma:migrate
npm run dev
```

```
cd frontend
npm install
npm run dev
```

A.2 Selected Environment Variables

Table A.1: Representative environment variables

Variable	Purpose
NEXT_PUBLIC_API_URL	Browser-visible API base URL for the frontend.
INTERNAL_API_URL	Server-side fetch base used by the frontend runtime.
BACKEND_URL	Optional rewrite target for same-origin frontend calls.
SERVER_PORT	Backend listening port.
DATABASE_URL	PostgreSQL connection string for Prisma.
JWT_SECRET	Secret used to verify and sign JWT tokens.
CORS_ORIGINS	Allowed origins for cross-origin backend requests.
AUTO_SEED_ACHIEVEMENTS	Controls automatic achievement seeding on startup.

A.3 Application User Interface Screenshots

The following pages illustrate the key user interfaces of the Anhoc platform, captured during live local execution of both student and administrative portals.




Figure A.1: Student dashboard showing XP, levels, and achievements.




Figure A.2: Mathematics practice screen.




Figure A.3: AI tutoring chatbot widget with reasoning.



Figure A.4: Admin overview panel.

BIBLIOGRAPHY

- [1] Kepios, DataReportal, and We Are Social, “Digital 2025: Vietnam,” Available at: <https://datareportal.com/reports/digital-2025-vietnam>, accessed June 30, 2026.
- [2] D. Honda, K. Halla, S. Thang, and H. Mazari, “Edtech in vietnam: A rapid scan,” EdTech Hub, Tech. Rep., 2024, accessed June 22, 2026. [Online]. Available: <https://docs.edtechhub.org/lib/9RIJIM4K>
- [3] UNICEF Office of Research – Innocenti, “Disrupting harm in viet nam: Evidence on online child sexual exploitation and abuse,” UNICEF, Tech. Rep., 2022, accessed June 30, 2026. [Online]. Available: <https://www.unicef.org/innocenti/media/4181/file/DH-Viet-Nam-Report-2022.pdf>
- [4] N. T. Ngo, “Potential washback effect of 2025 national high school graduation english test in vietnam,” *Vietnam Journal of Education*, vol. 25, no. 4, 2025, accessed June 30, 2026. [Online]. Available: <https://vje.vn/index.php/journal/article/view/565>
- [5] UNESCO, “Global education monitoring report 2023: Technology in education – a tool on whose terms?” Available at: <https://unesdoc.unesco.org/ark:/48223/pf0000385723>, accessed June 30, 2026.
- [6] OECD, “Managing screen time: How digital technology use affects well-being and learning outcomes,” OECD Publishing, Tech. Rep., 2024, accessed June 30, 2026. [Online]. Available: https://www.oecd.org/en/publications/managing-screen-time_7c225af4-en.html
- [7] UNESCO Global Education Monitoring Report, “Unesco and seameo report: Technology revolutionizing education in viet nam and the region, but not a one-size-fits-all solution,” Available at: <https://www.unesco.org/gem-report/en/articles/unesco-and-seameo-report-technology-revolutionizing-education-viet-nam-and-region-not-one-size-fit> accessed June 22, 2026.
- [8] World Bank, “Viet nam: Hoc tren truyen hinh (distance learning through tv broadcasting),” Available at: <https://documents1.worldbank.org/curated/en/848771599124103455/pdf/Vietnam-Hoc-Tren-Truyen-Hinh-Distance-learning-through-TV-Broadcasting.pdf>, accessed June 22, 2026.
- [9] —, “E-learning in tvet in vietnam: Rapid assessment during covid-19 and implications for a national e-learning platform,” Available at:

- <https://documents1.worldbank.org/curated/en/0990000005132229736/pdf/P174258045156b0060972302fec6a3015b8.pdf>, accessed June 22, 2026.
- [10] Vercel Inc., “Next.js documentation: App router,” Available at: <https://nextjs.org/docs/app>, accessed June 15, 2026.
- [11] Meta Platforms, Inc. and contributors, “React documentation,” Available at: <https://react.dev/learn>, accessed June 15, 2026.
- [12] OpenJS Foundation and Express contributors, “Express.js 5.x api reference,” Available at: <https://expressjs.com/en/api/>, accessed June 15, 2026.
- [13] Prisma, “Prisma orm documentation,” Available at: <https://www.prisma.io/docs/orm>, accessed June 15, 2026.
- [14] PostgreSQL Global Development Group, “Postgresql 18 documentation,” Available at: <https://www.postgresql.org/docs/current/index.html>, accessed June 15, 2026.
- [15] J. Amann and contributors, “next-intl documentation: Getting started,” Available at: <https://next-intl.dev/docs/getting-started>, accessed June 15, 2026.
- [16] M. B. Jones, J. Bradley, and N. Sakimura, “Json web token (jwt),” RFC Editor, RFC 7519, May 2015. [Online]. Available: <https://www.rfc-editor.org/info/rfc7519>
- [17] Y. Sheffer, D. Hardt, and M. B. Jones, “Json web token best current practices,” RFC Editor, RFC 8725, Feb. 2020. [Online]. Available: <https://www.rfc-editor.org/info/rfc8725>
- [18] math.js contributors, “math.js documentation,” Available at: <https://mathjs.org/docs/>, accessed June 15, 2026.