


REVISION⁵ HISTORY


Schematics Index:

```
P01: REVISION HISTORY
P02: BLOCK
P03: POWER TREE
P04: GPIO ASSIGNMENT
P05: SOC1
P06: SOC2
P07: DDR3 16X2
P08: POWER
P09: NAND-eMMC
P10: CARD-USB-IR-SPDIF
P11: KEY-LED-ETH-DEBUG
P12: AV-HDMI
P13: WIFI-BT 2T2R
P14: WIFI-BT 1T1R
```

Revision	Description	Date	Drawn	Checked
Ver 2.0	Initial Version	2017-11-27	HJ	



POWER TREE



DEFAULT POWER ON

DEFAULT POWER OFF

GPIO ASSIGNMENT

PIN	Define	CFG	Function
PC0	NAND_WE	2	NAND/eMMC
PC1	NAND_ALE/SDC2_DS	2/3	
PC2	NAND_CLE	2	
PC3	NAND_CE0	2	
PC4	NAND_RE/SDC2_CLK	2/3	
PC5	NAND_RB0/SDC2_CMD	2/3	
PC6	NAND_DQ0/SDC2_D0	2/3	
PC7	NAND_DQ1/SDC2_D1	2/3	
PC8	NAND_DQ2/SDC2_D2	2/3	
PC9	NAND_DQ3/SDC2_D3	2/3	
PC10	NAND_DQ4/SDC2_D4	2/3	
PC11	NAND_DQ5/SDC2_D5	2/3	
PC12	NAND_DQ6/SDC2_D6	2/3	
PC13	NAND_DQ7/SDC2_D7	2/3	
PC14	NAND_DQS/SDC2_RST	2/3	
PC15	NAND_CE1	2	
PC16	NAND_RB1	2	

PIN	Define	CFG	Function
PD0			
PD1			
PD2			
PD3			
PD4			
PD5			
PD6			
PD7			
PD8			
PD9			
PD10			
PD11			
PD12			
PD13			
PD14			

PIN	Define	CFG	Function
PD15			
PD16			
PD17			
PD18			
PD19			
PD20			
PD21			
PD22			
PD23			
PD24			
PD25			
PD26			



PIN	Define	CFG	Function
PG0	SDC1_CLK	2	WIFI+BT
PG1	SDC1_CMD	2	
PG2	SDC1_D0	2	
PG3	SDC1_D1	2	
PG4	SDC1_D2	2	
PG5	SDC1_D3	2	
PG6	UART1_TX	2	
PG7	UART1_RX	2	
PG8	UART1_RTS	2	
PG9	UART1_CTS	2	
PG10	PCM2_SYNC	2	
PG11	PCM2_CLK	2	
PG12	PCM2_DOUT	2	
PG13	PCM2_DIN	2	
PG14			

PIN	Define	CFG	Function
PF0	SDC0_D1	2	CARD0
PF1	SDC0_D0	2	
PF2	SDC0_CLK/UART0_TX	2/3	
PF3	SDC0_CMD	2	
PF4	SDC0_D3/UART0_RX	2/3	
PF5	SDC0_D2	2	
PF6	SDC0-DET	2	


PIN	Define	CFG	Function
PH0	CPUX-UTX	2	
PH1	CPUX-URX	2	
PH2			
PH3			
PH4			
PH5			
PH6			
PH7	SPDIF_OUT	3	
PH8	HSCL	2	
PH9	HSDA	2	
PH10	HCEC	2	

PIN	Define	CFG	Function
PL0	PMU-SCK	3	WIFI+BT
PL1	PMU-SDA	3	
PL2	RECOVERY	2	
PL3	LINK-LED	1	
PL4	PWR-LED	1	
PL5	USB0-DRVVBUS	1	
PL6	MUTE	1	
PL7	STATUS-LED	1	
PL8			
PL9	IR-RX	2	
PL10	BT-WIFI-ON	1	
PM0	WL-WAKE-AP	0	
PM1	BT-WAKE-AP	0	
PM2	AP-WAKE-BT	1	
PM3	WL-REG-ON	1	
PM4	BT-REG-ON	1	

PC,PD, 部分IO口不具备中断功能
PF,PG,PH,PL,PM, 部分IO口有中断功能







eMMC


NAND

Xunlong Software CO.,Limited		
design name ORANGE_PL_LITE2		
Size A3	page name NAND-eMMC	Rev 2.0
Date: Monday, March 05, 2018		
Sheet 9 of 14		

SPDIF







CARD




USB



Differential pairs
Z0= 90 ohm





Audio




Video




VDD1V5-CSI=1.5V
VCC-CSI =2.8V



HDMI



Differential pairs
Z0= 100 ohm




EPHY-FE


Differential pairs
Z0= 100 ohm




DEBUG




LED




IR



MIC









KEY





Xunlong Software CO.,Limited			
design name			
ORANGE_PI_LITE2			
Size	page name	Rev	
A3	KEY-LED-ETH-DEBUG	2.0	
Date:	Monday, March 05, 2018	Sheet	12 of 14

WIFI+BT



RW51 RW45 RW46 RW50 RW52 RW53

不帶藍牙遙控	IO為1.8V	NC	NC	NC	0R	NC	0R
	IO為3.3V	NC	NC	NC	0R	0R	NC
帶藍牙遙控	IO為1.8V	0R	NC	NC	NC	NC	NC
	IO為3.3V	0R	0R	0R	NC	NC	NC



Ext Port

Ext

