# **Advanced HTML5**

**HTML5 Offline Applications** 

Craig Shoemaker http://craigshoemaker.net @craigshoemaker






### **Outline**


- Introduction
- What Are Offline Applications?
- Anatomy of Offline Application
- Application Cache API & Lifecycle
- Browser Support
- Demos:
  - Events
  - Manual Updates
  - Automatic Updates
  - 'Journal' Application
  - Debugging






Web Application






Web Application





Offline Application







# **JOURNAL** Send



```
<!doctype html>
<html manifest="journal-manifest.aspx">
<head>
   <title>Log</title>
   <link rel="Stylesheet" href="journal.css" type="text/css" />
   <script src="scripts/jquery-1.5.1.min.js" type="text/javascript"></script>
   <script src="offline.js" type="text/javascript"></script>
    <script>
       var isOnLine, box;
       var messages = [];
       function reportOnlineStatus() {
           isOnLine = navigator.onLine;
           $("#onlineStatus").html((isOnLine) ? "Yes" : "No");
       function storeMessage() {
           var message = box.val();
           if (!isOnLine) {
                storeMessageLocal(message);
           else {
                storeMessageRemote(message);
        }
       function storeMessageLocal(msg) {
           messages.push(msg);
           clearUI();
           logEvent("Message saved locally: '" + msg + "'");
```



```
<!doctype html>
<html manifest="journal-manifest.aspx";</pre>
<head>
    <title>Log</title>
    <link rel="Stylesheet" href="journal.css" type="text/css" />
    <script src="scripts/jquery-1.5.1.min.js" type="text/javascript"></script>
    <script src="offline.js" type="text/javascript"></script>
    <script>
        var isOnLine, box;
        var messages = [];
        function reportOnlineStatus() {
            isOnLine = navigator.onLine;
           $("#onlineStatus").html((isOnLine) ? "Yes" : "No");
        function storeMessage() {
            var message = box.val();
            if (!isOnLine) {
                storeMessageLocal(message);
            else {
                storeMessageRemote(message);
        }
        function storeMessageLocal(msg) {
            messages.push(msg);
            clearUI();
            logEvent("Message saved locally: '" + msg + "'");
```

### Manifest

- Assets
- Application Cache
- Online Status Awareness



```
<!doctype html>
<html manifest="journal-manifest.aspx">
<head>
   <title>Log</title>
   <link rel="Stylesheet" href="journal.css" type="text/css" />
   <script src="scripts/jquery-1.5.1.min.js" type="text/javascript"></script>
   <script src="offline.js" type="text/javascript"></script>
    <script>
        var isOnLine, box;
       var messages = [];
       function reportOnlineStatus() {
           isOnLine = navigator.onLine;
           $("#onlineStatus").html((isOnLine) ? "Yes" : "No");
       function storeMessage() {
           var message = box.val();
           if (!isOnLine) {
                storeMessageLocal(message);
           else {
                storeMessageRemote(message);
        }
       function storeMessageLocal(msg) {
           messages.push(msg);
           clearUI();
           logEvent("Message saved locally: '" + msg + "'");
```

- Manifest
- Assets
- Application Cache
- Online Status Awareness



```
<!doctype html>
<html manifest="journal-manifest.aspx">
<head>
   <title>Log</title>
   <link rel="Stylesheet" href="journal.css" type="text/css" />
   <script src="scripts/jquery-1.5.1.min.js" type="text/javascript"></script>
   <script src="offline.js" type="text/javascript"></script>
    <script>
        var isOnLine, box;
       var messages = [];
       function reportOnlineStatus() {
           isOnLine = navigator.onLine;
           $("#onlineStatus").html((isOnLine) ? "Yes" : "No");
       function storeMessage() {
           var message = box.val();
           if (!isOnLine) {
                storeMessageLocal(message);
           else {
                storeMessageRemote(message);
        }
       function storeMessageLocal(msg) {
           messages.push(msg);
           clearUI();
           logEvent("Message saved locally: '" + msg + "'");
```

- Manifest
- Assets
- Application Cache
- Online Status Awareness




```
<!doctype html>
<html manifest="journal-manifest.aspx">
<head>
   <title>Log</title>
   <link rel="Stylesheet" href="journal.css" type="text/css" />
   <script src="scripts/jquery-1.5.1.min.js" type="text/javascript"></script>
   <script src="offline.js" type="text/javascript"></script>
    <script>
        var isOnLine, box;
        var messages = [];
       function reportOnlineStatus() {
           isOnLine = navigator.onLine;
           $("#onlineStatus").html((isOnLine) ? "Yes" : "No");
       function storeMessage() {
           var message = box.val();
           if (!isOnLine) {
                storeMessageLocal(message);
           else {
                storeMessageRemote(message);
        }
       function storeMessageLocal(msg) {
           messages.push(msg);
           clearUI();
           logEvent("Message saved locally: '" + msg + "'");
```

- Manifest
- Assets
- Application Cache
- Online Status Awareness



# **Understanding Caching**


**Browser Caching** 





# **Understanding Caching**

**Application Caching** 






# **Understanding Caching**



Do not mix browser caching and application caching

# **Browser Caching vs. Application Caching**





```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



```
CACHE MANIFEST
# version 1
CACHE:
journal.aspx
journal-css.aspx
scripts/jquery-1.5.1.min.js
offline.js
journal-bkg.jpg
NETWORK:
journal/list
FALLBACK:
/home /journal-fallback.aspx
```



Mime Type: text/cache-manifest

Encoding: utf-8



window.applicationCache



window. application Cache

First Load

Checking


Downloading

Progress

Cached




window. application Cache





window.applicationCache





# **Cache States**

State	Status	Description
0	UNCACHED	Cache not initialized
1	IDLE	Cache not being updated
2	CHECKING	Looking at manifest for changes
3	DOWNLOADING	Serving files in manifest to browser
4	UPDATEREADY	All files in manifest are downloaded
5	OBSOLETE	Contents of cache are stale and need to be downloaded again



# **Browser Support**



# **Demos**



# **Summary**

- Offline Applications
  - Application Cache API
  - Online/Offline Browser Events
- Working with Events
- Manual and Automatic Installation
- Manifest Errors



For more in-depth online developer training visit



on-demand content from authors you trust

