

# Finite Automata

# Alphabets and Languages

Def

# Alphabets and Languages

## Def

$\Sigma$  - alphabet (finite set)

$\Sigma^n = \{a_1 a_2 \dots a_n \mid a_i \in \Sigma\}$  is the set of words of length  $n$

$\Sigma^* = \{w \mid \exists n \in \mathbb{N}. \exists a_1, a_2, \dots, a_n \in \Sigma. w = a_1 a_2 \dots a_n\}$  is the set of all words over  $\Sigma$

# Alphabets and Languages

## Def

$\Sigma$  - alphabet (finite set)

$\Sigma^n = \{a_1 a_2 \dots a_n \mid a_i \in \Sigma\}$  is the set of words of length  $n$

$\Sigma^* = \{w \mid \exists n \in \mathbb{N}. \exists a_1, a_2, \dots, a_n \in \Sigma. w = a_1 a_2 \dots a_n\}$  is the set of all words over  $\Sigma$

$\Sigma^0 = \{\epsilon\}$  contains only the empty word

# Alphabets and Languages

## Def

$\Sigma$  - alphabet (finite set)

$\Sigma^n = \{a_1 a_2 \dots a_n \mid a_i \in \Sigma\}$  is the set of words of length  $n$

$\Sigma^* = \{w \mid \exists n \in \mathbb{N}. \exists a_1, a_2, \dots, a_n \in \Sigma. w = a_1 a_2 \dots a_n\}$  is the set of all words over  $\Sigma$

$\Sigma^0 = \{\epsilon\}$  contains only the empty word


A language  $L$  over  $\Sigma$  is a subset  $L \subseteq \Sigma^*$

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :




# Deterministic Automata (DFA)

alphabet

Informal example

$\Sigma = \{0, 1\}$

$M_1$ :




# Deterministic Automata (DFA)

Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



alphabet

$q_0, q_1$  are states




# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



alphabet

$q_0, q_1$  are states


$q_0$  is initial

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



$q_0$  is initial

$q_1$  is final

$q_0, q_1$  are states


alphabet

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



$q_0$  is initial

$q_1$  is final

alphabet

$q_0, q_1$  are states


transitions, labelled by  
alphabet symbols

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



$q_0$  is initial

$q_1$  is final

alphabet

$q_0, q_1$  are states

transitions, labelled by  
alphabet symbols


Accepts the language  $L(M_1) = \{w \in \Sigma^* \mid w \text{ ends with a } 0\} = \Sigma^*0$

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



$q_0$  is initial

$q_1$  is final

alphabet

$q_0, q_1$  are states

transitions, labelled by  
alphabet symbols

Accepts the language  $L(M_1) = \{w \in \Sigma^* \mid w \text{ ends with a } 0\} = \Sigma^*0$


regular language

# Deterministic Automata (DFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_1$ :



$q_0$  is initial

$q_1$  is final

alphabet

$q_0, q_1$  are states

transitions, labelled by  
alphabet symbols

Accepts the language  $L(M_1) = \{w \in \Sigma^* \mid w \text{ ends with a } 0\} = \Sigma^*0$

regular language

regular expression

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \longrightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \longrightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

In the example  $M_1$



# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \rightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

In the example  $M_1$

$M_1 = (Q, \Sigma, \delta, q_0, F)$  for

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \rightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

In the example  $M_1$

$M_1 = (Q, \Sigma, \delta, q_0, F)$  for

$Q = \{q_0, q_1\}$

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \rightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

In the example  $M_1$

$M_1 = (Q, \Sigma, \delta, q_0, F)$  for

$Q = \{q_0, q_1\}$

$\Sigma = \{0, 1\}$

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \rightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

In the example  $M_1$

$M_1 = (Q, \Sigma, \delta, q_0, F)$  for

$Q = \{q_0, q_1\}$     $F = \{q_1\}$

$\Sigma = \{0, 1\}$

# DFA

## Definition

A deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \rightarrow Q$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

## In the example $M_1$

$$Q = \{q_0, q_1\} \quad F = \{q_1\}$$

$$\Sigma = \{0, 1\}$$

$$M_1 = (Q, \Sigma, \delta, q_0, F) \quad \text{for}$$

$$\delta(q_0, 0) = q_1, \delta(q_0, 1) = q_0$$

$$\delta(q_1, 0) = q_1, \delta(q_1, 1) = q_0$$

# DFA

The extended transition function

# DFA

## The extended transition function

Given  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma \rightarrow Q$  to

$$\delta^*: Q \times \Sigma^* \rightarrow Q$$

inductively, by:

$$\delta^*(q, \varepsilon) = q \text{ and } \delta^*(q, wa) = \delta(\delta^*(q, w), a)$$

# DFA

## The extended transition function

Given  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma \rightarrow Q$  to

$$\delta^*: Q \times \Sigma^* \rightarrow Q$$

inductively, by:

$$\delta^*(q, \varepsilon) = q \text{ and } \delta^*(q, wa) = \delta(\delta^*(q, w), a)$$

In  $M_1$ ,  $\delta^*(q_0, 110010) = q_1$



# DFA

## The extended transition function

Given  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma \rightarrow Q$  to

$$\delta^*: Q \times \Sigma^* \rightarrow Q$$

inductively, by:

$$\delta^*(q, \varepsilon) = q \text{ and } \delta^*(q, wa) = \delta(\delta^*(q, w), a)$$

In  $M_1$ ,  $\delta^*(q_0, 110010) = q_1$

## Definition

The language recognised / accepted by a deterministic finite automaton  $M = (Q, \Sigma, \delta, q_0, F)$  is

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \in F\}$$

# DFA

## The extended transition function

Given  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma \rightarrow Q$  to

$$\delta^*: Q \times \Sigma^* \rightarrow Q$$

inductively, by:

$$\delta^*(q, \varepsilon) = q \text{ and } \delta^*(q, wa) = \delta(\delta^*(q, w), a)$$


$$\text{In } M_1, \delta^*(q_0, 110010) = q_1$$

## Definition

The language recognised / accepted by a deterministic finite automaton  $M = (Q, \Sigma, \delta, q_0, F)$  is

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \in F\}$$


$$L(M_1) = \{w0 \mid w \in \{0,1\}^*\}$$

# Regular languages and operations

## Definition

Let  $\Sigma$  be an alphabet. A language  $L$  over  $\Sigma$  ( $L \subseteq \Sigma^*$ ) is regular iff it is recognised by a DFA.

# Regular languages and operations

## Definition

Let  $\Sigma$  be an alphabet. A language  $L$  over  $\Sigma$  ( $L \subseteq \Sigma^*$ ) is regular iff it is recognised by a DFA.

$L(M_1) = \{w0 \mid w \in \{0,1\}^*\}$   
is regular

# Regular languages and operations

$L(M_1) = \{w0 \mid w \in \{0,1\}^*\}$   
is regular

## Definition

Let  $\Sigma$  be an alphabet. A language  $L$  over  $\Sigma$  ( $L \subseteq \Sigma^*$ ) is regular iff it is recognised by a DFA.

## Regular operations

# Regular languages and operations

$L(M_1) = \{w0 \mid w \in \{0,1\}^*\}$   
is regular

## Definition

Let  $\Sigma$  be an alphabet. A language  $L$  over  $\Sigma$  ( $L \subseteq \Sigma^*$ ) is regular iff it is recognised by a DFA.

## Regular operations

Let  $L, L_1, L_2$  be languages over  $\Sigma$ . Then  $L_1 \cup L_2$ ,  $L_1 \cdot L_2$ , and  $L^*$  are languages, where

$$L_1 \cdot L_2 = \{w_1 \cdot w_2 \mid w_1 \in L_1, w_2 \in L_2\}$$

$$L^* = \{w \mid \exists n \in \mathbb{N}. \exists w_1, w_2, \dots, w_n \in L. w = w_1 w_2 \dots w_n\}$$

# Regular languages and operations

## Definition

Let  $\Sigma$  be an alphabet. A language  $L$  over  $\Sigma$  ( $L \subseteq \Sigma^*$ ) is regular iff it is recognised by a DFA.

$L(M_1) = \{w0 \mid w \in \{0,1\}^*\}$   
is regular

## Regular operations

Let  $L, L_1, L_2$  be languages over  $\Sigma$ . Then  $L_1 \cup L_2$ ,  $L_1 \cdot L_2$ , and  $L^*$  are languages, where

$$L_1 \cdot L_2 = \{w_1 \cdot w_2 \mid w_1 \in L_1, w_2 \in L_2\}$$

$$L^* = \{w \mid \exists n \in \mathbb{N}. \exists w_1, w_2, \dots, w_n \in L. w = w_1 w_2 \dots w_n\}$$

$\epsilon \in L^*$  always

# Regular expressions

## Definition



finite representation of infinite  
languages

# Regular expressions

Definition

finite representation of infinite  
languages

# Regular expressions

## Definition

Let  $\Sigma$  be an alphabet. The following are regular expressions

1.  $a$  for  $a \in \Sigma$
2.  $\varepsilon$
3.  $\emptyset$
4.  $(R_1 \cup R_2)$  for  $R_1, R_2$  regular expressions
5.  $(R_1 \cdot R_2)$  for  $R_1, R_2$  regular expressions
6.  $(R_1)^*$  for  $R_1$  regular expression

finite representation of infinite  
languages

# Regular expressions

inductive

## Definition

Let  $\Sigma$  be an alphabet. The following are regular expressions

1.  $a$  for  $a \in \Sigma$
2.  $\varepsilon$
3.  $\emptyset$
4.  $(R_1 \cup R_2)$  for  $R_1, R_2$  regular expressions
5.  $(R_1 \cdot R_2)$  for  $R_1, R_2$  regular expressions
6.  $(R_1)^*$  for  $R_1$  regular expression

finite representation of infinite  
languages

# Regular expressions

inductive

## Definition

example:  
 $(ab \cup a)^*$

Let  $\Sigma$  be an alphabet. The following are regular expressions

1.  $a$  for  $a \in \Sigma$
2.  $\varepsilon$
3.  $\emptyset$
4.  $(R_1 \cup R_2)$  for  $R_1, R_2$  regular expressions
5.  $(R_1 \cdot R_2)$  for  $R_1, R_2$  regular expressions
6.  $(R_1)^*$  for  $R_1$  regular expression

finite representation of infinite  
languages

# Regular expressions

inductive

## Definition

Let  $\Sigma$  be an alphabet. The following are regular expressions

1.  $a$  for  $a \in \Sigma$
2.  $\epsilon$
3.  $\emptyset$
4.  $(R_1 \cup R_2)$  for  $R_1, R_2$  regular expressions
5.  $(R_1 \cdot R_2)$  for  $R_1, R_2$  regular expressions
6.  $(R_1)^*$  for  $R_1$  regular expression

example:  
 $(ab \cup a)^*$

## corresponding languages

$$L(a) = \{a\}$$

$$L(\epsilon) = \{\epsilon\}$$

$$L(\emptyset) = \emptyset$$

$$L(R_1 \cup R_2) = L(R_1) \cup L(R_2)$$

$$L(R_1 \cdot R_2) = L(R_1) \cdot L(R_2)$$

$$L(R_1^*) = L(R_1)^*$$

# Closure under regular operations

# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

# Closure under regular operations

also under  
intersection

## Theorem CI

The class of regular languages is closed under union



# Closure under regular operations

also under  
intersection

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

# Closure under regular operations

also under  
intersection

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

# Closure under regular operations

also under  
intersection

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

## Theorem C4

The class of regular languages is closed under Kleene star

# Closure under regular operations

also under intersection

## Theorem C1

The class of regular languages is closed under union

We can already prove these!

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

## Theorem C4

The class of regular languages is closed under Kleene star

# Closure under regular operations

also under intersection

## Theorem C1

The class of regular languages is closed under union

We can already prove these!

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

But not yet these two...

## Theorem C4

The class of regular languages is closed under Kleene star

# Equivalence of regular expressions and regular languages

# Equivalence of regular expressions and regular languages

## Theorem (Kleene)

A language is regular (i.e., recognised by a finite automaton) iff it is the language of a regular expression.

# Equivalence of regular expressions and regular languages

## Theorem (Kleene)

A language is regular (i.e., recognised by a finite automaton) iff it is the language of a regular expression.

Proof  $\Leftarrow$  easy, as the constructions for the closure properties,  
 $\Rightarrow$  not so easy, we'll skip it for now...



# Equivalence of regular expressions and regular languages

## Theorem (Kleene)

A language is regular (i.e., recognised by a finite automaton) iff it is the language of a regular expression.


needs nondeterminism

Proof  $\Leftarrow$  easy, as the constructions for the closure properties,  
 $\Rightarrow$  not so easy, we'll skip it for now...

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$




# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :




sources of  
nondeterminism

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :




sources of  
nondeterminism

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :




sources of  
nondeterminism

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :



sources of  
nondeterminism


no 1 transition

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :



no 1 transition

no 0 transition


sources of  
nondeterminism

# Nondeterministic Automata (NFA)

## Informal example

$\Sigma = \{0, 1\}$

$M_2$ :



no 1 transition

no 0 transition

sources of  
nondeterminism

Accepts a word iff there **exists** an accepting run



# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example  $M_2$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example  $M_2$

$M_2 = (Q, \Sigma, \delta, q_0, F)$  for

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example  $M_2$

$M_2 = (Q, \Sigma, \delta, q_0, F)$  for

$$Q = \{q_0, q_1, q_2, q_3\}$$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example  $M_2$

$M_2 = (Q, \Sigma, \delta, q_0, F)$  for

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\}$$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

## In the example $M_2$

$M_2 = (Q, \Sigma, \delta, q_0, F)$  for

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\} \quad F = \{q_3\}$$

# NFA

## Definition

A **non**deterministic automaton  $M$  is a tuple  $M = (Q, \Sigma, \delta, q_0, F)$  where

$Q$  is a finite set of states

$\Sigma$  is a finite alphabet

$\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$  is the transition function

$q_0$  is the initial state,  $q_0 \in Q$

$F$  is a set of final states,  $F \subseteq Q$

$$\Sigma_\epsilon = \Sigma \cup \{\epsilon\}$$

## In the example $M_2$

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\} \quad F = \{q_3\}$$

$$M_2 = (Q, \Sigma, \delta, q_0, F) \quad \text{for}$$

$$\delta(q_0, 0) = \{q_0\}$$

$$\delta(q_0, 1) = \{q_0, q_1\}$$

$$\delta(q_0, \epsilon) = \emptyset$$

.....

||



# NFA

The extended transition function

# NFA

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \varepsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\varepsilon \longrightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \varepsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

$\epsilon$ -closure of  $q$ , all states reachable by  
 $\epsilon$ -transitions from  $q$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

$\epsilon$ -closure of  $q$ , all states reachable by  
 $\epsilon$ -transitions from  $q$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

$$E(X) = \bigcup_{x \in X} E(x)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E\left(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a)\right)$$

$\epsilon$ -closure of  $q$ , all states reachable by  $\epsilon$ -transitions from  $q$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

inductively, by:

$$E(X) = \bigcup_{x \in X} E(x)$$

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

$\epsilon$ -closure of  $q$ , all states reachable by  $\epsilon$ -transitions from  $q$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

inductively, by:

$$E(X) = \bigcup_{x \in X} E(x)$$

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E\left(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a)\right)$$

## Definition

The language recognised / accepted by a nondeterministic finite automaton  $M = (Q, \Sigma, \delta, q_0, F)$  is

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \cap F \neq \emptyset\}$$

$\epsilon$ -closure of  $q$ , all states reachable by  $\epsilon$ -transitions from  $q$

# NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

## The extended transition function

Given an NFA  $M = (Q, \Sigma, \delta, q_0, F)$  we can extend  $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$  to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

inductively, by:

$$E(X) = \bigcup_{x \in X} E(x)$$

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

## Definition

The language recognised / accepted by an NFA automaton  $M = (Q, \Sigma, \delta, q_0, F)$  is

$$L(M_2) = \{u101w \mid u, w \in \{0,1\}^*\} \cup \{u11w \mid u, w \in \{0,1\}^*\}$$

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \cap F \neq \emptyset\}$$



# Equivalence of automata

## Definition

# Equivalence of automata

## Definition

Two automata  $M_1$  and  $M_2$  are equivalent if  $L(M_1) = L(M_2)$

# Equivalence of automata

## Definition

Two automata  $M_1$  and  $M_2$  are equivalent if  $L(M_1) = L(M_2)$

## Theorem NFA $\sim$ DFA

Every NFA has an equivalent DFA

# Equivalence of automata

## Definition

Two automata  $M_1$  and  $M_2$  are equivalent if  $L(M_1) = L(M_2)$

## Theorem NFA $\sim$ DFA

Every NFA has an equivalent DFA

Proof via the “powerset construction” /  
determinization

# Equivalence of automata

## Definition

Two automata  $M_1$  and  $M_2$  are equivalent if  $L(M_1) = L(M_2)$

## Theorem NFA $\sim$ DFA

Every NFA has an equivalent DFA

Proof via the “powerset construction” /  
determinization

## Corollary

A language is regular iff it is recognised by a NFA

# Closure under regular operations

# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement



# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

## Theorem C4

The class of regular languages is closed under Kleene star

# Closure under regular operations

## Theorem C1

The class of regular languages is closed under union

## Theorem C2

The class of regular languages is closed under complement

## Theorem C3

The class of regular languages is closed under concatenation

## Theorem C4

The class of regular languages is closed under Kleene star

Now we can prove these too

# Nonregular languages

# Nonregular languages

Theorem (Pumping Lemma)

# Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

# Nonregular languages

every long enough word of a regular language can be pumped

## Theorem (Pumping Lemma)

If  $L$  is a regular language, then there is a number  $p \in \mathbb{N}$  (the pumping length) such that for any  $w \in L$  with  $|w| \geq p$ , there exist  $x, y, z \in \Sigma^*$  such that  $w = xyz$  and

1.  $xy^iz \in L$ , for all  $i \in \mathbb{N}$
2.  $|y| > 0$
3.  $|xy| \leq p$

# Nonregular languages

every long enough word of a regular language can be pumped

## Theorem (Pumping Lemma)

If  $L$  is a regular language, then there is a number  $p \in \mathbb{N}$  (the pumping length) such that for any  $w \in L$  with  $|w| \geq p$ , there exist  $x, y, z \in \Sigma^*$  such that  $w = xyz$  and

1.  $xy^iz \in L$ , for all  $i \in \mathbb{N}$
2.  $|y| > 0$
3.  $|xy| \leq p$

Proof easy, using the pigeonhole principle



# Nonregular languages

every long enough word of a regular language can be pumped

## Theorem (Pumping Lemma)

If  $L$  is a regular language, then there is a number  $p \in \mathbb{N}$  (the pumping length) such that for any  $w \in L$  with  $|w| \geq p$ , there exist  $x, y, z \in \Sigma^*$  such that  $w = xyz$  and

1.  $xy^iz \in L$ , for all  $i \in \mathbb{N}$
2.  $|y| > 0$
3.  $|xy| \leq p$

Proof easy, using the pigeonhole principle

## Example “corollary”

$L = \{ 0^n 1^n \mid n \in \mathbb{N} \}$  is nonregular.

# Nonregular languages

every long enough word of a regular language can be pumped

## Theorem (Pumping Lemma)

If  $L$  is a regular language, then there is a number  $p \in \mathbb{N}$  (the pumping length) such that for any  $w \in L$  with  $|w| \geq p$ , there exist  $x, y, z \in \Sigma^*$  such that  $w = xyz$  and

1.  $xy^iz \in L$ , for all  $i \in \mathbb{N}$
2.  $|y| > 0$
3.  $|xy| \leq p$

Proof easy, using the pigeonhole principle

## Example “corollary”

$L = \{ 0^n 1^n \mid n \in \mathbb{N} \}$  is nonregular.

Note the logical structure!