


Undecidability of first-order logic

Ana Sokolova  UNIVERSITY
of SALZBURG

University of Vienna 9.10.18

www.cs.uni-salzburg.at/~anas/undec-FOL

Alonzo Church
[1903-1995]
1935-36



Alan Turing
[1912-1954]
1936-37

Decidability

study motivated by
Hilbert's problems, in
particular by the
question of decidability
of FOL

A problem (set) P is decidable if there exists an algorithm that returns YES on any $p \in P$ and NO otherwise.

decision procedure
= YES/NO oracle
= computable function
= Turing machine

Hilbert's

1928

Entscheidungsproblem

Is there an algorithm that decides whether arbitrary FOL formula is valid / satisfiable ?

Is $\text{VALID} = \{\varphi \mid \varphi \text{ is a valid first-order formula}\}$ decidable ?

Clearly, VALID is decidable iff
 $\text{SAT} = \{\varphi \mid \varphi \text{ is a satisfiable first-order formula}\}$ is.

The answer is
NO

Outline of Turing's proof

Julius Richard Büchi
[1924 - 1984]
1961

Turing
introduced the Turing
machines and proved
first:

Reduction from the **halting
problem** to unsatisfiability

Lecture notes by
Larry Moss and Guram
Bezhanishvili 2008

Theorem HALT


The set

$\text{HALT} = \{ (M, i) \mid M \text{ is a Turing machine that halts on input } i \}$
is undecidable.

Theorem HALT-e

The set

$\text{HALT-e} = \{ M \mid M \text{ is a Turing machine that halts on empty input} \}$
is undecidable.



$$\exists x \forall y \dots \wedge (\forall x \forall z \dots \vee \forall x \exists y \dots) \wedge \dots$$

FOL: Reduction

HALT-e
to
UNSAT

Reduction Theorem

For a Turing machine M , we construct a FOL formula φ_M such that φ_M is unsatisfiable iff M halts on empty input.


Corollary - Undecidability of FOL

$\text{UNSAT} = \{\varphi \mid \varphi \text{ is an unsatisfiable first-order formula}\}$ is undecidable.
Hence, VALID is undecidable too.

What would happen to
HALT-e if UNSAT were
decidable?

Turing machine

= finite control (automaton states)
+ (potentially) infinite tape
+ head for reading/writing



unlimited access
to infinite memory

Turing machines

A Turing machine is a tuple $M = (Q, \Sigma, \delta, q_0, q_1)$, where


Q is a finite set of states with q_0 the halting state and q_1 the starting state,
($q_0, q_1 \in Q$)

Σ is a finite set, the alphabet, and

$\delta: Q \setminus \{q_0\} \times \Sigma \longrightarrow \Sigma \times \{L, C, R\} \times Q$ is the transition function.

$\delta(q,a) = (b,X,r)$ means that in a state q ,
reading the symbol a from the cell
on which the head is positioned,
the TM writes b in place of a ,
moves the head for one cell in direction X , and
changes to state r .

Example




Turing machines

Compute via configurations, triples (q,w,h)
notation uqv where $uv = w$ and $|u| = h-1$.

configuration:
aqab

infinite tape



state

↑
q

read / write head

$uaqbv \models uracv$ iff $\delta(q,b) = (c,L,r)$
 $uaqbv \models uarcv$ iff $\delta(q,b) = (c,C,r)$
 $uqbv \models ucrv$ iff $\delta(q,b) = (c,R,r)$
 $qbv \models r\Box cv$ iff $\delta(q,b) = (c,L,r)$
 $qbv \models rcv$ iff $\delta(q,b) = (c,C,r)$
 $uaq \models uarc$ iff $\delta(q,\Box) = (c,C,r)$
 $uaq \models uacr$ iff $\delta(q,\Box) = (c,R,r)$


M decides P iff

for all $p \in P$, $q_1p \models^* q_0\text{YES}$
 for all $p \notin P$, $q_1p \models^* q_0\text{NO}$


sequence of configurations

Example run on empty input

Example




gives us an intended model



The intended model of

φ_M

Example




...

				...					
				S _a	S _b	S _a	S _b	S _a	Q ₂
				S _a	S _b	S _a	S _b	Q ₁	
				S _a	S _b	S _a	Q ₂		
				S _a	S _b	Q ₁			
				S _a	Q ₂				
				Q ₁					

...

The signature of φ_M

Example



				S_a	S_b	S_a	S_b	S_a	Q_2
				S_a	S_b	S_a	S_b	Q_1	
				S_a	S_b	S_a	Q_2		
				S_a	S_b	Q_1			
				S_a	Q_2				
				Q_1					

Q_i - unary predicate symbol for each $q_i \in Q$

S_a - unary predicate symbol for each $a \in \Sigma$

head - unary predicate symbol

+ some more function and predicate symbols for describing the upper half plane:

origin - constant symbol

east, west, north - unary function symbols

y-axis, left-side, right-side, bottom - unary predicate symbols

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

$$\forall x. \bigvee_{a \in \Sigma} (S_a(x) \wedge \bigwedge_{b \neq a} \neg S_b(x))$$

one-step-formulas \wedge

head-movement-formula

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

$$Q_1(\text{origin}) \wedge \bigwedge_{k \neq 1} \neg Q_k(\text{origin}) \wedge \\ \forall x. \text{bottom}(x) \rightarrow S_{\square}(x) \wedge (x = \text{origin} \leftrightarrow \text{head}(x))$$

one-step-formulas \wedge

head-movement-formula

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

Homework

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

$$\forall x. \neg Q_0(x)$$

The encoding φ_M

$\varphi_M =$

upper-half-plane \wedge
 unique-symbol-per-cell \wedge
 initial-situation \wedge
 no-head-no-change \wedge
 does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

$$\delta(q_i, a) = (b, L, q_j)$$

$$\forall x. (\text{head}(x) \wedge Q_i(x) \wedge S_a(x)) \rightarrow$$

$$(S_b(\text{north}(x)) \wedge$$

$$\text{head}(\text{north} \circ \text{west}(x)) \wedge$$

$$Q_j(\text{north} \circ \text{west}(x)))$$

$$\forall x. (\text{head}(x) \wedge Q_i(x) \wedge S_a(x)) \rightarrow$$

...

$$\forall x. (\text{head}(x) \wedge Q_i(x) \wedge S_a(x)) \rightarrow$$

...

The encoding φ_M

$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

$$\begin{aligned} \forall x. \text{head}(x) \wedge Q_i(x) \wedge S_a(x) \rightarrow \\ & x = \text{origin} \vee \\ & \exists y. (\text{north} \circ \text{west}(y) = x \wedge \\ & \bigvee_{\delta(q_j, b) = (c, L, q_i)} (\text{head}(y) \wedge Q_j(y) \wedge S_b(y))) \\ & \vee (\text{north}(y) = x \wedge \dots) \\ & \vee (\text{north} \circ \text{east}(y) = x \wedge \dots) \end{aligned}$$

The encoding φ_M


$\varphi_M =$ upper-half-plane \wedge
unique-symbol-per-cell \wedge
initial-situation \wedge
no-head-no-change \wedge
does-not-halt \wedge

one-step-formulas \wedge

head-movement-formula

Let's write φ_M for

Example



The encoding φ_M

Next week we will
prove

φ_M is satisfiable iff M does not halt on empty input.

\Leftarrow easy:
the intended model is
indeed a model

\Rightarrow Simulation Lemma:
given a model of φ_M
we can show that M
does not halt on empty