


Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$




Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :




sources of
nondeterminism

Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :




sources of
nondeterminism

Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :




sources of
nondeterminism

Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :



sources of
nondeterminism


no 1 transition

Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :



sources of
nondeterminism

no 1 transition


no 0 transition

Nondeterministic Automata (NFA)

Informal example

$\Sigma = \{0, 1\}$

M_2 :



sources of
nondeterminism

no 1 transition

no 0 transition

Accepts a word iff there **exists** an accepting run

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

$M_2 = (Q, \Sigma, \delta, q_0, F)$ for

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

$M_2 = (Q, \Sigma, \delta, q_0, F)$ for

$$Q = \{q_0, q_1, q_2, q_3\}$$

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

$M_2 = (Q, \Sigma, \delta, q_0, F)$ for

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\}$$

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

$M_2 = (Q, \Sigma, \delta, q_0, F)$ for

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\} \quad F = \{q_3\}$$

NFA

Definition

A **non**deterministic automaton M is a tuple $M = (Q, \Sigma, \delta, q_0, F)$ where

Q is a finite set of states

Σ is a finite alphabet

$\delta: Q \times \Sigma_{\epsilon} \longrightarrow \mathcal{P}(Q)$ is the transition function

q_0 is the initial state, $q_0 \in Q$

F is a set of final states, $F \subseteq Q$

$$\Sigma_{\epsilon} = \Sigma \cup \{\epsilon\}$$

In the example M

$$Q = \{q_0, q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\} \quad F = \{q_3\}$$

$$M_2 = (Q, \Sigma, \delta, q_0, F) \quad \text{for}$$

$$\delta(q_0, 0) = \{q_0\}$$

$$\delta(q_0, 1) = \{q_0, q_1\}$$

$$\delta(q_0, \epsilon) = \emptyset$$

.....

NFA

The extended transition function

NFA

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \varepsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\varepsilon \longrightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \varepsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

ϵ -closure of q , all states reachable by
 ϵ -transitions from q

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

ϵ -closure of q , all states reachable by
 ϵ -transitions from q

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \longrightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \longrightarrow \mathcal{P}(Q)$$

$$E(X) = \bigcup_{x \in X} E(x)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a))$$

ϵ -closure of q , all states reachable by ϵ -transitions from q

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

$$E(X) = \bigcup_{x \in X} E(x)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E\left(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a)\right)$$

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

ϵ -closure of q , all states reachable by ϵ -transitions from q

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

$$E(X) = \bigcup_{x \in X} E(x)$$

inductively, by:

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E\left(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a)\right)$$

Definition

The language recognised / accepted by a nondeterministic finite automaton $M = (Q, \Sigma, \delta, q_0, F)$ is

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \cap F \neq \emptyset\}$$

ϵ -closure of q , all states reachable by ϵ -transitions from q

NFA

$$E(q) = \{q' \mid q' = q \vee \exists n \in \mathbb{N}^+. \exists q_0, \dots, q_n \in Q. q_0 = q, q_n = q', q_{i+1} \in \delta(q_i, \epsilon), \text{ for } i = 0, \dots, n-1\}$$

The extended transition function

Given an NFA $M = (Q, \Sigma, \delta, q_0, F)$ we can extend $\delta: Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ to

$$\delta^*: Q \times \Sigma^* \rightarrow \mathcal{P}(Q)$$

$$E(X) = \bigcup_{x \in X} E(x)$$

inductively, by:

$$\delta^*(q, \epsilon) = E(q) \text{ and } \delta^*(q, wa) = E\left(\bigcup_{q' \in \delta^*(q, w)} \delta(q', a)\right)$$

$$\text{In } M_2, \delta^*(q_0, 0110) = \{q_0, q_2, q_3\}$$

Definition

The language recognised / accepted by an automaton $M = (Q, \Sigma, \delta, q_0, F)$ is

$$L(M) = \{w \in \Sigma^* \mid \delta^*(q_0, w) \cap F \neq \emptyset\}$$

$$L(M_2) = \{u101w \mid u, w \in \{0,1\}^*\} \cup \{u11w \mid u, w \in \{0,1\}^*\}$$

Equivalence of automata

Definition

Equivalence of automata

Definition

Two automata M_1 and M_2 are equivalent if $L(M_1) = L(M_2)$

Equivalence of automata

Definition

Two automata M_1 and M_2 are equivalent if $L(M_1) = L(M_2)$

Theorem NFA \sim DFA

Every NFA has an equivalent DFA

Equivalence of automata

Definition

Two automata M_1 and M_2 are equivalent if $L(M_1) = L(M_2)$

Theorem NFA \sim DFA

Every NFA has an equivalent DFA

Proof via the “powerset construction” /
determinization

Equivalence of automata

Definition

Two automata M_1 and M_2 are equivalent if $L(M_1) = L(M_2)$

Theorem NFA \sim DFA

Every NFA has an equivalent DFA

Proof via the “powerset construction” /
determinization

Corollary

A language is regular iff it is recognised by a NFA

Closure under regular operations

Closure under regular operations

Theorem C1

The class of regular languages is closed under union

Closure under regular operations

Theorem C1

The class of regular languages is closed under union

Theorem C2

The class of regular languages is closed under complement

Closure under regular operations

Theorem C1

The class of regular languages is closed under union

Theorem C2

The class of regular languages is closed under complement

Theorem C3

The class of regular languages is closed under concatenation

Closure under regular operations

Theorem C1

The class of regular languages is closed under union

Theorem C2

The class of regular languages is closed under complement

Theorem C3

The class of regular languages is closed under concatenation

Theorem C4

The class of regular languages is closed under Kleene star

Closure under regular operations

Theorem C1

The class of regular languages is closed under union

Theorem C2

The class of regular languages is closed under complement

Theorem C3

The class of regular languages is closed under concatenation

Theorem C4

The class of regular languages is closed under Kleene star

Now we can prove these too

Regular expressions

Definition

finite representation of infinite
languages

Regular expressions

Definition

finite representation of infinite
languages

Regular expressions

Definition

Let Σ be an alphabet. The following are regular expressions

1. a for $a \in \Sigma$
2. ε
3. \emptyset
4. $(R_1 \cup R_2)$ for R_1, R_2 regular expressions
5. $(R_1 \cdot R_2)$ for R_1, R_2 regular expressions
6. $(R_1)^*$ for R_1 regular expression

finite representation of infinite
languages

Regular expressions

inductive

Definition

Let Σ be an alphabet. The following are regular expressions

1. a for $a \in \Sigma$
2. ε
3. \emptyset
4. $(R_1 \cup R_2)$ for R_1, R_2 regular expressions
5. $(R_1 \cdot R_2)$ for R_1, R_2 regular expressions
6. $(R_1)^*$ for R_1 regular expression

finite representation of infinite
languages

Regular expressions

inductive

Definition

example:
 $(ab \cup a)^*$

Let Σ be an alphabet. The following are regular expressions

1. a for $a \in \Sigma$
2. ϵ
3. \emptyset
4. $(R_1 \cup R_2)$ for R_1, R_2 regular expressions
5. $(R_1 \cdot R_2)$ for R_1, R_2 regular expressions
6. $(R_1)^*$ for R_1 regular expression

finite representation of infinite
languages

Regular expressions

inductive

Definition

Let Σ be an alphabet. The following are regular expressions

1. a for $a \in \Sigma$
2. ϵ
3. \emptyset
4. $(R_1 \cup R_2)$ for R_1, R_2 regular expressions
5. $(R_1 \cdot R_2)$ for R_1, R_2 regular expressions
6. $(R_1)^*$ for R_1 regular expression

example:
 $(ab \cup a)^*$

corresponding languages

$$L(a) = \{a\}$$

$$L(\epsilon) = \{\epsilon\}$$

$$L(\emptyset) = \emptyset$$

$$L(R_1 \cup R_2) = L(R_1) \cup L(R_2)$$

$$L(R_1 \cdot R_2) = L(R_1) \cdot L(R_2)$$

$$L(R_1^*) = L(R_1)^*$$

Equivalence of regular expressions and regular languages

Equivalence of regular expressions and regular languages

Theorem (Kleene)

A language is regular (i.e., recognised by a finite automaton) iff it is the language of a regular expression.

Equivalence of regular expressions and regular languages

Theorem (Kleene)

A language is regular (i.e., recognised by a finite automaton) iff it is the language of a regular expression.

Proof \Leftarrow easy, as the constructions for the closure properties,
 \Rightarrow not so easy, we'll skip it for now...

Nonregular languages

Nonregular languages

Theorem (Pumping Lemma)

Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

If L is a regular language, then there is a number $p \in \mathbb{N}$ (the pumping length) such that for any $w \in L$ with $|w| \geq p$, there exist $x, y, z \in \Sigma^*$ such that $w = xyz$ and

1. $xy^iz \in L$, for all $i \in \mathbb{N}$
2. $|y| > 0$
3. $|xy| \leq p$

Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

If L is a regular language, then there is a number $p \in \mathbb{N}$ (the pumping length) such that for any $w \in L$ with $|w| \geq p$, there exist $x, y, z \in \Sigma^*$ such that $w = xyz$ and

1. $xy^iz \in L$, for all $i \in \mathbb{N}$
2. $|y| > 0$
3. $|xy| \leq p$

Proof easy, using the pigeonhole principle

Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

If L is a regular language, then there is a number $p \in \mathbb{N}$ (the pumping length) such that for any $w \in L$ with $|w| \geq p$, there exist $x, y, z \in \Sigma^*$ such that $w = xyz$ and

1. $xy^iz \in L$, for all $i \in \mathbb{N}$
2. $|y| > 0$
3. $|xy| \leq p$

Proof easy, using the pigeonhole principle

Example “corollary”

$L = \{ 0^n 1^n \mid n \in \mathbb{N} \}$ is nonregular.

Nonregular languages

every long enough word of a regular language can be pumped

Theorem (Pumping Lemma)

If L is a regular language, then there is a number $p \in \mathbb{N}$ (the pumping length) such that for any $w \in L$ with $|w| \geq p$, there exist $x, y, z \in \Sigma^*$ such that $w = xyz$ and

1. $xy^iz \in L$, for all $i \in \mathbb{N}$
2. $|y| > 0$
3. $|xy| \leq p$

Proof easy, using the pigeonhole principle

Example “corollary”

$L = \{ 0^n 1^n \mid n \in \mathbb{N} \}$ is nonregular.

Note the logical structure!