

Package ‘cidtree’

April 24, 2024

Type Package

Title cidtree: A Package for mapping concepts using a tree-based data dictionary

Version 0.1.0

Author Jake Peters

Maintainer The package maintainer <jcbptrs@gmail.com>

Description

This package uses `data.tree` to construct a tree object from JSON representing a data dictionary. This package was originally developed for the Connect for Cancer Prevention Cohort Study.

License MIT License

Encoding UTF-8

LazyData true

Suggests knitr,
knitr,
rmarkdown

VignetteBuilder knitr

RoxygenNote 7.3.1

Roxygen list(markdown = TRUE)

R topics documented:

construct_dictionary_tree	2
get_cid	2
get_key	3
get_meta	3
get_responses	4
is_valid_cid	4
Index	6

```
construct_dictionary_tree
```

Construct a Dictionary Tree from JSON Files

Description

This function reads JSON files from a specified directory, creates nodes for each file, and builds a hierarchical tree based on the relationships defined within the files.

Usage

```
construct_dictionary_tree(path = "./data/test_dictionary")
```

Arguments

`path` The path to the directory containing JSON files.

Value

A Node object representing the root of the dictionary tree.

Examples

```
dd <- construct_dictionary_tree("./data/test_dictionary")
# Print output so that it does not wrap on the screen
output <- capture.output(print(dd, 'concept_str', 'concept_type', 'pathString'))
cat(output, sep="\n")
```

```
get_cid
```

Retrieve the Concept ID Associated with a Key

Description

This function returns the concept ID (cid) corresponding to a given key within the `data.tree` object representing the data dictionary.

Usage

```
get_cid(dd, key)
```

Arguments

`dd` A `data.tree` object representing the data dictionary.
`key` A key to locate the corresponding concept ID.

Value

The concept ID associated with the given key. If no match is found, returns `NULL`.

Examples

```
# Assuming `dd` is a properly structured `data.tree` object
# and 'my_key' is a valid key in the tree:
concept_id <- get_cid(dd, 'my_key')
```

`get_key`*Retrieve the Key Associated with a Concept ID from a Data Tree*

Description

This function takes a `data.tree` object representing a data dictionary and a concept ID (`cid`), returning the "key" associated with that specific concept ID within the data tree.

Usage

```
get_key(dd, cid)
```

Arguments

<code>dd</code>	A <code>data.tree</code> object representing the data dictionary.
<code>cid</code>	A concept ID as a string or numeric value, used to locate the specific node within the data tree whose key is desired.

Value

The key associated with the given concept ID. If the concept ID does not exist, returns `NULL`.

Examples

```
# Assuming `dd` is a properly structured `data.tree` object
# and '123' is a valid concept ID in the tree:
key_value <- get_key(dd, '123')
```

`get_meta`*Retrieve Metadata for a Concept*

Description

This function retrieves metadata for a concept based on whether it's a valid concept ID (`cid`) or key.

Usage

```
get_meta(dd, concept)
```

Arguments

<code>dd</code>	A <code>data.tree</code> object representing the data dictionary.
<code>concept</code>	The concept ID or key to find metadata for.

Value

A dataframe containing metadata for the given concept, or NULL if not found.

Examples

```
# Assuming `dd` is a properly structured `data.tree` object:
metadata <- get_meta(dd, '123456789') # for a valid cid
metadata <- get_meta(dd, 'FinanceDept') # for a valid key
```

get_responses	<i>Retrieve Responses for a Concept</i>
---------------	---

Description

This function retrieves responses associated with a given concept.

Usage

```
get_responses(dd, concept)
```

Arguments

dd	A <code>data.tree</code> object representing the data dictionary.
concept	The concept ID or key whose responses are to be retrieved.

Value

Responses associated with the concept if it is a question; otherwise, NULL.

Examples

```
# Assuming `dd` is a properly structured `data.tree` object:
responses <- get_responses(dd, '123456789')
```

is_valid_cid	<i>Validate if the Input is a 9-digit Concept ID (cid)</i>
--------------	--

Description

This function checks if a given input is a valid 9-digit concept ID. Returns TRUE if valid, FALSE otherwise.

Usage

```
is_valid_cid(input)
```

Arguments

input	The input to check, expected to be a string or numeric type.
-------	--

Value

A boolean indicating if the input is a valid 9-digit concept ID.

Examples

```
is_valid_cid(123456789)  # Should return TRUE
is_valid_cid("987654321") # Should return TRUE
is_valid_cid(12345)      # Should return FALSE
is_valid_cid(9876543210) # Should return FALSE
```

Index

`construct_dictionary_tree`, [2](#)

`get_cid`, [2](#)

`get_key`, [3](#)

`get_meta`, [3](#)

`get_responses`, [4](#)

`is_valid_cid`, [4](#)