

Azure Databricks

What is Azure Databricks?


Apache Spark-based

Analytics platform

Provides

- One-click setup
- Streamlined workflows and
- An interactive workspace
- Enables collaboration between data scientists, data engineers, and business analysts.

Azure Databricks



Azure Databricks

For a big data pipeline, the data is ingested into Azure

This data lands in


- Azure Blob Storage or
- Azure Data Lake Storage

Use Azure Databricks to read data from multiple data sources


- Azure Blob Storage
- Azure Data Lake Storage
- Azure Cosmos DB, or
- Azure SQL Data Warehouse

Using Databricks, turn it into breakthrough insights

Azure Databricks



Hands-On: Create Databricks Workspace



Azure Databricks

Hands-On: Create Databricks Workspace

[Basics *](#)[Networking](#)[Tags](#)[Review + Create](#)

Project Details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription * ⓘ

<your subscription> ▼

Resource group * ⓘ

(New) databricks-quickstart ▼

[Create new](#)

Intance Details

Workspace name *

mydatabricksws ✓

Location *

West US 2 ▼

Pricing Tier * ⓘ

Standard (Apache Spark, Secure with Azure AD) ^


Standard (Apache Spark, Secure with Azure AD)

Premium (+ Role-based access controls)

Trial (Premium - 14-Days Free DBUs)

Hands-On: Create a Spark cluster in Databricks

- Go to the Databricks workspace that you created, and then click Launch Workspace.
- You are redirected to the Azure Databricks portal.
- Click New Cluster



Hands-On: Create a Spark cluster in Databricks

- Make sure you select the Terminate after __ minutes of inactivity checkbox
- Provide a duration (in minutes) to terminate the cluster, if the cluster is not being used.

Microsoft Azure

Create Cluster

New Cluster Cancel Create Cluster **2-8 Workers:** 28.0-112.0 GB Memory, 8-32 Cores, 1.5-6 DBU
1 Driver: 14.0 GB Memory, 4 Cores, 0.75 DBU

Cluster Name
mysparkcluster

Cluster Mode ?
Standard

Pool ?
None

Databricks Runtime Version ? [Learn more](#)
Runtime: 6.4 (Scala 2.11, Spark 2.4.5)

New This Runtime version supports only Python 3.

Autopilot Options

☒ Enable autoscaling ?

☒ Terminate after minutes of inactivity ?

Worker Type ? Min Workers Max Workers
Standard_DS3_v2 14.0 GB Memory, 4 Cores, 0.75 DBU |

Driver Type
Same as worker 14.0 GB Memory, 4 Cores, 0.75 DBU |

► Advanced Options

Run a Spark SQL job

Hands-On: Run a Spark SQL job

Source Code:
[atinNotebook1.ipynb](#)

The screenshot displays the Azure Databricks web interface. On the left is a dark sidebar with navigation icons and labels: Home, Workspace, Recents, Data, Clusters, Jobs, and Models. The top of the sidebar is labeled 'Databricks'. The main content area features the 'Azure Databricks' logo at the top. Below the logo, there are two primary action cards: 'Explore the Quickstart Tutorial' (with a document icon) and 'Import & Explore Data' (with a cloud upload icon). The 'Explore the Quickstart Tutorial' card includes the text: 'Spin up a cluster, run queries on preloaded data, and display results in 5 minutes.' The 'Import & Explore Data' card includes the text: 'Quickly import data, preview its schema, create a table, and query it in a notebook.' Below these cards are two sections: 'Common Tasks' and 'Recents'. In the 'Common Tasks' section, the 'New Notebook' option, represented by a document icon, is highlighted with a red rectangular box. The 'Recents' section contains the text: 'Recent files appear here as you work.'

Hands-On: Run a Spark SQL job

- The following command sets the Azure storage access information.
 - `blob_account_name = "azureopendatastorage"`
 - `blob_container_name = "citydatacontainer"`
 - `blob_relative_path = "Safety/Release/city=Boston"`
 - `blob_sas_token = r"?st=2019-02-26T02%3A34%3A32Z&se=2119-02-27T02%3A34%3A00Z&sp=rl&sv=2018-03-28&sr=c&sig=XIJVWA7fMXCSxCKqJm8psMOh0W4h7cSYO28coRqF2fs%3D"`

Hands-On: Run a Spark SQL job

- The following command allows Spark to read from Blob storage remotely
 - `wasbs_path = 'wasbs://%s@%s.blob.core.windows.net/%s' % (blob_container_name, blob_account_name, blob_relative_path)`
 - `spark.conf.set('fs.azure.sas.%s.%s.blob.core.windows.net' % (blob_container_name, blob_account_name), blob_sas_token)`
 - `print('Remote blob path: ' + wasbs_path)`

Hands-On: Run a Spark SQL job

- The following command creates a DataFrame
 - `df = spark.read.parquet(wasbs_path)`
 - `print('Register the DataFrame as a SQL temporary view: source')`
 - `df.createOrReplaceTempView('source')`





Hands-On: Run a Spark SQL job

- Run a SQL statement return the top 10 rows of data
 - `print('Displaying top 10 rows: ')`
 - `display(spark.sql('SELECT * FROM source LIMIT 10'))`

```
1 print('Displaying top 10 rows: ')
2 display(spark.sql('SELECT * FROM source LIMIT 10'))
```


▶ (1) Spark Jobs

data ^T ype ▼	dataSub ^T ype ▼	date ^T ime ▼	category ▼	subcategory ▼	status ▼	address ▼	latitude ▼	longitude ▼	source ▼	extendedProperties ▼
Safety	311_All	2011-08-11T11:02:16.000+0000	Recycling	Request for Recycling Cart	Closed	43 Howell St Dorchester MA 02125	42.3255	-71.0587	Employee Generated	null
Safety	311_All	2016-12-15T09:08:21.000+0000	Street Cleaning	Pick up Dead Animal	Closed	74 Aldie St Allston MA 02134	42.3588	-71.1335	Citizens Connect App	null
Safety	311_All	2017-01-26T18:45:00.000+0000	Enforcement & Abandoned Vehicles	Parking Enforcement	Closed	98 Waltham St Roxbury MA 02118	42.3436	-71.0713	Constituent Call	null




Hands-On: Run a Spark SQL job

- You now create a visual representation of this data



Apache Spark-based analytics platform



Azure Databricks concepts

Azure Databricks concepts

Workspace

- Environment for accessing all of your Azure Databricks assets.
- Organizes objects into folders

Objects

Notebooks

Libraries

Dashboards

Experiments

Notebook

A web-based interface for documents

Document contain

- Runnable commands
- Visualizations, and
- Narrative text.

Dashboard

- Provides access to visualizations




Library

A package of code available to the notebook

Databricks runtimes include many libraries

You can add your own.



New Library

Language

Install PyPi Package

You can specify a package name with an optional [version specification](#)

PyPi Name

[Install Library](#)

Upload Egg


Library Name

Egg File:

[Create Library](#)

Experiment

- A collection of MLflow runs for training a machine learning model.



Authentication and authorization

User

- A unique individual who has access to the system.

Group

- A collection of users.

Access control list (ACL)

- A list of permissions attached to the objects.
- Specifies which users or system processes are granted access to the objects

Authentication



Who are you?

Validate a system is accessing by the right person

Authorization



Are you allowed to do that?


Check users' permissions to access data

Work with Notebooks

What is Notebook?


- A web-based interface to a document that contains
 - Runnable code
 - Visualizations, and
 - Narrative text

Hands-On: Create a notebook



Hands-On

- Open a Notebook
- Delete a Notebook
- Rename a notebook
- Import a notebook
- Export a notebook



Hands-On: Notebooks and clusters

- Before you can do any work in a notebook, you must first attach the notebook to a cluster
- Attach a notebook to a cluster
- Detach a notebook from a cluster
- View all notebooks attached to a cluster
- Schedule a notebook

Work with Jobs

What is a Job?

- A way of running a notebook on a scheduled basis
- Can create and run jobs using the
 - UI
 - CLI
 - By invoking the Jobs API

View jobs

- Click the Jobs icon Jobs Menu Icon in the sidebar

Jobs

🕒 ? 👤

+ Create Job

AllOwned by meAccessible By Me

🔍 Filter

Name ↑	Job ID	Created By	Task	Cluster	Schedule	Last Run	Action
● Job A	5	test		8 Workers: Standard_DS3_v2 (beta) 3.2 (includes Apache Spark 2.2.0, Scala 2.10)	None		✕
● Job B	6	test		8 Workers: Standard_DS3_v2 (beta) 3.2 (includes Apache Spark 2.2.0, Scala 2.10)	None		✕
● Job C	7	test		8 Workers: Standard_DS3_v2 (beta) 3.2 (includes Apache Spark 2.2.0, Scala 2.10)	None		✕

Hands-On: Create a job

Hands-On: Run a job

- Schedule a job
- Pause and resume a job schedule
- Run a job immediately

Hands-On: View job run details

Library dependencies

- To get the full list of the driver library dependencies, run the following command inside a notebook
 - `%sh`
 - `ls /databricks/jars`


Libraries Overview

Libraries Overview

- To make third-party or custom code available to notebooks and jobs running on your clusters, you can install a library.
- Libraries can be installed using:
 - Workspace libraries
 - Serve as a local repository from which you create cluster-installed libraries
 - Cluster libraries
 - Can be used by all notebooks running on a cluster
 - Can install a cluster library directly from a public repository such as PyPI
 - Notebook-scoped Python libraries
 - Allow to install Python libraries and create an environment scoped to a notebook session
 - These libraries do not persist and must be re-installed for each session.

Hands-On: Create a workspace library

- Right-click the workspace folder where you want to store the library.
- Select Create > Library.



Create Library

Library Source

Library Type

Library Name

Drop JAR here

Hands-On: Install a library on a cluster

- Two ways to install a library on a cluster:
 - Install a workspace library that has been already been uploaded to the workspace.
 - Install a library for use with a specific cluster only

Thanks