

		<ol style="list-style-type: none"> 1. A low-voltage switchgear and control gear assembly is a combination of low-voltage switching devices together with associated equipment (for controlling, measuring, signaling, etc) complete with all internal mechanical and electrical interconnections and structural parts. 2. LT panel to be (Totally Type Tested Assembly) as per IEC: 61439-1 & 2. 3. The sizing of LV boards shall be dependent on conditions such as total load connected to a board, diversity factors for various loads connected, Fault Level and Voltage Regulation Considerations, etc. 4. Short time rating for bus bars, ckt. breakers, current transformers and swgr. assembly is 50kA for 1 second. 5. LT Panel shall also be tested of design as per Seismic Zone Vol IEC 60068-3-3. 6. All switchboard frames and load bearing members shall be fabricated using suitable mild steel structural sections or pressed and shaped cold-rolled sheet steel of thickness 2.0 mm. 7. All switchboards shall be of dust-proof and vermin-proof construction and shall be provided with a degree of protection of IP: 5X as per IS/IEC 60947. However, the busbar chambers having a degree of protection of IP: 42 are also acceptable where continuous busbar rating is 1600A and above. Provision shall be made in all compartments for providing IP: 5X degree of protection when circuit - breaker or module trolley has been removed. All cut-outs shall be provided with EPDM / Neoprene gaskets. 8. Panel shall be rated for Impulse withstand capability equal to or greater than the switchgears inside the panel. 9. The metal enclosed switchgear shall be designed to operate continuously with reference to ambient temperature of 50°C without any de-rating. 10. The Circuit Breakers / Contactors shall be of air break type & should conform to the requirements of IS / IEC 60947. MCCB shall be provided for 100A, 125A, 160A, 250A & 400A supply feeders. The motor feeders for 110kW & above shall be Air Circuit Breaker controlled. 11. For 415V system, busduct assemblies shall be preferred for incoming connection from transformers to the switchboard and interconnecting sections between switchboards wherever transformer rating is 1000KVA or above. 12. LT panel construction shall be Indoor, ACB feeder single front and remaining double front, Draw out type. 13. The FORM of separation is 4B. 14. All ACB feeder in LT Panel shall be draw out type numerical relay.
--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<p>15. LT switchgear design shall be as per provision of termination of bus duct.</p> <p>16. LT panel flange & Bus duct flange should be matched & termination shall be done as per design.</p> <p>17. Provision for interlocking of LV Incomer breaker with HV side breaker shall be provided such that if the HV breaker trips then the LV breaker will trip, and it shall not be possible to close the LV breaker unless the HV side breaker is closed.</p> <p>18. The Panel shall be indoor type having incoming, sectionalization, outgoing switchgears etc. as per requirement. The design shall be cubical type. The degree of enclosure protection shall be IP 42.</p> <p>19. Bidder shall submit valid type test reports (as per relevant IEC/IS Standard) for approval. The type test reports submitted shall be of tests conducted within last 10 years.</p> <p>20. Bidder should have conducted type test on identical panel to those offered.</p> <p>21. Final scheme, components of switchgear assembly and number of feeders in LT switchgear shall be finalized at the stage of detailed engineering.</p> <p>22. Relevant IS/IEC standards shall be applicable for LT switchgear.</p> <p>23. All ACB's, MCCB's shall be draw out type module.</p> <p>24. All MCCB's with Microprocessor based LSIG release.</p> <p>25. All MCCB's shall be 80-120% setting range.</p> <p>26. All current rating of switchgear shall be at 50 DEG C ambient.</p> <p>27. For all VCB's, ACB's, MCCB's, MPCB's & MCB's feeder consider ON/OFF/TRIP, SPRING CHARGE, TCH, SERVICE POS TEST indication, L/R & TNC switch, phase indication R, Y, B to be provided.</p> <p>28. MFM shall be with communication on Ethernet port.</p> <p>29. Digital MFM 3-PH, 4-Wire (Programmable) CT, PT (Primary & Secondary)</p> <p>30. Spare contact of all components (ACB, MPCB, MCCB, Relay, Aux contact) wired up to terminal.</p> <p>31. Busbar insulation Heat shrinkable PVC sleeve with Identification.</p> <p>32. Bi-metallic strip to be used for different type of material connected.</p> <p>33. Space heater, Thermostat circuit, Door limit switch & Illumination lamp will be mounted in cable chamber.</p> <p>34. LT breaker has to be provided for supply to motors of 75 KW and above rating. MPR relay with single phase preventer should be provided for motor protection.</p> <p>35. Interlocks and protection as per CEA guideline shall be provided.</p>
18	Control Switch & Station	240 V AC control switch station to be provided with proper enclosure & proper earthing arrangement. (Explosion proof wherever required).