

WEEK-2 ASSIGNMENTS

1.HTTP Status Codes

1xx – Informational

- 100 Continue - Indicates that the client should continue with the request.
- 101 Switching Protocols - Indicates that the server is switching to another protocol.
- 103 Early Hints - This is used with the Link header, where preloading of resources begins and the server prepares responses.

2xx – Success

- 200 OK - Indicates a successful transaction.
- 202 Accepted - The request has been accepted for processing, but the processing has not yet been completed.
- 203 Non-Authoritative Information - The information returned is not from the original source of the request.
- 204 No Content - The request was successful, but no content is returned in the response body.
- 205 Reset Content - The browser should clear the form used for the transaction to allow new input.

3xx – Redirection

- 300 Multiple Choices - The requested URL refers to more than one resource.
- 301 Moved Permanently - The requested resource has been permanently moved to a new URL. The new location is specified in the Location header, and all future requests should use the new URL.
- 302 Found - The requested resource has been temporarily moved to another URL.
- 307 Temporary Redirect - The requested URL has moved, but only temporarily.

4xx – Client Error

- 400 Bad Request - This response code indicates that the server detected a syntax error in the client's request.
- 401 Unauthorized - The request failed because proper authentication credentials, such as a username and password, were not provided.
- 403 Forbidden - The request was denied for a reason that the server does not want to (or cannot) disclose to the client.
- 404 Not Found - The document at the specified URL does not exist.
- 429 Too Many Requests - This error occurs when too many requests are made within a certain period of time.

2. Types of variables

Local Variable

- Kept within the collection, within a specific request.
- They are temporary and accessible only in the context of that request.

Data Variable

- Data variables, also known as data files, are used for data-driven testing in Postman.

Environment Variable

- These can be accessed by all requests within that environment.
- They allow easy configuration for different environments such as development and staging.

Collection Variable

- Accessed by all requests within that collection.
- They provide a convenient way to share data between requests belonging to the same collection.

Global Variables

- Accessible by all requests and scripts across all collections and environments.
- They provide a centralized storage mechanism to store commonly used data such as API keys and authentication tokens.

3. Prompting techniques

CLEAR Technique

- C – Concise - Keep it short
- L – Logical - Make it well-structured
- E – Explicit - Be clear and specific
- A – Actionable - Ask for a clear action
- R – Relevant - Stay on topic

RACE Technique

- R – Role - Assign a role
- A – Action - What to do
- C – Context - Background info
- E – Expectation - Output format

CO-STAR Technique

- C – Context → Background
- Objective → Goal
- S – Style → Writing style
- T – Tone → Formal/informal
- A – Audience → Target users
- R – Response Format → Output type

4. Short hand terms for prompting

- **PITFALLS** – Identifies possible flaws and errors
- **ACT AS** – Makes ChatGPT speak in a specific role
- **DEV mode** – Simulates a raw, technical developer
- **PM Mode** – Gives a project management perspective
- **SWOT** – Provides: Strengths, Weaknesses, Opportunities, Threats
- **Deep Dive** – Detailed explanation
- **DRY RUN** – Step-by-step execution
- **EOD** – End of Day
- **TBD** – To Be Decided