Amazon S3 – Security

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – Object Encryption



- You can encrypt objects in S3 buckets using one of 4 methods

- Server-Side Encryption (SSE)
  - Server-Side Encryption with Amazon S3-Managed Keys (SSE-S3) – Enabled by Default
    - Encrypts S3 objects using keys handled, managed, and owned by AWS
  - Server-Side Encryption with KMS Keys stored in AWS KMS (SSE-KMS)
    - Leverage AWS Key Management Service (AWS KMS) to manage encryption keys
  - Server-Side Encryption with Customer-Provided Keys (SSE-C)
    - When you want to manage your own encryption keys
- Client-Side Encryption


- It's important to understand which ones are for which situation for the exam

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 Encryption – SSE-S3

- Encryption using keys handled, managed, and owned by AWS
- Object is encrypted server-side
- Encryption type is AES-256
- Must set header "x-amz-server-side-encryption": "AES256"
- Enabled by default for new buckets & new objects




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 Encryption – SSE-KMS

- Encryption using keys handled and managed by AWS KMS (Key Management Service)
- KMS advantages: user control + audit key usage using CloudTrail
- Object is encrypted server side
- Must set header **"x-amz-server-side-encryption": "aws:kms"**




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

SSE-KMS Limitation

- If you use SSE-KMS, you may be impacted by the KMS limits
- When you upload, it calls the **GenerateDataKey** KMS API
- When you download, it calls the **Decrypt** KMS API
- Count towards the KMS quota per second (5500, 10000, 30000 req/s based on region)
- You can request a quota increase using the Service Quotas Console




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 Encryption – SSE-C

- Server-Side Encryption using keys fully managed by the customer outside of AWS
- Amazon S3 does **NOT** store the encryption key you provide
- **HTTPS must be used**
- Encryption key must provided in HTTP headers, for every HTTP request made




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 Encryption – Client-Side Encryption

- Use client libraries such as **Amazon S3 Client-Side Encryption Library**
- Clients must encrypt data themselves before sending to Amazon S3
- Clients must decrypt data themselves when retrieving from Amazon S3
- Customer fully manages the keys and encryption cycle



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – Encryption in transit (SSL/TLS)

- Encryption in flight is also called SSL/TLS

- Amazon S3 exposes two endpoints:
  - HTTP Endpoint – non encrypted
  - HTTPS Endpoint – encryption in flight




- HTTPS is recommended
- HTTPS is mandatory for SSE-C
- Most clients would use the HTTPS endpoint by default

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – Force Encryption in Transit aws:SecureTransport




```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Principal": "*",
            "Action": "s3:GetObject",
            "Resource": "arn:aws:s3:::my-bucket/*",
            "Condition": {
                "Bool": {
                    "aws:SecureTransport": "false"
                }
            }
        }
    ]
}
```

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Amazon S3 – Default Encryption vs. Bucket Policies

- SSE-S3 encryption is automatically applied to new objects stored in S3 bucket
- Optionally, you can "force encryption" using a bucket policy and refuse any API call to PUT an S3 object without encryption headers (SSE-KMS or SSE-C)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Action": "s3:PutObject",
            "Principal": "*",
            "Resource": "arn:aws:s3:::my-bucket/*",
            "Condition": {
                "StringNotEquals": {
                    "s3:x-amz-server-side-encryption": "aws:kms"
                }
            }
        }
    ]
}
```

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Action": "s3:PutObject",
            "Principal": "*",
            "Resource": "arn:aws:s3:::my-bucket/*",
            "Condition": {
                "Null": {
                    "s3:x-amz-server-side-encryption-customer-algorithm": "true"
                }
            }
        }
    ]
}
```

- Note: Bucket Policies are evaluated before "Default Encryption"

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com


What is CORS?

- Cross-Origin Resource Sharing (CORS)
- Origin = scheme (protocol) + host (domain) + port
  - example: https://www.example.com (implied port is 443 for HTTPS, 80 for HTTP)
- **Web Browser** based mechanism to allow requests to other origins while visiting the main origin
- Same origin: http://example.com/app1 & http://example.com/app2
- Different origins: http://www.example.com & http://other.example.com
- The requests won't be fulfilled unless the other origin allows for the requests, using **CORS Headers** (example: **Access-Control-Allow-Origin**)

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

What is CORS?




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – CORS

- If a client makes a cross-origin request on our S3 bucket, we need to enable the correct CORS headers
- It's a popular exam question
- You can allow for a specific origin or for * (all origins)



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – MFA Delete

- **MFA (Multi-Factor Authentication)** – force users to generate a code on a device (usually a mobile phone or hardware) before doing important operations on S3
- MFA will be required to:
  - Permanently delete an object version
  - Suspend Versioning on the bucket
- MFA won't be required to:
  - Enable Versioning
  - List deleted versions
- To use MFA Delete, **Versioning must be enabled** on the bucket
- **Only the bucket owner (root account) can enable/disable MFA Delete**



Google Authenticator



MFA Hardware Device


© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

S3 Access Logs

- For audit purpose, you may want to log all access to S3 buckets
- Any request made to S3, from any account, authorized or denied, will be logged into another S3 bucket
- That data can be analyzed using data analysis tools…
- The target logging bucket must be in the same AWS region

- The log format is at: https://docs.aws.amazon.com/AmazonS3/latest/dev/LogFormat.html




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

S3 Access Logs: Warning

- Do not set your logging bucket to be the monitored bucket
- It will create a logging loop, and **your bucket will grow exponentially**



Do not try this at home ☺


© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Amazon S3 – Pre-Signed URLs

- Generate pre-signed URLs using the **S3 Console, AWS CLI or SDK**
- **URL Expiration**
  - **S3 Console** – 1 min up to 720 mins (12 hours)
  - **AWS CLI** – configure expiration with *--expires-in* parameter in seconds (default 3600 secs, max. 604800 secs ~ 168 hours)
- Users given a pre-signed URL inherit the permissions of the user that generated the URL for GET / PUT

- Examples:
  - Allow only logged-in users to download a premium video from your S3 bucket
  - Allow an ever-changing list of users to download files by generating URLs dynamically
  - Allow temporarily a user to upload a file to a precise location in your S3 bucket




NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

S3 Glacier Vault Lock

- Adopt a WORM (Write Once Read Many) model
- Create a Vault Lock Policy
- Lock the policy for future edits (can no longer be changed or deleted)
- Helpful for compliance and data retention



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com


S3 Object Lock (versioning must be enabled)

- Adopt a WORM (Write Once Read Many) model
- Block an object version deletion for a specified amount of time
- Retention mode - Compliance:
  - Object versions can't be overwritten or deleted by any user, including the root user
  - Objects retention modes can't be changed, and retention periods can't be shortened
- Retention mode - Governance:
  - Most users can't overwrite or delete an object version or alter its lock settings
  - Some users have special permissions to change the retention or delete the object
- Retention Period: protect the object for a fixed period, it can be extended
- Legal Hold:
  - protect the object indefinitely, independent from retention period
  - can be freely placed and removed using the *s3:PutObjectLegalHold* IAM permission

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

S3 – Access Points




- Access Points simplify security management for S3 Buckets
- Each Access Point has:
  - its own DNS name (Internet Origin or VPC Origin)
  - an access point policy (similar to bucket policy) – manage security at scale

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

S3 – Access Points – VPC Origin

- We can define the access point to be accessible only from within the VPC
- You must create a VPC Endpoint to access the Access Point (Gateway or Interface Endpoint)
- The VPC Endpoint Policy must allow access to the target bucket and Access Point





```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Principal": "*",
            "Action": [
                "s3:GetObject"
            ],
            "Effect": "Allow",
            "Resource": [
                "arn:aws:s3:::awsexamplebucket1/*",
                "arn:aws:s3:us-west-2:123456789012:accesspoint/example-vpc-ap/object/*"
            ]
        }
    ]
}
```

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

S3 Object Lambda

- Use AWS Lambda Functions to change the object before it is retrieved by the caller application
- Only one S3 bucket is needed, on top of which we create **S3 Access Point** and **S3 Object Lambda Access Points.**
- Use Cases:
  - Redacting personally identifiable information for analytics or non-production environments.
  - Converting across data formats, such as converting XML to JSON.
  - Resizing and watermarking images on the fly using caller-specific details, such as the user who requested the object.



NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek