

Python 3.14.0 (tags/v3.14.0:ebf955d, Oct 7 2025, 10:15:03) [MSC v.1944 64 bit (AMD64)] on win32

Enter "help" below or click "Help" above for more information.

Extra - non - keyword argument -> isolation

```
def testFunction(*args):  
    print(args, type(args))
```

```
testFunction(10, 20, 30, 40)  
(10, 20, 30, 40) <class 'tuple'>
```

t

```
testFunction()  
() <class 'tuple'>
```

Step 1: Lets add some formal parameters before extra-nonkeyword argument

d

```
def testFunction(a, b, c, *args):  
    print(a, b, c)  
    print(args)
```

```
testFunction(10, 20, 30)
```

10 20 30

()

```
testFunction(10, 20, 30, 40)
```

10 20 30

(40,)

```
testFunction(10, 20, 30, 40, [100, 200, 300])
```

10 20 30

(40, [100, 200, 300])

```
testFunction(10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160)
```

10 20 30

(40, 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160)

```
def testFunctionOne(a, b, c):
```

```
    print(a, b, c)
```

```
testFunctionOne(10, 20, 30)
```

10 20 30

```
testFunctionOne(a=10, b=20, c=30)
```

10 20 30

```
testFunction(a=10, b=20, c=30, 40, 50, 60)
```

SyntaxError: positional argument follows keyword argument

Step 2: Lets add some formal parameters to the right of extra-nonkeyword argument

```
def testFunction(a, b, c, *args, p, q):  
    print(a, b, c)  
    print(args)  
    print(p, q)
```

```

testFunction(10, 20, 30, 40, 50, 60, 70, 80, 90) # expectation: a=10, b=20, c=30,
args=(40, 50, 60, 70), p=80, q=90
Traceback (most recent call last):
  File "<pyshell#28>", line 1, in <module>
    testFunction(10, 20, 30, 40, 50, 60, 70, 80, 90) # expectation: a=10, b=20,
c=30, args=(40, 50, 60, 70), p=80, q=90
TypeError: testFunction() missing 2 required keyword-only arguments: 'p' and 'q'
testFunction(10, 20, 30, 40, 50, 60, 70, p=80, q=90)
10 20 30
(40, 50, 60, 70)
80 90
# Default arguments
def testFunction(a=10, b=20, c=30):
    print(a, b, c)

```

```

testFunction()
10 20 30
testFunction(a=100)
100 20 30
testFunction(100)
100 20 30
testFunction(10, 20, 300)
10 20 300
testFunction(c=300)
10 20 300
print('Hello,world')
Hello,world
print(10)
10
print(10, 20)
10 20
print(10, 20, 30, 40, sep=':')
10:20:30:40
# Integrating default parameters with positional, extra-non-keyword and keyword
only arguments
def testFunction(a, b, c, *args, x=1.1, y=2.2, p, q):
    print(a, b, c) # Positional arguments
    print(args)    # Extra-nonkeyword argument
    print(x, y)    # Default arguments
    print(p, q)    # Keyword only arguments

testFunction(10, 20, 30, 40, 50, 60, 70, y=20.25, p=False, q=True)
10 20 30
(40, 50, 60, 70)
1.1 20.25
False True
# Extra keyword argument isolation
def testFunction(**kwargs):

```

```
print(kwargs)
```

```
testFunction()
{}
testFunction(a=10, b=20, c=30)
{'a': 10, 'b': 20, 'c': 30}
# Integrating extra-keyword argument with existing parameter types
def MasterFunction(a, b, c, *args, x=1.1, y=2.2, p, q, **kwargs):
    print('Positional arguments')
    ...    print(f'a:{a}, b:{b}, c:{c}')
    ...    print('Extra non-keyword arguments')
    ...    for i in range(len(args)):
    ...        print(f'args[{i}]:{args[i]}')
    ...    print('Default arguments')
    ...    print(f'x:{x}, y:{y}')
    ...    print('Keyword only arguments')
    ...    print(f'p:{p}, q:{q}')
    ...    print('Extra-keyword arguments')
    ...    for (key, val) in kwargs.items():
    ...        print(key, val)
    ...
    ...
>>> MasterFunction(10, 20, 30, 40, 50, 60, 70, y=20.25, p=False, q=True, u=False,
w=True, v=False)
Positional arguments
a:10, b:20, c:30
Extra non-keyword arguments
args[0]:40
args[1]:50
args[2]:60
args[3]:70
Default arguments
x:1.1, y:20.25
Keyword only arguments
p:False, q:True
Extra-keyword arguments
u False
w True
v False
```