Track C technical report - 14 October 2026

Track C: contrastive speech analysis

Technical report • 14 October 2026 • Controlled digital edits and a private natural-speech pilot

Problem and output

The system compares a reference reading and a same-transcript take, estimates word boundaries, extracts local acoustic measurements, marks candidate deviations on the take timeline, and displays a reference-relative operational score. It targets pauses, recorded-level drops, locally faster words and locally slower words. Candidate events include start/end times, measured cause and an edit-strength-like severity. They are not human-rated rhetorical quality judgments.

Data and provenance

Twenty-one archival speech excerpts from Reagan, Kennedy and Obama are candidate references. Each has 12 deliberately modified variants: four operators at three strengths. The 273 released WAVs include 252 digital variants. Audio is 16-kHz mono PCM16. Exact half-open edit intervals and source hashes are stored in the manifest and labels. All references are genuine archival speech crops; the altered versions are synthetic edits of those crops, never authentic mistakes by the speakers. RIGHTS.md lists per-source reuse evidence and limits. No Windows SAPI audio is included.

Train, validation and test are separated by speaker/source and whole passage family: Reagan 130 clips, Kennedy 39, Obama 104. Different eras, microphones and venues are confounded with split. The 22 original recordings from four local participants are private development material with no recorded redistribution consent and are excluded from the public package. Their instructions are not verified acoustic ground truth.

Alignment and acoustic features

Offline archival word alignment uses imported MFA TextGrids for all 273 clips. The 170 review flags mean disagreement with an older automatic aligner over 100 ms; they are not verified MFA errors. No human boundary accuracy is known. A live take uses PocketSphinx forced alignment when installed, otherwise a bounded MFCC dynamic-time-warping transfer of the reference word times. The fallback abstains for duration outliers, collapsed words, nonmonotonic mappings or high normalized path cost. It cannot verify that the words were actually spoken; transcript entry and an explicit listener confirmation gate that feedback.

Frames use a 40-ms window and 20-ms hop. Measurements include log-FFT energy, 13 MFCCs, estimated F0 and relative pitch in semitones, RMS level, spectral centroid and zero-crossing rate. Per-word durations and energy are compared at aligned word positions; interword gap excess measures pauses. Uncertain alignment and microphone gain limit interpretation.

Detector and scoring

Predicted candidate intervals

Inference takes only the two audio signals, their estimated word boundaries and an explicit

same-setup flag. It never reads a clip ID, flaw label, intended take or programmed edit interval. For word i, the duration ratio is take duration/reference duration; the level difference is 10 log10(mean take frame power/mean reference frame power). For adjacent words, pause excess is take interword gap minus nonnegative reference gap. Threshold crossings generate word or gap intervals, and same-type neighbors within 120 ms merge.

Event | Train-selected threshold | Cause shown in dashboard

Pause | Gap excess >=0.25 s | Seconds longer than reference gap

Quiet local level | Clip-relative difference <-6 dB | Within-clip word energy change

Rush | Tempo-normalized duration ratio <0.82 | Locally shorter word duration

Drag | Tempo-normalized duration ratio >1.22 | Locally longer word duration

The duration ratio is divided by the pair’s median word-duration ratio, and word level change is centered by each clip’s median energy. This reduces uniform speaker-rate and gain differences while retaining localized deviations. Uniform whole-clip changes are shown separately and cannot be localized by these rules. The four thresholds were selected by a 144-point grid search on the Reagan training speaker, balancing overall event F1 and macro recall across flaw/severity groups at interval intersection-over-union (IoU) >=0.5. Kennedy and Obama were not used for threshold selection.

Transparent rubric

Three 0-10 operational dimensions cover pacing, pauses and local level. Merged events are scored by unique affected words with burden 1, 2 or 3 for minor, moderate or severe; this avoids multiplying a single displayed span by its number of word events. Pause score falls by 3 points per cumulative second of excess pause. The combined score is the mean of the three available dimensions. It is not a human preference score, speaking skill rating or MOS. Transcript or alignment failure withholds word-level measurements. Appropriate rhetorical pauses may be flagged.

Dashboard

The interactive evaluation.html page overlays reference and take curves by transcript word position, highlights predicted regions in orange and archive edit intervals separately in blue, and lists each explanation. It accepts a take and transcript for a matching archive passage. The public pair.html page accepts two arbitrary recordings for coarse activity, pause and level comparison; it does not claim word-level localization. Both pages use the local server. The human.html page and private pilot audio are excluded from the public package.

Evaluation, limits and reproduction

Held-out digital-edit results

One ground-truth edit exists per non-reference clip. A predicted event counts as localized only when its type matches and its interval IoU with the exact edit is at least 0.5. Event precision uses all predicted intervals; recall uses all labeled edits. This makes extra detections visible.

Split | Labeled edits | Type present | IoU>=0.5 recall | Event precision | Event F1

Train / Reagan | 120 | 75.0% | 52.5% | 37.7% | 43.9%

Validation / Kennedy | 36 | 80.6% | 47.2% | 22.4% | 30.4%

Test / Obama | 96 | 76.0% | 55.2% | 33.3% | 41.6%

On the test speaker, pause localization reached 23/24, quiet 7/24, rush 12/24 and drag 11/24. There were 106 extra or insufficient-overlap predicted intervals. Mean best same-type IoU was 0.516. Mean onset and offset errors among localized events were 0.226 s and 0.201 s. These numbers are controlled digital-edit localization only. The older whole-clip model's 97.1% digital edit-type accuracy is a different task and does not measure speaking-quality accuracy.

Limits and remaining human validation

The detector has low precision, especially on Kennedy, and word-alignment errors can create misleading regions. Quiet events are only recorded-energy differences; automatic gain control and microphone changes can reverse their meaning. The same-reference archival variants are far easier than unrelated natural performances. There is no verified natural-speech accuracy, human severity calibration, independent transcript audit or measured word-boundary error. Do not present this as a reliable judge of people or public speakers.

Reproduction

Install requirements.txt, run python src/build.py and python src/validate.py; use the supplied MFA alignments; run python -m unittest discover -s src -p 'test_*.py', python src/tune_localizer.py, python src/evaluate_localizer.py, python src/make_viewer_data.py, and python src/serve.py. Open http://127.0.0.1:8765/evaluation.html or /pair.html. Arbitrary pair comparison reports coarse speech activity, pauses and level; word-level localization is limited to aligned same-transcript pairs. Dataset hashes, edit labels, split manifests, event predictions, thresholds, test metrics and code are included. Unit tests and structural validation are separate from perceptual validation.

References: official Track C problem statement and submission guide supplied for the hackathon; MFA documentation; DTW implementation and source/rights links recorded in RIGHTS.md. The user handles the required submission video separately.