DOCUMENTATION · REFERENCE

Query metadata

The latest version is at anantharajuc.github.io/QueryAPIGate-website/Guide.dc.html?d=QUERY_METADATA_MANAGEMENT. This copy was made on 4 November 2026.

Each saved query lives in `queryapigate.db`, with one entry per version (`"1"`, `"2"`, …) - the same shape it always was as a `saved_sql/*.json` file, and the shape a bundle carries. Adding a version never changes an earlier one; the published version is what callers run unless they ask for another (see Drafts and publishing). The Management API presents the same fields with a few renamed (`sql` for `sql_query`, `parameters` for `query_parameters`) - see Save a query.

FIELD	TYPE	PURPOSE	EXAMPLE
`uuid`	string	Unique id of this version	`"c031f3ba-8b49-4e74-adf3-b085a12581f8"`
`sql_query`	string	The SQL, with optional `:name` parameters	`"SELECT * FROM film WHERE film_id = :id"`
`author`	string	Who saved it	`"anantha"`
`description`	string	What it is for	`"Look up a film"`
`tags`	string or array	Labels	`["example"]`
`query_parameters`	object	Parameter definitions: a type, or an object of rules (`type`, `required`, `default`, `enum`, `min`, `max`, `min_length`, `max_length`, `pattern`, `description`) - see Parameter rules	`{"id": {"type": "int", "min": 1}}`
`connection_name`	string	Optional default connection for `/q/<name>`	`"examples"`
`cache_ttl`	integer	Optional response-cache lifetime in seconds - see Response caching	`60`
`created_at`, `last_modified_at`	string	Timestamps	`"2024-03-23 23:50:57"`
`status`	string	Query state	`"active"`
`version`	integer	Version number	`2`
`execution_history`	array	The last 50 runs of this version	see below

An `execution_history` entry looks like:

```json
{"executed_at": "2024-03-23 23:51:02", "connection_name": "examples", "status": "success", "rows": 1, "duration_ms": 4}
```

Failed runs are recorded with `"status": "error"` and an `"error"` message instead of `rows` and `duration_ms`.