

MOVIE-TICKET BOOKING SYSTEM

★ STEP 1 — COMPLETE SQL PART (FINAL VERSION)

✓ 1. CREATE DATABASE

```
CREATE DATABASE movie_booking;
```

```
USE movie_booking;
```

✓ 2. CREATE ALL TABLES (ERROR-FREE VERSION)

TABLE 1 — User

```
CREATE TABLE Users (  
    user_id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(100),  
    email VARCHAR(100) UNIQUE,  
    password VARCHAR(50),  
    phone VARCHAR(15)  
);
```

TABLE 2 — Movie

```
CREATE TABLE Movie (  
    movie_id INT AUTO_INCREMENT PRIMARY KEY,  
    title VARCHAR(100),  
    genre VARCHAR(50),  
    rating DECIMAL(3,1),  
    duration INT  
);
```

MOVIE-TICKET BOOKING SYSTEM

TABLE 3 — Theater

```
CREATE TABLE Theater (  
    theater_id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(100),  
    address VARCHAR(200),  
    total_seats INT  
);
```

TABLE 4 — ShowTable (renamed to avoid SQL keyword conflict!)

```
CREATE TABLE ShowTable (  
    show_id INT AUTO_INCREMENT PRIMARY KEY,  
    movie_id INT,  
    theater_id INT,  
    show_date DATE,  
    show_time TIME,  
    FOREIGN KEY (movie_id) REFERENCES Movie(movie_id),  
    FOREIGN KEY (theater_id) REFERENCES Theater(theater_id)  
);
```

TABLE 5 — Seat

```
CREATE TABLE Seat (  
    seat_id INT AUTO_INCREMENT PRIMARY KEY,  
    show_id INT,  
    seat_number VARCHAR(10),  
    status ENUM('available','booked') DEFAULT 'available',  
    FOREIGN KEY (show_id) REFERENCES ShowTable(show_id)
```

MOVIE-TICKET BOOKING SYSTEM

);

TABLE 6 — Booking

```
CREATE TABLE Booking (  
    booking_id INT AUTO_INCREMENT PRIMARY KEY,  
    user_id INT,  
    show_id INT,  
    seat_id INT,  
    booking_time DATETIME DEFAULT NOW(),  
    payment_status ENUM('pending','paid') DEFAULT 'pending',  
    FOREIGN KEY (user_id) REFERENCES Users(user_id),  
    FOREIGN KEY (show_id) REFERENCES ShowTable(show_id),  
    FOREIGN KEY (seat_id) REFERENCES Seat(seat_id)  
);
```

TABLE 7 — Payment

```
CREATE TABLE Payment (  
    payment_id INT AUTO_INCREMENT PRIMARY KEY,  
    booking_id INT,  
    amount DECIMAL(10,2),  
    payment_mode VARCHAR(20),  
    payment_time DATETIME DEFAULT NOW(),  
    FOREIGN KEY (booking_id) REFERENCES Booking(booking_id)  
);
```

TABLE 8 — AuditLog (extra marks 🌟)

MOVIE-TICKET BOOKING SYSTEM

```
CREATE TABLE AuditLog (  
    log_id INT AUTO_INCREMENT PRIMARY KEY,  
    action VARCHAR(200),  
    action_time DATETIME DEFAULT NOW()  
);
```

✅ 3. TRIGGERS (ALL 100% WORKING)

★ These 3 triggers give you FULL MARKS — must include in project.

Trigger 1 — Prevent double booking (important)

DELIMITER \$\$

```
CREATE TRIGGER trg_prevent_double_booking  
BEFORE INSERT ON Booking  
FOR EACH ROW  
BEGIN  
    DECLARE s VARCHAR(20);  
  
    SELECT status INTO s  
    FROM Seat  
    WHERE seat_id = NEW.seat_id;  
  
    IF s = 'booked' THEN  
        SIGNAL SQLSTATE '45000'  
        SET MESSAGE_TEXT = 'Seat already booked!';  
    END IF;
```

MOVIE-TICKET BOOKING SYSTEM

END \$\$

DELIMITER ;

Trigger 2 — Auto update seat to booked

DELIMITER \$\$

```
CREATE TRIGGER trg_mark_seat_booked
AFTER INSERT ON Booking
FOR EACH ROW
BEGIN
    UPDATE Seat
    SET status = 'booked'
    WHERE seat_id = NEW.seat_id;
END $$
```

DELIMITER ;

Trigger 3 — Auto update booking status when payment done

DELIMITER \$\$

```
CREATE TRIGGER trg_payment_status
AFTER INSERT ON Payment
FOR EACH ROW
BEGIN
    UPDATE Booking
```

MOVIE-TICKET BOOKING SYSTEM

```
SET payment_status = 'paid'
WHERE booking_id = NEW.booking_id;
END $$
```

DELIMITER ;

Trigger 4 — Audit Log (extra marks)

DELIMITER \$\$

```
CREATE TRIGGER trg_log_booking
AFTER INSERT ON Booking
FOR EACH ROW
BEGIN
    INSERT INTO AuditLog(action)
    VALUES (CONCAT('Booking created with ID = ', NEW.booking_id));
END $$
```

DELIMITER ;

INSERT STATEMENTS:

1 Users Table

```
INSERT INTO Users (user_id, name, email, password,
phone) VALUES
(1, 'Anu', 'anu@gmail.com', 'anu123', '9876543210'),
(2, 'Kumar', 'kumar@gmail.com', 'kumar123',
'9876543211'),
```

MOVIE-TICKET BOOKING SYSTEM

```
(3, 'Ravi', 'ravi@gmail.com', 'ravi123',  
'9876543212'),  
(4, 'Sita', 'sita@gmail.com', 'sita123',  
'9876543213');
```

2 Movie Table

```
INSERT INTO Movie (movie_id, title, genre, rating,  
duration) VALUES  
(1, 'KGF 2', 'Action', 8.5, 168),  
(2, 'Leo', 'Thriller', 7.8, 165),  
(3, 'RRR', 'Action', 8.7, 182),  
(4, 'Jailer', 'Action', 7.4, 168),  
(5, 'Devara', 'Telugu Action', 8.2, 170);
```

3 Theater Table

```
INSERT INTO Theater (theater_id, name, address,  
total_seats) VALUES  
(1, 'PVR Cinemas', 'Bangalore', 100),  
(2, 'INOX', 'Hyderabad', 120),  
(3, 'Cinepolis', 'Chennai', 90);
```

4 ShowTable

```
INSERT INTO ShowTable (show_id, movie_id, theater_id,  
show_date, show_time) VALUES  
(1, 1, 1, '2025-11-15', '18:00:00'),  
(2, 1, 1, '2025-11-15', '21:00:00'),  
(3, 2, 2, '2025-11-16', '17:00:00'),  
(4, 3, 2, '2025-11-16', '19:00:00'),  
(5, 5, 2, '2025-11-17', '20:00:00'),  
(6, 4, 3, '2025-11-17', '16:00:00');
```

5 Seat Table

```
INSERT INTO Seat (seat_id, show_id, seat_number,  
status) VALUES  
(1, 1, 'A1', 'booked'),  
(2, 1, 'A2', 'booked'),
```

MOVIE-TICKET BOOKING SYSTEM

```
(3, 1, 'A3', 'booked'),
(4, 1, 'A4', 'booked'),
(5, 1, 'A5', 'available'),

(6, 2, 'B1', 'booked'),
(7, 2, 'B2', 'booked'),
(8, 2, 'B3', 'booked'),
(9, 2, 'B4', 'booked'),
(10, 2, 'B5', 'available'),

(11, 3, 'C1', 'booked'),
(12, 3, 'C2', 'booked'),
(13, 3, 'C3', 'booked'),
(14, 3, 'C4', 'booked'),
(15, 3, 'C5', 'available'),

(16, 4, 'D1', 'booked'),
(17, 4, 'D2', 'booked'),
(18, 4, 'D3', 'booked'),
(19, 4, 'D4', 'available'),
(20, 4, 'D5', 'booked'),

(21, 5, 'E1', 'booked'),
(22, 5, 'E2', 'booked'),
(23, 5, 'E3', 'available'),
(24, 5, 'E4', 'available'),
(25, 5, 'E5', 'booked'),

(26, 6, 'F1', 'booked'),
(27, 6, 'F2', 'booked'),
(28, 6, 'F3', 'available'),
(29, 6, 'F4', 'available'),
(30, 6, 'F5', 'available');
```

6 Booking Table

```
INSERT INTO Booking (booking_id, user_id, show_id,
seat_id, booking_time, payment_status) VALUES
(1, 1, 1, 3, '2025-11-15 21:29:52', 'paid'),
(2, 1, 1, 4, '2025-11-15 21:29:52', 'paid'),
(3, 2, 2, 6, '2025-11-15 21:29:52', 'paid'),
(4, 3, 2, 8, '2025-11-15 21:29:52', 'paid'),
(5, 4, 3, 12, '2025-11-15 21:29:52', 'paid'),
```

MOVIE-TICKET BOOKING SYSTEM

```
(6, 1, 3, 13, '2025-11-15 21:29:52', 'paid'),
(7, 2, 4, 16, '2025-11-15 21:29:52', 'paid'),
(8, 3, 4, 17, '2025-11-15 21:29:52', 'pending'),
(9, 4, 5, 22, '2025-11-15 21:29:52', 'pending'),
(10, 1, 6, 26, '2025-11-15 21:29:52', 'pending');
```

7 Payment Table

```
INSERT INTO Payment (payment_id, booking_id, amount,
payment_mode, payment_time) VALUES
(1, 1, 250.00, 'UPI', '2025-11-15 21:30:32'),
(2, 2, 250.00, 'Cash', '2025-11-15 21:30:32'),
(3, 3, 270.00, 'Card', '2025-11-15 21:30:32'),
(4, 4, 300.00, 'UPI', '2025-11-15 21:30:32'),
(5, 5, 350.00, 'NetBanking', '2025-11-15 21:30:32'),
(6, 6, 280.00, 'UPI', '2025-11-15 21:30:32'),
(7, 7, 280.00, 'Card', '2025-11-15 21:30:32');
```

IMPORTANT SQL QUERIES (must include in documentation)

1) List all movies

```
SELECT * FROM Movie;
```

2) List available seats for a show

```
SELECT seat_number FROM Seat
WHERE show_id = 1 AND status='available';
```

3) Show booking history of a user

```
SELECT * FROM Booking
WHERE user_id = 1;
```

4) Show total revenue per movie

```
SELECT m.title, SUM(p.amount) AS revenue
FROM Payment p
JOIN Booking b ON p.booking_id = b.booking_id
JOIN Movie m ON b.show_id = m.movie_id
```

MOVIE-TICKET BOOKING SYSTEM

```
GROUP BY m.title;
```

5) Count total bookings

```
SELECT COUNT(*) FROM Booking;
```

6) Show all shows with movie name

```
SELECT s.show_id, m.title, s.show_time  
FROM ShowTable s  
JOIN Movie m ON s.movie_id = m.movie_id;
```

7) Seats booked in a show

```
SELECT seat_number FROM Seat  
WHERE show_id = 1 AND status='booked';
```

8) Seats available in a show

```
SELECT seat_number FROM Seat  
WHERE show_id = 1 AND status='available';
```

9) Number of shows per theater

```
SELECT t.name, COUNT(*) AS total_shows  
FROM ShowTable s  
JOIN Theater t ON s.theater_id = t.theater_id  
GROUP BY t.name;
```

10) Movies with rating above 8

```
SELECT * FROM Movie WHERE rating > 8;
```

🔥 EVEN RARE / ADVANCED QUERIES WILL RETURN DATA

✓ Shows with booked seats

```
SELECT show_id, COUNT(*)  
FROM Seat  
WHERE status='booked'  
GROUP BY show_id;
```

✓ Movie with maximum bookings

MOVIE-TICKET BOOKING SYSTEM

```
SELECT m.title, COUNT(*) AS total_bookings
FROM Booking b
JOIN ShowTable s ON b.show_id = s.show_id
JOIN Movie m ON s.movie_id = m.movie_id
GROUP BY m.title
ORDER BY total_bookings DESC
LIMIT 1;
```

✓ Users who booked more than one ticket

```
SELECT user_id, COUNT(*) FROM Booking GROUP BY
user_id HAVING COUNT(*) > 1;
```

OUTPUTS:

```
mysql> desc users;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| user_id | int | NO | PRI | NULL | auto_increment |
| name | varchar(100) | YES | | NULL | |
| email | varchar(100) | YES | UNI | NULL | |
| password | varchar(50) | YES | | NULL | |
| phone | varchar(15) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> desc movie;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| movie_id | int | NO | PRI | NULL | auto_increment |
| title | varchar(100) | YES | | NULL | |
| genre | varchar(50) | YES | | NULL | |
| rating | decimal(3,1) | YES | | NULL | |
| duration | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> desc Theater;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| theater_id | int | NO | PRI | NULL | auto_increment |
| name | varchar(100) | YES | | NULL | |
| address | varchar(200) | YES | | NULL | |
| total_seats | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

```
mysql> desc ShowTable;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| show_id | int | NO | PRI | NULL | auto_increment |
| movie_id | int | YES | MUL | NULL | |
| theater_id | int | YES | MUL | NULL | |
| show_date | date | YES | | NULL | |
| show_time | time | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> desc Seat;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| seat_id | int | NO | PRI | NULL | auto_increment |
| show_id | int | YES | MUL | NULL | |
| seat_number | varchar(10) | YES | | NULL | |
| status | enum('available','booked') | YES | | available | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> desc Booking;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| booking_id | int | NO | PRI | NULL | auto_increment |
| user_id | int | YES | MUL | NULL | |
| show_id | int | YES | MUL | NULL | |
| seat_id | int | YES | MUL | NULL | |
| booking_time | datetime | YES | | CURRENT_TIMESTAMP | DEFAULT_GENERATED |
| payment_status | enum('pending','paid') | YES | | pending | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)
```

```
mysql> desc Payment;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| payment_id | int | NO | PRI | NULL | auto_increment |
| booking_id | int | YES | MUL | NULL | |
| amount | decimal(10,2) | YES | | NULL | |
| payment_mode | varchar(20) | YES | | NULL | |
| payment_time | datetime | YES | | CURRENT_TIMESTAMP | DEFAULT_GENERATED |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> desc AuditLog;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| log_id | int | NO | PRI | NULL | auto_increment |
| action | varchar(200) | YES | | NULL | |
| action_time | datetime | YES | | CURRENT_TIMESTAMP | DEFAULT_GENERATED |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

Insert outputs

MOVIE-TICKET BOOKING SYSTEM

```
mysql> select * from users;
+-----+-----+-----+-----+-----+
| user_id | name  | email          | password | phone  |
+-----+-----+-----+-----+-----+
| 1       | Anu   | anu@gmail.com  | anu123   | 9876543210 |
| 2       | Kumar | kumar@gmail.com | kumar123 | 9876543211 |
| 3       | Ravi  | ravi@gmail.com  | ravi123  | 9876543212 |
| 4       | Sita  | sita@gmail.com  | sita123  | 9876543213 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Movies;
ERROR 1146 (42S02): Table 'movie_booking.movies' doesn't exist
mysql> select * from users;
+-----+-----+-----+-----+-----+
| user_id | name  | email          | password | phone  |
+-----+-----+-----+-----+-----+
| 1       | Anu   | anu@gmail.com  | anu123   | 9876543210 |
| 2       | Kumar | kumar@gmail.com | kumar123 | 9876543211 |
| 3       | Ravi  | ravi@gmail.com  | ravi123  | 9876543212 |
| 4       | Sita  | sita@gmail.com  | sita123  | 9876543213 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Movie;
+-----+-----+-----+-----+-----+
| movie_id | title  | genre          | rating | duration |
+-----+-----+-----+-----+-----+
| 1       | KGF 2  | Action         | 8.5    | 168      |
| 2       | Leo    | Thriller       | 7.8    | 165      |
| 3       | RRR    | Action         | 8.7    | 182      |
| 4       | Jailer | Action         | 7.4    | 168      |
| 5       | Devara | Telugu Action  | 8.2    | 170      |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

```
mysql> select * from Theater;
```

theater_id	name	address	total_seats
1	PVR Cinemas	Bangalore	100
2	INOX	Hyderabad	120
3	Cinepolis	Chennai	90

```
3 rows in set (0.00 sec)
```

```
mysql> select * from ShowTable;
```

show_id	movie_id	theater_id	show_date	show_time
1	1	1	2025-11-15	18:00:00
2	1	1	2025-11-15	21:00:00
3	2	2	2025-11-16	17:00:00
4	3	2	2025-11-16	19:00:00
5	5	2	2025-11-17	20:00:00
6	4	3	2025-11-17	16:00:00

```
6 rows in set (0.00 sec)
```

```
mysql> select * from Seat;
```

seat_id	show_id	seat_number	status
1	1	A1	booked
2	1	A2	booked
3	1	A3	booked
4	1	A4	booked
5	1	A5	available
6	2	B1	booked
7	2	B2	booked
8	2	B3	booked
9	2	B4	booked
10	2	B5	available
11	3	C1	booked
12	3	C2	booked
13	3	C3	booked
14	3	C4	booked
15	3	C5	available
16	4	D1	booked
17	4	D2	booked
18	4	D3	booked
19	4	D4	available
20	4	D5	booked
21	5	E1	booked
22	5	E2	booked
23	5	E3	available
24	5	E4	available
25	5	E5	booked
26	6	F1	booked
27	6	F2	booked
28	6	F3	available
29	6	F4	available
30	6	F5	available

```
30 rows in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

```
mysql> select * from Booking;
```

booking_id	user_id	show_id	seat_id	booking_time	payment_status
1	1	1	3	2025-11-15 21:29:52	paid
2	1	1	4	2025-11-15 21:29:52	paid
3	2	2	6	2025-11-15 21:29:52	paid
4	3	2	8	2025-11-15 21:29:52	paid
5	4	3	12	2025-11-15 21:29:52	paid
6	1	3	13	2025-11-15 21:29:52	paid
7	2	4	16	2025-11-15 21:29:52	paid
8	3	4	17	2025-11-15 21:29:52	pending
9	4	5	22	2025-11-15 21:29:52	pending
10	1	6	26	2025-11-15 21:29:52	pending

```
10 rows in set (0.00 sec)
```



```
mysql> select * from Payment;
```

payment_id	booking_id	amount	payment_mode	payment_time
1	1	250.00	UPI	2025-11-15 21:30:32
2	2	250.00	Cash	2025-11-15 21:30:32
3	3	270.00	Card	2025-11-15 21:30:32
4	4	300.00	UPI	2025-11-15 21:30:32
5	5	350.00	NetBanking	2025-11-15 21:30:32
6	6	280.00	UPI	2025-11-15 21:30:32
7	7	280.00	Card	2025-11-15 21:30:32

```
7 rows in set (0.00 sec)
```

```
mysql> SELECT TRIGGER_NAME, EVENT_MANIPULATION, EVENT_OBJECT_TABLE, ACTION_TIMING
-> FROM information_schema.TRIGGERS
-> WHERE TRIGGER_NAME = 'trg_prevent_double_booking';
```

TRIGGER_NAME	EVENT_MANIPULATION	EVENT_OBJECT_TABLE	ACTION_TIMING
trg_prevent_double_booking	INSERT	booking	BEFORE

```
1 row in set (0.00 sec)
```



```
mysql> SELECT TRIGGER_NAME, EVENT_MANIPULATION, EVENT_OBJECT_TABLE, ACTION_TIMING
-> FROM information_schema.TRIGGERS
-> WHERE TRIGGER_NAME = 'trg_mark_seat_booked';
```

TRIGGER_NAME	EVENT_MANIPULATION	EVENT_OBJECT_TABLE	ACTION_TIMING
trg_mark_seat_booked	INSERT	booking	AFTER

```
1 row in set (0.00 sec)
```



```
mysql> SELECT TRIGGER_NAME, EVENT_MANIPULATION, EVENT_OBJECT_TABLE, ACTION_TIMING
-> FROM information_schema.TRIGGERS
-> WHERE TRIGGER_NAME = 'trg_payment_status';
```

TRIGGER_NAME	EVENT_MANIPULATION	EVENT_OBJECT_TABLE	ACTION_TIMING
trg_payment_status	INSERT	payment	AFTER

```
1 row in set (0.00 sec)
```



```
mysql> SELECT TRIGGER_NAME, EVENT_MANIPULATION, EVENT_OBJECT_TABLE, ACTION_TIMING
-> FROM information_schema.TRIGGERS
-> WHERE TRIGGER_NAME = 'trg_log_booking';
```

TRIGGER_NAME	EVENT_MANIPULATION	EVENT_OBJECT_TABLE	ACTION_TIMING
trg_log_booking	INSERT	booking	AFTER

```
1 row in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

QUERIES OUTPUT:

```
mysql> SELECT * FROM Movie;
+-----+-----+-----+-----+-----+
| movie_id | title | genre | rating | duration |
+-----+-----+-----+-----+-----+
| 1 | KGF 2 | Action | 8.5 | 168 |
| 2 | Leo | Thriller | 7.8 | 165 |
| 3 | RRR | Action | 8.7 | 182 |
| 4 | Jailer | Action | 7.4 | 168 |
| 5 | Devara | Telugu Action | 8.2 | 170 |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> SELECT seat_number FROM Seat
-> WHERE show_id = 1 AND status='available';
+-----+
| seat_number |
+-----+
| A5 |
+-----+
1 row in set (0.00 sec)

mysql> SELECT * FROM Booking
-> WHERE user_id = 1;
+-----+-----+-----+-----+-----+-----+
| booking_id | user_id | show_id | seat_id | booking_time | payment_status |
+-----+-----+-----+-----+-----+-----+
| 1 | 1 | 1 | 3 | 2025-11-15 21:29:52 | paid |
| 2 | 1 | 1 | 4 | 2025-11-15 21:29:52 | paid |
| 6 | 1 | 3 | 13 | 2025-11-15 21:29:52 | paid |
| 10 | 1 | 6 | 26 | 2025-11-15 21:29:52 | pending |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> SELECT m.title, SUM(p.amount) AS revenue
-> FROM Payment p
-> JOIN Booking b ON p.booking_id = b.booking_id
-> JOIN Movie m ON b.show_id = m.movie_id
-> GROUP BY m.title;
+-----+-----+
| title | revenue |
+-----+-----+
| KGF 2 | 500.00 |
| Leo | 570.00 |
| RRR | 630.00 |
| Jailer | 280.00 |
+-----+-----+
4 rows in set (0.00 sec)

mysql> SELECT COUNT(*) FROM Booking;
+-----+
| COUNT(*) |
+-----+
| 10 |
+-----+
1 row in set (0.00 sec)

mysql> SELECT s.show_id, m.title, s.show_time
-> FROM ShowTable s
-> JOIN Movie m ON s.movie_id = m.movie_id;
+-----+-----+-----+
| show_id | title | show_time |
+-----+-----+-----+
| 1 | KGF 2 | 18:00:00 |
| 2 | KGF 2 | 21:00:00 |
| 3 | Leo | 17:00:00 |
| 4 | RRR | 19:00:00 |
| 6 | Jailer | 16:00:00 |
| 5 | Devara | 20:00:00 |
+-----+-----+-----+
6 rows in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

```
mysql> SELECT seat_number FROM Seat
-> WHERE show_id = 1 AND status='booked';
+-----+
| seat_number |
+-----+
| A1          |
| A2          |
| A3          |
| A4          |
+-----+
4 rows in set (0.00 sec)

mysql> SELECT seat_number FROM Seat
-> WHERE show_id = 1 AND status='available';
+-----+
| seat_number |
+-----+
| A5          |
+-----+
1 row in set (0.00 sec)

mysql> SELECT t.name, COUNT(*) AS total_shows
-> FROM ShowTable s
-> JOIN Theater t ON s.theater_id = t.theater_id
-> GROUP BY t.name;
+-----+-----+
| name      | total_shows |
+-----+-----+
| PVR Cinemas | 2          |
| INOX      | 3          |
| Cinepolis | 1          |
+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM Movie WHERE rating > 8;
+-----+-----+-----+-----+-----+
| movie_id | title  | genre      | rating | duration |
+-----+-----+-----+-----+-----+
| 1        | KGF 2  | Action     | 8.5    | 168      |
| 3        | RRR    | Action     | 8.7    | 182      |
| 5        | Devara | Telugu Action | 8.2    | 170      |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> SELECT show_id, COUNT(*)
-> FROM Seat
-> WHERE status='booked'
-> GROUP BY show_id;
+-----+-----+
| show_id | COUNT(*) |
+-----+-----+
| 1       | 4        |
| 2       | 4        |
| 3       | 4        |
| 4       | 4        |
| 5       | 3        |
| 6       | 2        |
+-----+-----+
6 rows in set (0.00 sec)

mysql> SELECT m.title, COUNT(*) AS total_bookings
-> FROM Booking b
-> JOIN ShowTable s ON b.show_id = s.show_id
-> JOIN Movie m ON s.movie_id = m.movie_id
-> GROUP BY m.title
-> ORDER BY total_bookings DESC
-> LIMIT 1;
+-----+-----+
| title | total_bookings |
+-----+-----+
| KGF 2 | 4              |
+-----+-----+
1 row in set (0.00 sec)
```

MOVIE-TICKET BOOKING SYSTEM

```
mysql> SELECT user_id, COUNT(*) FROM Booking GROUP BY user_id HAVING COUNT(*) > 1;
```

user_id	COUNT(*)
1	4
2	2
3	2
4	2

```
4 rows in set (0.00 sec)
```