

POD

PROOF on Demand

PROOF on Demand

Current status and future plans

Different job managers



PoD is shipped with a number of plug-ins to cover all major RMSs, such as local cluster systems and Grid.

If there is no RMS available, then the SSH plug-in can be used.

The SSH plug-in is also used to setup PROOF clusters on Clouds.

Set your private PROOF cluster up

Start
PoD Server

pod-server start

Set your private PROOF cluster up



pod-server start

pod-submit -r [lsf | pbs | condor | ...] -q myqueue -n 100

or

pod-ssh -c pod_ssh.cfg submit

Set your private PROOF cluster up



pod-server start

pod-submit -r [lsf | pbs | condor | ...] -q myqueue -n 100

or

pod-ssh -c pod_ssh.cfg submit


pod-info -l -n

PoD vs “Static” approach

a User

- can entirely control his/her dynamic cluster,
- can setup and use it on demand,
- can dynamically change an amount of WNs,
- can select a preferable master host,
- doesn't need admins to take an action,
- doesn't disturb other users,
- is free to choose a ROOT ver. for services.

Binary Payload Attachment




Binary Payload Attachment



PoD SSH

a simple CSV file as an input to the plug-in:


ID,	login@host,	ssh params,	WN work dir,	num of proof WNs
r1,	anar@lxg27.gsi.de,	-p24,	/tmp/test,	10
a2,	user@lxi001.kkk.es,		~/pod_wn,	
l4,	doom@host.my,	-p22,	/opt/pod/,	



pod-remote: a thin client concept



pod-remote



```
pod-remote --start \  
--remote anar@host.gsi.de:/PoD/3.1.1 \  
--env-local env_demac0 | 2.sh
```



```
pod-remote --start \  
            --remote anar@host.gsi.de:/PoD/3.1.1 \  
            --env-local env_demac0 1 2.sh
```

```
pod-info -sd
```

PoD Server Type: remote (managed by pod-remote)
XPROOFD [47445] port: 21001
PoD agent [47450] port: 22001
PoD agent port is forwarded via local port: 22001
XPROOFD port is forwarded via local port: 21001

```
pod-remote --start \  
            --remote anar@host.gsi.de:/PoD/3.1.1 \  
            --env-local env_demac0 1 2.sh
```

```
pod-info -sd
```

PoD Server Type: remote (managed by pod-remote)
XPROOFD [47445] port: 21001
PoD agent [47450] port: 22001
PoD agent port is forwarded via local port: 22001
XPROOFD port is forwarded via local port: 21001

```
pod-info -c
```

```
anar@localhost:21001
```



```
pod-remote --command "pod-ssh -c /home/etc/ssh_hst.cfg submit"
```

```
pod-remote --command "pod-ssh -c /home/etc/ssh_hst.cfg submit"
```

```
pod-info -ln
```

64

```
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi049.gsi.de:2 | 00 | (direct connection) startup: 1s  
worker manafv@lxi054.gsi.de:2 | 00 | (direct connection) startup: 2s  
worker manafv@lxi054.gsi.de:2 | 00 | (direct connection) startup: 2s  
worker manafv@lxi054.gsi.de:2 | 00 | (direct connection) startup: 2s  
worker manafv@lxi054.gsi.de:2 | 00 | (direct connection) startup: 2s
```

...


```
TProof::Open(gSystem->GetFromPipe("pod-info -c"));
```

```
TProof::Open(gSystem->GetFromPipe("pod-info -c"));
```

```
TProof::Open("pod://")
```



```
TProof::Open(gSystem->GetFromPipe("pod-info -c"));
```


```
TProof::Open("pod://")
```

```
pod-remote --stop
```

no need to write all arguments when using
pod-ssh, pod-remote

```
pod-remote --start \  
  --remote anar@host.gsi.de:/PoD/3.11 \  
  --env-local env_demac012.sh
```


```
pod-remote --command "pod-ssh -c /home/etc/ssh_hst.cfg submit"
```



```
pod-remote --start
```

```
pod-remote --command "pod-ssh submit"
```


pod-remote: via open domain



PoD 4.0

- New CLI.

pod start <args to “start”>


pod server <args to “server”>


pod info <args to “info”>

...

- UI - Server communication.
- Dynamic Master architecture.

Dynamic Master architecture





~ **1300** Downloads since June, 2010 (was ~900 in 2011)

31 countries (was 24 last year)

220 Unique Downloads per year (was ~180 in 2011)


PoD is available on cvmfs:

[/cvmfs/sft.cern.ch/lcg/external/PoD/](https://cvmfs/sft.cern.ch/lcg/external/PoD/)


PoD is also an official part of ATLASLocalRootBase package:

https://twiki.atlas-canada.ca/bin/view/AtlasCanada/ATLASLocalRootBase#Using_PROOF_on_Demand_PoD


BACKUP




HEP DATA ANALYSIS



Typical HEP analysis needs a continuous algorithm refinement cycle



PROOF



POD

PROOF on Demand

PROOF on Demand

PROOF on Demand