

## TOURNIQUET QC CHECKLIST

Serial Number	
Location of Inspection	
Date of Inspection	
Person Inspecting	

1. Round clean edge sewn closed ☐
  2. Box stitch 30mm from round edge ☐
  3. No gaps or missing stitches down sides of strap, and between hook and loop ☐
  4. Clip on correctly with caps facing windlass ☐
  5. Rivets secure with no wiggle ☐
  6. Windlass on correctly between rivets and bridge of backplate ☐
  7. Slack on inner strap at windlass is 25mm ☐
  8. Distance from bridge of backplate to stitch at buckle is 35mm ☐
  9. Buckle on correctly with both inner and outer straps sewn through gap with no teeth ☐
- 

## TOURNIQUET QC CHECKLIST

Serial Number	
Location of Inspection	
Date of Inspection	
Person Inspecting	

1. Round clean edge sewn closed ☐
2. Box stitch 30mm from round edge ☐
3. No gaps or missing stitches down sides of strap, and between hook and loop ☐
4. Clip on correctly with caps facing windlass ☐
5. Rivets secure with no wiggle ☐
6. Windlass on correctly between rivets and bridge of backplate ☐
7. Slack on inner strap at windlass is 25mm ☐
8. Distance from bridge of backplate to stitch at buckle is 35mm ☐
9. Buckle on correctly with both inner and outer straps sewn through gap with no teeth ☐