

## TOURNIQUET QC CHECKLIST

Serial Number

**PASS**

**FAIL**

Description of failure:

---



---

	Tailor	Glia 1	Glia 2
Round clean edge sewn closed	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Box stitch 30mm from round edge	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
No gaps or missing stitches down sides of strap, and between hook and loop	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Clip on correctly with caps facing windlass	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inner strap moves freely	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rivets secure with no wiggle	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Windlass on correctly between rivets and bridge of backplate	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Slack on inner strap at windlass is 25mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Distance from bridge of backplate to stich at buckle is 35mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Both inner and outer straps are sewn through the buckle, and the slot on the buckle that is empty has teeth and faces the end	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## TOURNIQUET QC CHECKLIST

Serial Number

**PASS**

**FAIL**

Description of failure:

---



---

	Tailor	Glia 1	Glia 2
Round clean edge sewn closed	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Box stitch 30mm from round edge	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
No gaps or missing stitches down sides of strap, and between hook and loop	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Clip on correctly with caps facing windlass	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inner strap moves freely	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rivets secure with no wiggle	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Windlass on correctly between rivets and bridge of backplate	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Slack on inner strap at windlass is 25mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Distance from bridge of backplate to stich at buckle is 35mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Both inner and outer straps are sewn through the buckle, and the slot on the buckle that is empty has teeth and faces the end	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>