6.035

Project 3 Info Session

Fall 2018

Code Generation at a Glance

- Translate all the instructions in the intermediate representation to assembly language
- Handle expressions
- Allocate space
  - Local variables
  - Global variables
  - Arrays
- Adhere to function calling conventions
- Short circuiting of conditionals
- Runtime checks

Design Intermediate Representation

- Expressive enough to be able to perform analysis and transformation
- Concrete enough to be able to easily generate machine code

What to use as intermediate representation?

- Same as high IR? (with semantic restrictions)
- Assembly Language?

Design #1: From AST to Assembly

- Will have a compiler immediately

- But it will make your life difficult when doing most of the optimizations

- Ideally, want to provide framework for performing code transformations easily

Design Intermediate Representation

- Static Single Assignment

- Infinite register machine

- Stack-based machine

Expression Evaluation Alternatives

High Level

a = 1*2 + 3*4

b = a*a + 1

Temporaries

t1 = 1*2

t2 = 3*4

a = t1 + t2

t3 = a * a

b = t3 + 1

In Place

t1 = 1

t1 *= 2

t2 = 3

t2 = t2 * 4

t1 += t2

a = t1

t1 *= t1

t1 += 1

b = t1

Variables

- Start from Names (Source code) and Descriptors (high IR)

Intermediate allocation

- Everything on the stack?
  - Later optimize by moving to registers
- Everything in a register?
  - "Spill" excess to the stack
- Other techniques…
- Final allocation (fixed registers + stack)

- Register allocation is hard! (so start simple!)

Conditionals

Must eventually become labels and jumps

    if (a) { foo } else { bar }

Becomes:

cmp $0, a

je L1

foo

jmp L2

L1:bar

L2: //...rest of program

cmp: compare if these are equal
je: Jump if equal/zero

Target: x86-64

- Stack values are 64-bit (8-byte)
- Values in decaf are 64-bit (integer) or 1-bit (boolean)
- For this phase, we are not optimizing for space
- Use 64-bits (quadword) for ints and bools.
- Use instructions that operate on 64-bit values for stack and memory operations, e.g. mov**q**
- Same for arithmetic operations

Registers (Linux Calling Convention)

Register	Purpose	Saved across calls
%rax	temp register; return value	No
%rbx	callee-saved register	Yes
%rcx	used to pass 4th argument to functions	No
%rdx	used to pass 3rd argument to functions	No
%rsp	stack pointer	Yes
%rbp	callee-saved; base pointer	Yes
%rsi	used to pass 2nd argument to functions	No
%rdi	used to pass 1st argument to functions	No
%r8	used to pass 5th argument to functions	No
%r9	used to pass 6th argument to functions	No
%r10-r11	temporary	No
%r12-r15	callee-saved registers	Yes

Assembly Instructions

- Check out the x86-64 Architecture guide on course's resource page.
- We are using AT&T assembler syntax (gcc)
- Instructions have the form:
  - `operator op1 op2`, which is equivalent to `op2 = op1 operator op2`
- `$x` denotes immediate integer (base 10) value x
- `%r??` is a register
- You can use names of global variables directly

Allocating Read Only Data

- All Read-Only data in the text segment
- Integers
  - use immediates
- Strings
  - use the .string macro

```
.section .rodata
.msg:
    .string "Five: %d\n"
.section .text
.globl main
main:
    enter $0, $0
    mov $.msg, %rdi
    mov $5, %rsi
    mov $0, %rax
    call printf
    leave
    ret
```

ENTER —pushes the frame pointer from the BP register onto the stack,
copies the current stack pointer from the SP register into the BP/EBP/RBP register

https://www.felixcloutier.com/x86/ENTER.html

Allocating Global Variables

- Allocation: Use the assembler's .comm directive

- Use name or use pc relative addressing

- %rip is the current instruction address

- X(%rip) will add the offset from the current instruction location to the space for x in the data segment to %rip

- Creates easily relocatable binaries

```
...
.section .text
.globl main


main:
    enter$0, $0
    mov $.msg, %rdi

    mov x, %rsi

    mov $0, %rax

    call printf
    leave

    ret


.comm x, 8, 8
```

Addressing Modes

- (%reg) is the memory location pointed to by the value in %reg

- movq $5, -8(%rbp)

Arrays

- What code would you write for: a[4] = 5;

```
...
mov $5, %r10

mov $4, %r11

???...


.comm a, 8 * 10, 8
```

The data segment grows towards larger addresses.

How to access an array element?

We want something like
 base + offset * type_size
AT&T Asm Syntax:
 offset(base, index, scale) =
offset + base + (index * scale)

Runtime Checks

- Array bounds:
- For every read and write for a[idx]:

  if (idx <0 || idx >= length_a) { exit(-1); }

- Program returns
  - If a function returns a value, the execution must not fall off without returning a value (i.e., check that you always assign a value to the return register %rax)
  - Error handling: error(-2)

Procedure Abstraction

- Stack Frames

- Calling Convention

- What to do with live registers across a procedure call?
  - Callee Saved (belong to the caller)
  - %rsp, %rbp, %r12-15
  - The caller must assume that all other registers will be used by the callee

Generated Code

- Your code for this stage **should** be inefficient!

- Stack locations for all temporary values and variables

- For an expression, load operand value(s) into register(s) then perform operation and write to location in stack

- Use regs %r10 and %r11 for temporaries

Design a Low-Level IR

- Don't worry about machine portability
  - flat low-level IRs.
  - 2 address code: operand1 op= operand2
  - 3 address code: result = operand1 op operand2
- Close to ASM language (linear list of instructions)
  - binops, labels, jumps, calls, names, locations
- Make it flexible -- operands can be names or machines locations
  - First generate low-level IR with names, then a later pass resolves names to locations

Compiler Flow

- Template approach
  - break/continue and short-circuiting
  - Translate from AST to low IR
- Then have multiple passes to "lower" IR to machine level
  - resolve names to locations on stack
  - activation frame sizes for stack size calculations
  - pass arguments to methods for a call

Compilation

- **Compile C file to assembly:**
  `gcc –O0 –S –fverbose-asm foo.c –o foo.s`
- Building generated assembly code (gcc is in thise case a front-end for "as"):

  `gcc –c foo.s –o foo.o`

- From object file to assembly: `objdump –d foo.o`
- • Compile to executable: `gcc foo.s –o foo`

- Due: October 26 11:59pm
- Hidden code gen tests available: October 24, 11:59
- Worth 25% of your grade
- Documentation 20%, Testing 80%
- First submission due on Cyberportal on web page
- **Start early!**