

-By Siddharth Jain IIMCA - 5

Overview

I am pleased to present to you a report on the deployment of our Booking Web Application, developed using the MERN Stack (MongoDB, Express.js, React.js, and Node.js). This report provides essential information regarding the technology used, server storage requirements, and database details to assist you in making informed decisions for the deployment process.

Technology Used

The Booking Web Application has been built using the MERN Stack, which is a popular and powerful combination of technologies for developing robust and scalable web applications. Here's a breakdown of each component:

- MongoDB: As the database system, MongoDB is a NoSQL database that provides a
 flexible and scalable solution for managing data in our application. It stores structured
 data in a JSON-like format, making it suitable for handling various types of
 booking-related information.
- Express.js: Express.js is a minimal and flexible web application framework for Node.js. It provides a lightweight and efficient structure for developing the server-side of our web application, handling HTTP requests and routing.
- React.js: React.js is a JavaScript library for building user interfaces. It allows for the
 creation of interactive and dynamic components, resulting in a smooth and responsive
 user experience. React.js is particularly well-suited for single-page applications, such as
 our booking app.

Node.js: Node.js is a server-side JavaScript runtime environment that allows us to
execute JavaScript code outside of a web browser. It provides the necessary tools
and libraries to build scalable and high-performance web applications.

Server Storage Requirements

- Database Storage: MongoDB stores data in a flexible and schema-less format. The
 storage requirements will depend on the number of bookings, users, and associated
 data, such as customer information, booking details, and any additional custom fields. It
 is recommended to allocate sufficient storage to accommodate growth and ensure
 optimal performance.
- Application Code and Assets: The application's code, including JavaScript files, CSS stylesheets, and other assets, will require storage space on the server. The total size of the codebase, including the node_modules directory, is approximately 1 GB.

Process for Deployment

- **1.** Install Node.js and npm:
- Install Node.js on the server, preferably using a version manager like nvm (Node Version Manager) to manage different Node.js versions.
- Verify the installation by running node -v and npm -v commands, which should display the installed versions.
- **2.** Clone the Repository:
- Clone the Git repository of the Booking Web Application onto the server.
- Use the git clone command followed by the repository URL to create a local copy of the application code.

- 3. Install Client Dependencies:
- Navigate to the /client directory using cd /client.
- Run npm install to install all the project dependencies specified in the package.json file.
- This will download and install the required libraries and packages for the application to run.
- **4.** Install Client Dependencies:
- Navigate to the /server directory using cd /server.
- Run npm install to install all the project dependencies specified in the package.json file.
- This will download and install the required libraries and packages for the application to run.
- 5. Configure Environment Variables:

For Client

- Navigate to the /client directory using cd /client.
- Create a new file named .env using a text editor or the command line.
- Open the env file in a text editor.
- Add the following lines to the .env file, specifying the environment variable values as needed:

Variable Name	Example	Description	
REACT_APP_ADMIN_SIGN_UP	true	To Enable Admin Sign Up true for On and false for Off	
REACT_APP_HOD_FEATURE	false	To Enable HOD Feature true for On and false for Off	
REACT_APP_SERVER_URL	https://bookit******.com	Enter Server Url for API request	
REACT_APP_MASTER_ADMIN_E MAIL	master**min@gmail.com	Email of the Admin who has access to edit and delete all halls	

• Save the .env file

For Server

- Navigate to the /server directory using cd /server.
- Create a new file named .env using a text editor or the command line.
- Open the .env file in a text editor.
- Add the following lines to the .env file, specifying the environment variable values as needed:

Variable Name	Example	Description
DATABASE	mongodb+srv://*****:*****@*******.*****.mo ngodb.net/****?retryWrites=true&w=majority	Enter MongoDB connection Url
PORT	9002	Server PORT
SECRET_KEY	<secret key=""></secret>	MongoDB Key
ADMIN_KEY	<admin key=""></admin>	Any word that is required whtn signup as Admin
ADMIN_EMAIL	ad**n@gmail.com	Email of Admin
SENDER_EMAIL	ad**n@gmail.com	Email from which verificaion and forgot link will be sent
SENDER_PASSWORD	****	Password of Email from which verificaion and forgot link will be sent
CLIENT_URL	https://bookit******.com	Enter Client Url for API request
REACT_APP_HOD_F EATURE	false	To Enable HOD Feature true for On and false for

- https://myaccount.google.com/lesssecureapps go to this and enable access to less secure app link otherwise verification mail will not be send from above email
- Save the .env file.

6. Start the Application:

For Client

- Navigate to the /client directory using cd /client.
 https://myaccount.google.com/lesssecureapps go to this and enable access to less secure app link otherwise verification mail will not be send from above email
- Start the server by running npm start command.

For Server

- Navigate to the /server directory using cd /server.
- Start the server by running node app.js command.

Testing / Demo

The project is currently hosted on Render.com, and it is accessible through the following link: https://bookit-client-lezg.onrender.com/

Currently for database management, MongoDB Atlas is utilized as the database solution.

Test Emails

Email: adminofficer@acropolis.in

Password: 123456789

Email: neelamrajput@acropolis.in

Password: 123456789

Email: ajayajmera@acropolis.in

Password: 123456789

Email: faculty@acropolis.in

Password: 123456789