




```
import numpy as np
import matplotlib.pyplot as plt
from \ sklearn.model\_selection \ import \ train\_test\_split
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Conv2D, MaxPooling2D, Flatten, Dense
from tensorflow.keras.utils import to_categorical
# Load MNIST dataset
(X_train, y_train), (X_test, y_test) = mnist.load_data()
# Preprocess the data
# Normalize pixel values between 0 and 1
X_train = X_train.astype('float32') / 255.0
X_{\text{test}} = X_{\text{test.astype}}(\text{'float32'}) / 255.0
# Reshape the data to include a channel dimension (for Conv2D input)
X_train = np.expand_dims(X_train, axis=-1)
X_test = np.expand_dims(X_test, axis=-1)
# One-hot encode the labels
y_train = to_categorical(y_train, 10) # 10 classes (digits 0 through 9)
y_test = to_categorical(y_test, 10)
# Display the first few images
fig, axes = plt.subplots(1, 5, figsize=(15, 3))
for i in range(5):
    axes[i].imshow(X\_train[i, :, :, 0], cmap='gray')
    axes[i].axis('off')
    axes[i].set_title(f'Label: {np.argmax(y_train[i])}')
plt.show()
```











```
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Conv2D, MaxPooling2D, Flatten, Dense
# Create a Sequential model
model = Sequential()
# Add Convolutional layers with ReLU activation
model.add(Conv2D(32, (3, 3), activation='relu', input_shape=(28, 28, 1)))
model.add(MaxPooling2D((2, 2)))
model.add(Conv2D(64, (3, 3), activation='relu'))
model.add(MaxPooling2D((2, 2)))
model.add(Conv2D(128, (3, 3), activation='relu'))
model.add(MaxPooling2D((2, 2)))
# Flatten the 2D feature maps to a vector
model.add(Flatten())
# Add Dense (fully connected) layers with ReLU activation
model.add(Dense(128, activation='relu'))
model.add(Dense(64, activation='relu'))
# Output layer with softmax activation for multi-class classification
model.add(Dense(10, activation='softmax'))
# Compile the model
model.compile(optimizer='adam', loss='categorical_crossentropy', metrics=['accuracy'])
# Display the model summary
model.summary()
```

Model: "sequential"

1 (h)	Outrant Chana	D===== #
Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 26, 26, 32)	320
<pre>max_pooling2d (MaxPooling2 D)</pre>	(None, 13, 13, 32)	0
conv2d_1 (Conv2D)	(None, 11, 11, 64)	18496
<pre>max_pooling2d_1 (MaxPoolin g2D)</pre>	(None, 5, 5, 64)	0
conv2d_2 (Conv2D)	(None, 3, 3, 128)	73856
<pre>max_pooling2d_2 (MaxPoolin g2D)</pre>	(None, 1, 1, 128)	0
flatten (Flatten)	(None, 128)	0
dense (Dense)	(None, 128)	16512
dense_1 (Dense)	(None, 64)	8256
dense_2 (Dense)	(None, 10)	650
Total params: 118090 (461.29 KB)		

Trainable params: 118090 (461.29 KB)

Non-trainable params: 0 (0.00 Byte)

Train the model

```
\label{eq:history} \mbox{history = model.fit(X\_train, y\_train, epochs=10, batch\_size=32, validation\_data=(X\_test, y\_test))}
```

```
Epoch 1/10
1875/1875 [============] - 58s 30ms/step - loss: 0.1967 - accuracy: 0.9383 - val_loss: 0.0714 - val_accuracy: 0.9791
Epoch 2/10
1875/1875 [=================] - 58s 31ms/step - loss: 0.0646 - accuracy: 0.9806 - val_loss: 0.0689 - val_accuracy: 0.9799
Epoch 3/10
Epoch 4/10
Epoch 5/10
```

```
Epoch 6/10
  1875/1875 [===========] - 55s 29ms/step - loss: 0.0250 - accuracy: 0.9922 - val_loss: 0.0555 - val_accuracy: 0.9848
  Epoch 7/10
  Epoch 8/10
  1875/1875 [===========] - 56s 30ms/step - loss: 0.0207 - accuracy: 0.9937 - val_loss: 0.0469 - val_accuracy: 0.9881
  Epoch 9/10
  Epoch 10/10
  # Evaluate the model on the test set
test_loss, test_accuracy = model.evaluate(X_test, y_test)
print(f'Test Loss: {test_loss:.4f}')
print(f'Test Accuracy: {test_accuracy:.4f}')
```