Terminal:

```
Microsoft Windows [Version 10.0.19045.6466]
(c) Microsoft Corporation. All rights reserved.

D:\Media Vault>cd /d "D:\Media Vault"

D:\Media Vault>npm list vite
media-vault@0.0.0 D:\Media Vault
+-- @vitejs/plugin-react@6.1.2
| `-- vite@8.3.4 deduped
`-- vite@8.3.4


D:\Media Vault>npm install tailwindcss @tailwindcss/vite

added 11 packages, and audited 155 packages in 2m

33 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities

D:\Media Vault>npm list tailwindcss @tailwindcss/vite
media-vault@0.0.0 D:\Media Vault
+-- @tailwindcss/vite@4.3.3
| +-- @tailwindcss/node@4.3.3
```

```
| | `-- tailwindcss@4.3.3 deduped
| `-- tailwindcss@4.3.3 deduped
`-- tailwindcss@4.3.3


D:\Media Vault>git status
On branch main
Your branch is up to date with 'origin/main'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   package-lock.json
        modified:   package.json
        modified:   src/App.jsx
        modified:   src/index.css
        modified:   vite.config.js

no changes added to commit (use "git add" and/or "git commit -a")

D:\Media Vault>git add .
warning: in the working copy of 'package-lock.json', LF will be replaced by CRLF the next time Git
touches it
warning: in the working copy of 'package.json', LF will be replaced by CRLF the next time Git touches it
warning: in the working copy of 'src/App.jsx', LF will be replaced by CRLF the next time Git touches it
warning: in the working copy of 'src/index.css', LF will be replaced by CRLF the next time Git touches it
warning: in the working copy of 'vite.config.js', LF will be replaced by CRLF the next time Git touches it

D:\Media Vault>git commit
```

```
Aborting commit due to empty commit message.

D:\Media Vault>git commit
Aborting commit due to empty commit message.

D:\Media Vault>git status
On branch main
Your branch is up to date with 'origin/main'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   package-lock.json
        modified:   package.json
        modified:   src/App.jsx
        modified:   src/index.css
        modified:   vite.config.js


D:\Media Vault>git commit -m "docs: add project planning files"
[main fc7c817] docs: add project planning files
 5 files changed, 638 insertions(+), 64 deletions(-)

D:\Media Vault>git status
On branch main
Your branch is ahead of 'origin/main' by 1 commit.
  (use "git push" to publish your local commits)

nothing to commit, working tree clean
```

```
D:\Media Vault>git push
Enumerating objects: 15, done.
Counting objects: 100% (15/15), done.
Delta compression using up to 4 threads
Compressing objects: 100% (8/8), done.
Writing objects: 100% (8/8), 5.62 KiB | 639.00 KiB/s, done.
Total 8 (delta 5), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (5/5), completed with 5 local objects.
To https://github.com/AnasSaifullahDev/MediaVault.git
   96243fb..fc7c817  main -> main

D:\Media Vault>git status
On branch main
Your branch is up to date with 'origin/main'.

nothing to commit, working tree clean

D:\Media Vault>npm run dev

> media-vault@0.0.0 dev
> vite

9:08:33 AM [vite] (client) Re-optimizing dependencies because lockfile has changed

  VITE v8.3.4  ready in 1801 ms

  ➜  Local:   http://localhost:5173/
  ➜  Network: use --host to expose
  ➜  press h + enter to show help
```

o

9:09:00 AM [vite] (client) hmr update /src/App.jsx, /src/index.css

9:09:03 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x2)

9:16:45 AM [vite] (client) hmr update /src/index.css

Microsoft Windows [Version 10.0.19045.6466]

(c) Microsoft Corporation. All rights reserved.

D:\Media Vault>code .

D:\Media Vault>npm run dev

> media-vault@0.0.0 dev

> vite

VITE v8.3.4 ready in 5952 ms

➜ Local: http://localhost:5173/

➜ Network: use --host to expose

➜ press h + enter to show help

o

12:25:50 AM [vite] (client) hmr update /src/App.jsx, /src/index.css

12:29:37 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x2)

12:32:29 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x3)

12:32:56 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x4)

12:35:02 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x5)

12:35:48 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x6)

12:36:23 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x7)

12:41:27 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x8)

12:43:36 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x9)

12:46:55 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x10)

12:47:34 AM [vite] (client) hmr update /src/App.jsx, /src/index.css (x11)

12:50:12 AM [vite] (client) hmr update /src/index.css

12:53:46 AM [vite] (client) hmr update /src/App.css, /src/index.css

12:55:24 AM [vite] (client) hmr update /src/App.jsx, /src/index.css

Code:

App.jsx:

```
import './App.css'

function Sidebar() {
  return (
    <aside className="w-full lg:w-64 shrink-0 p-6 text-left">
      <nav>
        <ul>
          <li><a href="#dashboard">Dashboard</a></li>
          <li><a href="#entries">All Entries</a></li>
          <li><a href="#media">Media</a></li>
          <li><a href="#literature">Literature</a></li>
        </ul>
```

```
    </nav>
   </aside>
  )
}

function MediaCard({title, type, status, episode, totalEpisodes}) {
  return (
   <article className="bg-gray-800 p-4 rounded-lg">
    <h2>{title}</h2>
    <p>{type} • {status}</p>
    <p>Episode {episode} / {totalEpisodes}</p>
   </article>
  )
}

function App() {
  return (
   <>
    <header className="flex items-center justify-between p-6">
     <h1 className="text-3xl font-bold text-purple-500">MediaVault</h1>
     <button type="button">Create</button>
    </header>

    <div className="flex flex-col lg:flex-row gap-6">

     <Sidebar />

     <main id="dashboard" className="flex-1 min-w-0 p-6 text-left">
      <h1>Dashboard</h1>
```

```
        <section id="entries" className="flex flex-col gap-4">
          <h2>Latest Entries</h2>

            <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
              <MediaCard
              title="Example Anime"
              type="Anime"
              status="In Progress"
              episode={5}
              totalEpisodes={12}
              />
              <MediaCard
              title="Example Movie"
              type="Movie"
              status="Completed"
              episode={1}
              totalEpisodes={1}
              />
            </div>
        </section>
      </main>
    </div>
  </>
 )
}

export default App
```

index.css:

```
@import "tailwindcss";

:root {
  --text: #6b6375;
  --text-h: #08060d;
  --bg: #fff;
  --border: #e5e4e7;
  --code-bg: #f4f3ec;
  --accent: #aa3bff;
  --accent-bg: rgba(170, 59, 255, 0.1);
  --accent-border: rgba(170, 59, 255, 0.5);
  --social-bg: rgba(244, 243, 236, 0.5);
  --shadow:
    rgba(0, 0, 0, 0.1) 0 10px 15px -3px, rgba(0, 0, 0, 0.05) 0 4px 6px -2px;

  --sans: system-ui, 'Segoe UI', Roboto, sans-serif;
  --heading: system-ui, 'Segoe UI', Roboto, sans-serif;
  --mono: ui-monospace, Consolas, monospace;

  font: 18px/145% var(--sans);
  letter-spacing: 0.18px;
  color-scheme: light dark;
  color: var(--text);
  background: var(--bg);
  font-synthesis: none;
```

```
  text-rendering: optimizeLegibility;
  -webkit-font-smoothing: antialiased;
  -moz-osx-font-smoothing: grayscale;

  @media (max-width: 1024px) {
    font-size: 16px;
  }
}

@media (prefers-color-scheme: dark) {
  :root {
    --text: #9ca3af;
    --text-h: #f3f4f6;
    --bg: #16171d;
    --border: #2e303a;
    --code-bg: #1f2028;
    --accent: #c084fc;
    --accent-bg: rgba(192, 132, 252, 0.15);
    --accent-border: rgba(192, 132, 252, 0.5);
    --social-bg: rgba(47, 48, 58, 0.5);
    --shadow:
      rgba(0, 0, 0, 0.4) 0 10px 15px -3px, rgba(0, 0, 0, 0.25) 0 4px 6px -2px;
  }

  #social .button-icon {
    filter: invert(1) brightness(2);
  }
}
```

```
body {
  margin: 0;
}



#root {
  width: 100%;
  min-height: 100svh;
}

h1,
h2 {
  font-family: var(--heading);
  font-weight: 500;
}

h1 {
  font-size: 56px;
  letter-spacing: -1.68px;
  margin: 32px 0;
  @media (max-width: 1024px) {
    font-size: 36px;
    margin: 20px 0;
  }
}
h2 {
  font-size: 24px;
  line-height: 118%;
  letter-spacing: -0.24px;
```

```
  margin: 0 0 8px;
  @media (max-width: 1024px) {
    font-size: 20px;
  }
}
p {
  margin: 0;
}

code,
.counter {
  font-family: var(--mono);
  display: inline-flex;
  border-radius: 4px;
  color: var(--text-h);
}

code {
  font-size: 15px;
  line-height: 135%;
  padding: 4px 8px;
  background: var(--code-bg);
}
```