camera desc

dalmir silva <dalmirdasilva@gmail.com> Mon, Nov 19, 2012 at 11:25 AM
To: dalmir silva <dalmirdasilva@gmail.com>

OV7670 Camera Module For Robot-All glass+Metal Lens

This camera module is special for robot、electronic car、image processing and some other

electronic gadgets.

It's very useful for Electronic lovers.

You can make it be more powerful and useful beyond your imagination.



OV7670 Camera Module For Robot-All glass+Metal Lens

General Description

The OV7670/OV7171 CAMERACHIP™ image sensor is a low voltage CMOS device that provides the full functionality of a single-chip VGA camera and image processor in a small footprint package. The OV7670/OV7171 provides full-frame, sub-sampled or windowed 8-bit images in a wide range of formats, controlled through the Serial Camera Control Bus (SCCB) interface.

This product has an image array capable of operating at up to 30 frames per second (fps) in VGA with complete user control over image quality, formatting and output data transfer. All required image processing functions, including exposure control, gamma, white balance, color saturation, hue control and more, are also programmable through the SCCB interface. In addition, OmniVision sensors use proprietary sensor technology to improve image quality by reducing or eliminating common lighting/electrical sources of image contamination, such as fixed pattern noise (FPN), smearing, blooming, etc., to produce a clean, fully stable color image.

Note: The OV7670/OV7171 uses a lead-free package.

Features

- High sensitivity for low-light operation
- Low operating voltage for embedded portable apps
- Standard SCCB interface compatible with I2C interface
- Output support for Raw RGB, RGB (GRB 4:2:2, RGB565/555/444), YUV (4:2:2) and YCbCr (4:2:2) formats
- Supports image sizes: VGA, CIF, and any size scaling down from CIF to 40x30
- VarioPixel® method for sub-sampling
- Automatic image control functions including: Automatic Exposure Control (AEC), Automatic Gain Control (AGC), Automatic White Balance (AWB), Automatic Band Filter (ABF), and Automatic Black-Level Calibration (ABLC)
- Image quality controls including color saturation, hue, gamma, sharpness (edge enhancement), and anti-blooming
- ISP includes noise reduction and defect correction
- Supports LED and flash strobe mode
- Supports scaling
- Lens shading correction
- Flicker (50/60 Hz) auto detection
- Saturation level auto adjust (UV adjust)
- Edge enhancement level auto adjust
- De-noise level auto adjust

Key Specifications

Active Array Size		640 x 480
Power Supply	Digital Core	1.8VDC ±10%
	Analog	2.45V to 3.0V
	I/O	1.7V to 3.0V[a]
Power Requirements	Active	60 mW typical (15fps VGA YUV format)
	Standby	< 20 µA
Temperature Range	Operation	-30°C to 70°C
	Stable Image	0°C to 50°C
Output Formats (8-bit)		• YUV/YCbCr 4:2:2 • RGB565/555/444 • GRB 4:2:2 • Raw RGB Data
Lens Size		1/6"
Chief Ray Angle		25°
Maximum Image Transfer Rate		30 fps for VGA
Sensitivity		1.3 V/(Lux • sec)
S/N Ratio		46 dB
Dynamic Range		52 dB
Scan Mode		Progressive
Electronics Exposure		Up to 510:1 (for selected fps)
Pixel Size		3.6 µm x 3.6 µm
Dark Current		12 mV/s at 60°C
Well Capacity		17 K e
Image Area		2.36 mm x 1.76 mm
Package Dimensions		3785 µm x 4235 µm

a. I/O power should be 2.45V or higher when using the internal regulator for Core (1.8V); otherwise, it is necessary to provide an external 1.8V for the Core power supply.

Figure 1 OV7670/OV7171 Pin Diagram (Top View)



Figure 2 Functional Block Diagram









Click to get download more information

Related Items

--

_____
Dalmir da Silva
Software Engineer
T&T/HP